A coarse-space preconditioner for multiple-shooting Newton–Krylov: GMRES iterations independent of the period

Notes for NKSearch.jl, branch `coarse-precond`

October 2026

Abstract

In a multiple-shooting Newton–Krylov search with segments of fixed length τ, the number of GMRES iterations per Newton step grows with the period T: faster than linearly with the regular row ordering, and linearly with the Ashtari ordering used by NKSearch. With the Ashtari ordering the Newton operator is $-I$ plus a cyclic block subdiagonal of segment tangent maps, and its spectrum consists of one circle of radius $e^{\lambda\tau}$ around -1 for every Floquet exponent λ. The linear growth comes only from the few circles of the unstable and neutral directions, which surround the origin. We remove them with a coarse space spanned, at every shooting point, by the leading covariant subspace of the tangent dynamics. The resulting right preconditioner is $-I$ outside the coarse space and an exact Galerkin solve on it; the coarse problem is small, cyclic and block-bidiagonal, and must be factorised by QR. For Kuramoto–Sivashinsky the number of GMRES iterations becomes 4 (rtol 10^{-6}) at every period from 16 to 2048, as predicted by the first excluded Lyapunov exponent, and full Newton searches on orbits with periods 53 to 425 take 2–3 GMRES iterations per step. The total work of a search becomes proportional to T instead of T^2, including the cost of building the subspaces. The method is the multiple-shooting counterpart of the Newton–Picard method of Lust et al., used as a Krylov preconditioner.

Contents

1 The multiple-shooting Newton system **2**

2 Why GMRES needs $O(N)$ iterations **2**

3 The coarse space and the preconditioner **3**
3.1 Invariant covariant subspaces . . . 3
3.2 The preconditioner . . . 4
3.3 Building the subspaces . . . 4
3.4 The coarse solve must use QR . . . 5

4 Cost **5**

5 Results for Kuramoto–Sivashinsky **5**
5.1 Linear solves along a chaotic trajectory . . . 6
5.2 Newton searches on long periodic orbits . . . 7

6 Relation to Newton–Picard and to two-grid methods **7**

7 Implementation in NKSearch **9**

8 Reproducing the results **9**

1 The multiple-shooting Newton system

We look for a periodic orbit of $\dot{x} = f(x)$, $x \in \mathbb{R}^n$, with N shooting points $x_1, \dots, x_N$ and period T. Let φ_t be the flow and $\tau = T/N$ the segment length. The equations are

$$F_i(x, T) = \varphi_\tau(x_i) - x_{i+1} = 0, \qquad i = 1, \dots, N, \qquad x_{N+1} \equiv x_1, \tag{1}$$

(for a relative periodic orbit the last segment is followed by the shift $S(\cdot, s)$, and s is a further unknown). One Newton step solves for $(\delta x_1, \dots, \delta x_N, \delta T)$

$$M_i\, \delta x_i - \delta x_{i+1} + \frac{1}{N}\, \dot{x}_i^T\, \delta T = -F_i, \qquad f(x_1)^{\mathsf{T}} \delta x_1 = 0, \tag{2}$$

where $M_i = \partial \varphi_\tau / \partial x\,(x_i)$ is the tangent map of segment i and $\dot{x}_i^T$ the derivative of its end point with respect to the period (computed by finite differences in NKSearch). The last row is the phase condition. In NKSearch the action of the operator costs one tangent integration per segment, done in parallel over segments.

Row orderings. With the *regular* ordering, row block i holds equation i: the diagonal blocks are M_i and the superdiagonal blocks $-I$. With the *Ashtari* ordering (the NKSearch default), equation i is placed in row block $i+1$. The diagonal blocks become $-I$ and the tangent maps move to the subdiagonal:

$$A = -I + C + (\text{period column, phase row}), \qquad C = \begin{pmatrix} 0 & & & M_N \\ M_1 & 0 & & \\ & \ddots & \ddots & \\ & & M_{N-1} & 0 \end{pmatrix}. \tag{3}$$

The reordering is a row permutation: it does not change the solution, but it changes the spectrum completely, and GMRES only sees the spectrum (and the non-normality).

2 Why GMRES needs $O(N)$ iterations

Proposition 1. *Let $\Phi = M_N \cdots M_1$ be the monodromy matrix (at x_1) with eigenvalues $\mu_1, \dots, \mu_n$ (Floquet multipliers, all nonzero). The eigenvalues of C in (3) are the nN numbers σ with $\sigma^N = \mu_j$, i.e. $\sigma = \mu_j^{1/N} e^{2\pi i m/N}$, $m = 0, \dots, N-1$. Hence the eigenvalues of $-I + C$ are*

$$-1 + |\mu_j|^{1/N} e^{i(\arg \mu_j + 2\pi m)/N} :$$

for every multiplier, N points on the circle of centre -1 and radius $|\mu_j|^{1/N} = e^{\lambda_j \tau}$, where $\lambda_j = \log|\mu_j|/T$ is the Floquet exponent.

Proof. C^N is block diagonal with blocks $M_{i-1} \cdots M_1 M_N \cdots M_i$, all similar to Φ. If $Cv = \sigma v$ then $C^N v = \sigma^N v$, so σ^N is a multiplier. Conversely, if $\Phi u = \mu u$ and $\sigma^N = \mu$, the vector with blocks $v_1 = u$, $v_{i+1} = \sigma^{-1} M_i v_i$ satisfies $Cv = \sigma v$ (the last block closes because $\sigma^{-N}\Phi u = u$). □

The radius $e^{\lambda_j \tau}$ depends on the segment length only, not on T: making the orbit longer at fixed τ adds points on the same circles. Two cases follow.

- **Contracting directions**, $\lambda_j < 0$. The circle lies inside the disc $|z+1| < 1$ and stays away from the origin. GMRES reduces these components by roughly $e^{\lambda_j \tau}$ per iteration, whatever N.




Figure 1: Eigenvalues of the NKSearch Newton operator for KS ($L = 39$, odd subspace, 32 modes) along a chaotic trajectory, $N = 32$ segments of length $\tau = 2$, assembled column by column from the code (`spectrum.jl`). Left: regular ordering. Middle: Ashtari ordering; the dashed circle has centre -1 and radius 1. Right: preconditioned operator AM^{-1} with $k = 8$; all 1025 eigenvalues lie within 0.014 of 1 (dashed: circle of radius 1 around 1). The red cross marks the origin.

- **Unstable and neutral directions**, $\lambda_j \geq 0$. The circle surrounds or touches the origin. The GMRES residual polynomial p has $p(0) = 1$ and must be small at N points that surround 0; for points equally spaced on such a circle this needs degree $\approx N$. The extreme case is the cyclic shift ($M_i = I$), for which GMRES makes no progress for $N - 1$ iterations. Physically, each matrix-vector product moves information by one segment, and the unstable components must travel once around the whole orbit.

So with the Ashtari ordering the iteration count is $O(N) = O(T/\tau)$, and the work of a Newton step (iterations $\times$ N segment integrations) is $O(T^2)$. Figure 1 shows the spectra for KS: the Ashtari spectrum is a set of concentric circles around -1, and the outermost ones pass through the origin. With the regular ordering the eigenvalues fill a region around the origin, and GMRES does worse.

3 The coarse space and the preconditioner

3.1 Invariant covariant subspaces

Order the multipliers by modulus and assume a gap, $|\mu_k| > |\mu_{k+1}|$. Let U_1 be the invariant subspace of Φ for $\mu_1, \ldots, \mu_k$, and $U_{i+1} = M_i U_i$. These are the leading covariant (Floquet) subspaces at the shooting points; they satisfy $M_i U_i = U_{i+1}$ exactly, including $M_N U_N = U_1$. Therefore the space

$$\mathcal{W} = U_1 \oplus \cdots \oplus U_N \subset \mathbb{R}^{nN}$$

is invariant under C, and so under $-I + C$: the Newton operator maps $\mathcal{W}$ into itself. It carries exactly the eigenvalues of Proposition 1 with $j \leq k$.

Let $V_i \in \mathbb{R}^{n \times k}$ be orthonormal bases of U_i, and $W = \mathrm{blockdiag}(V_1, \ldots, V_N, I_{N_s})$, where the last block keeps the N_s scalar unknowns (period, and shift if present) in the coarse space. W has orthonormal columns. The coarse matrix is the Galerkin projection $E = W^{\mathsf{T}} A W$, of size $Nk + N_s$.

3.2 The preconditioner

We use the right preconditioner

$$M^{-1} = -(I - WW^{\mathsf{T}}) + WE^{-1}W^{\mathsf{T}}, \qquad M = -(I - WW^{\mathsf{T}}) + WEW^{\mathsf{T}}. \tag{4}$$

It is the inverse of the Ashtari diagonal $(-I)$ outside the coarse space, and an exact solve on it. GMRES is applied to $AM^{-1}y = b$, then $x = M^{-1}y$; right preconditioning leaves the residual unchanged. Both M and M^{-1} are cheap, which lets us map a warm start x_0 to $y_0 = Mx_0$ exactly.

Proposition 2. *Ignore the period column and phase row, and assume $\mathcal{W}$ is exactly invariant. In the splitting $\mathbb{R}^{nN} = \mathcal{W} \oplus \mathcal{W}^{\perp}$, A is block upper triangular, and AM^{-1} has the eigenvalue 1 on $\mathcal{W}$ and, on the complement, the eigenvalues $1 - \sigma$ with $\sigma^N = \mu_j$, $j > k$: circles of radius $e^{\lambda_j \tau}$ around 1.*

Proof. $A\mathcal{W} \subset \mathcal{W}$ makes $A = \begin{pmatrix} E & A_{12} \\ 0 & A_{22} \end{pmatrix}$, so the eigenvalues of A_{22} are those of A not carried by $\mathcal{W}$. In the same splitting $M^{-1} = \mathrm{diag}(E^{-1}, -I)$, so $AM^{-1} = \begin{pmatrix} I & -A_{12} \\ 0 & -A_{22} \end{pmatrix}$. □

Hence GMRES converges at a rate set by the first excluded exponent,

$$m \approx \frac{\log \mathrm{rtol}}{\lambda_{k+1}\tau}, \tag{5}$$

independently of N and T (up to non-normality, and to the bordering, which adds a rank-N_s coupling that GMRES absorbs in a few iterations). Section 5 checks (5) quantitatively.

3.3 Building the subspaces

The bases are obtained by subspace iteration around the orbit, all segments in parallel:

$$P_i = M_i V_i \ (k \text{ tangent integrations per segment}), \qquad V_{i+1} \leftarrow \mathrm{orth}(P_i)$$

(the last segment includes the shift). Each sweep advances every basis by one segment. The leading covariant subspace at a point depends only on the recent past of the trajectory, with errors decaying roughly as $e^{(\lambda_{k+1} - \lambda_k)\tau}$ per sweep, so the number of sweeps needed does not grow with N. In NKSearch:

- at the first Newton step, V_i are random and `coarse_sweeps` sweeps are done;
- at every later step, the images P_i of the previous step (computed at the previous orbit) are used as a warm start, $V_{i+1} \leftarrow \mathrm{orth}(P_i)$, without new integrations;
- then one more round $P_i = M_i V_i$ gives the blocks of E:

$$E_{i+1,i} = V_{i+1}^{\mathsf{T}} P_i, \quad E_{i+1,i+1} = -I_k, \quad E_{i+1,T} = V_{i+1}^{\mathsf{T}} \dot{x}_i^T / N, \quad E_{\text{phase},1} = f(x_1)^{\mathsf{T}} V_1.$$

So in steady state a Newton step costs k tangent integrations per segment for the coarse space.

Choosing k. k must exceed the number of unstable and neutral directions, and it is best placed at a spectral gap. If $\lambda_k - \lambda_{k+1}$ is small, the subspace converges slowly; GMRES still converges, but with an iteration count that again grows with N (Table 2).

3.4 The coarse solve must use QR

E is sparse, cyclic and block-bidiagonal, with $k \times k$ blocks, plus the bordering. A direct factorisation costs $O(Nk^3)$ operations. Gaussian elimination with partial pivoting is unstable on matrices with this structure [3]: the growth around the cycle is $e^{\lambda_1 T}$, and once it exceeds $1/\varepsilon$ the LU solve is wrong. We observed exactly this: at $T = 1024$ (growth e^{41}) GMRES reported convergence while the true residual $\|Ax - b\|/\|b\|$ was 10^3–10^4. A sparse QR factorisation (SuiteSparse SPQR) is backward stable and fixes it; all results below use QR.

4 Cost

Count the cost in segment tangent integrations c (each re-integrates the base flow for one segment, as in NKSearch). Let m_0 and m_k be the GMRES iterations without and with the coarse space, n_N the number of Newton steps and $s =$ `coarse_sweeps`.

	work per Newton step	wall time on N workers
no preconditioner	$m_0 N c$, $m_0 \propto N$: $\propto T^2$	$m_0 c \propto T$
coarse, steady state	$(m_k + k)Nc$: $\propto T$	$(m_k + k)c$: constant
coarse, first step (extra)	$skNc$	skc

A whole search costs $N[\, n_N(m_k + k) + sk\,]c$ with the coarse space against $Nn_N m_0 c$ without. The other costs are small:

- *Coarse QR*: $O(Nk^3)$ flops per Newton step. For a PDE this is negligible next to one tangent integration.
- *Applying* M^{-1}: k inner products and k axpys per segment.
- *Memory*: V and P hold $2Nk$ states. This is the main overhead for large states: for example $N = 200$, $k = 30$ and 256^2 grids need about 6 GB. It is partly offset by the Krylov basis, which shrinks from $m_0 N$ to $m_k N$ states. P could be dropped and recomputed at the price of k integrations per step.

On a GPU the k images of a segment can be integrated as one batch (one base flow, k tangent vectors), which makes the coarse space cheaper than k separate integrations.

5 Results for Kuramoto–Sivashinsky

Set-up. $u_t = -uu_x - u_{xx} - u_{xxxx}$ on $L = 39$ in the odd subspace, as in the ReSolver notes: 32 sine coefficients, the advection term evaluated on 128 points (no aliasing), IMEX CB3R2R3e with $\Delta t = 0.025$ from Flows.jl, and the exact coupled tangent (`ks.jl`). Segments have length $\tau \approx 2$. The first Lyapunov exponents along the attractor are

j	1	2	3	4	5	6	7	8	9	10
λ_j	0.045	−0.008	−0.176	−0.264	−0.319	−0.385	−0.569	−0.667	−2.127	−4.020
$e^{\lambda_j \tau}$	1.093	0.984	0.704	0.590	0.528	0.463	0.320	0.264	0.014	$< 10^{-3}$

One unstable and one neutral direction, and a large gap after $j = 8$.




Figure 2: GMRES iterations versus period, trajectory operators, rtol 10^{-6}, `coarse_sweeps` $= 5$ unless stated.

N	T	no prec.	$k=4$	$k=5$	$k=6$	$k=7$	$k=8$	$k=12$
8	16	48	22	17	13	11	5	4
16	32	64	20	15	11	11	4	3
32	64	103	21	16	11	11	4	2
64	128	174	26	19	14	11	4	3
128	256	300	31	23	13	11	4	2
256	512	567	44	30	17	14	4	3
512	1024	1089	65	40	19	13	4	3
1024	2048	–	89	51	21	14	4	3
prediction (5)			22	18	12	10.4	3.2	< 2
gap $\lambda_k - \lambda_{k+1}$			0.055	0.066	0.184	0.098	1.460	4.65

Table 1: GMRES iterations (Figure 2). All solves were checked with the true residual. The unpreconditioned case was not run at $N = 1024$.

5.1 Linear solves along a chaotic trajectory

To reach long periods, we build the NKSearch operator (with period column and phase row) at N seeds spaced $\tau = 2$ apart on a chaotic trajectory, closed cyclically, and solve with a random right-hand side to rtol 10^{-6} (`scaling_trajectory.jl`). The operator has the spectral structure of an orbit of period $T = 2N$, although the trajectory is not periodic.

Without preconditioner the count grows linearly in T (Table 1, Figure 2). With $k = 8$, at the large spectral gap, it is 4 at every period up to 2048, in agreement with (5): $\log 10^{-6}/\log 0.014 = 3.2$. The cluster radius 0.014 is also visible in Figure 1.

For $k = 4$ to 7 the short orbits meet the prediction (5) within one or two iterations (22, 17, 13, 11 against 22, 18, 12, 10.4), so the coarse space removes what it should and GMRES then converges at the rate of the first excluded exponent. For long orbits the count creeps up: from 22 to 89 for $k = 4$ (gap $\lambda_k - \lambda_{k+1} = 0.055$), from 17 to 51 for $k = 5$ (0.066), from 13 to 21 for $k = 6$ (0.184) and from 11 to 14 for $k = 7$ (0.098). The two smallest gaps give by far the largest growth, but $k = 6$ and 7 are not ordered by their gap, so the gap is not the only factor. The growth is not a failure of the coarse space as such but of its construction: with a small gap, 5 sweeps leave the computed subspace slightly off the invariant one, and the residual coupling to the unstable direction is again transported around the orbit. Table 2 confirms this: with 20 sweeps $k = 4$

		$k = 4$			$k = 8$	
N	T	1 sweep	5 sweeps	20 sweeps	1 sweep	5 sweeps
64	128	95	26	23	12	4
256	512	308	44	22	23	4

Table 2: Effect of the number of subspace sweeps at the first Newton step.

			$k = 8$		no preconditioner		
M	N	T	GMRES/step	work	GMRES/step	work	ratio
1	27	53.1	3, 3, 2	2 025	79, 81, 81	6 588	3.3
2	54	106.3	3, 2, 3	4 050	135, 135, 135	22 032	5.4
4	108	212.5	3, 3, 2	8 100	243, 244, 243	79 164	9.8
8	216	425.1	3, 3, 3	16 416	456, 460, 435, 455	390 960	23.8

Table 3: Newton searches on repeated orbits. "Work" is the number of segment tangent integrations of the whole search: GMRES products, one initial residual per solve, and for $k = 8$ the coarse space (k per step plus $5k$ at the first step). Nonlinear integrations (residuals, line search, period differences) are the same for both and are not counted. Wall time at $M = 8$ on two cores: 34 s against 359 s.

stays at 22–23 up to $T = 512$, and with a single sweep even $k = 8$ degrades. In practice k should be placed at a clear gap, or the number of sweeps raised when no such gap is available.

5.2 Newton searches on long periodic orbits

We converged periodic orbits from near recurrences with the hookstep method (`find_upo.jl`; periods 52.043, 53.134, 76.846). A long orbit is the M-fold repetition of the orbit with $T_0 = 53.134$ ($N_0 = 27$ segments): a genuine periodic orbit of period MT_0, with multipliers μ_j^M. We perturb all seeds and the period by a relative 10^{-3} and reconverge with `:ls_iterative`, GMRES rtol 10^{-3} (`scaling_upo.jl`). All searches reach residuals between $5 \cdot 10^{-13}$ and $3 \cdot 10^{-11}$ in 3–4 Newton steps.

The total work of a search is proportional to T with the coarse space and to T^2 without, so the gain grows linearly with the period (Table 3, Figure 3). At rtol 10^{-3} the coarse runs need 2–3 iterations; most of their cost is the coarse space itself (64 of the 76 integrations per segment at $M = 8$), which is the price of making the count independent of T.

6 Relation to Newton–Picard and to two-grid methods

The construction is the multiple-shooting counterpart of the Newton–Picard method of Lust, Roose, Spence and Champneys [1]. For single shooting, that method splits the state space into the subspace of the dominant Floquet multipliers, computed by subspace iteration with monodromy products, and its complement. It applies Newton to the small projected system and Picard (fixed-point) iteration to the complement, where all multipliers are below a threshold $\rho < 1$. The correspondence is:




Figure 3: Newton searches on repeated orbits (Table 3). Left: mean GMRES iterations per Newton step. Right: segment tangent integrations of the whole search, coarse-space cost included.

Newton–Picard (single shooting)	this preconditioner (multiple shooting)
dominant Floquet subspace at x_0	covariant subspace V_i at every seed, by the same subspace iteration distributed over the segments
Newton on the $p \times p$ projected system	exact Galerkin solve with E, size $Nk + N_s$
Picard iteration on the complement	$-I$ on the complement. With the Ashtari ordering, Richardson iteration with $M = -I$ is Picard propagation along the segments; GMRES accelerates it

Iterated as a stationary method, the preconditioner would be a multiple-shooting Newton–Picard iteration. Using it inside GMRES instead has two advantages: GMRES removes the effect of an imperfect subspace and of weakly contracting directions (Table 2), and the Krylov solve keeps the standard Newton–Krylov globalisation. Newton–Picard splittings used as Krylov preconditioners also appear in Potschka, Mommer, Schlöder and Bock [2] for time-periodic parabolic optimal control, where a two-grid alternative to the eigenspace splitting is proposed as well.

The differences from single-shooting Newton–Picard are where multiple shooting matters:

- *Stability for long T.* The single-shooting projected system $V^{\mathsf{T}}(\Phi - I)V$ carries the growth $e^{\lambda_1 T}$. Here the coarse problem keeps the multiple-shooting structure and is solved by QR; this is exactly where LU failed at $T = 1024$.

- *Parallelism.* Subspace iteration, coarse assembly and Krylov products are all per segment, so the wall time of a Newton step does not depend on T.

The same principle underlies the space-time two-grid preconditioner of the ReSolver notes: one coarse space contains everything the cheap part of the preconditioner (there the diagonal smoother, here $-I$) does not damp. There the coarse space is organised by scale (low sine modes); here it is organised by Floquet direction. Before claiming the multiple-shooting version is new, the literature on Newton–Picard (including Lust's own work) should be checked for an existing multiple-shooting variant.

7 Implementation in NKSearch

Usage.

```
opts = Options(method=:ls_iterative,  # row_order=:ashtari is the default
               coarse_dim=8,          # k; 0 disables (default)
               coarse_sweeps=5,       # sweeps at the first Newton step
               gmres_rtol=1e-3, gmres_maxiter=100)
search!(G, L, F, z, opts)
```

The preconditioner needs nothing beyond what NKSearch already uses: the linearised flow L (applied k times per segment and Newton step), the shift S and the derivative operators. The state type must support `randn!` (for the random initial bases), `dot`, `norm` and broadcasting.

Code.

- `src/coarse_precond.jl`: the type `CoarsePrecond` (bases V, images P, sparse E and its QR), subspace iteration, assembly of E, M^{-1} and M, and the operator AM^{-1} passed to GMRES.
- `src/iter_sol_cache.jl`: `IterSolCache` holds the preconditioner (or `nothing`), updates it at every Newton step after the period derivatives, and dispatches the preconditioned solve.
- `src/options.jl`: options `coarse_dim`, `coarse_sweeps`.
- `test/test_coarse.jl`: with $k = n$ the preconditioner is A^{-1} and GMRES converges in one iteration; $MM^{-1} = I$; searches converge with partial coarse spaces.

Line-search driver. Two problems in `src/search_linesearch.jl` were fixed in a separate commit. The first correction was initialised with `similar(z0) .*= 0.0`, which keeps NaN from uninitialised memory; it is now `zero(z0)`, as in the hookstep driver. GMRES was warm-started from the previous Newton correction, which after the first step is much larger than the new right-hand side; GMRES then started from a relative residual of order 10^2–10^3. The driver now applies `opts.gmres_start` (default: zero), like the hookstep driver.

Limitations.

- Only `:ls_iterative` with the Ashtari ordering. For the hookstep, the trust-region constraint must be $\|M^{-1}Q_m y\| \le \Delta$ rather than $\|Q_m y\| \le \Delta$; this requires storing $M^{-1}q_j$ in GMRES.jl (flexible-GMRES style) and solving the hookstep subproblem in that norm.
- Memory $2Nk$ states.
- k is fixed by the user. An adaptive choice, as in adaptive Newton–Picard, could monitor the Ritz values of the subspace iteration and enlarge k until a gap is found.

8 Reproducing the results

All scripts are in `docs/notes/coarse_precond` and need Flows.jl, GMRES.jl and this branch of NKSearch. Run with `julia -t 2`:

- `ks.jl`: the KS model (included by the other scripts).
- `lyapunov.jl`: Lyapunov exponents → `data/lyapunov.txt`.

- `spectrum.jl`: eigenvalues of Figure 1 → `data/spectrum.txt`.
- `scaling_trajectory.jl`: Table 1; environment variables `NS`, `KS`, `SWEEPS` select the runs → `data/trajectory_*.txt`, `data/sweeps_*.txt`.
- `find_upo.jl`: periodic orbits from near recurrences → `upos/`.
- `scaling_upo.jl upos/T_53.134.txt`: Table 3; variables `MS`, `KS` → `data/upo_newton.txt`.
- `python3 make_figs.py`: the figures, from `data/`.

The file `data/trajectory_k0.txt` comes from a run with the earlier LU coarse solve; only its unpreconditioned rows are used.

References

[1] K. Lust, D. Roose, A. Spence, A. R. Champneys, An adaptive Newton–Picard algorithm with subspace iteration for computing periodic solutions, *SIAM J. Sci. Comput.* 19(4), 1188–1209, 1998.

[2] A. Potschka, M. S. Mommer, J. P. Schlöder, H. G. Bock, Newton–Picard-based preconditioning for linear-quadratic optimization problems with time-periodic parabolic PDE constraints, *SIAM J. Sci. Comput.* 34(2), A1214–A1239, 2012.

[3] S. J. Wright, A collection of problems for which Gaussian elimination with partial pivoting is unstable, *SIAM J. Sci. Comput.* 14(1), 231–238, 1993.