

Computer Vision - Lab 5

Panoramic Image

Davide Dravindran Pistilli

29th May 2020

1 Introduction

The purpose of this lab experience is the creation of a panoramic image from a set of consecutive pictures. In order to run, the program requires the following command line arguments:

- **Image folder:** the folder where the source images are stored.
- **Image field of view:** the field of view of the images, it must be the same for all of them.
- **Distance ratio:** larger values allow for higher error margins.

2 Workflow

The first step is to perform a cylindrical projection of all source images. After each projection, the corresponding histograms are equalised on order to improve results. After this pre-processing step is performed, the keypoints and descriptors for each image are computed. The algorithm can use either ORB or SIFT features in order to compare the two results. Using the features from the previous step, matches are computed between each consecutive pair of images. In order to avoid bad matches, the *distance ratio* parameter is used to remove those based on really different keypoints. Furthermore, a homography matrix is computed between the two images. This allows to further improve the quality of the matches by removing all outliers that don't fit the transformation. At this point the average translation between matches can be computed. The actual panoramic image is computed considering both horizontal and vertical translations that were computed before. Since the border between images is usually quite visible, a Gaussian blur with a $(1, 7)$ kernel and $\sigma = 2.5$ is applied to all transitions.

No final histogram equalisation was applied, since it only worsened the result.

3 Results

The program was tested on 5 different datasets with both ORB and SIFT features.