



PELLET



WOOD



THERMO



SICURO TOP
INSIDE



17,3 kW

12,3 kW



11,2 kW

6,5 kW



4,8 kW

4,8 kW

η

93 %

91,9 %



TOP EXIT

PELLET

WOOD

PRODUCT DETAILS



A

			PELLET	WOOD
Potenza termica normale Nominal heat output	Pmin-Pmax	kg/h	4,7-16,1	11,3
Consumo pellet-legna Pellet-logs consumption	Pmin-Pmax	kg/h	1-3,5	2,8
Autonomia di funzionamento Operation autonomy	Pmin-Pmax	h	30-9	—
Capacità serbatoio Tank capacity		kg	30	—
Scarico fumi Exhaust flue		Ø	180	

Potenza massima ottenibile a pieno carico.
Maximum power obtainable with full load.

Componenti idraulici tutti di serie

Rivestimento in acciaio verniciato e maiolica superiore

Regolazione aria comburente legna con valvola termostatica

Guarnizione di sicurezza in acciaio inox

Maniglia di apertura porta "fredda"

Porta fuoco con doppio vetro ceramico

All plumbing components as standard supply

Covering in painted steel and majolica at the top

Wood combustion air regulation with thermostatic valve

Safety seal in stainless steel

"Cold" door handle

Fire door with double ceramic glazing

PREZZO • PRICE

CODICE • CODE	DESCRIZIONE • DESCRIPTION	PREZZO • PRICE €
DH	Termostufa DUAL	8.190,00
P	Kit sanitario Sanitary kit	405,00

TRASPORTO • SHIPPING: € 97,00

ACCESSORI • OPTIONAL	DESCRIZIONE • DESCRIPTION	PREZZO • PRICE €
MODULO.WIFI2.0	Modulo per gestione Wi-Fi Wi-Fi device	312,00

COLORI • COLORS



AVORIO



TERRA DI SIENA



BORDEAUX



MATT BLACK

DUAL

PELLET 16,1 kW - WOOD 11,3 kW

PELLET+WOOD 27,4 kW - 680 m³

cm 87x63x110 h • 330 kg



STEEL