

OpenRoad TMS External API 1.0 OAS 3.1

/api-docs/ext/v1/openapi.yaml

REST API for integrating with the OpenRoad TMS platform.

For AI-assisted integration, see [/llms.txt](#) (short summary) or [/llms-full.txt](#) (full LLM-friendly reference). For integration best practices (auth rotation, retry policy, observability, versioning), see the "Integration best practices" section in [/llms-full.txt](#).

Authentication

HTTP Basic Auth with your application's client ID and secret. Secrets can be rotated at any time; rotations include a 24-hour grace period during which both the old and new secrets remain valid, so you can roll over your integration without downtime.

Response envelope

Every response uses the same three-field envelope (data, error, meta). Successful responses populate data and meta with error set to null. Failed responses populate error and meta with data set to null. The meta object always includes a unique request_id (include this when contacting support) and a server timestamp in UTC.

Errors always include a **details** array. For errors with per-field context (filter validation, record validation, missing parameters), each entry is **{field, code, message}** so clients can parse without regex. For errors without field context (auth, not-found, server-side), **details** is an empty array — always present, never omitted, so one parsing path fits every error.

Filtering, sorting, pagination

Collection endpoints support consistent query syntax:

Feature	Syntax	Example
Equality filter	?field=value	?status=delivered
Multi-value filter (OR)	?field[]=a&field[]=b	?status[]=delivered&status[]=billed
Range filter	?field[op]=value	?total[gte]=1000&total[lte]=5000
Sort ascending	?sort=field	?sort=created_at
Sort descending	?sort=-field	?sort=-created_at
Pagination	?page=N&per_page=M	?page=2&per_page=50 (max 100)

Supported range operators: gte ($\geq$), gt ($>$), lte ($\leq$), lt ($<$). Each endpoint documents which fields accept which operators.

Any parameter whose description says "Multi-value supported" accepts the bracket syntax shown above (**?field[]=a&field[]=b**). The non-bracketed repeated form (**?field=a&field=b**) is **not** parsed as multi-value — only the last value is used.

Multi-value filters (including bulk ID lookups via **?id[]=**) cap at 100 values per request. Larger requests return **400 invalid_filter** with **details[].code: too_many_values** . Chunk in batches of 100 for

FK resolution patterns — see the **Performance & batching** section in [//lms-full.txt](#) for the canonical recipe.

Note for OpenAPI client-codegen consumers: standard array serialization (**style: form, explode: true**) generates the non-bracketed form, which the server treats as last-wins. Multi-value query params are documented as scalar in this spec; partners using generated clients need to send the bracket form manually for multi-value calls.

Request body conventions

All write endpoints (**POST** , **PATCH**) wrap request bodies under a singular resource key:

Endpoint	Wrapper	Example
POST /loads/:id/notes , /drivers/:id/notes , /trucks/:id/notes , /trailers/:id/notes	note	<pre>{"note": {"content": "..."} }</pre>
PATCH /trucks/:id	truck	<pre>{"truck": {"oos": true, "oos_note": "..."} }</pre>
PATCH /trailers/:id	trailer	<pre>{"trailer": {"needs_repair": false} }</pre>

Bodies sent without the wrapper return **400 bad_request** .

Embedded summaries

Some endpoints embed fixed-shape projections of related entities to enable single-roundtrip rendering of joined data. [/assignments](#) embeds **driver** (DriverSummary) and **assignment** (TruckSummary or TrailerSummary, polymorphic). When you only need a name or unit number for a list view, the summary is enough — drill down to the resource endpoint only when full detail is required. See [//lms-full.txt](#) for the full pattern.

Rate limiting

Rate limiting is not currently enforced on [/api/ext/v1/*](#) . The **rate_limited** (429) error code is reserved as part of the public contract — partners should implement exponential backoff and respect **Retry-After** headers now, so that limits can be added in a future release without requiring client changes.

Data types

Timestamps are UTC ISO 8601 (**2026-04-14T12:00:00Z**). Money and miles fields use decimal-precision strings (e.g. **"1234.56"**) to preserve arbitrary precision — see each field's type below. When a nullable field is included in the response, a null value is rendered as **null** , never omitted (ungranted grantable fields are a separate case — omitted entirely; see field visibility).

Error codes

Top-level **error.code** values (machine-readable category):

Code	HTTP	When it happens
unauthorized	401	Missing or invalid credentials
forbidden	403	Endpoint not granted to your application

Code	HTTP	When it happens
<code>not_found</code>	404	Resource does not exist or is not accessible to your account
<code>bad_request</code>	400	Required parameter missing or malformed
<code>invalid_filter</code>	400	One or more filter parameters are invalid (see <code>error.details</code>)
<code>invalid_sort</code>	400	Sort field is not allowed for this endpoint (see <code>error.details</code>)
<code>validation_error</code>	422	Input failed validation (see <code>error.details</code>)
<code>rate_limited</code>	429	Request rate exceeded — back off per <code>Retry-After</code> header
<code>internal_error</code>	500	Server-side fault — report the <code>request_id</code> from response meta

Per-detail `error.details[].code` values (what's wrong with a specific field):

Code	Meaning
<code>unknown_field</code>	Field is not recognized for this operation. May mean the field does not exist, or exists but your application has not been granted access — the API does not distinguish between these to prevent schema enumeration.
<code>invalid_value</code>	Value failed validation (wrong type, not in allowed set, or malformed)
<code>unsupported_op</code>	Operator is not supported for this field (e.g., range operator on a non-range field, multi-value syntax on a non-multi field)
<code>invalid_operator</code>	Range operator is not one of <code>gt</code> , <code>gte</code> , <code>lt</code> , <code>lte</code>
<code>missing_parameter</code>	A required parameter was not provided
<code>too_many_values</code>	Multi-value filter exceeded the per-request cap (max 100 values, e.g. <code>?id[]=</code> for bulk lookups)

Servers

/api/ext/v1 - Current environment

Authorize 

Filter by tag

Assignments

List current driver assignments to trucks and trailers.

^

GET	/assignments	List current driver assignments	 ^
-----	--------------	---------------------------------	---

Returns currently active driver-to-truck or driver-to-trailer assignments (start_date in the past, end_date null or in the future). Scoped to the authenticated application's account.

Parameters

Cancel

Name	Description
page integer (query)	1
per_page integer (query)	25
sort string (query)	Sort field. Prefix with - for descending. --
driver_id integer (query)	Filter by driver ID. Multi-value supported. driver_id
assignment_id integer (query)	Filter by assignment foreign key (truck or trailer ID). Multi-value supported. assignment_id
assignment_type string (query)	Filter by assignment type. Use ?assignment_type[]=Truck for multi-value. --
start_date string(\$date-time) (query)	Filter by start_date. Accepts range. start_date
end_date string(\$date-time) (query)	Filter by end_date. Accepts range. end_date

Name	Description
created_at string(\$date-time) (query)	Filter by created_at. Accepts range. created_at
updated_at string(\$date-time) (query)	Filter by updated_at. Accepts range. updated_at

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema<pre>{ "data": [{ "id": 9912, "driver_id": 8421, "assignment_id": 312, "assignment_type": "Truck", "start_date": "2026-07-09T11:12:25.632Z", "end_date": "2026-07-09T11:12:25.632Z", "created_at": "2026-07-09T11:12:25.632Z", "updated_at": "2026-07-09T11:12:25.632Z", "driver": { "id": 8421, "first_name": "string", "last_name": "string", "driver_nr": "string", "status": "active" }, "assignment": {} }], "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:25.632Z", "page": 1, "per_page": 25, "total": 142 } }</pre>	No links
400	Request was malformed or contained invalid parameters.	No links

Code	Description	Links
	Media type application/json Examples Unknown filter value (single error) Example Value Schema<pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema<pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema<pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	No links

Code	Description	Links
	<pre>} }</pre>	

Availability Events

List driver availability windows (off-duty, planned, hometime, loaded).

^

GET

/availability_events

List driver availability events

^

Returns a paginated, sortable, filterable list of driver availability windows scoped to the authenticated application's account. Use to plan around driver off-duty, planned, hometime, and loaded states.

Parameters

Cancel

Name	Description
page integer (query)	1
per_page integer (query)	25
sort string (query)	Sort field. Prefix with - for descending. --
driver_id integer (query)	Filter by driver ID. Multi-value supported. driver_id
status string (query)	Filter by status. Multi-value supported. --
start_date string(\$date-time) (query)	Filter by start_date. Accepts range. start_date
end_date string(\$date-time)	Filter by end_date. Accepts range.

Name	Description
(query)	end_date
created_at string(\$date-time) (query)	Filter by created_at. Accepts range. created_at
updated_at string(\$date-time) (query)	Filter by updated_at. Accepts range. updated_at

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": [{ "id": 17234, "driver_id": 8421, "status": "loaded", "start_date": "2026-07-09T11:12:25.728Z", "end_date": "2026-07-09T11:12:25.728Z", "created_at": "2026-07-09T11:12:25.728Z", "updated_at": "2026-07-09T11:12:25.728Z", "off_duty_reason": "string" }], "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:25.728Z", "page": 1, "per_page": 25, "total": 142 } }</pre>	No links
400	Request was malformed or contained invalid parameters. Media type Examples	No links

Code	Description	Links
	application/json Unknown filter value (single error)	
	Example Value Schema <pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Billing Settings

List and retrieve billing profile templates referenced by customers.



GET /billing_settings List billing settings



GET /billing_settings/{id} Retrieve a billing setting



Parameters

Cancel

Name Description

id * required

integer
(path)

id

Execute

Responses

Code	Description	Links
200	Successful response	No links
	Media type	
	application/json	
	Controls Accept header.	
	Example Value Schema	
	<pre>{ "data": { "id": 12, "profile_name": "string", "default": true, "created_at": "2026-07-09T11:12:25.742Z", "updated_at": "2026-07-09T11:12:25.742Z" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:25.742Z" } }</pre>	
401	Missing or invalid credentials.	No links
	Media type	
	application/json	

Code	Description	Links
	Example Value Schema	
	<pre> { "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } } </pre>	
403	Your application does not have permission for this endpoint.	No links
	Media type application/json	
	Example Value Schema	
	<pre> { "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } } </pre>	
404	The resource does not exist or is not accessible to this account.	No links
	Media type application/json	
	Example Value Schema	
	<pre> { "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } } </pre>	

Compensations

Driver pay structures and rates. The endpoint itself requires explicit grant; rate, percentage, flat, and bonus fields require additional field grants on top of the endpoint grant.



GET /compensations List compensations



Returns a paginated list of driver nav structures (Per Mile / Percentage / Flat). The endpoint itself requires explicit grant in `api_application_endpoints` — without it the request returns 403. Default fields (`id`, `name`, `status`) are visible once granted; rate, percentage, flat, and bonus fields require additional field grants.

Parameters

Cancel

Name	Description
id integer (query)	id
page integer (query)	1
per_page integer (query)	25
sort string (query)	--
status string (query)	Filter by compensation status. Multi-value supported. --

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema	No links

Code	Description	Links
	<pre>{ "data": [{ "id": 312, "name": "Standard Per Mile", "status": "Per Mile", "created_at": "2026-07-09T11:12:25.776Z", "updated_at": "2026-07-09T11:12:25.776Z", "loaded_mile_rate": "string", "empty_mile_rate": "string", "banded": true, "linehaul_percentage": "string", "fuel_surcharge_percentage": "string", "flat_status": "string", "flat_rate": "string", "seniority_bonus_enabled": true, "seniority_bonus_cents_per_mile_per_year": "string", "seniority_bonus_excluded_event_reasons": ["string"] }], "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:25.776Z", "page": 1, "per_page": 25, } }</pre>	

400

Request was malformed or contained invalid parameters.

No links

Media type

Examples

application/json

Unknown filter value (single error)

Example Value Schema

```
{
  "data": null,
  "error": {
    "code": "invalid_filter",
    "message": "Invalid filter parameters",
    "details": [
      {
        "field": "status",
        "code": "invalid_value",
        "message": "value 'banana' is not one of [booked, assigned,
...]"
      }
    ]
  },
  "meta": {
    "request_id": "8f3a-c4e2-bb19-2f7d",
    "timestamp": "2026-04-14T12:00:00Z"
  }
}
```

401

Missing or invalid credentials.

No links

Media type

application/json

Example Value Schema

```
{
  "data": null,
```

Code	Description	Links
	<pre>"error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

GET

/compensations/{id}

Retrieve a compensation



Parameters

Cancel

Name	Description
id * required integer (path)	id

Execute

Responses

Code	Description	Links
200	Successful response	No links
	Media type	

Code	Description	Links
	application/json Controls Accept header. Example Value Schema <pre>{ "data": { "id": 312, "name": "Standard Per Mile", "status": "Per Mile", "created_at": "2026-07-09T11:12:25.800Z", "updated_at": "2026-07-09T11:12:25.800Z", "loaded_mile_rate": "string", "empty_mile_rate": "string", "banded": true, "linehaul_percentage": "string", "fuel_surcharge_percentage": "string", "flat_status": "string", "flat_rate": "string", "seniority_bonus_enabled": true, "seniority_bonus_cents_per_mile_per_year": "string", "seniority_bonus_excluded_event_reasons": ["string"] }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:25.800Z" } }</pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint",</pre>	No links

Code	Description	Links
	<pre>"details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Customers

List and retrieve customers (shippers, brokers, 3PLs) booked on loads.

^

GET

/customers

List customers

^

Returns a paginated, sortable, filterable list of customers (shippers, brokers, 3PLs) scoped to the authenticated application's account.

Sensitive contact, manager, and financial fields require explicit grants. Internal operational flags (**critical_customer** , **not_scheduled_loads** , **protect_from_freeze** , default-load-type config, FFS usernames, fuel-account routing) are never exposed regardless of grants. External system IDs (**macropoint_id** , **apex_broker_id** , **tmw_id**) ARE available with field grants for partners that need to map records back to their own systems.

Parameters

Cancel

Name	Description
id integer (query)	Bulk lookup. ?id[]=1&id[]=2 returns only customers matching those IDs.

id

Name	Description
page integer (query)	1
per_page integer (query)	25
sort string (query)	Sort field. Prefix with - for descending. --
status string (query)	Filter by status. Multi-value supported. --
customer_type string (query)	Filter by customer type. Multi-value supported. --
tier string (query)	Filter by tier. Multi-value supported. --
account_manager_id integer (query)	Filter by account manager User ID. Multi-value supported. account_manager_id
customer_service_representative_id integer (query)	Filter by customer service rep User ID. Multi-value supported. customer_service_representative_id
capacity_manager_id integer (query)	Filter by capacity manager Employee ID. Multi-value supported. Resolve via /employees . capacity_manager_id
billing_setting_id integer (query)	Filter by billing profile (BillingSetting) ID. Multi-value supported. Resolve via /billing_settings .

Name

Description

	billing_setting_id
macropoint_integration boolean (query)	Filter by Macropoint integration flag. --
four_kites_integration boolean (query)	Filter by FourKites integration flag. --
credit_hold boolean (query)	Filter by credit hold flag. Requires credit_hold field grant. --
custom_billing boolean (query)	Filter by custom billing flag. Requires custom_billing field grant. --
created_at string(\$date-time) (query)	Filter by created at. Accepts range — ? created_at[gte]=2026-04-01 . created_at
updated_at string(\$date-time) (query)	Filter by updated_at. Accepts range. updated_at

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema	No links

Code

Description

Links

```
{
  "data": [
    {
      "id": 4421,
      "name": "string",
      "dba": "string",
      "mc": "string",
      "status": "active",
      "customer_type": "3pl",
      "tier": "tier_1",
      "macropoint_integration": true,
      "ryder_integration": true,
      "four_kites_integration": true,
      "fourkites_epod": true,
      "load_status_notification_email": true,
      "created_at": "2026-07-09T11:12:25.896Z",
      "updated_at": "2026-07-09T11:12:25.896Z",
      "phone": "string",
      "email": "string",
      "fax": "string",
      "contact": "string",
      "extra_contact": "string",
      "extra_phone": "string",
      "street": "string",
      "street_second": "string",
      "city": "string",
      "state_code": "string",
      "zipcode": "string",
    }
  ]
}
```

400

Request was malformed or contained invalid parameters.

No links

Media type

application/json

Examples

Unknown filter value (single error

Example Value Schema

```
{
  "data": null,
  "error": {
    "code": "invalid_filter",
    "message": "Invalid filter parameters",
    "details": [
      {
        "field": "status",
        "code": "invalid_value",
        "message": "value 'banana' is not one of [booked, assigned,
      ...]"
    }
  ]
},
  "meta": {
    "request_id": "8f3a-c4e2-bb19-2f7d",
    "timestamp": "2026-04-14T12:00:00Z"
  }
}
```

401

Missing or invalid credentials.

No links

Media type

application/json

Example Value Schema

```
{
  "data": null,
```

Code	Description	Links
	<pre>"error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

GET	/customers/{id} Retrieve a customer	 
Parameters		Cancel
Name	Description	
id * required integer (path)	id	
Execute		
Responses		
Code	Description	Links
200	Successful response	No links
Media type		

Code

Description

Links

application/json

Controls Accept header.

Example Value Schema

```
{
  "data": {
    "id": 4421,
    "name": "string",
    "dba": "string",
    "mc": "string",
    "status": "active",
    "customer_type": "3pl",
    "tier": "tier_1",
    "macropoint_integration": true,
    "ryder_integration": true,
    "four_kites_integration": true,
    "fourkites_epod": true,
    "load_status_notification_email": true,
    "created_at": "2026-07-09T11:12:25.917Z",
    "updated_at": "2026-07-09T11:12:25.917Z",
    "phone": "string",
    "email": "string",
    "fax": "string",
    "contact": "string",
    "extra_contact": "string",
    "extra_phone": "string",
    "street": "string",
    "street_second": "string",
    "city": "string",
    "state_code": "string",
    "zipcode": "string",
    "ap_contact": "string",
  }
}
```



401

Missing or invalid credentials.

No links

Media type

application/json

Example Value Schema

```
{
  "data": null,
  "error": {
    "code": "unauthorized",
    "message": "Invalid credentials",
    "details": []
  },
  "meta": {
    "request_id": "8f3a-c4e2-bb19-2f7d",
    "timestamp": "2026-04-14T12:00:00Z"
  }
}
```

403

Your application does not have permission for this endpoint.

No links

Media type

application/json

Example Value Schema

```
{
  "data": null,
  "error": {
    "code": "forbidden",
  }
}
```

Code	Description	Links
	<pre>"message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }</pre>	
404	The resource does not exist or is not accessible to this account.	No links
	Media type application/json	
	Example Value Schema	
	<pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	

Customer Documents

List, retrieve, and upload (multipart) documents attached to a customer profile.

^

GET

/customers/{customer_id}/documents

List documents on a customer



Returns a paginated list of documents attached to the customer, newest first On the in-app UI, customer documents are organized into folders by contract year — upload_type is the year string (e.g. "2026" , "2025").

Parameters

Cancel

Name	Description
customer_id * required integer (path)	customer_id
page integer (query)	1

Name	Description
per_page integer (query)	25

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": [{ "id": 0, "upload_name": "contract.pdf", "upload_type": "2026", "content_type": "application/pdf", "size_bytes": 24576, "created_at": "2026-07-09T11:12:25.943Z", "updated_at": "2026-07-09T11:12:25.943Z" }], "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:25.943Z", "page": 1, "per_page": 25, "total": 142 } }</pre>	No links
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": {</pre>	No links

Code	Description	Links
	<pre>"request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

POST

/customers/{customer_id}/documents Upload a document to a customer



Uploads a file (multipart/form-data) attached to the customer's Files section. **upload_type** selects a **year folder** (e.g. **"2026"**). See **/drivers/{driver_id}/documents** POST for full multipart contract details (size limit, MIME whitelist, extensions).

Parameters

Cancel

Reset

Name	Description
customer_id * required integer (path)	customer_id

Request body required

multipart/form-data

file * required
string(\$binary)

Choose File

No file chosen

upload_type * required
string

Required. A year string from 2014 to the current year (e.g. "2026"). Determines which year-folder the file lands in on the customer's Files tab.

2026

Execute

Responses

Code	Description	Links
201	Document uploaded Media type application/json Controls Accept header. Example Value Schema<pre>{ "data": { "id": 0, "upload_name": "contract.pdf", "upload_type": "2026", "content_type": "application/pdf", "size_bytes": 24576, "created_at": "2026-07-09T11:12:25.972Z", "updated_at": "2026-07-09T11:12:25.972Z" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:25.972Z" }}</pre>	No links

Code	Description	Links
400	Request was malformed or contained invalid parameters.	No links
Media type application/json Examples Unknown filter value (single error)		
Example Value Schema <pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>		
401	Missing or invalid credentials.	No links
Media type application/json		
Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>		
403	Your application does not have permission for this endpoint.	No links
Media type application/json		
Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d",</pre>		

Code	Description	Links
	<pre>"timestamp": "2026-04-14T12:00:00Z" } }</pre>	
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
422	Request was well-formed but failed validation. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "validation_error", "message": "Validation failed", "details": [{ "field": "content", "code": "invalid_value", "message": "can't be blank" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

GET

/customers/{customer_id}/documents/{id}

Retrieve a customer document



Returns metadata for a single document attached to the customer.

Parameters

Cancel

Name	Description
customer_id * required integer (path)	customer_id
id * required integer (path)	id

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "id": 0, "upload_name": "contract.pdf", "upload_type": "2026", "content_type": "application/pdf", "size_bytes": 24576, "created_at": "2026-07-09T11:12:26.002Z", "updated_at": "2026-07-09T11:12:26.002Z" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:26.002Z" } }</pre>	No links
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] } }</pre>	No links

Code	Description	Links
	<pre> }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } } }</pre>	
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Customer Detention Info

Retrieve aggregated detention totals for a customer over a **from..to** window. Returns one record, not a list.

^

GET	/customers/{customer_id}/detention_info Retrieve aggregated detention info for a customer	 ^
Returns one aggregated record for the customer over the from..to window — not a list, not paginated. Counts and sums ended detentions on the customer's loads. Cache responses client-side rather than polling tightly.		

`estimated_amount` and `paid_out_amount` (raw decimals) are grantable.

Parameters

Cancel

Name	Description
customer_id * required integer (path) customer_id	
from * required string (query) from	Start of the aggregation window. ISO 8601 date (<code>2026-01-01</code>) or timestamp (<code>2026-01-01T00:00:00Z</code>).
to * required string (query) to	End of the aggregation window. ISO 8601 date (<code>2026-03-31</code>) or timestamp (<code>2026-03-31T23:59:59Z</code>). Must be <code>>= from</code> .

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "customer_id": 0, "from": "2026-07-09T11:12:26.036Z", "to": "2026-07-09T11:12:26.036Z", "detentions_count": 0, "destinations_count": 0, "duration_minutes": 0, "estimated_amount": "string", "paid_out_amount": "string" }, "error": null, "meta": {</pre>	No links

Code	Description	Links
	<pre>"request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:26.036Z" } }</pre>	
400	Request was malformed or contained invalid parameters.	No links
	Media type application/json Examples Unknown filter value (single error)	
	Example Value Schema <pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
401	Missing or invalid credentials.	No links
	Media type application/json	
	Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
403	Your application does not have permission for this endpoint.	No links
	Media type application/json	
	Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden",</pre>	

Code	Description	Links
	<pre>"message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }</pre>	
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Destinations

List and retrieve load stops across the account. Also nested under /loads.

^

GET /destinations List destinations

🔒 ^

Returns a paginated list of destinations.

customer_id is computed from the parent load. phone is grantable.

Parameters

Cancel

Name	Description
page integer (query)	1
per_page integer (query)	25

Name	Description
sort string (query)	--
stop_type string (query)	Filter by stop type. Multi-value via <code>?stop_type[]=pick_up&stop_type[]=delivery</code> . --
load_id integer (query)	Filter by load. Multi-value supported. load_id
driver_id integer (query)	Filter by driver. Multi-value supported. driver_id
trailer_id integer (query)	Filter by trailer. Multi-value supported. trailer_id
customer_id integer (query)	Filter by customer (joined via load). Multi-value supported. customer_id
app_date string(\$date) (query)	Filter by app_date. Accepts range — <code>?app_date[gte]=2026-01-01</code> . app_date
time_from string(\$date-time) (query)	Filter by scheduled start. Accepts range. time_from
time_to string(\$date-time) (query)	Filter by scheduled end. Accepts range. time_to
time_in string(\$date-time) (query)	Filter by actual arrival. Accepts range. time_in

Name	Description
time_out string(\$date-time) (query)	Filter by actual departure. Accepts range. time_out
created_at string(\$date-time) (query)	Filter by created_at. Accepts range. created_at
updated_at string(\$date-time) (query)	Filter by updated_at. Accepts range. updated_at

Execute

Responses

Code	Description	Links
200	Successful response	No links

Media type

application/json

Controls Accept header.

Example Value Schema

```
{
  "data": [
    {
      "id": 0,
      "position": 0,
      "stop_type": "pick_up",
      "stop_company_name": "string",
      "address": "string",
      "city": "string",
      "state_code": "string",
      "zip_code": "string",
      "lat": 0,
      "lng": 0,
      "on_time": true,
      "arrival_status": "string",
      "completed": true,
      "load_id": 0,
      "customer_id": 0,
      "driver_id": 0,
      "driver_assigned_by_id": 0,
      "trailer_id": 0,
      "app_date": "2026-07-09",
      "time_from": "2026-07-09T11:12:26.132Z",
      "time_to": "2026-07-09T11:12:26.132Z",
    }
  ]
}
```



Code	Description	Links
400	<code>"time_in": "2026-07-09T11:12:26.132Z",</code> <code>"time_out": "2026-07-09T11:12:26.132Z",</code> <code>"driver_assigned_at": "2026-07-09T11:12:26.132Z",</code> <code>"created at": "2026-07-09T11:12:26.132Z",</code> Request was malformed or contained invalid parameters. Media type application/json Examples Unknown filter value (single error Example Value Schema <pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint",</pre>	No links

Code	Description	Links
	<pre>"details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	

GET

/destinations/{id}

Retrieve a destination



Parameters

Cancel

Name	Description
id * required integer (path)	id

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "id": 0, "position": 0, "stop_type": "pick_up", "stop_company_name": "string", "address": "string", "city": "string", "state_code": "string", "zip_code": "string", "lat": 0, "lng": 0, "on_time": true, "arrival_status": "string", "completed": true, "load_id": 0, "customer_id": 0, "driver_id": 0, "driver_assigned_by_id": 0, </pre>	

 No links |

Code	Description	Links
401	<pre>"trailer_id": 0, "app_date": "2026-07-09", "time_from": "2026-07-09T11:12:26.160Z", "time_to": "2026-07-09T11:12:26.160Z", "time_in": "2026-07-09T11:12:26.160Z", "time_out": "2026-07-09T11:12:26.160Z", "driver_assigned_at": "2026-07-09T11:12:26.160Z", "created_at": "2026-07-09T11:12:26.160Z", "undated_at": "2026-07-09T11:12:26.160Z"</pre> Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": {</pre>	No links

Code	Description	Links
	<pre>"request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }</pre>	

Detentions

List and retrieve detention events at destinations.

▼

Drivers

List and retrieve driver identity, status, and employment details.

▲

GET

/drivers

List drivers

 ▲

Paginated list of drivers scoped to the authenticated application's account.

Parameters

Cancel

Name	Description
id integer (query)	Bulk lookup. <code>?id[]=1&id[]=2</code> returns only drivers matching those IDs. id
page integer (query)	1
per_page integer (query)	25
sort string (query)	Sort field. Prefix with <code>-</code> for descending. --
status string (query)	Filter by status. Use <code>?status[]=a&status[]=b</code> for multiple values (OR). --

Name	Description
driver_type string (query)	Filter by driver type. Multi-value supported. --
tax_type string (query)	Filter by tax type. Multi-value supported. --
fleet_group string (query)	Filter by fleet group. Multi-value supported. --
manager_id integer (query)	Filter by manager User ID. Multi-value supported. manager_id
substitute_manager_id integer (query)	Filter by substitute manager User ID. Multi-value supported. substitute_manager_id
compensation_id integer (query)	Filter by compensation ID. Multi-value supported. compensation_id
payroll_schedule_id integer (query)	Filter by payroll schedule ID. Multi-value supported. payroll_schedule_id
created_at string(\$date-time) (query)	Filter by created_at. Accepts range — ? created_at[gte]=2026-01-01 . created_at
updated_at string(\$date-time) (query)	Filter by updated_at. Accepts range. updated_at

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": [{ "id": 8421, "first_name": "string", "last_name": "string", "middle_name": "string", "driver_nr": "string", "status": "active", "driver_type": "string", "tax_type": "string", "fleet_group": "none", "manager_id": 0, "substitute_manager_id": 0, "compensation_id": 0, "payroll_schedule_id": 0, "phone": "string", "email": "string", "cdl": "string", "cdl_state": "string", "address": "string", "city": "string", "state_code": "string", "zipcode": "string", "dob": "2026-07-09", "cdl_expire_date": "2026-07-09", "soc_sec_no": "string", "date_added": "2026-07-09", }]}</pre>	No links
400	Request was malformed or contained invalid parameters. Media type application/json Examples Unknown filter value (single error Example Value Schema <pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	No links

Code	Description	Links
	<pre>} }</pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

GET

/drivers/{id} Retrieve a driver



Parameters

Cancel

Name	Description
id * required integer (path)	id

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "id": 8421, "first_name": "string", "last_name": "string", "middle_name": "string", "driver_nr": "string", "status": "active", "driver_type": "string", "tax_type": "string", "fleet_group": "none", "manager_id": 0, "substitute_manager_id": 0, "compensation_id": 0, "payroll_schedule_id": 0, "phone": "string", "email": "string", "cdl": "string", "cdl_state": "string", "address": "string", "city": "string", "state_code": "string", "zipcode": "string", "dob": "2026-07-09", "cdl_expire_date": "2026-07-09", "soc_sec_no": "string", "date_added": "2026-07-09", "date_removed": "2026-07-09", } }</pre>	No links
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Code	Description	Links
	<pre>} }</pre>	
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Driver Notes List, retrieve, and create notes attached to drivers.



GET	/drivers/{driver_id}/notes List notes on a driver	 
Returns a paginated list of notes attached to the driver, newest first. Scoped to the authenticated application's account.		
Parameters		Cancel

Name	Description
driver_id * required integer (path)	driver_id
page integer (query)	1
per_page integer (query)	25

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": [{ "id": 0, "content": "Driver completed annual safety review.", "created_at": "2026-07-09T11:12:26.306Z", "updated_at": "2026-07-09T11:12:26.306Z" }], "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:26.306Z", "page": 1, "per_page": 25, "total": 142 } }</pre>	No links
401	Missing or invalid credentials. Media type application/json Example Value Schema	No links

Code	Description	Links
	<pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
403	Your application does not have permission for this endpoint.	No links
	Media type application/json	
	Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
404	The resource does not exist or is not accessible to this account.	No links
	Media type application/json	
	Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	

POST /drivers/{driver_id}/notes Create a note on a driver



Attaches a free-form note to the specified driver. The note is stored without an author user — partner-created notes appear in the internal UI marked as SYSTEM authorship.

Parameters

Cancel

NameDescription

driver_id * required
integer
(path)

driver_id

Request body required

application/json

Edit Value Schema

```
{
  "note": {
    "content": "Driver completed annual safety review."
  }
}
```



Execute

Responses

Code	Description	Links
201	Note created	No links
	Media type	
	application/json	
	Controls Accept header.	
	Example Value Schema	
	{ "data": { "id": 0, "content": "Driver completed annual safety review.", "created_at": "2026-07-09T11:12:26.341Z", "updated_at": "2026-07-09T11:12:26.341Z" } }	

Code	Description	Links
	<pre> }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:26.341Z" } } }</pre>	
400	Request was malformed or contained invalid parameters. Media type application/json Examples Unknown filter value (single error) Example Value Schema <pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema	No links

Code	Description	Links
	<pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
404	The resource does not exist or is not accessible to this account.	No links
	Media type application/json	
	Example Value Schema	
	<pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
422	Request was well-formed but failed validation.	No links
	Media type application/json	
	Example Value Schema	
	<pre>{ "data": null, "error": { "code": "validation_error", "message": "Validation failed", "details": [{ "field": "content", "code": "invalid_value", "message": "can't be blank" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	

GET

/drivers/{driver_id}/notes/{id} Retrieve a driver note



Returns a single note by id, scoped to the parent driver and the authenticated application's account.

Parameters

Cancel

Name

Description

driver_id * required

integer
(path)

driver_id

id * required

integer
(path)

id

Execute

Responses

Code

Description

Links

200

Successful response

No links

Media type

application/json

Controls Accept header.

Example Value Schema

```
{
  "data": {
    "id": 0,
    "content": "Driver completed annual safety review.",
    "created_at": "2026-07-09T11:12:26.392Z",
    "updated_at": "2026-07-09T11:12:26.392Z"
  },
  "error": null,
  "meta": {
    "request_id": "8f3a-c4e2-bb19-2f7d",
    "timestamp": "2026-07-09T11:12:26.392Z"
  }
}
```

401

Missing or invalid credentials.

No links

Media type

application/json

Example Value Schema

Code	Description	Links
	<pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Driver Documents

List, retrieve, and upload (multipart) documents attached to a driver profile.



GET	/drivers/{driver_id}/documents	List documents on a driver	
-----	--------------------------------	----------------------------	--

Returns a paginated list of documents attached to the driver, newest first. Scoped to the authenticated application's account.

Parameters

Cancel

Name

Description

driver_id * required

integer
(path)

driver_id

page

integer
(query)

1

per_page

integer
(query)

25

Execute

Responses

Code

Description

Links

200

Successful response

No links

Media type

application/json

Controls Accept header.

Example Value Schema

```
{
  "data": [
    {
      "id": 0,
      "upload_name": "cd1.pdf",
      "upload_type": "cd1",
      "content_type": "application/pdf",
      "size_bytes": 24576,
      "created_at": "2026-07-09T11:12:26.417Z",
      "updated_at": "2026-07-09T11:12:26.417Z"
    }
  ],
  "error": null,
  "meta": {
    "request_id": "8f3a-c4e2-bb19-2f7d",
    "timestamp": "2026-07-09T11:12:26.417Z",
  }
}
```

Code	Description	Links
	<pre>"page": 1, "per_page": 25, "total": 142 } }</pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Code	Description	Links
	<pre>} }</pre>	

POST

/drivers/{driver_id}/documents

Upload a document to a driver



Uploads a file (multipart/form-data) and attaches it to the driver's Files section, organized by **upload_type** into the corresponding folder. The file is stored in its original format — no PDF conversion.

Constraints:

- Max file size: 25 MB
- Allowed content types: `application/pdf` , `image/ineg` , `image/png` , `application/msword` , `application/vnd.openxmlformats-officedocument.wordprocessingml.document` , `application/vnd.ms-excel` , `application/vnd.openxmlformats-officedocument.spreadsheetml.sheet` , `text/csv` , `text/plain`
- Allowed extensions: `.pdf` , `.jpg` , `.jpeg` , `.png` , `.doc` , `.docx` , `.xls` , `.xlsx` , `.csv` , `.txt`
- **upload_type** is **required** and must match a Files-tab folder (see enum).

Curl example:

```
curl -X POST https://openroadtms.com/api/ext/v1/drivers/42/documents \  
-u "$CLIENT_ID:$CLIENT_SECRET" \  
-F "file=@/path/to/cdl.pdf" \  
-F "upload_type=cdl"
```

Parameters

Cancel

Reset

Name	Description
driver_id * required integer (path)	driver_id

Request body **required**

multipart/form-data

file * required

string(\$binary)

The file to upload. Required.

Choose File

No file chosen

upload_type * required
string

Required. Determines which folder the file appears in on the driver's Files tab.

cdl

Execute

Responses

Code	Description	Links
201	Document uploaded	No links

Media type

application/json

Controls Accept header.

Example Value Schema

```
{
  "data": {
    "id": 0,
    "upload_name": "cdl.pdf",
    "upload_type": "cdl",
    "content_type": "application/pdf",
    "size_bytes": 24576,
    "created_at": "2026-07-09T11:12:26.462Z",
    "updated_at": "2026-07-09T11:12:26.462Z"
  },
  "error": null,
  "meta": {
    "request_id": "8f3a-c4e2-bb19-2f7d",
    "timestamp": "2026-07-09T11:12:26.462Z"
  }
}
```

400	Request was malformed or contained invalid parameters.	No links
-----	--	----------

Media type

application/json

Examples

Unknown filter value (single error

Example Value Schema

```
{
  "data": null,
  "error": {
    "code": "invalid_filter",
    "message": "Invalid filter parameters",
    "details": [
      {
        "field": "status",
        "code": "invalid_value",
        "message": "value 'banana' is not one of [booked, assigned,
...]"
      }
    ]
  }
},
```

Code	Description	Links
	<pre>"meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }</pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Code	Description	Links
	<pre>} }</pre>	
422	Request was well-formed but failed validation. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "validation_error", "message": "Validation failed", "details": [{ "field": "content", "code": "invalid_value", "message": "can't be blank" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

GET `/drivers/{driver_id}/documents/{id}` Retrieve a driver document  

Returns a single document's metadata (no file bytes — download is out of scope for v1).

Parameters Cancel

Name	Description
driver_id * required integer (path)	driver_id
id * required integer (path)	id

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "id": 0, "upload_name": "cd1.pdf", "upload_type": "cd1", "content_type": "application/pdf", "size_bytes": 24576, "created_at": "2026-07-09T11:12:26.488Z", "updated_at": "2026-07-09T11:12:26.488Z" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:26.488Z" }}</pre>	No links
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	No links

Code	Description	Links
	<pre>} }</pre>	
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Elite Scores

Driver performance score snapshots over time periods. Each snapshot has a headline **score** and a set of grantable component sub-scores.

^

GET

/elite_scores

List elite score snapshots

^

Returns a paginated list of driver performance score snapshots. Each snapshot covers a date range (**period_start** to **period_end**) and carries a headline **score** . Component sub-scores (idle, route+fuel, mpg, on-time, etc.) are exposed as grantable fields — partners with the relevant grants see them inline; without grants they're omitted.

Filter by **driver_id** and date ranges to pull "current month" / "last month" / "last 30 days" / arbitrary windows.

Parameters

Cancel

Name	Description
id integer (query)	id
page integer (query)	1

NameDescription

per_page
integer
(query)

25

sort
string
(query)

--

driver_id
integer
(query)

Filter by driver. Multi-value supported.
driver_id

period_start
string(\$date-time)
(query)

Filter by `period_start` . Accepts range — `?period_start[gte]=2026-01-01` .
period_start

period_end
string(\$date-time)
(query)

Filter by `period_end` . Accepts range.
period_end

created_at
string(\$date-time)
(query)

Filter by created_at. Accepts range.
created_at

updated_at
string(\$date-time)
(query)

Filter by updated_at. Accepts range.
updated_at

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header.	No links

Code	Description	Links
	Example ValueSchema <pre>{ "data": [{ "id": 9182, "driver_id": 8421, "score": "string", "period_start": "2026-07-09T11:12:26.531Z", "period_end": "2026-07-09T11:12:26.531Z", "created_at": "2026-07-09T11:12:26.531Z", "updated_at": "2026-07-09T11:12:26.531Z", "idelic_score": 0, "home_time_score": 0, "mpg_score": 0, "route_and_fuel_score": 0, "idle_score": 0, "on_time_score": 0 }], "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:26.531Z", "page": 1, "per_page": 25, "total": 142 } }</pre>	

400Request was malformed or contained invalid parameters.No links

Media typeExamples

application/jsonUnknown filter value (single error)

Example Value	Schema
<pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	

401Missing or invalid credentials.No links

Media type

application/json

Example Value	Schema
---------------	--------

Code	Description	Links
	<pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
403	Your application does not have permission for this endpoint.	No links
	Media type application/json	
	Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	

GET

/elite_scores/{id}

Retrieve an elite score snapshot



Parameters

Cancel

Name	Description
id * required integer (path)	id

Execute

Responses

Code	Description	Links
200	Successful response	No links

Code	Description	Links
	Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "id": 9182, "driver_id": 8421, "score": "string", "period_start": "2026-07-09T11:12:26.547Z", "period_end": "2026-07-09T11:12:26.547Z", "created_at": "2026-07-09T11:12:26.547Z", "updated_at": "2026-07-09T11:12:26.547Z", "idelic_score": 0, "home_time_score": 0, "mpg_score": 0, "route_and_fuel_score": 0, "idle_score": 0, "on_time_score": 0 }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:26.547Z" } }</pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, }</pre>	No links

Code	Description	Links
	<pre>"meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }</pre>	
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Employees

Back-office staff referenced by FKs (e.g. `capacity_manager_id` on Customer). Minimal resolver shape — sensitive HR data (SSN, banking, emergency contacts) is never exposed.

^

GET /employees List employees  ^

Returns a paginated, sortable, filterable list of back-office staff scoped to the authenticated application's account.

Use this endpoint to resolve `capacity manager id` (and any future Employee FKs) into a name. Drivers are NOT here — drivers are on `/drivers`.

The response shape is intentionally minimal — this is a resolver, not a full HR record. SSN, DOB, banking, emergency contacts, and compensation data are never exposed regardless of grants.

Parameters

Cancel

Name	Description
id integer (query)	Bulk lookup. <code>?id[]=1&id[]=2</code> returns only employees matching those IDs. id

Name	Description
page integer (query)	1
per_page integer (query)	25
sort string (query)	Sort field. Prefix with - for descending. --
status string (query)	Filter by status. Multi-value supported. --
position string (query)	Filter by position. Multi-value supported. --
user_id integer (query)	Filter by linked User ID. Multi-value supported. user_id

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": [{ "id": 87, "first_name": "string", "last_name": "string", "position": "string", "status": "active", "office": "string", </pre>	No links

Code	Description	Links
400	<pre>"department": "string", "user_id": 0, "created_at": "2026-07-09T11:12:26.577Z", "updated_at": "2026-07-09T11:12:26.577Z", "email": "string", "phone": "string", "work_extension": "string", "work_phone": "string", "employment_date": "2026-07-09", "termination_date": "2026-07-09" }], "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:26.577Z", "page": 1, "per_page": 25, "total": 142 }</pre> Request was malformed or contained invalid parameters. Media type Examples application/json Unknown filter value (single error Example Value Schema <pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Code	Description	Links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	No links

GET	/employees/{id} Retrieve an employee	 
Parameters		Cancel
Name	Description	
id * required integer (path)	id	
Execute		
Responses		
Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "id": 87, "first_name": "string",</pre>	No links

Code	Description	Links
	<pre>"last_name": "string", "position": "string", "status": "active", "office": "string", "department": "string", "user_id": 0, "created_at": "2026-07-09T11:12:26.594Z", "updated_at": "2026-07-09T11:12:26.594Z", "email": "string", "phone": "string", "work_extension": "string", "work_phone": "string", "employment_date": "2026-07-09", "termination_date": "2026-07-09" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:26.594Z" } }</pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type	No links

Code	Description	Links
	application/json	
	Example ValueSchema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	

Loads

List and retrieve loads with their destinations.



GET

/loads

List loads

Returns a paginated, sortable, filterable list of loads scoped to the authenticated application's account.

Filter svntax: single value `?status=delivered` , multiple values `?status[]=delivered&status[]=billed` , range `?total[gte]=1000&total[lte]=5000` . Sort with `?sort=field` or `?sort=-field` for descending.

Parameters

Cancel

Name	Description
id integer (query)	Bulk lookup. <code>?id[]=1&id[]=2</code> returns only loads matching those IDs. id
page integer (query)	Page number (1-indexed) 1
per_page integer (query)	Results per page (capped at 100) 25

Name	Description
sort string (query)	Sort field. Prefix with - for descending. --
status string (query)	Filter by status. Use ?status[]=a&status[]=b for multiple values (OR). --
customer_id integer (query)	Filter by customer ID. Use ?customer_id[]=1&customer_id[]=2 for multiple values. customer_id
user_id integer (query)	Filter by load creator (implicit sales rep). Multi-value supported. user_id
account_manager_id integer (query)	Filter by account manager User ID. Multi-value supported. account_manager_id
csr_manager_id integer (query)	Filter by customer-service-rep manager User ID. Multi-value supported. csr_manager_id
planner_manager_id integer (query)	Filter by planner manager User ID. Multi-value supported. planner_manager_id
hot boolean (query)	Filter by hot flag (?hot=true). --
high_value boolean (query)	Filter by high-value flag. --
short_haul boolean (query)	Filter by short-haul flag (load-level "local" indicator). --

Name	Description
flatbed boolean (query)	Filter by flatbed flag. --
edi_load boolean (query)	Filter by EDI-tendered loads. --
edi_accepted boolean (query)	Filter by EDI-accepted loads (only meaningful when edi_load=true). --
total number (query)	Filter by total. Accepts exact match (?total=1000) or range (?total[gte]=1000&total[lte]=5000). Range operators: gte , gt , lte , lt . total
miles number (query)	Filter by miles. Accepts exact match or range. Range operators: gte , gt , lte , lt . miles
linehaul_rate number (query)	Filter by line-haul rate. Accepts exact match or range. Range operators: gte , gt , lte , lt . linehaul_rate
fuel_surcharge number (query)	Filter by fuel surcharge. Accepts exact match or range. Range operators: gte , gt , lte , lt . fuel_surcharge
empty_miles_sum number (query)	Filter by empty (deadhead) miles sum. Accepts exact match or range. Range operators: gte , gt , lte , lt . empty_miles_sum

Name	Description
detention_sum number (query)	Filter by stored detention charge total on the load. Accepts exact match or range — use <code>?detention_sum[gt]=0</code> to list loads with detention. detention_sum
first_pu_time_from string(\$date-time) (query)	Filter by first pickup window start. Accepts range — <code>?first_pu_time_from[gte]=2026-04-01</code> . first_pu_time_from
last_del_time_to string(\$date-time) (query)	Filter by last delivery window end. Accepts range — <code>?last_del_time_to[lt]=2026-05-01</code> . last_del_time_to
created_at string(\$date-time) (query)	Filter by created_at. Accepts range. created_at
updated_at string(\$date-time) (query)	Filter by updated_at. Accepts range. updated_at

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema<pre>{ "data": [{ "id": 12345,</pre>	No links

Code	Description	Links
	<pre>"status": "delivered", "customer_load": "string", "gp_load": "string", "customer_id": 0, "customer_name": "string", "user_id": 0, "account_manager_id": 0, "csr_manager_id": 0, "planner_manager_id": 0, "equipment": "Van", "commodity": "string", "weight": "string", "size": "FTL", "temperature": "string", "contract_spot": "contract", "hot": true, "high_value": true, "short_haul": true, "flatbed": true, "edi_load": true, "edi_accepted": true, "empty_miles_sum": "string", "detention_sum": "string", "first_mile_time_from": "2026-07-08T11:13:36-0700"</pre>	

400

Request was malformed or contained invalid parameters.

No links

Media type

Examples

application/json

Unknown filter value (single error

Example Value Schema

```
{
  "data": null,
  "error": {
    "code": "invalid_filter",
    "message": "Invalid filter parameters",
    "details": [
      {
        "field": "status",
        "code": "invalid_value",
        "message": "value 'banana' is not one of [booked, assigned,
...]"
      }
    ]
  },
  "meta": {
    "request_id": "8f3a-c4e2-bb19-2f7d",
    "timestamp": "2026-04-14T12:00:00Z"
  }
}
```

401

Missing or invalid credentials.

No links

Media type

application/json

Example Value Schema

```
{
  "data": null,
  "error": {
    "code": "unauthorized",
    "message": "Invalid credentials",
    "details": []
  },
  "meta": {
```

Code	Description	Links
	<pre>"request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

GET /loads/{id} Retrieve a load

Returns a single load with its destinations.

Parameters

Cancel

Name	Description
id * required integer (path)	Load ID id

Execute

Responses

Code	Description	Links
200	Successful response	No links

Media type

Code

Description

Links

application/json

Controls Accept header.

Example Value Schema

```
{
  "data": {
    "id": 12345,
    "status": "delivered",
    "customer_load": "string",
    "gp_load": "string",
    "customer_id": 0,
    "customer_name": "string",
    "user_id": 0,
    "account_manager_id": 0,
    "csr_manager_id": 0,
    "planner_manager_id": 0,
    "equipment": "Van",
    "commodity": "string",
    "weight": "string",
    "size": "FTL",
    "temperature": "string",
    "contract_spot": "contract",
    "hot": true,
    "high_value": true,
    "short_haul": true,
    "flatbed": true,
    "edi_load": true,
    "edi_accepted": true,
    "empty_miles_sum": "string",
    "detention_sum": "string",
    "first_pu_time_from": "2026-07-09T11:12:26.688Z",
    "last_del_time_to": "2026-07-09T11:12:26.688Z",
  }
}
```

401

Missing or invalid credentials.

No links

Media type

application/json

Example Value Schema

```
{
  "data": null,
  "error": {
    "code": "unauthorized",
    "message": "Invalid credentials",
    "details": []
  },
  "meta": {
    "request_id": "8f3a-c4e2-bb19-2f7d",
    "timestamp": "2026-04-14T12:00:00Z"
  }
}
```

403

Your application does not have permission for this endpoint.

No links

Media type

application/json

Example Value Schema

```
{
  "data": null,
  "error": {
    "code": "forbidden",
  }
}
```

Code	Description	Links
	<pre>"message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }</pre>	
404	The resource does not exist or is not accessible to this account.	No links
Media type		
application/json		
Example Value Schema		
<pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>		

Load Notes

List, retrieve, and create notes attached to loads.

^

GET

/loads/{load_id}/notes

List notes on a load

^

Returns a paginated list of notes attached to the load, newest first. Scoped to the authenticated application's account — notes on loads in other accounts are not accessible.

Parameters

Cancel

Name	Description
load_id * required integer (path)	Load ID load_id
page integer (query)	Page number (1-indexed) 1

Name	Description
per_page integer (query)	Results per page (capped at 100) 25

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": [{ "id": 4821, "content": "Delivered early – receiver confirmed at 14:05.", "created_at": "2026-07-09T11:12:26.709Z", "updated_at": "2026-07-09T11:12:26.709Z" }], "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:26.709Z", "page": 1, "per_page": 25, "total": 142 } }</pre>	No links
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Code	Description	Links
	<pre>} }</pre>	
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

POST

/loads/{load_id}/notes

Create a note on a load



Attaches a free-form note to the specified load. The note is stored without an author user — partner-created notes appear in the internal UI marked as SYSTEM authorship. Use `meta.request_id` to correlate with support.

Parameters

Cancel

Name	Description
load_id * required	Load ID

Name

Description

integer
(path)

load_id

Request body

required

application/json

Edit Value

Schema

```
{
  "note": {
    "content": "Delivered early – receiver confirmed at 14:05."
  }
}
```

↗

Execute

Responses

Code	Description	Links
201	Note created Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "id": 4821, "content": "Delivered early – receiver confirmed at 14:05.", "created_at": "2026-07-09T11:12:26.726Z", "updated_at": "2026-07-09T11:12:26.726Z" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:26.726Z" } }</pre>	

 No links |

Code	Description	Links
	<pre>} }</pre>	
400	Request was malformed or contained invalid parameters.	No links
	Media type application/json Examples Unknown filter value (single error	
	Example Value Schema <pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
401	Missing or invalid credentials.	No links
	Media type application/json	
	Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
403	Your application does not have permission for this endpoint.	No links
	Media type application/json	
	Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] } }</pre>	

Code	Description	Links
	<pre> }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } } }</pre>	
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
422	Request was well-formed but failed validation. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "validation_error", "message": "Validation failed", "details": [{ "field": "content", "code": "invalid_value", "message": "can't be blank" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

GET

/loads/{load_id}/notes/{id}

Retrieve a note



Returns a single note by id, scoped to the parent load and the authenticated application's account.

Parameters

Cancel

Name	Description
load_id * required integer (path)	Load ID load_id
id * required integer (path)	Note ID id

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "id": 4821, "content": "Delivered early – receiver confirmed at 14:05.", "created_at": "2026-07-09T11:12:26.743Z", "updated_at": "2026-07-09T11:12:26.743Z" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:26.743Z" }}</pre>	No links
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials",</pre>	No links

Code	Description	Links
	<pre>"details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Payroll Schedules

Pay-cadence reference data used by drivers. Small set of records per account; partners typically fetch once and cache.



GET	/payroll_schedules	List payroll schedules	 
Returns a paginated list of pay schedules in the account. Stable reference data — typically a handful of records per account that partners fetch once and cache. No grantable fields; whole record is non-PII.			

Parameters

Cancel

Name	Description
id integer (query)	Bulk lookup. <code>?id[]=1&id[]=2</code> returns only schedules matching those IDs. id
page integer (query)	1
per_page integer (query)	25
sort string (query)	Sort field. Prefix with <code>-</code> for descending. --
frequency string (query)	Filter by frequency. Multi-value supported. --

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema<pre>{ "data": [{ "id": 7, "name": "NET6 Weekly", "frequency": "weekly", "start_day": 0, "days_to_pay": 0,</pre>	No links

Code	Description	Links
	<pre>"created_at": "2026-07-09T11:12:26.768Z", "updated_at": "2026-07-09T11:12:26.768Z" }], "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:26.768Z", "page": 1, "per_page": 25, "total": 142 } }</pre>	
400	Request was malformed or contained invalid parameters.	No links
Media type application/json		
Examples Unknown filter value (single error)		
Example Value Schema		
	<pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
401	Missing or invalid credentials.	No links
Media type application/json		
Example Value Schema		
	<pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
403	Your application does not have permission for this endpoint.	No links
Media type		

Code	Description	Links
	application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	

GET	/payroll_schedules/{id} Retrieve a payroll schedule	 
Parameters		Cancel
Name	Description	
id * required integer (path)	id	
Execute		
Responses		
Code	Description	Links
200	Successful response	No links
	Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "id": 7, "name": "NET6 Weekly", "frequency": "weekly", "start_day": 0, "days_to_pay": 0, "created_at": "2026-07-09T11:12:26.792Z",</pre>	

Code	Description	Links
	<pre>"updated_at": "2026-07-09T11:12:26.792Z" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:26.792Z" } }</pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": {</pre>	No links

Code	Description	Links
	<pre>"request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }</pre>	

Trailers

List and retrieve fleet trailer details.



GET

/trailers

List trailers

Paginated list of trailers scoped to the authenticated application's account.

Parameters

Cancel

Name	Description
id integer (query)	Bulk lookup. <code>?id[]=1&id[]=2</code> returns only trailers matching those IDs. id
page integer (query)	1
per_page integer (query)	25
sort string (query)	Sort field. Prefix with <code>-</code> for descending. Grant-gated date sorts (<code>annual inspection_date</code> , <code>annual inspection exp date</code> , <code>quarterly maintenance_date</code> , <code>ins_expiration_date</code>) require the matching field grant — otherwise the request returns 400 <code>invalid_sort</code> . --
status string (query)	Filter by status. Multi-value supported. --
ownership_type string	Filter by ownership type. Multi-value supported.

Name	Description
<i>(query)</i>	ownership_type
reefer_type string <i>(query)</i>	Filter by reefer type. Multi-value supported. reefer_type
make string <i>(query)</i>	Filter by make. Multi-value supported. make
year integer <i>(query)</i>	Filter by year. Accepts range. year
OOS boolean <i>(query)</i>	Filter by out-of-service flag. --
needs_repair boolean <i>(query)</i>	Filter by needs-repair flag. --
lease boolean <i>(query)</i>	Filter by lease flag. --
samsara_dev_id string <i>(query)</i>	Filter by Samsara device ID. Multi-value supported. samsara_dev_id
insurance_policy string <i>(query)</i>	Filter by insurance policy reference. Multi-value supported. Grant-gated — requires insurance_policy field grant. insurance_policy
annual_inspection_date string(\$date) <i>(query)</i>	Filter by annual inspection date. Accepts range. Grant-gated — requires annual_inspection_date field grant. annual_inspection_date

Name	Description
annual_inspection_exp_date string(\$date) (query)	Filter by annual inspection expiration date. Accepts range. Grant-gated — requires annual_inspection_exp_date field grant. annual_inspection_exp_date
quarterly_maintenance_date string(\$date) (query)	Filter by quarterly maintenance date. Accepts range. Grant-gated — requires quarterly_maintenance_date field grant. quarterly_maintenance_date
ins_expiration_date string(\$date) (query)	Filter by insurance expiration date. Accepts range. Grant-gated — requires ins_expiration_date field grant. ins_expiration_date
cost number (query)	Filter by acquisition cost. Accepts range. Grant-gated — requires cost field grant. cost
created_at string(\$date-time) (query)	Filter by created_at. Accepts range. created_at
updated_at string(\$date-time) (query)	Filter by updated_at. Accepts range. updated_at
Execute	

Responses

Code	Description	Links
200	Successful response Media type	No links

Code

Description

Links

application/json

Controls Accept header.

Example Value Schema

```
{
  "data": [
    {
      "id": 502,
      "trailer_id": "string",
      "status": "active",
      "make": "string",
      "model": "string",
      "year": 0,
      "vin": "string",
      "length": 0,
      "reefer_type": "string",
      "trailer_type": "string",
      "license_plate": "string",
      "license_state_code": "string",
      "ownership_type": "string",
      "oos": true,
      "needs_repair": true,
      "lease": true,
      "samsara_dev_id": "string",
      "annual_inspection_date": "2026-07-09",
      "annual_inspection_exp_date": "2026-07-09",
      "acquisition_date": "2026-07-09T11:12:26.911Z",
      "oos_note": "string",
      "needs_repair_note": "string",
      "quarterly_maintenance_date": "2026-07-09",
      "monthly_insurance_cost": "string",
      "ins_expiration_date": "2026-07-09",
    }
  ]
}
```

400

Request was malformed or contained invalid parameters.

No links

Media type

Examples

application/json

Unknown filter value (single error

Example Value Schema

```
{
  "data": null,
  "error": {
    "code": "invalid_filter",
    "message": "Invalid filter parameters",
    "details": [
      {
        "field": "status",
        "code": "invalid_value",
        "message": "value 'banana' is not one of [booked, assigned,
      ...]"
      }
    ]
  },
  "meta": {
    "request_id": "8f3a-c4e2-bb19-2f7d",
    "timestamp": "2026-04-14T12:00:00Z"
  }
}
```

401

Missing or invalid credentials.

No links

Media type

Code	Description	Links
	application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	No links

GET

/trailers/{id}

Retrieve a trailer



Parameters

Cancel

Name	Description
id * required integer (path)	id

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "id": 502, "trailer_id": "string", "status": "active", "make": "string", "model": "string", "year": 0, "vin": "string", "length": 0, "reefer_type": "string", "trailer_type": "string", "license_plate": "string", "license_state_code": "string", "ownership_type": "string", "oos": true, "needs_repair": true, "lease": true, "samsara_dev_id": "string", "annual_inspection_date": "2026-07-09", "annual_inspection_exp_date": "2026-07-09", "acquisition_date": "2026-07-09T11:12:26.935Z", "oos_note": "string", "needs_repair_note": "string", "quarterly_maintenance_date": "2026-07-09", "monthly_insurance_cost": "string", "ins_expiration_date": "2026-07-09", "total_insurance_cost": "string", } }</pre>	No links
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json	No links

Code	Description	Links
	Example ValueSchema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	
404	The resource does not exist or is not accessible to this account. Media type application/json Example ValueSchema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	No links

PATCH

/trailers/{id}

Update a trailer



Update mutable fields on a trailer. See the request body schema below for the current writable field set; any other body keys are silently dropped.

Grantable fields require the matching field grant to write — without the grant, those keys are silently dropped from the request (consistent with read-side behavior).

Parameters

Cancel

Name	Description
id * required integer (path)	id

Request body required

application/json

Edit Value Schema

```
{
  "trailer": {
    "oos": true,
    "oos_note": "Reefer unit failure"
  }
}
```



Execute

Responses

Code	Description	Links
200	Trailer updated	No links

Media type

application/json

Controls Accept header.

Example Value Schema

```
{
  "data": {
    "id": 502,
    "trailer_id": "string",
    "status": "active",
    "make": "string",
    "model": "string",
    "year": 0,
    "vin": "string",
    "length": 0,
    "reefer_type": "string",
    "trailer_type": "string",
    "license_plate": "string",
    "license_state_code": "string",
    "ownership_type": "string",
    "oos": true,
    "needs_repair": true,
    "lease": true,
    "samsara_dev_id": "string",
    "annual_inspection_date": "2026-07-09",
    "annual_inspection_exp_date": "2026-07-09",
    "acquisition_date": "2026-07-09T11:12:26.979Z",
    "oos_note": "string",
  }
}
```



Code	Description	Links
400	<pre>"needs_repair_note": "string", "quarterly_maintenance_date": "2026-07-09", "monthly_insurance_cost": "string", "ins_expiration_date": "2026-07-09",</pre>	No links
	Request was malformed or contained invalid parameters.	
	Media type	
	Examples	
	application/json Unknown filter value (single error	
	Example Value Schema	
	<pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
401	Missing or invalid credentials.	No links
	Media type	
	application/json	
	Example Value Schema	
	<pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
403	Your application does not have permission for this endpoint.	No links
	Media type	
	application/json	
	Example Value Schema	
	<pre>{ "data": null, "error": { "code": "forbidden",</pre>	

Code	Description	Links
	<pre>"message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }</pre>	
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
422	Request was well-formed but failed validation. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "validation_error", "message": "Validation failed", "details": [{ "field": "content", "code": "invalid_value", "message": "can't be blank" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Trailer Notes

List, retrieve, and create notes attached to trailers.



GET	/trailers/{trailer_id}/notes	List notes on a trailer	 
-----	------------------------------	-------------------------	---

Paginated list of notes attached to the trailer, newest first. Scoped to the authenticated application's account.

Parameters

Cancel

Name

Description

trailer_id * required

integer
(path)

trailer_id

page

integer
(query)

1

per_page

integer
(query)

25

Execute

Responses

Code

Description

Links

200

Successful response

No links

Media type

application/json

Controls Accept header.

Example Value Schema

```
{
  "data": [
    {
      "id": 0,
      "content": "Reefer unit serviced and back in rotation.",
      "created_at": "2026-07-09T11:12:27.032Z",
      "updated_at": "2026-07-09T11:12:27.032Z"
    }
  ],
  "error": null,
  "meta": {
    "request_id": "8f3a-c4e2-bb19-2f7d",
    "timestamp": "2026-07-09T11:12:27.032Z",
    "page": 1,
    "per_page": 25,
    "total": 142
  }
}
```

Code	Description	Links
	<pre>} }</pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

POST /trailers/{trailer_id}/notes Create a note on a trailer



Attaches a free-form note to the specified trailer. Partner-created notes appear in the internal UI marked as SYSTEM authorship.

Parameters

Cancel

Name Description

trailer_id * required
integer
(path)

trailer_id

Request body required

application/json

Edit Value Schema

```
{
  "note": {
    "content": "Reefer unit serviced and back in rotation."
  }
}
```



Execute

Responses

Code	Description	Links
201	Note created	No links
	Media type	
	application/json	

Code	Description	Links
	Controls Accept header.	
	Example Value Schema	
	<pre>{ "data": { "id": 0, "content": "Reefer unit serviced and back in rotation.", "created_at": "2026-07-09T11:12:27.066Z", "updated_at": "2026-07-09T11:12:27.066Z" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:27.066Z" } }</pre>	
400	Request was malformed or contained invalid parameters.	No links
	Media type	Examples
	application/json	Unknown filter value (single error)
	Example Value Schema	
	<pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
401	Missing or invalid credentials.	No links
	Media type	
	application/json	
	Example Value Schema	
	<pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	

Code	Description	Links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	No links
422	Request was well-formed but failed validation. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "validation_error", "message": "Validation failed", "details": [{ "field": "content", "code": "invalid_value", "message": "can't be blank" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	No links

Code	Description	Links
	<pre>} }</pre>	

GET

/trailers/{trailer_id}/notes/{id}

Retrieve a trailer note



Returns a single note by id, scoped to the parent trailer and the authenticated application's account.

Parameters

Cancel

Name	Description
trailer_id * required integer (path)	trailer_id
id * required integer (path)	id

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "id": 0, "content": "Reefer unit serviced and back in rotation.", "created_at": "2026-07-09T11:12:27.100Z", "updated_at": "2026-07-09T11:12:27.101Z" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:27.101Z" } }</pre>	No links

Code	Description	Links
	<pre>} }</pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Trailer Documents

List, retrieve, and upload (multipart) documents attached to a trailer.



GET

/trailers/{trailer_id}/documents

List documents on a trailer

Paginated list of documents attached to the trailer, newest first.

Parameters

Cancel

Name	Description
trailer_id * required integer (path)	trailer_id
page integer (query)	1
per_page integer (query)	25

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": [{ "id": 0, "upload_name": "trailer_registration.pdf", "upload_type": "trailer_registration", "content_type": "application/pdf", "size_bytes": 24576, "created_at": "2026-07-09T11:12:27.130Z", }]}</pre>	

 No links |

Code	Description	Links
	<pre> "updated_at": "2026-07-09T11:12:27.130Z" }], "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:27.130Z", "page": 1, "per_page": 25, "total": 142 } } }</pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found",</pre>	No links

Code	Description	Links
	<pre>"message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }</pre>	

POST

/trailers/{trailer_id}/documents

Upload a document to a trailer



Uploads a file (multipart/form-data) attached to the trailer's Files section. See [/drivers/{driver_id}/documents](#) POST for full multipart contract details (size limit, MIME whitelist, extensions).

Parameters

Cancel

Reset

Name	Description
trailer_id * required integer (path)	trailer_id

Request body required

multipart/form-data

file * required

string(\$binary)

Choose File

No file chosen

upload_type * required

string

Required. Determines which folder the file appears in on the trailer's Files tab.

trailer_registration

Execute

Responses

Code	Description	Links
201	Document uploaded	No links

Code	Description	Links
	Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "id": 0, "upload_name": "trailer_registration.pdf", "upload_type": "trailer_registration", "content_type": "application/pdf", "size_bytes": 24576, "created_at": "2026-07-09T11:12:27.166Z", "updated_at": "2026-07-09T11:12:27.166Z" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:27.166Z" }}</pre>	
400	Request was malformed or contained invalid parameters. Media type application/json Examples Unknown filter value (single error) Example Value Schema <pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	No links
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials",</pre>	No links

Code	Description	Links
	<pre>"details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
422	Request was well-formed but failed validation. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "validation_error", "message": "Validation failed", "details": [{ "field": "content", "code": "invalid_value", </pre>	No links

Code	Description	Links
	<pre> "message": "can't be blank" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	

GET

/trailers/{trailer_id}/documents/{id}

Retrieve a trailer document



Returns metadata for a single document attached to the trailer.

Parameters

Cancel

Name	Description
trailer_id * required integer (path)	trailer_id
id * required integer (path)	id

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "id": 0, "upload_name": "trailer_registration.pdf", "upload_type": "trailer_registration", "content_type": "application/pdf",</pre>	No links

Code	Description	Links
	<pre> "size_bytes": 24576, "created_at": "2026-07-09T11:12:27.203Z", "updated_at": "2026-07-09T11:12:27.203Z" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:27.203Z" } } </pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre> { "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } } </pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre> { "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } } </pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre> { "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] } } </pre>	No links

Code	Description	Links
	<pre> }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } } }</pre>	

Trucks

List and retrieve fleet truck details.



GET

/trucks

List trucks

Paginated list of trucks scoped to the authenticated application's account.

Parameters

Cancel

Name	Description
id integer (query)	Bulk lookup. <code>?id[]=1&id[]=2</code> returns only trucks matching those IDs. id
page integer (query)	1
per_page integer (query)	25
sort string (query)	Sort field. Prefix with <code>-</code> for descending. Grant-gated date sorts (<code>iro expiration date</code> , <code>ins expiration date</code> , <code>annual_inspection_date</code> , <code>quarterly_maintenance_date</code>) require the matching field grant — otherwise the request returns 400 <code>invalid_sort</code> . --
status string (query)	Filter by status. Multi-value supported. --
ownership_type	Filter by ownership type. Multi-value supported.

Name	Description
string (query)	ownership_type
make string (query)	Filter by make. Multi-value supported. make
year integer (query)	Filter by year. Accepts range — <code>?year[gte]=2020</code> . year
OOS boolean (query)	Filter by out-of-service flag. --
needs_repair boolean (query)	Filter by needs-repair flag. --
irp boolean (query)	Filter by IRP registration flag. --
lease boolean (query)	Filter by lease flag. --
samsara_dev_id string (query)	Filter by Samsara device ID. Multi-value supported. samsara_dev_id
irp_expiration_date string(\$date) (query)	Filter by IRP expiration date. Accepts range — <code>?irp_expiration_date[lt]=2026-12-31</code> . Grant-gated — without the <code>irp_expiration_date</code> field grant, returns 400 <code>invalid_filter</code> . irp_expiration_date
ins_expiration_date string(\$date) (query)	Filter by insurance expiration date. Accepts range. Grant-gated — requires <code>ins_expiration_date</code> field grant. ins_expiration_date

Name	Description
annual_inspection_date string(\$date) (query)	Filter by annual inspection date. Accepts range. Grant-gated — requires annual_inspection_date field grant. annual_inspection_date
quarterly_maintenance_date string(\$date) (query)	Filter by quarterly maintenance date. Accepts range. Grant-gated — requires quarterly_maintenance_date field grant. quarterly_maintenance_date
cost number (query)	Filter by acquisition cost. Accepts range. Grant-gated — requires cost field grant. cost
created_at string(\$date-time) (query)	Filter by created_at. Accepts range. created_at
updated_at string(\$date-time) (query)	Filter by updated_at. Accepts range. updated_at
Execute	

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": [{</pre>	No links

Code	Description	Links
400	<pre>"id": 312, "unit": "string", "status": "active", "make": "string", "model": "string", "year": 0, "color": "string", "vin": "string", "license_plate": "string", "state_code": "string", "ownership_type": "string", "oos": true, "needs_repair": true, "slip_seating": true, "irp": true, "lease": true, "samsara_dev_id": "string", "annual_inspection_date": "2026-07-09", "irp_expiration_date": "2026-07-09", "ins_expiration_date": "2026-07-09", "insured_value": "string", "acquisition_date": "2026-07-09T11:12:27.306Z", "oos_note": "string", "needs_repair_note": "string", "irn add date": "2026-07-09".</pre> Request was malformed or contained invalid parameters. Media type Examples application/json Unknown filter value (single error	No links

Example Value Schema

```
{
  "data": null,
  "error": {
    "code": "invalid_filter",
    "message": "Invalid filter parameters",
    "details": [
      {
        "field": "status",
        "code": "invalid_value",
        "message": "value 'banana' is not one of [booked, assigned,
...]"
      }
    ]
  },
  "meta": {
    "request_id": "8f3a-c4e2-bb19-2f7d",
    "timestamp": "2026-04-14T12:00:00Z"
  }
}
```

401	Missing or invalid credentials. Media type application/json	No links
-----	--	----------

Example Value Schema

```
{
  "data": null,
  "error": {
    "code": "unauthorized",
    "message": "Invalid credentials",
    "details": []
  }
}
```

Code	Description	Links
	<pre> }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } } }</pre>	
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

GET	/trucks/{id} Retrieve a truck	 
Parameters		Cancel
Name	Description	
id * required integer (path)	id	
Execute		
Responses		
Code	Description	Links
200	Successful response Media type application/json Controls Accept header.	No links

Code	Description	Links
	Example Value Schema <pre>{ "data": { "id": 312, "unit": "string", "status": "active", "make": "string", "model": "string", "year": 0, "color": "string", "vin": "string", "license_plate": "string", "state_code": "string", "ownership_type": "string", "oos": true, "needs_repair": true, "slip_seating": true, "irp": true, "lease": true, "samsara_dev_id": "string", "annual_inspection_date": "2026-07-09", "irp_expiration_date": "2026-07-09", "ins_expiration_date": "2026-07-09", "insured_value": "string", "acquisition_date": "2026-07-09T11:12:27.325Z", "oos_note": "string", "needs_repair_note": "string", "irp_add_date": "2026-07-09", "irp_remove_date": "2026-07-09", } }</pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": {</pre>	No links

Code	Description	Links
	<pre>"request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema<pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

PATCH

/trucks/{id}

Update a truck



Update mutable fields on a truck. See the request body schema below for the current writable field set; any other body keys are silently dropped.

Grantable fields require the matching field grant to write — without the grant, those keys are silently dropped from the request (consistent with read-side behavior).

Parameters

Cancel

Name	Description
id * required integer (path)	id

Request body required

application/json

Edit Value

Schema

```
{
  "truck": {
    "oos": true,
    "oos_note": "Engine fault – towed to shop"
  }
}
```



Execute

Responses

Code	Description	Links
200	Truck updated	No links

Media type

application/json

Controls Accept header.

Example Value Schema

```
{
  "data": {
    "id": 312,
    "unit": "string",
    "status": "active",
    "make": "string",
    "model": "string",
    "year": 0,
    "color": "string",
    "vin": "string",
    "license_plate": "string",
    "state_code": "string",
    "ownership_type": "string",
    "oos": true,
    "needs_repair": true,
    "slip_seating": true,
    "irp": true,
    "lease": true,
    "samsara_dev_id": "string",
    "annual_inspection_date": "2026-07-09",
    "irp_expiration_date": "2026-07-09",
    "ins_expiration_date": "2026-07-09",
    "insured_value": "string",
    "acquisition_date": "2026-07-09T11:12:27.363Z",
    "oos_note": "string",
    "needs_repair_note": "string",
    "irp_add_date": "2026-07-09",
```



119/154

Code	Description	Links
	<pre>"request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
422	Request was well-formed but failed validation. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "validation_error", "message": "Validation failed", "details": [{ "field": "content", "code": "invalid_value", "message": "can't be blank" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Truck Notes

List, retrieve, and create notes attached to trucks.



GET	/trucks/{truck_id}/notes	List notes on a truck	 
Paginated list of notes attached to the truck, newest first. Scoped to the authenticated application's			

account.

Parameters

Cancel

NameDescription

truck_id * required
integer
(path)

truck_id

page
integer
(query)

1

per_page
integer
(query)

25

Execute

Responses

Code	Description	Links
200	Successful response	No links

Media type

application/json

Controls Accept header.

Example Value Schema

```
{
  "data": [
    {
      "id": 0,
      "content": "Tire pressure check passed.",
      "created_at": "2026-07-09T11:12:27.409Z",
      "updated_at": "2026-07-09T11:12:27.409Z"
    }
  ],
  "error": null,
  "meta": {
    "request_id": "8f3a-c4e2-bb19-2f7d",
    "timestamp": "2026-07-09T11:12:27.409Z",
    "page": 1,
    "per_page": 25,
    "total": 142
  }
}
```

Code	Description	Links
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

POST /trucks/{truck_id}/notes Create a note on a truck



Attaches a free-form note to the specified truck. Partner-created notes appear in the internal UI marked as SYSTEM authorship.

Parameters

Cancel

Name Description

truck_id * required
integer
(path)

truck_id

Request body required

application/json

Edit Value Schema

```
{
  "note": {
    "content": "Tire pressure check passed."
  }
}
```



Execute

Responses

Code	Description	Links
201	Note created	No links
Media type		application/json

Code	Description	Links
	Controls Accept header.	
	Example Value Schema	
	<pre>{ "data": { "id": 0, "content": "Tire pressure check passed.", "created_at": "2026-07-09T11:12:27.438Z", "updated_at": "2026-07-09T11:12:27.438Z" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:27.438Z" } }</pre>	
400	Request was malformed or contained invalid parameters.	No links
	Media type	Examples
	application/json	Unknown filter value (single error)
	Example Value Schema	
	<pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
401	Missing or invalid credentials.	No links
	Media type	
	application/json	
	Example Value Schema	
	<pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	

Code	Description	Links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	No links
422	Request was well-formed but failed validation. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "validation_error", "message": "Validation failed", "details": [{ "field": "content", "code": "invalid_value", "message": "can't be blank" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	No links

Code	Description	Links
	<pre>} }</pre>	

GET

/trucks/{truck_id}/notes/{id}

Retrieve a truck note



Returns a single note by id, scoped to the parent truck and the authenticated application's account.

Parameters

Cancel

Name	Description
truck_id * required integer (path)	truck_id
id * required integer (path)	id

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "id": 0, "content": "Tire pressure check passed.", "created_at": "2026-07-09T11:12:27.469Z", "updated_at": "2026-07-09T11:12:27.469Z" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:27.469Z" } }</pre>	No links

Code	Description	Links
	<pre>} }</pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Truck Documents

List, retrieve, and upload (multipart) documents attached to a truck.

^

GET

/trucks/{truck_id}/documents

List documents on a truck



Returns a paginated list of documents attached to the truck, newest first. Scoped to the authenticated application's account.

Parameters

Cancel

Name	Description
truck_id * required integer (path)	truck_id
page integer (query)	1
per_page integer (query)	25

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": [{ "id": 0, "upload_name": "annual_inspection.pdf", "upload_type": "annual_inspection", "content_type": "application/pdf", }]}</pre>	

 No links |

Code	Description	Links
	<pre>"size_bytes": 24576, "created_at": "2026-07-09T11:12:27.502Z", "updated_at": "2026-07-09T11:12:27.502Z" }], "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:27.502Z", "page": 1, "per_page": 25, "total": 142 } }</pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null,</pre>	No links

Code	Description	Links
	<pre>"error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	

POST

/trucks/{truck_id}/documents

Upload a document to a truck



Uploads a file (multipart/form-data) and attaches it to the truck's Files section, organized by **upload_type** into the corresponding folder. The file is stored in its original format — no PDF conversion. See [/drivers/{driver_id}/documents](#) POST for full multipart contract details (size limit, MIME whitelist, extensions).

Parameters

Cancel

Reset

Name	Description
truck_id * required integer (path)	truck_id

Request body **required**

multipart/form-data

file * required

string(\$binary)

Choose File

No file chosen

upload_type * required

string

Required. Determines which folder the file appears in on the truck's Files tab.

lease_agreement

Execute

Responses

Code	Description	Links
201	Document uploaded Media type application/json Controls Accept header. Example Value Schema<pre>{ "data": { "id": 0, "upload_name": "annual_inspection.pdf", "upload_type": "annual_inspection", "content_type": "application/pdf", "size_bytes": 24576, "created_at": "2026-07-09T11:12:27.557Z", "updated_at": "2026-07-09T11:12:27.557Z" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:27.557Z" }}</pre>	No links
400	Request was malformed or contained invalid parameters. Media type application/json Examples Unknown filter value (single error) Example Value Schema<pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>	No links
401	Missing or invalid credentials. Media type application/json Example Value Schema<pre>{ "data": null,</pre>	No links

Code	Description	Links
	<pre>"error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
422	Request was well-formed but failed validation. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "validation_error", "message": "Validation failed", "details": [</pre>	No links

Code	Description	Links
	<pre>{ "field": "content", "code": "invalid_value", "message": "can't be blank" }], }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	

GET

/trucks/{truck_id}/documents/{id}

Retrieve a truck document



Returns metadata for a single document attached to the truck. No file bytes — download is out of scope for v1.

Parameters

Cancel

Name	Description
truck_id * required integer (path)	truck_id
id * required integer (path)	id

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema	No links

Code	Description	Links
	<pre>{ "data": { "id": 0, "upload_name": "annual_inspection.pdf", "upload_type": "annual_inspection", "content_type": "application/pdf", "size_bytes": 24576, "created_at": "2026-07-09T11:12:27.591Z", "updated_at": "2026-07-09T11:12:27.591Z" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:27.591Z" } }</pre>	
401	Missing or invalid credentials. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema	No links

Code	Description	Links
	<pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	

Users

Users in the account, referenced by other resources via FKs (managers, sales reps, planners, etc.). MobileUser (driver mobile-app login) accounts are excluded: back-office staff appear here only when they have a User record — use `/employees` to resolve `capacity_manager_id` and similar.



GET

/users List users

^

Returns a paginated, sortable, filterable list of users scoped to the authenticated application's account. Excludes mobile-app driver login accounts (drivers themselves are on `/drivers`) (type `MobileUser`).

Use this endpoint to resolve user IDs that appear on other resources (e.g. `manager_id`, `substitute manager id` on drivers; `account manager id`, `customer service representative_id`, `billing specialist ids`, `detention specialist ids` on customers; `user_id`, `account_manager_id`, `csr manager id`, `planner_manager id` on loads). Back-office staff FKs (e.g. `capacity_manager_id`) resolve via `/employees`, not here.

Parameters

Cancel

Name	Description
id integer (query)	Bulk lookup. <code>?id[]=1&id[]=2</code> returns only users matching those IDs. id
page integer (query)	1
per_page integer (query)	25

Name	Description
sort string (query)	Sort field. Prefix with - for descending. --
type string (query)	Filter by user type. Multi-value supported. MobileUser is not a valid filter value. --
status string (query)	Filter by status. Multi-value supported. --

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": [{ "id": 1024, "name": "string", "lastname": "string", "type": "Dispatcher", "status": "active", "email": "string", "phone": "string", "office": "string", "team": "string", "created_at": "2026-07-09T11:12:27.629Z", "updated_at": "2026-07-09T11:12:27.629Z" }], "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:27.629Z", "page": 1, "per_page": 25, "total": 142 } }</pre>	No links

Code	Description	Links
400	Request was malformed or contained invalid parameters.	No links
Media type application/json Examples Unknown filter value (single error)		
Example Value Schema <pre>{ "data": null, "error": { "code": "invalid_filter", "message": "Invalid filter parameters", "details": [{ "field": "status", "code": "invalid_value", "message": "value 'banana' is not one of [booked, assigned, ...]" }] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>		
401	Missing or invalid credentials.	No links
Media type application/json		
Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" }}</pre>		
403	Your application does not have permission for this endpoint.	No links
Media type application/json		
Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d",</pre>		

Code	Description	Links
	<pre> "timestamp": "2026-04-14T12:00:00Z" } }</pre>	

GET

/users/{id} Retrieve a user



Parameters

Cancel

Name	Description
id * required integer (path)	id

Execute

Responses

Code	Description	Links
200	Successful response Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "id": 1024, "name": "string", "lastname": "string", "type": "Dispatcher", "status": "active", "email": "string", "phone": "string", "office": "string", "team": "string", "created_at": "2026-07-09T11:12:27.644Z", "updated_at": "2026-07-09T11:12:27.644Z" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:27.644Z" } }</pre>	

 No links || 401 | Missing or invalid credentials. | No links |

Code	Description	Links
	Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "unauthorized", "message": "Invalid credentials", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	
403	Your application does not have permission for this endpoint. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "forbidden", "message": "You do not have permission to access this endpoint", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links
404	The resource does not exist or is not accessible to this account. Media type application/json Example Value Schema <pre>{ "data": null, "error": { "code": "not_found", "message": "Resource not found", "details": [] }, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-04-14T12:00:00Z" } }</pre>	No links

Health

Service health check (unauthenticated).



GET

/health

Health check

^

Unauthenticated service health probe. Returns 200 when the API is reachable.

Parameters

Cancel

No parameters

Execute

Responses

Code	Description	Links
200	Service is healthy Media type application/json Controls Accept header. Example Value Schema <pre>{ "data": { "status": "ok" }, "error": null, "meta": { "request_id": "8f3a-c4e2-bb19-2f7d", "timestamp": "2026-07-09T11:12:27.650Z" }}</pre>	No links

Schemas

^

Load ^ Collapse all object

A shipment load with its destinations. Fields marked "grantable" require explicit grant from the Admin Panel; if not granted, they are omitted from the response.

Status workflow groups (canonical): the status enum has 19 values that move through a roughly linear workflow. For UI grouping, partners are encouraged to use the canonical buckets below to keep behavior consistent across integrations.

Group	Statuses
pre_dispatch	booked
assigned	assigned
in_transit	en route to shinner , at shinner , nicked_up , delayed , en_route_to consignee , at consignee
delivered	delivered , delivered_pending
needs_paperwork	missing_paperwork
billed	exported , billed_pending , billed , billed_pending_acc
closed	closed , open_balance
exception	canceled , tonu
id > Expand all integer status > Expand all string customer_load > Expand all string gp_load > Expand all string customer_id > Expand all integer customer_name > Expand all string user_id > Expand all integer account_manager_id > Expand all integer csr_manager_id > Expand all integer planner_manager_id > Expand all integer equipment > Expand all string commodity > Expand all string weight > Expand all string size > Expand all string temperature > Expand all string contract_spot > Expand all string hot > Expand all boolean high_value > Expand all boolean short_haul > Expand all boolean flatbed > Expand all boolean edi_load > Expand all boolean edi_accepted > Expand all boolean empty_miles_sum > Expand all string detention_sum > Expand all string first_pu_time_from > Expand all string date-time	

last_del_time_to > Expand all **string** **date-time**
created_at **string** **date-time**
updated_at **string** **date-time**
linehaul_rate > Expand all **string**
miles > Expand all **string**
total > Expand all **string**
fuel_surcharge > Expand all **string**
destinations > Expand all **array<object>**

Destination ^ Collapse all **object**

A single stop on a load. Fields marked "grantable" require explicit grant from the Admin Panel.

id **integer**
position > Expand all **integer**
stop_type > Expand all **string**
stop_company_name > Expand all **string**
address > Expand all **string**
city > Expand all **string**
state_code > Expand all **string**
zip_code > Expand all **string**
lat > Expand all **number**
lng > Expand all **number**
on_time > Expand all **boolean**
arrival_status > Expand all **string**
completed > Expand all **boolean**
load_id > Expand all **integer**
customer_id > Expand all **integer**
driver_id > Expand all **integer**
driver_assigned_by_id > Expand all **integer**
trailer_id > Expand all **integer**
app_date **string** **date**
time_from > Expand all **string** **date-time**
time_to > Expand all **string** **date-time**
time_in > Expand all **string** **date-time**
time_out > Expand all **string** **date-time**
driver_assigned_at > Expand all **string** **date-time**
created_at **string** **date-time**
updated_at **string** **date-time**

phone > Expand all string

Detention ^ Collapse all object

A detention event for a destination. `destination_id` is stored on the row; `load_id`, `driver_id`, and `customer_id` are derived from the parent destination (and load, for `customer_id`) — they're exposed and filterable so partners don't have to pre-resolve via `/destinations`.

id > Expand all integer

destination_id integer

load_id > Expand all integer

driver_id > Expand all integer

customer_id > Expand all integer

workflow_state > Expand all string

started_at > Expand all string date-time

ended_at > Expand all string date-time

created_at string date-time

updated_at string date-time

upcoming_started_at > Expand all string date-time

CustomerDetentionInfo ^ Collapse all object

Aggregated detention totals for one customer over a time window. Not paginated — one record per request. Counts and duration are always returned. Monetary totals are grant-gated.

customer_id > Expand all integer

from > Expand all string date-time

to > Expand all string date-time

detentions_count > Expand all integer

destinations_count > Expand all integer

duration_minutes > Expand all integer

estimated_amount > Expand all string

paid_out_amount > Expand all string

LoadNote ^ Collapse all object

A free-form note attached to a load. Created via the external API or internally via the admin UI. Partner-created notes have no author user.

id > Expand all integer

content > Expand all string

created_at string date-time

updated_at string date-time

DriverNote ^ Collapse all object

A free-form note attached to a driver. Same shape and authorship rules as LoadNote.

```
id integer

content > Expand all string

created_at string date-time

updated_at string date-time
```

DriverDocument ^ Collapse all object

A file attached to a driver's Files section. Stored in its original format; **content_type** and **size_bytes** reflect the file as received. The **upload_type** corresponds to the folder it appears in on the driver's Files tab.

```
id integer

upload_name > Expand all string

upload_type > Expand all string

content_type > Expand all string

size_bytes > Expand all integer

created_at string date-time

updated_at string date-time
```

CustomerDocument ^ Collapse all object

A file attached to a customer's Files section. Same shape as DriverDocument; **upload_type** is a year string corresponding to the customer's year-based Files-tab folders.

```
id integer

upload_name > Expand all string

upload_type > Expand all string

content_type > Expand all string

size_bytes > Expand all integer

created_at string date-time

updated_at string date-time
```

TruckDocument ^ Collapse all object

A file attached to a truck's Files section. Same shape as DriverDocument; **upload_type** corresponds to the truck's Files-tab folders (registration, inspection, title, etc.).

```
id integer

upload_name > Expand all string

upload_type > Expand all string

content_type > Expand all string

size_bytes > Expand all integer

created_at string date-time

updated_at string date-time
```

TrailerDocument ^ Collapse all object

A file attached to a trailer's Files section. Same shape as DriverDocument; **upload_type** corresponds to the trailer's Files-tab folders.

```
id integer
upload_name > Expand all string
upload_type > Expand all string
content_type > Expand all string
size_bytes > Expand all integer
created_at string date-time
updated_at string date-time
```

TruckNote ^ Collapse all object

A free-form note attached to a truck. Same shape and authorship rules as LoadNote.

```
id integer
content > Expand all string
created_at string date-time
updated_at string date-time
```

TrailerNote ^ Collapse all object

A free-form note attached to a trailer. Same shape and authorship rules as LoadNote.

```
id integer
content > Expand all string
created_at string date-time
updated_at string date-time
```

Driver ^ Collapse all object

A driver record. Fields marked "grantable" require explicit grant from the Admin Panel — sensitive data (SSN, DOB, home address, license details) is hidden by default.

Security note for **soc_sec_no (driver SSN).** This is the most sensitive field on the API surface. The grant is reviewed individually — most integrations should not request it. Partners that do receive the grant take on additional handling obligations: PCI/PII storage standards, access logging, and (in many jurisdictions) breach notification responsibilities. Request only if your integration has a genuine, documented need.

```
id > Expand all integer
first_name > Expand all string
last_name > Expand all string
middle_name > Expand all string
driver_nr > Expand all string
status > Expand all string
driver_type > Expand all string
tax_type > Expand all string
fleet_group > Expand all string
```

manager_id > Expand all **integer**

substitute_manager_id > Expand all **integer**

compensation_id > Expand all **integer**

payroll_schedule_id > Expand all **integer**

phone > Expand all **string**

email > Expand all **string**

cdl > Expand all **string**

cdl_state > Expand all **string**

address > Expand all **string**

city > Expand all **string**

state_code > Expand all **string**

zipcode > Expand all **string**

dob > Expand all **string** **date**

cdl_expire_date > Expand all **string** **date**

soc_sec_no > Expand all **string**

date_added > Expand all **string** **date**

date_removed > Expand all **string** **date**

created_at **string** **date-time**

updated_at **string** **date-time**

Truck ^ Collapse all **object**

A truck in the fleet. Fields marked "grantable" require explicit grant from the Admin Panel.

id > Expand all **integer**

unit > Expand all **string**

status > Expand all **string**

make > Expand all **string**

model > Expand all **string**

year > Expand all **integer**

color > Expand all **string**

vin > Expand all **string**

license_plate > Expand all **string**

state_code > Expand all **string**

ownership_type > Expand all **string**

oos > Expand all **boolean**

needs_repair > Expand all **boolean**

slip_seating > Expand all **boolean**

irp > Expand all **boolean**

lease > Expand all **boolean**

samsara_dev_id > Expand all **string**
annual_inspection_date > Expand all **string** **date**
irp_expiration_date > Expand all **string** **date**
ins_expiration_date > Expand all **string** **date**
insured_value > Expand all **string**
acquisition_date > Expand all **string** **date-time**
oos_note > Expand all **string**
needs_repair_note > Expand all **string**
irp_add_date > Expand all **string** **date**
irp_remove_date > Expand all **string** **date**
quarterly_maintenance_date > Expand all **string** **date**
monthly_insurance_cost > Expand all **string**
total_insurance_cost > Expand all **string**
cost > Expand all **string**
monthly_payment > Expand all **string**
interest > Expand all **string**
created_at **string** **date-time**
updated_at **string** **date-time**

Trailer > Expand all **object**

Assignment ^ Collapse all **object**

A current driver-to-truck or driver-to-trailer assignment. **assignment_type** is either **Truck** or **Trailer** , and **assignment_id** points to the corresponding resource.

The **driver** and **assignment** properties carry minimal embedded summaries so consumers can render "who's driving what" in a single request. Summaries are fixed shape — sensitive fields (SSN, DOB, phone, VIN, license plate) never appear here regardless of per-app grants.

id > Expand all **integer**
driver_id > Expand all **integer**
assignment_id > Expand all **integer**
assignment_type > Expand all **string**
start_date **string** **date-time**
end_date > Expand all **string** **date-time**
created_at **string** **date-time**
updated_at **string** **date-time**
driver > Expand all **object**
assignment > Expand all **object**

DriverSummary ^ Collapse all **object**

Minimal embedded driver projection. Fixed shape — no field grants apply; sensitive fields (SSN, DOB, phone, email, CDL, address) never appear here. Use [GET /drivers/:id](#) for full detail when needed.

id > Expand all **integer**

first_name > Expand all **string**

last_name > Expand all **string**

driver_nr > Expand all **string**

status > Expand all **string**

TruckSummary ^ Collapse all **object**

Minimal embedded truck projection. Fixed shape — [vin](#) , [license_plate](#) , inspection dates, and insurance details never appear here. Use [GET /trucks/:id](#) for full detail.

id > Expand all **integer**

unit > Expand all **string**

year > Expand all **integer**

make > Expand all **string**

model > Expand all **string**

TrailerSummary ^ Collapse all **object**

Minimal embedded trailer projection. Fixed shape — [vin](#) , [license_plate](#) , and inspection dates never appear here. Use [GET /trailers/:id](#) for full detail.

id > Expand all **integer**

trailer_id > Expand all **string**

year > Expand all **integer**

make > Expand all **string**

model > Expand all **string**

length > Expand all **integer**

AvailabilityEvent ^ Collapse all **object**

A single availability window for a driver. Status indicates the kind of window: [loaded](#) (on a load), [off_duty](#) (resting/HOS), [planned](#) (scheduled time off), [pending_hometime](#) .

id > Expand all **integer**

driver_id > Expand all **integer**

status > Expand all **string**

start_date **string** **date-time**

end_date **string** **date-time**

created_at **string** **date-time**

updated_at **string** **date-time**

off_duty_reason > Expand all **string**

User ^ Collapse all **object**

A user in the account referenced by other resources via FKs (**manager_id** and **substitute manager id** on drivers: **account manager id** , **customer service representative_id** , **billing specialist_ids** and **detention specialist ids** on customers: **user_id** (creator/sales rep), **account_manager_id** , **csr_manager_id** , **planner_manager_id** on loads). MobileUser (driver mobile-app login) accounts are excluded: back-office staff appear here only when they have a User record — use **/employees** to resolve **capacity_manager_id** and similar. Sensitive contact fields require explicit grants.

id > Expand all **integer**

name > Expand all **string**

lastname > Expand all **string**

type > Expand all **string**

status > Expand all **string**

email > Expand all **string**

phone > Expand all **string**

office > Expand all **string**

team > Expand all **string**

created_at **string** **date-time**

updated_at **string** **date-time**

Customer ^ Collapse all **object**

A customer (shipper, broker, or 3PL) booked on loads. Sensitive contact, manager, and financial fields require explicit grants. Internal operational flags (**critical_customer** , **not_scheduled_loads** , **protect_from_freeze** , default-load-type config, EFS usernames, fuel-account routing) are never exposed via this API regardless of grants. External system IDs (**macropoint_id** , **apex_broker_id** , **tmw_id**) ARE available with field grants for partners that need to map records back to their own systems.

Freshness note for credit fields. **open_balance** , **available_balance** , and **available_balance_limit** reflect the state of accounting at the moment the request was processed. Reads can lag writes by a few seconds (read-replica propagation). For workflows where stale credit data has real cost — e.g. a credit check before booking a load — re-fetch immediately before the check rather than relying on cached values.

id > Expand all **integer**

name **string**

dba > Expand all **string**

mc > Expand all **string**

status > Expand all **string**

customer_type > Expand all **string**

tier > Expand all **string**

macropoint_integration > Expand all **boolean**

ryder_integration > Expand all **boolean**

four_kites_integration > Expand all **boolean**

fourkites_epod > Expand all **boolean**

load_status_notification_email > Expand all **boolean**

created_at **string** **date-time**

`updated_at` **string** `date-time`

`phone` > Expand all **string**

`email` > Expand all **string**

`fax` > Expand all **string**

`contact` > Expand all **string**

`extra_contact` > Expand all **string**

`extra_phone` > Expand all **string**

`street` > Expand all **string**

`street_second` > Expand all **string**

`city` > Expand all **string**

`state_code` > Expand all **string**

`zipcode` > Expand all **string**

`ap_contact` > Expand all **string**

`ap_phone` > Expand all **string**

`ap_fax` > Expand all **string**

`ap_email` > Expand all **array<string>**

`bol_notification_emails` > Expand all **array<string>**

`load_status_notification_email_value` > Expand all **array<string>**

`contracted_loads_info_email` > Expand all **string**

`account_manager_id` > Expand all **integer**

`customer_service_representative_id` > Expand all **integer**

`capacity_manager_id` > Expand all **integer**

`billing_specialist_ids` > Expand all **array<integer>**

`detention_specialist_ids` > Expand all **array<integer>**

`billing_preference` > Expand all **string**

`payment_terms` > Expand all **string**

`ar_type` > Expand all **string**

`billing_setting_id` > Expand all **integer**

`sage_id` > Expand all **integer**

`custom_billing` > Expand all **boolean**

`open_balance` > Expand all **string**

`available_balance` > Expand all **string**

`available_balance_limit` > Expand all **string**

`credit_hold` > Expand all **boolean**

`contract_start_date` > Expand all **string** `date-time`

`contract_end_date` > Expand all **string** `date-time`

`procedures` > Expand all **string**

`macropoint_id` > Expand all **string**

apex_broker_id > Expand all **string**

tmw_id > Expand all **string**

Employee ^ Collapse all **object**

A back-office staff member referenced by FKs (e.g. **capacity_manager_id** on Customer). The schema below is the security boundary — fields not listed here (SSN, DOB, banking, emergency contacts, compensation, etc.) are NEVER exposed via this API regardless of grants.

id > Expand all **integer**

first_name **string**

last_name > Expand all **string**

position > Expand all **string**

status > Expand all **string**

office > Expand all **string**

department > Expand all **string**

user_id > Expand all **integer**

created_at **string** **date-time**

updated_at **string** **date-time**

email > Expand all **string**

phone > Expand all **string**

work_extension > Expand all **string**

work_phone > Expand all **string**

employment_date > Expand all **string** **date**

termination_date > Expand all **string** **date**

BillingSetting ^ Collapse all **object**

A billing profile template referenced by customers via **billing_setting_id** . Internal template configuration (logo, address, signature) lives in non-exposed fields.

id > Expand all **integer**

profile_name > Expand all **string**

default > Expand all **boolean**

created_at **string** **date-time**

updated_at **string** **date-time**

PayrollSchedule ^ Collapse all **object**

A pay-cadence definition. Small set per account; reference data partners typically fetch once and cache. No grantable fields — whole record is non-PII.

id > Expand all **integer**

name > Expand all **string**

frequency > Expand all **string**

start_day > Expand all **integer**

`days_to_pay` > Expand all `integer`

`created_at` `string` `date-time`

`updated_at` `string` `date-time`

EliteScore Collapse all `object`

A driver performance score snapshot covering one date range. The headline `score` is always exposed; component sub-scores (idle, route+fuel, mpg, on-time, etc.) are extracted from the snapshot's underlying components and require explicit grants per component.

`id` > Expand all `integer`

`driver_id` > Expand all `integer`

`score` > Expand all `string`

`period_start` `string` `date-time`

`period_end` `string` `date-time`

`created_at` `string` `date-time`

`updated_at` `string` `date-time`

`idelic_score` > Expand all `number`

`home_time_score` > Expand all `number`

`mpg_score` > Expand all `number`

`route_and_fuel_score` > Expand all `number`

`idle_score` > Expand all `number`

`on_time_score` > Expand all `number`

Compensation Collapse all `object`

Driver pay structure (Per Mile, Percentage, or Flat). The `/compensations` endpoint requires explicit grant — without it the request returns 403. Once granted, only `id`, `name`, `status` are visible by default; rate, percentage, flat, and bonus fields require additional field grants on top of the endpoint grant.

`id` > Expand all `integer`

`name` > Expand all `string`

`status` > Expand all `string`

`created_at` `string` `date-time`

`updated_at` `string` `date-time`

`loaded_mile_rate` > Expand all `string`

`empty_mile_rate` > Expand all `string`

`banded` > Expand all `boolean`

`linehaul_percentage` > Expand all `string`

`fuel_surcharge_percentage` > Expand all `string`

`flat_status` > Expand all `string`

`flat_rate` > Expand all `string`

`seniority_bonus_enabled` > Expand all `boolean`

`seniority_bonus_cents_per_mile_per_year` > Expand all `string`

seniority_bonus_excluded_event_reasons > Expand all **array<string>**

Meta > Expand all **object**

PaginationMeta > Expand all **object**

Error ^ Collapse all **object**

code* > Expand all **string**

message* > Expand all **string**

details* > Expand all **array<object>**

ErrorDetail ^ Collapse all **object**

field* > Expand all **string**

code* > Expand all **string**

message* > Expand all **string**

ErrorResponse ^ Collapse all **object**

Failure response. **data** is null; **error** and **meta** are populated.

data ^ Collapse all **null**

Always null on error responses.

Example=null

error ^ Collapse all **object**

code* ^ Collapse all **string**

Machine-readable top-level error code

Enum ^ Collapse all **array**

#0="unauthorized"

#1="forbidden"

#2="not_found"

#3="bad_request"

#4="invalid_filter"

#5="invalid_sort"

#6="validation_error"

#7="rate_limited"

#8="internal_error"

Example="invalid_filter"

message* ^ Collapse all **string**

Short human-readable summary. For per-field detail, see **details**.

Example="Invalid filter parameters"

details* ^ Collapse all **array<object>**

Per-field error entries. Empty for errors without field context (auth, not-found, server-side).

Items ^ Collapse all **object**

field* ^ Collapse all **string**

The parameter or attribute that triggered this error

Example="status"

code* ^ Collapse all **string**

Machine-readable per-field error code

Enum ^ Collapse all **array**

#0="unknown_field"

#1="invalid_value"

#2="unsupported_op"

#3="invalid_operator"

#4="missing_parameter"

#5="too_many_values"

Example="invalid_value"

message* ^ Collapse all **string**

Human-readable description of this specific field error

Example="value 'banana' is not one of [booked, assigned, ...]"

meta ^ Collapse all **object**

request_id* ^ Collapse all **string**

Unique identifier for this request. Include in support inquiries.

Example="8f3a-c4e2-bb19-2f7d"

timestamp* ^ Collapse all **string** **date-time**

Server timestamp (UTC)