

*\* Note: Health variables (*RXattempts*, *changeRouterAttempts*) are completely reset whenever a successful response is received from the router.*

**Node (Mota)**  
Client

**Default Router**  
Coordinator

Wakes up.  
*RXattempts* = 3  
*changeRouterAttempts* = 7  
Sends DATA...

DATA (0x20)

**Router Offline / Power Loss**  
(No Response)

**Watchdog Timeout** (*RX\_TIMEOUT.VALUE*)  
*RXattempts*-- → 2  
*changeRouterAttempts*-- → 6

Retry DATA Transmission...

If *RXattempts* ≤ 0:  
Goes to **Deep Sleep** until next interval

(... Subsequent wake-ups ...)  
Router continues offline

**Watchdog Timeout**  
*changeRouterAttempts* drops to 0

**ALT: Terminal Network Failure** (*changeRouterAttempts* ≤ 0)

**IF** *allowPublicConn* == 1

**STATE\_START\_SCAN**  
Automatically scans for strongest public Router

Connects to Public Router  
Sends Join, then Data  
(Autonomous Fault Tolerance)

**ELSE** (*allowPublicConn* == 0)

No permission to switch networks.  
State = **STATE\_SLEEP** (Deep Sleep)  
Wait for default router to recover.