

Exercise I – Markdown HTML

LAB University of Applied Sciences

Bachelor of engineering: industrial Information Technology

2027

Davin Pihaljasaari

1 Markdown

[Attendance Checker]

An attendance checker for educators and bosses the world over.

Features

- Feature 1: Checks attendance based on barcode on the back of student cards.
- Feature 2: saves each classes attendance separately.
- Coming Soon: Better UI.

Tech Stack

Component	Tool	Version
Frontend	GTK	3.24.51
Backend	C	C23
Datastorage	CSV	
Styling	GTK	3.24.51

Installation

To get the app running locally, follow these steps:

1. Clone the .exe file attendance_v0.9_boxed.exe
2. Create folder
3. place .exe file in folder
4. Run the app

Usage

To help a manager or teacher keep attendance. Just use a barcode or other scanner that outputs a unique string and it will hash that as a ID for that persons card.

Developers

| Creator | Davin Pihlajasaari | | Maintainer | Davin Pihlajasaari |

2 HTML

[Attendance Checker]

An attendance checker for educators and bosses the world over.

Features

- **Feature 1:** Checks attendance based on barcode on the back of student cards.
- **Feature 2:** saves each classes attendance separately.
- **Coming Soon:** Better UI.

Tech Stack

Component	Tool	Version
Frontend	GTK	3.24.51
Backend	C	C23
Datastorage	CSV	
Styling	GTK	3.24.51

Installation

To get the app running locally, follow these steps:

1. **Clone the .exe file** attendance_v0.9_boxed.exe
2. **Create folder**
3. **place .exe file in folder**
4. **Run the app**

Usage

To help a manager or teacher keep attendance. Just use a barcode or other scanner that outputs a unique string and it will hash that as a ID for that persons card.

Developers

Position	Developer
Creator	Davin Pihlajasaari
Maintainer	Davin Pihlajasaari

3 HTML v2

[Attendance Checker]

An attendance checker for educators and bosses the world over.

Features

- **Feature 1:** Checks attendance based on barcode on the back of student cards.
- **Feature 2:** saves each classes attendance separately.
- **Coming Soon:** Better UI.

Tech Stack

Component	Tool	Version
-----------	------	---------

Frontend	GTK	3.24.51
----------	-----	---------

Backend	C	C23
---------	---	-----

Datastorage	CSV	
-------------	-----	--

Styling	GTK	3.24.51
---------	-----	---------

Installation

To get the app running locally, follow these steps:

1. **Clone the .exe file** attendance_v0.9_boxed.exe
2. **Create folder**
3. **place .exe file in folder**
4. **Run the app**

Usage

To help a manager or teacher keep attendance. Just use a barcode or other scanner that outputs a unique string and it will hash that as a ID for that persons card.

Developers

Position	Developer
----------	-----------

Creator	Davin Pihlajasaari
---------	--------------------

Maintainer	Davin Pihlajasaari
------------	--------------------

4 Markdown raw

```
# [Attendance Checker]

> An attendance checker for educators and bosses the world over.

---

## Features
* Feature 1: Checks attendance based on barcode on the back of student cards.
* Feature 2: saves each classes attendance separately.
* Coming Soon: Better UI.

## Tech Stack

| Component | Tool | Version |
| :--- | :--- | :--- |
| Frontend | GTK | 3.24.51 |
| Backend | C | C23 |
| Datastorage | CSV | |
| Styling | GTK | 3.24.51 |

## Installation

To get the app running locally, follow these steps:

1. Clone the .exe file
   attendance_v0.9_boxed.exe
2. Create folder
3. place .exe file in folder
4. Run the app

## Usage

To help a manager or teacher keep attendance.
Just use a barcode or other scanner that outputs a unique string and it will hash that as a ID for that persons card.

## Developers

| Position | Developer |
| :--- | :--- | :--- |
| Creator | Davin Pihlajasaari |
| Maintainer | Davin Pihlajasaari |
```

5 Markdown explanation

`##` - makes text into a heading

`>` - makes text into a subheading with greying

`*` - makes bullet points

`**` - makes bold text

`|||` - makes text with spacing to work in a table

`| :--- | :--- | :--- |` - makes a table

5.1 HTML rendering issues

The subheading was not rendered properly on both versions of the html that were rendered with different viewers, with one just making it smaller text and the other making it a dark bar on the page. The tables did not render their borders but were still formatted correctly. The general structure was preserved.

6 HTML raw

```
<h1 id="-attendance-checker-">[Attendance Checker]</h1>
<blockquote>
<p>An attendance checker for educators and bosses the world over.</p>
</blockquote>
<hr>
<h2 id="features">Features</h2>
<ul>
<li><strong>Feature 1</strong>: Checks attendance based on barcode on the
back of student cards.</li>
<li><strong>Feature 2</strong>: saves each classes attendance
separately.</li>
<li><strong>Coming Soon</strong>: Better UI.</li>
</ul>
<h2 id="tech-stack">Tech Stack</h2>
<table>
<thead>
<tr>
<th style="text-align:left">Component</th>
<th style="text-align:left">Tool</th>
<th style="text-align:left">Version</th>
</tr>
</thead>
<tbody>
<tr>
<td style="text-align:left"><strong>Frontend</strong></td>
<td style="text-align:left">GTK</td>
<td style="text-align:left">3.24.51</td>
</tr>
<tr>
<td style="text-align:left"><strong>Backend</strong></td>
<td style="text-align:left">C</td>
<td style="text-align:left">C23</td>
</tr>
<tr>
<td style="text-align:left"><strong>Datastorage</strong></td>
<td style="text-align:left">CSV</td>
<td style="text-align:left"></td>
</tr>
<tr>
<td style="text-align:left"><strong>Styling</strong></td>
<td style="text-align:left">GTK</td>
<td style="text-align:left">3.24.51</td>
</tr>
</tbody>
</table>
<h2 id="installation">Installation</h2>
```

```

<p>To get the app running locally, follow these steps:</p>
<ol>
<li><strong>Clone the .exe file</strong>
attendance_v0.9_boxed.exe</li>
<li><strong>Create folder</strong></li>
<li><strong>place .exe file in folder</strong></li>
<li><strong>Run the app</strong></li>
</ol>
<h2 id="usage">Usage</h2>
<p>To help a manager or teacher keep attendance.
Just use a barcode or other scanner that outputs a unique string and it will
hash that as a ID for that persons card.</p>
<h2 id="developers">Developers</h2>
<table>
<thead>
<tr>
<th style="text-align:left">Position</th>
<th style="text-align:left">Developer</th>
</tr>
</thead>
<tbody>
<tr>
<td style="text-align:left">Creator</td>
<td style="text-align:left">Davin Pihlajasaari</td>
</tr>
<tr>
<td style="text-align:left">Maintainer</td>
<td style="text-align:left">Davin Pihlajasaari</td>
</tr>
</tbody>
</table>

```