

Lecture #6: Abstraction and Objects

Last modified: Fri Mar 2 00:43:45 2012

CS61A: Lecture #6 1

Pig Contest Rules

- The score for an entry is the sum of win rates against every other entry.
- All strategies must be deterministic functions of the current score! Non-deterministic strategies will be disqualified.
- Winner: 3 points extra credit on Project 1
- Second place: 2 points
- Third place: 1 point
- The real prize: honor and glory
- To enter: submit a file `pig.py` that contains a function called `final_strategy` via the command `submit proj1-contest` by Monday, 2/13.

Last modified: Fri Mar 2 00:43:45 2012

CS61A: Lecture #6 2

Decorators: Pythonic Use of Higher-Order Functions

- The syntax

```
@expr
def func(expr):
    body
```

is equivalent to

```
def func(expr):
    body
func = expr(func)
```
- For example, our `ucb` module defines decorator `trace`. After

```
from ucb import trace
@trace
def mysum(x, y):
    return x + y
```

`mysum` will print its arguments and return value each time it is called.
- Usually, `expr` is a simple name, but it can be any expression that takes and returns a function.

Last modified: Fri Mar 2 00:43:45 2012

CS61A: Lecture #6 3

Functional Abstraction

Consider two implementations of polynomial evaluation:

```
def quadratic_val(a, b, c, x):
    """The value of A*X**2+B*X+C."""
    return a*x**2 + b*x + c
```

```
def quadratic_val(a, b, c, x):
    """The value of A*X**2+B*X+C."""
    return c + x*(b + x*a)
```

- Both have the same name, signature, and (for integers) values.
- To use them, that's all we need—the implementations are irrelevant.
- There is a *separation of concerns* here:
 - The caller (client) is concerned with providing values of `x`, `a`, `b`, and `c` and using the result, but *not* how the result is computed.
 - The implementor is concerned with how the result is computed, but not where `x`, `a`, `b`, and `c` come from or how the value is used.
 - From the client's point of view, `quadratic_val` is an *abstraction* from the set of possible ways to compute this result.
 - We call this particular kind *functional abstraction*.
- Programming is largely about choosing abstractions that lead to clear, fast, and maintainable programs.

Last modified: Fri Mar 2 00:43:45 2012

CS61A: Lecture #6 4

Guidelines for Defining Functions (I)

- Each function should have exactly one, logically coherent and well defined job.
 - Intellectual manageability.
 - Ease of testing.
- Functions should be properly documented, either by having names (and parameter names) that are unambiguously understandable, or by having comments (docstrings in Python) that accurately describe them.
 - Should be able to understand code that calls a function without reading the body of the function.
- Don't Repeat Yourself (*DRY*).
 - Simplifies revisions.
 - Isolates problems.

Last modified: Fri Mar 2 00:43:45 2012

CS61A: Lecture #6 5

Guidelines for Defining Functions (II)

- Corollary of DRY: Make functions general
 - copy-paste leads to maintenance headaches
- Keep names of functions and parameters meaningful:

Instead of	Use
boolean	<code>turn_is_over</code>
<code>d</code>	<code>dice</code>
helper	<code>take_turn</code>
(Bowling example From Kernighan&Plauger):	
<code>y</code>	<code>score</code>
<code>L</code>	<code>ball</code>
<code>f</code>	<code>frame</code>

Last modified: Fri Mar 2 00:43:45 2012

CS61A: Lecture #6 6

Data Abstraction

- Functions are abstractions that represents computations and actions.
- In the old days, one described programs as hierarchies of actions: *procedural decomposition*.
- Starting in the 1970's, emphasis moved to the data that the functions operate on.
- An *abstract data type* represents some kind of thing and the operations upon it.
- We can usefully organize our programs around the abstract data types in them.
- We could just organize our documentation into sections describing the abstract data types we conceptually use,
- But modern programming languages tend to have specific features and syntax for this purpose: *object-oriented programming*.

Last modified: Fri Mar 2 00:43:45 2012

CS61A: Lecture #6 7

Objects in Python

- In Python 3, every value is an object.
- Varieties of object correspond (roughly) to *classes (types)*.
- Each object has some set of *attributes*, accessible using dot notation, which are values:
 - *E.Attr*, where *E* is a simple expression and *Attr* is a name, means "the current value of the *Attr* attribute of the value of *E*."
- Among these attributes are those whose values are a kind of function known as a *method*.
- For historical reasons or convenience, there are often alternative ways to access attributes than dot notation:

<code>x.__add__(y)</code>	<code>add(x, y) or x+y</code>
<code>L.__getitem__(k)</code>	<code>L[k]</code>
<code>x.__len__()</code>	<code>len(x)</code>
<code>x.__eq__(y)</code>	<code>x == y</code>

Last modified: Fri Mar 2 00:43:45 2012

CS61A: Lecture #6 8

Primitive Types: Numbers

- A *primitive type* is one that is built into a language, possibly with characteristics or syntax that cannot be written into user-defined types.
- In Python, numbers are such types: have their own literals and internal attributes that are not accessible to the programmer.
- Python distinguishes four types:
 - *int*: Integers.
 - *bool*: Limited integers restricted to values that denote true and false.
 - *float*: A subset of the rational numbers used to approximate real-valued quantities.
 - *complex*: A subset of the rational complex numbers used to approximate complex-valued quantities.
- Let's look briefly at one of them: float.

Last modified: Fri Mar 2 00:43:45 2012

CS61A: Lecture #6 9


Floating-point

- It would be nice if we could represent general real arithmetic efficiently, but we can't.
- Even if we restrict ourselves to the rationals, simple computations can become quite slow (denominators can grow exponentially).
- Since we don't usually need absolute accuracy, floating-point was devised as a compromise.
- Typically, (i.e., according to the IEEE Floating-point standard, to which Berkeley faculty (Prof. Kahan) made major contributions), the floating-point numbers are the set
$$\{\pm s \cdot 2^e \mid 0 \leq s < 2^{53}, -1023 \leq e + 53 \leq 1024\} \cup \{\pm\infty, -0, \dots\}$$
allowing us to represent numbers with maximum magnitude up to 2^{1024} and non-zero magnitudes as small as 2^{-1074} .
- *s* is the *significand*, *e* is the *exponent*.

Last modified: Fri Mar 2 00:43:45 2012

CS61A: Lecture #6 10

Floating-point Approximation Visualized

- To make things manageable, suppose we restrict *s* to the range 0-3, and *e* to the range -3 to 1
- Then the set of positive floating-point numbers would look like this on a number line:
- Numbers get farther apart for larger magnitudes.
- Arithmetic results on these numbers that fall between the represented numbers are *rounded* to a represented number. (Therein lies much confusion.)
- Although this means that the approximation error increases for larger numbers, the *relative error*—ratio of the error in an approximated number to the magnitude of the number—does not, which is the reason for choosing the floating-point representation.
- Also means that the number of *significant digits* (more precisely, significant bits) remains about the same.

Last modified: Fri Mar 2 00:43:45 2012

CS61A: Lecture #6 11