


Lecture #20: Recursive Processes, Memoization, Tree Structures

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 1

Example: Escape from a Maze

- Consider a rectangular maze consisting of an array of squares some of which are occupied by large blocks of concrete:



- Given the size of the maze and locations of the blocks, prisoner, and exit, how does the prisoner escape?

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 2

Maze Program (Incorrect)

```
def solve_maze(row0, col0, maze):
    """Assume that MAZE is a rectangular 2D array (list of lists) where
    maze[r][c] is true iff there is a concrete block occupying
    column c of row r. ROW0 and COL0 are the initial row and column
    of the prisoner. Returns true iff there is a path of empty
    squares that are horizontally or vertically adjacent to each other
    starting with (ROW0, COL0) and ending outside the maze."""
    if row0 not in range(len(maze)) or col0 not in range(len(maze[row])):
        return True
    elif maze[row0][col0]: # In wall
        return False
    else:
        return solve_maze(row0+1, col0, maze) or solve_maze(row0-1, col0, maze) \
            or solve_maze(row0, col0+1, maze) or solve_maze(row0, col0-1, maze) \
    # What's wrong?
```

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 3

Maze Program (Corrected)

To fix the problem, remember where we've been:

```
def solve_maze(row0, col0, maze):
    """Assume that MAZE is a rectangular 2D array (list of lists) where
    maze[r][c] is true iff there is a concrete block occupying
    column c of row r. ROW0 and COL0 are the initial row and column
    of the prisoner. Returns true iff there is a path of empty
    squares that are horizontally or vertically adjacent to each other
    starting with (ROW0, COL0) and ending outside the maze."""
    visited = set() # Set of visited cells
    cols, rows = range(len(maze[0])), range(len(maze))
    def escapep(r, c):
        """True iff is a path of empty, unvisited cells from (R, C) out of maze."""
        if r not in rows or c not in cols:
            return True
        elif maze[r][c] or (r, c) in visited:
            return False
        else:
            visited.add((r,c))
            return escapep(r+1, c) or escapep(r-1, c) \
                or escapep(r, c+1) or escapep(r, c-1)
    return escapep(row0, col0)
```

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 4

Example: Making Change

```
def count_change(amount, denoms = (50, 25, 10, 5, 1)):
    """The number of ways to change AMOUNT cents given the
    denominations of coins and bills in DENOMS.
    >>> # 9 cents = 1 nickel and 4 pennies, or 9 pennies
    >>> count_change(9)
    2
    >>> # 12 cents = 1 dime and 2 pennies, 2 nickels and 2 pennies,
    >>> # 1 nickel and 7 pennies, or 12 pennies
    >>> count_change(12)
    4
    """
    if amount == 0: return 1
    elif len(denoms) == 0: return 0
    elif amount >= denoms[0]:
        return count_change(amount-denoms[0], denoms) \
            + count_change(amount, denoms[1:])
    else:
        return count_change(amount, denoms[1:])
```

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 5

Avoiding Redundant Computation

- In the (tree-recursive) maze example, a naive search could take us in circles, resulting in infinite time.
- Hence the `visited` set in the `escapep` function.
- This set is intended to catch redundant computation, in which re-processing certain arguments cannot produce anything new.
- We can apply this idea to cases of finite but redundant computation.
- For example, in `count_change`, we often revisit the same subproblem:
 - E.g., Consider making change for 87 cents.
 - When choose to use one half-dollar piece, we have the same subproblem as when we choose to use no half-dollars and two quarters.
- Saw an approach in Lecture #16: memoization.

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 6

Memoizing

- Idea is to keep around a table ("memo table") of previously computed values.
- Consult the table before using the full computation.
- Example: `count_change`:

```
def count_change(amount, denoms = (50, 25, 10, 5, 1)):
    memo_table = {} # Indexed by pairs (row, column)
    # Local definition hides outer one so we can cut-and-paste
    # from the unmemoized solution.
    def count_change(amount, denoms):
        if (amount, denoms) not in memo_table:
            memo_table[(amount, denoms)] = \
                full_count_change(amount, denoms)
        return memo_table[(amount, denoms)]
    def full_count_change(amount, denoms):
        unmemoized original solution goes here verbatim
    return count_change(amount, denoms)
```

- Question: how could we test for infinite recursion?

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 7

Optimizing Memoization

- Used a dictionary to memoize `count_change`, which is highly general, but can be relatively slow.
- More often, we use arrays indexed by integers (lists in Python), but the idea is the same.
- For example, in the `count_change` program, we can index by `amount` and by the portion of `denoms` that we use, which is always a slice that runs to the end.

```
def count_change(amount, denoms = (50, 25, 10, 5, 1)):
    # memo_table[amt][k] contains the value computed for
    # count_change(amt, denoms[k:])
    memo_table = [ [-1] * (len(denoms)+1) for i in range(amount+1) ]
    def count_change(amount, denoms):
        if memo_table[amount][len(denoms)] == -1:
            memo_table[amount][len(denoms)] = \
                full_count_change(amount, denoms)
        return memo_table[amount][len(denoms)]
    ...
```

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 8

Order of Calls

- Going one step further, we can analyze the order in which our program ends up filling in the table.
- So consider adding some tracing to our memoized `count_change` program:

```
memo_table = {}
def count_change(amount, denoms):
    ... full_count_change(amount, denoms) ...
    return memo_table[(amount, denoms)]
@trace
def full_count_change(amount, denoms):
    if amount == 0: return 1
    elif not denoms: return 0
    elif amount >= denoms[0]:
        return count_change(amount, denoms[1:]) \
            + count_change(amount-denoms[0], denoms)
    else:
        return count_change(amount, denoms[1:])
    return count_change(amount, denoms)
```

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 9

Result of Tracing

- Consider `count_change(57)` (returns only):

```
full_count_change(57, ()) -> 0
full_count_change(56, ()) -> 0
...
full_count_change(1, ()) -> 0
full_count_change(0, (1,)) -> 1
full_count_change(1, (1,)) -> 1
...
full_count_change(57, (1,)) -> 1
full_count_change(2, (5, 1,)) -> 1
full_count_change(7, (5, 1,)) -> 2
...
full_count_change(57, (5, 1,)) -> 12
full_count_change(7, (10, 5, 1,)) -> 2
full_count_change(17, (10, 5, 1,)) -> 6
...
full_count_change(32, (10, 5, 1,)) -> 16
full_count_change(7, (25, 10, 5, 1,)) -> 2
full_count_change(32, (25, 10, 5, 1,)) -> 18
full_count_change(57, (25, 10, 5, 1,)) -> 60
full_count_change(7, (50, 25, 10, 5, 1,)) -> 2
full_count_change(57, (50, 25, 10, 5, 1,)) -> 62
```

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 10

Dynamic Programming

- Now rewrite `count_change` to make the order of calls explicit, so that we needn't check to see if a value is memoized.
- Technique is called *dynamic programming* (for some reason).
- We start with the base cases, and work backwards.

```
def count_change(amount, denoms = (50, 25, 10, 5, 1)):
    memo_table = [ [-1] * (len(denoms)+1) for i in range(amount+1) ]
    def count_change(amount, denoms):
        return memo_table[amount][len(denoms)]
    def full_count_change(amount, denoms):
        # How often is this called?
        ... # (calls count_change for recursive results)

    for a in range(0, amount+1):
        memo_table[a][0] = full_count_change(a, ())
    for k in range(1, len(denoms) + 1):
        for a in range(1, amount+1):
            memo_table[a][k] = full_count_change(a, denoms[-k:])
    return count_change(amount, denoms)
```

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 11

New Topic: Tree-Structured Data


- 1 Linear-recursive and tail-recursive functions make a single recursive call in the function body. Tree-recursive functions can make more.
- Linear recursive data structures (think rlists) have single embedded recursive references to data of the same type, and usually correspond to linear- or tail-recursive programs.
- To model some things, we need multiple recursive references in objects.
- In the absence of circularity (paths from an object eventually leading back to it), such objects form data structures called *trees*:
 - The objects themselves are called *nodes* or *vertices*.
 - Tree objects that have no (non-null) pointers to other tree objects are called *leaves*.
 - Those that do have such pointers are called *inner nodes*, and the objects they point to are *children* (or *subtrees* or (uncommonly) *branches*).
 - A collection of disjoint trees is called a *forest*.

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 12

Example: Expressions

- An expression (in Python or other languages) typically has a recursive structure. It is either
 - A literal (like 5) or symbol (like x)—a leaf—or
 - A compound expression consisting of an operator and zero or more operands, each of which is itself an expression.
- For example, the expression $x + (y+2)*(z+10)$ can be thought of as a tree (what happened to the parentheses?):




Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 13

Expressions as Tuples or Lists

- We can represent the abstract structure of the last slide with Python objects we've already seen:



Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 14

Class Representation

- ...or we can introduce a Python class:

```
class ExprTree:
    def __init__(self, operator):
        self._operator = operator

    @property
    def operator(self):
        return self._operator

    @property
    def left(self):
        raise NotImplementedError

    @property
    def right(self):
        raise NotImplementedError

class Leaf(ExprTree):
    pass

class Inner(ExprTree):
    def __init__(self, operator, left, right):
        ExprTree.__init__(self, operator)
        self._left = left
        self._right = right

    @property
    def left(self):
        return self._left

    @property
    def right(self):
        return self._right

Inner("+", Leaf("x"),
      Inner("*", Inner("+", Leaf("y"), Leaf("2")),
                Inner("+", Leaf("z"), Leaf("10"))))
```

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 15

A General Tree Type

- Trees don't quite lend themselves to being captured with standard syntax like tuples or lists, because they get accessed in various ways, with slightly varying interfaces.
- To start with, we'll use this type, which has no empty trees:

```
class Tree:
    """A Tree consists of a label and a sequence
    of 0 or more Trees, called its children."""

    def __init__(self, label, *children):
        """A Tree with given label and children.
        For convenience, if children[k] is not a Tree,
        it is converted into a leaf whose operator is
        children[k]."""
        self._label = label
        self._children = \
            [ c if type(c) is Tree else Tree(c)
              for c in children]
```

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 16

A General Tree Type: Accessors

```
# class Tree:
#     @property
#     def is_leaf(self):
#         return self.arity == 0

#     @property
#     def label(self):
#         return self._label

#     @property
#     def arity(self):
#         """The number of my children."""
#         return len(self._children)

#     def __iter__(self):
#         """An iterator over my children."""
#         return iter(self._children)

#     def __getitem__(self, k):
#         """My kth child."""
#         return self._children[k]
```

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 17

A Simple Recursion

- Since trees are recursively defined, recursion generally figures in algorithms on them.
- Example: number of leaf nodes.

```
def leaf_count(T):
    """Number of leaf nodes in the Tree T."""
    if T.is_leaf:
        return 1
    else:
        s = 0
        for child in T:
            s += leaf_count(child)
        return s
    # Can you put the else clause in one line instead?
    return functools.reduce(operator.add, map(leaf_count, T), 0)
```

- How long does this take (for a tree with N leaves)?

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 18

Tree to List

- Another example with no explicit base cases:


```
from functools import reduce
from operator import add
def tree_to_list_preorder(T):
    """The list of all labels in T, listing the labels
    of trees before those of their children, and listing their
    children left to right (preorder)."""
    return (T.label, ) + \
        reduce(add, map(tree_to_list_preorder, T, ()))
```

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 20

Search Trees

- The book talks about *search trees* as implementations of sets of values.
- Here, the purpose of the tree is to divide data into smaller parts.
- In a *binary search tree*, each node is either empty or has two children that are binary search trees such that all labels in the first (left) child are less than the node's label and all labels in the second (right) child are greater.



Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 21

Search Tree Class

- To work on search trees, it is useful to have a few more methods on trees:

```
class BinaryTree(Tree):
    @property
    def is_empty(self):
        """This tree contains no labels or children."""

    @property
    def left(self):
        return self[0]

    @property
    def right(self):
        return self[1]

    """The empty tree"""
    empty_tree = ...
```

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 22

Tree Search Program

```
def tree_find(T, x):
    """True iff x is a label in set T, represented as a search tree.
    That is, T
    (a) Represents an empty tree if its label is None, or
    (b) has two children, both search trees, and all labels in
    T[0] are less than T.label, and all labels in T[1] are
    greater than T.label."""
    if T.is_empty:
        return False
    if x == T.label:
        return True
    if x < T.label:
        return tree_find(T.left, x)
    else:
        return tree_find(T.right, x)
```

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 23

Timing

- How long does the `tree.find` program (search binary tree) take in the worst case
 - 1. As a function of D , the depth of the tree?
 - 2. As a function of N , the number of keys in the tree?
 - 3. As a function of D if the tree is as shallow as possible for the amount of data?
 - 3. As a function of N if the tree is as shallow as possible for the amount of data?

Last modified: Wed Mar 12 13:55:35 2014

CS61A: Lecture #20 24

Timing

- How long does the `tree_find` program (search binary tree) the worst case
 - 1. As a function of D , the depth of the tree? $\Theta(D)$
 - 2. As a function of N , the number of keys in the tree?
 - 3. As a function of D if the tree is as shallow as possible amount of data?
 - 3. As a function of N if the tree is as shallow as possible amount of data?

Timing

- How long does the `tree_find` program (search binary tree) the worst case
 - 1. As a function of D , the depth of the tree? $\Theta(D)$
 - 2. As a function of N , the number of keys in the tree? $\Theta(N)$
 - 3. As a function of D if the tree is as shallow as possible amount of data?
 - 3. As a function of N if the tree is as shallow as possible amount of data?

Timing

- How long does the `tree_find` program (search binary tree) the worst case
 - 1. As a function of D , the depth of the tree? $\Theta(D)$
 - 2. As a function of N , the number of keys in the tree? $\Theta(N)$
 - 3. As a function of D if the tree is as shallow as possible amount of data? $\Theta(D)$
 - 3. As a function of N if the tree is as shallow as possible amount of data?

Timing

- How long does the `tree_find` program (search binary tree) the worst case
 - 1. As a function of D , the depth of the tree? $\Theta(D)$
 - 2. As a function of N , the number of keys in the tree? $\Theta(N)$
 - 3. As a function of D if the tree is as shallow as possible amount of data? $\Theta(D)$
 - 3. As a function of N if the tree is as shallow as possible amount of data? $\Theta(\lg N)$

Timing

- How long does the `tree_find` program (search binary tree) the worst case
 - 1. As a function of D , the depth of the tree? $\Theta(D)$
 - 2. As a function of N , the number of keys in the tree? $\Theta(N)$
 - 3. As a function of D if the tree is as shallow as possible amount of data? $\Theta(D)$
 - 3. As a function of N if the tree is as shallow as possible amount of data? $\Theta(\lg N)$