

Package ‘msImpute’

July 28, 2020

Type Package

Title Peptide imputation in label-free proteomics

Version 1.2.0

Description msImpute provides tools for matrix completion in label-free proteomics quantification at the peptide-level. Currently, msImpute completes missing values by low-rank approximation of the underlying data matrix.

Imports softImpute

License MIT

Encoding UTF-8

LazyData true

BugReports <https://github.com/DavisLaboratory/msImpute/issues>

RoxygenNote 7.0.2

R topics documented:

CPD	1
KNC	2
KNN	3
msImpute	3
scaleData	5
selectFeatures	6
Index	8

CPD

CPD

Description

Spearman correlation between pairwise distances in the original data and imputed data. CPD quantifies preservation of the global structure after imputation. Requires complete datasets - for developers/use in benchmark studies only.

Usage

```
CPD(xorigin, ximputed)
```

Arguments

<code>xorigin</code>	numeric matrix. The original data. Can not contain missing values.
<code>ximputed</code>	numeric matrix. The imputed data. Can not contain missing values.

Value

numeric

KNC	<i>k-nearest class means (KNC)</i>
-----	------------------------------------

Description

The fraction of k-nearest class means in the original data that are preserved as k-nearest class means in imputed data. KNC quantifies preservation of the mesoscopic structure after imputation. Requires complete datasets - for developers/use in benchmark studies only.

Usage

```
KNC(xorigin, ximputed, class, k = 3)
```

Arguments

<code>xorigin</code>	numeric matrix. The original data. Can contain missing values.
<code>ximputed</code>	numeric matrix. The imputed data.
<code>class</code>	factor. A vector of length number of columns (samples) in the data specifying the class/label (i.e. experimental group) of each sample.
<code>k</code>	number of nearest class means. default to k=3.

Value

numeric The proportion of preserved k-nearest class means in imputed data.

KNN	<i>k-nearest neighbour (KNN)</i>
-----	----------------------------------

Description

The fraction of k-nearest neighbours in the original data that are preserved as k-nearest neighbours in imputed data. KNN quantifies preservation of the local, or microscopic structure. Requires complete datasets - for developers/use in benchmark studies only.

Usage

```
KNN(xorigin, ximputed, k = 3)
```

Arguments

<code>xorigin</code>	numeric matrix. The original data. Can not contain missing values.
<code>ximputed</code>	numeric matrix. The imputed data. Can not contain missing values.
<code>k</code>	number of nearest neighbours. default to k=3.

Value

numeric The proportion of preserved k-nearest neighbours in imputed data.

<code>msImpute</code>	<i>Peptide-level imputation in mass spectrometry label-free proteomics by low-rank approximation</i>
-----------------------	--

Description

Returns a completed peptide intensity matrix where missing values (NAs) are imputed by low-rank approximation of the input matrix. Non-NA entries remain unmodified. `msImpute` requires at least 4 non-missing measurements per peptide across all samples. It is assumed that peptide intensities (DDA), or MS1/MS2 normalised peak areas (DIA), are log2-transformed and normalised (e.g. quantile normalisation).

Usage

```
msImpute(object, rank.max = NULL, lambda = NULL, thresh = 1e-05,
  maxit = 100, trace.it = FALSE, warm.start = NULL,
  final.svd = TRUE)
```

Arguments

<code>object</code>	Numeric matrix where missing values are denoted by NA. Rows are peptides, columns are samples.
<code>rank.max</code>	Numeric. This restricts the rank of the solution. is set to $\min(\dim(\text{object})-1)$ by default.

<code>lambda</code>	Numeric. Nuclear-norm regularization parameter. Controls the low-rank property of the solution to the matrix completion problem. By default, it is determined at the scaling step. If set to zero the algorithm reverts to "hardImputation", where the convergence will be slower.
<code>thresh</code>	Numeric. Convergence threshold. Set to 1e-05, by default.
<code>maxit</code>	Numeric. Maximum number of iterations of the algorithm before the algorithm is converged. 100 by default.
<code>trace.it</code>	Logical. Prints traces of progress of the algorithm.
<code>warm.start</code>	List. A SVD object can be used to initialize the algorithm instead of random initialization.
<code>final.svd</code>	Logical. Shall final SVD object be saved? The solutions to the matrix completion problems are computed from U, D and V components of final SVD.

Details

`msImpute` operates on the `softImpute`-ALS algorithm. For more details on the underlying algorithm, please see [softImpute](#) package.

Value

Missing values are imputed by low-rank approximation of the input matrix. If input is a numeric matrix, a numeric matrix of identical dimensions is returned. If `x` is a `MAList` object, the `E` component is replaced with the completed matrix, and the updated `MAList` object is returned. Non-NA entries remain unmodified.

See Also

`selectFeatures`, `scaleData`

Examples

```
set.seed(101)
n=200
p=100
J=50
np=n*p
missfrac=0.3
x=matrix(rnorm(n*J),n,J)%*%matrix(rnorm(J*p),J,p)+matrix(rnorm(np),n,p)/5
ix=seq(np)
imiss=sample(ix,np*missfrac,replace=FALSE)
xna=x
xna[imiss]=NA
xna <- scaleData(xna)
xcomplete <- msImpute(object=xna)
```

scaleData	<i>Standardize a matrix to have optionally row means zero and variances one, and/or column means zero and variances one.</i>
-----------	--

Description

Standardize a matrix to have optionally row means zero and variances one, and/or column means zero and variances one.

Usage

```
scaleData(object, maxit = 20, thresh = 1e-09, row.center = TRUE,  
          row.scale = TRUE, col.center = TRUE, col.scale = TRUE,  
          trace = FALSE)
```

Arguments

object	numeric matrix where missing values are denoted by NA. Rows are peptides, columns are samples.
maxit	numeric. maximum iteration for the algorithm to converge (default to 20). When both row and column centering/scaling is requested, iteration may be necessary.
thresh	numeric. Convergence threshold (default to 1e-09).
row.center	logical. if row.center==TRUE (the default), row centering will be performed resulting in a matrix with row means zero. If row.center is a vector, it will be used to center the rows. If row.center=FALSE nothing is done.
row.scale	if row.scale==TRUE, the rows are scaled (after possibly centering, to have variance one. Alternatively, if a positive vector is supplied, it is used for row centering.
col.center	Similar to row.center
col.scale	Similar to row.scale
trace	logical. With trace=TRUE, convergence progress is reported, when iteration is needed.

Details

Standardizes rows and/or columns of a matrix with missing values, according to the biScale algorithm in Hastie et al. 2015.

Value

A list of two components: E and E.scaled. E contains the input matrix, E.scaled contains the scaled data

See Also

selectFeatures, msImpute

Examples

```

set.seed(101)
n=200
p=100
J=50
np=n*p
missfrac=0.3
x=matrix(rnorm(n*J),n,J)%*%matrix(rnorm(J*p),J,p)+matrix(rnorm(np),n,p)/5
ix=seq(np)
imiss=sample(ix,np*missfrac,replace=FALSE)
xna=x
xna[imiss]=NA
xna <- scaleData(xna)

```

selectFeatures

*Select features with high biological dropout rate***Description**

Fits a linear model to peptide dropout rate against peptide abundance. The selected features (peptides) can be used to determine if data is Missing Not At Random (MNAR). Users should note that msImpute assumes peptides are Missing At Random (MAR).

Usage

```
selectFeatures(object, n_features = 500, suppress_plot = FALSE)
```

Arguments

object	Numeric matrix where missing values are denoted by NA. Rows are peptides, columns are samples.
n_features	Numeric, number of features with high dropout rate. 500 by default.
suppress_plot	Logical show plot of dropouts vs abundances.

Value

A data frame with a logical column denoting the selected features

See Also

scaleData, msImpute

Examples

```

set.seed(101)
n=800
p=100
J=50
np=n*p
missfrac=0.3
x=matrix(rnorm(n*J),n,J)%*%matrix(rnorm(J*p),J,p)+matrix(rnorm(np),n,p)/5

```

```

ix=seq(np)
imiss=sample(ix,np*missfrac,replace=FALSE)
xna=x
xna[imiss]=NA
rownames(xna) <- 1:nrow(xna)
hdp <- selectFeatures(xna, n_features=500, suppress_plot=FALSE)
# construct matrix M to capture missing entries
M <- ifelse(is.na(xna),1,0)
M <- M[hdp$msImpute_feature,]
# plot a heatmap of missingness patterns for the selected peptides
library(ComplexHeatmap)
hm <- Heatmap(M,
column_title = "dropout pattern, columns ordered by dropout similarity",
  name = "",
  col = c("#8FBC8F", "#FFEFDB"),
  show_row_names = FALSE,
  show_column_names = TRUE,
  cluster_rows = TRUE,
  cluster_columns = TRUE,
  show_column_dend = FALSE,
  show_row_dend = FALSE,
  row_names_gp = gpar(fontsize = 7),
  column_names_gp = gpar(fontsize = 8),
  heatmap_legend_param = list(#direction = "horizontal",
  heatmap_legend_side = "bottom",
  labels = c("observed","missing"),
  legend_width = unit(6, "cm")),
)
hm <- draw(hm, heatmap_legend_side = "left")

```

Index

CPD, [1](#)

KNC, [2](#)

KNN, [3](#)

msImpute, [3](#)

scaleData, [5](#)

selectFeatures, [6](#)

softImpute, [4](#)