HW2 Problem Set

ECS 240

Due: TBD

This problem set contains 5 problems. Problems 1 and 5 are pure theory problems, and 2, 3, and 4 are coding problems. Most problems have multiple parts. For the coding problems, edit and add your source code in the provided `src/main.rs`. Solutions to the theory and free response questions should be written in LaTeX.

---

1. In class (Lecture 2, Part 1) we discussed that for compilers, there are three different languages involved – each with their own semantics, and a valid compiler must be consistent with all three of them. Namely:

   - The source language S (language in which we write the program)
   - The meta language M (language in which we write the compiler)
   - The target language T (language to which we compile the program).

   This problem asks you to complete the definition of a *correct* compiler (one which implements the semantics), based on these three semantics.

   (a) Complete the definition below based on the template that we started in class. **Hint:** you may find it helpful to reference the definition of when an interpreter satisfies a semantics that we saw in class (Lecture 1). Your definition should follow a similar idea.

   Defiition 1. *Let M be the semantics (set of $(\texttt{INPUT}, \texttt{prog}, \texttt{OUTPUT})$) for the metalanguage. Let S be the semantics of the source language. Let T be the semantics of the target language.*

   A compiler C is a program in the metalanguage M.

   *A compiler C **is correct**, or **satisfies** the semantics, if . . . TODO: Complete the definition here.*

   (b) Use your definition to prove the following: If C_1 is a correct compiler from S to T, and C_2 is a correct compiler from T to U, then the compiler C defined by the following pseudocode is a correct compiler from S to U:

   ```
   Compiler C from S to U:
   On input prog:
   - Run C1: set out1 = C1(prog).
   - Run C2 on the result: set out2 = C2(output1).
   - Return out2.
   ```

You may assume that the meta-language M runs the pseudocode above in the way that you would expect (i.e., it runs C_1, followed by C_2, and returns the result, similar to how `Seq` works for `RandProg`.)

Note: This part is essentially showing that compiling a program through an intermediate representation works out. In this case, the intermediate representation is T and the overall compiler is from S to U.

(c) Use your definition to prove the following: If C is a correct compiler from S to T, and I_T is an interpreter for T that implements the semantics, then running C, followed by running I_T on the result, results in a correct interpreter for S. That is:

```
Interpreter I_S for S:
On input (INPUT, prog):
- Run C: set out = C(prog).
- Run I_T((INPUT, out)).
```

You may assume that the meta-language M runs the pseudocode above in the way that you would expect (i.e., it runs C followed by I_T).

(d) Define the "do nothing" compiler from S to S to be a compiler which simply takes the input program, and returns it without any changes. This is a program in the metalanguage M such that

$$(\texttt{INPUT}, \texttt{do_nothing}, \texttt{OUTPUT})$$

is valid if and only if $\texttt{INPUT} = \texttt{OUTPUT}$.

Use your definition to prove or disprove the following: Regardless of the semantics of S, and even if S is nondeterministic, a do-nothing compiler is a valid compiler from S to itself.

2. This problem will ask you to expand the basic `RandProg` compiler from class to add some syntactic sugar. First, copy in any necessary code involving `RandProg` from the Lecture 2, Part 1 source code. Then complete the following (this was an exercise that we skipped in class):

(a) First, fix our compiler from class to produce runnable code. To do this, you will need to have it generate a `main` function, and you may also need to inline (or include with the compiled target code) the utility functions we used from `util.rs`. The compiler should now produce a single `String` for a `main.rs` source file, which can be run directly.

Write a unit test to see that it is working.

(b) Add syntactic sugar to our language for 4-bit integers, which support equality, less-than, and addition. Adapt and structure the compiler in such a way that the 4-bit integer logic is compiled out, and the 4-bit integers are reduced to Booleans.

(c) Add at least two unit tests to ensure that your new compiler is working.

Function and type names: For part (a), use the same `RandProg` and compiler from class. For part (b), please define a Rust enum `RandProgP2` for the syntax with the syntactic sugar, `struct RandProgP2Compiler` for the compiler, which supports methods

```
impl RandProgP2Compiler {
    pub fn new() -> Self
    pub fn compile(&mut self, prog: &RandProgP2) -> String
}
```

For the unit tests in (a) and (c), please name these `test_2a`, `test_2c_1`, and `test_2c_2`. (You may add other unit tests with other names.)

3. This problem will ask you to expand the basic `RandProg` to add something resembling platform-specific code. Use the same `RandProg` enum from Problem 2. Then, complete the following (this was an exercise that we skipped in class):

   (a) Add some "platform-specific code" for random number generation by allowing our language to be configured to different pseudorandom number generators at the back-end: (1) Rust thread RNG (default Rust random generator) (2) Always return Heads (3) Always return Tails (4) On Unix systems, use Unix's `/dev/random` for RNG rather than the built in Rust thread RNG.

   (b) Add at least three unit tests to ensure that your new compiler is working.

   (c) Then answer the following (in your LaTeX document and PDF): Why might it be more helpful to generate this platform-specific code, *after* any compiler analysis and optimization passes on various intermediate representations have completed? Comment on why you think this separated design is often used in compiler development in practice.

   Function and type names: Use `RandProg` for the syntax, and `RandProgP3Compiler` for the compiler. To get this to work, you will need to add a `RandProgRngConfig` enum to your compiler that tells which platform to compile for:

```
#[derive(Debug, Copy, Clone)]
pub enum RandProgRngConfig {
    DefaultRng,
    AlwaysHeads,
    AlwaysTails,
    DevRandom,
}
```

   Then, your compiler should have two different constructors:

```
impl RandProgP3Compiler {
    pub fn new() -> Self // Use default Rng
    pub fn new_with_rng(RandProgRngConfig) -> Self
    pub fn compile(&mut self, prog: &RandProg) -> String
}
```

   Please name your unit tests `test_3b_1`, `test_3b_2`, and `test_3b_3`. (You may add other unit tests with other names.)

4. This problem and the following one will revisit the BF language from HW1.

   One extremely important intermediate representation in the context of real compilers is that of a *control flow graph*. To define a control-flow graph for a language, we define a set of nodes and edges. These are defined as follows:

   - **Nodes:** The nodes are the set of **basic blocks** of the program. A basic block is a sequence of instructions, none of which is a branching or loop statement (with the possible exception of the very last statement). In the context of BF, that means it will be a sequence of instructions in the program that doesn't have the `[]` characters, except (possibly) its very last character. The idea of a "basic block" is that it is a basic sequence of instructions that can be executed in order – and is always executed in order, "as a whole" – with exactly one entry and exit point. In particular, it is impossible for any other part of the program to ever jump or branch to the middle of a basic block.

     Also, one special basic block is designated as the entrypoint of the program, and one as the exit point. The exit point block (unlike the others) may be empty, in the case that the program ends in a jump or branch statement (to distinguish from the block of instructions prior to the jump, and after the jump when the program will terminate). The entry point block should always be nonempty, unless the program itself is empty, in which case it should have only one basic block, which is both the entry and exit point.
   - **Edges:** The edges are then from one basic block to another, if it is possible for that basic block to transition to the other one after it finishes executing. For example, in languages with `if` statements, for the basic block immediately prior to an `if` statement, it would have an edge to both branches of the `if`. In languages with `loop`s (of all kinds), the basic block immediately prior to the loop will have an edge to both the block inside the loop, and after the loop.

   For this problem, write two functions:

   ```
   pub fn num_basic_blocks(bf_prog: &str) -> usize
   ```

   which takes a BF program as a plain ASCII string and calculates the number of basic blocks; and

   ```
   pub fn num_edges(bf_prog: &str) -> usize
   ```

   which takes a BF program as a plain ASCII string and calculates the number of edges. Both functions may assume the BF program is valid (has matching loop instructions) It may be the empty string.

   You do not need to actually write a compiler which takes the BF program and calculates its control flow graph as an intermediate representation as part of this problem, though you may choose to do so. We will grade only your two functions for correctness.

   You may want to write some unit tests for your functions to ensure they are working correctly.

5. Most programming languages that are designed and studied in practice are what is called *Turing-complete*. This can be defined as "has the ability to simulate, and can be simulated by, a Turing machine", or it may be defined more informally as simply "has the ability to simulate, and can be simulated by, any regular program" (such as one written in Python or C). Alternatively, it may be defined in terms of concepts introduced in HW1, as: the semantics of the language can both simulate BF, and can be simulated by BF.

   However, not all languages are Turing-complete. For example, from class, `RandProg` is not Turing-complete. It has only Boolean variables, so cannot store and access infinite memory. It would be Turing-complete if we were to add integer variables and loops. Any type of loop would do, `while` loops or `for` loops or `label/goto` statements.

   This problem will have two parts. The first part will ask you to design a language that is *weaker* than Turing-complete, and the second *stronger* than Turing complete.

   Below, `BF` is used as a stand-in language for a Turing-complete language for these problems. However, if you are more comfortable with some other Turing-complete language, such as Turing machines themselves, you can also use that instead of BF. Or if you are more comfortable working with Python programs or pseudocode, you may use that. You can assume that a semantics has been given for any of these languages that matches your intuition.

   To prove that one language can simulate another, you should do so by defining a function f, as in HW Part 1, that translates Argue informally that your translation is correct based on the semantics of the source and target languages.

   (a) Consider the following language, called `FORLOOP`:

```
Var ::= x | y | z
IntExpr ::= 0 | 1 | Var | (IntExpr + IntExpr) | (IntExpr * IntExpr)
BoolExpr ::= IntExpr < IntExpr | IntExpr == IntExpr
Prog ::=
    Var := IntExpr
    | Prog ; Prog
    | If BoolExpr Then { Prog } Else { Prog }
    | For { Var } from { IntExpr } to { IntExpr } do { Prog }
```

   In the semantics of `FORLOOP`, the expression `For Var from IntExpr to IntExpr do Prog` means that the starting integer i and ending integer j will be calculated up front, and then the for loop will be executed by setting `Var` to every value $i, i+1, i+2, \ldots, j-1$ (like a Python `range`) this remains the case even if the variable `Var` is modified in the loop body. (So, modifications to `Var` in the loop body are only retained for the duration of that loop body, and don't affect the following loop iteration.) If $j \leq i$, the for loop will terminate immediately.

   You do not need to write down the formal semantics of the language, but assume that it matches the above description for `For` and your intuition for the other commands. You can work with the following: we use the initial values of `x`, `y`, and `z` as input, the final values of `x`, `y`, and `z` are output. Then, assume that $((x_0, y_0, z_0), \texttt{prog}, (x_1, y_1, z_1))$ is valid if, when running the program `prog` as you would expect (interpreting If statements and For loops as they are usually

understood), starting with initial values of the variables (x_0, y_0, z_0), (x_1, y_1, z_1) are the final values of the variables.

Prove that `FORLOOP` is not Turing complete, but it is more specifically *weaker* than Turing complete: it can be simulated by BF, but not vice versa.

(b) Now consider the following language, called `HALT`:

```
Var ::= x | y | z
IntExpr ::= 0 | 1 | Var | (IntExpr + IntExpr) | (IntExpr * IntExpr)
BoolExpr ::= IntExpr < IntExpr | IntExpr == IntExpr | HALTS(BFProg)
Prog ::=
    Var := IntExpr
    | Prog ; Prog
    | If BoolExpr Then { Prog } Else { Prog }
    | While { BoolExpr } do { Prog }
```

The boolean expression `HALTS(BFProg)` returns `True` if and only if the BF program given to it halts. You may assume that the BF programs in question do not take input.

Prove that `HALT` is not Turing complete, but it is more specifically *stronger* than Turing complete: it can simulate BF, but not vice versa.

(c) Explain why, due to the above constraints, it will be impossible to write a correct compiler in *any* metalanguage – even one that is more powerful than Turing machines – from `HALT` to `BF` or from `BF` to `FORLOOP`.

Submission instructions:

- Upload your solutions (as a PDF) and your code (as a `.zip` file, as with HW0: including the entire repository directory including config files like `Cargo.toml`, but excluding `target/`) in Gradescope.
- Your PDF should be a single file `hw2.pdf`. If you use this LaTeX template to create your solutions, please remove the problem statements and include only your solutions.
- The `main.rs` should contain your solutions to all coding parts (including functions and types as described above). Please do not modify function signatures. You are welcome to add additional functions and tests – if you do so, please include all additional tests only at the bottom of the file.
- You may add utility modules, like `mod util;` then `use util::...`, if you feel that you need them; but you should put all the main functions with the names as above in `main.rs`. Please double check on Piazza before importing any external crates in your `Cargo.toml`.
- Make sure that `cargo build`, `cargo clippy`, `cargo test`, and `cargo fmt` (or `cargo fmt --check`) pass without any errors.