

Huxtable functionality demo/test

David Hugh-Jones

2/03/2017

Basic usage

Creating a huxtable

```
ht_orig <- huxtable(a = c('Parsley', 'Sage', 'Rosemary', 'Thyme'), b = 10 ^ (2:5))
ht_orig <- set_all_borders(ht_orig, 1:nrow(ht_orig), 1:ncol(ht_orig), 1)
ht_orig
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Borders

```
ht <- ht_orig
ht <- set_all_borders(ht, 1:4, 1:2, 0)
top_border(ht) <- c(2, 0, 0, 1)
bottom_border(ht)[4,] <- 2
ht
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Cell alignment

```
ht <- ht_orig
align(ht)[,1] <- 'left'
ht
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Vertical alignment

```
ht <- ht_orig
row_height(ht) <- '50pt'
valign(ht)[,1] <- 'top'
valign(ht)[,2] <- 'bottom'
ht
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Column span

```
ht <- ht_orig
background_color(ht)[1,1] <- 'green'
colspan(ht)[1,1] <- 2
ht
```

Parsley	
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Row span

```
ht <- ht_orig
ht[1,1] <- 'A rather long block of text'
background_color(ht)[1,1] <- 'green'
rowspan(ht)[1,1] <- 2
ht
```

A rather long block of text	100.00
	1000.00
Rosemary	10000.00
Thyme	100000.00

Table position

```
ht <- ht_orig
position(ht) <- 'left'
ht
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Table width

```
ht <- ht_orig
width(ht) <- 1/3
ht
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Column width

```
ht <- ht_orig
col_width(ht) <- c(.8, .2)
ht
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Row height

```
ht <- ht_orig
height(ht) <- 0.2;
if (! is_latex) height(ht) <- '100px' # need a specific height for row heights to work in HTML
row_height(ht) <- c(.4, .2, .2, .2) * 0.2
ht
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Text color, bold, italic, font size

```
ht <- ht_orig
text_color(ht)[,2] <- 'red'
bold(ht)[1,] <- TRUE
italic(ht)[3,] <- TRUE
font_size(ht)[2,] <- 14
font(ht)[4,] <- if (is_latex) 'phv' else 'times'
ht
```

Parsley	100.00
Sage	1000.00
<i>Rosemary</i>	<i>10000.00</i>
Thyme	100000.00

Number formatting

```
ht <- ht_orig
ht[,2] <- ht[,2] + rnorm(4)
```

```
number_format(ht)[2,] <- 2
number_format(ht)[3,] <- '%011.4f'
number_format(ht)[4,] <- list(function(x) prettyNum(round(x, 3), big.mark = ','))

ht
```

Parsley	99.83
Sage	999.87
Rosemary	009999.1913
Thyme	100,001.1

Replace NAs

```
ht <- ht_orig
ht[2,] <- NA
ht
```

Parsley	100.00
Rosemary	10000.00
Thyme	100000.00

```
na_string(ht) <- '--'
ht
```

Parsley	100.00
—	—
Rosemary	10000.00
Thyme	100000.00

Pipe style with magrittr

```
if (require('magrittr')) {
ht <- ht_orig
ht %>%
  set_all_borders(1:4, 1:2, 0) %>%
  set_top_border(1, 1:2, 1) %>%
  set_bold(1, 1:2, TRUE) %>%
  set_background_color(1:4, 1:2, 'wheat') %>%
  set_number_format(1:4, 1:2, '%03.1d') %>%
  set_align(1:4, 1, 'left') %>%
```

```
set_align(1:4, 2, 'right')
}
```

```
## Loading required package: magrittr
```

Parsley	100
Sage	1000
Rosemary	10000
Thyme	100000

Quick themes

```
ht <- ht_orig
ht <- rbind(c("Herb", "Amount"), ht)
theme_minimal(ht)
```

Herb	Amount
Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

```
theme_stripped(ht, header_col = FALSE)
```

Herb	Amount
Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

```
theme_article(ht)
```

Herb	Amount
Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Converting other objects to huxtables

```
defaults <- function(ht) {
  bottom_border(ht)[1,] <- 1
  background_color(ht)[seq(1, nrow(ht), 2), ] <- grey(.9)
  ht
}
```

```
defaults(as_hux(letters[1:5]))
```

a
b
c
d
e

```
defaults(as_hux(matrix(letters[1:10], 2)))
```

a	c	e	g	i
b	d	f	h	j

```
data(mtcars)
defaults(as_hux(mtcars[1:10,]))
```

21.00	6.00	160.00	110.00	3.90	2.62	16.46	0.00	1.00	4.00	4.00
21.00	6.00	160.00	110.00	3.90	2.88	17.02	0.00	1.00	4.00	4.00
22.80	4.00	108.00	93.00	3.85	2.32	18.61	1.00	1.00	4.00	1.00
21.40	6.00	258.00	110.00	3.08	3.21	19.44	1.00	0.00	3.00	1.00
18.70	8.00	360.00	175.00	3.15	3.44	17.02	0.00	0.00	3.00	2.00
18.10	6.00	225.00	105.00	2.76	3.46	20.22	1.00	0.00	3.00	1.00
14.30	8.00	360.00	245.00	3.21	3.57	15.84	0.00	0.00	3.00	4.00
24.40	4.00	146.70	62.00	3.69	3.19	20.00	1.00	0.00	4.00	2.00
22.80	4.00	140.80	95.00	3.92	3.15	22.90	1.00	0.00	4.00	2.00
19.20	6.00	167.60	123.00	3.92	3.44	18.30	1.00	0.00	4.00	4.00

```
car_table <- xtabs(~ cyl + gear, mtcars)
defaults(as_hux(car_table))
```

1.00	8.00	2.00
2.00	4.00	1.00
12.00	0.00	2.00

```
car_ft <- ftable(cyl ~ gear + vs, mtcars)
defaults(as_hux(car_ft))
```

		cyl	4.00	6.00	8.00
gear	vs				
	3.00	0.00	0.00	0.00	12.00
	1.00		1.00	2.00	0.00
4.00	0.00		0.00	2.00	0.00
	1.00		8.00	2.00	0.00
5.00	0.00		1.00	1.00	2.00
	1.00		1.00	0.00	0.00

Joining, subsetting and manipulating huxtables

Subsets

```
ht <- ht_orig
bottom_border(ht)[c(1,4),] <- 1
background_color(ht)[1,] <- 'wheat'
```



```
ht[1:3,1]
```

Parsley
Sage
Rosemary

Joining

```
ht2 <- ht_orig  
italic(ht2) <- TRUE  
rbind(ht, ht2)
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00
<i>Parsley</i>	<i>100.00</i>
<i>Sage</i>	<i>1000.00</i>
<i>Rosemary</i>	<i>10000.00</i>
<i>Thyme</i>	<i>100000.00</i>

```
cbind(ht, ht2)
```

Parsley	100.00	<i>Parsley</i>	<i>100.00</i>
Sage	1000.00	<i>Sage</i>	<i>1000.00</i>
Rosemary	10000.00	<i>Rosemary</i>	<i>10000.00</i>
Thyme	100000.00	<i>Thyme</i>	<i>100000.00</i>

```
rbind(c("Oregano", 300), ht)
```

Oregano	300.00
Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Transpose

```
colspan(ht)[1, 1] <- 2
ht
```

Parsley	
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

```
t(ht)
```

	Sage	Rosemary	Thyme
Parsley	1000.00	10000.00	100000.00

Advanced features

Printing on screen

```
ht <- ht_orig
# Basic data:
print(ht)
```

```
##           a      b
## 1 Parsley 1e+02
## 2   Sage 1e+03
## 3 Rosemary 1e+04
## 4   Thyme 1e+05
```

```
# Pretty print:
print_screen(ht)
```

```
## -----
## | Parsley | 100.00 |
## -----
## | Sage    | 1000.00 |
## -----
## | Rosemary | 10000.00 |
```

```
## -----
## | Thyme      | 100000.00 |
## -----
```

Markdown:

```
print_md(ht)
```

```
## -----
## Parsley                                100.00
## -----
## Sage                                  1000.00
##
## Rosemary                             10000.00
##
## Thyme                                100000.00
## -----
```

Padding

```
ht <- ht_orig
ht <- set_all_padding(ht, 1:4, 1:2, 0)
left_padding(ht)[,1] <- 40
right_padding(ht)[,2] <- 40
top_padding(ht) <- 20
bottom_padding(ht) <- 20
ht
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Cell rotation

```
ht <- ht_orig
height(ht) <- 0.2 # necessary
if (! is_latex) height(ht) <- '300px'
```

```
col_width(ht) <- c(.25, .75)
rotation(ht)[,1] <- 90
ht
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Border width

```
ht <- ht_orig
bottom_border(ht)[1,] <- 3
ht
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Caption

```
ht <- ht_orig
caption(ht) <- 'A simple table'
ht
```

Table 1: A simple table

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Caption below

```
ht <- ht_orig
caption(ht) <- 'A simple table'
caption_pos(ht) <- 'bottom'
ht
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Table 2: A simple table

Label

```
ht <- ht_orig
caption(ht) <- 'Captions are required for labels to work'
label(ht) <- 'tab:mytable'
ht
```

Table 3: Captions are required for labels to work

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

```
knitr::asis_output('If this is LaTeX we can see a reference to table \\ref{tab:mytable}.')
```

If this is LaTeX we can see a reference to table 3.

NB: references may not work if knitting PDFs in Rstudio.

Testing corner cases

Heights and padding

```
ht <- ht_orig

row_height(ht) <- c(.1, .05, .05, .05)
# top_padding(ht) <- 10
# bottom_padding(ht) <- 20
ht
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Row and column span

```
ht <- ht_orig
ht[1,1] <- 'A rather long block of text'
background_color(ht)[1,1] <- 'green'
rowspan(ht)[1,1] <- 2
colspan(ht)[1,1] <- 2
ht
```

A rather long block of text	
Rosemary	10000.00
Thyme	100000.00

Huge table of cross-validation

```
set_rowcol <- function(ht, fun, rc, value) {
  ht[1, rc] <- ht[rc, 1] <- paste(deparse(substitute(fun)), '=', value)
  ht <- fun(ht, rc, 1:ncol(ht), value)
  ht <- fun(ht, 1:nrow(ht), rc, value)
  ht
}

N <- 22
megahux <- as_hux(matrix("", N, N))
megahux[1:5,] <- 'Some text'
megahux[6:10,] <- rnorm(5*N)
megahux[11:15,] <- 'Some more text'
megahux[18:22, ] <- rnorm(5*N)
megahux[16:17, ] <- substring(stringi::stri_rand_lipsum(2*N), 0, 50)
# for (col in c(2,7,12,17,22)) test_hux[,col] <- sample(test_hux[,col])
```

```

megahux <- megahux                                %>%
  set_rowcol(set_valign, 1, 'top')                 %>%
  set_rowcol(set_align, 2, 'left')                 %>%
  set_rowcol(set_top_border, 3, 1)                 %>%
  set_rowcol(set_bottom_border, 4, 2)              %>%
  set_rowcol(set_left_border, 5, 1)                %>%
  set_rowcol(set_right_border, 6, 1)               %>%
  set_rowcol(set_background_color, 9, 'wheat')     %>%
  set_rowcol(set_text_color, 10, 'red')            %>%
  set_rowcol(set_top_padding, 12, 20)              %>%
  set_rowcol(set_bottom_padding, 13, 20)           %>%
  set_rowcol(set_left_padding, 14, 20)             %>%
  set_rowcol(set_right_padding, 15, 20)            %>%
  set_rowcol(set_escape_contents, 16, FALSE)       %>%
  set_rowcol(set_na_string, 17, 'N.a.')            %>%
  set_rowcol(set_bold, 18, TRUE)                   %>%
  set_rowcol(set_italic, 19, TRUE)                 %>%
  set_rowcol(set_font_size, 20, 20)                %>%
  set_rowcol(set_number_format, 21, '%9.6f')       %>%
  set_rowcol(set_font, 22, 'times')

colspan(megahux)[11, 4] <- 6
rowspan(megahux)[4, 11] <- 6
megahux[11,4] <- stringi::stri_rand_lipsum(1)
megahux[4, 11] <- stringi::stri_rand_lipsum(1)
megahux[,16] <- megahux[16,] <- '<b>Non escaped HTML</b>'
megahux[,17] <- megahux[17,] <- sample(c(1:10, rep(NA, 12)))

megahux

```

set_wdignign test = = = = top left 1 2				set_bordleftbordright = = text text		set_bgcolorcolorcolorcolor = = text = = = = wheatred 20 20 20 20				set_buildinginfilingNaldiset = = es- = = caped TRUE HTML						
set_alSomeSomeSomeSomeSomeSomeSome = text text text text text text text text left				SomeSomeSomeSomeSomeSomeSome text text text text text text text text				SomeSomeSomeSomeSomeSomeSome text text text text text text text text				SomeSomeSomeSomeSomeSomeSome text es- = = caped text t HTML				
set_tSomeSomeSomeSomeSomeSomeSome = text text text text text text text text 1				SomeSomeSomeSomeSomeSomeSome text text text text text text text text				SomeSomeSomeSomeSomeSomeSome text text text text text text text text				SomeSomeSomeSomeSomeSomeSome text es- = = caped text t HTML				
set_bSomeSomeSomeSomeSomeSomeSome = text text text text text text text text 2				SomeSomeSomeSomeSomeSomeSome text text text text text text text text				SomeSomeSomeSomeSomeSomeSome text text text text text text text text				SomeSomeSomeSomeSomeSomeSome text es- = = caped text t HTML				
set_lSomeSomeSomeSomeSomeSomeSome = text text text text text text text text 1	SomeSomeSomeSomeSomeSomeSome text text text text text text text text			SomeSomeSomeSomeSomeSomeSome text text text text text text text text				SomeSomeSomeSomeSomeSomeSome text text text text text text text text				SomeSomeSomeSomeSomeSomeSome text es- = = caped text t HTML				
	set_rSomeSomeSomeSomeSomeSomeSome = text text text text text text text text 1			SomeSomeSomeSomeSomeSomeSome text text text text text text text text				SomeSomeSomeSomeSomeSomeSome text text text text text text text text				SomeSomeSomeSomeSomeSomeSome text es- = = caped text t HTML				
	set_rSomeSomeSomeSomeSomeSomeSome = text text text text text text text text 1			SomeSomeSomeSomeSomeSomeSome text text text text text text text text				SomeSomeSomeSomeSomeSomeSome text text text text text text text text				SomeSomeSomeSomeSomeSomeSome text es- = = caped text t HTML				
- - 0.03 - 0.10 1.26 - - 0.47 0.40 0.63 0.81 0.74 0.14 0.09				- - - - 0.98 0.48 0.97 0.39 0.65 0.98 0.48				- 1.13 0.49 No. 0.10 1.00 es- = = caped 0.10 HTML				- 1.18 es- = = caped 1.18 HTML				
0.13 - 0.14 0.83 0.53 0.40 - 0.3 0.98 - 1.98 0.38 0.54				- 0.17 - - No. 0.01 0.70 0.82 1.97 es- = = caped 0.01 HTML				- 0.17 - - No. 0.01 0.70 0.82 1.97 es- = = caped 0.01 HTML				- 0.01 es- = = caped 0.01 HTML				
set_ - 1.8 - 0.4 0.4 - 0.1 - - = 0.70 0.82 0.07 0.87 0.39 whe				- - - - 2.09 0.59 0.27 0.22 es- = = caped 0.22 HTI				- N.ε 0.4 es- = = caped 0.4 HTI				- 0.4 es- = = caped 0.4 HTI				
set_text_col - 0.76 - 0.96 0.7 - 1.68 - - - = 0.04 0.87 1.34 0.06 0.50 0.01 1.50 red				0.0019 No. - es- = = caped - HTML				0.0019 No. - es- = = caped - HTML				- 0.21 es- = = caped 0.21 HTML				