# Quick guide to functionality

David Hugh-Jones 2/03/2017

## Basic usage

### Creating a huxtable

```
ht_orig <- huxtable(a = c('Parsley', 'Sage', 'Rosemary', 'Thyme'), b = 10 ^ (2:5))
width(ht_orig) <- 0.25
ht_orig <- set_all_borders(ht_orig, 1:nrow(ht_orig), 1:ncol(ht_orig), 1)
ht_orig</pre>
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

#### **Borders**

```
ht <- ht_orig
ht <- set_all_borders(ht, 1:4, 1:2, 0)
top_border(ht) <- c(2, 0, 0, 1)
bottom_border(ht)[4,] <- 2
ht</pre>
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

### Cell alignment

```
ht <- ht_orig
align(ht)[,1] <- 'left'
ht</pre>
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

## Vertical alignment

```
ht <- ht_orig
row_height(ht) <- '50pt'
valign(ht)[,1] <- 'top'
ht</pre>
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

## Column span

```
ht <- ht_orig
background_color(ht)[1,1] <- 'green'
colspan(ht)[1,1] <- 2
ht</pre>
```

Parsley	
$\operatorname{Sage}$	1000.00
Rosemary	10000.00
Thyme	100000.00

### Row span

```
ht <- ht_orig
ht[1,1] <- 'A rather long block of text'
background_color(ht)[1,1] <- 'green'
rowspan(ht)[1,1] <- 2
ht</pre>
```

A rather long block of text	100.00
A father long block of text	1000.00
Rosemary	10000.00
Thyme	100000.00

## Table position

```
ht <- ht_orig
position(ht) <- 'left'
ht</pre>
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

### Table width

```
ht <- ht_orig
width(ht) <- 0.5
ht</pre>
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

## Column width

```
ht <- ht_orig
col_width(ht) <- c(.8, .2)
ht</pre>
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

### Row height

```
ht <- ht_orig
height(ht) <- 0.2;
if (! is_latex) height(ht) <- '100px' # need a specific height for row heights to work in HTML
row_height(ht) <- c(.4, .2, .2, .2) * 0.2
ht</pre>
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

### Text color, bold, italic, font size

```
ht <- ht_orig
text_color(ht)[,2] <- 'red'
bold(ht)[1,] <- TRUE
italic(ht)[3,] <- TRUE
font_size(ht)[2,] <- 14
font(ht)[4,] <- if (is_latex) 'phv' else 'times'
ht</pre>
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

### Number formatting

```
ht <- ht_orig
ht[,2] <- ht[,2] + rnorm(4)
number_format(ht)[2,] <- 2
number_format(ht)[3,] <- '%011.4f'
number_format(ht)[4,] <- list(function(x) prettyNum(round(x, 3), big.mark = ','))
ht</pre>
```

Parsley	99.65
Sage	997.30
Rosemary	009999.3085
Thyme	99,999.83

### Replace NAs

```
ht <- ht_orig
ht[2,] <- NA
ht</pre>
```

Parsley	100.00
Rosemary	10000.00
Thyme	100000.00

```
na_string(ht) <- '--'
ht</pre>
```

Parsley	100.00
_	_
Rosemary	10000.00
Thyme	100000.00

### Pipe style with magrittr

```
if (require('magrittr')) {
ht <- ht_orig
ht %>%
                                              %>%
     set_all_borders(1:4, 1:2, 0)
                                              %>%
      set_top_border(1, 1:2, 1)
     set_bold(1, 1:2, TRUE)
                                              %>%
      set_background_color(1:4, 1:2, 'wheat') %>%
      set_number_format(1:4, 1:2, '%03.1d')
                                              %>%
      set_align(1:4, 1, 'left')
                                              %>%
      set_align(1:4, 2, 'right')
}
```

## Loading required package: magrittr

Parsley	100
1 412103	
Sage	1000
0	-000
Rosemary	10000
_	100000
Thyme	100000

## Quick themes

```
ht <- ht_orig
ht <- rbind(c("Herb", "Amount"), ht)
theme_minimal(ht)</pre>
```

Herb	Amount
Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

theme\_striped(ht, header\_col = FALSE)

$\operatorname{Herb}$	Amount
Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

theme\_article(ht)

Herb	Amount
Parsley	100.00
$\mathbf{Sage}$	1000.00
Rosemary	10000.00
Thyme	100000.00

## Converting other objects to huxtables

```
defaults <- function(ht) {
  bottom_border(ht)[1,] <- 1
  background_color(ht)[seq(1, nrow(ht), 2), ] <- grey(.9)
  ht
}
defaults(as_hux(letters[1:5]))</pre>
```

a
b
c
d
e

defaults(as\_hux(matrix(letters[1:10], 2)))

a	$\mathbf{c}$	e	g	i
b	d	f	h	j

```
data(mtcars)
defaults(as_hux(mtcars[1:10,]))
```

21.00	6.00	160.00	110.00	3.90	2.62	16.46	0.00	1.00
21.00	6.00	160.00	110.00	3.90	2.88	17.02	0.00	1.00
22.80	4.00	108.00	93.00	3.85	2.32	18.61	1.00	1.00
21.40	6.00	258.00	110.00	3.08	3.21	19.44	1.00	0.00
18.70	8.00	360.00	175.00	3.15	3.44	17.02	0.00	0.00
18.10	6.00	225.00	105.00	2.76	3.46	20.22	1.00	0.00
14.30	8.00	360.00	245.00	3.21	3.57	15.84	0.00	0.00
24.40	4.00	146.70	62.00	3.69	3.19	20.00	1.00	0.00
22.80	4.00	140.80	95.00	3.92	3.15	22.90	1.00	0.00
19.20	6.00	167.60	123.00	3.92	3.44	18.30	1.00	0.00

```
car_table <- xtabs(~ cyl + gear, mtcars)
defaults(as_hux(car_table))</pre>
```

1.00	8.00	2.00
2.00	4.00	1.00
12.00	0.00	2.00

```
car_ft <- ftable(cyl ~ gear + vs, mtcars)
defaults(as_hux(car_ft))</pre>
```

		cyl	4.00	6.00	8.00
gear	vs				
3.00	0.00		0.00	0.00	12.00
	1.00		1.00	2.00	0.00
4.00	0.00		0.00	2.00	0.00
	1.00		8.00	2.00	0.00
5.00	0.00		1.00	1.00	2.00
	1.00		1.00	0.00	0.00

# Joining, subsetting and manipulating huxtables

### Subsets

```
ht <- ht_orig
bottom_border(ht)[c(1,4),] <- 1
background_color(ht)[1,] <- 'wheat'
ht[1:3,1]</pre>
```

Parsley
Sage
Rosemary

## Joining

ht2 <- ht\_orig
italic(ht2) <- TRUE
rbind(ht, ht2)</pre>

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00
Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

### cbind(ht, ht2)

Parsley	100.00	Parsley	100.00
Sage	1000.00	Sage	1000.00
Rosemary	10000.00	Rosemary	10000.00
Thyme	100000.00	Thyme	100000.00

rbind(c("Oregano", 300), ht)

Oregano	300.00
Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

### Transpose

```
colspan(ht)[1, 1] <- 2
ht</pre>
```

Parsley		
Sage	1000.00	
Rosemary	10000.00	
Thyme	100000.00	

t(ht)

Parslev	$\operatorname{Sage}$	Rosemary	Thyme
1 arsiey	1000.00	10000.00	100000.00

## Advanced features

### Printing on screen

```
ht <- ht_orig
# Basic data:
print(ht)
##
          a
## 1 Parsley 1e+02
## 2
       Sage 1e+03
## 3 Rosemary 1e+04
## 4
      Thyme 1e+05
# Pretty print:
print_screen(ht)
## | Parsley | 100.00 |
## -----
## |
      Sage | 1000.00 |
## -----
## | Rosemary | 10000.00 |
##
##
  | Thyme | 100000.00 |
##
# Markdown:
print_md(ht)
```

##		
##	Parsley	100.00
##		
##	Sage	1000.00
##		
##	Rosemary	10000.00
##		
##	Thyme	100000.00
##		
##		

### Padding

```
ht <- ht_orig
ht <- set_all_padding(ht, 1:4, 1:2, 0)
left_padding(ht)[,1] <- 40
right_padding(ht)[,2] <- 40
top_padding(ht) <- 20
bottom_padding(ht) <- 20
ht</pre>
```

Parsley	100.00
$\operatorname{Sage}$	1000.00
Rosemary	10000.00
Thyme	100000.00

### Cell rotation

```
ht <- ht_orig
height(ht) <- 0.2 # necessary
if (! is_latex) height(ht) <- '300px'
col_width(ht) <- c(.25, .75)
rotation(ht)[,1] <- 90
ht</pre>
```

_	
Parsley	100.00
Sage	
$\tilde{\mathbf{x}}$	1000.00
Rosemary	10000.00
<u> </u>	
hyme	
	100000.00

## Border width

```
ht <- ht_orig
bottom_border(ht)[1,] <- 3
ht</pre>
```

Parsley	100.00
$\operatorname{Sage}$	1000.00
Rosemary	10000.00
Thyme	100000.00

## Caption

```
ht <- ht_orig
caption(ht) <- 'A simple table'
ht</pre>
```

Table 1: A simple table

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

## Caption below

```
ht <- ht_orig
caption(ht) <- 'A simple table'
caption_pos(ht) <- 'bottom'
ht</pre>
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

Table 2: A simple table

#### Label

```
ht <- ht_orig
caption(ht) <- 'Captions are required for labels to work'
label(ht) <- 'tab:mytable'
ht</pre>
```

Table 3: Captions are required for labels to work

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

```
knitr::asis_output('If this is LaTeX we can see a reference to table \\ref{tab:mytable}.')
```

If this is LaTeX we can see a reference to table 3.

NB: references may not work if knitting PDFs in Rstudio.

## Testing corner cases

### Heights and padding

```
ht <- ht_orig

row_height(ht) <- c(.1, .05, .05, .05)
# top_padding(ht) <- 10
# bottom_padding(ht) <- 20
ht</pre>
```

Parsley	100.00
Sage	1000.00
Rosemary	10000.00
Thyme	100000.00

## Row and column span

```
ht <- ht_orig
ht[1,1] <- 'A rather long block of text'
background_color(ht)[1,1] <- 'green'
rowspan(ht)[1,1] <- 2
colspan(ht)[1,1] <- 2
ht</pre>
```

A rather long block of text	
Rosemary	10000.00
Thyme	100000.00