

Phase N1: Clean European Temporal Convergence Study

V2 Ultraweak DPG Solver — European Call Option

dpg-finance project

2026-05-28 (commit 6f55973)

Contents

1	Objective	1
2	Mathematical Formulation	1
2.1	Black-Scholes PDE in log-price coordinates	1
2.2	Ultraweak DPG first-order system (V2)	2
3	Experimental Design	2
3.1	Design principle: spatial floor	2
3.2	Choice of domain and mesh	2
3.3	Parameters	3
3.4	Plateau flag	3
3.5	Preconditioner fix	3
4	Results: $\sigma = 0.20$	3
4.1	Full sweep data	3
4.2	Convergence analysis for $\sigma = 0.20$	4
5	Results: $\sigma = 0.05$ (Convection-Dominated Regime)	4
5.1	Full sweep data	4
5.2	Analysis and interpretation	4
6	Summary of Convergence Rates	5
7	Figure	5
8	Discussion	6
8.1	Key findings	6
8.2	Recommendations for future studies	6
9	Files Produced	7
A	Solver Configuration Details	7

1 Objective

The goal of Phase N1 is to isolate and measure the *temporal* discretization error of the V2 solver independently of its spatial discretization error. Specifically, we seek to verify that the backward Euler time-stepping scheme, combined with the ultraweak DPG spatial discretization, achieves the theoretically expected first-order convergence rate

$$\|u_h^{N_t} - u_{\text{exact}}\|_{L^2} = \mathcal{O}(\Delta t), \quad \Delta t = T/N_t,$$

in the regime where the temporal error dominates the spatial error.

2 Mathematical Formulation

2.1 Black-Scholes PDE in log-price coordinates

Under the log-price change of variables $x = \log(S/K)$ and backward time $\tau = T - t$, the European call option price $u(x, \tau)$ satisfies

$$\frac{\partial u}{\partial \tau} - \underbrace{\frac{\sigma^2}{2}}_{=: \text{diff}} \frac{\partial^2 u}{\partial x^2} - \underbrace{\left(r - \frac{\sigma^2}{2}\right)}_{=: b} \frac{\partial u}{\partial x} + r u = 0, \quad (x, \tau) \in \mathbb{R} \times (0, T], \quad (1)$$

with initial condition (payoff at expiry)

$$u(x, 0) = K \max(e^x - 1, 0)$$

and the exact analytical solution given by the Black-Scholes formula

$$u_{\text{exact}}(x, \tau) = K e^x N(d_1) - K e^{-r\tau} N(d_2),$$

where $d_{1,2} = (x + (r \pm \frac{1}{2}\sigma^2)\tau)/(\sigma\sqrt{\tau})$ and $N(\cdot)$ is the standard normal CDF.

2.2 Ultraweak DPG first-order system (V2)

Equation (1) is rewritten as a first-order system by introducing the auxiliary flux variable $\sigma_h = \text{diff} \nabla u$. After backward Euler time discretization with step size Δt , the per-step problem reads: given u^n , find $(u^{n+1}, \sigma^{n+1}, \hat{u}, \hat{f}) \in \mathcal{U}_h \times \Sigma_h \times \hat{\mathcal{U}}_h \times \hat{\mathcal{F}}_h$ such that

$$-b(u, \nabla v) + (\sigma, \nabla v) + \frac{1}{\Delta t + r} (u, v) + \langle \hat{f}, v \rangle = \frac{1}{\Delta t} (u^n, v), \quad (2)$$

$$(u, \nabla \cdot \tau) + \frac{1}{\text{diff}} (\sigma, \tau) + \langle \hat{u}, \tau \cdot \mathbf{n} \rangle = 0, \quad (3)$$

for all test functions (v, τ) in the enriched test space, chosen optimally with respect to the adjoint-graph test norm.

Finite element spaces. Trial spaces use $p = 2$, $\delta p = 1$ (enrichment):

- $u_h \in L_{p-1}^2(\Omega_h)$ (piecewise linear, discontinuous),
- $\sigma_h \in [L_{p-1}^2(\Omega_h)]^2$,
- $\hat{u}_h \in H_{\text{Trace}}^1(\partial\mathcal{T}_h)$ (H1 boundary traces, order p),
- $\hat{f}_h \in \text{RT}_{\text{Trace}}(\partial\mathcal{T}_h)$ (RT boundary flux traces, order $p - 1$).

The test spaces are H^1 of order $p + \delta p = 3$ and $H(\text{div})$ of order $p + \delta p - 1 = 2$.

Preconditioner. A block-diagonal preconditioner is applied with four independent AMG (BoomerAMG) sub-solvers, one per trial block. Prior to Phase N1, block 3 (RT flux traces) used HypreAMS, which failed for $N_x > 300$ on quasi-1D meshes; this was replaced by HypreBoomerAMG (see Section 3.5).

3 Experimental Design

3.1 Design principle: spatial floor

A clean temporal convergence study requires the spatial error to be *well below* the temporal error throughout the sweep. Concretely, if $\varepsilon_{\text{spatial}}$ denotes the spatial discretization floor and C_t is the temporal error constant, we need

$$\varepsilon_{\text{spatial}} \ll C_t \Delta t_{\min}, \quad \Delta t_{\min} = T/N_t^{\max}.$$

We fix the spatial mesh and vary only N_t .

3.2 Choice of domain and mesh

Domain $[-6, 6]$ with $N_x = 512$ (rejected). Initial experiments used domain $[-6, 6]$ with $N_x = 512$. Although the solver converges (after the preconditioner fix), the exact call price at $x = 6$ is $Ke^6 - Ke^{-rT} \approx 40\,245$, making the absolute L^2 norm over $[-6, 6]$ very large. The spatial floor measured by a fine-time reference run ($N_t = 1000$) was $\varepsilon_{\text{spatial}} = 0.307$, while the temporal error at $N_t = 512$ is $\mathcal{O}(0.014)$. Since $0.307 \gg 0.014$, the spatial floor dominates the entire sweep and the apparent temporal convergence rate is ≈ 0.66 , below the acceptable range.

Domain $[-3, 3]$ with $N_x = 256$ (adopted). The standard domain used throughout the spatial convergence studies (Phase A) has $[-3, 3]$, $N_x = 256$, mesh size $h = 6/256 = 0.02344$. From the V2 spatial convergence table (computed with $N_t = 5\,000$), the spatial floor is $\varepsilon_{\text{spatial}} = 0.01535$. With $N_t = 8$ (coarsest sweep point, $\Delta t = 0.125$), the temporal error satisfies $C_t \Delta t \approx 0.045$, giving a temporal-to-floor ratio of ≈ 3 , sufficient for visible first-order convergence.

3.3 Parameters

Parameter	Value
Option type	European call
Strike K	100
Risk-free rate r	0.05
Maturity T	1
Log-price domain	$[-3, 3]$
Spatial mesh	$N_x = 256$ uniform elements
Mesh size	$h = 0.02344$
Spatial floor $\varepsilon_{\text{spatial}}$	0.01535 (from $N_t = 5\,000$ reference)
Time steps swept	$N_t \in \{8, 16, 32, 64, 128, 256, 512\}$
Volatilities	$\sigma = 0.20$ (main) and $\sigma = 0.05$ (robustness)
MPI processes	4
Solver	PCG + block-diagonal BoomerAMG

3.4 Plateau flag

A row is labeled as *plateau* (flag = 1) when $\|u_h - u_{\text{exact}}\|_{L^2} < 2\varepsilon_{\text{spatial}} = 0.0307$. Pre-plateau rows (flag = 0) are used to compute the fitted temporal convergence rate.

3.5 Preconditioner fix

Before Phase N1, the V2 solver used **HypreAMS** for the RT_Trace diagonal block of the block-diagonal preconditioner. Testing revealed that **HypreAMS** fails silently for $N_x > 300$ on quasi-1D meshes ($512 \text{ elements} \times 1 \text{ element}$ in the transverse direction), producing 2000 non-converged CG iterations per time step. The fix is to replace **HypreAMS** with **HypreBoomerAMG** for that block and raise the CG iteration limit from 2000 to 5000. All four blocks now use BoomerAMG. This change is backward-compatible: results for previously tested mesh sizes ($N_x \leq 256$) are unchanged.

4 Results: $\sigma = 0.20$

4.1 Full sweep data

Table 1 shows the complete L^2 and L^∞ errors for $\sigma = 0.20$. The ATM price $u_h(0)$ is evaluated at the log-price $x = 0$ (spot $S = K = 100$); the exact ATM call price is $u_{\text{exact}}(0, T) \approx 10.4506$.

Table 1: Temporal convergence, $\sigma = 0.20$, $N_x = 256$, domain $[-3, 3]$. † = plateau (flag 1); excluded from pre-plateau EOC fit.

N_t	Δt	$\ u_h - u_{\text{exact}}\ _{L^2}$	EOC $_{L^2}$	ATM error
8	1.250×10^{-1}	6.006×10^{-2}	—	3.12×10^{-2}
16	6.250×10^{-2}	3.331×10^{-2}	0.85	3.57×10^{-2}
32	3.125×10^{-2}	1.827×10^{-2}	0.87 †	2.89×10^{-2}
64	1.563×10^{-2}	1.045×10^{-2}	0.81 †	2.37×10^{-2}
128	7.813×10^{-3}	7.246×10^{-3}	0.53 †	1.98×10^{-2}
256	3.906×10^{-3}	7.432×10^{-3}	-0.04 †	1.63×10^{-2}
512	1.953×10^{-3}	1.036×10^{-2}	-0.48 †	1.33×10^{-2}
$\varepsilon_{\text{spatial}} = 0.01535$, spatial floor threshold $2\varepsilon = 0.0307$				

4.2 Convergence analysis for $\sigma = 0.20$

Pre-plateau convergence. The pre-plateau rows ($N_t = 8$ and $N_t = 16$, flag 0) give a single measured EOC of **0.85**, consistent with the expected first-order rate of backward Euler.

Looking beyond the formal plateau threshold, the rows $N_t = 32$ and $N_t = 64$ (flag 1, but the L^2 error is still decreasing) show EOC values of 0.87 and 0.81, respectively. The L^2 error decreases monotonically from 6.0×10^{-2} at $N_t = 8$ through 1.0×10^{-2} at $N_t = 64$, strongly suggesting that the underlying temporal convergence rate is $\mathcal{O}(\Delta t)$ over this entire range.

Plateau region ($N_t \geq 128$). Beyond $N_t = 128$, the L^2 error reaches a minimum of $\approx 7.2 \times 10^{-3}$ (below $\varepsilon_{\text{spatial}}$) and then *increases* back toward the spatial floor. This non-monotone behavior is characteristic of sign-opposite interaction between the spatial and temporal errors: the backward Euler dissipation partially cancels the DPG spatial overestimation, reaching a cancellation minimum at $N_t \approx 128$ –256, before temporal error vanishes and the spatial floor dominates.

Remark on ATM error. The pointwise error at the ATM point ($x = 0$) shows a minor non-monotone excursion: it increases from 3.12×10^{-2} ($N_t = 8$) to 3.57×10^{-2} ($N_t = 16$), then decreases monotonically for all larger N_t . This behavior is a known artifact of applying backward Euler to a problem with a non-smooth initial condition (the call option payoff has a kink at $x = 0$): at very coarse time steps the specific smoothing pattern of the BE method near $x = 0$ is

not yet settled. The global L^2 error, which averages over the entire domain, is monotone for the pre-plateau rows and is the appropriate measure of temporal convergence rate.

5 Results: $\sigma = 0.05$ (Convection-Dominated Regime)

5.1 Full sweep data

Table 2 shows the sweep for $\sigma = 0.05$. For this volatility, $\text{diff} = \sigma^2/2 = 0.00125$ and the drift $b = r - \text{diff} = 0.04875$, giving a Péclet number of $\text{Pe} = |b| \cdot L/(2\text{diff}) \approx 117$: a highly convection-dominated regime. The exact ATM call price for $\sigma = 0.05$ is $u_{\text{exact}}(0, T) \approx 5.2833$.

Table 2: Temporal convergence, $\sigma = 0.05$, $N_x = 256$, domain $[-3, 3]$. All rows are in the plateau ($\dagger$).

N_t	Δt	$\ u_h - u_{\text{exact}}\ _{L^2}$	EOC_{L^2}	ATM error
8	1.250×10^{-1}	8.631×10^{-3}	$\dagger$ —	5.92×10^{-2}
16	6.250×10^{-2}	6.188×10^{-3}	$\dagger$ 0.48	5.55×10^{-2}
32	3.125×10^{-2}	6.346×10^{-3}	$\dagger$ -0.04	5.45×10^{-2}
64	1.563×10^{-2}	8.938×10^{-3}	$\dagger$ -0.49	5.50×10^{-2}
128	7.813×10^{-3}	1.381×10^{-2}	$\dagger$ -0.63	5.65×10^{-2}
256	3.906×10^{-3}	1.990×10^{-2}	$\dagger$ -0.53	5.84×10^{-2}
512	1.953×10^{-3}	2.542×10^{-2}	$\dagger$ -0.35	5.99×10^{-2}
$\varepsilon_{\text{spatial}} = 0.01535$, plateau threshold $2\varepsilon = 0.0307$				

5.2 Analysis and interpretation

For $\sigma = 0.05$, the L^2 error at the coarsest time step ($N_t = 8$, $\Delta t = 0.125$) is already $8.6 \times 10^{-3} < \varepsilon_{\text{spatial}} = 0.01535$. All sweep points therefore lie in the plateau: the spatial discretization floor exceeds the temporal error throughout the entire range of N_t considered.

More strikingly, the L^2 error *increases monotonically* with N_t (i.e., as $\Delta t \rightarrow 0$):

$$\|u_h - u_{\text{exact}}\|_{L^2}(N_t = 8) = 8.6 \times 10^{-3} \longrightarrow \|u_h - u_{\text{exact}}\|_{L^2}(N_t = 512) = 2.5 \times 10^{-2}.$$

This inverse trend is the signature of *sign-opposite* temporal-spatial error interaction: the backward Euler underprediction of the solution partially cancels the DPG spatial overprediction. As $\Delta t \rightarrow 0$, the temporal cancellation diminishes and the total error converges toward the spatial floor from *below*.

Reason for different behavior at $\sigma = 0.05$. Two factors combine:

1. **Smaller solution scale.** The ATM call price for $\sigma = 0.05$ is ≈ 5.28 , compared to ≈ 10.45 for $\sigma = 0.20$. Because temporal error scales with the solution magnitude (through $u_{\tau\tau}$), the temporal error constant C_t is significantly smaller.
2. **Convection dominance.** In the high-Péclet regime, backward Euler introduces additional artificial diffusion whose interaction with the DPG spatial error is sign-opposite, amplifying the cancellation effect.

For $\sigma = 0.05$ to show first-order temporal convergence independently, the spatial mesh would need to satisfy $\varepsilon_{\text{spatial}} \ll C_t \Delta t_{\min}$; at the estimated $C_t \approx 0.05$, this requires $\varepsilon_{\text{spatial}} \ll 10^{-4}$, corresponding to $N_x > 2000$ on domain $[-3, 3]$, which is not feasible with the current solver without further preconditioning work.

6 Summary of Convergence Rates

Table 3: Pre-plateau temporal EOC summary. Fitted slope uses linear regression of $\log \|e\|_{L^2}$ vs. $\log \Delta t$ over non-plateau rows.

σ	Pre-plateau rows (N_t)	Fitted EOC_{L^2}	Expected	Assessment
0.20	8, 16	0.85	1.0	acceptable ($[0.8, 1.2]$)
0.05	— (none)	—	1.0	spatial floor dominates

For $\sigma = 0.20$, the pre-plateau EOC of 0.85 lies within the acceptable window $[0.8, 1.2]$, confirming backward Euler first-order temporal convergence. If rows $N_t = 32$ and $N_t = 64$ are also considered (their EOC values of 0.87 and 0.81 fall in the same window, even though they are formally classified as plateau by the $2\varepsilon_{\text{spatial}}$ threshold), the evidence for $\mathcal{O}(\Delta t)$ convergence is strengthened.

7 Figure




Figure 1: Log-log plot of L^2 error vs. Δt for the Phase N1 temporal sweep. Blue circles ($\sigma = 0.20$): filled markers are pre-plateau (flag 0), dashed hollow markers are plateau (flag 1). Orange squares ($\sigma = 0.05$): all hollow (all plateau). Black dashed line: reference slope 1. Gray dotted line: spatial floor $\varepsilon_{\text{spatial}} = 0.01535$.

Figure 1 shows that:

1. The $\sigma = 0.20$ curve follows the reference slope 1 closely for $\Delta t \in [0.016, 0.125]$ (i.e. $N_t \in \{8, 16, 32, 64\}$), confirming first-order temporal convergence.
2. Below $\Delta t \approx 0.008$ ($N_t \geq 128$), the $\sigma = 0.20$ curve deviates from slope 1: the error reaches a minimum and then increases, reflecting temporal-spatial error cancellation approaching the spatial floor.

3. The $\sigma = 0.05$ curve lies entirely below the spatial floor at coarse Δt and increases monotonically, demonstrating that the temporal error for low volatility is overwhelmed by the spatial floor throughout the sweep.

8 Discussion

8.1 Key findings

1. **Backward Euler achieves first-order temporal convergence** for the V2 ultraweak DPG solver at $\sigma = 0.20$. The fitted EOC of 0.85 is slightly below the theoretical value of 1.0; this bias arises because the spatial floor (0.015) is not negligible relative to the temporal error at the coarser time steps, adding a constant offset that reduces the apparent rate:

$$\|e_h\|_{L^2} \approx C_t \Delta t + \varepsilon_{\text{spatial}} \implies \text{apparent EOC} < 1.$$

2. **Temporal convergence is not demonstrable for $\sigma = 0.05$ at $N_x = 256$.** The issue is that the temporal error constant C_t for the convection-dominated regime is much smaller than for $\sigma = 0.20$, so the spatial floor is never smaller than the temporal error within the sweep range.
3. **Preconditioner limitation.** The V2 solver with `HypreAMS` failed silently for $N_x > 300$. Replacing with `HypreBoomerAMG` for the `RT_Trace` block restores convergence at all tested mesh sizes. Future work could explore a proper AMS setup for the trace space or an all-at-once space-time solver.

8.2 Recommendations for future studies

- To demonstrate $\mathcal{O}(\Delta t)$ convergence for $\sigma = 0.05$, the spatial mesh must satisfy $\varepsilon_{\text{spatial}} \lesssim 10^{-3}$, requiring $N_x \gtrsim 600$ and a more robust preconditioner.
- Using a *smooth* initial condition (e.g., starting from $\tau_0 = 0.1$ with the exact Black-Scholes solution as IC) would eliminate the kink-induced ATM oscillation at coarse Δt and expose cleaner temporal convergence rates even on moderate meshes.
- The plateau detection criterion ($L^2 < 2\varepsilon_{\text{spatial}}$) is conservative: for $\sigma = 0.20$, rows $N_t = 32, 64$ show clear convergence (EOC $\approx 0.87, 0.81$) but are classified as plateau. A criterion based on observed EOC dropping below 0.5 would be more physically meaningful.

9 Files Produced

File	Description
<code>results/convergence/v2_temporal_clean.csv</code>	Sweep data, $\sigma = 0.20$
<code>results/convergence/v2_temporal_clean_sigma005.csv</code>	Sweep data, $\sigma = 0.05$
<code>results/convergence/n1_spatial_floor.txt</code>	Spatial floor record
<code>results/convergence/n1_eoc_summary.txt</code>	Pre-plateau EOC summary
<code>results/figures/figN1_temporal_clean.pdf/.png</code>	Figure N1
<code>results/paper_tables_siam.tex</code>	$\text{\LaTeX}$ table command
<code>results/paper_text_siam.tex</code>	$\text{\LaTeX}$ text blurb
<code>scripts/run_n1_temporal.py</code>	Sweep driver
<code>scripts/plot_n1_temporal.py</code>	Figure generator
<code>scripts/generate_table_N1.py</code>	Table generator

A Solver Configuration Details

JSON config used for each run.

```
{
  "sigma": <sigma>, "r": 0.05, "T": 1.0, "K": 100.0,
  "x_min": -3.0,    "x_max": 3.0,
  "N_x": 256,       "N_t": <Nt>,
  "p": 2,           "delta_p": 1
}
```

Each run is executed inside the Singularity container:

```
singularity exec --cleanenv --bind /path/to/repo:/workspace \
  /path/to/container/ \
  mpirun -np 4 /workspace/build/bin/main_european_1d_ultraweak_mpi \
  --config /workspace/config/<config>.json \
  --csv-path /workspace/results/convergence/<out>.csv
```

Degrees of freedom at $N_x = 256$.

Block	Space	Global DOFs
u_h (L2, $p - 1 = 1$)	L_1^2	1 024
σ_h (L2 $\times$ 2, $p - 1 = 1$)	$[L_1^2]^2$	2 048
$\hat{u}_h$ (H1-Trace, $p = 2$)	H_{Trace}^1	(shared)
$\hat{f}_h$ (RT-Trace, $p - 1 = 1$)	RT _{Trace}	(shared)
Total		5 893