AI CODE EVALUATION PLATFORM

Two Sum - Evaluation report

Submission label	Corrected reference
Submission ID	35578fdc-bbbf-4e65-bbdd-0ef5eaf64884
Challenge	Two Sum
Evaluated (UTC)	2026-10-17T18:27:40.927975+00:00
Source label	trusted-example
Mode	trusted
Test pass rate	5/5 (100.00%)
Completed-case time	5.065 ms
Ruff	completed; 0 findings
Reference verified	True
Runtime	CPython 3.12.14
Candidate SHA-256	8cf428b414c00da94e973168fe1ac606 f39f9afb47f430ec81f48ccecfb4a06f

5/5 deterministic tests passed. Test pass rate is not code coverage or proof of general correctness. All reference checks passed.

Deterministic test pass rate is not code coverage or proof of correctness. Timings are single measurements, include interpreter work and exclude container startup. Timed-out or resource-terminated cases have no completed duration. RSS includes the interpreter (Linux KiB). Hidden edge cases are revealed after evaluation for reproducible debugging.

basic - passed

hidden: False

input: {"nums": [2, 7, 11], "target": 9}

expected: [0, 1]

actual: [0, 1]

error: None

duration_ms: 0.835154

reference_duration_ms: 0.920703

peak_rss_kib: 42496

no-reuse - passed

hidden: True

input: {"nums": [3], "target": 6}

expected: []

actual: []

error: None

duration_ms: 0.895415

reference_duration_ms: 1.271931

peak_rss_kib: 42496

repeated - passed

hidden: True

input: {"nums": [3, 3], "target": 6}

expected: [0, 1]

actual: [0, 1]

error: None

duration_ms: 1.199722

reference_duration_ms: 1.134665

peak_rss_kib: 42496

empty - passed

hidden: True

input: {"nums": [], "target": 0}

expected: []

actual: []

error: None

duration_ms: 1.073362

reference_duration_ms: 0.909557

peak_rss_kib: 42496

negative - passed

hidden: True

input: {"nums": [-4, 2, 5], "target": 1}

expected: [0, 2]

actual: [0, 2]

error: None

duration_ms: 1.061615

reference_duration_ms: 0.882195

peak_rss_kib: 42496

Static analysis

[]

Candidate source

```
def solve(nums, target):
    seen = {}
    for i, value in enumerate(nums):
        if target - value in seen:
            return [seen[target - value], i]
        seen.setdefault(value, i)
    return []
```

Execution limits

{
"wall_seconds_per_case": 3,
"cpu_seconds_per_case": 1,
"memory_mib": 128,
"output_bytes": 65536,
"docker_pids": 16,
"network": "none",
"scope": "per test; RSS includes interpreter; Linux KiB; time excludes container startup"
}