

Noisy labels

Alicja Gosiewska, Mateusz Staniak

29 XI 2018

- label noise: as anything that obscures the relationship between the features of an instance and its class (Ray J. Hickey, *Noise modelling and evaluating learning from examples*).
- unreliable labels.

Types of noise

- Noisy Completely at random (NCAR).
- Noisy at random (NAR): probability of incorrect class depends on the true class.
- Noit not at random (NNAR): probability of incorrect class depends on the on true class and features.

Label noise is known to

- decrease model performance,
- increase model complexity.

1. Robust models

- specialized models (e.g. logistic regression with noise label-correction),
- choice of model hyper-parameters (e.g. split criterion in decision trees).

2. Data Cleansing

- anomaly and outlier detection,
- influential observations,
- removing misclassified instances,
- kNN-based methods,
- voting filtering

Identifying and Eliminating Mislabeled Training Instances

Identifying Mislabeled Training Data Brodley, C. E., & Friedl, M. A. (1999). *Journal of Artificial Intelligence Research*, 11, 131–167.


- The approach employs an ensemble of classifiers that serve as a filter for the training data.
- The idea: using a set of classifiers formed from part of the training data to test whether instances in the remaining part of the training data are mislabeled.
- m learning algorithms, n -fold cross-validation
- consensus vote - all classifier must agree

3. Removing just the labels (turns the problem into semi-supervised, example of semi-sup: The R Package bgmm: Mixture Modeling with Uncertain Knowledge)
4. Probabilistic frameworks

Training deep neural-networks based on unreliable labels. Bekker, A. J., & Goldberger, J. (2016). In 2016 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP).

- multi-class neutral-network
- adding extra noise layer by assuming that the observed labels were created from the true labels by passing through a noisy channel whose parameters are unknown

Training deep neural-networks based on unreliable labels



- Since the random variables y_i are hidden, we apply the EM algorithm to find the maximum-likelihood parameter set.

Applications to microarrays

Detecting potential labeling errors in microarrays by data perturbation, Andrea Malossini, Enrico Blanzieri, Raymond T. Ng (2006).

- A Matrix called LOOPC (Leave-One-Out Perturbed Classification) is built: $\text{LOOPC}[i, j]$ is the result of flipping the label of x_i and leaving x_j out of the sample.
- $\text{LOOPC}[i,]$: predictions of different observations based on the same dataset (x_i removed).
- $\text{LOOPC}[, j]$: predictions for x_j based on different datasets.
- Column analysis: classification stability algorithm. Correctly labeled samples should be classified consistently despite small perturbations.
- Row analysis: Leave-One-Out-Error-sensitivity algorithm. If an observation is mislabeled, flipping the label should improve model performance.



A. J. Bekker and J. Goldberger.

Training deep neural-networks based on unreliable labels.

In 2016 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), pages 2682–2686, Shanghai, Mar. 2016. IEEE.



C. E. Brodley and M. A. Friedl.

Identifying and Eliminating Mislabeled Training Instances.

page 7.



C. E. Brodley and M. A. Friedl.

Identifying Mislabeled Training Data.

Journal of Artificial Intelligence Research, 11:131–167, Aug. 1999.



B. Frenay.

Uncertainty and Label Noise in Machine Learning.

page 268.



N. Hughes, S. Roberts, and L. Tarassenko.

Semi-supervised learning of probabilistic models for ECG segmentation.

In The 26th Annual International Conference of the IEEE Engineering in Medicine and Biology Society, volume 3, pages 434–437, San Francisco, CA, USA, 2004. IEEE.



C. P. Lam, D. G. Stork, and M. Park.

Evaluating Classifiers by Means of Test Data with Noisy Labels.

page 6.



N. D. Lawrence and B. Schölkopf.

Estimating a Kernel Fisher Discriminant in the Presence of Label Noise.

In *ICML*, 2001.



A. Malossini, E. Blanzieri, and R. T. Ng.

Detecting potential labeling errors in microarrays by data perturbation.

Bioinformatics, 22(17):2114–2121, Sept. 2006.



N. Natarajan, I. S. Dhillon, P. K. Ravikumar, and A. Tewari.

Learning with Noisy Labels.

page 9.



U. Rebbapragada, C. E. Brodley, D. Sulla-Menashe, and M. A. Friedl.

Active Label Correction.

In 2012 IEEE 12th International Conference on Data Mining, pages 1080–1085, Dec. 2012.



R. Sloan.

Types of Noise in Data for Concept Learning.

In Proceedings of the First Annual Workshop on Computational Learning Theory, COLT '88, pages 91–96, San Francisco, CA, USA, 1988. Morgan Kaufmann Publishers Inc.



H. Valizadegan and P.-N. Tan.

Kernel Based Detection of Mislabeled Training Examples.

In C. Apte, D. Skillicorn, B. Liu, and S. Parthasarathy, editors, *Proceedings of the 2007 SIAM International Conference on Data Mining*, pages 309–319. Society for Industrial and Applied Mathematics, Philadelphia, PA, Apr. 2007.



S. Verbaeten and A. V. Assche.

Ensemble Methods for Noise Elimination in Classification Problems.

2003.



D. R. Wilson.

Reduction Techniques for Instance-Based Learning Algorithms.
page 30.



C. Zhang, C. Wu, E. Blanzieri, Y. Zhou, Y. Wang, W. Du, and Y. Liang.
**Methods for labeling error detection in microarrays based on
the effect of data perturbation on the regression model.**
Bioinformatics, 25(20):2708–2714, Oct. 2009.