# ELO: interpretable score of model predictive power

Alicja Gosiewska Mateusz Bakała Katarzyna Woźnica Maciej Zwoliński dr hab. inż. Przemysław Biecek

October 9, 2019



### Contents

1 Motivation: Problems of used performance measure

What is Elo ranking system?

3 EloML



### **Problems**

Team	AUC
Erkut & Mark,Google AutoML	0.618492
Erkut & Mark	0.616913
Google AutoML	0.615982
Erkut & Mark, Google AutoML, Sweet Deal	0.615858
Sweet Deal	0.615766
Arno Candel @ H2O.ai	0.615492
ALDAPOP	0.615040
9hr Overfitness	0.614371
Shlandryn	0.614132
Erin (H2O AutoML 100 mins)	0.612657

Table: Top 10 results of KaggleDays SF competition in 2019.  ${\tt https://www.kaggle.com/antgoldbloom/analyzing-kaggledays-sf-competition-data/notebook}$ 



### **Problems**

Team	AUC
Erkut & Mark,Google AutoML	0.618492
Erkut & Mark	0.616913
Google AutoML	0.615982
Erkut & Mark, Google AutoML, Sweet Deal	0.615858
Sweet Deal	0.615766
Arno Candel @ H2O.ai	0.615492
ALDAPOP	0.615040
9hr Overfitness	0.614371
Shlandryn	0.614132
Erin (H2O AutoML 100 mins)	0.612657

Table: Top 10 results of KaggleDays SF competition in 2019. https://www.kaggle.com/antgoldbloom/analyzing-kaggledays-sf-competition-data/notebook

Weakness 1: There is no interpretation of differences in performance



### **Problems**

Team	AUC
Erkut & Mark,Google AutoML	0.618492
Erkut & Mark	0.616913
Google AutoML	0.615982
Erkut & Mark,Google AutoML,Sweet Deal	0.615858
Sweet Deal	0.615766
Arno Candel @ H2O.ai	0.615492
ALDAPOP	0.615040
9hr Overfitness	0.614371
Shlandryn	0.614132
Erin (H2O AutoML 100 mins)	0.612657

Table: Top 10 results of KaggleDays SF competition in 2019. https://www.kaggle.com/antgoldbloom/analyzing-kaggledays-sf-competition-data/notebook

Weakness 1: There is no interpretation of differences in performance Weakness 2: There is no procedure for assessing the significance of the difference in performances

k	AUC AutoML_1	AUC AutoML_2
1	0.8	0.9
2	0.8	0.78
3	0.8	0.78
4	0.8	0.78
Mean AUC	0.8	0.81

Table: Artifficial results from 4-fold cross-validation.



k	AUC AutoML $_{-}1$	AUC AutoML_2
1	0.8	0.9
2	0.8	0.78
3	0.8	0.78
4	0.8	0.78
Mean AUC	0.8	0.81

Table: Artifficial results from 4-fold cross-validation.

Weakness 3: You cannot assess the stability of the performance in cross-validation folds



Team Name	AUC
Asian Ensemble	0.8043
.baGGaj.	0.8039
Erkut & Mark,Google AutoML	0.8039
ARG eMMSamble	0.8037
n₋m	0.8021

Team Name	AUC
alijs	0.9562
7777777777777	0.9559
ML Keksika	0.9546
krivoship	0.9544
2 old mipt dogs	0.9543

Table: Springleaf Marketing Response Kaggle Competition, https://www.kaggle.com/c/springleaf-marketing-response

Table: IEEE-CIS Fraud Detection Kaggle Competition,

https://www.kaggle.com/c/ieee-fraud-detection



Team Name	AUC
Asian Ensemble	0.8043
.baGGaj.	0.8039
Erkut & Mark,Google AutoML	0.8039
ARG eMMSamble	0.8037
n_m	0.8021

Team Name	AUC
alijs	0.9562
7777777777777	0.9559
ML Keksika	0.9546
krivoship	0.9544
2 old mipt dogs	0.9543

Table: Springleaf Marketing Response Kaggle Competition, https://www.kaggle.com/c/springleaf-marketing-response

Table: IEEE-CIS Fraud Detection Kaggle Competition, https://www.kaggle.com/c/ ieee-fraud-detection

Weakness 4: You cannot compare performances between data sets



# What is Elo ranking system?

#### Elo is used in:

- chess
- football and basketball ratings

Pros: The difference between Elo ratings of two players can be transferred into probabilities of winning when they play against each other.





# What is Elo ranking system?

Elo is used in:

- chess
- football and basketball ratings

Pros: The difference between Elo ratings of two players can be transferred into probabilities of winning when they play against each other.



• rating is calculated on the basis of two components, result of match and rating of the opponent, The scores are updated after each match

$$E_1 = \frac{1}{1 + 10^{\frac{(S_1 - S_2)}{400}}}.$$

$$S_1' = S_1 + K(A_1 - E_1),$$



### Calculating ELO for predictive power

Let  $p_{i,j}$  be the probability of model  $M_i$  wining with model  $M_j$ 

$$logit(p_{i,j}) = \beta_{M_i} - \beta_{M_j}$$
.

For larger number of models:

$$logit(p_{i,j}) = \beta_{M_1} x_{M_1} + \beta_{M_2} x_{M_2} + ... + \beta_{M_k} x_{M_n}$$

where

$$x_{M_a} = egin{cases} 1 & \text{if } a = i \\ -1 & \text{if } a = j \\ 0 & \text{otherwise} \end{cases}$$





### Calculating ELO for predictive power

Let  $p_{i,j}$  be the probability of model  $M_i$  wining with model  $M_j$ 

$$logit(p_{i,j}) = \beta_{M_i} - \beta_{M_j}$$
.

For larger number of models:

$$logit(p_{i,j}) = \beta_{M_1} x_{M_1} + \beta_{M_2} x_{M_2} + ... + \beta_{M_k} x_{M_n}$$

where

$$x_{M_a} = \begin{cases} 1 & \text{if } a = i \\ -1 & \text{if } a = j \\ 0 & \text{otherwise} \end{cases}$$

We use logistic regression with contrast matrix.







Figure: Our novel concept of Elo-based model ranking. Colors represent machine learning algorithms, gradients represent sets of hyperparameters, border styles represent data set.



# Expected vs. Actual Results





### The advantages of ELO


ELO score provides the direct interpretation in terms of probability

$$p_{i,j} = invlogit(eta_{M_i} - eta_{M_j}) = rac{e^{eta_{M_i} - eta_{M_j}}}{1 + e^{eta_{M_i} - eta_{M_j}}}.$$


- There is a procedure for assessing the significance of the difference in performances
- You can assess the stability of the performance in cross-validation folds
- You can compare performances between data sets



# Tunability



# Comparison between datasets





https://github.com/ModelOriented/EloML

