



**SAP Note 2399979 presents a tool that can help with monitoring tasks**

2399979 - How-To: Configuring automatic SAP HANA Data Collection with SAP HANASitter

- It is a python script to be downloaded from <https://github.com/chriselswede/hanasitter>
- It is intended to be executed as <sid>adm on your SAP HANA Server (since then the proper python version is already in your path, installed together with SAP HANA)
- It connects via host, port and DB user, provided in hdbuserstore

<https://github.com/chriselswede/hanasitter>



chriselswede Add files via upload



README.md



hanasitter.pdf



hanasitter.py



hanasitter\_configfile\_example.txt



Host, port and DB user needs to be provided in the hdbuserstore:

```
mo-fc8d991e0:~> hdbuserstore SET HANASITTER1KEY mo-fc8d991e0:30015 HANASITTER1 PassWord1
mo-fc8d991e0:~> hdbuserstore LIST
DATA FILE      : /usr/sap/CH0/home/.hdb/mo-fc8d991e0/SSFS_HDB.DAT
KEY FILE       : /usr/sap/CH0/home/.hdb/mo-fc8d991e0/SSFS_HDB.KEY

KEY HANASITTER1KEY
  ENV : mo-fc8d991e0:30015
  USER: HANASITTER1
```

Then the hanasitter can connect using the info stored in hdbuserstore:

```
mo-fc8d991e0:/tmp/HANASitter> whoami
ch0adm
mo-fc8d991e0:/tmp/HANASitter> python hanasitter.py -k HANASITTER1KEY -nc 1
DB Address = , mo-fc8d991e0 , DB Instance = , 00
Online, Primary and Not-secondary Check: , Every 3600 seconds
Ping Check:      , Every 60 seconds, Ping Timeout = , 60 seconds
Thread Checks:   , Every 60 seconds, Thread Checker Timeout = , 60 seconds
```



The user that hanasitter uses to connect can be treated as a technical user

The user needs CATALOG READ and it must be a standard user

The user could be treated as a technical user, i.e. that its password should not expire

**HANASITTER1**

☐ Disable ODBC/JDBC access

**Authentication**

☒ Password  
Password\*: ..... Confirm\*: .....  
Force password change on next logon: ☐ Yes ☒ No

☐ Kerberos  
External ID\*: .....

☐ SAML [Configure](#)

☐ X509 [Configure](#)

Valid From: 05.04.2017 21:50:29 GMT+02:00 Valid Until: .....

**HANASITTER1**

☐ Disable ODBC/JDBC access

**Authentication**

☒ Password  
Password\*: .....  
Force password change on next logon: ☐ Yes ☐ No

☐ Kerberos  
External ID\*: .....

Valid From: 04.08.2017 12:46:40 GMT+02:00

Session Client: .....

**Granted Roles** **System Privileges** **Object Privileges**

System Privilege	Grantor
🔑 CATALOG READ	SYSTEM



First check tests if HANA is online, i.e. that

- all services are running
- it is the primary instance (in case of a system replication setup)
- it is a worker node (in case of a scale-out scenario)

If not online, it sleeps, by default, 1 hour and then tests if it is online again

The online test interval can be controlled by the `-oi` flag

Flag	Unit	Details	Explanation	Default
<code>-oi</code>	sec	online test interval	time it waits before it checks again if DB is online, primary (in SysRep scenario), and not-secondary (in ScaleOut scenario)	3600

## Example:

The online check finds that this HANA is secondary, therefore HANASitter will not do anything for a while

```
haladm@dewdfglp00765:/tmp/HANASitter> python hanasitter.py -nc 1
Host = dewdfglp00765, DB Instance = 00, Single DB System
Online, Primary and Not-Secondary Check: Interval = 3600 seconds
Action          , Timestamp          , Duration          , Successful , Result , Comment
Online Check    , 2017-06-09 09:53:43 , -                 , True       , True   , Number running services: 7 out of 7
Primary Check   , 2017-06-09 09:53:46 , -                 , True       , False ,
One of the online checks found out that this HANA instance is not online. HANASitter will now have a 3600 seconds break.
```



If HANA is online the hanasitter starts “tracking” using three types of checks

1. CPU Check
2. Ping Check
3. Critical Feature Checks

If any of these checks finds a critical situation hanasitter starts to “record”, using four possible types of recording

1. GStacks
2. Kernel Profiler Trace
3. Call Stacks
4. RTE Dumps

If no recording was done, the tracking checks will restart after `-ci` seconds

If recording was done, hanasitter will exit (`-ar < 0`) or break `-ar` seconds before restarting the online check and tracking

Flag	Unit	Details	Explanation	Default
<code>-ci</code>	sec	check interval	time it waits before tracking checks restart (if no recording was done)	60
<code>-ar</code>	sec	after recording	time it waits before online check and tracking after recording	-1 (exit)



First tracking check (which is non-compulsory) tests if HANA is currently using too much CPU

The CPU check can consist of a number of CPU readings with a time interval between each readings; then the CPU check is done over a period

The CPU test can be controlled by the `-cpu` flag which has 4 items

Flag	Unit	Details	Explanation	Default
<code>-cpu</code>	, #, sec, %	CPU test	this flag should be followed by 4 items separated by only a comma; <1 <sup>st</sup> item>,<2 <sup>nd</sup> item>,<3 <sup>rd</sup> item>,<4 <sup>th</sup> item> <ul style="list-style-type: none"> <li>1<sup>st</sup> item defines CPU type, 0=not used, 1=user cpu, 2=system cpu</li> <li>2<sup>nd</sup> item defines number of CPU readings</li> <li>3<sup>rd</sup> item defines the interval between the CPU readings [sec]</li> <li>4<sup>th</sup> item sets a limit of average used CPU for all readings [%]</li> </ul>	0,0,0,100 (not used)

#### Example:

System CPU is checked with the average CPU over 5 readings with 5 seconds intervals with the limit 1 % The result turns out to be almost 4 %, so hanasitter starts to record

```
haladm@dewdfglp00766:/tmp/HANASitter> python hanasitter.py -cpu 2,5,5,1 -nc 1
Host = dewdfglp00766, DB Instance = 00, Single DB System
Action      , Timestamp      , Duration      , Successful    , Result        , Comment
Online Check , 2017-06-09 10:11:42 , -            , True         , True         , Number running services: 7 out of 7
Primary Check , 2017-06-09 10:11:44 , -            , True         , True         ,
Non-standby Check , 2017-06-09 10:11:44 , -            , True         , True         ,
System CPU Check , 2017-06-09 10:12:09 , 0:00:25.009656 , True         , False        , Av. CPU = 3.67 % (Allowed = 1 %)
Call Stack Record , 2017-06-09 10:12:10 , 0:00:00.301395 , -            , -            , /tmp/hanasitter_output/callstack_2017
```



Second tracking check tries to connect to the database with a simple ping statement:

```
select * from dummy
```

If there is no response after `-pt` seconds, HANA is considered unresponsive, i.e. we have a “hanging” situation

Flag	Unit	Details	Explanation	Default
<b>-pt</b>	sec	ping timeout	time it waits before the DB is considered unresponsive during a ping test (select * from dummy)	60

## Example:

Here the ping timeout was defined to only 1 second and there was no response from HANA within this time  
HANA is considered unresponsive and recording starts

```
DEWDFGLP00765:/tmp/HANASitter> python hanasitter.py -pt 1 -nc 1
DB Address = , localhost , DB Instance = , 00
Ping Check      , 2017-04-10 01:04:12      , 0:00:01.000700      , -      , False      , No response from DB within 1 seconds.
Call Stack Record , 2017-04-10 01:04:13      , 0:00:01.281263      , -      , -      , /tmp/nanasitter_output/callstack_2017-0
```





## Third tracking check searches for, user defined, critical features - The flag `-cf` has two different modes:

1. One Column; a column in an `M_` view, a value and maximum number counts of that “feature”, or
2. Where Clause; an `M_` view, a where clause and maximum number counts of that where clause

Flag	Unit	Details	Explanation	Default
<b>-cf</b>	-	list of critical features	<p>a list, surrounded by “, of multiples of 4 items, separated by a comma only; “&lt;1<sup>st</sup> item&gt;, ..., &lt;4<sup>th</sup> item&gt;, ..., &lt;1<sup>st</sup> item&gt;, ..., &lt;4<sup>th</sup> item&gt;”</p> <p>1. One column mode:</p> <ul style="list-style-type: none"> <li>• 1<sup>st</sup> item defines a monitoring view, i.e. a <code>SYS.M_*</code> view</li> <li>• 2<sup>nd</sup> item defines a column in the view</li> <li>• 3<sup>rd</sup> item defines a possible value of column specified by 2<sup>nd</sup> item (* possible)</li> <li>• 4<sup>th</sup> item sets a limit of number of counts allowed for that feature (default, &lt;i&gt;, and &lt;i&gt;: maximum number, &gt;i&gt;: minimum number, where &lt;i&gt; is an integer)</li> </ul> <p>2. Where clause mode:</p> <ul style="list-style-type: none"> <li>• 1<sup>st</sup> item defines a monitoring view, i.e. a <code>SYS.M_*</code> view</li> <li>• 2<sup>nd</sup> item is the keyword <code>WHERE</code></li> <li>• 3<sup>rd</sup> item defines a complete sql where clause</li> <li>• 4<sup>th</sup> item sets a limit of number of counts allowed for that feature (default, &lt;i&gt;, and &lt;i&gt;: maximum number, &gt;i&gt;: minimum number, where &lt;i&gt; is an integer)</li> </ul>	“ (not used)
<b>-tf</b>	sec	feature check timeout	time it waits before the DB is considered unresponsive during a feature check (see above)	60
<b>-lf</b>	true/ false	log critical features	true → all info of the critical feature states defined by <code>-cf</code> will be logged, in the log directory in a <code>criticalFeatures</code> log file	false



# HANASitter – Critical Feature Checks (2/5)



## Example:

Here 2 critical feature checks are defined by only allowing

- 1 unload from table VARINUM
- 10 threads with the state IS\_ACTIVE = TRUE

After the ping check the first feature check finds 0 unloads from table VARINUM, then the second feature check finds 11 threads that are active, this is more than allowed, so recording starts

```
mo-fc8d991e0:/tmp/HANASitter> python hanasitter.py -cf "M_CS_UNLOADS,TABLE_NAME,VARINUM,1,M_SERVICE_THREADS,IS_ACTIVE,TRUE,10" -nc 1
Host = mo-fc8d991e0, DB Instance = 00, Single DB System
Online, Primary and Not-Secondary Check: Interval = 3600 seconds
Ping Check: Interval = 60 seconds, Timeout = 60 seconds
Feature Checks: Interval 60 seconds, Timeout = 60 seconds
Feature Check 1, allows maximum 1 features in the state, TABLE_NAME = VARINUM, in the view, M_CS_UNLOADS
Feature Check 2, allows maximum 10 features in the state, IS_ACTIVE = TRUE, in the view, M_SERVICE_THREADS
Recording mode: 1
Recording Type      , Number Recordings , Intervals [seconds] , Durations [seconds] , Wait [milliseconds]
GStack              , 0                  , 60                  ,                      , 0
Kernel Profiler     , 0                  , 60                  , 60                  , 0
Call Stack          , 1                  , 60                  ,                      , 0
RTE Dumps           , 0                  , 60                  ,                      , 0
After Recording: Exit
Action      , Timestamp          , Duration          , Successful , Result , Comment
Online Check , 2017-06-11 16:26:22 , -                 , True       , True   , Number running services: 11 out of 11
Primary Check , 2017-06-11 16:26:28 , -                 , True       , True   ,
Non-standby Check , 2017-06-11 16:26:28 , -                 , True       , True   ,
Ping Check    , 2017-06-11 16:26:28 , 0:00:00.164583    , -          , True   , DB responded faster than 60 seconds
Feature Check 1 , 2017-06-11 16:26:30 , 0:00:01.668655    , True       , True   , # Critical Features = 0 (allowed = 1), 0
Feature Check 2 , 2017-06-11 16:26:30 , 0:00:00.264757    , True       , False  , # Critical Features = 11 (allowed = 10)
Call Stack Record , 2017-06-11 16:26:30 , 0:00:00.101899    , -          , -      , /tmp/hanasitter_output/callstack_2017-06
```

# HANASitter – Critical Feature Checks (3/5)



## Example:

Here 1 critical feature check is defined by only allowing 1 indexserver thread to be active

The feature check finds 3 indexserver threads that are active, this is more than allowed, so recording starts

```
mo-fc8d991e0:/tmp/HANASitter> python hanasitter.py -cf "M_SERVICE_THREADS,WHERE,IS_ACTIVE='TRUE' and SERVICE_NAME='indexserver',1" -nc 1
Host = mo-fc8d991e0, DB Instance = 00, Single DB System
Online, Primary and Not-Secondary Check: Interval = 3600 seconds
Ping Check: Interval = 60 seconds, Timeout = 60 seconds
Feature Checks: Interval 60 seconds, Timeout = 60 seconds
Feature Check 1, allows maximum 1 features from the where clause = IS_ACTIVE='TRUE' and SERVICE_NAME='indexserver', in the view, M_SERVICE_THREADS
Recording mode: 1
Recording Type      , Number Recordings      , Intervals [seconds] , Durations [seconds]   , Wait [milliseconds]
GStack              , 0                        , 60                  ,                        , 
Kernel Profiler     , 0                        , 60                  , 60                     , 0
Call Stack          , 1                        , 60                  ,                        , 
RTE Dumps           , 0                        , 60                  ,                        , 
After Recording: Exit
Action              , Timestamp                , Duration            , Successful             , Result                , Comment
Online Check        , 2017-06-11 16:32:51      , -                   , True                   , True                  , Number running services: 11 out of 11
Primary Check       , 2017-06-11 16:32:58      , -                   , True                   , True                  , 
Non-standby Check   , 2017-06-11 16:32:58      , -                   , True                   , True                  , 
Ping Check          , 2017-06-11 16:32:58      , 0:00:00.164220     , -                      , True                  , DB responded faster than 60 seconds
Feature Check 1     , 2017-06-11 16:32:58      , 0:00:00.164219     , True                   , False                 , # Critical Features = 3 (allowed = 1), Check: WHERE =
Call Stack Record   , 2017-06-11 16:32:58      , 0:00:00.105039     , -                      , -                     , /tmp/hanasitter/output/callstack_2017-06-11_16:32:58.t
```

# HANASitter – Critical Feature Checks (4/5)



## Example:

Here 1 critical feature check is defined by requiring at least 10 indexserver threads to be active

The feature check finds 3 indexserver threads that are active, this is not enough, so recording starts

```
oqladm@ls80010:/tmp/HANASitter> python hanasitter.py -cf "M_SERVICE_THREADS,WHERE,IS_ACTIVE='TRUE' and SERVICE_NAME='indexserver',>10" -nc 1
Feature Checks: Interval 60 seconds, Timeout = 60 seconds
Feature Check 1 requires at least 10 times that IS_ACTIVE='TRUE' and SERVICE_NAME='indexserver' in M_SERVICE_THREADS
Recording mode: 1
After Recording: Exit
```

Action	Timestamp	Duration	Successful	Result	Comment
Online Check	2018-04-16 14:47:59	-	True	True	Number running services: 9 out of 9
Primary Check	2018-04-16 14:48:01	-	True	True	
Ping Check	2018-04-16 14:48:01	0:00:00.164004	-	True	DB responded faster than 60 seconds
Feature Check 1	2018-04-16 14:48:01	0:00:00.163813	True	False	# Critical Features = 3 (minimum required = 10)
Call Stack Record	2018-04-16 14:48:01	0:00:00.130066	-	-	/tmp/hanasitter_output/callstack_ls80010_OQL_201

# HANASitter – Critical Feature Checks (5/5)



## Example:

Here 2 critical features are defined

- THREAD\_STATE = Semaphore Wait in M\_SERVICE\_THREADS (Single Column Mode)
- IS\_ACTIVE = 'TRUE' in M\_SERVICE\_THREADS (Where Clause Mode)

Since the log feature flag, -lf, is set to true, all features found with one of these states will be logged

```
mo-fc8d991e0:/tmp/HANASitter> python hanasitter.py -cf "M_SERVICE_THREADS,THREAD_STATE,Semaphore Wait,1,M_SERVICE_THREADS,WHERE,IS_ACTIVE = 'TRUE',2" -lf true
Host = mo-fc8d991e0, DB Instance = 00, Single DB System
Online, Primary and Not-Secondary Check: Interval = 3600 seconds
Ping Check: Interval = 60 seconds, Timeout = 60 seconds
Feature Checks: Interval 60 seconds, Timeout = 60 seconds
Feature Check 1, allows maximum 1 features in the state, THREAD_STATE = Semaphore Wait, in the view, M_SERVICE_THREADS
Feature Check 2, allows maximum 2 features from the where clause = IS_ACTIVE = 'TRUE', in the view, M_SERVICE_THREADS
All information for all features that are in one of the above critical feature states is recorded in the /tmp/hanasitter_output/criticalFeatures log
Recording mode: 1
Recording Type      , Number Recordings      , Intervals [seconds] , Durations [seconds] , Wait [milliseconds]
GStack              , 0                        , 60                  ,                      ,
Kernel Profiler     , 0                        , 60                  , 60                   , 0
Call Stack          , 0                        , 60                  ,                      ,
RTE Dumps           , 0                        , 60                  ,                      ,
After Recording: Exit
Action      , Timestamp      , Duration      , Successful , Result , Comment
Online Check , 2017-06-11 19:25:10 , -            , True      , True  , Number running services: 11 out of 11
Primary Check , 2017-06-11 19:25:16 , -            , True      , True  ,
Non-standby Check , 2017-06-11 19:25:16 , -            , True      , True  ,
Ping Check , 2017-06-11 19:25:16 , 0:00:00.164571 , -        , True  , DB responded faster than 60 seconds
Feature Check 1 , 2017-06-11 19:25:17 , 0:00:00.264591 , True     , False , # Critical Features = 4 (allowed = 1), Check: THREAD_STATE = Semap
```

**NOTE:** This log flag, -lf, could be very costly and is normally not to be used with any of the other recording types



**HANASitter can do the critical feature checks multiple times and compare the average from the results to the threshold**

Flag	Details	Explanation	Default
-if	number checks and intervals	<# checks 1>,<interval [s] 1>,...,<# checks N>,<interval [s] N>	

## Example:

if, on average from 3 checks with 5s interval, > 30 THREAD\_STATE=Running, or if any column from table VARINUM was unloaded → record

```
oqladm@ls80010:/tmp/HANASitter> python hanasitter.py -cf "M_SERVICE_THREADS,THREAD_STATE,Running,30,M_CS_UNLOADS,TABLE_NAME,VARINUM,1" -if 3,5,1,0 -nc 2
Will make a CF with M_CS_UNLOADS TABLE_NAME VARINUM 1
Host = ls80010, DB Instance = 00, Single DB System
Online, Primary and Not-Secondary Check: Interval = 3600 seconds
Ping Check: Interval = 60 seconds, Timeout = 60 seconds
Feature Checks: Interval 60 seconds, Timeout = 60 seconds
Feature Check 1 allows only 30 times that THREAD_STATE = 'Running' in M_SERVICE_THREADS as an average from 3 checks with 5 seconds intervals
Feature Check 2 allows only 1 times that TABLE_NAME = 'VARINUM' in M_CS_UNLOADS
Recording mode: 1
Recording Type      , Number Recordings      , Intervals [seconds]      , Durations [seconds]      , Wait [milliseconds]
GStack              , 0                        , 60                        ,                          , 
Kernel Profiler     , 0                        , 60                        , 60                        , 0
Call Stack          , 2                        , 60                        ,                          , 
RTE Dumps           , 0                        , 60                        ,                          , 
After Recording: Exit
Action              , Timestamp                , Duration                 , Successful                , Result                    , Comment
Online Check       , 2017-07-14 17:58:11      , -                        , True                      , True                      , Number running services: 9 out of 9
Primary Check      , 2017-07-14 17:58:12      , -                        , True                      , True                      , 
Non-standby Check , 2017-07-14 17:58:12      , -                        , True                      , True                      , 
Ping Check         , 2017-07-14 17:58:12      , 0:00:00.163895          , -                          , True                      , DB responded faster than 60 seconds
Feature Check 1    , 2017-07-14 17:58:28      , 0:00:15.387558          , True                      , True                      , # Critical Features = 8 (allowed = 30), Check: THREAD_STATE = 
Feature Check 2    , 2017-07-14 17:58:34      , 0:00:06.923696          , True                      , False                     , # Critical Features = 4 (allowed = 1), Check: TABLE_NAME = 
Call Stack Record  , 2017-07-14 17:58:35      , 0:00:00.145709          , -                          , -                         , /tmp/hanasitter_output/callstack_ls80010_OQL_2017-07-14_17:58
Call Stack Record  , 2017-07-14 17:59:25      , 0:00:00.120000          , -                          , -                         , /tmp/hanasitter_output/callstack_ls80010_OQL_2017-07-14_17:59
```

# HANASitter – Recording Mode (1/2)



HANASitter can record with the following recording types

- 1. GStacks
- 2. Kernel Profiler Trace
- 3. Call Stacks
- 4. RTE Dumps

If hanasitter is supposed to record using more than one of the recording types then there are 3 different “recording modes”, defined with `-rm`

Flag	Unit	Details	Explanation	Default
-rm	-	recording mode	1 = each requested recording types are done one after each other, e.g. GStack1, GStack2, ..., GStackN, RTE1, ..., RTEN 2 = recordings are done after each other, e.g. GStack1, RTE1, GStack2, RTE2, ... 3 = different recording types are recorded in parallel threads, e.g. if 2 GStacks and 1 RTE are requested then GStack1 and RTE1 are first done in parallel, when both are done GStack2 starts	1



# HANASitter – Recording Mode (2/2)



## Example:

Here hanasitter is requested to find the situation that more then 5 threads in the state IS\_ACTIVE = TRUE

When this situation is found hanasitter records using 3 Call Stacks, 2 RTE Dumps, and 1 GStack

Since Recording Mode 3 is requested they are recorded in parallel in the following order:

1. RTE Dump1, Call Stack 1, and GStack 1
2. Call Stack 2, and RTE Dump 2
3. Call Stack 3

```
oqladm@ls80010:/tmp/HANASitter> python hanasitter.py -cf "M_SERVICE_THREADS,IS_ACTIVE,TRUE,5" -nc 3 -nr 2 -ng 1 -rm 3
Host = ls80010, DB Instance = 00, Single DB System
Online, Primary and Not-Secondary Check: Interval = 3600 seconds
Ping Check: Interval = 60 seconds, Timeout = 60 seconds
Feature Checks: Interval 60 seconds, Timeout = 60 seconds
Feature Check 1 allows only 5 times that IS_ACTIVE = 'TRUE' in M_SERVICE_THREADS
Recording mode: 3
Recording Type      , Number Recordings , Intervals [seconds] , Durations [seconds] , Wait [milliseconds]
GStack              , 1                  , 60                  ,                      , 
Kernel Profiler     , 0                  , 60                  , 60                  , 0
Call Stack          , 3                  , 60                  ,                      , 
RTE Dumps           , 2                  , 60                  ,                      , 
After Recording: Exit
Action              , Timestamp          , Duration            , Successful           , Result              , Comment
Online Check        , 2017-10-01 17:18:45 , -                   , True                 , True                , Number running services: 9
Primary Check       , 2017-10-01 17:18:46 , -                   , True                 , True                , 
Ping Check          , 2017-10-01 17:18:46 , 0:00:00.164017     , -                    , True                , DB responded faster than 60
Feature Check 1     , 2017-10-01 17:18:47 , 0:00:00.214006     , True                 , False               , # Critical Features = 13 (
RTE Dump Record     , 2017-10-01 17:21:25 , 0:02:37.905730     , True                 , -                   , /tmp/hanasitter_output/rted
Call Stack Record   , 2017-10-01 17:21:24 , 0:02:37.756701     , -                    , -                   , /tmp/hanasitter_output/call
GStack Record       , 2017-10-01 17:21:25 , 0:02:37.926312     , -                    , -                   , /tmp/hanasitter_output/gsta
RTE Dump Record     , 2017-10-01 17:22:26 , 0:00:00.992576     , True                 , -                   , /tmp/hanasitter_output/rted
Call Stack Record   , 2017-10-01 17:22:25 , 0:00:00.225087     , -                    , -                   , /tmp/hanasitter_output/call
Call Stack Record   , 2017-10-01 17:23:26 , 0:00:00.146175     , -                    , -                   , /tmp/hanasitter_output/call
```



Monitoring

# HANASitter – Recording Priority



With the -rp flag one can define the order of the recording types

Flag	Unit	Details	Explanation	Default
-rp	List with 4 integers between 1 and 4	recording priority	This list of 4 integers defines the order of the recording types 1 = RTE, 2 = Call Stacks, 3 = G-Stacks, 4 = Kernel Profiler	1,2,3,4

Example:

Here the recording order is requested to be G-Stacks, Call Stacks, Kernel Profiler and then RTE dumps. Since 1 RTE dump, 2 Call Stacks, and 1 G-Stack was required with recording mode 2, first the G-Stack, then a Call Stack and then the RTE dump is recorded before the last Call Stack

```
oqladm@ls80010:/tmp/HANASitter> python hanasitter.py -cf "M_SERVICE_THREADS,THREAD_STATE,Running,1" -nr 1 -nc 2 -ng 1 -rm 2 -rp 3,2,4,1
Recording Type      , Number Recordings , Intervals [seconds] , Durations [seconds] , Wait [milliseconds]
GStack              , 1                  , 60                  ,                      , 
Kernel Profiler     , 0                  , 60                  , 60                  , 0
Call Stack          , 2                  , 60                  ,                      , 
RTE Dumps           , 1                  , 60                  ,                      , 
Recording Priority:  G-Stacks  Call Stacks  Kernel Profiler  RTE
After Recording: Exit
Action              , Timestamp          , Duration            , Successful           , Result              , Comment
Online Check        , 2017-11-15 14:07:13 , -                   , True                 , True                , Number running services: 9 out of 9
Primary Check       , 2017-11-15 14:07:14 , -                   , True                 , True                , 
Ping Check          , 2017-11-15 14:07:14 , 0:00:00.164236      , -                    , True                , DB responded faster than 60 seconds
Feature Check 1     , 2017-11-15 14:07:14 , 0:00:00.214050      , True                 , False               , # Critical Features = 8 (allowed = 1), Chec
GStack Record       , 2017-11-15 14:10:14 , 0:03:00.055366      , -                    , -                   , /tmp/hanasitter_output/gstack_11417_2017-11-
Call Stack Record   , 2017-11-15 14:11:15 , 0:00:00.153899      , -                    , -                   , /tmp/hanasitter_output/callstack_ls80010_OQL
RTE Dump Record     , 2017-11-15 14:12:16 , 0:00:01.354217      , True                 , -                   , /tmp/hanasitter_output/rtedump_ls80010_OQL_2
Call Stack Record   , 2017-11-15 14:13:16 , 0:00:00.116943      , -                    , -                   , /tmp/hanasitter_output/callstack_ls80010_OQL
```



One of the possible recording options is to do gstack of the indexserver, i.e. an execution stack trace of the indexserver from OS-level

This recording option is controlled by the `-ng` and `-ig` flags

Flag	Unit	Details	Explanation	Default
<code>-ng</code>	-	number gstacks	Number indexserver gstacks created if the DB is considered unresponsive	0
<code>-ig</code>	sec	gstacks interval	<code>-rm = 1</code> : time it waits between each gstack <code>-rm = 2</code> : time it waits after a gstack <code>-rm = 3</code> : time the thread waits after a gstack	60

**Note:** This recording option will only be done on current host

## Example:

Here 2 GStacks with 30 seconds delay are requested when there is more than 1 active thread

Hanasitter slept for 30 seconds after the 1<sup>st</sup> GStack finished, at 13:35:35, and the 2<sup>nd</sup> GStack started to record at 13:36:05

```
mo-fc8d991e0:/tmp/HANASitter> python hanasitter.py -cf "M_SERVICE_THREADS,IS_ACTIVE,TRUE,1" -ng 2 -ig 30
Host = mo-fc8d991e0, DB Instance = 00, Single DB System
Ping Check      , 2017-06-16 13:33:41 , 0:00:00.214811 , - , True , DB responded faster than 60 seconds
Feature Check 1 , 2017-06-16 13:33:41 , 0:00:00.214887 , True , False , # Critical Features = 10 (allowed = 1), Check: IS_ACTIVE = TRUE
GStack Record  , 2017-06-16 13:35:35 , 0:01:54.029790 , - , - , /tmp/hanasitter_output/gstack_6090_2017-06-16_13:33:41.txt
GStack Record  , 2017-06-16 13:37:56 , 0:01:51.052227 , - , - , /tmp/hanasitter_output/gstack_6090_2017-06-16_13:36:05.txt
```



Another possible recording option is to do Kernel Profiler traces of the indexserver – mainly for performance analysis, this is controlled by the `-np`, `-dp`, `-wp`, and `-ip` flags

Flag	Unit	Details	Explanation	Default
<b>-np</b>	-	number kernel profiler traces	Number indexserver kernel profiler traces created if the DB is considered unresponsive	0
<b>-dp</b>	sec	profiler duration	How long time it is tracing	60
<b>-wp</b>	millise conds	profiler wait time	wait time after callstacks of all running threads have been taken	0
<b>-ip</b>	sec	kernel interval	-rm = 1: time it waits between each profiler trace -rm = 2: time it waits after a profiler trace -rm = 3: time the thread waits after a profiler trace	60

### Example:

Here 2 Kernel Profiler traces with a duration of 30 seconds and a delay of 30 seconds are recorded:

```
mo-fc8d991e0:/tmp/HANASitter> python hanasitter.py -cf "M_SERVICE_THREADS,IS_ACTIVE,TRUE,1" -np 2 -dp 30 -ig 30
Host = mo-fc8d991e0, DB Instance = 00, Single DB System
Feature Check 1, 2017-06-16 13:23:19, 0:00:00.214674, True, False, # Critical Features = 10 (allowed = 1), Check: IS_ACTIVE = TRUE, in
view M_SERVICE_THREADS
Kernel Profiler, 2017-06-16 13:23:50, 0:00:30.684400, -, -, /tmp/hanasitter_output/kernel_profiler_cpu_2017-06-16_13:23:19.dot a
nd /tmp/hanasitter_output/kernel_profiler_wait_2017-06-16_13:23:19.dot
Kernel Profiler, 2017-06-16 13:25:21, 0:00:30.648090, -, -, /tmp/hanasitter_output/kernel_profiler_cpu_2017-06-16_13:24:50.dot a
nd /tmp/hanasitter_output/kernel_profiler_wait_2017-06-16_13:24:50.dot
```

# HANASitter – Kernel Profiler at Scale Out



**Kernel Profiler traces are done for each host in a scale out scenario**

(due to limitations of hdbcons the kernel profiler traces will not have be separated in cpu and wait files)

**This is controlled by the `-np`, `-dp`, `-wp`, and `-ip` flags**

```

hsiadm@dewdfglp00835:/tmp/HANASitter> python hanasitter.py -cf "M_SERVICE_THREADS,IS_ACTIVE,TRUE,1" -np 1
Host = dewdfglp00835, DB Instance = 00, Scale Out DB System with hosts: dewdfglp00835, dewdfglp00837, dewdfglp00836
Online, Primary and Not-Secondary Check: Interval = 3600 seconds
Ping Check: Interval = 60 seconds, Timeout = 60 seconds
Feature Checks: Interval 60 seconds, Timeout = 60 seconds
Feature Check 1, allows maximum 1 features in the state, IS_ACTIVE = TRUE, in the view, M_SERVICE_THREADS
Recording mode: 1
Recording Type      , Number Recordings , Intervals [seconds] , Durations [seconds] , Wait [milliseconds]
GStack              , 0                  , 60                  ,                      , 
Kernel Profiler     , 1                  , 60                  , 60                  , 0
Call Stack          , 0                  , 60                  ,                      , 
RTE Dumps           , 0                  , 60                  ,                      , 
After Recording: Exit
Action      , Timestamp      , Duration      , Successful , Result , Comment
Online Check , 2017-06-16 15:10:09 , -            , True      , True  , Number running services: 5 out of 5
Primary Check , 2017-06-16 15:10:12 , -            , True      , True  , 
Non-standby Check , 2017-06-16 15:10:12 , -            , True      , True  , 
Ping Check    , 2017-06-16 15:10:12 , 0:00:00.164554 , -        , True  , DB responded faster than 60 seconds
Feature Check 1 , 2017-06-16 15:10:12 , 0:00:00.264813 , True     , False , # Critical Features = 30 (allowed = 1), Check: IS_ACTIVE = TRUE, in view M_SERVICE_THREADS
Kernel Profiler , 2017-06-16 15:11:14 , 0:01:01.595220 , -        , -     , /tmp/hanasitter_output/kernel_profiler_cpu_wait_dewdfglp00835_HSI_2017-06-16_15:10:12.dot
Kernel Profiler , 2017-06-16 15:12:15 , 0:01:00.851089 , -        , -     , /tmp/hanasitter_output/kernel_profiler_cpu_wait_dewdfglp00837_HSI_2017-06-16_15:11:14.dot
Kernel Profiler , 2017-06-16 15:13:17 , 0:01:01.835549 , -        , -     , /tmp/hanasitter_output/kernel_profiler_cpu_wait_dewdfglp00836_HSI_2017-06-16_15:12:15.dot
  
```



Another recording option is to do Call Stacks

This is controlled by the `-nc`, and `-ic` flags

Flag	Unit	Details	Explanation	Default
<code>-nc</code>	-	number call stacks	Number call stacks created if the DB is considered unresponsive	0
<code>-ic</code>	sec	call stacks interval	-rm = 1: time it waits between each call stack -rm = 2: time it waits after a call stack -rm = 3: time the thread waits after a call stack	60

## Example:

Here, when there are more than 5 threads with the state `IS_ACTIVE=TRUE`, 2 call stacks, with 30 seconds between them, are recorded:

```
oqladm@ls80010:/tmp/HANASitter> python hanasitter.py -cf "M_SERVICE_THREADS,IS_ACTIVE,TRUE,5" -nc 2 -ic 30
Host = ls80010, DB Instance = 00, Single DB System
Ping Check      , 2017-10-01 17:33:24      , 0:00:00.164094      , -      , True      , DB responded fast
Feature Check 1 , 2017-10-01 17:33:24      , 0:00:00.213978      , True   , False     , # Critical Feat
Call Stack Record ← 2017-10-01 17:33:24      , 0:00:00.127802      , -      , -        , /tmp/hanasitter_
Call Stack Record ← 2017-10-01 17:33:54      , 0:00:00.122938      , -      , -        , /tmp/hanasitter_
```





## Call Stacks will be done for all hosts in a scale out automatically

```

hsiadm@dewdfglp00835:/tmp/HANASitter> python hanasitter.py -cf "M_SERVICE_THREADS,IS_ACTIVE,TRUE,1" -nc 1
Host = dewdfglp00835, DB Instance = 00, Scale Out DB System with hosts: dewdfglp00835, dewdfglp00837, dewdfglp00836
Online, Primary and Not-Secondary Check: Interval = 3600 seconds
Ping Check: Interval = 60 seconds, Timeout = 60 seconds
Feature Checks: Interval 60 seconds, Timeout = 60 seconds
Feature Check 1, allows maximum 1 features in the state, IS_ACTIVE = TRUE, in the view, M_SERVICE_THREADS
Recording mode: 1
Recording Type      , Number Recordings , Intervals [seconds] , Durations [seconds] , Wait [milliseconds]
GStack              , 0                  , 60                  ,                      , 
Kernel Profiler     , 0                  , 60                  , 60                  , 0
Call Stack          , 1                  , 60                  ,                      , 
RTE Dumps           , 0                  , 60                  ,                      , 
After Recording: Exit
Action      , Timestamp      , Duration      , Successful , Result , Comment
Online Check , 2017-06-16 12:55:43 , -            , True      , True  , Number running services: 5 out of 5
Primary Check , 2017-06-16 12:55:46 , -            , True      , True  , 
Non-standby Check , 2017-06-16 12:55:46 , -            , True      , True  , 
Ping Check    , 2017-06-16 12:55:46 , 0:00:00.164382 , -        , True  , DB responded faster than 60 seconds
Feature Check 1 , 2017-06-16 12:55:46 , 0:00:00.314905 , True     , False , # Critical Features = 28 (allowed = 1), Check: IS_ACTIVE = TRUE, in view M_SERVICE_THREADS
Call Stack Record , 2017-06-16 12:55:47 , 0:00:00.232236 , -        , -     , /tmp/hanasitter_output/callstack_dewdfglp00835_HSI_2017-06-16_12:55:46.txt
Call Stack Record , 2017-06-16 12:55:47 , 0:00:00.269409 , -        , -     , /tmp/hanasitter_output/callstack_dewdfglp00837_HSI_2017-06-16_12:55:47.txt
Call Stack Record , 2017-06-16 12:55:47 , 0:00:00.248774 , -        , -     , /tmp/hanasitter_output/callstack_dewdfglp00836_HSI_2017-06-16_12:55:47.txt

```

Monitoring

# HANASitter – RTE Dumps



Another recording option is to do RunTime Environment Dumps (RTE Dumps)

This is controlled by the `-nr`, `-ir`, and `-mr` flags

Flag	Unit	Details	Explanation	Default
-nr	-	number RTE dumps	Number RTE Dumps created if the DB is considered unresponsive	0
-ir	sec	RTE dumps interval	-rm = 1: time it waits between each RTE dump -rm = 2: time it waits after an RTE dump -rm = 3: time the thread waits after an RTE dump	60
-mr	0,1	RTE	-mr = 0: normal RTE dump -mr = 1: light RTE dump mode, only RTE dump with STACK_SHORT and THREADS sections, and the views M_JOBEXECUTORS_, M_DEV_JOBEX_THREADGROUPS, M_DEV_JOBEXWAITING, M_DEV_CONTEXTS, M_CONNECTIONS, M_DEV_SESSION_PARTITIONS	0

**Example:**  
Here, when there are more then 5 threads with the state IS\_ACTIVE=TRUE, 2 RTE dumps, with 30 seconds between them, are recorded:

```
oqladm@ls80010:/tmp/HANASitter> python hanasitter.py -cf "M_SERVICE_THREADS,IS_ACTIVE,TRUE,5" -nr 2 -ir 30
Host = ls80010, DB Instance = 00, Single DB System
Ping Check      , 2017-10-01 17:38:00      , 0:00:00.163893      , -      , True      , DB responded fa
Feature Check 1  , 2017-10-01 17:38:00      , 0:00:00.213988      , True    , False     , # Critical Fea
RTE Dump Record ◀, 2017-10-01 17:38:01      , 0:00:00.897289      , True    , -         , /tmp/hanasitter
RTE Dump Record ◀, 2017-10-01 17:38:32      , 0:00:00.898280      , True    , -         , /tmp/hanasitter
```





The light RTE dump mode is here used to make 3 small RTE dumps with an interval of 10 seconds:

```
ha2adm@atgvmls7050:/tmp/HANASitter> python hanasitter.py -cf M_SERVICE_THREADS,THREAD_STATE,Running,3 -nr 3 -ir 10 -mr 1 -k SYSTEMDBKEY

HANASitter executed 2018-05-03 15:45:52 with
hanasitter.py -cf M_SERVICE_THREADS,THREAD_STATE,Running,3 -nr 3 -ir 10 -mr 1 -k SYSTEMDBKEY
as SYSTEMDBKEY: KEY SYSTEMDBKEY
  ENV : atgvmls7050:30013
  USER: system
  DATABASE: systemdb

Host = atgvmls7050, SID = HA2, DB Instance = 00, MDC SystemDB, Nameserver Port = 30001
Online, Primary and Not-Secondary Check: Interval = 3600 seconds
Ping Check: Interval = 60 seconds, Timeout = 60 seconds
Feature Checks: Interval 60 seconds, Timeout = 60 seconds
Feature Check 1 allows only 3 times that THREAD_STATE = 'Running' in M_SERVICE_THREADS
Recording mode: 1
Recording Type      , Number Recordings      , Intervals [seconds]      , Durations [seconds]      , Wait [milliseconds]
GStack              , 0                        , 60                        ,                          , 
Kernel Profiler     , 0                        , 60                        , 60                        , 0
Call Stack          , 0                        , 60                        ,                          , 
RTE Dumps (light)   , 3                        , 10                        ,                          , 
Recording Priority: RTE    Call Stacks    G-Stacks    Kernel Profiler
After Recording: Exit
Action      , Timestamp      , Duration      , Successful      , Result      , Comment
Online Check , 2018-05-03 15:45:52 , -            , True            , True        , Number running services: 11 out of 11
Primary Check , 2018-05-03 15:45:54 , -            , True            , True        , 
Ping Check   , 2018-05-03 15:45:54 , 0:00:00.164322 , -              , True        , DB responded faster than 60 seconds
Feature Check 1 , 2018-05-03 15:45:54 , 0:00:00.265588 , True           , False       , # Critical Features = 4 (maximum allowed = 3), Check: THREAD_STATE = 'Running'
RTE Dump Record , 2018-05-03 15:45:55 , 0:00:00.800020 , True           , -           , /tmp/hanasitter_output/rtedump_light_atgvmls7050_HA2_2018-05-03_15-45-54.trc
RTE Dump Record , 2018-05-03 15:46:06 , 0:00:00.666470 , True           , -           , /tmp/hanasitter_output/rtedump_light_atgvmls7050_HA2_2018-05-03_15-46-05.trc
RTE Dump Record , 2018-05-03 15:46:16 , 0:00:00.679907 , True           , -           , /tmp/hanasitter_output/rtedump_light_atgvmls7050_HA2_2018-05-03_15-46-16.trc
```

The light RTE dump mode, -mr = 1, might be useful to continuously create small dumps during certain situations...



RTE Dumps will automatically be done for all hosts in a scale out scenario

```

hsiadm@dewdfglp00835:/tmp/HANASitter> python hanasitter.py -cf "M_SERVICE_THREADS,THREAD_STATE,Running,1" -nr 1
Host = dewdfglp00835, DB Instance = 00, Scale Out DB System with hosts: dewdfglp00835, dewdfglp00836, dewdfglp00837
Online, Primary and Not-Secondary Check: Interval = 3600 seconds
Ping Check: Interval = 60 seconds, Timeout = 60 seconds
Feature Checks: Interval 60 seconds, Timeout = 60 seconds
Feature Check 1 allows only 1 times that THREAD_STATE = 'Running' in M_SERVICE_THREADS
Recording mode: 1
Recording Type      , Number Recordings      , Intervals [seconds] , Durations [seconds] , Wait [milliseconds]
GStack              , 0                        , 60                  ,                      , 
Kernel Profiler     , 0                        , 60                  , 60                   , 0
Call Stack          , 0                        , 60                  ,                      , 
RTE Dumps           , 1                        , 60                  ,                      , 
After Recording: Exit
Action              , Timestamp                , Duration            , Successful            , Result                , Comment
Online Check        , 2017-09-07 15:45:22      , -                   , True                  , True                  , Number running services: 7 out of 7
Primary Check       , 2017-09-07 15:45:26      , -                   , True                  , True                  , 
Non-standby Check   , 2017-09-07 15:45:26      , -                   , True                  , True                  , 
Ping Check          , 2017-09-07 15:45:26      , 0:00:00.164829      , -                     , True                  , DB responded faster than 60 seconds
Feature Check 1     , 2017-09-07 15:45:26      , 0:00:00.316117      , True                  , False                 , # Critical Features = 14 (allowed = 1), Chec
E_THREADS
RTE Dump Record     , 2017-09-07 15:45:27      , 0:00:00.802223      , True                  , -                     , /tmp/hanasitter_output/rtedump_dewdfglp00835_
RTE Dump Record     , 2017-09-07 15:45:28      , 0:00:00.991286      , True                  , -                     , /tmp/hanasitter_output/rtedump_dewdfglp00836_
RTE Dump Record     , 2017-09-07 15:45:28      , 0:00:00.354565      , True                  , -                     , /tmp/hanasitter_output/rtedump_dewdfglp00837_

```

# HANASitter – Key With All Hosts



It is possible to provide a user key in hdbuserstore that contains all hosts:

```
KEY HANASITTERKEY
```

```
ENV : dewdfglp00835:30015,dewdfglp00836:30015,dewdfglp00837:30015
```

```
USER: HANASITTER1
```

HANASitter will then automatically use the local host:

```
hsiadm@dewdfglp00836:/tmp/HANASitter> python hanasitter.py -k HANASITTERKEY -cf "M_SERVICE_T  
Host = dewdfglp00836, DB Instance = 00, Scale Out DB System with hosts: dewdfglp00835, dewdf  
Online, Primary and Not-Secondary Check: Interval = 3600 seconds  
Ping Check: Interval = 60 seconds, Timeout = 60 seconds
```



## HANASitter detects an MDC scenario and if it is the System or a Tenant (due to technical reason hanasitter does not support MDC and Scale Out together)

### Example:

Here the key of a DB user in the System DB in an MDC setup is used to run hanasitter:

```
ls2999:/tmp/HANASitter> python hanasitter.py -cf "M_SERVICE_THREADS,IS_ACTIVE,TRUE,1" -nr 1 -k SYSKEY
Host = ls2999, DB Instance = 01, MDC system
Online, Primary and Not-Secondary Check: Interval = 3600 seconds
Ping Check: Interval = 60 seconds, Timeout = 60 seconds
Feature Checks: Interval 60 seconds, Timeout = 60 seconds
Feature Check 1, allows maximum 1 features in the state, IS_ACTIVE = TRUE, in the view, M_SERVICE_THREADS
Recording mode: 1
Recording Type      , Number Recordings , Intervals [seconds] , Durations [seconds] , Wait [milliseconds]
GStack              , 0                  , 60                   ,                      , 
Kernel Profiler     , 0                  , 60                   , 60                   , 0
Call Stack          , 0                  , 60                   ,                      , 
RTE Dumps           , 1                  , 60                   ,                      , 
After Recording: Exit
Action      , Timestamp          , Duration      , Successful , Result , Comment
Online Check , 2017-06-16 16:37:52 , -             , True       , True   , Number running services: 7 out of 7
Primary Check , 2017-06-16 16:37:55 , -             , True       , True   , 
Non-standby Check , 2017-06-16 16:37:55 , -             , True       , True   , 
Ping Check    , 2017-06-16 16:37:55 , 0:00:00.164097 , -          , True   , DB responded faster than 60 seconds
Feature Check 1 , 2017-06-16 16:37:55 , 0:00:00.163950 , True       , False  , # Critical Features = 3 (allowed = 1), Check:
RTE Dump Record , 2017-06-16 16:37:56 , 0:00:00.974544 , True       , -      , /tmp/hanasitter_output/rtedump_ls2999_H00_2017
ls2999:/tmp/HANASitter>
```



## HANASitter detects an MDC scenario and if it is the System or a Tenant (due to technical reason hanasitter does not support MDC and Scale Out together)

### Example:

Here the key of a DB user in one of the Tenant DBs in an MDC setup is used to run hanasitter:

```
ls2999:/tmp/HANASitter> python hanasitter.py -cf "M_SERVICE_THREADS,IS_ACTIVE,TRUE,1" -nc 1 -nr 1 -k TEN1KEY
Host = ls2999, DB Instance = 01, MDC tenant = H01, Indexserver Port = 30140
Online, Primary and Not-Secondary Check: Interval = 3000 seconds
Ping Check: Interval = 60 seconds, Timeout = 60 seconds
Feature Checks: Interval 60 seconds, Timeout = 60 seconds
Feature Check 1, allows maximum 1 features in the state, IS_ACTIVE = TRUE, in the view, M_SERVICE_THREADS
Recording mode: 1
Recording Type      , Number Recordings , Intervals [seconds] , Durations [seconds] , Wait [milliseconds]
GStack              , 0                  , 60                   ,                      , 
Kernel Profiler     , 0                  , 60                   , 60                   , 0
Call Stack          , 1                  , 60                   ,                      , 
RTE Dumps           , 1                  , 60                   ,                      , 
After Recording: Exit
Action      , Timestamp      , Duration      , Successful , Result , Comment
Online Check , 2017-06-16 16:48:11 , -            , True      , True   , Number running services: 7 out of 7
Primary Check , 2017-06-16 16:48:14 , -            , True      , True   , 
Non-standby Check , 2017-06-16 16:48:14 , -            , True      , True   , 
Ping Check    , 2017-06-16 16:48:14 , 0:00:00.164167 , -        , True   , DB responded faster than 60 seconds
Feature Check 1 , 2017-06-16 16:48:14 , 0:00:00.163977 , True     , False  , # Critical Features = 3 (allowed = 1), Check: IS_ACTI
Call Stack Record , 2017-06-16 16:48:14 , 0:00:00.154666 , -        , -      , /tmp/hanasitter_output/callstack_ls2999_H01_2017-06-16
RTE Dump Record , 2017-06-16 16:49:15 , 0:00:00.902135 , True     , -      , /tmp/hanasitter_output/rtedump_ls2999_H01_2017-06-16_1
ls2999:/tmp/HANASitter>
```



# HANASitter – If HANA Goes Offline



**HANASitter has a Online check so that it will not start tracking if DB is offline**

**Additionally, if HANA goes offline during tracking, it will exit tracking and start with the online check**

**Example:** Here HANA is turned off during tracking so the 4<sup>th</sup> Ping Check finds that the DB is offline:

```
HANASitter executed 2017-11-24 17:32:48 with
hanasitter.py -ci 30 -pt 30 -nc 1

Host = mo-fc8d991e0, SID = CH0, DB Instance = 00
Online, Primary and Not-Secondary Check: Interval = 3600 seconds
Ping Check: Interval = 30 seconds, Timeout = 30 seconds
Feature Checks: Interval 30 seconds, Timeout = 60 seconds
Feature Check 1 allows only 30 times that IS_ACTIVE = 'TRUE' in M_SERVICE_THREADS
Recording mode: 1
Recording Type      , Number Recordings      , Intervals [seconds] , Durations [seconds] , Wait [milliseconds]
GStack              , 0                        , 60                  ,                      , 
Kernel Profiler     , 0                        , 60                  , 60                  , 0
Call Stack          , 1                        , 60                  ,                      , 
RTE Dumps           , 0                        , 60                  ,                      , 
Recording Priority: RTE   Call Stacks   G-Stacks   Kernel Profiler
After Recording: Exit
Action      , Timestamp      , Duration      , Successful , Result , Comment
Online Check , 2017-11-24 17:32:48 , -            , True      , True  , Number running services: 11 out of 11
Primary Check , 2017-11-24 17:32:54 , -            , True      , True  , 
Ping Check   , 2017-11-24 17:32:54 , 0:00:00.164599 , -        , True  , DB responded faster than 30 seconds
Feature Check 1 , 2017-11-24 17:32:54 , 0:00:00.264682 , True     , True  , # Critical Features = 11 (allowed = 30)
Ping Check   , 2017-11-24 17:33:24 , 0:00:00.164389 , -        , True  , DB responded faster than 30 seconds
Feature Check 1 , 2017-11-24 17:33:25 , 0:00:00.214380 , True     , True  , # Critical Features = 10 (allowed = 30)
Ping Check   , 2017-11-24 17:33:55 , 0:00:00.164413 , -        , True  , DB responded faster than 30 seconds
Feature Check 1 , 2017-11-24 17:33:55 , 0:00:00.214246 , True     , True  , # Critical Features = 10 (allowed = 30)
Ping Check   , 2017-11-24 17:35:00 , 0:00:34.455389 , -        , False , DB is offline, will exit the tracker
Online Check , 2017-11-24 17:35:00 , -            , True      , False , Number running services: 3 out of 11

One of the online checks found out that this HANA instance is not online. HANASitter will now have a 3600 seconds break.
```



**HANASitter can be controlled with a configuration file**  
**(additional flags given will overwrite flags in the configuration file)**

Flag	Unit	Details	Explanation	Default
-ff		flag file	full path to the configuration file	

**Example:**

```
haladm@dewdfglp00766:/tmp/HANASitter> more hanasitter_configfile.txt
MY HANASITTER CONFIGURATION FILE
If more than 20 threads have been in state TREAD_STATE=Running for more than 10 seconds
-cf M SERVICE_THREADS,THREAD_STATE,Running,20,10
then 2 call stacks
-nc 2
with 30 seconds between them
-ic 30
are recorded. This is the key in hdbuserstore that is used:
-k SYSTEMKEY
haladm@dewdfglp00766:/tmp/HANASitter> python hanasitter.py -ff hanasitter_configfile.txt
Host = dewdfglp00766, DB Instance = 00, Single DB System
Online, Primary and Not-Secondary Check: Interval = 3600 seconds
Ping Check: Interval = 60 seconds, Timeout = 60 seconds
Feature Checks: Interval 60 seconds, Timeout = 60 seconds
Feature Check 1, allows maximum 20 features in the state, THREAD_STATE = Running, for > 10 seconds, in the view, M_SERVICE_THREADS
Recording mode: 1
Recording Type      , Number Recordings      , Intervals [seconds] , Durations [seconds] , Wait [miliseconds]
GStack              , 0                        , 60                  ,                      , 
Kernel Profiler     , 0                        , 60                  , 60                   , 0
Call Stack          , 2                        , 30                  ,                      , 
RTE Dumps           , 0                        , 60                  ,                      , 
After Recording: Exit
Action      , Timestamp      , Duration      , Successful , Result , Comment
Online Check , 2017-06-09 11:54:21 , -            , True      , True  , Number running services: 7 out of 7
Primary Check , 2017-06-09 11:54:23 , -            , True      , True  , 
Non-standby Check , 2017-06-09 11:54:23 , -            , True      , True  , 
Ping Check , 2017-06-09 11:54:24 , 0:00:00.164766 , -        , True  , DB responded faster than 60 seconds
Feature Check 1 , 2017-06-09 11:54:24 , 0:00:00.314682 , True     , True  , # Critical Features = 0 (allowed = 20),
```





To control the output of the hanasitter there are these flags

Flag	Unit	Details	Explanation	Default
-od		output path	full path of the folder where the hanasitter logs are written	/tmp/hanasitter_output
-so		standard out switch	true: write to std out, false: do not write to std out	true

**Example:**

Here a output folder is deleted and then automatically created again by hanasitter and the daily log file written into it:

```
DEWDFGLP00765:/tmp/HANASitter> rm -r /tmp/hanasitterout/
DEWDFGLP00765:/tmp/HANASitter> python hanasitter.py -ct IS_ACTIVE,TRUE,5 -nc 1 -od /tmp/hanasitterout
DB Address = , localhost , DB Instance = , 00
Online, Primary and Not-secondary Check: , Every 3600 seconds
Call Stack Record , 2017-04-10 23:50:07 , 0:00:00.228039 , - , - , /tmp/hanas
DEWDFGLP00765:/tmp/HANASitter> ls /tmp/hanasitterout/
callstack_2017-04-10_23:50:07.txt hanasitterlog_2017-04-10.txt
DEWDFGLP00765:/tmp/HANASitter>
```



## Automatic house keeping of the hanasitter logs with -or flag

Flag	Unit	Details	Explanation	Default
-or		log retention days	hanasitterlogs in the path specified with -od are only saved for this number of days	-1 (not used)

### Example:

Here there are two old hanasitterlog files and after a run of hanasitter with -or they are removed and there is now only the new hanasitterlog file left

```
oqladm@ls80010:/tmp/HANASitter> ll ../hanasitter_output/
total 224
-rw-r----- 1 oqladm sapsys  25092 Dec  6 13:18 hanasitterlog_2017-12-06.txt
-rw-r----- 1 oqladm sapsys  19134 Dec 26 17:31 hanasitterlog_2017-12-26.txt
-rw-r--r--  1 oqladm sapsys 102842 Dec  6 11:29 kernel_profiler_cpu_ls80010_OQL_2017-12-06_11-28-36.dot
-rw-r--r--  1 oqladm sapsys  65260 Dec  6 11:29 kernel_profiler_wait_ls80010_OQL_2017-12-06_11-28-36.dot
oqladm@ls80010:/tmp/HANASitter>
```

```
oqladm@ls80010:/tmp/HANASitter> python hanasitter.py -nc 1 -or 2
2 hanasitter daily log files were removed
Ping Check      , 2018-01-05 12:09:59      , 0:00:00.163895      , -      , True
Feature Check 1 , 2018-01-05 12:10:00      , 0:00:00.163768      , True    , True
```

```
oqladm@ls80010:/tmp/HANASitter> ll ../hanasitter_output/
total 180
-rw-r----- 1 oqladm sapsys   1968 Jan  5 12:10 hanasitterlog_2018-01-05.txt
-rw-r--r--  1 oqladm sapsys 102842 Dec  6 11:29 kernel_profiler_cpu_ls80010_OQL_2017-12-06_11-28-36.dot
-rw-r--r--  1 oqladm sapsys  65260 Dec  6 11:29 kernel_profiler_wait_ls80010_OQL_2017-12-06_11-28-36.dot
oqladm@ls80010:/tmp/HANASitter>
```