

Directives and Forms

Creating Directives. Handling Forms.



SoftUni Team
Technical Trainers



SoftUni



Software University

<https://softuni.bg>

Have a Question?

sli.do

#angular

1. Directives

- Attribute Directives
- Structural Directives
- Building an Attribute Directive

2. Handling Forms

- Template-Driven Forms
- Reactive Forms





Directives

Manipulating the DOM in Angular

Directives Overview



- There are **three** types of **directives** in Angular
 - **Components** - directives with template
 - **Attribute** directives - change the **appearance** or behavior of an element, component or another directive (**ngStyle** and **ngClass**)
 - **Structural** directives - change the DOM **layout** by **adding** and **removing** DOM elements (**@if** and **@For**)

- **Attribute** Directives
 - Look like HTML attributes
 - Only affect / change the **element** they are **added to**
 - Example - **ngStyle**, **ngClass**
- **Structural** Directives
 - Have a leading *
 - Affect a **whole area** in the DOM
 - Examples - **@if**, **@for**



Build a Simple Attribute Directive

- An attribute directive minimally requires building a controller class **annotated** with **@Directive**

```
import { Directive } from '@angular/core'
```

- Surround the **selector** with **square** brackets

```
@Directive({  
  selector: '[appHighlight]',  
  standalone: true  
})  
export class HighlightDirective {  
  constructor() { }  
}
```


Import the directive
in **declarations** array

Attach Styles to Referenced Elements

- Now **inject** the **referenced** element and **change** its background style

```
export class HighlightDirective implements OnInit {  
  constructor(private el : ElementRef) {}  
  
  ngOnInit() {  
    this.el.nativeElement.style.backgroundColor = 'yellow';  
  }  
}
```


Warning - Use Renderer2

- 
- It's not a good practice to **directly access** DOM elements via **ElementRef**
 - Angular is **not limited** to run only on the browser (could run with service workers)
 - Services Worker – environment where the DOM is **inaccessible**
 - Use **Renderer2** to manipulate DOM elements

```
import { Renderer2 } from '@angular/core'
```

- Inject the renderer and access its **methods** to change the DOM

```
constructor( private renderer: Renderer2) { }  
  
ngOnInit() {  
    this.renderer.setStyle(  
        this.el.nativeElement,  
        'background-color',  
        'red'  
    );  
}
```

- A directive can be more **dynamic** and **detect** user events

```
import { HostListener } from '@angular/core'
```

- Attach host **listeners** to handle different **DOM events**

```
@HostListener('mouseenter') onMouseLeave(e) {  
  this.highlight('yellow');  
}  
@HostListener('mouseleave') onMouseLeave(e) {  
  this.highlight('blue');  
}
```

- Bind to DOM properties **without** Renderer

```
import { HostBinding } from '@angular/core'
```

```
export class BasicHighlightDirective {  
  @HostBinding('style.backgroundColor')  
  backgroundColor: string;  
  
  highlight(color: string) {  
    this.backgroundColor = color;  
  }  
}
```



Handling Forms

Template-Driven Forms

Forms Overview

- Forms are the **mainstay** of **business** applications
- We use Forms to
 - Register / Log in
 - Submit a **help** request
 - **Place** an order
 - **Book** a flight and more
- Guide the user **efficiently** and **effectively** when creating forms



Template-Driven Forms



- Build a Form by writing **templates** using the Angular **template syntax**
 - Track **state** changes (**validity** of form controls)
 - Provide **visual** feedback **using** special **CSS** classes
 - Display **validation** errors when **needed**
 - Use **reference variables** to share information

Problem: Create a Template-Driven Form

- Create a **Template-Driven** Form looking like this

Laptop Form

Processor

Intel Core i7

RAM

16 GB DDR4

Hard Disk (GB)

1000

Operating System

Windows 10

Submit

- Bootstrap is the most **popular** open-source **front-end** framework for **designing** web **sites** and web **apps**
- Install via **npm** and import it inside **angular.json**

```
"styles": [  
  "node_modules/bootstrap/dist/css/bootstrap.min.css",  
  "src/styles.css"  
]
```

- Create **containers**, **form-groups**, **form-controls**, **style** buttons and errors

Introducing Forms Module

- Angular is **module based** and to handle Forms (**ngModel**, **ngSubmit**, **ngForm**) we need **Forms Module**
- Import the following in **app.component.ts**

```
import { FormsModule } from '@angular/forms';  
  
@Component({  
  selector: 'app-root',  
  standalone: true,  
  imports: [FormsModule]  
})  
export class AppComponent { }
```

Create Form Component

- An **Angular** form has **two** parts
 - An HTML-based **template**
 - Component **class** to **handle** data

```
@Component({...})
export class LaptopFormComponent {
  operatingSystems: string[] = [
    'Windows 10',
    'Linux',
    'Mac OS'
  ];
}
```

Initial HTML Template

```
<div class="container">
  <h1>Laptop Form</h1>
  <form>
    <div class="form-group">
      <label for="processor">Processor</label>
      <input type="text" class="form-control" id="processor"
        required>
    </div>
    <div class="form-group">
      <label for="ram">RAM</label>
      <input type="text" class="form-control" id="ram"
        required>
    </div>
    <div class="form-group">
      <label for="hardDisk">Hard Disk (GB)</label>
      <input type="number" class="form-control" id="hardDisk">
    </div>
  </form>
</div>
```

```
<div class="form-group">
  <label for="os">Operating System</label>
  <select class="form-control" id="os" required>
    @for(os of operatingSystems; track os){
      <option [value]="os">{{ os }}</option>
    }
  </select>
</div>
```

- We need to **display**, **listen** and **extract** data at the same time
 - This is done by using the **ngModel** directive

```
<input type="text"  
  class="form-control" id="processor"  
  ngModel />
```

- The following directive will **not** work without a **name attribute**

```
<input name="processor"/>
```

- Declare a **template** variable to the form

```
<form #f="ngForm">
```

- Angular **automatically** attaches an **NgForm directive**
- The NgForm directive adds **additional** features
 - **Monitors** properties
 - **Validates** properties
 - It holds a **valid** property which is **true** only if **all controls** are valid

- Use **@ViewChild** to access the local reference

```
@Component({...})
export class LaptopFormComponent implements AfterViewInit {
  @ViewChild('f') form: NgForm

  ngAfterViewInit() {
    console.dir(this.form);
  }
}
```


- To submit a form bind **ngSubmit** event property to form component's **onSubmit** method

```
<form (ngSubmit)="onSubmit()" #f="ngForm">
```

- The **onSubmit** method should send the **control values** directly to an **API** through a **service** of some sort

```
onSubmit() {  
  const content = this.form.value;  
  // Send model to API  
}
```

Tracking Form State

- The **NgForm** Directive
 - Tracks if the user **touched** the control
 - Tracks if the user **changed** the control
 - Tracks if the control is **valid**
- The directive doesn't just track state
 - It can **update** the control with special **Angular CSS** classes
 - Leverage those class names to **change** appearance



State	Class if true	Class if false
The control was visited	ng-touched	ng-untouched
The control's value was changed	ng-dirty	ng-pristine
The control is valid	ng-valid	ng-invalid

- You can mark **required** fields and **invalid** data at the **same** time with a **colored** bar on the **left** of the **input box**

styles.css

```
input.ng-valid {  
    border-left: 5px solid #42A948; /* green */  
}  
  
input.ng-invalid.ng-touched {  
    border-left: 5px solid #A94442; /* red */  
}
```

- Add **HTML 5 attributes** to input fields for validation
- Angular tracks most attributes and **changes** the **state** depending on what the user enters

```
<input type="text" class="form-control"
id="processor"
required
minLength="5"
ngModel
name="processor">
```

List of Validators / Third-party Validators

- Angular is shipped with the following validators
 - <https://angular.dev/api/forms/Validators>
- For template-driven forms you will need directives
 - <https://angular.dev/api?type=directive>
- There are multiple npm packages for custom validators
 - <https://www.npmjs.com/package/ng5-validation>

Outputting Error Messages

- The user should know **exactly** what went wrong
- Leverage the control's **state** to reveal a helpful **message**
- Add a template reference **variable** in the **input**

```
<input type="text" class="form-control"
id="processor"
required
ngModel
name="processor"
#processor="ngModel">
```

Outputting Error Messages

- Create a div and **display** it **only** when the control state is **invalid**
- Use the reference **variable** to **check** the state
- Add a **helpful** message **inside** the div

```
@if(processor.invalid && processor.touched ){  
  <div alert alert-danger">  
    Processor is required!  
  </div>  
}
```


- We can **bind** the form's overall **validity** using the **reference variable** declared in the **<form>** tag
- **Block** the submit button in case a control has **invalid** state

```
<button type="submit" class="btn btn-success"  
[disabled]="f.invalid">  
Submit  
</button>
```



- Instantly react to any changes using **two-way** data binding

```
<input type="text" class="form-control"
  id="processor"
  required
  [(ngModel)]="laptop.processor"
  name="processor"
  #processor="ngModel">
```

```
constructor() {
  this.laptop = new Laptop()
}
```

The NgModelGroup Directive

- Group similar input fields using **ngModelGroup**
- Useful for input fields that have the **same validation**
 - Password / Confirm password

```
<div  
  ngModelGroup="passData"  
  #passData="ngModelGroup">
```

```
@if(passData.invalid && passData.touched){  
  <div>  
    Both passwords must be valid!  
  </div>  
}
```


Setting and Patching Form Value

- Use **setValue()** or **patchValue()** to change the form from **inside** the component or add default values

```
changeInput() {  
  this.laptopForm.form.patchValue({  
    ram: '16 GB'  
    processor: 'Intel Core i7'  
  });  
}
```

- After a form is submitted resetting is necessary to **clear** all input fields and **reset** the **track state**

```
onSubmit() {  
  const body = this.form.value;  
  // Send body to an API  
  this.form.reset();  
}
```





Handling Forms

Reactive Forms

Reactive Forms Overview

- There are some scenarios that can't be **resolved** using template-driven forms
 - **Using** Form Arrays
 - Dynamic Form **Creation**



- In order to **use** reactive forms, we need the **Reactive Forms Module**

```
import { ReactiveFormsModule } from '@angular/forms'
```

- Now we have **access** to all the needed **directives**
 - **formGroup**
 - **formControl** and **formControlName**
 - **formGroupName**
 - **formArrayName**

The Component Class

- The component class will create **instances** of **FormGroup** and **FormControl** that will bind later in the template
- The core **idea** is to **transfer** most of the logic from the **template** inside the **component** class

```
import { FormGroup, FormControl } from '@angular/forms'
```

```
this.laptopForm = new FormGroup({  
  processor : new FormControl('Intel Core i7'),  
  ram : new FormControl('16 GB DDR4')  
});
```

- In the **template** we have to **mark** the main **formGroup** and after that add **formControlName** to each form control

```
<form (ngSubmit)="save()" [formGroup]="laptopForm">
```

```
<input type="text" class="form-control" id="processor"  
required  
formControlName="processor">
```

The **name** of the **key**
instance

- Two ways to **access** the **properties** of the form model

```
laptopForm.controls.processor.valid
```

```
laptopForm.get('processor').valid
```

- The idea is to **shorten** the **template** and **transfer** such logic in the **component** when using **reactive forms**

- Use **FormBuilder** service to avoid create **instances** of **FormGroup** and **FormControl** name

```
import { FormBuilder } from '@angular/forms';
```

- Inject it **into** the constructor

```
constructor(private fb : FormBuilder) { }
```

```
this.laptopForm = this.fb.group({  
  processor : 'Intel Core i7',  
  ram : '16 GB DDR4'  
});
```



- In reactive forms we can add validation more **dynamically** based on user **action**
- We can **adjust** rules at **runtime**
- We can create **custom** validators
 - Custom validators excepting **parameters**
- **Cross-field** validations and more



- Defining our **FormGroup** with a **FormBuilder** allows us to add an **array** of validations using the **Validators** class

```
this.laptopForm = this.fb.group({  
  processor : [  
    'Intel core i7', [  
      Validators.required,  
      Validators.minLength(10)  
    ]  
  ]  
});
```



- The **formGroup** directive has an **errors** property which can be used to **show** errors only when **needed**

```
@if(laptopForm.get('processor').touched
|| laptopForm.get('processor').dirty
&& laptopForm.get('processor').errors") {
<div class="alert alert-danger">
  @if(laptopForm.get('processor').errors.required) {
<span>
  Processor is required!
</span>}
  @if(laptopForm.get('processor').errors.minlength) {
<span>
  Processor should be at least 10 symbols long!
</span>}
</div>}
```

Watching and Reacting to Changes

- Using **Reactive Forms**, we have the ability to **watch** and **react** to changes on form **groups** and form **controls**
- Whenever a **value** of an input **changes** we can **subscribe** to that event and handle the **observable**

```
this.laptopForm.get('os')  
  .valueChanges  
  .subscribe(console.log);
```



- Import **throttleTime** from the following library

```
import { throttleTime } 'rxjs/operators';
```

- Attach the **throttleTime** function to a form control's **valueChanges** event

```
processorControl.valueChanges  
.pipe(throttleTime(1500))  
.subscribe(value => {  
    console.log(value);  
});
```


- There are **three** types of Directives
 - Components, Structural, Attribute
- There are **two** ways to handle **forms** in Angular
 - Template-driven Forms (two-way binding)
 - Reactive Forms (more dynamic approach)
- Directives are **integrated** into **Form Modules**



Questions?



SoftUni



SoftUni Diamond Partners



- Software University – High-Quality Education, Profession and Job for Software Developers
 - softuni.bg, softuni.org
- Software University Foundation
 - softuni.foundation
- Software University @ Facebook
 - facebook.com/SoftwareUniversity



- This course (slides, examples, demos, exercises, homework, documents, videos and other assets) is **copyrighted content**
- Unauthorized copy, reproduction or use is illegal
- © SoftUni – <https://softuni.org>
- © Software University – <https://softuni.bg>

