



Configure



Общие настройки



Управление исходным кодом



Triggers



Environment



Save

Применить

Общие настройки

Enabled



Описание

Plain text [Предпросмотр](#)



GitHub project



Throttle builds



Удалять устаревшие сборки



Это - параметризованная сборка



Разрешить параллельный запуск задачи

Расширенные 

Управление исходным кодом

Connect and manage your code repository to automatically pull the latest code for your builds.

☐ Нет

☒ Git

Repositories

Repository URL

https://github.com/DayronAdmit/java_for_testers

Credentials

- none -

+ Add

Расширенные ▾

+ Add Repository

Branches to build

Branch Specifier (blank for 'any')

*/main

+ Add Branch

Просмотрщик репозитория

(Автоматически)

Additional Behaviours

+ Добавить

Triggers

Set up automated actions that start your build based on specific events, like code changes or scheduled times.

- ☐ Trigger builds remotely (e.g., from scripts)
- ☐ GitHub hook trigger for GITScm polling
- ☐ Запускать периодически
- ☐ Запустить по окончании сборки других проектов
- ☐ Опрашивать SCM об изменениях

Environment

Configure settings and variables that define the context in which your build runs, like credentials, paths, and global parameters.

- ☐ Delete workspace before build starts
- ☐ Use secret text(s) or file(s)
- ☐ Add timestamps to the Console Output
- ☐ Terminate a build if it's stuck
- ☐ With Ant

Шаги сборки

Automate your build process with ordered tasks like code compilation, testing, and deployment.

Invoke Gradle script

☐ Invoke Gradle

☒ Use Gradle Wrapper

☐ Make gradlew executable

Wrapper location

Tasks



Расширенные ▾



Edited

[+ Добавить шаг сборки](#)

Послесборочные операции

Define what happens after a build completes, like sending notifications, archiving artifacts, or triggering other jobs.

Allure Report ✕

☐ Disabled

Allure Version

Select which version of Allure to use for report generation.



Results:

Paths to Allure results directories relative from workspace.

E.g. **target/allure-results**.

Path

[+ Добавить](#)

Properties

[+ Добавить](#)

Allure CLI Installation

Select Allure 2 CLI installation. If only one installation is configured, it will be used automatically.

2.39.0



Расширенные ▾

Publish JUnit test result report



XML файлы с отчетами о тестировании

[Fileset 'includes'](#) setting that specifies the generated raw XML report files, such as 'myproject/target/test-reports/*.xml'. Basedir of the fileset is [the workspace root](#).

/test-results//*.xml

Test output retention

None

☐

keep all the properties

☐

Keep original test names, even when reporting from multiple stages

Health report amplification factor

1,0

1% failing tests scores as 99% health. 5% failing tests scores as 95% health

Allow empty results

☐

Do not fail the build on empty test results

Skip publishing checks

☐

If unchecked, then issues will be published to SCM provider platforms

Checks name

Skip marking build as unstable on test failure

☐ If checked, the test failures will still be reported but won't mark the build as unstable

Skip report files older than build start

☐ If checked, the test report files older than build start will not be included in the parsing

+ Добавить шаг после сборки