

Optimal Sizing of a Nuclear Reactor for Embedded Grid Systems

Preliminary Work

Samuel G. Dotson
Advanced Reactors and Fuel Cycles Group

University of Illinois at Urbana-Champaign

May 28, 2020



ILLINOIS



Outline

1 Motivation

Illinois Climate Action Plan (iCAP)
Need for Nuclear
Framing the Question

2 Methods

3 Results

RAVEN results
Temoa: Business As Usual
Temoa: Nuclear Scenarios
Scenario 1: Zero Capital Costs
Scenario 2: No Capacity Limit
Scenario 3: Small Modular Reactor

4 Conclusion

iCAP Goal and Obstacles




Figure: Shows projected CO₂ emissions for UIUC [7]. Offsets include shutdown of the Blue Waters Supercomputer.

Goal:

Carbon neutrality by 2050 or sooner.

Obstacles:

- ① Requires *zero net space growth*.
- ② Campus depends on a system of steam tunnels for heating.
- ③ and more...

The Nuclear Option

Nuclear energy...

- ① ...produces almost no carbon emissions [6].
- ② ...can produce high-temperature steam.
- ③ ...requires little physical space*.

*compared to solar and wind.




Figure: Lifetime carbon-equivalent emissions by energy source from IPCC findings [6].

What is the optimal size for a nuclear reactor on the UIUC grid?

Outline

① Motivation

- Illinois Climate Action Plan (iCAP)
- Need for Nuclear
- Framing the Question

② Methods

③ Results

- RAVEN results
- Temoa: Business As Usual
- Temoa: Nuclear Scenarios
- Scenario 1: Zero Capital Costs
- Scenario 2: No Capacity Limit
- Scenario 3: Small Modular Reactor

④ Conclusion

To answer this question we considered two modeling approaches:

- ① RAVEN (INL) - Risk Analysis and Virtual Environment [1][5]
- ② TEMOA (NCSU) - Tools for Energy Model Optimization and Analysis [3][2]

Workflow in RAVEN




Figure: A general optimization workflow in RAVEN

Outline

1 Motivation

Illinois Climate Action Plan (iCAP)

Need for Nuclear

Framing the Question

2 Methods

3 Results

RAVEN results

Temoa: Business As Usual

Temoa: Nuclear Scenarios

Scenario 1: Zero Capital Costs

Scenario 2: No Capacity Limit

Scenario 3: Small Modular Reactor

4 Conclusion



Step 1: Generate Synthetic Histories




Figure: Shows the synthetic (red) vs typical (blue) hourly electricity demand at UIUC.




Figure: Shows the synthetic (red) vs typical (blue) hourly steam demand at UIUC.

BAU: Grid Model




Figure: Graph representation of the UIUC embedded grid.

BAU: Generation




Figure: The change in activity from each energy source from 2020-2030. Assuming 1% demand growth each year

BAU: Emissions




Figure: The change in activity from each energy source from 2020-2030. Assuming 1% demand growth each year




Figure: Predicted growth in emissions from iCAP [7].

Nuclear Scenarios



- ① Scenario 1: Zero Capital Costs
- ② Scenario 2: No Capacity Limit
- ③ Scenario 3: Limited to Small Modular Reactor (100MWth)

Table: Summary of Nuclear Scenarios. Costs from EIA and NEI reports [4][8].

Scenario	Operation Costs [\$/MWh(th)]	Capital Costs [M\$/MWth]	Maximum Capacity [MWth]
1	8.91	-	-
2	8.91	1.982	-
3	8.91	1.982	100

Scenario 1: Generation




Figure: The electric generation without a cost constraint on nuclear

Scenario 1: Emissions



Figure: The carbon equivalent emissions without a cost constraint on nuclear

Scenario 2: Generation




Figure: The electric generation without a size constraint on nuclear

Scenario 2: Emissions




Figure: The carbon equivalent emissions without a size constraint on nuclear

Scenario 3: Generation




Figure: The electric generation with constrained nuclear.




Figure: The steam generation with constrained nuclear

Scenario 3: Emissions




Figure: The carbon equivalent emissions without a cost constraint on nuclear

Outline

① Motivation

Illinois Climate Action Plan (iCAP)
Need for Nuclear
Framing the Question

② Methods

③ Results

RAVEN results
Temoa: Business As Usual
Temoa: Nuclear Scenarios
Scenario 1: Zero Capital Costs
Scenario 2: No Capacity Limit
Scenario 3: Small Modular Reactor

④ Conclusion

Conclusion



Acknowledgement

This work was made possible with data provided by UIUC Facilities and Services, in particular, Morgan White, Mike Marquissee, and Mike Larson. Additionally, this work is funded by the NRC Fellowship Program.

References I

- [1] T. E. Baker, A. S. Epiney, C. Rabiti, and E. Shittu.
Optimal sizing of flexible nuclear hybrid energy system components considering wind volatility.
212:498–508.
- [2] J.F. DeCarolis, S. Babaei, B. Li, and S. Kanungo.
Modelling to generate alternatives with an energy system optimization model.
79:300–310.
- [3] Joseph DeCarolis, Kevin Hunter, and Sarat Sreepathi.
The TEMOA project: tools for energy model optimization and analysis.
- [4] Harsh Desai.
Nuclear costs in context.
- [5] Aaron (ORCID:0000000291485749) Epiney, Cristian (ORCID:0000000201085291) Rabiti, Andrea (ORCID:0000000328664346) Alfonsi, Paul (ORCID:0000000296729044) Talbot, and Francesco Ganda.
Report on the economic optimization of a demonstration case for a static n-r HES configuration using RAVEN.

References II

- [6] Intergovernmental Panel on Climate Change.
Climate Change 2014 Mitigation of Climate Change: Working Group III Contribution to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change.
Cambridge University Press.
- [7] iSEE.
Illinois climate action plan (iCAP).
- [8] U.S. Department of Energy.
Capital cost estimates for utility scale electricity generating plants.
page 141.