

Optimal Sizing of a Nuclear Reactor for Embedded Grid Systems

Preliminary Work

Samuel G. Dotson
Advanced Reactors and Fuel Cycles Group

University of Illinois at Urbana-Champaign

May 29, 2020



ILLINOIS



Outline

1 Motivation

Illinois Climate Action Plan (iCAP)

Need for Nuclear

Framing the Question

2 Methods

Overview

Methods for RAVEN

Methods for Temoa

Modeling-to-Generate-Alternatives (MGA)

3 Results

RAVEN results

Temoa: Business As Usual

Temoa: Nuclear Scenarios

Scenario 1: Zero Capital Costs

Scenario 2: No Capacity Limit

Scenario 3: Small Modular Reactor

4 Conclusion

iCAP Goal and Obstacles




Figure: Shows projected CO₂ emissions for UIUC [9]. Offsets include shutdown of the Blue Waters Supercomputer.

Goal:

Carbon neutrality by 2050 or sooner.

Obstacles:

- ① Requires *zero net space growth*.
- ② Campus depends on a system of steam tunnels for heating.
- ③ and more...

The Nuclear Option

Nuclear energy...

- ① ...produces almost no carbon emissions [8].
- ② ...can produce high-temperature steam.
- ③ ...requires little physical space*.

*compared to solar and wind.




Figure: Lifetime carbon-equivalent emissions by energy source from IPCC findings [8].

What is the optimal size for a nuclear reactor on the UIUC grid?

Outline

1 Motivation

- Illinois Climate Action Plan (iCAP)
- Need for Nuclear
- Framing the Question

2 Methods

- Overview
- Methods for RAVEN
- Methods for Temoa
- Modeling-to-Generate-Alternatives (MGA)

3 Results

- RAVEN results
- Temoa: Business As Usual
- Temoa: Nuclear Scenarios
- Scenario 1: Zero Capital Costs
- Scenario 2: No Capacity Limit
- Scenario 3: Small Modular Reactor

4 Conclusion

To answer this question we considered two modeling approaches:

- ① RAVEN (INL) - Risk Analysis and Virtual Environment [1][6]
- ② TEMOA (NCSU) - Tools for Energy Model Optimization and Analysis [3][4][7]

Both modeling tools are open source and use publicly available version control software, `Git`, to track changes.

The analysis in RAVEN requires some external modules that are not currently available to the public.

Workflow in RAVEN




Figure: A general optimization workflow in RAVEN



Temoa Implementation

Temoa uses linear optimization to search decision space [7].

- ① Objective Function (minimizes system cost)
- ② Constraints
 - ① Demand must be satisfied at each time step (always).
 - ② Carbon limits must be satisfied at each time step (optionally).
- ③ Variables
 - ① Cost
 - ② Generation
 - ③ Capacity



Modeling-to-Generate-Alternatives (MGA)

Temoa uses the Hop-Skip-Jump formulation of MGA [2].

- ① Identify an optimal solution by any method.
- ② Relax the original objective function by adding a slack variable.
- ③ Find another sub-optimal solution that still satisfies constraints.

Outline

1 Motivation

Illinois Climate Action Plan (iCAP)

Need for Nuclear

Framing the Question

2 Methods

Overview

Methods for RAVEN

Methods for Temoa

Modeling-to-Generate-Alternatives (MGA)

3 Results

RAVEN results

Temoa: Business As Usual

Temoa: Nuclear Scenarios

Scenario 1: Zero Capital Costs

Scenario 2: No Capacity Limit

Scenario 3: Small Modular Reactor

4 Conclusion

Step 1: Generate Synthetic Histories




Figure: Shows the synthetic (red) vs typical (blue) hourly electricity demand at UIUC.




Figure: Shows the synthetic (red) vs typical (blue) hourly steam demand at UIUC.

BAU: Grid Model




Figure: Graph representation of the UIUC embedded grid.

BAU: Generation




Figure: The change in activity from each energy source from 2020-2030. Assuming 1% demand growth each year

BAU: Emissions




Figure: The change in activity from each energy source from 2020-2030. Assuming 1% demand growth each year




Figure: Predicted growth in emissions from iCAP [9].



Nuclear Scenarios

- ① Scenario 1: Zero Capital Costs
- ② Scenario 2: No Capacity Limit
- ③ Scenario 3: Limited to Small Modular Reactor (100MWth)

Table: Summary of Nuclear Scenarios. Costs from EIA and NEI reports [5][10]. Assumes thermal efficiency of 33%.

Scenario	Operation Costs [\$ /MWth(th)]	Capital Costs [M\$/MWth]	Maximum Capacity [MWth]
1	8.91	-	-
2	8.91	1.982	-
3	8.91	1.982	100

Nuclear Scenarios: Grid Model




Figure: Graph representation of the UIUC grid with nuclear reactor.

Scenario 1: Generation




Figure: The electric generation without a cost constraint on nuclear

Scenario 1: Emissions



Figure: The carbon equivalent emissions without a cost constraint on nuclear

Scenario 2: Generation




Figure: The electric generation without a size constraint on nuclear

Scenario 2: Emissions




Figure: The carbon equivalent emissions without a size constraint on nuclear

Scenario 3: Generation




Figure: The electric generation with constrained nuclear.




Figure: The steam generation with constrained nuclear

Scenario 3: Emissions




Figure: The carbon equivalent emissions without a cost constraint on nuclear

Outline

① Motivation

- Illinois Climate Action Plan (iCAP)
- Need for Nuclear
- Framing the Question

② Methods

- Overview
- Methods for RAVEN
- Methods for Temoa
- Modeling-to-Generate-Alternatives (MGA)

③ Results

- RAVEN results
- Temoa: Business As Usual
- Temoa: Nuclear Scenarios
- Scenario 1: Zero Capital Costs
- Scenario 2: No Capacity Limit
- Scenario 3: Small Modular Reactor

④ Conclusion

Conclusion



- ① Replacing “ABBOTT” with nuclear would resolve all of the Universities carbon goals, *regardless of other offsets and building growth*.
- ② Adding a small modular reactor will cost effectively meet carbon goals until mid-decade when renewable resources must be expanded.

Acknowledgement

This work was made possible with data provided by UIUC Facilities and Services, in particular, Morgan White, Mike Marquissee, and Mike Larson.

Also thanks to Roberto Fairhurst and other members of the ARFC group for their input.

Additionally, this work is funded by the NRC Fellowship Program.

References I

- [1] T. E. Baker, A. S. Epiney, C. Rabiti, and E. Shittu.
Optimal sizing of flexible nuclear hybrid energy system components considering wind volatility.
212:498–508.
- [2] E. Downey Brill, Shouu-Yuh Chang, and Lewis D. Hopkins.
Modeling to generate alternatives: The HSJ approach and an illustration using a problem in
land use planning.
28(3):221–235.
Publisher: INFORMS.
- [3] J.F. DeCarolis, S. Babaee, B. Li, and S. Kanungo.
Modelling to generate alternatives with an energy system optimization model.
79:300–310.
- [4] Joseph DeCarolis, Kevin Hunter, and Sarat Sreepathi.
The TEMOA project: tools for energy model optimization and analysis.
- [5] Harsh Desai.
Nuclear costs in context.

References II

- [6] Aaron (ORCID:0000000291485749) Epiney, Cristian (ORCID:0000000201085291) Rabiti, Andrea (ORCID:0000000328664346) Alfonsi, Paul (ORCID:0000000296729044) Talbot, and Francesco Ganda.
Report on the economic optimization of a demonstration case for a static n-r HES configuration using RAVEN.
- [7] Kevin Hunter, Sarat Sreepathi, and Joseph F. DeCarolís.
Modeling for insight using tools for energy model optimization and analysis (temoa).
40:339–349.
- [8] Intergovernmental Panel on Climate Change.
Climate Change 2014 Mitigation of Climate Change: Working Group III Contribution to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change.
Cambridge University Press.
- [9] iSEE.
Illinois climate action plan (iCAP).
- [10] U.S. Department of Energy.
Capital cost estimates for utility scale electricity generating plants.
page 141.