

Worksheet-2 in R

Worksheet for R Programming

Instructions:

- Use RStudio or the RStudio Cloud accomplish this worksheet. + Save the R script as *RWorksheet_lastname#2.R*.
- Create your own *GitHub repository* and push the R script as well as this pdf worksheet to your own repo.

Accomplish this worksheet by answering the questions being asked and writing the code manually.

Using Vectors

1. Create a vector using : operator

a. Sequence from -5 to 5. Write the R code and its output. Describe its output.

Answer:

```
seq(-5:5)
[1]  -5  -4  -3  -2  -1   0   1   2   3   4   5
```

b. `x <- 1:7`. What will be the value of x?

Answer:

```
> x <- 1:7
> x
[1] 1 2 3 4 5 6 7
```

2.* Create a vector using `seq()` function

a. `seq(1, 3, by=0.2)` # specify step size

Write the R code and its output. Describe the output.

Answer:

```
seq(1,3,by = 0.2)
[1] 1.0 1.2 1.4 1.6 1.8 2.0 2.2 2.4 2.6 2.8 3.0
```

3. A factory has a census of its workers. There are 50 workers in total. The following list shows their ages: 34, 28, 22, 36, 27, 18, 52, 39, 42, 29, 35, 31, 27, 22, 37, 34, 19, 20, 57, 49, 50, 37, 46, 25, 17, 37, 43, 53, 41, 51, 35, 24, 33, 41, 53, 40, 18, 44, 38, 41, 48, 27, 39, 19, 30, 61, 54, 58, 26, 18.

```
Wrkrs_age <- c(34,28,22,36,27,18,52,39,42,29,35,31,27,22,37,
               34,19,20,57,49,50,37,46,25,17,37,43,53,41,51,
               35,24,33,41,53,40,18,44,38,41,48,27,39,19,30,
               61,54,58,26,18)
```

- a. Access 3rd element, what is the value?

Answer:

```
Wrkrs_age[3]
[1] 22
```

- b. Access 2nd and 4th element, what are the values?

Answer:

```
Wrkrs_age[2]
[1] 28
Wrkrs_age[4]
[1] 36
```

- c. Access all but the 1st element is not included. Write the R code and its output.

R code:

```
Wrkrs_age[2:50]
```

Output:

```
Wrkrs_age[2:50]
[1] 28 22 36 27 18 52 39 42 29 35 31 27 22 37 34 19 20 57 49 50 37 46 25 17
[25] 37 43 53 41 51 35 24 33 41 53 40 18 44 38 41 48 27 39 19 30 61 54 58 26
[49] 18
```

4. *Create a vector `x <- c("first"=3, "second"=0, "third"=9)`. Then named the vector, `names(x)`.

- a. Print the results. Then access `x[c("first", "third")]`.
Describe the output.

Answer: The output are now arranged in row and column.

```
names <- c("first"=3, "second"=0, "third"=9)
names
first second third
    3      0     9
```

- b. Write the code and its output.

R CODE:

```
names [c("first", "third")]
```

OUTPUT:

```
names [c("first", "third")]
      first third
        3     9
```

5. Create a sequence `x` from `-3:2`.

Answer:

```
x <- c(-3:2)
x
[1] -3 -2 -1  0  1  2
```

- a. Modify 2nd element and change it to 0;

```
x[2] <- 0
```

x

Describe the output.

ANSWER: THE SECOND ELEMENT WAS REPLACED BY THE ASSIGNED NEW VALUE WHICH IS "0"

```
[1] -3  0 -1  0  1  2
```

b. Write the code and its output.

R CODE:

```
x[2] <- 0  
x
```

OUTPUT:

```
[1] -3  0 -1  0  1  2
```

6. *The following data shows the diesel fuel purchased by Mr. Cruz.

Month	Jan	Feb	March	Apr	May	June
Price per liter (PhP)	52.50	57.25	60.00	65.00	74.25	54.00
Purchase-quantity(Liters)	25	30	40	50	10	45

a. Create a data frame for month, price per liter (php) and purchase-quantity (liter).
Write the codes.

R CODES:

```
Month = c("Jan","Feb","March","Apr","May","June")  
Php <- c(52.20,57.25,60.00,65.00,74.25,54.00)  
Liters <- c(25,30,40,50,10,45)
```

```
Diesel_fuel <- data.frame (Month, Php, Liters)  
Diesel_fuel
```

b. What is the average fuel expenditure of Mr. Cruz from Jan to June? Note: Use
`weighted.mean(liter, purchase)`

Answer:

```
weighted.mean(Php, Liters)  
[1] 59.225
```

7. R has actually lots of built-in datasets. For example, the rivers data “gives the lengths (in miles) of 141 “major” rivers in North America, as compiled by the US Geological Survey”.

- a. Type “rivers” in your R console. Create a vector data with 7 elements, containing the number of elements (length) in rivers, their sum (sum), mean (mean), median (median), variance (var) standard deviation (sd), minimum (min) and maximum (max).

```
data <- c(length(rivers), sum(rivers), mean(rivers), median(rivers), var(rivers),
sd(rivers), min(rivers), max(rivers))
```

- b. What are the results?

Answer:

```
rivers
[1] 735 320 325 392 524 450 1459 135 465 600 330 336 280 315
[15] 870 906 202 329 290 1000 600 505 1450 840 1243 890 350 407
[29] 286 280 525 720 390 250 327 230 265 850 210 630 260 230
[43] 360 730 600 306 390 420 291 710 340 217 281 352 259 250
[57] 470 680 570 350 300 560 900 625 332 2348 1171 3710 2315 2533
[71] 780 280 410 460 260 255 431 350 760 618 338 981 1306 500
[85] 696 605 250 411 1054 735 233 435 490 310 460 383 375 1270
[99] 545 445 1885 380 300 380 377 425 276 210 800 420 350 360
[113] 538 1100 1205 314 237 610 360 540 1038 424 310 300 444 301
[127] 268 620 215 652 900 525 246 360 529 500 720 270 430 671
[141] 1770
> #data
> data
[1] 141.0000 83357.0000 591.1844 425.0000 243908.4086 493.8708
[7] 135.0000 3710.0000
```

- c. Write the code and its outputs.

R code:

```
#rivers
rivers
```

Output:

```
[1] 735 320 325 392 524 450 1459 135 465 600 330 336 280 315
[15] 870 906 202 329 290 1000 600 505 1450 840 1243 890 350 407
[29] 286 280 525 720 390 250 327 230 265 850 210 630 260 230
[43] 360 730 600 306 390 420 291 710 340 217 281 352 259 250
[57] 470 680 570 350 300 560 900 625 332 2348 1171 3710 2315 2533
[71] 780 280 410 460 260 255 431 350 760 618 338 981 1306 500
[85] 696 605 250 411 1054 735 233 435 490 310 460 383 375 1270
[99] 545 445 1885 380 300 380 377 425 276 210 800 420 350 360
[113] 538 1100 1205 314 237 610 360 540 1038 424 310 300 444 301
[127] 268 620 215 652 900 525 246 360 529 500 720 270 430 671
[141] 1770
```

R code:

```
#data  
data
```

output:

```
[1] 141.0000 83357.0000 591.1844 425.0000 243908.4086 493.8708  
[7] 135.0000 3710.000
```

8. The table below gives the 25 most powerful celebrities and their annual pay as ranked by the editions of Forbes magazine and as listed on the Forbes.com website.

Power Ranking	Celebrity Name	Pay	Power Ranking	Celebrity Name	Pay
1	Tom Cruise	67	14	Paul McCartney	40
2	Rolling Stones	90	15	George Lucas	233
3	Oprah Winfrey	225	16	Elton John	34
4	U2	110	17	David Letterman	40
5	Tiger Woods	90	18	Phil Mickelson	47
6	Steven Spielberg	332	19	J.K. Rowling	75
7	Howard Stern	302	20	Bradd Pitt	25
8	50 Cent	41	21	Peter Jackson	39
9	Cast of the Sopranos	52	22	Dr. Phil McGraw	45
10	Dan Brown	88	23	Jay Lenon	32
11	Bruce Springsteen	55	24	Celine Dion	40
12	Donald Trump	44	25	Kobe Bryant	31
13	Muhammad Ali	55			

Figure 1: Forbes Ranking

- a. Create vectors according to the above table. Write the codes.

R codes:

```
Power_Ranking <- c(1:25)
```

```
Celebrity_Name = c("Tom Cruise", "Rolling Stones", "Oprah Winfrey", "U2", "Tiger Woods", "Steven Spielberg", "Howard Stern", "50 Cent", "Cast of the Sopranos", "Dan Brown", "Bruce Springsteen", "Donald Trump", "Muhammad Ali", "Paul McCartney", "George Lucas", "Elton John", "David Letterman", "Phil Mickelson", "J.K. Rowling", "Bradd Pitt", "Peter Jackson", "Dr. Phil McGraw", "Ja Lenon", "Celine Dion", "Kobe Bryant")
```

```
Pay <- c(67,90,225,110,90,332,302,41,52,88,55,44,55,40,233,34,40,47,75,25,39,45,32,40,31)
```

```
Celebrities_pay <- data.frame( Power_Ranking, Celebrity_Name, Pay)
```

```
Celebrities_pay
```

b. Modify the power ranking and pay of J.K. Rowling. Change power ranking to 15 and pay to 90. Write the codes and its output.

R CODES:

```
Celebrities_pay <- data.frame( Power_Ranking, Celebrity_Name,  
                               Pay)  
Celebrities_pay[Celebrities_pay == 19] <-15  
Celebrities_pay[Celebrities_pay ==75] <-90  
Celebrities_pay
```

OUTPUT:

	Power_Ranking	Celebrity_Name	Pay
1	1	Tom Cruise	67
2	2	Rolling Stones	90
3	3	Oprah Winfrey	225
4	4	U2	110
5	5	Tiger Woods	90
6	6	Steven Speilberg	332
7	7	Howard Stern	302
8	8	50 Cent	41
9	9	Cast of the Sopranos	52
10	10	Dan Brown	88
11	11	Bruce Springsteen	55
12	12	Donald Trump	44
13	13	Muhammad Ali	55
14	14	Paul McCartney	40
15	15	George Lucas	233
16	16	Elton John	34
17	17	David Letterman	40
18	18	Phil Mickelson	47
19	15	J.K Rowling	90
20	20	Bradd Pitt	25
21	21	Peter Jackson	39
22	22	Dr. Phil McGraw	45
23	23	Ja Lenon	32
24	24	Celine Dion	40
25	25	Kobe Bryant	31

c. Interpret the data.

```
Celebrities_pay <- data.frame( Power_Ranking, Celebrity_Name,
                                Pay)
```

	Power_Ranking	Celebrity_Name	Pay
1	1	Tom Cruise	67
2	2	Rolling Stones	90
3	3	Oprah Winfrey	225
4	4	U2	110
5	5	Tiger Woods	90
6	6	Steven Speilberg	332
7	7	Howard Stern	302
8	8	50 Cent	41
9	9	Cast of the Sopranos	52
10	10	Dan Brown	88
11	11	Bruce Springsteen	55
12	12	Donald Trump	44
13	13	Muhammad Ali	55
14	14	Paul Mccartney	40
15	15	George Lucas	233
16	16	Elton John	34
17	17	David Letterman	40
18	18	Phil Mickelson	47
19	19	J.K Rowling	75
20	20	Bradd Pitt	25
21	21	Peter Jackson	39
22	22	Dr. Phil McGraw	45
23	23	Ja Lenon	32
24	24	Celine Dion	40
25	25	Kobe Bryant	31