



SAFETY TOOLBOX TALK

Ref:	047	Author:	D Bibby	Date:	07.02.2024
Topic:			REFUELLING PLANT / EQUIPMENT		

This briefing is not intended to tell you how to do your jobs, it is designed to help keep you safe. We want everybody to be able to return home safely to their family and friends at the end of each day.

Service station operations and equipment are designed with safety in mind. But what happens when you fill up a machine or portable generator on site? Do you do it the safe way so you will not get hurt?

Rules to Remember.

Never smoke during refueling operations. And do not refuel near an open flame. Keep a CO2 (carbon dioxide), or an ABC Dry Powder extinguisher handy, just in case.

If there is a chance of a vehicle rolling while being refueled, chock the wheels. Before filling the fuel tank shut off the engine.

If the tank is near the engine or other hot areas, such as the manifold or muffler, let the engine cool before filling the tank.

When choosing where to refuel, consider what would happen if a spill occurred and the environmental consequences.

When transferring fuel from a can, mobile tank or fuel truck, keep the spout or nozzle in contact with the fuel tank. Few people know this, but as fuel is poured, it can generate static electricity. If a spark ignites the vapors, it is all over for you.

Do not spill the fuel because it might ignite when it comes in contact with something hot. And do not make one of the most common mistakes - overfilling the tank. If the equipment is in the hot sun, the fuel will expand and eventually overflow. Leave enough space in the tank to compensate for expansion or tilting.

After refueling has been completed, be sure all fuel has been drained from the hose and that any spills are cleaned up immediately.

Discussion Points

Do equipment fuel caps indicate the type of fuel required?

Are you familiar with what fuel each piece of equipment uses?

Which fire extinguisher do you use if needed on refuelling operations?