

Risk Assessment No: WP-008				Task: Water Circuit — Pumps, Tanks and Ring Main							
Prepared By: Derick Bibby				Date: 02.08.2026			RA Review Date: 01.08.2027				
				Reviewed By: Lee Hardy			Date: 02.08.2026				
PPE: Safety Footwear, High Visibility Jacket, High Visibility Trousers, Hard Hat, Gloves, Ear Defenders, Mask, Eye Protection											
Hazard	Persons at Risk	L	S	R	Control Measures				L	S	R
Pressurised water release during pump maintenance	Maintenance	3	3	9	- Isolate pump electrically and close upstream/downstream valves before opening casing. - Bleed pressure via test valve and verify zero at gauge. - Face-shield during casing removal in case of residual pressure. - Bunded work area or drip trays under pump body.				1	3	3
Water ring-main leak or burst under high flow	All plant personnel	2	3	6	- Weekly walk-around inspection of visible pipework, flanges and fittings. - Pressure gauge alarm on ring main — auto-stop pump on abnormal drop. - No modification to pipework without engineering assessment. - Pipework routed away from walkways where practicable.				1	3	3
Chemical release from flocculant bulk storage	Maintenance Delivery drivers	2	3	6	- Bulk storage in a bunded IBC store; dosing lines routed away from walkways. - Delivery under permit with a trained supervisor; driver remains in view. - Spill kit and eyewash at delivery point. - COSHH assessment specific to the flocculant product held with SDS.				1	3	3
Stored energy — hydraulic accumulators, pneumatic receivers	Maintenance Contractors	3	5	15	- Bleed hydraulic accumulators to zero pressure and confirm via gauge before opening manifolds. - Drain air receivers to zero via test valve before hose or fitting removal. - Padlock the isolator on the pump or compressor supplying the circuit. - PSSR examination of accumulators and receivers at statutory interval.				1	5	5
Chemical exposure — flocculant, lubricants, coolants, hydraulic fluid	Maintenance Operator	3	3	9	- COSHH assessment for every chemical on site; SDS held at MCC and maintenance office. - Chemical-resistant gloves and eye/face protection during handling and dosing. - Bunded storage; spill kits at each storage point. - Emergency eyewash station at MCC and picking station. - Waste chemicals disposed via licensed contractor; consignment notes retained.				1	3	3
Slips, trips and falls on the same level	All plant personnel	4	3	12	- Anti-slip walkways and stair-treads; wash-down at end of shift. - No trailing hoses or cables across walkways — stored on reels or coiled. - Immediate clean-up of oil, hydraulic fluid or fines spillage.				2	3	6

					• Adequate task lighting throughout the plant. • Correct footwear with slip-resistant sole to SRC.			
Environmental release — silt-laden runoff, oil spillage	Environment Site neighbours	3	4	12	• Closed-loop water recycling via thickener and filter press; filter cake removed as solid. • Silt-trap and interceptor at yard discharge; inspected weekly. • Environmental permit monitoring and sampling per permit schedule. • Spill kits at fuel, oil and flocculant points. • Bunded storage on all above-ground tanks meeting oil storage regulations.	1	4	4