

Risk Assessment No: P009			Task: Operating Road Sweeper						
Prepared By: Derick Bibby			Date: 21.08.2025			RA Review Date: 20.08.2026			
			Reviewed By: Lee Hardy			Date: 21.08.2025			
PPE: Safety Footwear, High Visibility Jacket, High Visibility Trousers, Hard Hat									
Hazard	Persons at Risk	L	S	R	Control Measures	L	S	R	
Collison with persons, vehicles, or property	Operative Site personnel Pedestrians	3	5	15	- Ensure that there is sufficient clearance between the sweeper and any obstruction (property, vehicles etc.) - Clear segregation to mark all pedestrian routes from plant work areas - Where this is not possible, all persons to notify operator upon approach to plant, prior to entering work area. This must be by way of ‘thumbs up’, which will be instructed to all personnel and visitors upon site induction. - Always use mirrors and in-cab cameras to maintain all-round visibility from the cab.	1	5	5	
Equipment failure	Operative Site personnel	3	4	12	- All-round checks must be done before start of work each day. These will include all aspects of the wagon and will be recorded on a checklist, provided to each driver at the start of the week. - All faults and damage must be recorded on the checklist and reported to Fox Group immediately. - All wagons will be roadworthy and of legal standard. - All drivers must ensure that their machines are kept sufficiently clean and mechanically sound. - All items of equipment on the wagon that are provided as safety features must be kept in sound working order. This is especially important with lights, mirrors, horn, cameras and reversing beepers. In the event of any of these elements not working, stop and report the issue immediately. - It is also extremely important that windows are kept clean, to	2	4	8	

					maintain all-round vision from within the cab.			
Incorrect/Unauthorised Use	Operative Site personnel Pedestrians	4	5	20	- Only assigned licenced drivers are permitted to drive wagons. - Safe Working Load (SWL) must not be exceeded. - All wagons must be kept locked and isolated when not in use. Engines must be switched off and keys on the driver's person. No wagons must ever be left running unattended. - All drivers should acquaint themselves with the manual for the wagon they are provided and operate according to the manufacturer's instructions.	1	5	5
Overtuning	Operative	2	4	8	- Only operate on finished roads or concrete hardstanding. - Driver must not operate or traverse wagon while visibility is poor. If visibility worsens while working, stop the operation and safely isolate wagon until it is safe to carry on. - Ensure haul roads/routes are maintained and in a good condition to drive over. - Thoroughly check wheels for cracks and warps, and tyre pressures and condition at the beginning and end of each shift. - Always wear a seatbelt. Operatives must NEVER clip in a seatbelt and sit on it. This will be inspected regularly by the Fox Group supervisor/foreman.	1	4	4

COSHH & Environmental Hazards	Operative Site personnel Pedestrians	4	4	16	- COSHH assessments for diesel and hydraulic oil have been created and communicated to all operatives on site. - When waiting to work, engines should be switched off to reduce exhaust fumes. Operatives must not sit inside a machine with an idling engine. - Daily plant checks for leaks, cracks, and hoses/attachment fittings to identify any potential problems. - Report all spillages immediately - Tank only to be emptied/filled at designated sites.	2	4	8
Falls From Height	Operative	3	4	12	- When entering or exiting wagon, maintain 3 points of contact at all times and always face towards the cab. - Never jump from the cab. - Inspect steps, grips, handles on daily plant checks - Where fitted, ensure hand rails are secure and clean	1	4	4
Fire	Operative Site personnel	2	4	8	- No smoking in any wagon - If smell or see smoke, switch off and isolate wagon immediately and report to Fox Group foreman/supervisor.	1	4	4