

Safe System of Work

Loading of Tipper Wagons

Ref. SSoW-016	Author.	Lee Hardy	Date:	01.09.2022
---------------	---------	-----------	-------	------------

Reviewed By: Name	Derick Bibby	Date of Review:	29.08.2025
-------------------	--------------	-----------------	------------

Record of Amendments			

Next Review Due Date:			31.08.2026
-----------------------	--	--	------------

Overview

The following information provides guidance on the company's Safe System of Work for works that involve the loading of Tipper Wagons.

The loading of Tipper Wagons can be dangerous. The machinery or load can seriously hurt people. A lot of vehicles overturn each year, sometimes causing fatal accidents.

All employees have a responsibility for their safety and the safety of others by adhering to these codes of practice.

The Operator must always refer to any task Risk Assessment and Method Statements prior to starting works.

Hazards Identified

- Adverse weather
- Crushing
- Machine Rollover
- Cuts and abrasions
- Vehicle movements
- Falls from height.
- Manual handling
- Slips & Trips.

Personal Protective Equipment (PPE) Requirements



All loading will be under the direction of site management. You must ensure the integrity of the upper body before loading, establish loading and traffic management instructions on arrival at site and observe legal requirements with regard to the loading of road vehicles.

Drivers must ensure that loads are kept within the legal axle and gross vehicle weight limits. Trimming of loads and/or disposing of surplus material may only be carried out in designated areas agreed by site management.

Drivers must follow the instructions given by the loading machine operator. They must park to be loaded in the position guided by the operator.

Exclusion Zone – Loading Operations

Loading must not commence until a suitable exclusion zone is in place and the area is controlled to prevent unauthorised persons entering the loading area.

- The driver must ensure that only the loading machine operator and any authorised site personnel are within the loading area.
- The exclusion zone must include the area around the tipper wagon and the working radius of the loading machine, including any area where material may fall, spill, or be discharged.
- Drivers must remain in the cab while the vehicle is being loaded or stand in a safe designated area agreed with the site management / loading operator.
- Pedestrians must be kept clear of the exclusion zone at all times and no person must stand or walk between the loading machine and the wagon during loading.
- If any person enters the exclusion zone at any time, loading must STOP immediately and must not recommence until the area is confirmed clear.
- Where applicable, physical controls such as cones, barriers, signage and designated walkways must be used to support segregation between loading operations and pedestrians.
- The driver must never approach the loading machine, wagon body, chute, hopper, or loading point unless the loading machine has stopped operations and the operator has acknowledged the driver's presence.

Tipper drivers are required to inspect their load to ensure it has been loaded centrally within the body. If a load is found to be loaded off centre or too much to the front or rear, contact the loading operator to instigate controlled rectification. It is the driver's responsibility to ensure that the load is secure and loaded correctly.

Material should be checked for uniform colour and consistency to ensure it matches the material description they have been provided with.

Never enter the body while it is parked in a position where there is a possibility of the vehicle being loaded.

Remain in the cab while the vehicle is being loaded or stand in a safe designated area, maintaining segregation from the loading plant and within the agreed exclusion zone arrangements..

If loading from a chute or hopper, refer to site management for site specific rules.

After the vehicle has been loaded and sheeted, check for loose material.

It is strictly forbidden to climb onto a loaded vehicle or stand on top of the load.

Inspection of the load can only take place in a designated area for inspection or at a point where it is safe to do so. This should be via the purpose made platform/access system. If this is not available then



access can be made via the body ladder and handles, maintaining three points of contact at all times.

Always ensure the tailboard is locked into position before moving off.