

Fox Group Quarries

VEHICLE RULES

Managers Rules Vehicles

Issued to _____

It should be noted that these rules placed in writing by the manager become legally binding under the Quarry regulations (1999) and should be adhered to as the Regulation itself. This means that it is an offence not to comply with rules and other instructions (Verbal or written) given by the Manager or his appointed deputy. These rules are intended to draw attention to the many dangers when driving in Tong Quarry. They supersede any previous rules and are particular to Tong Quarry only.

The object of these rules is to help each driver/operator: -

- Comply with relevant Health and Safety Policies, Provisions and Regulations.
- Work safely with other employees and/or contractors
- Maintain & Improve safety within the quarry.

Any operator failing to comply or found negligent will face disciplinary action.

Managers Rules
Vehicles

CONTENTS

- 1. Introduction**
- 2. Regulations**
- 3. Risk Assessments**
- 4. Traffic Routes**
- 5. Driver Requirements**
- 6. Training, Assessment and Appointment**
- 7. Contractors**
- 8. Safety Specifications**
 - 8.1 Lighting**
 - 8.2 Visual Aids**
 - 8.3 Flashing Beacons**
 - 8.4 Safety Warning Devices**
 - 8.5 Seat Belts/Seating**
 - 8.6 Fire Extinguishers**
 - 8.7 Small Vehicles**
 - 8.8 Air Conditioning**
- 9. Routine Daily checks**
- 10. Brake Testing**
- 11. Maintenance & Servicing**
- 12. Vehicle Recovery**
- 13. Reversing**
- 14. Parking**
- 15. Jump starting**
- 16. Traffic Signs**

17. Pedestrians

18. Towing of Trailers/Browsers

19. Overhead Obstructions/Power Lines

20. Underground Services

21. Edge Protection

22. Tipping operations

23. Unsafe Driving/Substance Abuse

24. Access & Egress

25. General Rules of the Road

26. Specific Vehicles: -

26.1 Rigid/Articulated Dumpers and Lorries

26.2 Excavators

26.3 Wheeled Loaders

26.4 Forklift Trucks/Telehandlers

26.5 Safety in working with Power Operated Static & Mobile Work Platforms

26.6 Ancillary Vehicles

27. Site Specific Rules

27.1 Tong Quarry

1. INTRODUCTION

These rules are made under Regulation 14 of the Quarries Regulations 1999, and form part of the operating procedures under Regulation 10. Site-specific rules appertaining to individual quarries (Local variances & additions to these rules) can be found at section 27 parts 1 to 7 of these rules and must be read and complied with for the specific quarry.

A “vehicle” is any mechanically propelled vehicle (including mechanically propelled plant).

2. REGULATIONS

These rules provide compliance with the Quarries Regulations and also the following main pieces of legislation:

- **Health & Safety at Work Act 1974 (HASAWA 1974)**
- **Provision & Use Work Equipment regulations 1998 (PUWER 98)**
- **Lifting Operations & Lifting Equipment Regulations (LOLER)**
- **Reporting of Injuries, Diseases & dangerous Occurrences Regulations 1995 (RIDDOR)**
- **Management of Health & Safety at Work 1992 (MHSW)**
- **Workplace health, Safety & Welfare Regulations 1992 (WHSW)**

The list is not exhaustive.

Under PUWER, the employer (Read site manager) has a duty to select workplace vehicles that are suitable for the intended work. I.e. employers must ensure that all vehicles, including hired or leased vehicles, are selected and used in accordance with the manufacturers specification and instructions and with due regard to specific site conditions.

Do not assume that suppliers will automatically provide a vehicle or plant that is SAFE to use.

3. RISK ASSESSMENT

It is critical that the right vehicles are chosen for the intended work.

Consideration should be given to many factors including:

- Adequate all-round visibility for the driver. This includes the provision of additional mirrors, Radar, cameras etc. and should include an assessment of the “Blind Spots” (If any) on all vehicles which should be documented.
- ROPS & FOPS for driver protection (Any repairs should be completed by the manufacturer or a suitably qualified fitter).
- Safe access and egress from the driver’s cab and other areas for servicing, maintenance, etc.
- Air conditioning.
- Adequate & suitable lighting.
- Effective braking systems.
- Suitable seat belts (lap, diagonal or full harness).
- Area where the vehicle will be working & type of work to be undertaken.

Site-specific rules will cover such items as the danger to pedestrians and to inherent dangers presented by the location. Work instructions for each specific site will include machine type and the procedures to be followed.

4. TRAFFIC ROUTES

Traffic routes are designed to take account of such requirements as the need to:

- Minimise reversing
- Segregate vehicles and pedestrians
- Segregate light vehicles and “quarry” vehicles
- Conform to the quarry regulations in regard to slope gradients (1 in 10 road vehicles, 1 in 8 for quarry vehicles).
- Avoid overhead obstructions where possible.
- Implement and make use of one-way systems.

5. DRIVER REQUIREMENTS

No person shall drive any vehicle at the quarry unless they are:

- Over 17 years of age for vehicles under 3.5tonnes unladen weight.
- Over 18 years of age for vehicles under 7.5tonnes unladen weight.
- Over 21years of age for vehicles over 7.5tonnes unladen weight.
- Over 21 years of age for heavy vehicles including mobile cranes crossing or travelling on a public highway
- Properly trained and appointed in writing by the quarry manager to drive that vehicle.

6. TRAINING, ASSESSMENT AND APPOINTMENT

No person will be trained on any vehicle unless they are under the continuous supervision of a qualified training instructor.

The person being trained will be appointed by the manager as a person under instruction and will have received and signed for a copy of these rules and company rules.

The rules shall be explained fully to the driver before they are signed for.

Before being appointed as competent, drivers will be assessed by a qualified assessor and will, on successful completion, be issued with the relevant certificate (a copy of which will be retained on site).

Assessments other than EPIC or CITB must be approved by the Health & Safety department.

EPIC assessments must be renewed every 5 years.

All operators are expected to achieve NVQ Level 2 in Specialised Plant and Machinery Operations.

On successfully completing the assessment, drivers will be appointed as fully competent for the relevant vehicle, the appointment is valid for this quarry only; separate appointments will be made for other quarries where a driver may be expected to work.

All drivers must be medically fit to operate any vehicle and should inform management if there is a medical reason why they should not (Prescribed Medication, Hay-fever remedies etc).

The Manager reserves the right to withdraw authorisation to drive or operate any site or road licensed vehicle or machine at any time.

7. CONTRACTORS

Contractor's drivers, before operating ANY item of plant or vehicles on site will be appointed by the manager in writing first. The Contractor or driver will provide the site manager with proof of competence to operate the intended machine (A Nationally recognised certificate of competency for the relevant vehicle).

The induction process will cover these (and any other relevant) rules and be signed for by all drivers new on site.

ALL Contractors vehicles will be of the same minimum standard of equipment as site vehicles and subject to the same maintenance, servicing and brake-testing regime. Fox Group's plant checklist will be completed for all machines brought on site.

All contractors engaged by Fox Group will be subject to the same Fox Group Employee General Conduct Rules as regular employees and must sign and comply with the rules.

8. SAFETY SPECIFICATIONS

8.1 Lighting

No vehicle shall be used during the hours of darkness or during periods of poor visibility unless it is equipped with sufficient, suitable, working lighting to enable it to be used safely (this includes flashing beacons and brake lights, as well as work lights).

8.2 Visual Aids

All vehicles and plant that have "Blind Spots" to the rear shall be fitted with a rear vision CCTV camera system. Only those vehicles classed as having "All round visibility" will be exempt (Agricultural tractors with full vision cabs, MEWP, Mini Diggers etc).

ALL large vehicles, which have restricted vision to the front or sides, shall be provided with additional mirrors (Convex, ¼ mirrors wide angle etc).

Any vehicle fitted with the above alarms, cameras or mirrors shall not be used if they become defective. All drivers of machines fitted with such equipment must ensure such systems are fully functional and have received training for the reverse systems in accordance with site rules.

8.3 Flashing Beacons

All small vehicles (Below Transit size) must display an operating flashing beacon and headlights.

8.4 Safety Warning Devices

No vehicle shall be used unless it is provided with a working horn capable of giving adequate audible warning of its approach or position (Above the level of surrounding sounds)

All vehicles must be provided with a working reverse warning device that operates automatically when reverse gear is selected.

All tipping vehicles must be provided with an audible and visual "Body Up" warning device. If any of the above equipment is not functioning, the machine should be parked up and the fitters or management informed.

8.5 Seat Belts/Seating

All vehicles are provided with driver seat belts that should be worn at all times whilst operating. Passenger seats are also fitted with seat belts that should be worn by the passenger at all times unless under a Permit to Work situation where the driver is undergoing training or assessment. External flashing green lights are fitted to new machines to indicate the belt is being worn.

Seat belts **MUST NOT** be plugged in when not being worn.

The bypassing of a visible indication of seat belt engagement is considered intentional non-compliance of the Employees' General Conduct Rules and also Section 8 of the Health and Safety at Work Act 1974 (No person shall intentionally or recklessly interfere with or misuse anything provided in the interests of health, safety or welfare in pursuance of any of the relevant statutory provisions).

8.6 Fire Extinguishers

All vehicles are fitted with the correct extinguisher, maintained on a regular basis or with automatic systems.

8.7 Small Vehicles

Where company vans, Land Rovers etc. are expected to enter the “quarry area” (The area demarcated by the site manager); they shall be fitted with flashing beacons.

Any non-company vehicles without flashing beacons will be escorted by a site vehicle. Visitors will be escorted at all times inside the demarcated area.

8.8 Air Conditioning

Where air conditioning systems are fitted, doors and windows should be closed at all times ensuring that systems are fully effective and minimising exposure to noise and dust.

Competent persons to ensure that they function correctly will check systems regularly (At least once a year by qualified engineers).

Cab filters should be cleaned and checked by the operator on a regular basis (Weekly, or more frequently in dusty conditions).

9. ROUTINE DAILY CHECKS

Prior to the start of a shift, checks should be carried out and the relevant check sheet completed. All defects that may affect the safe operation of the vehicle must be reported immediately to the fitters or management. Defects regarding brakes, steering, warning devices or visibility aids will necessitate the machine being parked up until the fault is rectified.

Defects affecting the operational efficiency should be reported immediately so that planned repairs can be organised.

Relief operators are responsible for checking the machine prior to operating and should ensure they complete the daily checks and record on the relevant check sheet.

10. BRAKE TESTING

At the start of each shift (or when taking over a machine), ensure that service brakes are functioning correctly before entering the working area (Conduct a simple stopping test). All drivers shall conduct the accepted method of brake testing for the machine being operated, as per their training.

A braking efficiency test will be carried out periodically on all mobile plant vehicles on site.

All brake test records will be retained on site and vehicles must be withdrawn from use immediately should they fail to reach the required standard.

11. MAINTENANCE & SERVICING

Maintenance shall be carried out in accordance with the manufacturer’s recommendations (As a minimum standard); more frequent maintenance should be completed as conditions dictate (Dusty/Dry conditions etc). Automatic lubrication systems shall be checked on a regular basis to ensure that they are operating.

Competent personnel, in accordance with the manufacturer’s recommendations, will carry out servicing in dedicated areas.

When refuelling, the engine must be stopped, and the keys removed from the vehicle. The driver/operator must be in attendance whilst fuel is being pumped. Any spillages must be dealt with in accordance with site environmental procedures.

Maintenance records will be kept for each vehicle and retained for its life, being sent with that vehicle if it is transferred or sold.

In a “Break down” situation, a competent person will risk assess the situation for power lines and other hazards before repair or recovery begins.

No vehicle body will be in a raised position without the correct “Prop” in place if personnel are to complete work in the area below the skip. Hydraulic Jacks are not adequate props.

Check sheets will be handed in to the manager on a weekly basis.

12. VEHICLE RECOVERY

Vehicle recovery shall only be carried out under the control of a competent, authorised person. Only labelled towing chains/bars will be used and the number of persons at the recovery site must be kept to the absolute minimum.

Personnel will keep out of the radius of the chain during recovery operations except to connect/disconnect the vehicles.

UNDER NO CIRCUMSTANCE WILL LIFTING CHAINS BE USED FOR TOWING.

A competent authorised person will inspect the vehicle after recovery to ensure its continued safe use/condition (Fitter, Site Supervisor)

13. REVERSING

It is the duty of every operator to ensure that it is safe to reverse and use any warning or reversing aids.

Reversing manoeuvres should be kept to a minimum and the driver request assistance if visibility is restricted in any way.

Before reversing, drivers should ensure that all reverse warning systems are operational. If any system has failed, the vehicle should be parked up and the problem reported.

Banksman should be visible to the driver/operator at all times, and provide clear signals, as per approved training provided.

14. PARKING

Vehicles & Plant must be parked in the designated areas, preferably without having to reverse. If unavoidable, then the reversing manoeuvres should be completed first, so that the first direction on moving off is forwards.

When parked, the engine must be switched off, parking brake applied, keys removed and the vehicle isolated.

No vehicle may be parked or stopped immediately behind or in the vicinity of any other working or stationary vehicle other than for loading.

Road going or light vehicles may only be left adjacent to quarry vehicles for the purpose of maintenance or repair.

All equipment should be lowered to the ground unless supported safely by other means.

In some situations, the vehicle wheels may also have to be chocked.

Keys should be secured in accordance with site requirements.

A "Fire Break" of at least 2m must be maintained between each parked up vehicle and any building.

No vehicle must be parked up unattended with the engine running.

Vehicles should not park adjacent to flammable materials such as: bag stores, pallets, compressed gas bottles etc.

15. JUMP STARTING

"Jump Starting" will only be carried out by competent, authorised persons, issued with and wearing the correct PPE.

16. TRAFFIC SIGNS

Drivers must comply with all information and warning signs at all times, and also be directed as necessary by competent site personnel.

The speed limit is 5MPH on the haul road and within the quarry. This is a maximum speed and vehicles should be driven with due regard to site and weather conditions.

During periods of inclement weather and poor visibility, the site management may impose further restrictions on vehicles in the interest of safety.

17. PEDESTRIANS

Barriers are used to segregate pedestrians and vehicles. While visitors are on site, they shall be escorted at all times by a site representative, unless otherwise authorised by the manager.

Pedestrians shall not enter the operating area of any vehicle or machine until eye contact has been made with the operator and directed to do so by the operator/driver.

Visitors are classed as: Persons not employed by Fox Group or those Fox Group personnel who are not conversant with site or quarry operations (Hazards and Risks associated with site vehicles/plant) at Tong Quarry.

18. TOWING TRAILERS/BOWSERS

Drivers/operators must inspect the tow hitch to ensure it is in a safe condition and also carry out a brake test of the towing unit and trailer/bowser combined.

Where brakes are not fitted to the towed item, its loaded weight should not exceed 90% of the towing vehicle weight.

Towing of other vehicles will be classed as "Recovery" and should be controlled by a competent person.

Where trailers etc. are fitted with brakes, these should be coupled to the towing unit as required (Hydraulic, Air etc).

Only four-wheel drive vehicles shall be used on site by employees/contractors on company business.

19. OVERHEAD OBSTRUCTIONS/POWER LINES

All overhead obstructions shall be indicated to operators/drivers visually, during induction. Warning signs and/or goal posts will be provided on both sides of power lines to indicate their position.

All obstructions in the loading/working area for daily operations are positioned above the height of the largest item of plant on site (Above 4.0m) and also indicated by signs/markings etc.

Stock piles will not be constructed within 27m of overhead power lines, shovels and excavators will not work within 23m of overhead power lines unless a Risk Assessment and Safe System of Work has been agreed.

The MEWP shall not operate where it is able to approach within 9m of high voltage power lines, except to travel or whilst repairing power cables under a Permit to Work (Risk Assessment & Safe System of Work in place).

20. UNDERGROUND SERVICES

No excavating or drilling will take place outside the normal quarrying operations area unless full investigations have been carried out for the presence of cables and services, and a Permit to Work authorised.

A plan of underground services is held on site in the Manager's office.

21. EDGE PROTECTION

All benches and roads used by heavy vehicles/plant shall have edge protection in place where there is risk of a vehicle leaving the road and harm/damage being caused to the operator or machine.

The MINIMUM standard of edge protection is: A bank of unconsolidated material to the down slope side of the bench or road 1.5m high (or at least half the diameter of the largest wheel whichever is greater).

Additional protection shall be provided at sharp bends and steep gradients.

Access to the crests shall be controlled by barriers; vehicle access being restricted to drill rigs or other machines as authorised by management (As operational constraints dictate).

Barriers will be clearly marked with: "Restricted Area, No Entry, Authorised Personnel Only".

Signs alerting personnel to danger will be posted around the site and on fences.

22. TIPPING OPERATIONS

When tipping on tips and stockpiles, dumpers must not reverse closer than 5m to any edge unless a stop block is in place, when the distance may be reduced to 3m.

Where a Bulldozer or Shovel is pushing the material over the edge, it is the drivers/operators duty to ensure that edge and side protection is maintained to the same standard as afforded on roads and benches.

Loaders and bulldozers must work at right angles to the tip edge wherever possible.

No loading out will take place from the bottom of any stockpile unless the driver has checked and ensured the top area is secure.

During loading operations of non-free flowing materials, the driver should work across the face of the stockpile to reduce the possibility of overhangs.

Detailed Tipping Rules for the site are given in the Excavations and Tips Rules and take into account Risks and Hazards assessed at Tong Quarry.

23. UNSAFE DRIVING/SUBSTANCE ABUSE

Any person who appears unfit through drink, drugs or other reason shall not be permitted to drive a vehicle at Tong Quarry (A guide is any person unfit to drive on a public road will be considered unfit to drive a vehicle on site).

ANY person driving a vehicle without due care and attention and having regard to all circumstances including the nature, condition and use of the road or other place where the vehicle is being driven, and visibility at the time, shall be subject to disciplinary action.

Mobile phones are not allowed in the quarry area, and communication radios should only be operated whilst the vehicle is stationary.

24. ACCESS AND EGRESS

Faults with vehicle access steps or guard/hand rails should be reported immediately.

Drivers should always face the machine whilst climbing into or out and also maintain three points of contact.

Never attempt to climb vertical access steps whilst carrying something in one hand.

Jumping from steps or climbing across/between machines is prohibited.

25. GENERAL RULES OF THE ROAD

No person shall drive a company vehicle on the highway unless the vehicle is authorised for that purpose and the driver holds a current, appropriate licence.

The Highway Code should be observed on all public roads and access roads.

Unloaded vehicles must always give way to loaded vehicles as necessary.

26. SPECIFIC VEHICLES

26.1 Rigid/Articulated Dumpers and Lorries

Rigid/Articulated dumpers and lorries must have one or more independent working devices, whether as part of the equipment of the vehicle, trailer or otherwise, that shall be used to prevent a tipping body from collapsing from the raised position (BODY PROP).

UNDER NO CIRCUMSTANCES SHOULD THE VEHICLE'S HYDRAULIC SYSTEM BE RELIED UPON TO SUPPORT THE RAISED TIPPING BODY.

Drivers shall not reverse or come closer than 3m to a tip or open face edge with stop blocks in place/ banksman in attendance, or 5m at all other times.

Permanent stop blocks are located at crusher tipping stations and should be maintained free of built-up spillage (Causes ramping affect into tipping hopper).

Vehicles shall not travel with the tipping body raised except for the short distance required to clear the body of material during tipping operations.

During loading operations, drivers must be aware and prepared for any unexpected movement of the vehicle body caused by the loading process.

Drivers must be alert and heed any warning or other signal given by the loader operator.

When the driver is required to be dismounted from the cab during loading (Rock Armour), he/she must be well clear of the operating zone, material that may fall off or face collapse/rock fall. In such cases the driver shall wear the appropriate PPE (Head protection, hi-visibility clothing, safety boots and eye/ear protection as required).

All external mirrors must be in a serviceable condition.

Drivers should not reverse unless it is safe to do so.

Loader drivers will ensure that the vehicle is loaded so that it is stable and secure to travel.

Ultimately, the driver is held responsible at all times for the stability and security of the load (Excavator/Loader drivers should notify the dumper driver if they are aware of possible problems with the load during face operations).

Faults with access steps should be reported immediately.

26.2 Excavators & Wheeled Loaders

Drivers will inspect the access to intended work areas and notify management if there are problems; dependant on the type and severity of the reported problem, may necessitate immediate remedial action.

If whilst working in the area, a hazard becomes apparent, the driver should ensure that he works at a safe distance from the hazard and reports it as soon as possible to management. Whilst travelling, the bucket of a machine should be within 0.5m of the ground surface at all times (Unless loading is taking place).

Approaching obstructions or overhead cables, the driver must observe warning signs and ensure that there is sufficient safe clearance for the machine to pass.

Before excavating in any area, a thorough investigation should be completed to ensure no services or power cables are below the surface. On excavating new areas (not in the normal quarrying area) a Permit to Work should be obtained first. Only competent personnel are to undertake the investigation and any procedures issued will be complied with.

Drivers should note the location of any pressurised pipelines and avoid/take the necessary precautions to prevent damage to them.

Drivers should not take machines into known areas of soft ground without instruction from management. If in doubt, ASK.

The operating surfaces should be maintained level and even.

Never attempt to lift material/rocks that appear to be outside the machine's capability.

Whilst stockpiling, using a wheeled loader, never attempt to turn whilst on a ramp.

When loading from the bottom of a stockpile, tipping must not take place directly above the loading machine.

Never use the bucket of a machine to carry or lift persons.

When operating Mini Diggers or Skid steer loaders, they shall be fitted with ROPS/FOPS protection and Risk Assessments should be made prior to working in confined areas.

26.3 Mobile Work Platforms

Work platforms are known by many popular names (Access Platforms, Cherry Pickers etc); they are used as temporary work platforms giving access to areas above and below ground level.

Only competent and authorised personnel shall operate the MEWP on site (Having successfully completed a recognised course of training).

Only machines with current certificates regarding capacity and state of machine (LOLER thorough inspection) may be used.

A Risk Assessment of the task and working area must be conducted before operations begin.

The area should be sealed off to pedestrians and other vehicles not involved in the task.

Warning signs should be posted.

26.4 Ancillary Vehicles

Whilst driving vehicles around site:

- Always wear the seat belt provided
- Obey all signs, speed limits and Managers rules
- Only carry passengers if suitable seats are fitted
- Always give way to Heavy Plant
- Keep a safe distance from beneath quarry faces
- Ensure loads are safe and secure
- Park on level ground without causing obstruction, facing the way that you will be moving away in.
- Only tow if the vehicle is fitted with a tow hitch and adhere to the Managers rules.
- During periods of poor visibility, darkness and inclement weather, display dipped headlights.
- Do not carry tools in foot wells or on seats
- If necessary, clean off footwear before driving
- Never drive with oil or grease on your hands
- When reversing into dark areas, physically check that the area is clear
- Ensure that the flashing beacon is operational
- Avoid puddles, they may hide sharp stones

27. SITE SPECIFIC RULES

DAILY VEHICLE INSPECTION

All drivers of mobile plant must undertake a daily vehicle/plant inspection and complete of the daily check sheet.

This inspection will include:

- Tyres – condition
 - Oil and coolant levels
 - Mirrors
 - Windscreen
 - Brake test
 - Operation of lights
 - Safety devices, such as cameras
 - Greasing
1. Any defects will be noted on the book for attention by site management. If defects require immediate attention, e.g. inoperable brakes, camera, the vehicle must be taken out of operation until repairs are made.

WORK ON TOP OF THE QUARRY FACE

No vehicle will work within 5m of quarry faces (bundled or not) unless instructed to do so. On the working face a bundled exclusion zone will be constructed to allow only agreed vehicles such as drillrigs or vehicles delivering stemming to operate under a manager's safework procedure.

Exclusion bunds will allow air compressors, shotfirer vehicles, fuel bowzers etc. to work fuel up, and drop off material from a safe area adjacent to the exclusion bund.

If vehicles have to enter the exclusion zone such as shotfirer vehicles drivers must always travel parallel to the drop below and not face on. When vehicles such as shovels construct exclusion bunds they must be supervised at all times.

WORK BENEATH THE QUARRY FACE

Where faces are stable and at a safe height (max. 15 metres) face shovels and excavators adequately protected with FOP cab (falling object protection) with ROP Cab (roll over protection) and laminated/meshed

windscreen can work the “blast pile”. The excavator driver will always work face onto the area to be worked and keep a careful watch out for rockfalls or unstable faces, reversing out of danger if the need arises.

EXPLOSIVE VEHICLES

Vehicles carrying explosives will have red flashing strobe fitted and display relevant warning signs. A fire extinguisher and first aid box must be carried.

LUBRICATION

All vehicles must be greased and lubricated daily or at least to manufacturer recommendations. Raised bodies and buckets must always be chocked before greasing.

ACCESS/EGRESS

All shovels and dumpers will have ladders, hand railing and work platforms provided to and each workplace. They will be inspected daily by the driver and are to be used at all times. The operator must always face the vehicle at all times.

Always have one hand and two feet or two hands and one foot in contact with the vehicle at any one time. Always use the hand grabs and foot holes provided. Only use authorised methods of access to the vehicle and take into account the weather conditions.

TYRE INFLATION

Topping up of air pressure on a day-to-day basis is permitted if the operator has received the correct training. Total or partial inflation must be undertaken by competent tyre fitters using a cage or standing to the side in the event of a blow out.

Never hot work on tyre rims, they will explode.

VEHICLE PARKING

Vehicles must be parked in their designated parking areas. If this is not possible then the vehicle parking area must be level. Vehicles should not park adjacent to flammable materials such as bag stores; pallets compressed gas bottles etc.

A “fire break” of at least 2 metres must be maintained between each parked up vehicle and any building. Vehicle keys must be removed and engine immobilised (if applicable). The vehicle hand brake must be applied. No vehicle must be parked up unattended with engine running.

If due to breakdown the vehicle is on an incline, then all wheels must be chocked.

The person in charge of the vehicle must keep the key and must ensure all persons are clear before re - starting the vehicle. No person shall attempt to start the vehicle if he has not located the key, unless he has consulted the Management.

EDGE PROTECTION

All haul roads must be bunded by contoured scalping walls at least 1.5 metres high, boulders are unacceptable. All bunkers, dump hoppers etc. must have end stops fitted. If this is deteriorating anywhere, inform the Manager immediately, or repair it!

OVERHEAD CABLES

All overhead cables must have height warning boards posted.

No vehicle must pass under overhead cables unless there is sufficient height clearance.

WORK AROUND WATER

All lagoons and silt ponds must be adequately bunded by 1-metre-high walls. Roads passing over or close by must be sufficiently wide (and bunded) to prevent collapse of the sides.

Where long reach excavators are used they must be positioned with tracks running at right angles to the face being worked. Before starting work at any waters edge the operative must assess the face to ensure stability.

WORK AROUND STOCKPILES

When loading from the large dust stockpiles overhangs and sudden collapse can be dangerous and catch the shovel driver unaware. The driver must always work face onto any stockpile face so as to be able to reverse out in an emergency. Access roads up to the top of stockpiles must not be at a steep angle and be adequately bunded by a 1.5m bank. If the stockpile is to be loaded, a bund must be placed at the front of the stockpile to prevent access.

When tipping material onto the stockpiles it must be tipped 5 metres from the face and pushed over leaving a one-metre bund in front of it. No vehicles must tip over stockpile/face edges. Tipping is only to take place in areas specified by the Manager. All vehicle bodies must be lowered before moving off.

WORK AROUND FACES

Ensure there is always a rocktrap in the area where you are working, if not make one and report the fact.

MAINTENANCE AND DEFECTS

The authorised driver of a quarry vehicle shall be responsible for:

- Checking and maintaining all fluid levels daily
- Checking and maintaining correct tyre pressure where fitted
- Maintaining cleanliness of windscreen, mirrors and reversing camera lens where fitted
- Checking the vehicle's brakes, emergency stopping devices (if fitted), horn and steering at the start of each shift and reporting any defect immediately to his superior
- Checking the proper function of audible reverse warning lights and flashing beacons
- Greasing the vehicles grease points as requested

All defects must be reported immediately to the statutory manager or appropriate foreman and entered on the vehicles daily check record sheet. Record sheets must be handed to the Manager weekly.

LOADING SHOVELS

The driver must first ensure that there is adequate working space in which to manoeuvre the shovel between the stockpile and the transport vehicle. The shovel must not be left unattended with the bucket in an elevated position.

Reversing is always a hazardous manoeuvre, keep it to a minimum and always be sure the rear is clear.

When parked for any reason, the vehicle must be securely braked and positioned so that it cannot move or be set in motion, and the bucket lowered to the ground.

A shovel working on the tip must take extra care when moving materials over the edge and to maintain 1-metre-high banks, 3 metres from the tip edge.

All roads must be kept well maintained at all times and spillage removed.

When tipping at the crusher pay attention to the traffic light system. Wait on the red light, go and help the crusher operator when red and amber shows, and tip only on the green light.

GENERAL

In the event of any machine becoming stuck, it must be reported immediately to the deputy manager or statutory manager. Only the towchain is to be used. All personnel must be out of radius of the chain when towing commences.

Body props or safety pins must be used whenever a person has to work under or around a tipping vehicle with a raised body or a shovel with a raised bucket. No person shall work under a vehicle unless suitable chocks are in position and checked.

All vehicles must operate on the left-hand side of the road.

All drivers must take extra care when approaching pedestrians.

No person shall attempt to board or alight from a vehicle in motion.

Do not run an engine in a non-ventilated area.

Safety glasses must be worn when working with batteries.

Vehicle lights must be used during the hours of darkness, or when visibility conditions are poor.

If spectacles are required to correct vision for driving, they must be worn.

Adequate edge protection of 1.5 metre high must be maintained along all elevated haul roads.

No person shall ride on or in any quarry vehicle unless a passenger seat is fitted in the cab of the vehicle, other than for training purposes (undertaken by a qualified instructor).

No quarry vehicle is to be parked on sloping ground.

All traffic signs are to be observed.

Reversing is always a hazardous manoeuvre, keep it to a minimum and always be sure the rear is clear before setting off.

Be extremely vigilant at all times for small vehicles entering, loading and leaving your area.

No person is to ride in the bucket of a front-end loader, or outside any machine, or in the body of a dumper.

No operator is to drive a front-end loader without clear vision, i.e. bucket fully raised or lowered.

Speed signs are to be observed at all times. Maximum speed in the quarry area is 15 mph but this must be reduced if conditions deteriorate. All other signs such as " Give Way " etc. are to be observed.

All vehicles are to be loaded so as to avoid danger from spillage.

Suitable gears are to be selected before an incline to avoid hill changing.

At no time will face material be dug in the area between and below the area marked, whilst danger flags are displayed.

Material will be carried in a shovel bucket lowered and tipped back.

ADVERSE WEATHER CONDITIONS/SITE CONDITIONS

Management will ensure the roads are graded, gritted and kept safe to ensure safe movement of vehicles. During fog, driving sleet, rain or poor visibility a judgement will be made by management and drivers on the continuation of driving operations.

In foggy, snowy or icy conditions driving speeds should be reduced, and if there is a high risk of danger the machine must be parked up. In fog you need at least 20m visibility and you must contact the Manager or Foreman if visibility is impaired. If there is a sudden decrease in visibility, stop the machine immediately, and sound your horn if a rescue is necessary. Do not wander around the faces in extreme foggy conditions on your own.

NEW STARTERS

Management must properly supervise new drivers or change of vehicle drivers.

SAFE VEHICLES

Drivers must maintain the vehicle on a daily basis and immediately report any defected to management for rectification.

COSHH

Lubricants, anti-freeze, aerosols etc. can present hazards to staff during daily maintenance. They can be an irritant or cause dermatitis if instructions on the containers are not followed or if protective equipment is not worn. The site COSHH file will contain hazard information sheets, which you should read.

RADIATOR TOPPING UP

On a daily basis ensure that "brush" does not build up around the radiator to restrict cooling. If brush builds up hose down thoroughly to remove.

When topping up warm engines allow them to cool before attempting to remove the filler cap; otherwise the sudden release of pressure may scald.

Always check levels when the engine is cold.



Barry Thompson / Roy Underwood
QUARRY MANAGER

Compliance

**I confirm that I have read and understood the Managers Vehicle Rules
for Fox Group Quarries and that I will adhere to those said rules.**

Signed **Print**

Dated