Gift App API Record

Total endpoints: 251

Endpoint Index

- `POST` `/api/v1/auth/users/register` — PUBLIC — —
- `POST` `/api/v1/auth/providers/register` — PUBLIC — —
- `POST` `/api/v1/auth/guest/session` — PUBLIC — —
- `POST` `/api/v1/auth/login` — PUBLIC — —
- `POST` `/api/v1/auth/refresh` — PUBLIC — —
- `POST` `/api/v1/auth/logout` — Authenticated — —
- `POST` `/api/v1/auth/verify-email` — Authenticated — —
- `POST` `/api/v1/auth/resend-otp` — Authenticated — —
- `POST` `/api/v1/auth/forgot-password` — PUBLIC — —
- `POST` `/api/v1/auth/verify-reset-otp` — PUBLIC — —
- `POST` `/api/v1/auth/reset-password` — PUBLIC — —
- `PATCH` `/api/v1/auth/change-password` — Authenticated — —
- `GET` `/api/v1/auth/me` — Authenticated — —
- `DELETE` `/api/v1/auth/account` — Authenticated — —
- `POST` `/api/v1/auth/cancel-deletion` — Authenticated — —
- `GET` `/api/v1/login-attempts/stats` — Authenticated — —
- `GET` `/api/v1/login-attempts/export` — Authenticated — —
- `GET` `/api/v1/login-attempts` — Authenticated — —
- `GET` `/api/v1/customer/referrals/summary` — REGISTERED_USER — Fetch own referral reward summary
- `GET` `/api/v1/customer/referrals/link` — Authenticated — Fetch own referral link
- `GET` `/api/v1/customer/referrals/history` — REGISTERED_USER — List own referral history
- `POST` `/api/v1/customer/referrals/redeem` — Authenticated — Redeem own available reward credit
- `GET` `/api/v1/customer/rewards/balance` — Authenticated — Fetch own reward balance
- `GET` `/api/v1/customer/rewards/ledger` — REGISTERED_USER — List own reward ledger
- `GET` `/api/v1/customer/referrals/terms` — Authenticated — Fetch referral terms
- `GET` `/api/v1/customer/wallet` — REGISTERED_USER — Fetch own wallet
- `POST` `/api/v1/customer/wallet/add-funds` — Authenticated — Create wallet top-up payment
- `GET` `/api/v1/customer/wallet/history` — Authenticated — List own wallet history
- `POST` `/api/v1/customer/bank-accounts` — Authenticated — Link placeholder bank account
- `GET` `/api/v1/customer/bank-accounts` — Authenticated — List own bank accounts
- `PATCH` `/api/v1/customer/bank-accounts/{id}/default` — Authenticated — Set own default bank account
- `DELETE` `/api/v1/customer/bank-accounts/{id}` — Authenticated — Delete own bank account
- `GET` `/api/v1/referral-settings` — SUPER_ADMIN, ADMIN — Fetch referral settings
- `PATCH` `/api/v1/referral-settings` — SUPER_ADMIN, ADMIN — Update referral settings
- `POST` `/api/v1/referral-settings/activate` — SUPER_ADMIN, ADMIN — Activate referral program
- `POST` `/api/v1/referral-settings/deactivate` — SUPER_ADMIN, ADMIN — Deactivate referral program
- `GET` `/api/v1/referral-settings/stats` — SUPER_ADMIN, ADMIN — Fetch referral stats
- `GET` `/api/v1/referral-settings/audit-logs` — SUPER_ADMIN, ADMIN — List referral settings audit logs
- `POST` `/api/v1/admins` — SUPER_ADMIN, ADMIN — Create admin staff user
- `GET` `/api/v1/admins` — SUPER_ADMIN, ADMIN — List admin staff users
- `GET` `/api/v1/admins/{id}` — Authenticated — —
- `PATCH` `/api/v1/admins/{id}` — Authenticated — —
- `PATCH` `/api/v1/admins/{id}/active-status` — Authenticated — —
- `PATCH` `/api/v1/admins/{id}/password` — Authenticated — —
- `GET` `/api/v1/admin-roles` — SUPER_ADMIN, ADMIN — —
- `POST` `/api/v1/admin-roles` — Authenticated — —
- `GET` `/api/v1/admin-roles/{id}` — Authenticated — —
- `PATCH` `/api/v1/admin-roles/{id}` — Authenticated — —
- `DELETE` `/api/v1/admin-roles/{id}` — Authenticated — —
- `PATCH` `/api/v1/admin-roles/{id}/permissions` — Authenticated — —
- `GET` `/api/v1/permissions/catalog` — Authenticated — —
- `GET` `/api/v1/providers/export` — Authenticated — —
- `GET` `/api/v1/providers/stats` — Authenticated — —
- `GET` `/api/v1/providers` — SUPER_ADMIN, ADMIN — List providers
- `POST` `/api/v1/providers` — Authenticated — —
- `GET` `/api/v1/providers/lookup` — Authenticated — —
- `GET` `/api/v1/providers/{id}` — Authenticated — —
- `PATCH` `/api/v1/providers/{id}` — Authenticated — —
- `PATCH` `/api/v1/providers/{id}/status` — SUPER_ADMIN, ADMIN — Update provider lifecycle status
- `GET` `/api/v1/providers/{id}/items` — Authenticated — —
- `GET` `/api/v1/providers/{id}/activity` — Authenticated — —
- `POST` `/api/v1/providers/{id}/message` — Authenticated — —
- `GET` `/api/v1/provider-business-categories` — PUBLIC — List active provider business categories

- `POST` `/api/v1/provider-business-categories` — SUPER_ADMIN, ADMIN — Create provider business category
- `GET` `/api/v1/provider-business-categories/{id}` — SUPER_ADMIN, ADMIN — Fetch provider business category details
- `PATCH` `/api/v1/provider-business-categories/{id}` — SUPER_ADMIN, ADMIN — Update provider business category
- `DELETE` `/api/v1/provider-business-categories/{id}` — SUPER_ADMIN, ADMIN — Soft-delete provider business category
- `GET` `/api/v1/provider/inventory` — PROVIDER — List provider inventory items
- `POST` `/api/v1/provider/inventory` — PROVIDER — Create provider inventory item with optional nested variants
- `GET` `/api/v1/provider/inventory/stats` — Authenticated — Fetch provider inventory stats
- `GET` `/api/v1/provider/inventory/lookup` — Authenticated — Lookup active approved provider inventory items
- `GET` `/api/v1/provider/inventory/{id}` — Authenticated — Fetch own provider inventory item details
- `PATCH` `/api/v1/provider/inventory/{id}` — Authenticated — Update own provider inventory item and upsert variants
- `DELETE` `/api/v1/provider/inventory/{id}` — Authenticated — Soft-delete own inventory item
- `PATCH` `/api/v1/provider/inventory/{id}/availability` — Authenticated — Update own inventory availability
- `GET` `/api/v1/provider/orders` — PROVIDER — List own assigned provider orders
- `GET` `/api/v1/provider/orders/history` — PROVIDER — List own provider order history
- `GET` `/api/v1/provider/orders/performance` — PROVIDER — Fetch own provider order performance
- `GET` `/api/v1/provider/orders/analytics/revenue` — PROVIDER — Fetch own provider revenue analytics
- `GET` `/api/v1/provider/orders/analytics/ratings` — PROVIDER — Fetch own provider ratings analytics
- `GET` `/api/v1/provider/orders/recent` — PROVIDER — List recent own provider orders
- `GET` `/api/v1/provider/orders/export` — PROVIDER — Export own provider orders as CSV
- `GET` `/api/v1/provider/orders/summary` — PROVIDER — Fetch own provider order summary
- `GET` `/api/v1/provider/orders/reject-reasons` — Authenticated — List provider order reject reasons
- `PATCH` `/api/v1/provider/orders/{id}/status` — PROVIDER — Update own provider order fulfillment status
- `GET` `/api/v1/provider/orders/{id}/timeline` — PROVIDER — Fetch own provider order timeline
- `GET` `/api/v1/provider/orders/{id}/checklist` — PROVIDER — Fetch own provider order checklist
- `PATCH` `/api/v1/provider/orders/{id}/checklist` — PROVIDER — Update own provider order checklist
- `POST` `/api/v1/provider/orders/{id}/message-buyer` — PROVIDER — Message buyer for own provider order
- `GET` `/api/v1/provider/orders/{id}` — PROVIDER — Fetch own provider order details
- `POST` `/api/v1/provider/orders/{id}/accept` — Authenticated — Accept own pending provider order
- `POST` `/api/v1/provider/orders/{id}/reject` — Authenticated — Reject own pending provider order
- `GET` `/api/v1/provider/offers` — Authenticated — —
- `POST` `/api/v1/provider/offers` — Authenticated — —
- `GET` `/api/v1/provider/offers/{id}` — Authenticated — —
- `PATCH` `/api/v1/provider/offers/{id}` — Authenticated — —
- `DELETE` `/api/v1/provider/offers/{id}` — Authenticated — —
- `PATCH` `/api/v1/provider/offers/{id}/status` — Authenticated — —
- `GET` `/api/v1/promotional-offers/stats` — Authenticated — —
- `GET` `/api/v1/promotional-offers/export` — Authenticated — —
- `GET` `/api/v1/promotional-offers` — Authenticated — —
- `POST` `/api/v1/promotional-offers` — Authenticated — —
- `GET` `/api/v1/promotional-offers/{id}` — Authenticated — —
- `PATCH` `/api/v1/promotional-offers/{id}` — Authenticated — —
- `DELETE` `/api/v1/promotional-offers/{id}` — Authenticated — —
- `PATCH` `/api/v1/promotional-offers/{id}/approve` — Authenticated — —
- `PATCH` `/api/v1/promotional-offers/{id}/reject` — Authenticated — —
- `PATCH` `/api/v1/promotional-offers/{id}/status` — Authenticated — —
- `GET` `/api/v1/users/export` — Authenticated — —
- `GET` `/api/v1/users` — SUPER_ADMIN, ADMIN — List registered users
- `GET` `/api/v1/users/{id}` — Authenticated — —
- `PATCH` `/api/v1/users/{id}` — Authenticated — —
- `PATCH` `/api/v1/users/{id}/status` — Authenticated — —
- `POST` `/api/v1/users/{id}/suspend` — Authenticated — —
- `POST` `/api/v1/users/{id}/unsuspend` — Authenticated — —
- `POST` `/api/v1/users/{id}/reset-password` — SUPER_ADMIN; ADMIN with users.resetPassword — Change registered user password
- `GET` `/api/v1/users/{id}/activity` — Authenticated — —
- `GET` `/api/v1/users/{id}/stats` — Authenticated — —
- `GET` `/api/v1/customer/contacts` — REGISTERED_USER — List customer contacts
- `POST` `/api/v1/customer/contacts` — REGISTERED_USER — Create customer contact
- `GET` `/api/v1/customer/contacts/{id}` — REGISTERED_USER — Fetch customer contact
- `PATCH` `/api/v1/customer/contacts/{id}` — REGISTERED_USER — Update customer contact
- `DELETE` `/api/v1/customer/contacts/{id}` — REGISTERED_USER — Soft-delete customer contact
- `GET` `/api/v1/customer/events` — REGISTERED_USER — List customer events
- `POST` `/api/v1/customer/events` — REGISTERED_USER — Create customer event
- `GET` `/api/v1/customer/events/calendar` — REGISTERED_USER — Fetch monthly calendar events

- `GET` `/api/v1/customer/events/upcoming` — REGISTERED_USER — Fetch upcoming customer events
- `GET` `/api/v1/customer/events/{id}/reminder-settings` — REGISTERED_USER — Fetch event reminder settings
- `PATCH` `/api/v1/customer/events/{id}/reminder-settings` — REGISTERED_USER — Update event reminder settings
- `GET` `/api/v1/customer/events/{id}` — REGISTERED_USER — Fetch customer event details
- `PATCH` `/api/v1/customer/events/{id}` — REGISTERED_USER — Update customer event
- `DELETE` `/api/v1/customer/events/{id}` — REGISTERED_USER — Soft-delete customer event
- `GET` `/api/v1/customer/home` — REGISTERED_USER — Fetch customer app home
- `GET` `/api/v1/customer/categories` — REGISTERED_USER — List customer marketplace categories
- `GET` `/api/v1/customer/gifts/discounted` — REGISTERED_USER — List discounted customer gifts
- `GET` `/api/v1/customer/gifts/filter-options` — REGISTERED_USER — Fetch marketplace gift filter options
- `GET` `/api/v1/customer/gifts` — REGISTERED_USER — List customer marketplace gifts
- `GET` `/api/v1/customer/gifts/{id}` — REGISTERED_USER — Fetch customer-safe gift details
- `GET` `/api/v1/customer/wishlist` — REGISTERED_USER — List wishlist gifts
- `POST` `/api/v1/customer/wishlist/{giftId}` — REGISTERED_USER — Add gift to wishlist
- `DELETE` `/api/v1/customer/wishlist/{giftId}` — REGISTERED_USER — Remove gift from wishlist
- `GET` `/api/v1/customer/addresses` — REGISTERED_USER — List customer addresses
- `POST` `/api/v1/customer/addresses` — REGISTERED_USER — Create customer address
- `GET` `/api/v1/customer/addresses/{id}` — REGISTERED_USER — Fetch customer address
- `PATCH` `/api/v1/customer/addresses/{id}` — REGISTERED_USER — Update customer address
- `DELETE` `/api/v1/customer/addresses/{id}` — REGISTERED_USER — Soft-delete customer address
- `PATCH` `/api/v1/customer/addresses/{id}/default` — REGISTERED_USER — Set default customer address
- `GET` `/api/v1/customer/cart` — REGISTERED_USER — Fetch active cart
- `DELETE` `/api/v1/customer/cart` — REGISTERED_USER — Clear active cart
- `POST` `/api/v1/customer/cart/items` — REGISTERED_USER — Add item to cart
- `PATCH` `/api/v1/customer/cart/items/{id}` — REGISTERED_USER — Update cart item
- `DELETE` `/api/v1/customer/cart/items/{id}` — REGISTERED_USER — Delete cart item
- `POST` `/api/v1/customer/orders` — REGISTERED_USER — Create order from active cart
- `GET` `/api/v1/customer/orders` — REGISTERED_USER — List customer orders
- `GET` `/api/v1/customer/orders/{id}` — REGISTERED_USER — Fetch customer order
- `GET` `/api/v1/customer/recurring-payments` — REGISTERED_USER — List own recurring payments
- `POST` `/api/v1/customer/recurring-payments` — REGISTERED_USER — Create recurring payment
- `GET` `/api/v1/customer/recurring-payments/summary` — Authenticated — Fetch recurring payment summary counts
- `GET` `/api/v1/customer/recurring-payments/{id}` — REGISTERED_USER — Fetch own recurring payment details
- `PATCH` `/api/v1/customer/recurring-payments/{id}` — Authenticated — Update own recurring payment
- `POST` `/api/v1/customer/recurring-payments/{id}/pause` — Authenticated — Pause own active recurring payment
- `POST` `/api/v1/customer/recurring-payments/{id}/resume` — Authenticated — Resume own paused recurring payment
- `POST` `/api/v1/customer/recurring-payments/{id}/cancel` — Authenticated — Cancel own recurring payment
- `GET` `/api/v1/customer/recurring-payments/{id}/history` — Authenticated — List own recurring payment billing history
- `POST` `/api/v1/customer/payment-methods/setup-intent` — Authenticated — Create Stripe SetupIntent for saving card
- `GET` `/api/v1/customer/payment-methods/saved` — Authenticated — List own saved payment methods
- `DELETE` `/api/v1/customer/payment-methods/{id}` — Authenticated — Delete own saved payment method
- `GET` `/api/v1/customer/transactions` — REGISTERED_USER — List own customer transactions
- `GET` `/api/v1/customer/transactions/summary` — Authenticated — Fetch own transaction summary
- `GET` `/api/v1/customer/transactions/export` — Authenticated — Export own transactions
- `GET` `/api/v1/customer/transactions/{id}` — Authenticated — Fetch own transaction details
- `GET` `/api/v1/customer/transactions/{id}/receipt` — Authenticated — Download own transaction receipt
- `GET` `/api/v1/gift-categories/lookup` — PUBLIC — Lookup active gift categories
- `POST` `/api/v1/gift-categories` — Authenticated — Create gift category
- `GET` `/api/v1/gift-categories` — Authenticated — List gift categories
- `GET` `/api/v1/gift-categories/stats` — Authenticated — Fetch gift category stats
- `GET` `/api/v1/gift-categories/{id}` — Authenticated — Fetch gift category details
- `PATCH` `/api/v1/gift-categories/{id}` — Authenticated — Update gift category
- `DELETE` `/api/v1/gift-categories/{id}` — Authenticated — Soft-delete gift category
- `POST` `/api/v1/gifts` — SUPER_ADMIN, ADMIN — Create admin gift with optional nested variants
- `GET` `/api/v1/gifts` — SUPER_ADMIN, ADMIN — List admin gifts
- `GET` `/api/v1/gifts/stats` — Authenticated — Fetch gift inventory stats
- `GET` `/api/v1/gifts/export` — Authenticated — Export gift inventory
- `GET` `/api/v1/gifts/{id}` — Authenticated — Fetch admin gift details with variants
- `PATCH` `/api/v1/gifts/{id}` — Authenticated — Update admin gift and upsert nested variants
- `DELETE` `/api/v1/gifts/{id}` — Authenticated — Soft-delete gift
- `PATCH` `/api/v1/gifts/{id}/status` — Authenticated — Update gift status
- `GET` `/api/v1/gift-moderation` — Authenticated — —
- `PATCH` `/api/v1/gift-moderation/{id}/approve` — Authenticated — —

- `PATCH` `/api/v1/gift-moderation/{id}/reject` — Authenticated — —
- `PATCH` `/api/v1/gift-moderation/{id}/flag` — Authenticated — —
- `POST` `/api/v1/broadcasts` — Authenticated — —
- `GET` `/api/v1/broadcasts` — Authenticated — —
- `GET` `/api/v1/broadcasts/{id}` — Authenticated — —
- `PATCH` `/api/v1/broadcasts/{id}` — Authenticated — —
- `PATCH` `/api/v1/broadcasts/{id}/targeting` — Authenticated — —
- `POST` `/api/v1/broadcasts/estimate-reach` — Authenticated — —
- `PATCH` `/api/v1/broadcasts/{id}/schedule` — Authenticated — —
- `POST` `/api/v1/broadcasts/{id}/cancel` — Authenticated — —
- `GET` `/api/v1/broadcasts/{id}/report` — Authenticated — —
- `GET` `/api/v1/broadcasts/{id}/recipients` — Authenticated — —
- `GET` `/api/v1/notifications` — Authenticated — List notifications
- `GET` `/api/v1/notifications/summary` — Authenticated — Fetch notification summary
- `GET` `/api/v1/notifications/preferences` — Authenticated — Fetch notification preferences
- `PATCH` `/api/v1/notifications/preferences` — Authenticated — Update notification preferences
- `PATCH` `/api/v1/notifications/read-all` — Authenticated — Mark all own notifications as read
- `PATCH` `/api/v1/notifications/{id}/read` — Authenticated — Mark notification as read
- `POST` `/api/v1/notifications/{id}/action` — Authenticated — Process notification action
- `POST` `/api/v1/notifications/device-tokens` — Authenticated — Save device token
- `DELETE` `/api/v1/notifications/device-tokens/{id}` — Authenticated — Disable device token
- `GET` `/api/v1/subscription-plans` — Authenticated — —
- `POST` `/api/v1/subscription-plans` — Authenticated — —
- `GET` `/api/v1/subscription-plans/stats` — Authenticated — —
- `GET` `/api/v1/subscription-plans/{id}` — Authenticated — —
- `PATCH` `/api/v1/subscription-plans/{id}` — Authenticated — —
- `DELETE` `/api/v1/subscription-plans/{id}` — Authenticated — —
- `PATCH` `/api/v1/subscription-plans/{id}/status` — Authenticated — —
- `PATCH` `/api/v1/subscription-plans/{id}/visibility` — Authenticated — —
- `GET` `/api/v1/subscription-plans/{id}/analytics` — Authenticated — —
- `GET` `/api/v1/plan-features/catalog` — Authenticated — —
- `GET` `/api/v1/plan-features` — Authenticated — —
- `POST` `/api/v1/plan-features` — Authenticated — —
- `GET` `/api/v1/plan-features/{id}` — Authenticated — —
- `PATCH` `/api/v1/plan-features/{id}` — Authenticated — —
- `DELETE` `/api/v1/plan-features/{id}` — Authenticated — —
- `GET` `/api/v1/coupons` — Authenticated — —
- `POST` `/api/v1/coupons` — Authenticated — —
- `GET` `/api/v1/coupons/{id}` — Authenticated — —
- `PATCH` `/api/v1/coupons/{id}` — Authenticated — —
- `DELETE` `/api/v1/coupons/{id}` — Authenticated — —
- `PATCH` `/api/v1/coupons/{id}/status` — Authenticated — —
- `GET` `/api/v1/media-upload-policy` — SUPER_ADMIN, ADMIN — Fetch global media upload policy
- `PATCH` `/api/v1/media-upload-policy` — SUPER_ADMIN, ADMIN — Update global media upload policy
- `GET` `/api/v1/media-upload-policy/audit-logs` — SUPER_ADMIN, ADMIN — List media upload policy audit logs
- `POST` `/api/v1/customer/payments/create-intent` — REGISTERED_USER — Create payment intent from active cart
- `POST` `/api/v1/customer/payments/confirm` — REGISTERED_USER — Confirm Stripe payment
- `GET` `/api/v1/customer/payments/{id}` — Authenticated — Fetch own payment details
- `GET` `/api/v1/customer/payment-methods` — Authenticated — List supported customer payment methods
- `PATCH` `/api/v1/customer/payment-methods/{id}/default` — Authenticated — Set own default payment method
- `POST` `/api/v1/payments/stripe/webhook` — PUBLIC — Stripe webhook endpoint
- `POST` `/api/v1/customer/money-gifts` — Authenticated — Send payment as gift
- `GET` `/api/v1/customer/money-gifts` — Authenticated — List own money gifts
- `GET` `/api/v1/customer/money-gifts/{id}` — Authenticated — Fetch own money gift details
- `GET` `/api/v1/audit-logs/export` — Authenticated — —
- `GET` `/api/v1/audit-logs` — Authenticated — —
- `GET` `/api/v1/audit-logs/{id}` — Authenticated — —
- `POST` `/api/v1/uploads/presigned-url` — Authenticated — —
- `POST` `/api/v1/uploads/complete` — Authenticated — —
- `GET` `/api/v1/uploads` — Authenticated — —
- `GET` `/api/v1/uploads/{id}` — Authenticated — —
- `DELETE` `/api/v1/uploads/{id}` — Authenticated — —

Auth

POST /api/v1/auth/users/register

Allowed role/access: PUBLIC

Summary: —

Request payload example:

```
{
  "email": "string",
  "password": "string",
  "firstName": "string",
  "lastName": "string",
  "phone": "string",
  "referralCode": "SARAH-M"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/auth/providers/register

Allowed role/access: PUBLIC

Summary: —

Request payload example:

```
{
  "email": "string",
  "password": "string",
  "firstName": "string",
  "lastName": "string",
  "phone": "string",
  "referralCode": "SARAH-M",
  "businessName": "string",
  "businessCategoryId": "string",
  "taxId": "string",
  "businessAddress": "string",
  "fulfillmentMethods": [],
  "autoAcceptOrders": false
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/auth/guest/session

Allowed role/access: PUBLIC

Summary: —

Request payload example:

```
{
  "capabilities": []
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/auth/login

Allowed role/access: PUBLIC

Summary: —

Request payload example:

```
{
  "email": "string",
```

```
  "password": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/auth/refresh

Allowed role/access: PUBLIC

Summary: —

Request payload example:

```
{
  "refreshToken": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/auth/logout

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/auth/verify-email

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
{
  "otp": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/auth/resend-otp

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/auth/forgot-password

Allowed role/access: PUBLIC

Summary: —

Request payload example:

```
{
  "email": "user@example.com"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/auth/verify-reset-otp

Allowed role/access: PUBLIC

Summary: —

Request payload example:

```
{
  "email": "user@example.com",
  "otp": "334018"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/auth/reset-password

Allowed role/access: PUBLIC

Summary: —

Request payload example:

```
{
  "email": "user@example.com",
  "otp": "334018",
  "newPassword": "NewPassword@123"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/auth/change-password

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
{
  "currentPassword": "string",
  "newPassword": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/auth/me

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

DELETE /api/v1/auth/account

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/auth/cancel-deletion

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Login Attempts

GET /api/v1/login-attempts/stats

Allowed role/access: Authenticated

Summary: —

Parameters:

- `email` (query, optional)
- `status` (query, optional)
- `role` (query, optional)
- `page` (query, optional)
- `limit` (query, optional)
- `userId` (query, optional)
- `from` (query, optional)
- `to` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/login-attempts/export

Allowed role/access: Authenticated

Summary: —

Parameters:

- `email` (query, optional)
- `status` (query, optional)
- `role` (query, optional)
- `page` (query, optional)
- `limit` (query, optional)
- `userId` (query, optional)
- `from` (query, optional)
- `to` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/login-attempts

Allowed role/access: Authenticated

Summary: —

Parameters:

- `email` (query, optional)
- `status` (query, optional)
- `role` (query, optional)
- `page` (query, optional)
- `limit` (query, optional)
- `userId` (query, optional)
- `from` (query, optional)
- `to` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Admin Staff Management

POST /api/v1/admins

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: Create admin staff user

Description: Creates an ADMIN staff user under Super Admin. The roleId field is the AdminRole ID that controls this staff user's permissions. This endpoint cannot create SUPER_ADMIN, REGISTERED_USER, PROVIDER, or GUEST_USER accounts.

Request payload example:

```
{}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/admins

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: List admin staff users

Description: SUPER_ADMIN only. Returns User.role = ADMIN staff accounts only; SUPER_ADMIN accounts are intentionally excluded.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `roleId` (query, optional)
- `role` (query, optional)
- `status` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": [
    {
      "id": "admin_id",
      "firstName": "Operations",
      "lastName": "Staff",
      "fullName": "Operations Staff",
      "email": "staff@example.com",
      "phone": "+15550000002",
      "role": {
        "id": "admin_role_id",
        "name": "Gift Manager",
        "slug": "gift-manager"
      },
      "isActive": true,
      "isVerified": true,
      "createdAt": "2026-05-09T10:00:00.000Z",
      "lastLoginAt": null
    }
  ],
  "meta": {
    "page": 1,
    "limit": 10,
    "total": 1,
    "totalPages": 1
```

```
  },
  "message": "Admins fetched successfully"
}
```

GET /api/v1/admins/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/admins/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "firstName": "string",
  "lastName": "string",
  "phone": "string",
  "avatarUrl": "string",
  "title": "string",
  "roleId": "string",
  "isActive": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/admins/{id}/active-status

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "isActive": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/admins/{id}/password

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "temporaryPassword": "string",
  "generateTemporaryPassword": true,
  "mustChangePassword": true,
  "sendEmail": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Admin Roles / RBAC

GET /api/v1/admin-roles

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: —

Description: Admin Roles / RBAC manages permission roles for ADMIN staff users only. SUPER_ADMIN has full immutable access and does not depend on AdminRole permissions.

Parameters:

- `search` (query, optional)
- `isSystem` (query, optional)
- `isActive` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/admin-roles

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
{
  "name": "string",
  "description": "string",
  "permissions": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/admin-roles/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/admin-roles/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "name": "string",
  "description": "string",
  "isActive": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

DELETE /api/v1/admin-roles/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/admin-roles/{id}/permissions

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "permissions": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/permissions/catalog

Allowed role/access: Authenticated

Summary: —

Description: Read-only list of backend-supported permission keys that can be assigned to admin roles.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

User Management

GET /api/v1/users/export

Allowed role/access: Authenticated

Summary: —

Parameters:

- `search` (query, optional)
- `status` (query, optional)
- `registrationFrom` (query, optional)
- `registrationTo` (query, optional)
- `format` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/users

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: List registered users

Description: SUPER_ADMIN/ADMIN with users.read permission.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `status` (query, optional)
- `registrationFrom` (query, optional)

- `registrationTo` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": [
    {
      "id": "user_id",
      "email": "customer@example.com",
      "firstName": "Sarah",
      "lastName": "Johnson",
      "phone": "+923001234567",
      "role": "REGISTERED_USER",
      "isVerified": true,
      "isActive": true,
      "createdAt": "2026-05-09T10:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Users fetched successfully"
}
```

GET /api/v1/users/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/users/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "firstName": "Alex",
  "lastName": "Johnson",
  "phone": "+15552345678",
  "avatarUrl": "https://<YOUR_PUBLIC_BUCKET_OR_CDN_URL>/user-avatars/avatar.jpg",
  "location": "New York, USA"
}
```

Response example:

```
{
  "success": true,
  "data": {},
```

```
  "message": "Request completed successfully"
}
```

PATCH /api/v1/users/{id}/status

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "status": "string",
  "reason": "string",
  "comment": "Suspicious activity detected on this account.",
  "notifyUser": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/users/{id}/suspend

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "reason": "string",
  "comment": "Suspicious account activity.",
  "notifyUser": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/users/{id}/unsuspend

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "comment": "Account reviewed and restored.",
  "notifyUser": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/users/{id}/reset-password

Allowed role/access: SUPER_ADMIN; ADMIN with users.resetPassword

Summary: Change registered user password

Description: SUPER_ADMIN or ADMIN with users.resetPassword permission can change a REGISTERED_USER password from the dashboard. Optionally sends email and in-app notification to the user.

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "newPassword": "NewUser@123456",
  "sendEmail": true,
  "sendNotification": true,
  "reason": "Password changed by support request."
}
```

Response example:

```
{
  "success": true,
  "data": {
    "userId": "user_id",
    "email": "user@example.com",
    "emailSent": true,
    "notificationSent": true
  },
  "message": "User password changed successfully."
}
```

GET /api/v1/users/{id}/activity

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)
- `page` (query, optional)
- `limit` (query, optional)
- `type` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/users/{id}/stats

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
```

```
  "message": "Request completed successfully"
}
```

Provider Management

GET /api/v1/providers/export

Allowed role/access: Authenticated

Summary: —

Parameters:

- `search` (query, optional)
- `status` (query, optional)
- `approvalStatus` (query, optional)
- `format` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/providers/stats

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/providers

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: List providers

Description: SUPER_ADMIN/ADMIN with providers.read permission.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `status` (query, optional)
- `approvalStatus` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": [
    {
      "id": "provider_id",
```

```
      "businessName": "Premium Gifts Co",
      "email": "provider@example.com",
      "phone": "+923001234567",
      "approvalStatus": "APPROVED",
      "isActive": true,
      "businessCategory": {
        "id": "category_id",
        "name": "Gift Supplier"
      },
      "createdAt": "2026-05-09T10:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Providers fetched successfully"
}
```


POST /api/v1/providers

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
{
  "businessName": "Gifts & Blooms Co. Ltd",
  "email": "contact@giftsandblooms.com",
  "phone": "+15551234567",
  "serviceArea": "New York, USA",
  "headquarters": "New York, USA",
  "documentUrls": [],
  "generateTemporaryPassword": true,
  "mustChangePassword": true,
  "approvalStatus": "string",
  "isActive": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/providers/lookup

Allowed role/access: Authenticated

Summary: —

Parameters:

- `search` (query, optional)
- `approvalStatus` (query, optional)
- `isActive` (query, optional)
- `limit` (query, optional)

Request payload example:

```
None
```

Response example:


```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```


GET /api/v1/providers/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/providers/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "businessName": "Gifts & Blooms Co. Ltd",
  "phone": "+15551234567",
  "serviceArea": "New York, USA",
  "headquarters": "New York, USA",
  "avatarUrl": "https://<YOUR_PUBLIC_BUCKET_OR_CDN_URL>/provider-logos/logo.png",
  "documentUrls": []
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/providers/{id}/status

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: Update provider lifecycle status

Description: SUPER_ADMIN or ADMIN with providers.updateStatus permission can use this unified provider lifecycle endpoint for approving, rejecting, activating, deactivating, suspending, and unsuspending providers. Uses action-based request body.

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "action": "APPROVE",
  "status": "ACTIVE",
  "reason": "INCOMPLETE_DOCUMENTS",
  "comment": "Documents verified successfully.",
  "notifyProvider": true
}
```

Response example:

```
{
  "success": true,
  "data": {
    "id": "provider_id",
    "approvalStatus": "APPROVED",
    "status": "ACTIVE",
    "isActive": true
  },
  "message": "Provider approved successfully."
}
```

GET /api/v1/providers/{id}/items

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)
- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `status` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/providers/{id}/activity

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)
- `page` (query, optional)
- `limit` (query, optional)
- `type` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/providers/{id}/message

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "subject": "Account update",
  "message": "Please update your business documents.",
  "channel": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/provider-business-categories

Allowed role/access: PUBLIC

Summary: List active provider business categories

Description: Public signup dropdown. Returns active, non-deleted provider business categories only.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `isActive` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/provider-business-categories

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: Create provider business category

Description: SUPER_ADMIN or ADMIN with providerBusinessCategories.create permission only.

Request payload example:

```
{
  "name": "string",
  "description": "string",
  "iconKey": "string",
  "sortOrder": 0,
  "isActive": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/provider-business-categories/{id}

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: Fetch provider business category details

Description: SUPER_ADMIN or ADMIN with providerBusinessCategories.read permission only.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/provider-business-categories/{id}

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: Update provider business category

Description: SUPER_ADMIN or ADMIN with providerBusinessCategories.update permission only.

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "name": "string",
  "description": "string",
  "iconKey": "string",
  "sortOrder": 0,
  "isActive": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

DELETE /api/v1/provider-business-categories/{id}

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: Soft-delete provider business category

Description: SUPER_ADMIN or ADMIN with providerBusinessCategories.delete permission only. Refuses deletion when active providers are attached.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Provider Inventory

GET /api/v1/provider/inventory

Allowed role/access: PROVIDER

Summary: List provider inventory items

Description: PROVIDER only. Returns only inventory owned by the authenticated provider.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `status` (query, optional)
- `categoryId` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": [
    {
      "id": "gift_id",
      "name": "Luxury Perfume",
      "price": 99.99,
      "currency": "PKR",
      "stockQuantity": 50,
      "status": "ACTIVE",
      "moderationStatus": "APPROVED",
      "isAvailable": true,
      "category": {
        "id": "category_id",
        "name": "Perfumes"
      },
      "variants": [
        {
          "id": "variant_id",
          "name": "50ml",
          "price": 129.99,
          "stockQuantity": 20,
          "isDefault": true
        }
      ]
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Provider inventory fetched successfully"
}
```

POST /api/v1/provider/inventory

Allowed role/access: PROVIDER

Summary: Create provider inventory item with optional nested variants

Description: PROVIDER only. providerId is derived from JWT; provider cannot approve/publish variants directly.

Request payload example:

```
{
  "name": "string",
  "description": "string",
  "shortDescription": "string",
  "price": 0,
  "currency": "string",
  "stockQuantity": 0,
  "sku": "string",
  "categoryId": "string",
  "imageUrls": [],
  "isAvailable": true,
  "variants": []
}
```

Response example:

```
{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume",
    "price": 99.99,
    "currency": "PKR",
    "stockQuantity": 50,
    "status": "ACTIVE",
    "moderationStatus": "PENDING",
    "variants": [
      {
        "id": "variant_id",
        "name": "50ml",
        "price": 129.99,
        "originalPrice": 159.99,
        "stockQuantity": 20,
        "sku": "PERFUME-50ML",
        "isDefault": true,
        "isActive": true
      }
    ]
  },
  "message": "Inventory item created successfully"
}
```

GET /api/v1/provider/inventory/stats

Allowed role/access: Authenticated

Summary: Fetch provider inventory stats

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/provider/inventory/lookup

Allowed role/access: Authenticated

Summary: Lookup active approved provider inventory items

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/provider/inventory/{id}

Allowed role/access: Authenticated

Summary: Fetch own provider inventory item details

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume",
    "description": "Long-lasting premium fragrance.",
    "price": 99.99,
    "currency": "PKR",
    "stockQuantity": 50,
    "status": "ACTIVE",
    "moderationStatus": "APPROVED",
    "imageUrls": [
      "https://cdn.yourdomain.com/gift-images/perfume.png"
    ],
    "variants": [
      {
        "id": "variant_id",
        "name": "50ml",
        "price": 129.99,
        "originalPrice": 159.99,
        "stockQuantity": 20,
        "sku": "PERFUME-50ML",
        "isDefault": true,
        "isActive": true
      }
    ]
  },
  "message": "Inventory item fetched successfully"
}
```

PATCH /api/v1/provider/inventory/{id}

Allowed role/access: Authenticated

Summary: Update own provider inventory item and upsert variants

Description: Variant id must belong to the provider-owned gift. Material variant changes re-submit approved gifts for moderation; stock-only changes do not.

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "name": "string",
  "description": "string",
  "shortDescription": "string",
  "price": 0,
  "currency": "string",
  "stockQuantity": 0,
  "sku": "string",
  "categoryId": "string",
  "imageUrls": [],
  "isAvailable": true,
  "replaceVariants": false,
  "variants": []
}
```

Response example:

```
{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume",
    "variants": [
      {
        "id": "variant_id",
        "name": "50ml",
        "price": 129.99,
        "stockQuantity": 20,
        "isDefault": true,
        "isActive": true
      }
    ]
  },
  "message": "Inventory item updated successfully"
}
```

DELETE /api/v1/provider/inventory/{id}

Allowed role/access: Authenticated

Summary: Soft-delete own inventory item

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/provider/inventory/{id}/availability

Allowed role/access: Authenticated

Summary: Update own inventory availability

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "isAvailable": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Provider Promotional Offers

GET /api/v1/provider/offers

Allowed role/access: Authenticated

Summary: —

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `status` (query, optional)
- `itemId` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/provider/offers

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
{
  "itemId": "string",
  "title": "string",
  "description": "string",
  "discountType": "string",
  "discountValue": 0,
  "startDate": "string",
  "endDate": "string",
  "eligibilityRules": "string",
  "isActive": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/provider/offers/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/provider/offers/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "title": "string",
  "description": "string",
  "discountType": "string",
  "discountValue": 0,
  "startDate": "string",
  "endDate": "string",
  "eligibilityRules": "string",
  "isActive": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

DELETE /api/v1/provider/offers/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/provider/offers/{id}/status

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "isActive": true,
```

```
  "reason": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Promotional Offers Management

GET /api/v1/promotional-offers/stats

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/promotional-offers/export

Allowed role/access: Authenticated

Summary: —

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `status` (query, optional)
- `itemId` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)
- `providerId` (query, optional)
- `approvalStatus` (query, optional)
- `discountType` (query, optional)
- `startFrom` (query, optional)
- `startTo` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/promotional-offers

Allowed role/access: Authenticated

Summary: —

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `status` (query, optional)
- `itemId` (query, optional)

- `sortBy` (query, optional)
- `sortOrder` (query, optional)
- `providerId` (query, optional)
- `approvalStatus` (query, optional)
- `discountType` (query, optional)
- `startFrom` (query, optional)
- `startTo` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/promotional-offers

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
{
  "itemId": "string",
  "title": "string",
  "description": "string",
  "discountType": "string",
  "discountValue": 0,
  "startDate": "string",
  "endDate": "string",
  "eligibilityRules": "string",
  "isActive": true,
  "providerId": "string",
  "approvalStatus": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/promotional-offers/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/promotional-offers/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "title": "string",
  "description": "string",
  "discountType": "string",
  "discountValue": 0,
  "startDate": "string",
  "endDate": "string",
  "eligibilityRules": "string",
  "isActive": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

DELETE /api/v1/promotional-offers/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/promotional-offers/{id}/approve

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "comment": "string",
  "notifyProvider": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/promotional-offers/{id}/reject

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "reason": "string",
  "comment": "string",
  "notifyProvider": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/promotional-offers/{id}/status

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "isActive": true,
  "reason": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Gift Categories

GET /api/v1/gift-categories/lookup

Allowed role/access: PUBLIC

Summary: Lookup active gift categories

Description: Public lookup under Gift Categories. Returns active category identifiers and media fields for lightweight selectors.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/gift-categories

Allowed role/access: Authenticated

Summary: Create gift category

Description: RBAC permission: giftCategories.create. Slug is auto-generated and unique. backgroundColor defaults to #F3E8FF; color remains a backward-compatible alias.

Request payload example:

```
{
  "name": "string",
  "description": "string",
  "iconKey": "string",
  "color": "#8B5CF6",
  "backgroundColor": "#E9D5FF",
  "imageUrl": "https://<YOUR_PUBLIC_BUCKET_OR_CDN_URL>/gift-category-images/perfumes.png",
  "sortOrder": 0,
  "isActive": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/gift-categories

Allowed role/access: Authenticated

Summary: List gift categories

Description: RBAC permission: giftCategories.read. Returns soft-delete-filtered categories with gift counts and category media fields.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `isActive` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/gift-categories/stats

Allowed role/access: Authenticated

Summary: Fetch gift category stats

Description: RBAC permission: giftCategories.read. Returns admin category inventory counters.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/gift-categories/{id}

Allowed role/access: Authenticated

Summary: Fetch gift category details

Description: RBAC permission: giftCategories.read. Includes backgroundColor and imageUrl for customer app design support.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/gift-categories/{id}

Allowed role/access: Authenticated

Summary: Update gift category

Description: RBAC permission: giftCategories.update. Slug is regenerated when name changes. Soft-deleted categories are not updated.

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "name": "string",
  "description": "string",
  "iconKey": "string",
  "color": "#8B5CF6",
  "backgroundColor": "#E9D5FF",
  "imageUrl": "https://<YOUR_PUBLIC_BUCKET_OR_CDN_URL>/gift-category-images/perfumes.png",
  "sortOrder": 0,
  "isActive": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

DELETE /api/v1/gift-categories/{id}

Allowed role/access: Authenticated

Summary: Soft-delete gift category

Description: RBAC permission: giftCategories.delete. Categories with attached gifts cannot be deleted; delete writes an audit log.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Gift Management

POST /api/v1/gifts

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: Create admin gift with optional nested variants

Description: SUPER_ADMIN/ADMIN with gifts.create. Nested variants are created in the same transaction and stored in GiftVariant.

Request payload example:

```
{
  "name": "string",
  "description": "string",
  "shortDescription": "string",
  "categoryId": "string",
  "providerId": "string",
  "price": 0,
  "currency": "USD",
  "stockQuantity": 0,
  "sku": "string",
  "imageUrls": [],
  "isPublished": true,
  "isFeatured": true,
  "tags": [],
  "moderationStatus": "string",
  "variants": []
}
```

Response example:

```
{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume",
    "price": 99.99,
    "currency": "PKR",
    "stockQuantity": 50,
    "sku": "PERFUME-001",
    "variants": [
      {
        "id": "variant_id",
        "name": "50ml",
        "price": 129.99,
        "originalPrice": 159.99,
        "stockQuantity": 20,
        "sku": "PERFUME-50ML",
        "isPopular": true,
        "isDefault": true,
        "sortOrder": 2,
        "isActive": true
      }
    ]
  },
  "message": "Gift created successfully"
}
```

GET /api/v1/gifts

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: List admin gifts

Description: SUPER_ADMIN/ADMIN with gifts.read. Supports category/provider/status/moderation filters.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `categoryId` (query, optional)
- `providerId` (query, optional)
- `status` (query, optional)
- `moderationStatus` (query, optional)
- `isPublished` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/gifts/stats

Allowed role/access: Authenticated

Summary: Fetch gift inventory stats

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/gifts/export

Allowed role/access: Authenticated

Summary: Export gift inventory

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `categoryId` (query, optional)
- `providerId` (query, optional)
- `status` (query, optional)
- `moderationStatus` (query, optional)
- `isPublished` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)
- `format` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/gifts/{id}

Allowed role/access: Authenticated

Summary: Fetch admin gift details with variants

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
```

```
  "message": "Request completed successfully"
}
```

PATCH /api/v1/gifts/{id}

Allowed role/access: Authenticated

Summary: Update admin gift and upsert nested variants

Description: If replaceVariants=true, omitted variants are soft-deleted. Only one default variant is allowed.

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "name": "string",
  "description": "string",
  "shortDescription": "string",
  "categoryId": "string",
  "providerId": "string",
  "price": 0,
  "currency": "USD",
  "stockQuantity": 0,
  "sku": "string",
  "imageUrls": [],
  "isPublished": true,
  "isFeatured": true,
  "tags": [],
  "replaceVariants": false,
  "variants": []
}
```

Response example:

```
{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume Updated",
    "variants": [
      {
        "id": "variant_id",
        "name": "50ml",
        "price": 129.99,
        "originalPrice": 159.99,
        "stockQuantity": 20,
        "sku": "PERFUME-50ML",
        "isDefault": true,
        "isActive": true
      }
    ]
  },
  "message": "Gift updated successfully"
}
```

DELETE /api/v1/gifts/{id}

Allowed role/access: Authenticated

Summary: Soft-delete gift

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/gifts/{id}/status

Allowed role/access: Authenticated

Summary: Update gift status

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "status": "string",
  "reason": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Gift Moderation

GET /api/v1/gift-moderation

Allowed role/access: Authenticated

Summary: —

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `status` (query, optional)
- `search` (query, optional)
- `providerId` (query, optional)
- `view` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/gift-moderation/{id}/approve

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "comment": "string",
  "publishNow": true,
  "notifyProvider": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/gift-moderation/{id}/reject

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "reason": "string",
  "comment": "string",
  "notifyProvider": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/gift-moderation/{id}/flag

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "reason": "string",
  "comment": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Customer Marketplace

GET /api/v1/customer/home

Allowed role/access: REGISTERED_USER

Summary: Fetch customer app home

Description: REGISTERED_USER only. Returns safe marketplace categories, discounted gifts, default address, and upcoming reminder.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/categories

Allowed role/access: REGISTERED_USER

Summary: List customer marketplace categories

Description: REGISTERED_USER only. Returns active categories that have available approved gifts.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/gifts/discounted

Allowed role/access: REGISTERED_USER

Summary: List discounted customer gifts

Description: REGISTERED_USER only. Reuses marketplace gift filters with offerOnly=true.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `categoryId` (query, optional)
- `categorySlug` (query, optional)
- `providerId` (query, optional)
- `offerOnly` (query, optional)
- `minPrice` (query, optional)
- `maxPrice` (query, optional)
- `minRating` (query, optional)
- `brand` (query, optional)
- `deliveryOption` (query, optional)
- `sortBy` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/gifts/filter-options

Allowed role/access: REGISTERED_USER

Summary: Fetch marketplace gift filter options

Description: REGISTERED_USER only. Brands are derived from approved active provider business names.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/gifts

Allowed role/access: REGISTERED_USER

Summary: List customer marketplace gifts

Description: REGISTERED_USER only. Only approved, published, active, in-stock gifts from approved active providers are returned. Active offers are calculated by the backend.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `categoryId` (query, optional)
- `categorySlug` (query, optional)
- `providerId` (query, optional)
- `offerOnly` (query, optional)
- `minPrice` (query, optional)
- `maxPrice` (query, optional)
- `minRating` (query, optional)
- `brand` (query, optional)
- `deliveryOption` (query, optional)
- `sortBy` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": [
    {
      "id": "gift_id",
      "name": "Luxury Perfume",
      "price": 99.99,
      "currency": "PKR",
      "imageUrl": "https://cdn.yourdomain.com/gift-images/perfume.png",
      "rating": 4.8,
      "isWishlisted": false,
      "shortDescription": "Premium fragrance gift.",
      "reviewCount": 0,
      "stockQuantity": 50,
      "category": {
        "id": "gift_category_id",
        "name": "Perfumes",
        "slug": "perfumes"
      },
      "provider": {
        "id": "provider_id",
        "businessName": "Dcodax Gifts"
      },
      "deliveryOptions": [
        "SAME_DAY",
        "NEXT_DAY",
        "SCHEDULED"
      ],
      "activeOffer": null
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Customer gifts fetched successfully"
}
```

GET /api/v1/customer/gifts/{id}

Allowed role/access: REGISTERED_USER

Summary: Fetch customer-safe gift details

Description: REGISTERED_USER only. Hidden/admin-only gift records are never returned.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume",
    "description": "Long-lasting premium fragrance.",
    "shortDescription": "Premium fragrance gift.",
    "price": 99.99,
    "originalPrice": 99.99,
    "currency": "PKR",
    "imageUrls": [
      "https://cdn.yourdomain.com/gift-images/perfume.png"
    ],
    "rating": 4.8,
    "reviewCount": 0,
    "stockQuantity": 50,
    "sku": "PERFUME-001",
    "isWishlisted": false,
    "badges": [
      "AUTHENTIC"
    ],
    "category": {
      "id": "gift_category_id",
      "name": "Perfumes",
      "slug": "perfumes"
    },
    "provider": {
      "id": "provider_id",
      "businessName": "Dcodax Gifts",
      "rating": 4.8,
      "reviewCount": 0,
      "fulfillmentMethods": [
        "DELIVERY"
      ]
    },
    "variants": [
      {
        "id": "variant_id",
        "name": "50ml",
        "price": 129.99,
        "originalPrice": 159.99,
        "stockQuantity": 20,
        "sku": "PERFUME-50ML",
        "isPopular": true,
        "isDefault": true
      }
    ],
    "deliveryOptions": [
      "SAME_DAY",
      "NEXT_DAY",
      "SCHEDULED"
    ],
    "activeOffer": null
  },
  "message": "Gift details fetched successfully"
}
```

Customer Wishlist

GET /api/v1/customer/wishlist

Allowed role/access: REGISTERED_USER

Summary: List wishlist gifts

Description: REGISTERED_USER only. Returns customer-safe available gifts.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/customer/wishlist/{giftId}

Allowed role/access: REGISTERED_USER

Summary: Add gift to wishlist

Description: REGISTERED_USER only. Gift must be active, approved, published, and in stock. Duplicate wishlist entries are ignored.

Parameters:

- `giftId` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

DELETE /api/v1/customer/wishlist/{giftId}

Allowed role/access: REGISTERED_USER

Summary: Remove gift from wishlist

Description: REGISTERED_USER only. Removes only the current customer wishlist row.

Parameters:

- `giftId` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Customer Addresses

GET /api/v1/customer/addresses

Allowed role/access: REGISTERED_USER

Summary: List customer addresses

Description: REGISTERED_USER only. Customers can only view their own non-deleted addresses.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/customer/addresses

Allowed role/access: REGISTERED_USER

Summary: Create customer address

Description: REGISTERED_USER only. Maintains one default address per customer.

Request payload example:

```
{
  "label": "Home",
  "fullName": "Sarah Khan",
  "phone": "+923001234567",
  "line1": "House 12, Street 4, F-8/2",
  "line2": "Near Centaurus Mall",
  "city": "Islamabad",
```

```
  "state": "Islamabad Capital Territory",
  "country": "Pakistan",
  "postalCode": "44000",
  "latitude": 33.6844,
  "longitude": 73.0479,
  "deliveryInstructions": "Leave at reception.",
  "isDefault": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/addresses/{id}

Allowed role/access: REGISTERED_USER

Summary: Fetch customer address

Description: REGISTERED_USER only. Address must belong to the current customer.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/customer/addresses/{id}

Allowed role/access: REGISTERED_USER

Summary: Update customer address

Description: REGISTERED_USER only. Maintains one default address per customer.

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "label": "Home",
  "fullName": "Sarah Khan",
  "phone": "+923001234567",
  "line1": "House 12, Street 4, F-8/2",
  "line2": "Near Centaurus Mall",
  "city": "Islamabad",
  "state": "Islamabad Capital Territory",
  "country": "Pakistan",
  "postalCode": "44000",
  "latitude": 33.6844,
  "longitude": 73.0479,
  "deliveryInstructions": "Leave at reception.",
  "isDefault": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

DELETE /api/v1/customer/addresses/{id}

Allowed role/access: REGISTERED_USER

Summary: Soft-delete customer address

Description: REGISTERED_USER only. Address is soft deleted and removed from default status.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/customer/addresses/{id}/default

Allowed role/access: REGISTERED_USER

Summary: Set default customer address

Description: REGISTERED_USER only. Clears default flag from all other customer addresses.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Customer Contacts

GET /api/v1/customer/contacts

Allowed role/access: REGISTERED_USER

Summary: List customer contacts

Description: REGISTERED_USER only. Lists only contacts owned by the authenticated customer.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `relationship` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/customer/contacts

Allowed role/access: REGISTERED_USER

Summary: Create customer contact

Description: REGISTERED_USER only. Creates a personal gift contact owned by the authenticated customer. Requires at least one contact method: phone, email, or address.

Request payload example:

```
{
  "name": "Mary Wilson",
  "relationship": "Mother",
  "phone": "+1234567890",
  "email": "mary@example.com",
  "address": "387 Merdina",
  "likes": "Glasses, makeup, dresses",
  "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/mary.png",
  "birthday": "1990-05-12",
  "notes": "Prefers elegant gifts."
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/contacts/{id}

Allowed role/access: REGISTERED_USER

Summary: Fetch customer contact

Description: REGISTERED_USER only. Contact must belong to the authenticated customer.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/customer/contacts/{id}

Allowed role/access: REGISTERED_USER

Summary: Update customer contact

Description: REGISTERED_USER only. Updates only contacts owned by the authenticated customer.

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "name": "Mary Wilson",
  "relationship": "Mother",
  "phone": "+1234567890",
  "email": "mary@example.com",
  "address": "387 Merdina",
  "likes": "Glasses, makeup, dresses",
  "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/mary.png",
  "birthday": "1990-05-12",
  "notes": "Prefers elegant gifts."
}
```

Response example:

```
{
  "success": true,
  "data": {},
```

```
  "message": "Request completed successfully"
}
```

DELETE /api/v1/customer/contacts/{id}

Allowed role/access: REGISTERED_USER

Summary: Soft-delete customer contact

Description: REGISTERED_USER only. Soft deletes only contacts owned by the authenticated customer.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Customer Events

GET /api/v1/customer/events

Allowed role/access: REGISTERED_USER

Summary: List customer events

Description: REGISTERED_USER only. Lists only events owned by the authenticated customer.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `eventType` (query, optional)
- `fromDate` (query, optional)
- `toDate` (query, optional)
- `recipientId` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/customer/events

Allowed role/access: REGISTERED_USER

Summary: Create customer event

Description: REGISTERED_USER only. recipientId must belong to the authenticated customer.

Request payload example:

```
{
  "eventType": "BIRTHDAY",
  "title": "Sarah's Birthday",
  "recipientId": "cmf0contactmary001",
  "eventDate": "2026-01-31T00:00:00.000Z",
  "reminderTiming": "ON_THE_DAY",
  "reminderFrequency": "ONE_TIME",
  "customAlertTime": "09:00",
```

```
  "channels": [
    "EMAIL",
    "SMS"
  ],
  "notes": "Send a birthday gift.",
  "isActive": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/events/calendar

Allowed role/access: REGISTERED_USER

Summary: Fetch monthly calendar events

Description: REGISTERED_USER only. Returns marked dates and own events.

Parameters:

- `month` (query, required)
- `year` (query, required)
- `eventType` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/events/upcoming

Allowed role/access: REGISTERED_USER

Summary: Fetch upcoming customer events

Description: REGISTERED_USER only. Defaults to 10 events within 30 days.

Parameters:

- `limit` (query, optional)
- `daysAhead` (query, optional)
- `eventType` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/events/{id}

Allowed role/access: REGISTERED_USER

Summary: Fetch customer event details

Description: REGISTERED_USER only. Event must belong to the authenticated customer.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/customer/events/{id}

Allowed role/access: REGISTERED_USER

Summary: Update customer event

Description: REGISTERED_USER only. Event and recipient contact must belong to the authenticated customer.

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "eventType": "ANNIVERSARY",
  "title": "Sarah's Anniversary",
  "recipientId": "cmf0contactmary001",
  "eventDate": "2026-01-31T00:00:00.000Z",
  "reminderTiming": "THREE_DAYS_BEFORE",
  "reminderFrequency": "YEARLY",
  "customAlertTime": "09:00",
  "channels": [
    "PUSH",
    "EMAIL"
  ],
  "notes": "Send flowers.",
  "isActive": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

DELETE /api/v1/customer/events/{id}

Allowed role/access: REGISTERED_USER

Summary: Soft-delete customer event

Description: REGISTERED_USER only. Soft deletes only own event and cancels pending reminder jobs.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Customer Event Reminder Settings

GET /api/v1/customer/events/{id}/reminder-settings

Allowed role/access: REGISTERED_USER

Summary: Fetch event reminder settings

Description: REGISTERED_USER only. Event must belong to the authenticated customer.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/customer/events/{id}/reminder-settings

Allowed role/access: REGISTERED_USER

Summary: Update event reminder settings

Description: REGISTERED_USER only. Event must belong to the authenticated customer.

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "reminderFrequency": "YEARLY",
  "reminderTiming": "ONE_DAY_BEFORE",
  "customAlertTime": "09:00",
  "channels": {
    "push": true,
    "email": true,
    "sms": false
  }
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Customer Cart

GET /api/v1/customer/cart

Allowed role/access: REGISTERED_USER

Summary: Fetch active cart

Description: REGISTERED_USER only. Totals are backend calculated from price snapshots.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "id": "cart_id",
    "status": "ACTIVE",
    "items": [
      {
        "id": "cart_item_id",
        "giftId": "gift_id",
        "variantId": "variant_id",
        "name": "Luxury Perfume",
        "variantName": "50ml",
        "quantity": 1,
```

```
        "unitPrice": 129.99,
        "discountAmount": 20,
        "finalUnitPrice": 109.99,
        "lineTotal": 109.99,
        "imageUrl": "https://cdn.yourdomain.com/gift-images/perfume.png",
        "deliveryOption": "SAME_DAY",
        "recipient": {
          "contactId": "contact_id",
          "name": "Sarah Khan",
          "phone": "+923001234567",
          "addressId": "address_id"
        },
        "giftMessage": "Hope you love this special surprise!",
        "messageMediaUrls": [
          "https://cdn.yourdomain.com/gift-message-media/photo.png"
        ],
        "scheduledDeliveryAt": "2026-12-24T10:00:00.000Z"
      }
    ],
    "summary": {
      "subtotal": 129.99,
      "discountTotal": 20,
      "deliveryFee": 0,
      "tax": 0,
      "total": 109.99,
      "currency": "PKR"
    }
  },
  "message": "Cart fetched successfully"
}
```


DELETE /api/v1/customer/cart

Allowed role/access: REGISTERED_USER

Summary: Clear active cart

Description: REGISTERED_USER only. Removes all items from active cart.

Request payload example:

```
None
```

Response example:


```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```


POST /api/v1/customer/cart/items

Allowed role/access: REGISTERED_USER

Summary: Add item to cart

Description: REGISTERED_USER only. Backend calculates unit price, active offer discount, final price, subtotal, delivery fee placeholder, and total.

Request payload example:


```
{
  "giftId": "cmf0giftroses001",
  "variantId": "cmf0variant50ml001",
  "quantity": 1,
  "deliveryOption": "SCHEDULED",
  "recipientContactId": "cmf0contactmary001",
  "recipientName": "Sarah Khan",
  "recipientPhone": "+923001234567",
  "recipientAddressId": "cmf0addresshome001",
  "eventId": "cmf0eventbirthday001",
  "giftMessage": "Hope you love this special surprise!",
  "messageMediaUrls": [
    "https://cdn.yourdomain.com/gift-message-media/photo.png"
  ],
  "scheduledDeliveryAt": "2026-06-01T12:00:00.000Z"
}
```


Response example:


```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/customer/cart/items/{id}

Allowed role/access: REGISTERED_USER

Summary: Update cart item

Description: REGISTERED_USER only. Validates ownership through the active customer cart.

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "variantId": "cmf0variant100ml001",
  "quantity": 2,
  "deliveryOption": "NEXT_DAY",
  "recipientContactId": "cmf0contactmary001",
  "recipientName": "Sarah Khan",
  "recipientPhone": "+923001234567",
  "recipientAddressId": "cmf0addresshome001",
  "eventId": "cmf0eventbirthday001",
  "giftMessage": "Happy Birthday!",
  "messageMediaUrls": [
    "https://cdn.yourdomain.com/gift-message-media/video.mp4"
  ],
  "scheduledDeliveryAt": "2026-06-01T12:00:00.000Z"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

DELETE /api/v1/customer/cart/items/{id}

Allowed role/access: REGISTERED_USER

Summary: Delete cart item

Description: REGISTERED_USER only. Deletes only items in the current customer active cart.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Customer Orders

POST /api/v1/customer/orders

Allowed role/access: REGISTERED_USER

Summary: Create order from active cart

Description: REGISTERED_USER only. Prices are backend-calculated from cart/payment snapshots. STRIPE_CARD requires a successful owned paymentId; COD stays pending; PLACEHOLDER is for development only. Multiple providers are split into provider sub-orders.

Request payload example:

```
{
  "cartId": "cmf0cartactive001",
  "paymentId": "cmf0payment001",
  "deliveryAddressId": "cmf0addresshome001",
  "paymentMethod": "COD"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/orders

Allowed role/access: REGISTERED_USER

Summary: List customer orders

Description: REGISTERED_USER only. Returns orders owned by the current customer.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `type` (query, optional)
- `status` (query, optional)
- `fromDate` (query, optional)
- `toDate` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/orders/{id}

Allowed role/access: REGISTERED_USER

Summary: Fetch customer order

Description: REGISTERED_USER only. Order must belong to the current customer.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "id": "order_id",
    "orderNumber": "ORD-1760000000000",
    "status": "CONFIRMED",
    "paymentStatus": "SUCCEEDED",
    "paymentMethod": "STRIPE_CARD",
    "recipient": {
      "name": "Sarah Khan",
      "email": null,
      "phone": "+923001234567",
      "avatarUrl": null
    },
    "deliveryDate": "2026-12-24T10:00:00.000Z",
    "occasion": null,
    "giftMessage": "Hope you love this special surprise!",
    "items": [
      {
        "giftId": "gift_id",
        "name": "Luxury Perfume",
        "variantName": "50ml",
        "quantity": 1,
        "imageUrl": "https://cdn.yourdomain.com/gift-images/perfume.png",
        "total": 109.99
      }
    ],
    "summary": {
```

```
      "subtotal": 129.99,
      "discountTotal": 20,
      "deliveryFee": 0,
      "tax": 0,
      "total": 109.99,
      "currency": "PKR"
    }
  },
  "message": "Order fetched successfully."
}
```

Customer Recurring Payments

GET /api/v1/customer/recurring-payments

Allowed role/access: REGISTERED_USER

Summary: List own recurring payments

Description: REGISTERED_USER only. Returns recurring money/gift payment subscriptions owned by the logged-in customer.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `status` (query, optional)
- `frequency` (query, optional)
- `recipientContactId` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": [
    {
      "id": "recurring_payment_id",
      "title": "Sarah's Birthday",
      "recipient": {
        "id": "contact_id",
        "name": "Sarah Johnson",
        "email": "sarah.j@example.com",
        "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/sarah.png"
      },
      "amount": 50,
      "currency": "PKR",
      "frequency": "MONTHLY",
      "nextBillingAt": "2026-03-15T09:00:00.000Z",
      "status": "ACTIVE",
      "message": "Monthly flowers",
      "createdAt": "2026-05-09T10:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Recurring payments fetched successfully."
}
```

POST /api/v1/customer/recurring-payments

Allowed role/access: REGISTERED_USER

Summary: Create recurring payment

Description: REGISTERED_USER only. Recipient contact and saved Stripe payment method must both belong to the logged-in customer. Stripe card recurring payments require a saved payment method.

Request payload example:

```
{
  "amount": 100,
  "currency": "PKR",
  "frequency": "WEEKLY",
  "schedule": "string",
```

```
  "recipientContactId": "contact_id",
  "message": "Hope you love this special surprise!",
  "messageMediaUrls": [
    "https://cdn.yourdomain.com/gift-message-media/photo.png"
  ],
  "paymentMethod": "STRIPE_CARD",
  "stripePaymentMethodId": "pm_xxx",
  "startDate": "2026-05-10T00:00:00.000Z",
  "endDate": null,
  "autoSend": true
}
```

Response example:

```
{
  "success": true,
  "data": {
    "id": "recurring_payment_id",
    "amount": 100,
    "currency": "PKR",
    "frequency": "WEEKLY",
    "nextBillingAt": "2026-05-12T09:00:00.000Z",
    "status": "ACTIVE"
  },
  "message": "Recurring payment created successfully."
}
```

GET /api/v1/customer/recurring-payments/summary

Allowed role/access: Authenticated

Summary: Fetch recurring payment summary counts

Description: Must stay before /customer/recurring-payments/:id route.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "total": 5,
    "active": 3,
    "paused": 1,
    "cancelled": 1,
    "failed": 0
  },
  "message": "Recurring payment summary fetched successfully."
}
```

GET /api/v1/customer/recurring-payments/{id}

Allowed role/access: REGISTERED_USER

Summary: Fetch own recurring payment details

Description: REGISTERED_USER only. Customer cannot access another user’s recurring payment.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "id": "recurring_payment_id",
    "title": "Monthly Flowers",
    "recipient": {
      "id": "contact_id",
      "name": "Sarah Johnson",
      "email": "sarah.j@example.com",
      "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/sarah.png"
    },
    "amount": 50,
    "currency": "PKR",
    "frequency": "MONTHLY",
```

```
    "nextBillingAt": "2026-03-15T09:00:00.000Z",
    "status": "ACTIVE",
    "message": "Fresh seasonal bouquet delivered to her doorstep every month",
    "messageMediaUrls": [],
    "paymentMethod": {
      "type": "STRIPE_CARD",
      "brand": "visa",
      "last4": "4242",
      "expiryMonth": 12,
      "expiryYear": 2026
    },
    "schedule": {
      "frequency": "MONTHLY",
      "dayOfMonth": 15,
      "time": "09:00",
      "timezone": "Asia/Karachi"
    },
    "createdAt": "2026-05-09T10:00:00.000Z"
  },
  "message": "Recurring payment fetched successfully."
}
```

PATCH /api/v1/customer/recurring-payments/{id}

Allowed role/access: Authenticated

Summary: Update own recurring payment

Description: Cannot edit CANCELLED recurring payments. Changes apply from the next billing cycle and nextBillingAt is recalculated.

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "amount": 50,
  "frequency": "MONTHLY",
  "schedule": "string",
  "message": "Fresh flowers every month.",
  "messageMediaUrls": [],
  "stripePaymentMethodId": "pm_xxx"
}
```

Response example:

```
{
  "success": true,
  "data": {
    "id": "recurring_payment_id",
    "status": "ACTIVE",
    "nextBillingAt": "2026-03-15T09:00:00.000Z"
  },
  "message": "Recurring payment updated successfully. Changes will apply from the next billing
cycle."
}
```

POST /api/v1/customer/recurring-payments/{id}/pause

Allowed role/access: Authenticated

Summary: Pause own active recurring payment

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "reason": "User paused recurring payment."
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/customer/recurring-payments/{id}/resume

Allowed role/access: Authenticated

Summary: Resume own paused recurring payment

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/customer/recurring-payments/{id}/cancel

Allowed role/access: Authenticated

Summary: Cancel own recurring payment

Description: IMMEDIATELY cancels future processing. AFTER_CURRENT_BILLING_CYCLE sets cancelAtPeriodEnd and cancelAt.

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "cancelMode": "IMMEDIATELY",
  "reason": "No longer needed."
}
```

Response example:

```
{
  "success": true,
  "data": {
    "id": "recurring_payment_id",
    "status": "CANCELLED",
    "cancelMode": "IMMEDIATELY"
  },
  "message": "Recurring payment cancelled successfully."
}
```

GET /api/v1/customer/recurring-payments/{id}/history

Allowed role/access: Authenticated

Summary: List own recurring payment billing history

Parameters:

- `id` (path, required)
- `page` (query, optional)
- `limit` (query, optional)
- `status` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": [
    {
      "id": "history_id",
      "paymentId": "payment_id",
      "amount": 50,
      "currency": "PKR",
```

```
      "status": "SUCCESS",
      "billingDate": "2026-02-15T09:00:00.000Z",
      "transactionId": "GFT-8829-XPL",
      "failureReason": null
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Recurring payment history fetched successfully."
}
```

Customer Transactions

GET /api/v1/customer/transactions

Allowed role/access: REGISTERED_USER

Summary: List own customer transactions

Description: REGISTERED_USER only. Normalizes backend Payment, Order, MoneyGift, and RecurringPayment occurrence records owned by the logged-in customer.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `fromDate` (query, optional)
- `toDate` (query, optional)
- `type` (query, optional)
- `status` (query, optional)
- `paymentMethod` (query, optional)
- `minAmount` (query, optional)
- `maxAmount` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": [
    {
      "id": "payment_id",
      "transactionId": "TXN-2026-001234",
      "title": "Monthly Flowers",
      "description": "Recurring payment",
      "recipient": {
        "id": "contact_id",
        "name": "Sarah Johnson",
        "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/sarah.png"
      },
      "amount": 50,
      "currency": "PKR",
      "type": "RECURRING_PAYMENT",
      "status": "SUCCESS",
      "paymentMethod": "STRIPE_CARD",
      "createdAt": "2026-03-01T14:34:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Transactions fetched successfully."
}
```

GET /api/v1/customer/transactions/summary

Allowed role/access: Authenticated

Summary: Fetch own transaction summary

Description: Defaults to current month when no date range is provided. Uses backend-calculated payment records only.

Parameters:

- `fromDate` (query, optional)
- `toDate` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "totalSpentThisMonth": 255,
    "currency": "PKR",
    "successfulCount": 9,
    "failedCount": 1,
    "pendingCount": 0,
    "refundedCount": 0
  },
  "message": "Transaction summary fetched successfully."
}
```

GET /api/v1/customer/transactions/export

Allowed role/access: Authenticated

Summary: Export own transactions

Description: CSV is supported and returned as a file. Export is scoped to the logged-in customer only.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `fromDate` (query, optional)
- `toDate` (query, optional)
- `type` (query, optional)
- `status` (query, optional)
- `paymentMethod` (query, optional)
- `minAmount` (query, optional)
- `maxAmount` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)
- `format` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/transactions/{id}

Allowed role/access: Authenticated

Summary: Fetch own transaction details

Description: Includes order, money gift, recurring payment, and payment gateway references when available. Billing address returns null until available.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "id": "payment_id",
    "transactionId": "TXN-2026-001234-ABC-XYZ",
    "status": "SUCCESS",
    "amount": 50,
    "currency": "PKR",
    "createdAt": "2026-03-01T14:34:00.000Z",
    "type": "RECURRING_PAYMENT",
    "giftInformation": {
      "giftName": "Monthly Flowers Subscription",
      "deliveryType": "Money",
      "recipient": {
        "id": "contact_id",
        "name": "Sarah Johnson",
        "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/sarah.png"
      },
      "orderReference": null,
      "recurringPaymentId": "recurring_payment_id"
    },
    "paymentInformation": {
      "paymentMethod": "Stripe card",
      "gatewayReference": "pi_3MmlLrLkdIwHu7ix0fhBHWqt",
      "billingAddress": null
    }
  },
  "message": "Transaction details fetched successfully."
}
```

GET /api/v1/customer/transactions/{id}/receipt

Allowed role/access: Authenticated

Summary: Download own transaction receipt

Description: Receipt is generated only for the transaction owner and never exposes Stripe secret data.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Payments

POST /api/v1/customer/payments/create-intent

Allowed role/access: REGISTERED_USER

Summary: Create payment intent from active cart

Description: REGISTERED_USER only. Amount is calculated from backend cart totals; frontend amount is never accepted.

Request payload example:

```
{
  "cartId": "cmf0cartactive001",
  "paymentMethod": "STRIPE_CARD"
}
```

Response example:

```
{
  "success": true,
  "data": {
    "paymentId": "payment_id",
    "stripePaymentIntentId": "pi_xxx",
    "clientSecret": "pi_xxx_secret_xxx",
    "publishableKey": "pk_live_or_test",
    "amount": 10999,
```

```
    "currency": "PKR"
  },
  "message": "Payment intent created successfully."
}
```

POST /api/v1/customer/payments/confirm

Allowed role/access: REGISTERED_USER

Summary: Confirm Stripe payment

Description: REGISTERED_USER only. Retrieves Stripe PaymentIntent server-side before updating local payment status.

Request payload example:

```
{
  "paymentId": "cmf0payment001",
  "stripePaymentIntentId": "pi_3Pxxxxxxxxxxxxxxx"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/payments/{id}

Allowed role/access: Authenticated

Summary: Fetch own payment details

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "paymentId": "payment_id",
    "provider": "STRIPE",
    "stripePaymentIntentId": "pi_xxx",
    "amount": 109.99,
    "currency": "PKR",
    "status": "SUCCEEDED",
    "paymentMethod": "STRIPE_CARD",
    "failureReason": null
  },
  "message": "Payment fetched successfully."
}
```

POST /api/v1/payments/stripe/webhook

Allowed role/access: PUBLIC

Summary: Stripe webhook endpoint

Description: Verifies Stripe-Signature using the configured webhook secret before processing events.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/customer/money-gifts

Allowed role/access: Authenticated

Summary: Send payment as gift

Description: Creates a customer-to-recipient money gift record and Stripe PaymentIntent for STRIPE_CARD.

Request payload example:

```
{
  "amount": 100,
  "currency": "PKR",
  "recipientContactId": "cmf0contactmary001",
  "message": "Hope this helps. Enjoy your day!",
  "messageMediaUrls": [
    "https://cdn.yourdomain.com/gift-message-media/photo.png"
  ],
  "deliveryDate": "2026-12-24T00:00:00.000Z",
  "repeatAnnually": false,
  "paymentMethod": "STRIPE_CARD"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/money-gifts

Allowed role/access: Authenticated

Summary: List own money gifts

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/money-gifts/{id}

Allowed role/access: Authenticated

Summary: Fetch own money gift details

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Customer Referrals & Rewards

GET /api/v1/customer/referrals/summary

Allowed role/access: REGISTERED_USER

Summary: Fetch own referral reward summary

Description: REGISTERED_USER only. Customers can view only their own referral progress and ledger-derived balances.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "invitedFriends": 3,
    "successfulReferrals": 2,
    "rewardsEarned": 20,
    "availableCredit": 20,
    "currency": "USD",
    "progress": {
      "totalInvited": 3,
      "joined": 2,
      "pending": 1
    }
  },
  "message": "Referral summary fetched successfully."
}
```

GET /api/v1/customer/referrals/link

Allowed role/access: Authenticated

Summary: Fetch own referral link

Description: Generates a unique customer referral code when missing. The link never exposes internal user IDs.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "referralCode": "SARAH-M",
    "referralLink": "https://giftapp.com/share/sarah-m",
    "shareTitle": "Invite Friends, Earn Rewards",
    "shareMessage": "Join Gift App with my referral link and we both earn rewards after your
first gift purchase.",
    "rewardText": "Get $10 credit after your friend's first gift purchase."
  },
  "message": "Referral link fetched successfully."
}
```

GET /api/v1/customer/referrals/history

Allowed role/access: REGISTERED_USER

Summary: List own referral history

Description: REGISTERED_USER only. History is scoped to referrals created by the logged-in customer.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `status` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/customer/referrals/redeem

Allowed role/access: Authenticated

Summary: Redeem own available reward credit

Description: Creates a REDEEMED reward ledger entry. Redemption cannot exceed ledger-derived available credit.

Request payload example:

```
{
  "amount": 20,
  "redeemTo": "WALLET"
}
```

Response example:

```
{
  "success": true,
  "data": {
    "redeemedAmount": 20,
    "currency": "USD",
    "walletBalance": 20
  },
  "message": "Reward redeemed successfully."
}
```

GET /api/v1/customer/rewards/balance

Allowed role/access: Authenticated

Summary: Fetch own reward balance

Description: Balance is calculated from RewardLedger entries, not a mutable user balance field.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "availableCredit": 20,
    "lifetimeEarned": 20,
    "lifetimeRedeemed": 0,
    "currency": "USD"
  },
  "message": "Reward balance fetched successfully."
}
```

GET /api/v1/customer/rewards/ledger

Allowed role/access: REGISTERED_USER

Summary: List own reward ledger

Description: REGISTERED_USER only. Returns ledger entries owned by the logged-in customer.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `type` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/referrals/terms

Allowed role/access: Authenticated

Summary: Fetch referral terms

Description: Returns config/env based customer referral terms for the mobile app.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "title": "Referral Terms",
    "rewardAmount": 10,
    "currency": "USD",
    "qualificationRule": "Reward is credited after your referred friend completes their first
gift purchase.",
    "terms": [
      "Referral rewards are available only for registered users.",
      "Reward is credited after the referred user's first successful purchase.",
      "Cancelled or refunded orders may revoke reward eligibility.",
      "Referral abuse may result in reward cancellation."
    ]
  },
  "message": "Referral terms fetched successfully."
}
```

Customer Wallet

GET /api/v1/customer/wallet

Allowed role/access: REGISTERED_USER

Summary: Fetch own wallet

Description: REGISTERED_USER only. Wallet is lazily created and balances are backed by wallet ledger entries.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "totalBalance": 1240.5,
    "giftCredits": 350,
    "cashBalance": 890.5,
    "currency": "USD",
    "defaultPaymentMethod": {
      "id": "pm_xxx",
      "type": "CARD",
      "brand": "visa",
      "last4": "4242",
      "expiryMonth": 9,
      "expiryYear": 2025,
      "isDefault": true
    },
    "defaultBankAccount": {
      "id": "bank_account_id",
      "bankName": "Chase Bank",
      "last4": "8821",
      "isDefault": false
    }
  },
  "message": "Wallet fetched successfully."
}
```

POST /api/v1/customer/wallet/add-funds

Allowed role/access: Authenticated

Summary: Create wallet top-up payment

Description: Uses Stripe PaymentIntent. Wallet is credited only after successful server-side confirmation/webhook.

Request payload example:

```
{
  "amount": 100,
  "currency": "USD",
  "paymentMethod": "STRIPE_CARD",
  "stripePaymentMethodId": "pm_xxx"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/customer/wallet/history

Allowed role/access: Authenticated

Summary: List own wallet history

Description: Positive amounts are credits, negative amounts are debits. Results are scoped to the logged-in customer.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `type` (query, optional)
- `status` (query, optional)
- `fromDate` (query, optional)
- `toDate` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Media Upload Policy

GET /api/v1/media-upload-policy

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: Fetch global media upload policy

Description: SUPER_ADMIN or ADMIN with mediaPolicy.read. uploads/presigned-url enforces this policy before issuing upload URLs.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "allowedFileTypes": {
      "jpeg": true,
      "jpg": true,
      "png": true,
      "gif": false,
      "mp4": true,
      "mov": true,
      "mp3": true,
      "wav": false,
      "svg": false
    },
    "maxImageSizeMb": 10,
    "maxVideoSizeMb": 500,
    "maxAudioSizeMb": 50,
    "scanUploads": true,
    "blockSvgUploads": true,
```

```
    "updatedAt": "2026-05-09T10:00:00.000Z",
    "updatedBy": {
      "id": "admin_id",
      "name": "Alex Rivera"
    }
  },
  "message": "Media upload policy fetched successfully."
}
```

PATCH /api/v1/media-upload-policy

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: Update global media upload policy

Description: SUPER_ADMIN only. Does not expose AWS secrets or bucket credentials.

Request payload example:

```
{
  "allowedFileTypes": "string",
  "maxImageSizeMb": 10,
  "maxVideoSizeMb": 500,
  "maxAudioSizeMb": 50,
  "scanUploads": true,
  "blockSvgUploads": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/media-upload-policy/audit-logs

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: List media upload policy audit logs

Description: SUPER_ADMIN only.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `fromDate` (query, optional)
- `toDate` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Referral Settings

GET /api/v1/referral-settings

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: Fetch referral settings

Description: SUPER_ADMIN or ADMIN with referralSettings.read. Customer referral APIs consume these settings. Pending referrals use the settings snapshot stored at referral creation.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "isActive": true,
    "referrerRewardAmount": 25,
    "newUserRewardAmount": 10,
    "rewardCurrency": "USD",
    "minimumTransactionAmount": 50,
    "referralExpirationValue": 30,
    "referralExpirationUnit": "DAYS",
    "allowSelfReferrals": false,
    "qualificationRule": "FIRST_SUCCESSFUL_PURCHASE",
    "updatedAt": "2026-05-09T10:00:00.000Z"
  },
  "message": "Referral settings fetched successfully."
}
```

PATCH /api/v1/referral-settings

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: Update referral settings

Description: SUPER_ADMIN only. Changes apply to future referral snapshots and do not recalculate already-earned rewards.

Request payload example:

```
{
  "referrerRewardAmount": 25,
  "newUserRewardAmount": 10,
  "rewardCurrency": "USD",
  "minimumTransactionAmount": 50,
  "referralExpirationValue": 30,
  "referralExpirationUnit": "DAYS",
  "allowSelfReferrals": false,
  "qualificationRule": "FIRST_SUCCESSFUL_PURCHASE"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/referral-settings/activate

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: Activate referral program

Description: SUPER_ADMIN only. Existing earned rewards remain redeemable.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/referral-settings/deactivate

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: Deactivate referral program

Description: SUPER_ADMIN only. New referral rewards are blocked while inactive; earned rewards remain redeemable.

Request payload example:

```
{
  "reason": "Temporarily paused by Super Admin."
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/referral-settings/stats

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: Fetch referral stats

Description: SUPER_ADMIN or ADMIN with referralSettings.read.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/referral-settings/audit-logs

Allowed role/access: SUPER_ADMIN, ADMIN

Summary: List referral settings audit logs

Description: SUPER_ADMIN only.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `fromDate` (query, optional)
- `toDate` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Notifications

GET /api/v1/notifications

Allowed role/access: Authenticated

Summary: List notifications

Description: JWT auth. Returns only notifications belonging to the logged-in account. Supports All, Unread, Birthdays, Deliveries, and New Contacts filters. No group gift notifications are supported.

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `filter` (query, optional)
- `type` (query, optional)
- `isRead` (query, optional)
- `groupByDate` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": [
    {
      "id": "notification_id",
      "title": "Payment successful",
      "message": "Your payment was completed successfully.",
      "type": "PAYMENT_SUCCEEDED",
      "isRead": false,
      "metadata": {
        "paymentId": "payment_id"
      },
      "createdAt": "2026-05-09T10:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Notifications fetched successfully"
}
```

GET /api/v1/notifications/summary

Allowed role/access: Authenticated

Summary: Fetch notification summary

Description: JWT auth. Counts only notifications belonging to the logged-in account.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {
    "total": 12,
    "unread": 3,
    "byType": {
      "PAYMENT_SUCCEEDED": 2,
      "RECURRING_PAYMENT_CHARGE_FAILED": 1,
      "BROADCAST": 9
    }
  },
  "message": "Notification summary fetched successfully"
}
```

GET /api/v1/notifications/preferences

Allowed role/access: Authenticated

Summary: Fetch notification preferences

Description: JWT auth. Preferences belong only to the logged-in account.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/notifications/preferences

Allowed role/access: Authenticated

Summary: Update notification preferences

Description: JWT auth. Push toggle does not delete device tokens. No group gift preference exists.

Request payload example:

```
{
  "pushEnabled": true,
  "emailEnabled": true,
  "smsEnabled": false,
  "dealUpdatesEnabled": true,
  "birthdayRemindersEnabled": true,
  "deliveryUpdatesEnabled": true,
  "newContactAlertsEnabled": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/notifications/read-all

Allowed role/access: Authenticated

Summary: Mark all own notifications as read

Description: JWT auth. Marks only notifications belonging to the logged-in account.

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/notifications/{id}/read

Allowed role/access: Authenticated

Summary: Mark notification as read

Description: JWT auth. Notification must belong to the logged-in account.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/notifications/{id}/action

Allowed role/access: Authenticated

Summary: Process notification action

Description: JWT auth. Supports SEND_GIFT, REMIND_ME_LATER, VIEW_ORDER, VIEW_CONTACT. Group gift actions are not supported.

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "action": "SEND_GIFT"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/notifications/device-tokens

Allowed role/access: Authenticated

Summary: Save device token

Description: JWT auth. Token belongs only to logged-in account. Duplicate deviceId updates existing record.

Request payload example:

```
{
  "token": "ExponentPushToken[xxxxxxxxxxxxxxxxxxxxxx]",
  "platform": "IOS",
  "deviceId": "ios-iphone-15-pro-device-id"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

DELETE /api/v1/notifications/device-tokens/{id}

Allowed role/access: Authenticated

Summary: Disable device token

Description: JWT auth. Users can disable only their own device tokens.

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Broadcast Notifications

POST /api/v1/broadcasts

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
{
  "title": "string",
  "message": "string",
  "imageUrl": "string",
  "ctaLabel": "string",
  "ctaUrl": "string",
  "channels": [],
  "priority": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/broadcasts

Allowed role/access: Authenticated

Summary: —

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `status` (query, optional)
- `channel` (query, optional)
- `priority` (query, optional)
- `createdFrom` (query, optional)
- `createdTo` (query, optional)
- `scheduledFrom` (query, optional)
- `scheduledTo` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/broadcasts/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/broadcasts/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "title": "string",
  "message": "string",
```

```
  "imageUrl": "string",
  "ctaLabel": "string",
  "ctaUrl": "string",
  "channels": [],
  "priority": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/broadcasts/{id}/targeting

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "mode": "string",
  "roles": [],
  "filters": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/broadcasts/estimate-reach

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
{
  "channels": [],
  "targeting": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/broadcasts/{id}/schedule

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "sendMode": "string",
  "scheduledAt": "string",
  "timezone": "string",
  "isRecurring": true,
  "recurrence": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/broadcasts/{id}/cancel

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "reason": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/broadcasts/{id}/report

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/broadcasts/{id}/recipients

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)
- `page` (query, optional)
- `limit` (query, optional)
- `channel` (query, optional)
- `status` (query, optional)
- `search` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
```

```
  "message": "Request completed successfully"
}
```

Subscription Plans

GET /api/v1/subscription-plans

Allowed role/access: Authenticated

Summary: —

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `status` (query, optional)
- `visibility` (query, optional)
- `billingCycle` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/subscription-plans

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
{
  "name": "string",
  "description": "string",
  "monthlyPrice": 0,
  "yearlyPrice": 0,
  "currency": "USD",
  "visibility": "string",
  "status": "string",
  "isPopular": true,
  "features": "string",
  "limits": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/subscription-plans/stats

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
```

```
  "message": "Request completed successfully"
}
```

GET /api/v1/subscription-plans/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/subscription-plans/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "name": "string",
  "description": "string",
  "monthlyPrice": 0,
  "yearlyPrice": 0,
  "currency": "string",
  "visibility": "string",
  "status": "string",
  "isPopular": true,
  "features": "string",
  "limits": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

DELETE /api/v1/subscription-plans/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/subscription-plans/{id}/status

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "status": "string",
  "reason": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/subscription-plans/{id}/visibility

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "visibility": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/subscription-plans/{id}/analytics

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/plan-features/catalog

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/plan-features

Allowed role/access: Authenticated

Summary: —

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `isActive` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/plan-features

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
{
  "key": "string",
  "label": "string",
  "description": "string",
  "type": "string",
  "isActive": true,
  "sortOrder": 0
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/plan-features/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
```

```
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/plan-features/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "key": "string",
  "label": "string",
  "description": "string",
  "type": "string",
  "isActive": true,
  "sortOrder": 0
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

DELETE /api/v1/plan-features/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Coupons

GET /api/v1/coupons

Allowed role/access: Authenticated

Summary: —

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `search` (query, optional)
- `status` (query, optional)
- `planId` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
```

```
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/coupons

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
{
  "code": "string",
  "description": "string",
  "discountType": "string",
  "discountValue": 0,
  "planIds": [],
  "startsAt": "string",
  "expiresAt": "string",
  "maxRedemptions": 0,
  "isActive": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/coupons/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/coupons/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "code": "string",
  "description": "string",
  "discountType": "string",
  "discountValue": 0,
  "planIds": [],
  "startsAt": "string",
  "expiresAt": "string",
  "maxRedemptions": 0,
  "isActive": true
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

DELETE /api/v1/coupons/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

PATCH /api/v1/coupons/{id}/status

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
{
  "status": "string",
  "reason": "string"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Storage

POST /api/v1/uploads/presigned-url

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
{
  "folder": "string",
  "fileName": "avatar.png",
  "contentType": "image/png",
  "sizeBytes": 1048576,
  "targetAccountId": "target_account_id",
  "giftId": "gift_id"
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

POST /api/v1/uploads/complete

Allowed role/access: Authenticated

Summary: —

Request payload example:

```
{
  "uploadId": "string",
  "sizeBytes": 0
}
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/uploads

Allowed role/access: Authenticated

Summary: —

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `folder` (query, optional)
- `ownerId` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/uploads/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

DELETE /api/v1/uploads/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Audit Logs

GET /api/v1/audit-logs/export

Allowed role/access: Authenticated

Summary: —

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `actorId` (query, optional)
- `targetId` (query, optional)
- `action` (query, optional)
- `targetType` (query, optional)
- `module` (query, optional)
- `from` (query, optional)
- `to` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/audit-logs

Allowed role/access: Authenticated

Summary: —

Parameters:

- `page` (query, optional)
- `limit` (query, optional)
- `actorId` (query, optional)
- `targetId` (query, optional)
- `action` (query, optional)
- `targetType` (query, optional)
- `module` (query, optional)
- `from` (query, optional)
- `to` (query, optional)
- `sortBy` (query, optional)
- `sortOrder` (query, optional)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

GET /api/v1/audit-logs/{id}

Allowed role/access: Authenticated

Summary: —

Parameters:

- `id` (path, required)

Request payload example:

```
None
```

Response example:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```