Gift App Backend — Detailed API Record

Generated: 2026-05-09 08:47 UTC

Base URL: `/api/v1`

All protected APIs use:

```
Authorization: Bearer <accessToken>
```

> Secrets are intentionally omitted. Stripe/AWS/JWT/SMTP secret values are not documented here.

Contents

- Auth
- Customer Marketplace
- Customer Wishlist
- Customer Addresses
- Customer Contacts
- Customer Events
- Customer Event Reminder Settings
- Customer Cart
- Customer Orders
- Payments
- Notifications
- Broadcast Notifications
- Gift Categories
- Gift Management
- Provider Inventory
- Promotional Offers Management
- Provider Promotional Offers
- Provider Management
- User Management
- Admin Staff Management
- Admin Roles / RBAC
- Subscription Plans
- Coupons
- Storage
- Audit Logs
- Login Attempts
- Gift Moderation

Auth

Method	Path	Roles	Summary
DELETE	/auth/account	AUTHENTICATED	
POST	/auth/cancel-deletion	AUTHENTICATED	
PATCH	/auth/change-password	AUTHENTICATED	
POST	/auth/forgot-password	PUBLIC	
POST	/auth/guest/session	PUBLIC	
POST	/auth/login	PUBLIC	
POST	/auth/logout	AUTHENTICATED	
GET	/auth/me	AUTHENTICATED	
POST	/auth/providers/register	PUBLIC	
POST	/auth/refresh	PUBLIC	
POST	/auth/resend-otp	AUTHENTICATED	

Method	Path	Roles	Summary
POST	/auth/reset-password	PUBLIC	
POST	/auth/users/register	PUBLIC	
POST	/auth/verify-email	AUTHENTICATED	
POST	/auth/verify-reset-otp	PUBLIC	

DELETE /auth/account

Allowed role(s): AUTHENTICATED

Swagger tag: Auth

Summary: —

Parameters: None

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /auth/cancel-deletion

Allowed role(s): AUTHENTICATED

Swagger tag: Auth

Summary: —

Parameters: None

Request payload: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /auth/change-password

Allowed role(s): AUTHENTICATED

Swagger tag: Auth

Summary: —

Parameters: None

Request DTO: `ChangePasswordDto`

Request payload example:

```
{
  "currentPassword": "example",
  "newPassword": "example"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /auth/forgot-password

Allowed role(s): PUBLIC

Swagger tag: Auth

Summary: —

Parameters: None

Request DTO: `ForgotPasswordDto`

Request payload example:

```
{
  "email": "user@example.com"
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /auth/guest/session

Allowed role(s): PUBLIC

Swagger tag: Auth

Summary: —

Parameters: None

Request DTO: `GuestSessionDto`

Request payload example:

```
{
  "capabilities": [
    "example"
  ]
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /auth/login

Allowed role(s): PUBLIC

Swagger tag: Auth

Summary: —

Parameters: None

Request DTO: `LoginDto`

Request payload example:

```
{
  "email": "example",
  "password": "example"
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /auth/logout

Allowed role(s): AUTHENTICATED

Swagger tag: Auth

Summary: —

Parameters: None

Request payload: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /auth/me

Allowed role(s): AUTHENTICATED

Swagger tag: Auth

Summary: —

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /auth/providers/register

Allowed role(s): PUBLIC

Swagger tag: Auth

Summary: —

Parameters: None

Request DTO: `RegisterProviderDto`

Request payload example:

```
{
  "email": "example",
  "password": "example",
  "firstName": "example",
  "lastName": "example",
```

```
  "phone": "example",
  "businessName": "example",
  "businessCategoryId": "example",
  "taxId": "example",
  "businessAddress": "example",
  "fulfillmentMethods": [
    "PICKUP"
  ],
  "autoAcceptOrders": true
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /auth/refresh

Allowed role(s): PUBLIC

Swagger tag: Auth

Summary: —

Parameters: None

Request DTO: `RefreshDto`

Request payload example:

```
{
  "refreshToken": "example"
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /auth/resend-otp

Allowed role(s): AUTHENTICATED

Swagger tag: Auth

Summary: —

Parameters: None

Request payload: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /auth/reset-password

Allowed role(s): PUBLIC

Swagger tag: Auth

Summary: —

Parameters: None

Request DTO: `ResetPasswordDto`

Request payload example:

```
{
  "email": "user@example.com",
  "otp": "334018",
  "newPassword": "NewPassword@123"
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /auth/users/register

Allowed role(s): PUBLIC

Swagger tag: Auth

Summary: —

Parameters: None

Request DTO: `RegisterUserDto`

Request payload example:

```
{
  "email": "example",
  "password": "example",
  "firstName": "example",
  "lastName": "example",
  "phone": "example"
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /auth/verify-email

Allowed role(s): AUTHENTICATED

Swagger tag: Auth

Summary: —

Parameters: None

Request DTO: `VerifyEmailDto`

Request payload example:

```
{
  "otp": "example"
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /auth/verify-reset-otp

Allowed role(s): PUBLIC

Swagger tag: Auth

Summary: —

Parameters: None

Request DTO: `VerifyResetOtpDto`

Request payload example:

```
{
  "email": "user@example.com",
  "otp": "334018"
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Customer Marketplace

Method	Path	Roles	Summary
GET	/customer/categories	REGISTERED_USER	List customer marketplace categories
GET	/customer/gifts	REGISTERED_USER	List customer marketplace gifts
GET	/customer/gifts/discounted	REGISTERED_USER	List discounted customer gifts
GET	/customer/gifts/filter-options	REGISTERED_USER	Fetch marketplace gift filter options
GET	/customer/home	REGISTERED_USER	Fetch customer app home
GET	/customer/gifts/{id}	REGISTERED_USER	Fetch customer-safe gift details

GET /customer/categories

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Marketplace

Summary: List customer marketplace categories

Description: REGISTERED_USER only. Returns active categories that have available approved gifts.

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Customer categories fetched successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /customer/gifts

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Marketplace

Summary: List customer marketplace gifts

Description: REGISTERED_USER only. Only approved, published, active, in-stock gifts from approved active providers are returned. Active offers are calculated by the backend.

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `categoryId` (query, optional), `categorySlug` (query, optional), `providerId` (query, optional), `offerOnly` (query, optional), `minPrice` (query, optional), `maxPrice` (query, optional), `minRating` (query, optional), `brand` (query, optional), `deliveryOption` (query, optional), `sortBy` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Customer gifts fetched successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /customer/gifts/discounted

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Marketplace

Summary: List discounted customer gifts

Description: REGISTERED_USER only. Reuses marketplace gift filters with offerOnly=true.

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `categoryId` (query, optional), `categorySlug` (query, optional), `providerId` (query, optional), `offerOnly` (query, optional), `minPrice` (query, optional), `maxPrice` (query, optional), `minRating` (query, optional), `brand` (query, optional), `deliveryOption` (query, optional), `sortBy` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Discounted gifts fetched successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /customer/gifts/filter-options

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Marketplace

Summary: Fetch marketplace gift filter options

Description: REGISTERED_USER only. Brands are derived from approved active provider business names.

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Gift filter options fetched successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /customer/home

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Marketplace

Summary: Fetch customer app home

Description: REGISTERED_USER only. Returns safe marketplace categories, discounted gifts, default address, and upcoming reminder.

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Customer home fetched successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /customer/gifts/{id}

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Marketplace

Summary: Fetch customer-safe gift details

Description: REGISTERED_USER only. Hidden/admin-only gift records are never returned.

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Gift details fetched successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

Customer Wishlist

Method	Path	Roles	Summary
`GET`	`/customer/wishlist`	REGISTERED_USER	List wishlist gifts
`POST`	`/customer/wishlist/{giftId}`	REGISTERED_USER	Add gift to wishlist

Method	Path	Roles	Summary
`DELETE`	`/customer/wishlist/{giftId}`	REGISTERED_USER	Remove gift from wishlist

GET /customer/wishlist

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Wishlist

Summary: List wishlist gifts

Description: REGISTERED_USER only. Returns customer-safe available gifts.

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /customer/wishlist/{giftId}

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Wishlist

Summary: Add gift to wishlist

Description: REGISTERED_USER only. Gift must be active, approved, published, and in stock. Duplicate wishlist entries are ignored.

Parameters: `giftId` (path, required)

Request payload: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

DELETE /customer/wishlist/{giftId}

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Wishlist

Summary: Remove gift from wishlist

Description: REGISTERED_USER only. Removes only the current customer wishlist row.

Parameters: `giftId` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Customer Addresses

Method	Path	Roles	Summary
GET	/customer/addresses	REGISTERED_USER	List customer addresses
POST	/customer/addresses	REGISTERED_USER	Create customer address
GET	/customer/addresses/{id}	REGISTERED_USER	Fetch customer address
PATCH	/customer/addresses/{id}	REGISTERED_USER	Update customer address
DELETE	/customer/addresses/{id}	REGISTERED_USER	Soft-delete customer address
PATCH	/customer/addresses/{id}/default	REGISTERED_USER	Set default customer address

GET /customer/addresses

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Addresses

Summary: List customer addresses

Description: REGISTERED_USER only. Customers can only view their own non-deleted addresses.

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /customer/addresses

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Addresses

Summary: Create customer address

Description: REGISTERED_USER only. Maintains one default address per customer.

Parameters: None

Request DTO: `CreateCustomerAddressDto`

Request payload example:

```
{
  "label": "Home",
  "fullName": "Sarah Khan",
  "phone": "+923001234567",
  "line1": "House 12, Street 4, F-8/2",
  "line2": "Near Centaurus Mall",
  "city": "Islamabad",
  "state": "Islamabad Capital Territory",
  "country": "Pakistan",
  "postalCode": "44000",
  "latitude": 33.6844,
  "longitude": 73.0479,
  "deliveryInstructions": "Leave at reception."
}
```

Example response:

```
{
  "success": true,
  "data": {},
```

```
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /customer/addresses/{id}

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Addresses

Summary: Fetch customer address

Description: REGISTERED_USER only. Address must belong to the current customer.

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /customer/addresses/{id}

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Addresses

Summary: Update customer address

Description: REGISTERED_USER only. Maintains one default address per customer.

Parameters: `id` (path, required)

Request DTO: `UpdateCustomerAddressDto`

Request payload example:

```
{
  "label": "Home",
  "fullName": "Sarah Khan",
  "phone": "+923001234567",
  "line1": "House 12, Street 4, F-8/2",
  "line2": "Near Centaurus Mall",
  "city": "Islamabad",
  "state": "Islamabad Capital Territory",
  "country": "Pakistan",
  "postalCode": "44000",
  "latitude": 33.6844,
  "longitude": 73.0479,
  "deliveryInstructions": "Leave at reception."
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

DELETE /customer/addresses/{id}

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Addresses

Summary: Soft-delete customer address

Description: REGISTERED_USER only. Address is soft deleted and removed from default status.

Parameters: `id` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /customer/addresses/{id}/default

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Addresses

Summary: Set default customer address

Description: REGISTERED_USER only. Clears default flag from all other customer addresses.

Parameters: `id` (path, required)

Request payload: None

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Customer Contacts

Method	Path	Roles	Summary
`GET`	`/customer/contacts`	REGISTERED_USER	List customer contacts
`POST`	`/customer/contacts`	REGISTERED_USER	Create customer contact
`GET`	`/customer/contacts/{id}`	REGISTERED_USER	Fetch customer contact
`PATCH`	`/customer/contacts/{id}`	REGISTERED_USER	Update customer contact
`DELETE`	`/customer/contacts/{id}`	REGISTERED_USER	Soft-delete customer contact

GET /customer/contacts

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Contacts

Summary: List customer contacts

Description: REGISTERED_USER only. Lists only contacts owned by the authenticated customer.

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `relationship` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Contacts fetched successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /customer/contacts

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Contacts

Summary: Create customer contact

Description: REGISTERED_USER only. Creates a personal gift contact owned by the authenticated customer. Requires at least one contact method: phone, email, or address.

Parameters: None

Request DTO: `CreateCustomerContactDto`

Request payload example:

```
{
  "name": "Mary Wilson",
  "relationship": "Mother",
  "phone": "+1234567890",
  "email": "mary@example.com",
  "address": "387 Merdina",
  "likes": "Glasses, makeup, dresses",
  "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/mary.png",
  "birthday": "1990-05-12",
  "notes": "Prefers elegant gifts."
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Contact created successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /customer/contacts/{id}

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Contacts

Summary: Fetch customer contact

Description: REGISTERED_USER only. Contact must belong to the authenticated customer.

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Contact fetched successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /customer/contacts/{id}

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Contacts

Summary: Update customer contact

Description: REGISTERED_USER only. Updates only contacts owned by the authenticated customer.

Parameters: `id` (path, required)

Request DTO: `UpdateCustomerContactDto`

Request payload example:

```
{
  "name": "Mary Wilson",
  "relationship": "Mother",
  "phone": "+1234567890",
  "email": "mary@example.com",
  "address": "387 Merdina",
  "likes": "Glasses, makeup, dresses",
  "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/mary.png",
  "birthday": "1990-05-12",
  "notes": "Prefers elegant gifts."
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

DELETE /customer/contacts/{id}

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Contacts

Summary: Soft-delete customer contact

Description: REGISTERED_USER only. Soft deletes only contacts owned by the authenticated customer.

Parameters: `id` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Customer Events

Method	Path	Roles	Summary
`GET`	`/customer/events`	REGISTERED_USER	List customer events
`POST`	`/customer/events`	REGISTERED_USER	Create customer event
`GET`	`/customer/events/calendar`	REGISTERED_USER	Fetch monthly calendar events
`GET`	`/customer/events/upcoming`	REGISTERED_USER	Fetch upcoming customer events
`GET`	`/customer/events/{id}`	REGISTERED_USER	Fetch customer event details
`PATCH`	`/customer/events/{id}`	REGISTERED_USER	Update customer event
`DELETE`	`/customer/events/{id}`	REGISTERED_USER	Soft-delete customer event

GET /customer/events

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Events

Summary: List customer events

Description: REGISTERED_USER only. Lists only events owned by the authenticated customer.

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `eventType` (query, optional), `fromDate` (query, optional), `toDate` (query, optional), `recipientId` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Events fetched successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /customer/events

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Events

Summary: Create customer event

Description: REGISTERED_USER only. recipientId must belong to the authenticated customer.

Parameters: None

Request DTO: `CreateCustomerEventDto`

Request payload example:

```
{
  "eventType": "BIRTHDAY",
  "title": "Sarah's Birthday",
  "recipientId": "cmf0contactmary001",
  "eventDate": "2026-01-31T00:00:00.000Z",
  "reminderTiming": "ON_THE_DAY",
  "reminderFrequency": "ONE_TIME",
  "customAlertTime": "09:00",
  "channels": [
    "EMAIL",
    "SMS"
  ],
  "notes": "Send a birthday gift.",
  "isActive": true
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Event created successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /customer/events/calendar

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Events

Summary: Fetch monthly calendar events

Description: REGISTERED_USER only. Returns marked dates and own events.

Parameters: `month` (query, required), `year` (query, required), `eventType` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /customer/events/upcoming

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Events

Summary: Fetch upcoming customer events

Description: REGISTERED_USER only. Defaults to 10 events within 30 days.

Parameters: `limit` (query, optional), `daysAhead` (query, optional), `eventType` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /customer/events/{id}

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Events

Summary: Fetch customer event details

Description: REGISTERED_USER only. Event must belong to the authenticated customer.

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /customer/events/{id}

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Events

Summary: Update customer event

Description: REGISTERED_USER only. Event and recipient contact must belong to the authenticated customer.

Parameters: `id` (path, required)

Request DTO: `UpdateCustomerEventDto`

Request payload example:

```
{
  "eventType": "ANNIVERSARY",
  "title": "Sarah's Anniversary",
  "recipientId": "cmf0contactmary001",
  "eventDate": "2026-01-31T00:00:00.000Z",
  "reminderTiming": "THREE_DAYS_BEFORE",
  "reminderFrequency": "YEARLY",
  "customAlertTime": "09:00",
  "channels": [
    "PUSH",
    "EMAIL"
  ],
  "notes": "Send flowers.",
  "isActive": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

DELETE /customer/events/{id}

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Events

Summary: Soft-delete customer event

Description: REGISTERED_USER only. Soft deletes only own event and cancels pending reminder jobs.

Parameters: `id` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Customer Event Reminder Settings

Method	Path	Roles	Summary
GET	/customer/events/{id}/reminder-settings	REGISTERED_USER	Fetch event reminder settings
PATCH	/customer/events/{id}/reminder-settings	REGISTERED_USER	Update event reminder settings

GET /customer/events/{id}/reminder-settings

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Event Reminder Settings

Summary: Fetch event reminder settings

Description: REGISTERED_USER only. Event must belong to the authenticated customer.

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /customer/events/{id}/reminder-settings

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Event Reminder Settings

Summary: Update event reminder settings

Description: REGISTERED_USER only. Event must belong to the authenticated customer.

Parameters: `id` (path, required)

Request DTO: `UpdateReminderSettingsDto`

Request payload example:

```
{
  "reminderFrequency": "YEARLY",
  "reminderTiming": "ONE_DAY_BEFORE",
  "customAlertTime": "09:00",
  "channels": {
    "push": true,
    "email": true,
    "sms": false
  }
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Customer Cart

Method	Path	Roles	Summary
GET	/customer/cart	REGISTERED_USER	Fetch active cart
DELETE	/customer/cart	REGISTERED_USER	Clear active cart
POST	/customer/cart/items	REGISTERED_USER	Add item to cart
		REGISTERED_USER	Update cart item

Method	Path	Roles	Summary
PATCH	/customer/cart/items/{id}		
DELETE	/customer/cart/items/{id}	REGISTERED_USER	Delete cart item

GET /customer/cart

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Cart

Summary: Fetch active cart

Description: REGISTERED_USER only. Totals are backend calculated from price snapshots.

Parameters: None

Example response:

```
{
  "success": true,
  "data": {
    "id": "cmf0cartactive001",
    "items": [
      {
        "id": "cmf0cartitem001",
        "giftId": "cmf0giftroses001",
        "variantId": "cmf0variant50ml001",
        "name": "Perfume",
        "variantName": "50ml",
        "quantity": 1,
        "unitPrice": 34.99,
        "discountAmount": 7,
        "finalUnitPrice": 27.99,
        "lineTotal": 27.99,
        "imageUrl": "https://cdn.example.com/gift-images/perfume.png",
        "deliveryOption": "SAME_DAY",
        "recipient": {
          "contactId": "cmf0contactmary001",
          "name": "Sarah Khan",
          "phone": "+923001234567",
          "addressId": "cmf0addresshome001"
        },
        "giftMessage": "Hope you love this special surprise!",
        "scheduledDeliveryAt": "2026-12-24T10:00:00.000Z"
      }
    ],
    "summary": {
      "subtotal": 34.99,
      "discountTotal": 7,
      "deliveryFee": 0,
      "tax": 0,
      "total": 27.99,
      "currency": "PKR"
    }
  },
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

DELETE /customer/cart

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Cart

Summary: Clear active cart

Description: REGISTERED_USER only. Removes all items from active cart.

Parameters: None

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /customer/cart/items

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Cart

Summary: Add item to cart

Description: REGISTERED_USER only. Backend calculates unit price, active offer discount, final price, subtotal, delivery fee placeholder, and total.

Parameters: None

Request DTO: `AddCartItemDto`

Request payload example:

```
{
  "giftId": "cmf0giftroses001",
  "variantId": "cmf0variant50ml001",
  "quantity": 1,
  "deliveryOption": "SAME_DAY",
  "recipientContactId": "cmf0contactmary001",
  "recipientName": "Sarah Khan",
  "recipientPhone": "+923001234567",
  "recipientAddressId": "cmf0addresshome001",
  "eventId": "cmf0eventbirthday001",
  "giftMessage": "Hope you love this special surprise!",
  "messageMediaUrls": [
    "https://cdn.yourdomain.com/gift-message-media/photo.png"
  ],
  "scheduledDeliveryAt": "2026-12-24T10:00:00.000Z"
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /customer/cart/items/{id}

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Cart

Summary: Update cart item

Description: REGISTERED_USER only. Validates ownership through the active customer cart.

Parameters: `id` (path, required)

Request DTO: `UpdateCartItemDto`

Request payload example:

```
{
  "variantId": "cmf0variant100ml001",
  "quantity": 2,
  "deliveryOption": "SCHEDULED",
  "recipientContactId": "cmf0contactmary001",
  "recipientName": "Sarah Khan",
  "recipientPhone": "+923001234567",
  "recipientAddressId": "cmf0addresshome001",
  "eventId": "cmf0eventbirthday001",
  "giftMessage": "Updated gift note.",
  "messageMediaUrls": [
    "https://cdn.yourdomain.com/gift-message-media/video.mp4"
  ],
  "scheduledDeliveryAt": "2026-12-25T10:00:00.000Z"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

DELETE /customer/cart/items/{id}

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Cart

Summary: Delete cart item

Description: REGISTERED_USER only. Deletes only items in the current customer active cart.

Parameters: `id` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Customer Orders

Method	Path	Roles	Summary
`GET`	`/customer/orders`	REGISTERED_USER	List customer orders
`POST`	`/customer/orders`	REGISTERED_USER	Create order from active cart
`GET`	`/customer/orders/{id}`	REGISTERED_USER	Fetch customer order

GET /customer/orders

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Orders

Summary: List customer orders

Description: REGISTERED_USER only. Returns orders owned by the current customer.

Parameters: `page` (query, optional), `limit` (query, optional), `type` (query, optional), `status` (query, optional), `fromDate` (query, optional), `toDate` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /customer/orders

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Orders

Summary: Create order from active cart

Description: REGISTERED_USER only. Prices are backend-calculated from cart/payment snapshots. STRIPE_CARD requires a successful owned paymentId; COD stays pending; PLACEHOLDER is for development only. Multiple providers are split into provider sub-orders.

Parameters: None

Request DTO: `CreateOrderDto`

Request payload example:

```
{
  "cartId": "cmf0cartactive001",
  "paymentId": "cmf0payment001",
  "deliveryAddressId": "cmf0addresshome001",
  "paymentMethod": "COD"
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /customer/orders/{id}

Allowed role(s): REGISTERED_USER

Swagger tag: Customer Orders

Summary: Fetch customer order

Description: REGISTERED_USER only. Order must belong to the current customer.

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {
    "id": "cmf0order001",
    "orderNumber": "ORD-1760000000000",
    "status": "CONFIRMED",
    "paymentStatus": "SUCCEEDED",
    "paymentMethod": "STRIPE_CARD",
    "recipient": {
      "name": "Sarah Khan",
      "email": null,
      "phone": "+923001234567",
      "avatarUrl": null
    },
    "deliveryDate": "2026-12-24T10:00:00.000Z",
    "occasion": null,
    "giftMessage": "Hope you love this special surprise!",
    "items": [
      {
        "giftId": "cmf0giftroses001",
        "name": "Perfume",
        "variantName": "50ml",
        "quantity": 1,
        "imageUrl": "https://cdn.example.com/gift-images/perfume.png",
        "total": 109.5
      }
    ],
    "summary": {
      "subtotal": 100,
      "deliveryFee": 0,
      "tax": 0,
      "discountTotal": 0,
      "total": 100,
      "currency": "PKR"
    }
  },
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

Payments

Method	Path	Roles	Summary
GET	/customer/money-gifts	REGISTERED_USER	List own money gifts
POST	/customer/money-gifts	REGISTERED_USER	Send payment as gift
GET	/customer/payment-methods	REGISTERED_USER	List supported customer payment methods
POST	/customer/payments/confirm	REGISTERED_USER	Confirm Stripe payment
POST	/customer/payments/create-intent	REGISTERED_USER	Create payment intent from active cart
POST	/payments/stripe/webhook	PUBLIC/WEBHOOK	Stripe webhook endpoint
GET	/customer/money-gifts/{id}	REGISTERED_USER	Fetch own money gift details
GET	/customer/payments/{id}	REGISTERED_USER	Fetch own payment details

GET /customer/money-gifts

Allowed role(s): REGISTERED_USER

Swagger tag: Payments

Summary: List own money gifts

Parameters: None

Example response:

```
{
  "success": true,
  "data": {
    "id": "cmf0moneygift001",
    "amount": 100,
    "currency": "PKR",
    "recipientContactId": "cmf0contactmary001",
    "message": "Hope this helps. Enjoy your day!",
    "messageMediaUrls": [],
    "deliveryDate": "2026-12-24T00:00:00.000Z",
    "repeatAnnually": false,
    "status": "PAYMENT_PENDING"
  },
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /customer/money-gifts

Allowed role(s): REGISTERED_USER

Swagger tag: Payments

Summary: Send payment as gift

Description: Creates a customer-to-recipient money gift record and Stripe PaymentIntent for STRIPE_CARD.

Parameters: None

Request DTO: `CreateMoneyGiftDto`

Request payload example:

```
{
  "amount": 100,
  "currency": "PKR",
  "recipientContactId": "cmf0contactmary001",
  "message": "Hope this helps. Enjoy your day!",
  "messageMediaUrls": [],
  "deliveryDate": "2026-12-24T00:00:00.000Z",
  "repeatAnnually": false,
  "paymentMethod": "STRIPE_CARD"
}
```

Example response:

```
{
  "success": true,
  "data": {
    "id": "cmf0moneygift001",
    "amount": 100,
    "currency": "PKR",
    "recipientContactId": "cmf0contactmary001",
    "message": "Hope this helps. Enjoy your day!",
    "messageMediaUrls": [],
    "deliveryDate": "2026-12-24T00:00:00.000Z",
    "repeatAnnually": false,
    "status": "PAYMENT_PENDING"
  },
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /customer/payment-methods

Allowed role(s): REGISTERED_USER

Swagger tag: Payments

Summary: List supported customer payment methods

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /customer/payments/confirm

Allowed role(s): REGISTERED_USER

Swagger tag: Payments

Summary: Confirm Stripe payment

Description: REGISTERED_USER only. Retrieves Stripe PaymentIntent server-side before updating local payment status.

Parameters: None

Request DTO: `ConfirmPaymentDto`

Request payload example:

```
{
  "paymentId": "cmf0payment001",
  "stripePaymentIntentId": "pi_3Pxxxxxxxxxxxxxxxx"
}
```

Example response:

```
{
  "success": true,
  "data": {
    "paymentId": "cmf0payment001",
    "status": "SUCCEEDED"
  },
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /customer/payments/create-intent

Allowed role(s): REGISTERED_USER

Swagger tag: Payments

Summary: Create payment intent from active cart

Description: REGISTERED_USER only. Amount is calculated from backend cart totals; frontend amount is never accepted.

Parameters: None

Request DTO: `CreatePaymentIntentDto`

Request payload example:

```
{
  "cartId": "cmf0cartactive001",
  "paymentMethod": "STRIPE_CARD"
}
```

Example response:

```
{
  "success": true,
  "data": {
    "paymentId": "cmf0payment001",
    "stripePaymentIntentId": "pi_xxx",
    "clientSecret": "pi_xxx_secret_xxx",
    "publishableKey": "pk_live_or_test",
    "amount": 10950,
    "currency": "PKR"
  },
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /payments/stripe/webhook

Allowed role(s): PUBLIC/WEBHOOK

Swagger tag: Payments

Summary: Stripe webhook endpoint

Description: Verifies Stripe-Signature using the configured webhook secret before processing events.

Parameters: None

Request payload: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /customer/money-gifts/{id}

Allowed role(s): REGISTERED_USER

Swagger tag: Payments

Summary: Fetch own money gift details

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {
    "id": "cmf0moneygift001",
    "amount": 100,
    "currency": "PKR",
    "recipientContactId": "cmf0contactmary001",
    "message": "Hope this helps. Enjoy your day!",
    "messageMediaUrls": [],
    "deliveryDate": "2026-12-24T00:00:00.000Z",
    "repeatAnnually": false,
    "status": "PAYMENT_PENDING"
  },
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /customer/payments/{id}

Allowed role(s): REGISTERED_USER

Swagger tag: Payments

Summary: Fetch own payment details

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

Notifications

Method	Path	Roles	Summary
GET	/notifications	SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER	List notifications
POST	/notifications/device-tokens	SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER	Save device token
GET	/notifications/preferences	SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER	Fetch notification preferences
PATCH	/notifications/preferences	SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER	Update notification preferences
PATCH	/notifications/read-all	SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER	Mark all own notifications as read
GET	/notifications/summary	SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER	Fetch notification summary
DELETE	/notifications/device-tokens/{id}	SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER	Disable device token
POST	/notifications/{id}/action	SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER	Process notification action
PATCH	/notifications/{id}/read	SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER	Mark notification as read

GET /notifications

Allowed role(s): SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER

Swagger tag: Notifications

Summary: List notifications

Description: JWT auth. Returns only notifications belonging to the logged-in account. Supports All, Unread, Birthdays, Deliveries, and New Contacts filters. No group gift notifications are supported.

Parameters: `page` (query, optional), `limit` (query, optional), `filter` (query, optional), `type` (query, optional), `isRead` (query, optional), `groupByDate` (query, optional), `sortOrder` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Notifications fetched successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /notifications/device-tokens

Allowed role(s): SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER

Swagger tag: Notifications

Summary: Save device token

Description: JWT auth. Token belongs only to logged-in account. Duplicate deviceId updates existing record.

Parameters: None

Request DTO: `DeviceTokenDto`

Request payload example:

```
{
  "token": "ExponentPushToken[xxxxxxxxxxxxxxxxxxxxxx]",
  "platform": "IOS",
  "deviceId": "ios-iphone-15-pro-device-id"
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /notifications/preferences

Allowed role(s): SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER

Swagger tag: Notifications

Summary: Fetch notification preferences

Description: JWT auth. Preferences belong only to the logged-in account.

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /notifications/preferences

Allowed role(s): SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER

Swagger tag: Notifications

Summary: Update notification preferences

Description: JWT auth. Push toggle does not delete device tokens. No group gift preference exists.

Parameters: None

Request DTO: `UpdateNotificationPreferencesDto`

Request payload example:

```
{
  "pushEnabled": true,
  "emailEnabled": true,
  "smsEnabled": false,
  "dealUpdatesEnabled": true,
  "birthdayRemindersEnabled": true,
  "deliveryUpdatesEnabled": true,
  "newContactAlertsEnabled": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /notifications/read-all

Allowed role(s): SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER

Swagger tag: Notifications

Summary: Mark all own notifications as read

Description: JWT auth. Marks only notifications belonging to the logged-in account.

Parameters: None

Request payload: None

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /notifications/summary

Allowed role(s): SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER

Swagger tag: Notifications

Summary: Fetch notification summary

Description: JWT auth. Counts only notifications belonging to the logged-in account.

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

DELETE /notifications/device-tokens/{id}

Allowed role(s): SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER

Swagger tag: Notifications

Summary: Disable device token

Description: JWT auth. Users can disable only their own device tokens.

Parameters: `id` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /notifications/{id}/action

Allowed role(s): SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER

Swagger tag: Notifications

Summary: Process notification action

Description: JWT auth. Supports SEND_GIFT, REMIND_ME_LATER, VIEW_ORDER, VIEW_CONTACT. Group gift actions are not supported.

Parameters: `id` (path, required)

Request DTO: `NotificationActionRequestDto`

Request payload example:

```
{
  "action": "SEND_GIFT"
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /notifications/{id}/read

Allowed role(s): SUPER_ADMIN, ADMIN, PROVIDER, REGISTERED_USER

Swagger tag: Notifications

Summary: Mark notification as read

Description: JWT auth. Notification must belong to the logged-in account.

Parameters: `id` (path, required)

Request payload: None

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Broadcast Notifications

Method	Path	Roles	Summary
GET	/broadcasts	SUPER_ADMIN, ADMIN	
POST	/broadcasts	SUPER_ADMIN, ADMIN	
POST	/broadcasts/estimate-reach	SUPER_ADMIN, ADMIN	
GET	/broadcasts/{id}	SUPER_ADMIN, ADMIN	
PATCH	/broadcasts/{id}	SUPER_ADMIN, ADMIN	

Method	Path	Roles	Summary
POST	/broadcasts/{id}/cancel	SUPER_ADMIN, ADMIN	
GET	/broadcasts/{id}/recipients	SUPER_ADMIN, ADMIN	
GET	/broadcasts/{id}/report	SUPER_ADMIN, ADMIN	
PATCH	/broadcasts/{id}/schedule	SUPER_ADMIN, ADMIN	
PATCH	/broadcasts/{id}/targeting	SUPER_ADMIN, ADMIN	

GET /broadcasts

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Broadcast Notifications

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `status` (query, optional), `channel` (query, optional), `priority` (query, optional), `createdFrom` (query, optional), `createdTo` (query, optional), `scheduledFrom` (query, optional), `scheduledTo` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /broadcasts

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Broadcast Notifications

Summary: —

Parameters: None

Request DTO: `CreateBroadcastDto`

Request payload example:

```
{
  "title": "example",
  "message": "example",
  "imageUrl": "example",
  "ctaLabel": "example",
  "ctaUrl": "example",
  "channels": [
    "EMAIL"
  ],
  "priority": "LOW"
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /broadcasts/estimate-reach

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Broadcast Notifications

Summary: —

Parameters: None

Request DTO: `EstimateReachDto`

Request payload example:

```
{
  "channels": [
    "EMAIL"
  ],
  "targeting": {
    "mode": "ALL_USERS",
    "roles": [
      "ADMIN"
    ],
    "filters": {
      "location": "example",
      "onlyVerifiedEmails": true,
      "excludeUnsubscribed": true,
      "excludeSuspended": true
    }
  }
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /broadcasts/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Broadcast Notifications

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /broadcasts/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Broadcast Notifications

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateBroadcastDto`

Request payload example:

```
{
  "title": "example",
  "message": "example",
  "imageUrl": "example",
  "ctaLabel": "example",
  "ctaUrl": "example",
  "channels": [
    "EMAIL"
  ],
  "priority": "LOW"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /broadcasts/{id}/cancel

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Broadcast Notifications

Summary: —

Parameters: `id` (path, required)

Request DTO: `CancelBroadcastDto`

Request payload example:

```
{
  "reason": "example"
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /broadcasts/{id}/recipients

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Broadcast Notifications

Summary: —

Parameters: `id` (path, required), `page` (query, optional), `limit` (query, optional), `channel` (query, optional), `status` (query, optional), `search` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /broadcasts/{id}/report

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Broadcast Notifications

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /broadcasts/{id}/schedule

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Broadcast Notifications

Summary: —

Parameters: `id` (path, required)

Request DTO: `ScheduleBroadcastDto`

Request payload example:

```
{
  "sendMode": "NOW",
  "scheduledAt": "example",
  "timezone": "example",
  "isRecurring": true,
  "recurrence": {}
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /broadcasts/{id}/targeting

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Broadcast Notifications

Summary: —

Parameters: `id` (path, required)

Request DTO: `BroadcastTargetingDto`

Request payload example:

```
{
  "mode": "ALL_USERS",
  "roles": [
    "ADMIN"
  ],
  "filters": {
    "location": "example",
    "onlyVerifiedEmails": true,
    "excludeUnsubscribed": true,
    "excludeSuspended": true
  }
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Gift Categories

Method	Path	Roles	Summary
GET	/gift-categories	SUPER_ADMIN, ADMIN	List gift categories
POST	/gift-categories	SUPER_ADMIN, ADMIN	Create gift category
GET	/gift-categories/lookup	PUBLIC/UNSPECIFIED	Lookup active gift categories
GET	/gift-categories/stats	SUPER_ADMIN, ADMIN	Fetch gift category stats
GET	/gift-categories/{id}	SUPER_ADMIN, ADMIN	Fetch gift category details
PATCH	/gift-categories/{id}	SUPER_ADMIN, ADMIN	Update gift category
DELETE	/gift-categories/{id}	SUPER_ADMIN, ADMIN	Soft-delete gift category

GET /gift-categories

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Categories

Summary: List gift categories

Description: RBAC permission: giftCategories.read. Returns soft-delete-filtered categories with gift counts and category media fields.

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `isActive` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Gift categories fetched successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /gift-categories

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Categories

Summary: Create gift category

Description: RBAC permission: giftCategories.create. Slug is auto-generated and unique. backgroundColor defaults to #F3E8FF; color remains a backward-compatible alias.

Parameters: None

Request DTO: `CreateGiftCategoryDto`

Request payload example:

```
{
  "name": "Perfumes",
  "description": "Premium fragrance gifts.",
  "iconKey": "perfume",
  "backgroundColor": "#E9D5FF",
  "imageUrl": "https://<YOUR_PUBLIC_BUCKET_OR_CDN_URL>/gift-category-images/perfumes.png",
  "sortOrder": 1,
  "isActive": true
}
```

Example response:

```
{
  "success": true,
  "data": {},
```

```
  "message": "Gift category created successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /gift-categories/lookup

Allowed role(s): PUBLIC/UNSPECIFIED

Swagger tag: Gift Categories

Summary: Lookup active gift categories

Description: Public lookup under Gift Categories. Returns active category identifiers and media fields for lightweight selectors.

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Gift category lookup fetched successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /gift-categories/stats

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Categories

Summary: Fetch gift category stats

Description: RBAC permission: giftCategories.read. Returns admin category inventory counters.

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /gift-categories/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Categories

Summary: Fetch gift category details

Description: RBAC permission: giftCategories.read. Includes backgroundColor and imageUrl for customer app design support.

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Gift category details fetched successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /gift-categories/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Categories

Summary: Update gift category

Description: RBAC permission: giftCategories.update. Slug is regenerated when name changes. Soft-deleted categories are not updated.

Parameters: `id` (path, required)

Request DTO: `UpdateGiftCategoryDto`

Request payload example:

```
{
  "backgroundColor": "#F3E8FF",
  "imageUrl": "https://<YOUR_PUBLIC_BUCKET_OR_CDN_URL>/gift-category-images/perfumes.png",
  "isActive": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

DELETE /gift-categories/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Categories

Summary: Soft-delete gift category

Description: RBAC permission: giftCategories.delete. Categories with attached gifts cannot be deleted; delete writes an audit log.

Parameters: `id` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Gift Management

Method	Path	Roles	Summary
GET	/gifts	SUPER_ADMIN, ADMIN	
POST	/gifts	SUPER_ADMIN, ADMIN	
GET	/gifts/export	SUPER_ADMIN, ADMIN	
GET	/gifts/stats	SUPER_ADMIN, ADMIN	
GET	/gifts/{id}	SUPER_ADMIN, ADMIN	
PATCH	/gifts/{id}	SUPER_ADMIN, ADMIN	
DELETE	/gifts/{id}	SUPER_ADMIN, ADMIN	
PATCH	/gifts/{id}/status	SUPER_ADMIN, ADMIN	

GET /gifts

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Management

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `categoryId` (query, optional), `providerId` (query, optional), `status` (query, optional), `moderationStatus` (query, optional), `isPublished` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /gifts

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Management

Summary: —

Parameters: None

Request DTO: `CreateGiftDto`

Request payload example:

```
{
  "name": "Luxury Perfume",
  "description": "Long-lasting premium fragrance.",
  "shortDescription": "Premium fragrance gift.",
  "categoryId": "gift_category_id",
  "providerId": "provider_id",
  "price": 99.99,
  "currency": "PKR",
  "stockQuantity": 50,
  "sku": "PERFUME-001",
  "imageUrls": [
    "https://cdn.yourdomain.com/gift-images/perfume.png"
  ],
  "isPublished": true,
  "isFeatured": false,
  "tags": [
    "perfume",
    "luxury"
  ],
  "moderationStatus": "APPROVED",
  "variants": [
    {
      "name": "30ml",
      "price": 89.99,
      "originalPrice": 119.99,
      "stockQuantity": 10,
      "sku": "PERFUME-30ML",
      "isPopular": false,
      "isDefault": false,
      "sortOrder": 1,
      "isActive": true
    },
    {
      "name": "50ml",
      "price": 129.99,
      "originalPrice": 159.99,
      "stockQuantity": 20,
      "sku": "PERFUME-50ML",
      "isPopular": true,
      "isDefault": true,
      "sortOrder": 2,
      "isActive": true
    }
  ]
}
```

Example response:

```
{
  "success": true,
  "data": {},
```

```
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /gifts/export

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Management

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `categoryId` (query, optional), `providerId` (query, optional), `status` (query, optional), `moderationStatus` (query, optional), `isPublished` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional), `format` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /gifts/stats

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Management

Summary: —

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /gifts/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Management

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /gifts/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateGiftDto`

Request payload example:

```
{
  "name": "Luxury Perfume Updated",
  "replaceVariants": false,
  "variants": [
    {
      "id": "variant_id",
      "name": "50ml",
      "price": 129.99,
      "originalPrice": 159.99,
      "stockQuantity": 20,
      "sku": "PERFUME-50ML",
      "isPopular": true,
      "isDefault": true,
      "sortOrder": 2,
      "isActive": true
    },
    {
      "name": "150ml",
      "price": 249.99,
      "originalPrice": 299.99,
      "stockQuantity": 5,
      "sku": "PERFUME-150ML",
      "isPopular": false,
      "isDefault": false,
      "sortOrder": 4,
      "isActive": true
    }
  ]
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

DELETE /gifts/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Management

Summary: —

Parameters: `id` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /gifts/{id}/status

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateGiftStatusDto`

Request payload example:

```
{
  "status": "ACTIVE",
  "reason": "example"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Provider Inventory

Method	Path	Roles	Summary
GET	/provider/inventory	PROVIDER	
POST	/provider/inventory	PROVIDER	
GET	/provider/inventory/lookup	PROVIDER	
GET	/provider/inventory/stats	PROVIDER	
GET	/provider/inventory/{id}	PROVIDER	
PATCH	/provider/inventory/{id}	PROVIDER	
DELETE	/provider/inventory/{id}	PROVIDER	
PATCH	/provider/inventory/{id}/availability	PROVIDER	

GET /provider/inventory

Allowed role(s): PROVIDER

Swagger tag: Provider Inventory

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `status` (query, optional), `categoryId` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /provider/inventory

Allowed role(s): PROVIDER

Swagger tag: Provider Inventory

Summary: —

Parameters: None

Request DTO: `CreateProviderInventoryItemDto`

Request payload example:

```
{
  "name": "Luxury Perfume",
  "description": "Long-lasting premium fragrance.",
  "shortDescription": "Premium fragrance gift.",
  "categoryId": "gift_category_id",
  "price": 99.99,
  "currency": "PKR",
  "stockQuantity": 50,
  "sku": "PERFUME-001",
  "imageUrls": [
    "https://cdn.yourdomain.com/gift-images/perfume.png"
  ],
  "isAvailable": true,
  "variants": [
    {
      "name": "30ml",
```

```
      "price": 89.99,
      "originalPrice": 119.99,
      "stockQuantity": 10,
      "sku": "PERFUME-30ML",
      "isPopular": false,
      "isDefault": false,
      "sortOrder": 1,
      "isActive": true
    },
    {
      "name": "50ml",
      "price": 129.99,
      "originalPrice": 159.99,
      "stockQuantity": 20,
      "sku": "PERFUME-50ML",
      "isPopular": true,
      "isDefault": true,
      "sortOrder": 2,
      "isActive": true
    }
  ]
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /provider/inventory/lookup

Allowed role(s): PROVIDER

Swagger tag: Provider Inventory

Summary: —

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /provider/inventory/stats

Allowed role(s): PROVIDER

Swagger tag: Provider Inventory

Summary: —

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /provider/inventory/{id}

Allowed role(s): PROVIDER

Swagger tag: Provider Inventory

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /provider/inventory/{id}

Allowed role(s): PROVIDER

Swagger tag: Provider Inventory

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateProviderInventoryItemDto`

Request payload example:

```
{
  "replaceVariants": false,
  "variants": [
    {
      "id": "variant_id",
      "name": "50ml",
      "price": 129.99,
      "originalPrice": 159.99,
      "stockQuantity": 20,
      "sku": "PERFUME-50ML",
      "isPopular": true,
      "isDefault": true,
      "sortOrder": 2,
      "isActive": true
    },
    {
      "name": "150ml",
      "price": 249.99,
      "originalPrice": 299.99,
      "stockQuantity": 5,
      "sku": "PERFUME-150ML",
      "isPopular": false,
      "isDefault": false,
      "sortOrder": 4,
      "isActive": true
    }
  ]
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

DELETE /provider/inventory/{id}

Allowed role(s): PROVIDER

Swagger tag: Provider Inventory

Summary: —

Parameters: `id` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /provider/inventory/{id}/availability

Allowed role(s): PROVIDER

Swagger tag: Provider Inventory

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateProviderAvailabilityDto`

Request payload example:

```
{
  "isAvailable": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Promotional Offers Management

Method	Path	Roles	Summary
GET	/promotional-offers	SUPER_ADMIN, ADMIN	
POST	/promotional-offers	SUPER_ADMIN, ADMIN	
GET	/promotional-offers/export	SUPER_ADMIN, ADMIN	
GET	/promotional-offers/stats	SUPER_ADMIN, ADMIN	
GET	/promotional-offers/{id}	SUPER_ADMIN, ADMIN	
PATCH	/promotional-offers/{id}	SUPER_ADMIN, ADMIN	
DELETE	/promotional-offers/{id}	SUPER_ADMIN, ADMIN	
PATCH	/promotional-offers/{id}/approve	SUPER_ADMIN, ADMIN	
PATCH	/promotional-offers/{id}/reject	SUPER_ADMIN, ADMIN	
PATCH	/promotional-offers/{id}/status	SUPER_ADMIN, ADMIN	

GET /promotional-offers

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Promotional Offers Management

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `status` (query, optional), `itemId` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional), `providerId` (query, optional), `approvalStatus` (query, optional), `discountType` (query, optional), `startFrom` (query, optional), `startTo` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /promotional-offers

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Promotional Offers Management

Summary: —

Parameters: None

Request DTO: `CreateAdminOfferDto`

Request payload example:

```
{
  "itemId": "example",
  "title": "example",
  "description": "example",
  "discountType": "PERCENTAGE",
  "discountValue": 100,
  "startDate": "example",
  "endDate": "example",
  "eligibilityRules": "example",
  "isActive": true,
  "providerId": "example",
  "approvalStatus": "PENDING"
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /promotional-offers/export

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Promotional Offers Management

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `status` (query, optional), `itemId` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional), `providerId` (query, optional), `approvalStatus` (query, optional), `discountType` (query, optional), `startFrom` (query, optional), `startTo` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /promotional-offers/stats

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Promotional Offers Management

Summary: —

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /promotional-offers/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Promotional Offers Management

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /promotional-offers/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Promotional Offers Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdatePromotionalOfferDto`

Request payload example:

```
{
  "title": "example",
  "description": "example",
  "discountType": "PERCENTAGE",
  "discountValue": 100,
  "startDate": "example",
  "endDate": "example",
  "eligibilityRules": "example",
  "isActive": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

DELETE /promotional-offers/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Promotional Offers Management

Summary: —

Parameters: `id` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /promotional-offers/{id}/approve

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Promotional Offers Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `ApproveOfferDto`

Request payload example:

```
{
  "comment": "example",
  "notifyProvider": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /promotional-offers/{id}/reject

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Promotional Offers Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `RejectOfferDto`

Request payload example:

```
{
  "reason": "INVALID_DISCOUNT",
  "comment": "example",
  "notifyProvider": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /promotional-offers/{id}/status

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Promotional Offers Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateOfferStatusDto`

Request payload example:

```
{
  "isActive": true,
  "reason": "example"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Provider Promotional Offers

Method	Path	Roles	Summary
GET	/provider/offers	PROVIDER	
POST	/provider/offers	PROVIDER	

Method	Path	Roles	Summary
GET	/provider/offers/{id}	PROVIDER	
PATCH	/provider/offers/{id}	PROVIDER	
DELETE	/provider/offers/{id}	PROVIDER	
PATCH	/provider/offers/{id}/status	PROVIDER	

GET /provider/offers

Allowed role(s): PROVIDER

Swagger tag: Provider Promotional Offers

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `status` (query, optional), `itemId` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /provider/offers

Allowed role(s): PROVIDER

Swagger tag: Provider Promotional Offers

Summary: —

Parameters: None

Request DTO: `CreateProviderOfferDto`

Request payload example:

```
{
  "itemId": "example",
  "title": "example",
  "description": "example",
  "discountType": "PERCENTAGE",
  "discountValue": 100,
  "startDate": "example",
  "endDate": "example",
  "eligibilityRules": "example",
  "isActive": true
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /provider/offers/{id}

Allowed role(s): PROVIDER

Swagger tag: Provider Promotional Offers

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /provider/offers/{id}

Allowed role(s): PROVIDER

Swagger tag: Provider Promotional Offers

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdatePromotionalOfferDto`

Request payload example:

```
{
  "title": "example",
  "description": "example",
  "discountType": "PERCENTAGE",
  "discountValue": 100,
  "startDate": "example",
  "endDate": "example",
  "eligibilityRules": "example",
  "isActive": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

DELETE /provider/offers/{id}

Allowed role(s): PROVIDER

Swagger tag: Provider Promotional Offers

Summary: —

Parameters: `id` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /provider/offers/{id}/status

Allowed role(s): PROVIDER

Swagger tag: Provider Promotional Offers

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateOfferStatusDto`

Request payload example:

```
{
  "isActive": true,
  "reason": "example"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Provider Management

Method	Path	Roles	Summary
GET	/provider-business-categories	PUBLIC/UNSPECIFIED	
POST	/provider-business-categories	PUBLIC/UNSPECIFIED	
GET	/providers	SUPER_ADMIN, ADMIN	
POST	/providers	SUPER_ADMIN, ADMIN	
GET	/providers/export	SUPER_ADMIN, ADMIN	
GET	/providers/lookup	SUPER_ADMIN, ADMIN	
GET	/providers/stats	SUPER_ADMIN, ADMIN	
GET	/provider-business-categories/{id}	PUBLIC/UNSPECIFIED	
PATCH	/provider-business-categories/{id}	PUBLIC/UNSPECIFIED	
DELETE	/provider-business-categories/{id}	PUBLIC/UNSPECIFIED	
GET	/providers/{id}	SUPER_ADMIN, ADMIN	
PATCH	/providers/{id}	SUPER_ADMIN, ADMIN	
GET	/providers/{id}/activity	SUPER_ADMIN, ADMIN	
PATCH	/providers/{id}/approve	SUPER_ADMIN, ADMIN	
GET	/providers/{id}/items	SUPER_ADMIN, ADMIN	
POST	/providers/{id}/message	SUPER_ADMIN, ADMIN	
PATCH	/providers/{id}/reject	SUPER_ADMIN, ADMIN	
PATCH	/providers/{id}/status	SUPER_ADMIN, ADMIN	
POST	/providers/{id}/suspend	SUPER_ADMIN, ADMIN	
POST	/providers/{id}/unsuspend	SUPER_ADMIN, ADMIN	

GET /provider-business-categories

Allowed role(s): PUBLIC/UNSPECIFIED

Swagger tag: Provider Management

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `isActive` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /provider-business-categories

Allowed role(s): PUBLIC/UNSPECIFIED

Swagger tag: Provider Management

Summary: —

Parameters: None

Request DTO: `CreateProviderBusinessCategoryDto`

Request payload example:

```
{
  "name": "example",
  "description": "example",
  "iconKey": "example",
  "sortOrder": 100,
  "isActive": true
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /providers

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Provider Management

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `status` (query, optional), `approvalStatus` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /providers

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Provider Management

Summary: —

Parameters: None

Request DTO: `CreateProviderDto`

Request payload example:

```
{
  "businessName": "Gifts & Blooms Co. Ltd",
  "email": "contact@giftsandblooms.com",
  "phone": "+15551234567",
  "serviceArea": "New York, USA",
  "headquarters": "New York, USA",
  "documentUrls": [
    "example"
  ],
  "generateTemporaryPassword": true,
  "mustChangePassword": true,
  "approvalStatus": "PENDING",
  "isActive": true
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /providers/export

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Provider Management

Summary: —

Parameters: `search` (query, optional), `status` (query, optional), `approvalStatus` (query, optional), `format` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /providers/lookup

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Provider Management

Summary: —

Parameters: `search` (query, optional), `approvalStatus` (query, optional), `isActive` (query, optional), `limit` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /providers/stats

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Provider Management

Summary: —

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /provider-business-categories/{id}

Allowed role(s): PUBLIC/UNSPECIFIED

Swagger tag: Provider Management

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /provider-business-categories/{id}

Allowed role(s): PUBLIC/UNSPECIFIED

Swagger tag: Provider Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateProviderBusinessCategoryDto`

Request payload example:

```
{
  "name": "example",
  "description": "example",
  "iconKey": "example",
  "sortOrder": 100,
  "isActive": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

DELETE /provider-business-categories/{id}

Allowed role(s): PUBLIC/UNSPECIFIED

Swagger tag: Provider Management

Summary: —

Parameters: `id` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /providers/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Provider Management

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
```

```
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /providers/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Provider Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateProviderDto`

Request payload example:

```
{
  "businessName": "Gifts & Blooms Co. Ltd",
  "phone": "+15551234567",
  "serviceArea": "New York, USA",
  "headquarters": "New York, USA",
  "avatarUrl": "https://<YOUR_PUBLIC_BUCKET_OR_CDN_URL>/provider-logos/logo.png",
  "documentUrls": [
    "example"
  ]
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /providers/{id}/activity

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Provider Management

Summary: —

Parameters: `id` (path, required), `page` (query, optional), `limit` (query, optional), `type` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /providers/{id}/approve

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Provider Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `ApproveProviderDto`

Request payload example:

```
{
  "comment": "Documents verified successfully.",
  "notifyProvider": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /providers/{id}/items

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Provider Management

Summary: —

Parameters: `id` (path, required), `page` (query, optional), `limit` (query, optional), `search` (query, optional), `status` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /providers/{id}/message

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Provider Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `MessageProviderDto`

Request payload example:

```
{
  "subject": "Account update",
  "message": "Please update your business documents.",
  "channel": "EMAIL"
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /providers/{id}/reject

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Provider Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `RejectProviderDto`

Request payload example:

```
{
  "reason": "INCOMPLETE_DOCUMENTS",
  "comment": "Business license document is missing.",
```

```
  "notifyProvider": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /providers/{id}/status

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Provider Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateProviderStatusDto`

Request payload example:

```
{
  "status": "ACTIVE",
  "reason": "POLICY_VIOLATION",
  "comment": "Provider violated platform policy.",
  "notifyProvider": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /providers/{id}/suspend

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Provider Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateProviderStatusDto`

Request payload example:

```
{
  "status": "ACTIVE",
  "reason": "POLICY_VIOLATION",
  "comment": "Provider violated platform policy.",
  "notifyProvider": true
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /providers/{id}/unsuspend

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Provider Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateProviderStatusDto`

Request payload example:

```
{
  "status": "ACTIVE",
  "reason": "POLICY_VIOLATION",
  "comment": "Provider violated platform policy.",
  "notifyProvider": true
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

User Management

Method	Path	Roles	Summary
GET	/users	SUPER_ADMIN, ADMIN	
GET	/users/export	SUPER_ADMIN, ADMIN	
GET	/users/{id}	SUPER_ADMIN, ADMIN	
PATCH	/users/{id}	SUPER_ADMIN, ADMIN	
GET	/users/{id}/activity	SUPER_ADMIN, ADMIN	
POST	/users/{id}/reset-password	SUPER_ADMIN, ADMIN	
GET	/users/{id}/stats	SUPER_ADMIN, ADMIN	
PATCH	/users/{id}/status	SUPER_ADMIN, ADMIN	
POST	/users/{id}/suspend	SUPER_ADMIN, ADMIN	
POST	/users/{id}/unsuspend	SUPER_ADMIN, ADMIN	

GET /users

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: User Management

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `status` (query, optional), `registrationFrom` (query, optional), `registrationTo` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /users/export

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: User Management

Summary: —

Parameters: `search` (query, optional), `status` (query, optional), `registrationFrom` (query, optional), `registrationTo` (query, optional), `format` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /users/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: User Management

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /users/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: User Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateRegisteredUserDto`

Request payload example:

```
{
  "firstName": "Alex",
  "lastName": "Johnson",
  "phone": "+15552345678",
  "avatarUrl": "https://<YOUR_PUBLIC_BUCKET_OR_CDN_URL>/user-avatars/avatar.jpg",
  "location": "New York, USA"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /users/{id}/activity

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: User Management

Summary: —

Parameters: `id` (path, required), `page` (query, optional), `limit` (query, optional), `type` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /users/{id}/reset-password

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: User Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `ResetRegisteredUserPasswordDto`

Request payload example:

```
{
  "sendEmail": true
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /users/{id}/stats

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: User Management

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /users/{id}/status

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: User Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateRegisteredUserStatusDto`

Request payload example:

```
{
  "status": "ACTIVE",
  "reason": "POLICY_VIOLATION",
  "comment": "Suspicious activity detected on this account.",
  "notifyUser": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /users/{id}/suspend

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: User Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `SuspendRegisteredUserDto`

Request payload example:

```
{
  "reason": "POLICY_VIOLATION",
  "comment": "Suspicious account activity.",
  "notifyUser": true
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /users/{id}/unsuspend

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: User Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `UnsuspendRegisteredUserDto`

Request payload example:

```
{
  "comment": "Account reviewed and restored.",
  "notifyUser": true
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Admin Staff Management

Method	Path	Roles	Summary
GET	/admins	SUPER_ADMIN	
POST	/admins	SUPER_ADMIN	Create admin staff user
GET	/admins/{id}	SUPER_ADMIN	
PATCH	/admins/{id}	SUPER_ADMIN	
PATCH	/admins/{id}/active-status	SUPER_ADMIN	
PATCH	/admins/{id}/password	SUPER_ADMIN	

GET /admins

Allowed role(s): SUPER_ADMIN

Swagger tag: Admin Staff Management

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `roleId` (query, optional), `role` (query, optional), `status` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /admins

Allowed role(s): SUPER_ADMIN

Swagger tag: Admin Staff Management

Summary: Create admin staff user

Description: Creates an ADMIN staff user under Super Admin. The roleId field is the AdminRole ID that controls this staff user's permissions. This endpoint cannot create SUPER_ADMIN, REGISTERED_USER, PROVIDER, or GUEST_USER accounts.

Parameters: None

Request payload example:

```
{
  "email": "staff@example.com",
  "temporaryPassword": "Temp@123456",
  "generateTemporaryPassword": false,
  "mustChangePassword": true,
  "firstName": "Operations",
  "lastName": "Staff",
  "phone": "+15550000002",
  "title": "Operations Manager",
  "roleId": "admin_role_id",
  "avatarUrl": "https://cdn.yourdomain.com/admin-avatars/staff.png",
  "isActive": true,
  "sendInviteEmail": true
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /admins/{id}

Allowed role(s): SUPER_ADMIN

Swagger tag: Admin Staff Management

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /admins/{id}

Allowed role(s): SUPER_ADMIN

Swagger tag: Admin Staff Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateAdminDto`

Request payload example:

```
{
  "firstName": "example",
  "lastName": "example",
  "phone": "example",
  "avatarUrl": "example",
  "title": "example",
  "roleId": "example",
  "isActive": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /admins/{id}/active-status

Allowed role(s): SUPER_ADMIN

Swagger tag: Admin Staff Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateAdminActiveStatusDto`

Request payload example:

```
{
  "isActive": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /admins/{id}/password

Allowed role(s): SUPER_ADMIN

Swagger tag: Admin Staff Management

Summary: —

Parameters: `id` (path, required)

Request DTO: `ResetAdminPasswordDto`

Request payload example:

```
{
  "temporaryPassword": "example",
  "generateTemporaryPassword": true,
  "mustChangePassword": true,
  "sendEmail": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Admin Roles / RBAC

Method	Path	Roles	Summary
GET	/admin-roles	SUPER_ADMIN	
POST	/admin-roles	SUPER_ADMIN	
GET	/permissions/catalog	SUPER_ADMIN	
GET	/admin-roles/{id}	SUPER_ADMIN	
PATCH	/admin-roles/{id}	SUPER_ADMIN	
DELETE	/admin-roles/{id}	SUPER_ADMIN	
PATCH	/admin-roles/{id}/permissions	SUPER_ADMIN	

GET /admin-roles

Allowed role(s): SUPER_ADMIN

Swagger tag: Admin Roles / RBAC

Summary: —

Description: Admin Roles / RBAC manages permission roles for ADMIN staff users only. SUPER_ADMIN has full immutable access and does not depend on AdminRole permissions.

Parameters: `search` (query, optional), `isSystem` (query, optional), `isActive` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /admin-roles

Allowed role(s): SUPER_ADMIN

Swagger tag: Admin Roles / RBAC

Summary: —

Parameters: None

Request DTO: `CreateAdminRoleDto`

Request payload example:

```
{
  "name": "example",
  "description": "example",
  "permissions": {}
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /permissions/catalog

Allowed role(s): SUPER_ADMIN

Swagger tag: Admin Roles / RBAC

Summary: —

Description: Read-only list of backend-supported permission keys that can be assigned to admin roles.

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /admin-roles/{id}

Allowed role(s): SUPER_ADMIN

Swagger tag: Admin Roles / RBAC

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /admin-roles/{id}

Allowed role(s): SUPER_ADMIN

Swagger tag: Admin Roles / RBAC

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateAdminRoleDto`

Request payload example:

```
{
  "name": "example",
  "description": "example",
  "isActive": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

DELETE /admin-roles/{id}

Allowed role(s): SUPER_ADMIN

Swagger tag: Admin Roles / RBAC

Summary: —

Parameters: `id` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /admin-roles/{id}/permissions

Allowed role(s): SUPER_ADMIN

Swagger tag: Admin Roles / RBAC

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateRolePermissionsDto`

Request payload example:

```
{
  "permissions": {}
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Subscription Plans

Method	Path	Roles	Summary
GET	/plan-features	SUPER_ADMIN, ADMIN	
POST	/plan-features	SUPER_ADMIN, ADMIN	
GET	/plan-features/catalog	SUPER_ADMIN, ADMIN	
GET	/subscription-plans	SUPER_ADMIN, ADMIN	
POST	/subscription-plans	SUPER_ADMIN, ADMIN	
GET	/subscription-plans/stats	SUPER_ADMIN, ADMIN	
GET	/plan-features/{id}	SUPER_ADMIN, ADMIN	
PATCH	/plan-features/{id}	SUPER_ADMIN, ADMIN	
DELETE	/plan-features/{id}	SUPER_ADMIN, ADMIN	
GET	/subscription-plans/{id}	SUPER_ADMIN, ADMIN	

Method	Path	Roles	Summary
PATCH	/subscription-plans/{id}	SUPER_ADMIN, ADMIN	
DELETE	/subscription-plans/{id}	SUPER_ADMIN, ADMIN	
GET	/subscription-plans/{id}/analytics	SUPER_ADMIN, ADMIN	
PATCH	/subscription-plans/{id}/status	SUPER_ADMIN, ADMIN	
PATCH	/subscription-plans/{id}/visibility	SUPER_ADMIN, ADMIN	

GET /plan-features

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Subscription Plans

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `isActive` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /plan-features

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Subscription Plans

Summary: —

Parameters: None

Request DTO: `CreatePlanFeatureDto`

Request payload example:

```
{
  "key": "example",
  "label": "example",
  "description": "example",
  "type": "BOOLEAN",
  "isActive": true,
  "sortOrder": 100
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /plan-features/catalog

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Subscription Plans

Summary: —

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /subscription-plans

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Subscription Plans

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `status` (query, optional), `visibility` (query, optional), `billingCycle` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /subscription-plans

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Subscription Plans

Summary: —

Parameters: None

Request DTO: `CreateSubscriptionPlanDto`

Request payload example:

```
{
  "name": "example",
  "description": "example",
  "monthlyPrice": 100,
  "yearlyPrice": 100,
  "currency": "USD",
  "visibility": "PUBLIC",
  "status": "ACTIVE",
  "isPopular": true,
  "features": {},
  "limits": {
    "maxGiftsPerMonth": 100,
    "maxGroupGiftingEvents": 100,
    "maxTeamMembers": 100,
    "storageGb": 100
  }
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /subscription-plans/stats

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Subscription Plans

Summary: —

Parameters: None

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /plan-features/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Subscription Plans

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /plan-features/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Subscription Plans

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdatePlanFeatureDto`

Request payload example:

```
{
  "key": "example",
  "label": "example",
  "description": "example",
  "type": "BOOLEAN",
  "isActive": true,
  "sortOrder": 100
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

DELETE /plan-features/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Subscription Plans

Summary: —

Parameters: `id` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /subscription-plans/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Subscription Plans

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /subscription-plans/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Subscription Plans

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateSubscriptionPlanDto`

Request payload example:

```
{
  "name": "example",
  "description": "example",
  "monthlyPrice": 100,
  "yearlyPrice": 100,
  "currency": "example",
  "visibility": "PUBLIC",
  "status": "ACTIVE",
  "isPopular": true,
  "features": {},
  "limits": {
    "maxGiftsPerMonth": 100,
    "maxGroupGiftingEvents": 100,
    "maxTeamMembers": 100,
    "storageGb": 100
  }
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

DELETE /subscription-plans/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Subscription Plans

Summary: —

Parameters: `id` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /subscription-plans/{id}/analytics

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Subscription Plans

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /subscription-plans/{id}/status

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Subscription Plans

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdatePlanStatusDto`

Request payload example:

```
{
  "status": "ACTIVE",
  "reason": "example"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /subscription-plans/{id}/visibility

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Subscription Plans

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdatePlanVisibilityDto`

Request payload example:

```
{
  "visibility": "PUBLIC"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Coupons

Method	Path	Roles	Summary
GET	/coupons	SUPER_ADMIN, ADMIN	
POST	/coupons	SUPER_ADMIN, ADMIN	
GET	/coupons/{id}	SUPER_ADMIN, ADMIN	
PATCH	/coupons/{id}	SUPER_ADMIN, ADMIN	
DELETE	/coupons/{id}	SUPER_ADMIN, ADMIN	
PATCH	/coupons/{id}/status	SUPER_ADMIN, ADMIN	

GET /coupons

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Coupons

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `search` (query, optional), `status` (query, optional), `planId` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /coupons

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Coupons

Summary: —

Parameters: None

Request DTO: `CreateCouponDto`

Request payload example:

```
{
  "code": "example",
  "description": "example",
  "discountType": "PERCENTAGE",
  "discountValue": 100,
  "planIds": [
    "example"
  ],
  "startsAt": "example",
  "expiresAt": "example",
  "maxRedemptions": 100,
  "isActive": true
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /coupons/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Coupons

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /coupons/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Coupons

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateCouponDto`

Request payload example:

```
{
  "code": "example",
  "description": "example",
  "discountType": "PERCENTAGE",
  "discountValue": 100,
  "planIds": [
    "example"
  ],
  "startsAt": "example",
  "expiresAt": "example",
  "maxRedemptions": 100,
  "isActive": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

DELETE /coupons/{id}

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Coupons

Summary: —

Parameters: `id` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /coupons/{id}/status

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Coupons

Summary: —

Parameters: `id` (path, required)

Request DTO: `UpdateCouponStatusDto`

Request payload example:

```
{
  "status": "ACTIVE",
  "reason": "example"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Storage

Method	Path	Roles	Summary
GET	/uploads	SUPER_ADMIN, ADMIN, REGISTERED_USER, PROVIDER	
POST	/uploads/complete	SUPER_ADMIN, ADMIN, REGISTERED_USER, PROVIDER	
POST	/uploads/presigned-url	SUPER_ADMIN, ADMIN, REGISTERED_USER, PROVIDER	
GET	/uploads/{id}	SUPER_ADMIN, ADMIN, REGISTERED_USER, PROVIDER	
DELETE	/uploads/{id}	SUPER_ADMIN, ADMIN, REGISTERED_USER, PROVIDER	

GET /uploads

Allowed role(s): SUPER_ADMIN, ADMIN, REGISTERED_USER, PROVIDER

Swagger tag: Storage

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `folder` (query, optional), `ownerId` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

POST /uploads/complete

Allowed role(s): SUPER_ADMIN, ADMIN, REGISTERED_USER, PROVIDER

Swagger tag: Storage

Summary: —

Parameters: None

Request DTO: `CompleteUploadDto`

Request payload example:

```
{
  "uploadId": "example",
  "sizeBytes": 100
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

POST /uploads/presigned-url

Allowed role(s): SUPER_ADMIN, ADMIN, REGISTERED_USER, PROVIDER

Swagger tag: Storage

Summary: —

Parameters: None

Request DTO: `CreatePresignedUploadDto`

Request payload example:

```
{
  "folder": "admin-avatars",
  "fileName": "avatar.png",
  "contentType": "image/png",
  "sizeBytes": 1048576,
  "targetAccountId": "target_account_id",
  "giftId": "gift_id"
}
```

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

GET /uploads/{id}

Allowed role(s): SUPER_ADMIN, ADMIN, REGISTERED_USER, PROVIDER

Swagger tag: Storage

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

DELETE /uploads/{id}

Allowed role(s): SUPER_ADMIN, ADMIN, REGISTERED_USER, PROVIDER

Swagger tag: Storage

Summary: —

Parameters: `id` (path, required)

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

Audit Logs

Method	Path	Roles	Summary
`GET`	`/audit-logs`	SUPER_ADMIN	
`GET`	`/audit-logs/export`	SUPER_ADMIN	
`GET`	`/audit-logs/{id}`	SUPER_ADMIN	

GET /audit-logs

Allowed role(s): SUPER_ADMIN

Swagger tag: Audit Logs

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `actorId` (query, optional), `targetId` (query, optional), `action` (query, optional), `targetType` (query, optional), `module` (query, optional), `from` (query, optional), `to` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /audit-logs/export

Allowed role(s): SUPER_ADMIN

Swagger tag: Audit Logs

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `actorId` (query, optional), `targetId` (query, optional), `action` (query, optional), `targetType` (query, optional), `module` (query, optional), `from` (query, optional), `to` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /audit-logs/{id}

Allowed role(s): SUPER_ADMIN

Swagger tag: Audit Logs

Summary: —

Parameters: `id` (path, required)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

Login Attempts

Method	Path	Roles	Summary
GET	/login-attempts	SUPER_ADMIN, ADMIN	
GET	/login-attempts/export	SUPER_ADMIN, ADMIN	
GET	/login-attempts/stats	SUPER_ADMIN, ADMIN	

GET /login-attempts

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Login Attempts

Summary: —

Parameters: `email` (query, optional), `status` (query, optional), `role` (query, optional), `page` (query, optional), `limit` (query, optional), `userId` (query, optional), `from` (query, optional), `to` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /login-attempts/export

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Login Attempts

Summary: —

Parameters: `email` (query, optional), `status` (query, optional), `role` (query, optional), `page` (query, optional), `limit` (query, optional), `userId` (query, optional), `from` (query, optional), `to` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

GET /login-attempts/stats

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Login Attempts

Summary: —

Parameters: `email` (query, optional), `status` (query, optional), `role` (query, optional), `page` (query, optional), `limit` (query, optional), `userId` (query, optional), `from` (query, optional), `to` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

Gift Moderation

Method	Path	Roles	Summary
GET	/gift-moderation	SUPER_ADMIN, ADMIN	
PATCH	/gift-moderation/{id}/approve	SUPER_ADMIN, ADMIN	
PATCH	/gift-moderation/{id}/flag	SUPER_ADMIN, ADMIN	
PATCH	/gift-moderation/{id}/reject	SUPER_ADMIN, ADMIN	

GET /gift-moderation

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Moderation

Summary: —

Parameters: `page` (query, optional), `limit` (query, optional), `status` (query, optional), `search` (query, optional), `providerId` (query, optional), `view` (query, optional), `sortBy` (query, optional), `sortOrder` (query, optional)

Example response:

```
{
  "success": true,
  "data": {},
  "message": "Request completed successfully"
}
```

Common failure responses: `401` missing/invalid token, `403` role/permission denied, `404` missing owned record when applicable.

PATCH /gift-moderation/{id}/approve

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Moderation

Summary: —

Parameters: `id` (path, required)

Request DTO: `ApproveGiftDto`

Request payload example:

```
{
  "comment": "example",
  "publishNow": true,
  "notifyProvider": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /gift-moderation/{id}/flag

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Moderation

Summary: —

Parameters: `id` (path, required)

Request DTO: `FlagGiftDto`

Request payload example:

```
{
  "reason": "NEEDS_MANUAL_REVIEW",
  "comment": "example"
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.

PATCH /gift-moderation/{id}/reject

Allowed role(s): SUPER_ADMIN, ADMIN

Swagger tag: Gift Moderation

Summary: —

Parameters: `id` (path, required)

Request DTO: `RejectGiftDto`

Request payload example:

```
{
  "reason": "INCOMPLETE_INFORMATION",
  "comment": "example",
  "notifyProvider": true
}
```

Common failure responses: `400` validation/business rule failure, `401` missing/invalid token, `403` role/permission denied, `404` missing owned record.