

Generated from docs/generated/openapi.json  
Generated at: 2026-05-20 05:50 UTC  
Do not edit manually.  
Run: npm run docs:generate

# Gift App Backend — Full API Reference

Generated: 2026-05-20 05:50 UTC

This document is generated from the current OpenAPI for the Gift App backend. For each API, it includes allowed role/access, request payloads for write endpoints, and response bodies for read/write endpoints.

## 01 Auth

**POST** /api/v1/auth/users/register

**Summary:** Create Auth Users Register

**Allowed role/access:** PUBLIC

**Notes:** Access: PUBLIC. PUBLIC.

**Request payload(s):**

payload

```
{
  "email": "<string>",
  "password": "<string>",
  "firstName": "<string>",
  "lastName": "<string>",
  "phone": "<string>",
  "referralCode": "SARAH-M"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/auth/providers/register

**Summary:** Create Auth Providers Register

**Allowed role/access:** PUBLIC

**Notes:** Access: PUBLIC. PUBLIC.

**Request payload(s):**

payload

```
{
  "email": "<string>",
  "password": "<string>",
  "firstName": "<string>",
  "lastName": "<string>",
  "phone": "<string>",
  "referralCode": "SARAH-M",
  "businessName": "<string>",
  "businessCategoryId": "<string>",
}
```

```
"taxId": "<string>",
"businessAddress": "<string>",
"fulfillmentMethods": [
  "PICKUP"
],
"autoAcceptOrders": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/auth/guest/session

**Summary:** Create guest browsing session

**Allowed role/access:** PUBLIC

**Notes:** Access: PUBLIC. PUBLIC. Optional metadata-only request body. Guest capabilities are server-issued from Admin Guest Access Settings. Client-provided capabilities are ignored and will be removed in a future version. Guest sessions are for limited browsing and onboarding access only. PUBLIC. Request body is optional metadata only. Guest capabilities are server-issued from Admin Guest Access Settings. Client-provided capabilities are ignored and will be removed in a future version. Guest sessions are for limited browsing and onboarding access only.

**Request payload(s):**

metadata

```
{
  "deviceId": "optional-device-id",
  "platform": "WEB",
  "appVersion": "1.0.0",
  "locale": "en",
  "timezone": "Asia/Karachi",
  "referrer": "landing-page"
}
```

empty

```
{}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "guestSessionId": "guest_session_id",
    "accessToken": "guest_jwt",
    "tokenType": "Bearer",
    "role": "GUEST_USER",
    "capabilities": [
      "VIEW_ONBOARDING",
      "BROWSE_MARKETPLACE",
      "VIEW_GIFT_DETAILS",
      "VIEW_MARKETPLACE_FILTERS",
      "VIEW_DISCOUNTED_GIFTS"
    ],
    "expiresAt": "2026-05-18T12:00:00.000Z",
    "guestAccess": {
      "allowMarketplaceBrowsing": true,

```

```
    "allowMarketplaceHome": true,  
    "allowGiftDetails": true,  
    "allowDiscountedGifts": true,  
    "allowFilterOptions": true,  
    "allowWishlist": false,  
    "allowCart": false,  
    "allowCheckout": false  
  }  
},  
"message": "Guest session created successfully."  
}
```

**POST** /api/v1/auth/login

**Summary:** Create Auth Login

**Allowed role/access:** PUBLIC

**Notes:** Access: PUBLIC. PUBLIC.

**Request payload(s):**

payload

```
{  
  "email": "<string>",  
  "password": "<string>"  
}
```

**Response body:**

```
{  
  "success": false,  
  "error": {  
    "code": "EMAIL_NOT_VERIFIED",  
    "message": "Please verify your email before login",  
    "user_verified": 0  
  },  
  "meta": {  
    "statusCode": 403,  
    "timestamp": "2026-05-18T11:04:05.524Z"  
  }  
}
```

**POST** /api/v1/auth/refresh

**Summary:** Create Auth Refresh

**Allowed role/access:** PUBLIC

**Notes:** Access: PUBLIC. PUBLIC.

**Request payload(s):**

payload

```
{  
  "refreshToken": "<string>"  
}
```

**Response body:**

```
{  
  "success": true,  
  "data": "<response returned by endpoint>,"  
}
```

```
"message": "Request completed successfully."
}
```

**POST** /api/v1/auth/logout

**Summary:** Create Auth Logout

**Allowed role/access:** Authenticated

**Notes:** Access: Authenticated. Authenticated JWT required.

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/auth/verify-email

**Summary:** Create Auth Verify Email

**Allowed role/access:** Authenticated

**Notes:** Access: Authenticated. Authenticated JWT required.

**Request payload(s):**

payload

```
{
  "otp": "<string>"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/auth/resend-otp

**Summary:** Create Auth Resend Otp

**Allowed role/access:** Authenticated

**Notes:** Access: Authenticated. Authenticated JWT required.

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```

```
"message": "Request completed successfully."
}
```

**POST** /api/v1/auth/resend-verification-email

**Summary:** Resend verification email for unverified login

**Allowed role/access:** PUBLIC

**Notes:** Access: PUBLIC. PUBLIC. Public endpoint. Always returns the same success envelope to avoid user enumeration. Sends verification OTP only when the email exists and is not verified.

**Request payload(s):**

payload

```
{
  "email": "user@example.com"
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "delivery": "OTP_SENT_IF_ELIGIBLE",
    "nextStep": "Use the 6-digit verification OTP to complete email verification."
  },
  "message": "If the email is registered and unverified, a 6-digit verification OTP has been sent."
}
```

**POST** /api/v1/auth/forgot-password

**Summary:** Create Auth Forgot Password

**Allowed role/access:** PUBLIC

**Notes:** Access: PUBLIC. PUBLIC.

**Request payload(s):**

payload

```
{
  "email": "user@example.com"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/auth/verify-reset-otp

**Summary:** Verify public OTP for password reset or unverified email flow

**Allowed role/access:** PUBLIC

**Notes:** Access: PUBLIC. PUBLIC. PUBLIC. For verified accounts this validates password reset OTP. For unverified accounts this accepts the latest verification OTP and marks the email as verified.

**Request payload(s):**

payload

```
{
  "email": "user@example.com",
  "otp": "334018"
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "purpose": "EMAIL_VERIFICATION",
    "emailVerified": true
  },
  "message": "Email verified successfully"
}
```

**POST** /api/v1/auth/reset-password

**Summary:** Create Auth Reset Password

**Allowed role/access:** PUBLIC

**Notes:** Access: PUBLIC. PUBLIC.

**Request payload(s):**

payload

```
{
  "email": "user@example.com",
  "otp": "334018",
  "newPassword": "NewPassword@123"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/auth/change-password

**Summary:** Update Auth Change Password

**Allowed role/access:** Authenticated

**Notes:** Access: Authenticated. Authenticated JWT required.

**Request payload(s):**

payload

```
{
  "currentPassword": "<string>",
  "newPassword": "<string>"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```

```
{
  "message": "Request completed successfully."
}
```

**GET** /api/v1/auth/me

**Summary:** List Auth Me

**Allowed role/access:** Authenticated

**Notes:** Access: Authenticated. Authenticated JWT required.

**Response body:**

```
{
  "success": true,
  "data": {
    "uid": "user_id",
    "role": "REGISTERED_USER",
    "email": "jane@example.com",
    "firstName": "Jane",
    "lastName": "Doe",
    "phone": "+923001234567",
    "avatarUrl": "https://cdn.yourdomain.com/user-avatars/jane.png",
    "permissions": null
  },
  "message": "Profile fetched successfully."
}
```

**PATCH** /api/v1/auth/me

**Summary:** Update Auth Me

**Allowed role/access:** Authenticated

**Notes:** Access: Authenticated. Authenticated JWT required.

**Request payload(s):**

payload

```
{
  "firstName": "Julian",
  "lastName": "Rivers",
  "phone": "+15551234567",
  "avatarUrl": "https://cdn.yourdomain.com/provider-avatars/julian.png"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/auth/sessions

**Summary:** List Auth Sessions

**Allowed role/access:** Authenticated

**Notes:** Access: Authenticated. Authenticated JWT required.

**Response body:**

```
{
  "success": true,
  "data": [
```

```
{
  "id": "session_id",
  "deviceName": "Chrome on Mac",
  "location": "Lahore, PK",
  "ipAddress": "203.0.113.10",
  "isCurrent": true,
  "lastActiveAt": "2026-04-08T11:45:00.000Z"
},
{
  "message": "Active sessions fetched successfully."
}
```

**POST** /api/v1/auth/sessions/logout-all

**Summary:** Create Auth Sessions Logout All

**Allowed role/access:** Authenticated

**Notes:** Access: Authenticated. Authenticated JWT required.

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/auth/sessions/{id}

**Summary:** Delete Auth Sessions

**Allowed role/access:** Authenticated

**Notes:** Access: Authenticated. Authenticated JWT required.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/auth/account

**Summary:** Delete Auth Account

**Allowed role/access:** Authenticated

**Notes:** Access: Authenticated. Authenticated JWT required.

**Request payload(s):**



payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/auth/cancel-deletion

**Summary:** Create Auth Cancel Deletion

**Allowed role/access:** Authenticated

**Notes:** Access: Authenticated. Authenticated JWT required.

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 01 Auth - Login Attempts

**GET** /api/v1/login-attempts/stats

**Summary:** List Login Attempts Stats

**Allowed role/access:** SUPER\_ADMIN or ADMIN with loginAttempts.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with loginAttempts.read. SUPER\_ADMIN or ADMIN with loginAttempts.read permission.

**Parameters:**

- email (query, optional, string)
- status (query, optional, string)
- role (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)
- userId (query, optional, string)
- from (query, optional, string)
- to (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/login-attempts/export

**Summary:** List Login Attempts Export

**Allowed role/access:** SUPER\_ADMIN or ADMIN with loginAttempts.export

**Notes:** Access: SUPER\_ADMIN or ADMIN with loginAttempts.export. SUPER\_ADMIN or ADMIN with loginAttempts.export permission.

**Parameters:**

- email (query, optional, string)
- status (query, optional, string)
- role (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)
- userId (query, optional, string)
- from (query, optional, string)
- to (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/login-attempts

**Summary:** List Login Attempts

**Allowed role/access:** SUPER\_ADMIN or ADMIN with loginAttempts.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with loginAttempts.read. SUPER\_ADMIN or ADMIN with loginAttempts.read permission.

**Parameters:**

- email (query, optional, string)
- status (query, optional, string)
- role (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)
- userId (query, optional, string)
- from (query, optional, string)
- to (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Staff Management

**GET** /api/v1/admins

**Summary:** List admin staff users

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Admin staff management is controlled by Super Admin only. SUPER\_ADMIN only. Returns User.role = ADMIN staff accounts only; SUPER\_ADMIN accounts are intentionally excluded.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- roleId (query, optional, string)
- role (query, optional, string)
- status (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "admin_id",
      "firstName": "Operations",
      "lastName": "Staff",
      "fullName": "Operations Staff",
      "email": "staff@example.com",
      "phone": "+15550000002",
      "role": {
        "id": "admin_role_id",
        "name": "Gift Manager",
        "slug": "gift-manager"
      },
      "isActive": true,
      "isVerified": true,
      "createdAt": "2026-05-09T10:00:00.000Z",
      "lastLoginAt": null
    }
  ]
}
```

```
],
"meta": {
  "page": 1,
  "limit": 10,
  "total": 1,
  "totalPages": 1
},
"message": "Admins fetched successfully"
}
```

**POST** /api/v1/admins

**Summary:** Create admin staff user

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Creates ADMIN staff users only. Creates an ADMIN staff user under Super Admin. The roleId field is the AdminRole ID that controls this staff user's permissions. This endpoint cannot create SUPER\_ADMIN, REGISTERED\_USER, PROVIDER, or GUEST\_USER accounts.

**Request payload(s):**

payload

```
{
  "email": "staff@example.com",
  "temporaryPassword": "Temp@123456",
  "generateTemporaryPassword": false,
  "mustChangePassword": true,
  "firstName": "Operations",
  "lastName": "Staff",
  "phone": "+15550000002",
  "title": "Operations Manager",
  "roleId": "admin_role_id",
  "avatarUrl": "https://cdn.yourdomain.com/admin-avatars/staff.png",
  "isActive": true,
  "sendInviteEmail": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admins/{id}

**Summary:** Fetch Admins details

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Fetches ADMIN staff details.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/admins/{id}

**Summary:** Update Admins

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Updates ADMIN staff account details.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "email": "staff.updated@example.com",
  "firstName": "<string>",
  "lastName": "<string>",
  "phone": "<string>",
  "avatarUrl": "<string>",
  "title": "<string>",
  "roleId": "<string>",
  "isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/admins/{id}

**Summary:** Permanently delete admin staff user

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Permanently deletes an ADMIN staff account. DANGER: This endpoint permanently deletes an ADMIN staff account from the database. This is not a soft delete. Use only from Super Admin danger zone screens. SUPER\_ADMIN accounts and self-delete are blocked.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": {
    "deletedAdminId": "admin_id"
  },
  "message": "Admin staff user permanently deleted successfully."
}
```

**PATCH** /api/v1/admins/{id}/active-status

**Summary:** Update Admins Active Status

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Updates ADMIN staff active status.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/admins/{id}/password

**Summary:** Update Admins Password

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Changes ADMIN staff password from dashboard.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "temporaryPassword": "<string>",
  "generateTemporaryPassword": true,
  "mustChangePassword": true,
  "sendEmail": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Roles & Permissions

**GET** /api/v1/admin-roles

**Summary:** List Admin Roles

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Only SUPER\_ADMIN can manage staff roles and permissions. Admin Roles / RBAC manages permission roles for ADMIN staff users only. SUPER\_ADMIN has full immutable access and does not depend on AdminRole permissions.

**Parameters:**

- search (query, optional, string)
- isSystem (query, optional, boolean)
- isActive (query, optional, boolean)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin-roles**Summary:** Create Admin Roles**Allowed role/access:** SUPER\_ADMIN**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. ADMIN staff cannot create roles.**Request payload(s):**

payload

```
{
  "name": "<string>",
  "description": "<string>",
  "permissions": {}
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin-roles/{id}**Summary:** Fetch Admin Roles details**Allowed role/access:** SUPER\_ADMIN**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. ADMIN staff cannot view role details.**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/admin-roles/{id}**Summary:** Update Admin Roles**Allowed role/access:** SUPER\_ADMIN**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. ADMIN staff cannot update roles.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "name": "<string>",
  "description": "<string>",
  "isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/admin-roles/{id}

**Summary:** Delete Admin Roles

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. ADMIN staff cannot delete roles.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/admin-roles/{id}/permissions

**Summary:** Update Admin Roles Permissions

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. ADMIN staff cannot update role permissions.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "permissions": {}
}
```

**Response body:**



```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/permissions/catalog

**Summary:** List Permissions Catalog

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Read-only backend permission catalog. Read-only list of backend-supported permission keys that can be assigned to admin roles.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - User Management

**GET** /api/v1/users/export

**Summary:** List Users Export

**Allowed role/access:** SUPER\_ADMIN or ADMIN with users.export

**Notes:** Access: SUPER\_ADMIN or ADMIN with users.export. SUPER\_ADMIN or ADMIN with users.export permission.

**Parameters:**

- search (query, optional, string)
- status (query, optional, string)
- registrationFrom (query, optional, string)
- registrationTo (query, optional, string)
- format (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/users

**Summary:** List registered users

**Allowed role/access:** SUPER\_ADMIN or ADMIN with users.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with users.read. SUPER\_ADMIN or ADMIN with users.read permission. SUPER\_ADMIN/ADMIN with users.read permission.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- registrationFrom (query, optional, string)

- registrationTo (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "user_id",
      "email": "customer@example.com",
      "firstName": "Sarah",
      "lastName": "Johnson",
      "phone": "+923001234567",
      "role": "REGISTERED_USER",
      "isVerified": true,
      "isActive": true,
      "createdAt": "2026-05-09T10:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Users fetched successfully"
}
```

**GET** /api/v1/users/{id}

**Summary:** Fetch Users details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with users.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with users.read. SUPER\_ADMIN or ADMIN with users.read permission.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/users/{id}

**Summary:** Update Users

**Allowed role/access:** SUPER\_ADMIN or ADMIN with users.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with users.update. SUPER\_ADMIN or ADMIN with users.update permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "firstName": "Alex",
```

```
"lastName": "Johnson",
"phone": "+15552345678",
"avatarUrl": "https://<YOUR_PUBLIC_BUCKET_OR_CDN_URL>/user-avatars/avatar.jpg",
"location": "New York, USA"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/users/{id}

**Summary:** Permanently delete registered user

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Permanent delete danger-zone endpoint. DANGER: This endpoint permanently deletes/anonymizes the registered user and removes related non-financial data from the database. This is not a soft delete. Use only from Super Admin danger zone screens.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": {
    "deletedUserId": "user_id",
    "deletedRelatedRecords": true
  },
  "message": "User permanently deleted successfully."
}
```

**PATCH** /api/v1/users/{id}/status

**Summary:** Update Users Status

**Allowed role/access:** SUPER\_ADMIN or ADMIN with users.status.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with users.status.update. SUPER\_ADMIN or ADMIN with users.status.update permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "status": "ACTIVE",
  "reason": "POLICY_VIOLATION",
  "comment": "Suspicious activity detected on this account.",
}
```

```
"notifyUser": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/users/{id}/suspend

**Summary:** Create Users Suspend

**Allowed role/access:** SUPER\_ADMIN or ADMIN with users.suspend

**Notes:** Access: SUPER\_ADMIN or ADMIN with users.suspend. SUPER\_ADMIN or ADMIN with users.suspend permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "reason": "POLICY_VIOLATION",
  "comment": "Suspicious account activity.",
  "notifyUser": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/users/{id}/unsuspend

**Summary:** Create Users Unsuspend

**Allowed role/access:** SUPER\_ADMIN or ADMIN with users.unsuspend

**Notes:** Access: SUPER\_ADMIN or ADMIN with users.unsuspend. SUPER\_ADMIN or ADMIN with users.unsuspend permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "comment": "Account reviewed and restored.",
  "notifyUser": true
}
```

**Response body:**

```
{
  "success": true,
```

```
"data": "<response returned by endpoint>",
"message": "Request completed successfully."
}
```

**POST** /api/v1/users/{id}/reset-password

**Summary:** Change registered user password

**Allowed role/access:** SUPER\_ADMIN or ADMIN with users.resetPassword

**Notes:** Access: SUPER\_ADMIN or ADMIN with users.resetPassword. SUPER\_ADMIN or ADMIN with users.resetPassword permission. SUPER\_ADMIN or ADMIN with users.resetPassword permission can change a REGISTERED\_USER password from the dashboard. Optionally sends email and in-app notification to the user.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "newPassword": "NewUser@123456",
  "sendEmail": true,
  "sendNotification": true,
  "reason": "Password changed by support request."
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "userId": "user_id",
    "email": "user@example.com",
    "emailSent": true,
    "notificationSent": true
  },
  "message": "User password changed successfully."
}
```

**GET** /api/v1/users/{id}/activity

**Summary:** Fetch Users Activity details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with users.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with users.read. SUPER\_ADMIN or ADMIN with users.read permission.

**Parameters:**

- id (path, required, string)
- page (query, optional, number)
- limit (query, optional, number)
- type (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/users/{id}/stats

**Summary:** Fetch Users Stats details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with users.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with users.read. SUPER\_ADMIN or ADMIN with users.read permission.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Provider Management

**GET** /api/v1/providers/export

**Summary:** List Providers Export

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providers.export

**Notes:** Access: SUPER\_ADMIN or ADMIN with providers.export. SUPER\_ADMIN or ADMIN with providers.export permission.

**Parameters:**

- search (query, optional, string)
- status (query, optional, string)
- approvalStatus (query, optional, string)
- format (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/providers/stats

**Summary:** List Providers Stats

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providers.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providers.read. SUPER\_ADMIN or ADMIN with providers.read permission.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/providers

**Summary:** List providers

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providers.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providers.read. SUPER\_ADMIN or ADMIN with providers.read permission. SUPER\_ADMIN/ADMIN with providers.read permission.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- approvalStatus (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "provider_id",
      "businessName": "Premium Gifts Co",
      "email": "provider@example.com",
      "phone": "+923001234567",
      "approvalStatus": "APPROVED",
      "isActive": true,
      "businessCategory": {
        "id": "category_id",
        "name": "Gift Supplier"
      },
      "createdAt": "2026-05-09T10:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Providers fetched successfully"
}
```

**POST** /api/v1/providers

**Summary:** Create provider from admin dashboard

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providers.create

**Notes:** Access: SUPER\_ADMIN or ADMIN with providers.create. SUPER\_ADMIN or ADMIN with providers.create permission. SUPER\_ADMIN or ADMIN with providers.create permission. Creates a PROVIDER account and provider business profile. Supports same business fields as provider self-registration, plus temporary password and invite email flow.

**Request payload(s):**

payload

```
{
  "email": "contact@giftsandblooms.com",
  "firstName": "Ali",
  "lastName": "Raza",
  "phone": "+15551234567",
  "businessName": "Gifts & Blooms Co. Ltd",
  "businessCategoryId": "provider_business_category_id",
  "taxId": "TAX-12345",
  "businessAddress": "123 Gift Street",
  "serviceArea": "New York, USA",
  "headquarters": "New York, USA",
  "fulfillmentMethods": [
```

```

    "PICKUP",
    "DELIVERY"
  ],
  "autoAcceptOrders": false,
  "documentUrls": [
    "https://cdn.yourdomain.com/provider-documents/license.pdf"
  ],
  "generateTemporaryPassword": true,
  "temporaryPassword": "Provider@123456",
  "mustChangePassword": true,
  "sendInviteEmail": true,
  "approvalStatus": "PENDING",
  "isActive": true
}

```

#### Response body:

```

{
  "success": true,
  "data": {
    "id": "provider_id",
    "userId": "provider_id",
    "email": "contact@giftsandblooms.com",
    "businessName": "Gifts & Blooms Co. Ltd",
    "approvalStatus": "PENDING",
    "isActive": true,
    "inviteEmailSent": true
  },
  "message": "Provider created successfully and invite email sent."
}

```

**GET** /api/v1/providers/lookup

**Summary:** List Providers Lookup

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providers.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providers.read. SUPER\_ADMIN or ADMIN with providers.read permission.

#### Parameters:

- search (query, optional, string)
- approvalStatus (query, optional, string)
- isActive (query, optional, boolean)
- limit (query, optional, number)

#### Response body:

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

**GET** /api/v1/providers/{id}

**Summary:** Fetch Providers details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providers.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providers.read. SUPER\_ADMIN or ADMIN with providers.read permission.

#### Parameters:

- id (path, required, string)

#### Response body:



```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/providers/{id}

**Summary:** Update Providers

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providers.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with providers.update. SUPER\_ADMIN or ADMIN with providers.update permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "businessName": "Gifts & Blooms Co. Ltd",
  "phone": "+15551234567",
  "serviceArea": "New York, USA",
  "headquarters": "New York, USA",
  "avatarUrl": "https://<YOUR_PUBLIC_BUCKET_OR_CDN_URL>/provider-logos/logo.png",
  "documentUrls": [
    "<string>"
  ]
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/providers/{id}

**Summary:** Permanently delete provider

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Permanent delete danger-zone endpoint. DANGER: This endpoint permanently deletes/anonymizes the provider and related provider data from the database. This is not a soft delete. Use only from Super Admin danger zone screens. Active processing orders block deletion.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": {
```

```
"deletedProviderId": "provider_id",
"deletedRelatedRecords": true
},
"message": "Provider permanently deleted successfully."
}
```

**PATCH** /api/v1/providers/{id}/status

**Summary:** Update provider lifecycle status

**Allowed role/access:** SUPER\_ADMIN or ADMIN with provider lifecycle permission (APPROVE=>providers.approve, REJECT=>providers.reject, SUSPEND=>providers.suspend, UNSUSPEND=>providers.suspend, UPDATE\_STATUS=>providers.updateStatus)

**Notes:** Access: SUPER\_ADMIN or ADMIN with provider lifecycle permission (APPROVE=>providers.approve, REJECT=>providers.reject, SUSPEND=>providers.suspend, UNSUSPEND=>providers.suspend, UPDATE\_STATUS=>providers.updateStatus). SUPER\_ADMIN or ADMIN with lifecycle permission. APPROVE requires providers.approve; REJECT requires providers.reject; SUSPEND and UNSUSPEND require providers.suspend; UPDATE\_STATUS requires providers.updateStatus. SUPER\_ADMIN or ADMIN with provider lifecycle permission. APPROVE requires providers.approve, REJECT requires providers.reject, SUSPEND and UNSUSPEND require providers.suspend, UPDATE\_STATUS requires providers.updateStatus. Uses action-based request body.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

approveProvider

```
{
  "action": "APPROVE",
  "comment": "Documents verified successfully.",
  "notifyProvider": true
}
```

rejectProvider

```
{
  "action": "REJECT",
  "reason": "INCOMPLETE_DOCUMENTS",
  "comment": "Business license document is missing.",
  "notifyProvider": true
}
```

updateStatus

```
{
  "action": "UPDATE_STATUS",
  "status": "ACTIVE",
  "reason": "OTHER",
  "comment": "Provider account restored after review.",
  "notifyProvider": true
}
```

suspendProvider

```
{
  "action": "SUSPEND",
  "reason": "POLICY_VIOLATION",
  "comment": "Provider violated platform policy.",
  "notifyProvider": true
}
```

unsuspendProvider

```
{
  "action": "UNSUSPEND",
  "comment": "Provider account reviewed and restored.",
  "notifyProvider": true
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "provider_id",
    "approvalStatus": "APPROVED",
    "status": "ACTIVE",
    "isActive": true
  },
  "message": "Provider approved successfully."
}
```

**GET** /api/v1/providers/{id}/items

**Summary:** Fetch Providers Items details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providers.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providers.read. SUPER\_ADMIN or ADMIN with providers.read permission.

**Parameters:**

- id (path, required, string)
- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/providers/{id}/activity

**Summary:** Fetch Providers Activity details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providers.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providers.read. SUPER\_ADMIN or ADMIN with providers.read permission.

**Parameters:**

- id (path, required, string)
- page (query, optional, number)
- limit (query, optional, number)
- type (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```

```
"message": "Request completed successfully."
}
```

**POST** /api/v1/providers/{id}/message

**Summary:** Create Providers Message

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providers.message

**Notes:** Access: SUPER\_ADMIN or ADMIN with providers.message. SUPER\_ADMIN or ADMIN with providers.message permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "subject": "Account update",
  "message": "Please update your business documents.",
  "channel": "EMAIL"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Provider Business Categories

**GET** /api/v1/provider-business-categories

**Summary:** List provider business categories

**Allowed role/access:** PUBLIC

**Notes:** Access: PUBLIC. PUBLIC. Active provider business category lookup for provider signup. Public/provider-signup dropdown. Returns active provider business categories.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- isActive (query, optional, boolean)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/provider-business-categories

**Summary:** Create provider business category

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerBusinessCategories.create

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerBusinessCategories.create. SUPER\_ADMIN or ADMIN with providerBusinessCategories.create permission. SUPER\_ADMIN or ADMIN with providerBusinessCategories.create permission only.

**Request payload(s):**

payload

```
{
  "name": "<string>",
  "description": "<string>",
  "iconKey": "<string>",
  "sortOrder": 1.0,
  "isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider-business-categories/{id}

**Summary:** Fetch provider business category details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerBusinessCategories.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerBusinessCategories.read. SUPER\_ADMIN or ADMIN with providerBusinessCategories.read permission. SUPER\_ADMIN or ADMIN with providerBusinessCategories.read permission only.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/provider-business-categories/{id}

**Summary:** Update provider business category

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerBusinessCategories.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerBusinessCategories.update. SUPER\_ADMIN or ADMIN with providerBusinessCategories.update permission. SUPER\_ADMIN or ADMIN with providerBusinessCategories.update permission only.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "name": "<string>",
  "description": "<string>",
  "iconKey": "<string>",
  "sortOrder": 1.0,
}
```

```
"isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/provider-business-categories/{id}

**Summary:** Delete provider business category

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerBusinessCategories.delete

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerBusinessCategories.delete. SUPER\_ADMIN or ADMIN with providerBusinessCategories.delete permission. SUPER\_ADMIN or ADMIN with providerBusinessCategories.delete permission. Permanently deletes the category; refuses deletion when active providers are attached.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Promotional Offers Management

**GET** /api/v1/promotional-offers/stats

**Summary:** List Promotional Offers Stats

**Allowed role/access:** SUPER\_ADMIN or ADMIN with promotionalOffers.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with promotionalOffers.read. SUPER\_ADMIN or ADMIN with promotionalOffers.read permission.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/promotional-offers/export

**Summary:** List Promotional Offers Export

**Allowed role/access:** SUPER\_ADMIN or ADMIN with promotionalOffers.export

**Notes:** Access: SUPER\_ADMIN or ADMIN with promotionalOffers.export. SUPER\_ADMIN or ADMIN with promotionalOffers.export permission.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- itemId (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)
- providerId (query, optional, string)
- approvalStatus (query, optional, string)
- discountType (query, optional, string)
- startFrom (query, optional, string)
- startTo (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/promotional-offers

**Summary:** List Promotional Offers

**Allowed role/access:** SUPER\_ADMIN or ADMIN with promotionalOffers.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with promotionalOffers.read. SUPER\_ADMIN or ADMIN with promotionalOffers.read permission.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- itemId (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)
- providerId (query, optional, string)
- approvalStatus (query, optional, string)
- discountType (query, optional, string)
- startFrom (query, optional, string)
- startTo (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/promotional-offers

**Summary:** Create Promotional Offers

**Allowed role/access:** SUPER\_ADMIN or ADMIN with promotionalOffers.create

**Notes:** Access: SUPER\_ADMIN or ADMIN with promotionalOffers.create. SUPER\_ADMIN or ADMIN with promotionalOffers.create permission.

**Request payload(s):**

payload

```
{
  "itemId": "<string>",
  "title": "<string>",
  "description": "<string>",
  "discountType": "PERCENTAGE",
  "discountValue": 1.0,
  "startDate": "<string>",
  "endDate": "<string>",
  "eligibilityRules": "<string>",
  "isActive": true,
  "providerId": "<string>",
  "approvalStatus": "PENDING"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/promotional-offers/{id}

**Summary:** Fetch Promotional Offers details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with promotionalOffers.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with promotionalOffers.read. SUPER\_ADMIN or ADMIN with promotionalOffers.read permission.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/promotional-offers/{id}

**Summary:** Update Promotional Offers

**Allowed role/access:** SUPER\_ADMIN or ADMIN with promotionalOffers.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with promotionalOffers.update. SUPER\_ADMIN or ADMIN with promotionalOffers.update permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "title": "<string>",
```



```
"description": "<string>",
"discountType": "PERCENTAGE",
"discountValue": 1.0,
"startDate": "<string>",
"endDate": "<string>",
"eligibilityRules": "<string>",
"isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/promotional-offers/{id}

**Summary:** Delete Promotional Offers

**Allowed role/access:** SUPER\_ADMIN or ADMIN with promotionalOffers.delete

**Notes:** Access: SUPER\_ADMIN or ADMIN with promotionalOffers.delete. SUPER\_ADMIN or ADMIN with promotionalOffers.delete permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/promotional-offers/{id}/approve

**Summary:** Update Promotional Offers Approve

**Allowed role/access:** SUPER\_ADMIN or ADMIN with promotionalOffers.approve

**Notes:** Access: SUPER\_ADMIN or ADMIN with promotionalOffers.approve. SUPER\_ADMIN or ADMIN with promotionalOffers.approve permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "comment": "<string>",
  "notifyProvider": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/promotional-offers/{id}/reject

**Summary:** Update Promotional Offers Reject

**Allowed role/access:** SUPER\_ADMIN or ADMIN with promotionalOffers.reject

**Notes:** Access: SUPER\_ADMIN or ADMIN with promotionalOffers.reject. SUPER\_ADMIN or ADMIN with promotionalOffers.reject permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "reason": "INVALID_DISCOUNT",
  "comment": "<string>",
  "notifyProvider": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/promotional-offers/{id}/status

**Summary:** Update Promotional Offers Status

**Allowed role/access:** SUPER\_ADMIN or ADMIN with promotionalOffers.status.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with promotionalOffers.status.update. SUPER\_ADMIN or ADMIN with promotionalOffers.status.update permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "isActive": true,
  "reason": "<string>"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Dashboard Overview

**GET** /api/v1/admin/dashboard/overview

**Summary:** Fetch Super Admin dashboard overview metrics

**Allowed role/access:** SUPER\_ADMIN or ADMIN with dashboard.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with dashboard.read. SUPER\_ADMIN or ADMIN with dashboard.read permission. Read-only dashboard overview metrics. SUPER\_ADMIN or ADMIN with dashboard.read. Read-only metrics are aggregated from existing users, providers, payments, and transaction records. Missing analytics sources return zeros instead of fake data.

**Response body:**

```
{
  "success": true,
  "data": {
    "totalUsers": 128430,
    "totalUsersDeltaPercent": 12.5,
    "totalProviders": 1240,
    "totalProvidersDeltaPercent": 5.2,
    "transactions": 45200,
    "transactionsDeltaPercent": 18.1,
    "totalRevenue": 1240000,
    "totalRevenueDeltaPercent": 10.3,
    "currency": "USD"
  },
  "message": "Dashboard overview fetched successfully."
}
```

**GET** /api/v1/admin/dashboard/revenue-trends

**Summary:** Fetch monthly revenue trends

**Allowed role/access:** SUPER\_ADMIN or ADMIN with dashboard.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with dashboard.read. SUPER\_ADMIN or ADMIN with dashboard.read permission. Read-only monthly revenue trends. SUPER\_ADMIN or ADMIN with dashboard.read. Uses successful payment records for the last 12 calendar months and returns zero for months with no revenue.

**Response body:**

```
{
  "success": true,
  "data": {
    "range": "LAST_12_MONTHS",
    "labels": [
      "Jan",
      "Feb",
      "Mar"
    ],
    "values": [
      12000,
      28000,
      16000
    ],
    "currency": "USD"
  },
  "message": "Revenue trends fetched successfully."
}
```

**GET** /api/v1/admin/dashboard/gift-vs-payment

**Summary:** Fetch gift vs direct payment distribution

**Allowed role/access:** SUPER\_ADMIN or ADMIN with dashboard.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with dashboard.read. SUPER\_ADMIN or ADMIN with dashboard.read permission. Read-only gift versus direct payment distribution. SUPER\_ADMIN or ADMIN with dashboard.read. Distribution is calculated from successful payment records; money gift payments count as gift cards and all other successful payments count as direct payments.

**Response body:**

```
{
  "success": true,
  "data": {
    "giftCardsPercent": 65,
    "directPaymentsPercent": 35
  },
  "message": "Gift vs payment distribution fetched successfully."
}
```

**GET** /api/v1/admin/dashboard/provider-performance

**Summary:** Fetch provider performance table

**Allowed role/access:** SUPER\_ADMIN or ADMIN with dashboard.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with dashboard.read. SUPER\_ADMIN or ADMIN with dashboard.read permission. Read-only provider performance table. SUPER\_ADMIN or ADMIN with dashboard.read. Aggregates provider order success rate and fulfilled volume from existing provider order records without exposing payout or customer-sensitive data.

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "providerId": "provider_id",
      "providerName": "Stripe Integration",
      "successRate": 99.2,
      "totalVolume": 450230,
      "currency": "USD"
    }
  ],
  "message": "Provider performance fetched successfully."
}
```

**GET** /api/v1/admin/dashboard/recent-disputes

**Summary:** Fetch recent disputes table

**Allowed role/access:** SUPER\_ADMIN or ADMIN with dashboard.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with dashboard.read. SUPER\_ADMIN or ADMIN with dashboard.read permission. Read-only recent dispute table without sensitive payment/customer data. SUPER\_ADMIN or ADMIN with dashboard.read. Combines recent customer and provider dispute cases and returns non-sensitive case, customer display name, reason, and priority/status only.

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "dispute_id",
      "caseId": "DISP-9021",
      "userName": "Marcus Wright",
      "reason": "Unauthorized transaction",
      "status": "HIGH_PRIORITY"
    }
  ],
}
```

```
"message": "Recent disputes fetched successfully."
}
```

## 02 Admin - Commission & Payout Settings

**GET** /api/v1/admin/payout-settings

**Summary:** Fetch commission and payout settings

**Allowed role/access:** SUPER\_ADMIN or ADMIN with payoutSettings.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with payoutSettings.read. SUPER\_ADMIN or ADMIN with payoutSettings.read permission. SUPER\_ADMIN or ADMIN with payoutSettings.read. Returns global platform commission, payout threshold/schedule, and active provider commission tiers. Settings affect future payout calculations only and do not rewrite historical payouts.

**Response body:**

```
{
  "success": true,
  "data": {
    "platformRatePercent": 5,
    "minimumPayoutThreshold": 100,
    "currency": "USD",
    "payoutSchedule": "MONTHLY_LAST_DAY",
    "payoutTimeUtc": "00:00",
    "autoPayoutEnabled": true,
    "lastUpdatedAt": "2026-05-16T10:00:00.000Z",
    "commissionTiers": [
      {
        "id": "tier_standard",
        "name": "Standard Tier",
        "commissionRatePercent": 15,
        "orderVolumeThreshold": 0,
        "sortOrder": 1,
        "isActive": true
      },
      {
        "id": "tier_silver",
        "name": "Silver Partner",
        "commissionRatePercent": 12.5,
        "orderVolumeThreshold": 5000,
        "sortOrder": 2,
        "isActive": true
      }
    ]
  },
  "message": "Payout settings fetched successfully."
}
```

**PATCH** /api/v1/admin/payout-settings

**Summary:** Update commission and payout settings

**Allowed role/access:** SUPER\_ADMIN or ADMIN with payoutSettings.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with payoutSettings.update. SUPER\_ADMIN or ADMIN with payoutSettings.update permission. Applies to future payout calculations only. SUPER\_ADMIN or ADMIN with payoutSettings.update. Updates global settings for future payout calculations only; existing historical payouts are not rewritten or recalculated.

**Request payload(s):**

update

```
{
  "platformRatePercent": 5,
  "minimumPayoutThreshold": 100,
  "currency": "USD",
  "payoutSchedule": "MONTHLY_LAST_DAY",
  "payoutTimeUtc": "00:00",
  "autoPayoutEnabled": true
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "platformRatePercent": 5,
    "minimumPayoutThreshold": 100,
    "currency": "USD",
    "payoutSchedule": "MONTHLY_LAST_DAY",
    "payoutTimeUtc": "00:00",
    "autoPayoutEnabled": true,
    "lastUpdatedAt": "2026-05-16T10:00:00.000Z"
  },
  "message": "Payout settings updated successfully."
}
```

**GET** /api/v1/admin/payout-settings/commission-tiers

**Summary:** List commission tiers

**Allowed role/access:** SUPER\_ADMIN or ADMIN with payoutSettings.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with payoutSettings.read. SUPER\_ADMIN or ADMIN with payoutSettings.read permission. SUPER\_ADMIN or ADMIN with payoutSettings.read. Returns active commission tiers ordered by sort order and threshold.

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "tier_standard",
      "name": "Standard Tier",
      "commissionRatePercent": 15,
      "orderVolumeThreshold": 0,
      "sortOrder": 1,
      "isActive": true
    }
  ],
  "message": "Commission tiers fetched successfully."
}
```

**POST** /api/v1/admin/payout-settings/commission-tiers

**Summary:** Create commission tier

**Allowed role/access:** SUPER\_ADMIN or ADMIN with payoutSettings.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with payoutSettings.update. SUPER\_ADMIN or ADMIN with payoutSettings.update permission. SUPER\_ADMIN or ADMIN with payoutSettings.update. Creates a provider commission tier for future billing/payout cycles only. Thresholds must be unique among active tiers.

**Request payload(s):**

create

```
{
  "name": "Gold Elite",
  "commissionRatePercent": 10,
  "orderVolumeThreshold": 15000,
  "sortOrder": 3,
  "isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "tier_gold",
    "name": "Gold Elite",
    "commissionRatePercent": 10,
    "orderVolumeThreshold": 15000,
    "sortOrder": 3,
    "isActive": true
  },
  "message": "Commission tier created successfully."
}
```

**PATCH** /api/v1/admin/payout-settings/commission-tiers/{id}

**Summary:** Update commission tier

**Allowed role/access:** SUPER\_ADMIN or ADMIN with payoutSettings.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with payoutSettings.update. SUPER\_ADMIN or ADMIN with payoutSettings.update permission. Applies next billing/payout cycle. SUPER\_ADMIN or ADMIN with payoutSettings.update. Tier changes take effect at the start of the next billing/payout cycle and do not rewrite historical payouts.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

update

```
{
  "name": "Gold Elite",
  "commissionRatePercent": 10,
  "orderVolumeThreshold": 15000,
  "sortOrder": 3,
  "isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "tier_gold",
    "name": "Gold Elite",
    "commissionRatePercent": 10,
    "orderVolumeThreshold": 15000,
    "sortOrder": 3,
    "isActive": true
  },
  "message": "Commission tier updated successfully."
}
```

**DELETE** /api/v1/admin/payout-settings/commission-tiers/{id}

**Summary:** Delete commission tier

**Allowed role/access:** SUPER\_ADMIN or ADMIN with payoutSettings.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with payoutSettings.update. SUPER\_ADMIN or ADMIN with payoutSettings.update permission. Permanently deletes the tier record. SUPER\_ADMIN or ADMIN with payoutSettings.update. Permanently deletes the tier record.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "tier_gold",
    "deleted": true
  },
  "message": "Commission tier deleted successfully."
}
```

**GET** /api/v1/admin/payout-settings/audit-logs

**Summary:** List payout settings audit logs

**Allowed role/access:** SUPER\_ADMIN or ADMIN with payoutSettings.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with payoutSettings.read. SUPER\_ADMIN or ADMIN with payoutSettings.read permission. SUPER\_ADMIN or ADMIN with payoutSettings.read. Returns audit logs for payout settings and commission tier changes, including sanitized before/after JSON.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "audit_log_id",
      "action": "PAYOUT_SETTINGS_UPDATED",
      "actor": {
        "id": "admin_id",
        "name": "Alex Rivera"
      },
      "targetType": "PAYOUT_SETTINGS",
      "before": {
        "platformRatePercent": 5
      },
      "after": {
        "platformRatePercent": 6
      },
      "createdAt": "2026-05-16T10:00:00.000Z"
    }
  ]
}
```



```
],
"meta": {
  "page": 1,
  "limit": 20,
  "total": 1,
  "totalPages": 1
},
"message": "Payout settings audit logs fetched successfully."
}
```

## 02 Admin - Provider Payouts

**GET** /api/v1/admin/provider-payouts/stats

**Summary:** Fetch provider payout dashboard stats

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerPayouts.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerPayouts.read. SUPER\_ADMIN or ADMIN with providerPayouts.read permission. SUPER\_ADMIN or ADMIN with providerPayouts.read. Aggregates from provider payout records only; no frontend totals are trusted.

**Response body:**

```
{
  "success": true,
  "data": {
    "totalPayoutsThisMonth": 128430,
    "totalPayoutsDeltaPercent": 12.5,
    "pendingPayouts": 12250,
    "pendingPayoutsDeltaPercent": -2.4,
    "completedPayouts": 116180,
    "completedPayoutsDeltaPercent": 14.2,
    "platformRevenue": 19264.5,
    "platformRevenueDeltaPercent": 8.1,
    "currency": "USD"
  },
  "message": "Provider payout stats fetched successfully."
}
```

**GET** /api/v1/admin/provider-payouts/trends

**Summary:** Fetch monthly provider payout trend

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerPayouts.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerPayouts.read. SUPER\_ADMIN or ADMIN with providerPayouts.read permission. SUPER\_ADMIN or ADMIN with providerPayouts.read. Returns last 12 months from provider payout records.

**Response body:**

```
{
  "success": true,
  "data": {
    "range": "LAST_12_MONTHS",
    "labels": [
      "Jan",
      "Feb",
      "Mar"
    ],
    "values": [
      12000,
      28000,
      16000
    ]
  }
}
```

```
    ],
    "currency": "USD"
  },
  "message": "Provider payout trends fetched successfully."
}
```

**GET** /api/v1/admin/provider-payouts/earning-distribution

**Summary:** Fetch earning distribution by provider tier

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerPayouts.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerPayouts.read. SUPER\_ADMIN or ADMIN with providerPayouts.read permission. SUPER\_ADMIN or ADMIN with providerPayouts.read. Uses provider earnings ledger totals and active commission tier thresholds.

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "tierId": "tier_silver",
      "tierName": "Silver Partner",
      "providerCount": 18,
      "totalEarnings": 450230,
      "currency": "USD"
    }
  ],
  "message": "Provider earning distribution fetched successfully."
}
```

**GET** /api/v1/admin/provider-payouts/export

**Summary:** Export provider payouts

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerPayouts.export

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerPayouts.export. SUPER\_ADMIN or ADMIN with providerPayouts.export permission. Uses list filters and excludes full bank account numbers. SUPER\_ADMIN or ADMIN with providerPayouts.export. Applies the same filters as list and never exports full bank account numbers.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- providerId (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)
- format (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/provider-payouts/bulk-approve

**Summary:** Bulk approve provider payouts

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerPayouts.approve

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerPayouts.approve. SUPER\_ADMIN or ADMIN with providerPayouts.approve permission. Returns per-item idempotent results. SUPER\_ADMIN or ADMIN with providerPayouts.approve. Idempotent per payout: already PROCESSING/COMPLETED payouts are returned as successful idempotent items and are not processed twice.

**Request payload(s):**

approve

```
{
  "payoutIds": [
    "payout_id_1",
    "payout_id_2"
  ],
  "comment": "Bulk approved after verification.",
  "notifyProvider": true
}
```

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "payoutId": "payout_id_1",
      "status": "PROCESSING",
      "success": true,
      "idempotent": false
    },
    {
      "payoutId": "payout_id_2",
      "status": "PROCESSING",
      "success": true,
      "idempotent": true
    }
  ],
  "message": "Bulk payout approval processed."
}
```

**GET** /api/v1/admin/provider-payouts

**Summary:** List provider payouts

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerPayouts.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerPayouts.read. SUPER\_ADMIN or ADMIN with providerPayouts.read permission. SUPER\_ADMIN or ADMIN with providerPayouts.read. Supports status/provider/date/search filters and sorting. Bank account data is masked only.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- providerId (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "payout_id",
      "provider": {
        "id": "provider_id",
        "businessName": "TechSolutions Inc.",
        "providerCode": "PRV-90210",
        "avatarUrl": "https://cdn.example.com/provider.png"
      },
      "pendingAmount": 3420,
      "currency": "USD",
      "lastPayoutDate": "2023-10-12T00:00:00.000Z",
      "nextPayoutDate": "2023-11-12T00:00:00.000Z",
      "status": "COMPLETED"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Provider payouts fetched successfully."
}
```

**GET** /api/v1/admin/provider-payouts/{id}/breakdown

**Summary:** Fetch pending payout transaction breakdown

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerPayouts.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerPayouts.read. SUPER\_ADMIN or ADMIN with providerPayouts.read permission. SUPER\_ADMIN or ADMIN with providerPayouts.read. Shows gross amount, platform fee, processing fee, net payout, and recent ledger transactions without full bank details.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "payoutId": "payout_id",
    "provider": {
      "id": "provider_id",
      "businessName": "CloudTech Solutions",
      "merchantId": "MER-29401-2023"
    },
    "grossAmount": 4200,
    "platformFee": 420,
    "platformFeePercent": 10,
    "processingFee": 12.5,
    "netPayout": 3767.5,
    "currency": "USD",
    "recentTransactions": [
      {
        "orderNumber": "88392",
        "description": "Subscription - Professional Plan",
        "amount": 199
      }
    ]
  }
}
```

```
},
"message": "Payout breakdown fetched successfully."
}
```

**POST** /api/v1/admin/provider-payouts/{id}/approve

**Summary:** Approve provider payout

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerPayouts.approve

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerPayouts.approve. SUPER\_ADMIN or ADMIN with providerPayouts.approve permission. Idempotent for already approved payouts. SUPER\_ADMIN or ADMIN with providerPayouts.approve. Only PENDING or ON\_HOLD payouts can be approved. Approved payouts move to PROCESSING for payout processor completion.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

approve

```
{
  "comment": "Approved after verification.",
  "notifyProvider": true
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "payout_id",
    "status": "PROCESSING"
  },
  "message": "Payout approved successfully."
}
```

**POST** /api/v1/admin/provider-payouts/{id}/hold

**Summary:** Hold provider payout

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerPayouts.hold

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerPayouts.hold. SUPER\_ADMIN or ADMIN with providerPayouts.hold permission. Keeps ledger balance locked. SUPER\_ADMIN or ADMIN with providerPayouts.hold. Holds a PENDING payout without releasing locked PAYOUT\_PENDING ledger balance.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

hold

```
{
  "reason": "BANK_VERIFICATION_PENDING",
  "comment": "Bank verification required.",
  "notifyProvider": true
}
```

**Response body:**

```
{
  "success": true,
  "data": {
```

```
    "id": "payout_id",
    "status": "ON_HOLD"
  },
  "message": "Payout held successfully."
}
```

**POST** /api/v1/admin/provider-payouts/{id}/reject

**Summary:** Reject provider payout

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerPayouts.reject

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerPayouts.reject. SUPER\_ADMIN or ADMIN with providerPayouts.reject permission. Releases locked ledger balance. SUPER\_ADMIN or ADMIN with providerPayouts.reject. Rejects PENDING or ON\_HOLD payout and releases locked PAYOUT\_PENDING ledger balance back to AVAILABLE.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

reject

```
{
  "reason": "INVALID_BANK_ACCOUNT",
  "comment": "Bank details are invalid.",
  "notifyProvider": true
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "payout_id",
    "status": "REJECTED",
    "ledgerReleased": true
  },
  "message": "Payout rejected successfully."
}
```

**GET** /api/v1/admin/provider-payouts/{id}

**Summary:** Fetch provider payout details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerPayouts.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerPayouts.read. SUPER\_ADMIN or ADMIN with providerPayouts.read permission. Payout destination is masked. SUPER\_ADMIN or ADMIN with providerPayouts.read. Returns payout details, provider display data, and masked payout destination only.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "payout_id",
    "provider": {
      "id": "provider_id",
      "businessName": "TechSolutions Inc.",
      "providerCode": "PRV-90210",
      "avatarUrl": "https://cdn.example.com/provider.png"
    },
  },
}
```

```

    "pendingAmount": 3420,
    "amount": 3420,
    "processingFee": 42,
    "totalToReceive": 3378,
    "currency": "USD",
    "status": "COMPLETED",
    "destination": {
      "id": "method_id",
      "bankName": "Chase Bank",
      "maskedAccount": "****1234",
      "last4": "1234",
      "verificationStatus": "VERIFIED"
    },
    "createdAt": "2023-10-12T00:00:00.000Z"
  },
  "message": "Provider payout details fetched successfully."
}

```

## 02 Admin - Transaction Monitoring

**GET** /api/v1/admin/transactions/stats

**Summary:** Fetch transaction monitoring stats

**Allowed role/access:** SUPER\_ADMIN or ADMIN with transactions.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with transactions.read. SUPER\_ADMIN or ADMIN with transactions.read permission. SUPER\_ADMIN or ADMIN with transactions.read. Stats are calculated from real payment/transaction records and return zeros when no records match.

**Parameters:**

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- transactionType (query, optional, string)
- status (query, optional, string)

**Response body:**

```

{
  "success": true,
  "data": {
    "totalVolume": 124500,
    "totalVolumeDeltaPercent": 12,
    "successRate": 98.2,
    "successRateDeltaPercent": 2.1,
    "pendingReview": 14,
    "failedToday": 3,
    "failedTodayDeltaPercent": -5,
    "currency": "PKR"
  },
  "message": "Transaction stats fetched successfully."
}

```

**GET** /api/v1/admin/transactions/export

**Summary:** Export admin transactions

**Allowed role/access:** SUPER\_ADMIN or ADMIN with transactions.export

**Notes:** Access: SUPER\_ADMIN or ADMIN with transactions.export. SUPER\_ADMIN or ADMIN with transactions.export permission. Excludes card and payment secrets. SUPER\_ADMIN or ADMIN with transactions.export. Applies the same filters as the list API and excludes raw card numbers, CVV, client secrets, and Stripe secret fields.

**Parameters:**

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- transactionType (query, optional, string)
- status (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- gatewayProvider (query, optional, string)
- userId (query, optional, string)
- providerId (query, optional, string)
- minAmount (query, optional, number)
- maxAmount (query, optional, number)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)
- format (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/transactions**Summary:** List admin transactions**Allowed role/access:** SUPER\_ADMIN or ADMIN with transactions.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with transactions.read. SUPER\_ADMIN or ADMIN with transactions.read permission. SUPER\_ADMIN or ADMIN with transactions.read. Admin-side financial monitoring endpoint; customer transaction history remains under /api/v1/customer/transactions. Search supports transaction ID, order number, customer name/email, gateway reference, and provider business name.

**Parameters:**

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- transactionType (query, optional, string)
- status (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- gatewayProvider (query, optional, string)
- userId (query, optional, string)
- providerId (query, optional, string)
- minAmount (query, optional, number)
- maxAmount (query, optional, number)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "transaction_id",
```



```

      "transactionId": "TXN-882194",
      "user": {
        "id": "user_id",
        "name": "Sarah Jenkins",
        "avatarUrl": "https://cdn.yourdomain.com/user-avatars/sarah.png"
      },
      "gatewayProvider": "STRIPE",
      "type": "PAYMENT",
      "amount": 1250,
      "currency": "PKR",
      "status": "SUCCESS",
      "createdAt": "2026-10-24T14:20:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Transactions fetched successfully."
}

```

**GET** /api/v1/admin/transactions/{id}/timeline

**Summary:** Fetch transaction timeline

**Allowed role/access:** SUPER\_ADMIN or ADMIN with transactions.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with transactions.read. SUPER\_ADMIN or ADMIN with transactions.read permission. SUPER\_ADMIN or ADMIN with transactions.read. Returns ordered payment, refund, dispute, notification, and audit events without card/payment secrets.

**Parameters:**

- id (path, required, string)

**Response body:**

```

{
  "success": true,
  "data": [
    {
      "status": "INITIATED",
      "title": "Initiated",
      "description": "Checkout session started by user via mobile application.",
      "source": "User Session",
      "timestamp": "2026-11-24T14:30:02.000Z"
    },
    {
      "status": "COMPLETED",
      "title": "Completed",
      "description": "Funds successfully transferred to the merchant escrow account.",
      "source": "System Auto-Update",
      "timestamp": "2026-11-24T14:32:10.000Z"
    }
  ],
  "message": "Transaction timeline fetched successfully."
}

```

**GET** /api/v1/admin/transactions/{id}/receipt

**Summary:** Download transaction receipt

**Allowed role/access:** SUPER\_ADMIN or ADMIN with transactions.receipt.download

**Notes:** Access: SUPER\_ADMIN or ADMIN with transactions.receipt.download. SUPER\_ADMIN or ADMIN with transactions.receipt.download permission. SUPER\_ADMIN or ADMIN with transactions.receipt.download. Returns a PDF-compatible receipt file with transaction ID, order ID, customer display info, amount breakdown, gateway provider, and masked payment method only.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/transactions/{id}/refund

**Summary:** Refund transaction

**Allowed role/access:** SUPER\_ADMIN or ADMIN with transactions.refund

**Notes:** Access: SUPER\_ADMIN or ADMIN with transactions.refund. SUPER\_ADMIN or ADMIN with transactions.refund permission. Refund amount is server-validated. SUPER\_ADMIN or ADMIN with transactions.refund. Refund amount is server-validated against remaining refundable amount and Refund Policy Settings. No frontend amount is trusted; no card/payment secrets are exposed.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

full

```
{
  "refundType": "FULL",
  "refundAmount": 1281.25,
  "reason": "CUSTOMER_REQUEST",
  "comment": "Refund approved by support.",
  "notifyUser": true
}
```

partial

```
{
  "refundType": "PARTIAL",
  "refundAmount": 250,
  "reason": "PRODUCT_NOT_RECEIVED",
  "comment": "Partial goodwill refund.",
  "notifyUser": true
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "transactionId": "TRX-982341",
    "refundId": "RF-45678",
    "refundAmount": 1281.25,
    "currency": "PKR",
    "status": "REFUNDED"
  },
}
```

```
"message": "Transaction refunded successfully."
}
```

**POST** /api/v1/admin/transactions/{id}/open-dispute

**Summary:** Open dispute from transaction

**Allowed role/access:** SUPER\_ADMIN or ADMIN with transactions.openDispute

**Notes:** Access: SUPER\_ADMIN or ADMIN with transactions.openDispute. SUPER\_ADMIN or ADMIN with transactions.openDispute permission. SUPER\_ADMIN or ADMIN with transactions.openDispute. Creates an Admin Dispute Manager case linked to transaction/payment/order and blocks duplicate open disputes.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

open

```
{
  "reason": "PRODUCT_NOT_RECEIVED",
  "priority": "HIGH",
  "claimDetails": "Dispute opened from transaction detail screen.",
  "assignToId": "admin_id"
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "disputeId": "dispute_id",
    "caseId": "DSP-1024",
    "transactionId": "TRX-982341",
    "status": "OPEN"
  },
  "message": "Dispute opened successfully."
}
```

**POST** /api/v1/admin/transactions/{id}/notify-user

**Summary:** Send transaction notification to user

**Allowed role/access:** SUPER\_ADMIN or ADMIN with transactions.notifyUser

**Notes:** Access: SUPER\_ADMIN or ADMIN with transactions.notifyUser. SUPER\_ADMIN or ADMIN with transactions.notifyUser permission. SUPER\_ADMIN or ADMIN with transactions.notifyUser. Creates in-app notification and/or email handoff audit; includeReceipt links receipt metadata without exposing payment secrets.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

email

```
{
  "channel": "EMAIL",
  "subject": "Transaction update",
  "message": "Your transaction has been successfully processed.",
  "includeReceipt": true
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "transactionId": "TRX-982341",
    "notificationSent": true,
    "channel": "EMAIL"
  },
  "message": "Notification sent successfully."
}
```

**GET** /api/v1/admin/transactions/{id}

**Summary:** Fetch transaction details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with transactions.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with transactions.read. SUPER\_ADMIN or ADMIN with transactions.read permission. Card/payment secrets are masked. SUPER\_ADMIN or ADMIN with transactions.read. Shows payment breakdown, gateway information, customer info, related records, and refund state. Raw card numbers, CVV, Stripe secret keys, and payment intent client secrets are never exposed.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "transaction_id",
    "transactionId": "TRX-982341",
    "status": "SUCCESS",
    "type": "PAYMENT",
    "currency": "PKR",
    "paymentBreakdown": {
      "subtotal": 1250,
      "processingFee": 31.25,
      "processingFeePercent": 2.5,
      "totalAmount": 1281.25
    },
    "gatewayInformation": {
      "provider": "STRIPE",
      "gatewayReference": "REF-XP-382341",
      "paymentMethod": "Visa **** 4242",
      "settlementStatus": "CLEARED",
      "processorAuthCode": "AUTH-9921-X"
    },
    "customer": {
      "id": "user_id",
      "name": "Julianne Doe",
      "email": "julianne.doe@example.com",
      "location": "San Francisco, CA, USA",
      "kycStatus": "KYC Level 2 Verified"
    },
    "relatedRecords": {
      "orderId": "order_id",
      "orderNumber": "ORD-88421",
      "paymentId": "payment_id",
      "subscriptionId": null,
      "moneyGiftId": null,
      "walletLedgerId": null
    },
    "refund": {
      "isRefundable": true,

```

```
    "refundedAmount": 0,
    "remainingRefundableAmount": 1281.25,
    "refundWindowEndsAt": "2026-11-24T00:00:00.000Z"
  },
  "createdAt": "2026-10-24T14:20:00.000Z"
},
"message": "Transaction details fetched successfully."
}
```

## 02 Admin - Message Moderation

**GET** /api/v1/admin/message-moderation/conversations

**Summary:** List flagged message moderation conversations

**Allowed role/access:** SUPER\_ADMIN or ADMIN with messageModeration.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with messageModeration.read. SUPER\_ADMIN or ADMIN with messageModeration.read permission. Harmful message previews are redacted. SUPER\_ADMIN or ADMIN with messageModeration.read. Supports page, limit, search, chatType, status, severity, flagReason, senderRole, participantType, assignedToAdminId, fromDate, toDate, sortBy, sortOrder.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- chatType (query, optional, string)
- status (query, optional, string)
- severity (query, optional, string)
- flagReason (query, optional, string)
- senderRole (query, optional, string)
- participantType (query, optional, string)
- assignedToAdminId (query, optional, string)
- source (query, optional, string)
- flagType (query, optional, string)
- assignedToId (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "conversation_id",
      "chatType": "BUYER_PROVIDER",
      "status": "PENDING_REVIEW",
      "severity": "HIGH",
      "flaggedMessageCount": 2,
      "lastFlaggedAt": "2026-05-18T10:00:00.000Z",
      "participants": [
        {
          "id": "customer_id",
          "type": "REGISTERED_USER",
          "name": "Sarah Johnson",
          "avatarUrl": null
        },
        {
```

```

        "id": "provider_id",
        "type": "PROVIDER",
        "name": "Dcodax Gifts",
        "avatarUrl": null
      }
    ],
    "lastMessagePreview": "Please pay outside the platform...",
    "flagReasons": [
      "OFF_PLATFORM_PAYMENT",
      "AUTO_FLAG_KEYWORD"
    ],
    "assignedTo": null
  }
},
"meta": {
  "page": 1,
  "limit": 20,
  "total": 1,
  "totalPages": 1
},
"message": "Flagged message conversations fetched successfully."
}

```

**GET** /api/v1/admin/message-moderation/stats

**Summary:** Fetch message moderation stats

**Allowed role/access:** SUPER\_ADMIN or ADMIN with messageModeration.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with messageModeration.read. SUPER\_ADMIN or ADMIN with messageModeration.read permission. SUPER\_ADMIN or ADMIN with messageModeration.read. Calculated from real moderation records.

**Response body:**

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

**GET** /api/v1/admin/message-moderation/filter-options

**Summary:** Fetch message moderation filter options

**Allowed role/access:** SUPER\_ADMIN or ADMIN with messageModeration.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with messageModeration.read. SUPER\_ADMIN or ADMIN with messageModeration.read permission. SUPER\_ADMIN or ADMIN with messageModeration.read.

**Response body:**

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

**GET** /api/v1/admin/message-moderation/export

**Summary:** Export message moderation rows

**Allowed role/access:** SUPER\_ADMIN or ADMIN with messageModeration.export

**Notes:** Access: SUPER\_ADMIN or ADMIN with messageModeration.export. SUPER\_ADMIN or ADMIN with messageModeration.export permission. Export is redacted. SUPER\_ADMIN or ADMIN with messageModeration.export. Export contains moderation-safe redacted fields only, not full private conversation history.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- chatType (query, optional, string)
- status (query, optional, string)
- severity (query, optional, string)
- flagReason (query, optional, string)
- senderRole (query, optional, string)
- participantType (query, optional, string)
- assignedToAdminId (query, optional, string)
- source (query, optional, string)
- flagType (query, optional, string)
- assignedToId (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/message-moderation/audit-logs

**Summary:** Fetch message moderation audit logs

**Allowed role/access:** SUPER\_ADMIN or ADMIN with messageModeration.auditLogs.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with messageModeration.auditLogs.read. SUPER\_ADMIN or ADMIN with messageModeration.auditLogs.read permission. SUPER\_ADMIN or ADMIN with messageModeration.auditLogs.read.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- conversationId (query, optional, string)
- messageId (query, optional, string)
- actorAdminId (query, optional, string)
- action (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/message-moderation/conversations/{id}

**Summary:** Fetch message moderation conversation detail

**Allowed role/access:** SUPER\_ADMIN or ADMIN with messageModeration.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with messageModeration.read. SUPER\_ADMIN or ADMIN with messageModeration.read permission. Flagged body is null by default; redactedBody is returned. SUPER\_ADMIN or ADMIN with messageModeration.read. Returns participants, flagged messages, internal notes, and action history.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/message-moderation/conversations/{id}/history

**Summary:** Fetch paginated message moderation conversation history

**Allowed role/access:** SUPER\_ADMIN or ADMIN with messageModeration.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with messageModeration.read. SUPER\_ADMIN or ADMIN with messageModeration.read permission. SUPER\_ADMIN or ADMIN with messageModeration.read. Defaults to paginated scoped history around flagged messages and masks sensitive payment/contact data.

**Parameters:**

- id (path, required, string)
- beforeMessageId (query, optional, string)
- afterMessageId (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/message-moderation/messages/{messageId}/block

**Summary:** Hide a flagged message from chat participants

**Allowed role/access:** SUPER\_ADMIN or ADMIN with messageModeration.moderate

**Notes:** Access: SUPER\_ADMIN or ADMIN with messageModeration.moderate. SUPER\_ADMIN or ADMIN with messageModeration.moderate permission. Hide a flagged message from chat participants. Does not block the sender account. SUPER\_ADMIN or ADMIN with messageModeration.moderate. Hide a flagged message from chat participants. Does not block the sender account. Internally records HIDE\_MESSAGE and never physically deletes chat messages.

**Parameters:**

- messageId (path, required, string)

**Request payload(s):**

payload

```
{
  "reason": "<string>",
  "comment": "<string>",
  "internalNote": "<string>",
  "notifyParticipants": true,
  "notifyUser": true
}
```



**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/message-moderation/messages/{messageId}/restore

**Summary:** Restore a hidden moderated message

**Allowed role/access:** SUPER\_ADMIN or ADMIN with messageModeration.moderate

**Notes:** Access: SUPER\_ADMIN or ADMIN with messageModeration.moderate. SUPER\_ADMIN or ADMIN with messageModeration.moderate permission. Restores a message hidden by moderation. SUPER\_ADMIN or ADMIN with messageModeration.moderate. Restores a message previously hidden by moderation and writes moderation/audit logs.

**Parameters:**

- messageId (path, required, string)

**Request payload(s):**

payload

```
{
  "reason": "FALSE_POSITIVE",
  "comment": "<string>",
  "notifyParticipants": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/message-moderation/messages/{messageId}/warn-user

**Summary:** Warn message sender

**Allowed role/access:** SUPER\_ADMIN or ADMIN with messageModeration.warn

**Notes:** Access: SUPER\_ADMIN or ADMIN with messageModeration.warn. SUPER\_ADMIN or ADMIN with messageModeration.warn permission. Creates warning notification and audit log. SUPER\_ADMIN or ADMIN with messageModeration.warn. Warn the message sender. Sender may be registered user or provider. Does not expose internal notes to sender.

**Parameters:**

- messageId (path, required, string)

**Request payload(s):**

payload

```
{
  "reason": "<string>",
  "comment": "<string>",
  "warningMessage": "<string>",
  "internalNote": "<string>",
  "notifySender": true,
  "notifyUser": true,
  "warningSeverity": "LOW"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/message-moderation/messages/{messageId}/suspend-account

**Summary:** Suspend message sender account

**Allowed role/access:** SUPER\_ADMIN or ADMIN with messageModeration.suspend

**Notes:** Access: SUPER\_ADMIN or ADMIN with messageModeration.suspend. SUPER\_ADMIN or ADMIN with messageModeration.suspend permission. Refuses ADMIN/SUPER\_ADMIN accounts. SUPER\_ADMIN or ADMIN with messageModeration.suspend. Suspends the message sender account using the correct registered-user/provider lifecycle service. Admin and Super Admin accounts cannot be suspended here.

**Parameters:**

- messageId (path, required, string)

**Request payload(s):**

payload

```
{
  "reason": "<string>",
  "comment": "<string>",
  "suspensionScope": "ACCOUNT",
  "durationDays": 1.0,
  "notifySender": true,
  "duration": "<string>",
  "suspendUntil": "<string>",
  "internalNote": "<string>",
  "notifyUser": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/message-moderation/messages/{messageId}/dismiss-flag

**Summary:** Dismiss a moderation flag

**Allowed role/access:** SUPER\_ADMIN or ADMIN with messageModeration.moderate

**Notes:** Access: SUPER\_ADMIN or ADMIN with messageModeration.moderate. SUPER\_ADMIN or ADMIN with messageModeration.moderate permission. SUPER\_ADMIN or ADMIN with messageModeration.moderate. Marks flag as false-positive/no-action and keeps the message visible.

**Parameters:**

- messageId (path, required, string)

**Request payload(s):**

payload

```
{
  "reason": "<string>",
  "comment": "<string>",
}
```

```
"internalNote": "<string>"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/message-moderation/messages/{messageId}/note

**Summary:** Add internal private moderation note

**Allowed role/access:** SUPER\_ADMIN or ADMIN with messageModeration.notes.create

**Notes:** Access: SUPER\_ADMIN or ADMIN with messageModeration.notes.create. SUPER\_ADMIN or ADMIN with messageModeration.notes.create permission. Internal-only note. SUPER\_ADMIN or ADMIN with messageModeration.notes.create. Internal-only note is never visible to customer/provider participants.

**Parameters:**

- messageId (path, required, string)

**Request payload(s):**

payload

```
{
  "note": "<string>"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/message-moderation/messages/{messageId}/reprocess

**Summary:** Reprocess a message through scanner

**Allowed role/access:** SUPER\_ADMIN or ADMIN with messageModeration.reprocess

**Notes:** Access: SUPER\_ADMIN or ADMIN with messageModeration.reprocess. SUPER\_ADMIN or ADMIN with messageModeration.reprocess permission. SUPER\_ADMIN or ADMIN with messageModeration.reprocess. Re-runs the content scanner using current policy and stores scanner result snapshot without duplicating active flags for the same reason.

**Parameters:**

- messageId (path, required, string)

**Request payload(s):**

payload

```
{
  "scannerMode": "CURRENT_POLICY",
  "comment": "<string>",
  "reason": "<string>"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/message-moderation/messages/{messageId}/escalate

**Summary:** Escalate a flagged message

**Allowed role/access:** SUPER\_ADMIN or ADMIN with messageModeration.escalate

**Notes:** Access: SUPER\_ADMIN or ADMIN with messageModeration.escalate. SUPER\_ADMIN or ADMIN with messageModeration.escalate permission. SUPER\_ADMIN or ADMIN with messageModeration.escalate. Escalates a flagged message to support, security, or dispute review.

**Parameters:**

- messageId (path, required, string)

**Request payload(s):**

payload

```
{
  "escalationType": "SUPPORT_REVIEW",
  "priority": "HIGH",
  "reason": "<string>",
  "assignToAdminId": "<string>",
  "notifyAssignedAdmin": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Social Moderation

**GET** /api/v1/admin/social-moderation/stats

**Summary:** Fetch social moderation stats

**Allowed role/access:** SUPER\_ADMIN or ADMIN with socialModeration.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with socialModeration.read. SUPER\_ADMIN or ADMIN with socialModeration.read permission. SUPER\_ADMIN or ADMIN with socialModeration.read.

**Parameters:**

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "totalFlaggedPosts": 245,
    "pendingReports": 38,
    "highSeverityReports": 12,
  }
}
```

```
"removedPosts": 19,
"hiddenPosts": 44,
"warningsSent": 28
},
"message": "Social moderation stats fetched successfully."
}
```

**GET** /api/v1/admin/social-moderation/export

**Summary:** Export social moderation log

**Allowed role/access:** SUPER\_ADMIN or ADMIN with socialModeration.export

**Notes:** Access: SUPER\_ADMIN or ADMIN with socialModeration.export. SUPER\_ADMIN or ADMIN with socialModeration.export permission. SUPER\_ADMIN or ADMIN with socialModeration.export. Exports moderation-safe fields only.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- reportType (query, optional, string)
- status (query, optional, string)
- severity (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)
- format (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/social-moderation/reports

**Summary:** List social moderation reports

**Allowed role/access:** SUPER\_ADMIN or ADMIN with socialModeration.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with socialModeration.read. SUPER\_ADMIN or ADMIN with socialModeration.read permission. SUPER\_ADMIN or ADMIN with socialModeration.read. Search supports post content, user name, username, report ID, and post ID.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- reportType (query, optional, string)
- status (query, optional, string)
- severity (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
```

```
"data": "<response returned by endpoint>",
"message": "Request completed successfully."
}
```

**GET** /api/v1/admin/social-moderation/reports/{id}

**Summary:** Fetch social report inspection details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with socialModeration.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with socialModeration.read. SUPER\_ADMIN or ADMIN with socialModeration.read permission. SUPER\_ADMIN or ADMIN with socialModeration.read. Returns post inspection drawer data and report history.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/social-moderation/reports/{id}/action

**Summary:** Run social moderation action

**Allowed role/access:** SUPER\_ADMIN or ADMIN with socialModeration.moderate

**Notes:** Access: SUPER\_ADMIN or ADMIN with socialModeration.moderate. SUPER\_ADMIN or ADMIN with socialModeration.moderate permission. SUPER\_ADMIN or ADMIN with socialModeration.moderate. HIDE/REMOVE/WARN\_USER create moderation logs and audit logs; posts are not physically deleted.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

hide

```
{
  "action": "HIDE",
  "reason": "SPAM",
  "comment": "Post hidden due to deceptive link reports.",
  "notifyUser": true
}
```

remove

```
{
  "action": "REMOVE",
  "reason": "DECEPTIVE_LINK",
  "comment": "Post removed after manual review.",
  "notifyUser": true
}
```

warn

```
{
  "action": "WARN_USER",
  "reason": "INAPPROPRIATE_BEHAVIOR",
  "comment": "Warning issued for repeated spam behavior.",
}
```

```
"notifyUser": true
}
```

reviewed

```
{
  "action": "MARK_REVIEWED",
  "comment": "Reviewed and no additional action required.",
  "notifyUser": false
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Social Reporting Rules

**GET** /api/v1/admin/social-reporting-rules/stats

**Summary:** Fetch social reporting rule stats

**Allowed role/access:** SUPER\_ADMIN or ADMIN with socialReportingRules.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with socialReportingRules.read. SUPER\_ADMIN or ADMIN with socialReportingRules.read permission. SUPER\_ADMIN or ADMIN with socialReportingRules.read.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/social-reporting-rules/export

**Summary:** Export social reporting rules

**Allowed role/access:** SUPER\_ADMIN or ADMIN with socialReportingRules.export

**Notes:** Access: SUPER\_ADMIN or ADMIN with socialReportingRules.export. SUPER\_ADMIN or ADMIN with socialReportingRules.export permission. SUPER\_ADMIN or ADMIN with socialReportingRules.export.

**Parameters:**

- format (query, optional, string)
- isActive (query, optional, boolean)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/social-reporting-rules

**Summary:** List social reporting rules

**Allowed role/access:** SUPER\_ADMIN or ADMIN with socialReportingRules.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with socialReportingRules.read. SUPER\_ADMIN or ADMIN with socialReportingRules.read permission. SUPER\_ADMIN or ADMIN with socialReportingRules.read.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- isActive (query, optional, boolean)
- reportCategory (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/social-reporting-rules

**Summary:** Create social reporting rule

**Allowed role/access:** SUPER\_ADMIN or ADMIN with socialReportingRules.create

**Notes:** Access: SUPER\_ADMIN or ADMIN with socialReportingRules.create. SUPER\_ADMIN or ADMIN with socialReportingRules.create permission. SUPER\_ADMIN or ADMIN with socialReportingRules.create.

**Request payload(s):**

payload

```
{
  "reportCategory": "<string>",
  "label": "<string>",
  "description": "<string>",
  "iconKey": "<string>",
  "autoFlagThreshold": 1.0,
  "escalationRule": "AUTO_HIDE_CONTENT",
  "isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/social-reporting-rules/{id}

**Summary:** Fetch social reporting rule details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with socialReportingRules.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with socialReportingRules.read. SUPER\_ADMIN or ADMIN with socialReportingRules.read permission. SUPER\_ADMIN or ADMIN with socialReportingRules.read.

**Parameters:**

- id (path, required, string)

**Response body:**



```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/admin/social-reporting-rules/{id}

**Summary:** Update social reporting rule

**Allowed role/access:** SUPER\_ADMIN or ADMIN with socialReportingRules.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with socialReportingRules.update. SUPER\_ADMIN or ADMIN with socialReportingRules.update permission. SUPER\_ADMIN or ADMIN with socialReportingRules.update.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "label": "<string>",
  "description": "<string>",
  "iconKey": "<string>",
  "autoFlagThreshold": 1.0,
  "escalationRule": "AUTO_HIDE_CONTENT",
  "isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/admin/social-reporting-rules/{id}

**Summary:** Delete social reporting rule

**Allowed role/access:** SUPER\_ADMIN or ADMIN with socialReportingRules.delete

**Notes:** Access: SUPER\_ADMIN or ADMIN with socialReportingRules.delete. SUPER\_ADMIN or ADMIN with socialReportingRules.delete permission. SUPER\_ADMIN or ADMIN with socialReportingRules.delete. Permanently deletes the rule record.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/admin/social-reporting-rules/{id}/status

**Summary:** Update social reporting rule status

**Allowed role/access:** SUPER\_ADMIN or ADMIN with socialReportingRules.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with socialReportingRules.update. SUPER\_ADMIN or ADMIN with socialReportingRules.update permission. SUPER\_ADMIN or ADMIN with socialReportingRules.update.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "isActive": true,
  "reason": "<string>"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Notification Delivery Monitoring

**GET** /api/v1/admin/notification-delivery/stats

**Summary:** Fetch notification delivery stats

**Allowed role/access:** Authenticated

**Notes:** Access: Authenticated. Authenticated JWT required. SUPER\_ADMIN or ADMIN with notifications.read.

**Response body:**

```
{
  "success": true,
  "data": {
    "total": 12,
    "queued": 0,
    "delivered": 10,
    "failed": 1,
    "skipped": 1,
    "retried": 2
  },
  "message": "Notification delivery stats fetched successfully."
}
```

**GET** /api/v1/admin/notification-delivery/logs

**Summary:** List notification delivery logs

**Allowed role/access:** Authenticated

**Notes:** Access: Authenticated. Authenticated JWT required. SUPER\_ADMIN or ADMIN with notifications.read.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)
- recipientType (query, optional, string)
- notificationType (query, optional, string)
- recipientId (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/notification-delivery/logs/{id}

**Summary:** Fetch notification delivery log detail

**Allowed role/access:** Authenticated

**Notes:** Access: Authenticated. Authenticated JWT required. SUPER\_ADMIN or ADMIN with notifications.read.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/notification-delivery/logs/{id}/retry

**Summary:** Retry notification delivery

**Allowed role/access:** Authenticated

**Notes:** Access: Authenticated. Authenticated JWT required. SUPER\_ADMIN or ADMIN with notifications.delivery.retry. Retries non-IN\_APP delivery channels without duplicating the existing in-app notification.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Referral Settings

**GET** /api/v1/referral-settings

**Summary:** Fetch referral settings

**Allowed role/access:** SUPER\_ADMIN or ADMIN with referralSettings.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with referralSettings.read. SUPER\_ADMIN or ADMIN with referralSettings.read permission. SUPER\_ADMIN or ADMIN with referralSettings.read. Customer referral APIs consume these settings. Pending referrals use the settings snapshot stored at referral creation.

**Response body:**

```
{
  "success": true,
  "data": {
    "isActive": true,
    "referrerRewardAmount": 25,
    "newUserRewardAmount": 10,
    "rewardCurrency": "USD",
    "minimumTransactionAmount": 50,
    "referralExpirationValue": 30,
    "referralExpirationUnit": "DAYS",
    "allowSelfReferrals": false,
    "qualificationRule": "FIRST_SUCCESSFUL_PURCHASE",
    "updatedAt": "2026-05-09T10:00:00.000Z"
  },
  "message": "Referral settings fetched successfully."
}
```

**PATCH** /api/v1/referral-settings

**Summary:** Update referral settings

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Changes apply to future referral snapshots. SUPER\_ADMIN only. Changes apply to future referral snapshots and do not recalculate already-earned rewards.

**Request payload(s):**

payload

```
{
  "referrerRewardAmount": 25,
  "newUserRewardAmount": 10,
  "rewardCurrency": "USD",
```

```
"minimumTransactionAmount": 50,  
"referralExpirationValue": 30,  
"referralExpirationUnit": "DAYS",  
"allowSelfReferrals": false,  
"qualificationRule": "FIRST_SUCCESSFUL_PURCHASE"  
}
```

**Response body:**

```
{  
  "success": true,  
  "data": "<response returned by endpoint>",  
  "message": "Request completed successfully."  
}
```

**POST** /api/v1/referral-settings/activate

**Summary:** Activate referral program

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Activates referral program. SUPER\_ADMIN only. Existing earned rewards remain redeemable.

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{  
  "success": true,  
  "data": "<response returned by endpoint>",  
  "message": "Request completed successfully."  
}
```

**POST** /api/v1/referral-settings/deactivate

**Summary:** Deactivate referral program

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Deactivates referral program. SUPER\_ADMIN only. New referral rewards are blocked while inactive; earned rewards remain redeemable.

**Request payload(s):**

payload

```
{  
  "reason": "Temporarily paused by Super Admin."  
}
```

**Response body:**

```
{  
  "success": true,  
  "data": "<response returned by endpoint>",  
  "message": "Request completed successfully."  
}
```

**GET** /api/v1/referral-settings/stats

**Summary:** Fetch referral stats

**Allowed role/access:** SUPER\_ADMIN or ADMIN with referralSettings.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with referralSettings.read. SUPER\_ADMIN or ADMIN with referralSettings.read permission. SUPER\_ADMIN or ADMIN with referralSettings.read.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/referral-settings/audit-logs

**Summary:** List referral settings audit logs

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Referral settings audit logs. SUPER\_ADMIN only.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Refund Policy Settings

**GET** /api/v1/admin/refund-policy-settings

**Summary:** Fetch refund policy settings

**Allowed role/access:** SUPER\_ADMIN or ADMIN with refundPolicies.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with refundPolicies.read. SUPER\_ADMIN or ADMIN with refundPolicies.read permission. Settings feed refund eligibility, auto-refund, dispute, and provider refund workflows. SUPER\_ADMIN or ADMIN with refundPolicies.read. These global settings are used by refund eligibility, auto-refund, dispute decisions, and provider refund workflows. Only active gift categories are returned as eligible auto-refund categories; non-selected categories require manual review.

**Response body:**

```
{
  "success": true,
  "data": {
    "refundWindowDays": 30,
    "autoRefundThresholdAmount": 50,
    "currency": "PKR",
    "autoApproveSmallRefunds": true,
    "smallRefundAutoApproveAmount": 15,
    "eligibleCategories": [
      {
        "id": "category_electronics",
        "name": "Electronics"
      }
    ],
  },
}
```

```

    {
      "id": "category_apparel",
      "name": "Apparel"
    },
    {
      "id": "category_home_decor",
      "name": "Home Decor"
    }
  ],
  "lastUpdatedAt": "2026-05-14T10:00:00.000Z",
  "lastUpdatedBy": {
    "id": "admin_id",
    "name": "Alex Rivera"
  }
},
"message": "Refund policy settings fetched successfully."
}

```

**PATCH** /api/v1/admin/refund-policy-settings

**Summary:** Update refund policy settings

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Updates global refund rules. SUPER\_ADMIN only. Updates global refund policy settings used by customer refund request eligibility, small auto-refunds, provider refund handling, and admin/provider dispute workflows.

**Request payload(s):**

update

```

{
  "refundWindowDays": 30,
  "autoRefundThresholdAmount": 50,
  "currency": "PKR",
  "autoApproveSmallRefunds": true,
  "smallRefundAutoApproveAmount": 15,
  "eligibleCategoryIds": [
    "category_electronics",
    "category_apparel",
    "category_home_decor"
  ]
}

```

**Response body:**

```

{
  "success": true,
  "data": {
    "refundWindowDays": 30,
    "autoRefundThresholdAmount": 50,
    "currency": "PKR",
    "autoApproveSmallRefunds": true,
    "smallRefundAutoApproveAmount": 15,
    "eligibleCategoryIds": [
      "category_electronics",
      "category_apparel",
      "category_home_decor"
    ],
    "lastUpdatedAt": "2026-05-14T10:00:00.000Z"
  },
  "message": "Refund policy settings updated successfully."
}

```

**GET** /api/v1/admin/refund-policy-settings/logs

**Summary:** List refund policy audit logs

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Refund policy settings audit logs. SUPER\_ADMIN only. Returns compliance logs for REFUND\_POLICY\_SETTINGS\_UPDATED changes, including before/after policy JSON.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "audit_log_id",
      "action": "REFUND_POLICY_SETTINGS_UPDATED",
      "actor": {
        "id": "admin_id",
        "name": "Alex Rivera"
      },
      "before": {
        "refundWindowDays": 14,
        "autoRefundThresholdAmount": 25
      },
      "after": {
        "refundWindowDays": 30,
        "autoRefundThresholdAmount": 50
      },
      "createdAt": "2026-05-14T10:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Refund policy audit logs fetched successfully."
}
```

## 02 Admin - Media Upload Policy

**GET** /api/v1/media-upload-policy

**Summary:** Fetch global media upload policy

**Allowed role/access:** SUPER\_ADMIN or ADMIN with mediaPolicy.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with mediaPolicy.read. SUPER\_ADMIN or ADMIN with mediaPolicy.read permission. SUPER\_ADMIN or ADMIN with mediaPolicy.read. uploads/presigned-url enforces this policy before issuing upload URLs.

**Response body:**

```
{
  "success": true,
  "data": {
    "allowedFileTypes": {
```



```

        "jpeg": true,
        "jpg": true,
        "png": true,
        "gif": false,
        "mp4": true,
        "mov": true,
        "mp3": true,
        "wav": false,
        "svg": false
    },
    "maxImageSizeMb": 10,
    "maxVideoSizeMb": 500,
    "maxAudioSizeMb": 50,
    "scanUploads": true,
    "blockSvgUploads": true,
    "updatedAt": "2026-05-09T10:00:00.000Z",
    "updatedBy": {
        "id": "admin_id",
        "name": "Alex Rivera"
    }
},
"message": "Media upload policy fetched successfully."
}

```

**PATCH** /api/v1/media-upload-policy

**Summary:** Update global media upload policy

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Updates global media upload policy. SUPER\_ADMIN only. Does not expose AWS secrets or bucket credentials.

**Request payload(s):**

payload

```

{
  "allowedFileTypes": {
    "jpeg": true,
    "jpg": true,
    "png": true,
    "gif": false,
    "mp4": true,
    "mov": true,
    "mp3": true,
    "wav": false,
    "svg": false
  },
  "maxImageSizeMb": 10,
  "maxVideoSizeMb": 500,
  "maxAudioSizeMb": 50,
  "scanUploads": true,
  "blockSvgUploads": true
}

```

**Response body:**

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

**GET** /api/v1/media-upload-policy/audit-logs

**Summary:** List media upload policy audit logs

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Media upload policy audit logs. SUPER\_ADMIN only.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - System Settings

**GET** /api/v1/admin/system-settings

**Summary:** Fetch system settings

**Allowed role/access:** SUPER\_ADMIN or ADMIN with systemSettings.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with systemSettings.read. SUPER\_ADMIN or ADMIN with systemSettings.read permission. SMTP secrets are never returned. SUPER\_ADMIN or ADMIN with systemSettings.read. SMTP secrets are never returned.

**Response body:**

```
{
  "success": true,
  "data": {
    "platformInfo": {
      "applicationName": "Gift App",
      "supportEmail": "support@giftapp.com",
      "platformLogoUrl": "https://cdn.example.com/logo.png"
    },
    "security": {
      "sessionTimeoutMinutes": 30,
      "adminMfaRequired": true,
      "passwordPolicy": {
        "minLength": 8,
        "requireUppercase": true,
        "requireLowercase": true,
        "requireNumber": true,
        "requireSymbol": true
      }
    },
    "payments": {
      "defaultCurrency": "USD",
      "transactionFeePercent": 2.5
    },
    "notifications": {
      "pushNotificationsEnabled": true,
      "emailNotificationsEnabled": true,
      "smtpConfigured": true
    }
  },
}
```

```
"message": "System settings fetched successfully."
}
```

**PATCH** /api/v1/admin/system-settings

**Summary:** Update system settings

**Allowed role/access:** SUPER\_ADMIN or ADMIN with systemSettings.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with systemSettings.update. SUPER\_ADMIN or ADMIN with systemSettings.update permission. SUPER\_ADMIN or ADMIN with systemSettings.update. Session timeout and payment fee changes apply to future sessions/transactions only.

**Request payload(s):**

payload

```
{
  "platformInfo": {
    "applicationName": "Gift App",
    "supportEmail": "support@giftapp.com",
    "platformLogoUrl": "https://cdn.example.com/logo.png"
  },
  "security": {
    "sessionTimeoutMinutes": 30,
    "adminMfaRequired": true,
    "passwordPolicy": {
      "minLength": 8,
      "requireUppercase": true,
      "requireLowercase": true,
      "requireNumber": true,
      "requireSymbol": true
    }
  },
  "payments": {
    "defaultCurrency": "USD",
    "transactionFeePercent": 2.5
  },
  "notifications": {
    "pushNotificationsEnabled": true,
    "emailNotificationsEnabled": true
  }
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/system-settings/logo

**Summary:** Update system logo URL/reference

**Allowed role/access:** SUPER\_ADMIN or ADMIN with systemSettings.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with systemSettings.update. SUPER\_ADMIN or ADMIN with systemSettings.update permission. Stores logo URL/reference only. SUPER\_ADMIN or ADMIN with systemSettings.update. Provide a completed Storage upload reference when available; only URL/reference is stored.

**Request payload(s):**

payload

```
{
  "platformLogoUrl": "https://cdn.example.com/logo.png",
}
```

```
"uploadId": "upload_id"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/system-settings/smtp/test

**Summary:** Send SMTP test email

**Allowed role/access:** SUPER\_ADMIN or ADMIN with systemSettings.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with systemSettings.update. SUPER\_ADMIN or ADMIN with systemSettings.update permission. Does not expose SMTP secrets. SUPER\_ADMIN or ADMIN with systemSettings.update. Uses configured mailer and does not expose SMTP password or secrets.

**Request payload(s):**

payload

```
{
  "to": "admin@giftapp.com"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/system-settings/audit-logs

**Summary:** List system settings audit logs

**Allowed role/access:** SUPER\_ADMIN or ADMIN with systemSettings.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with systemSettings.read. SUPER\_ADMIN or ADMIN with systemSettings.read permission. SUPER\_ADMIN or ADMIN with systemSettings.read.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Guest Access Settings

**GET** /api/v1/admin/guest-access-settings

**Summary:** Fetch guest access settings

**Allowed role/access:** SUPER\_ADMIN or ADMIN with guestAccessSettings.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with guestAccessSettings.read. SUPER\_ADMIN or ADMIN with guestAccessSettings.read permission. SUPER\_ADMIN or ADMIN with guestAccessSettings.read.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/admin/guest-access-settings

**Summary:** Update guest access settings

**Allowed role/access:** SUPER\_ADMIN or ADMIN with guestAccessSettings.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with guestAccessSettings.update. SUPER\_ADMIN or ADMIN with guestAccessSettings.update permission. SUPER\_ADMIN or ADMIN with guestAccessSettings.update. Creates audit logs.

**Request payload(s):**

payload

```
{
  "guestAccessEnabled": true,
  "allowMarketplaceBrowsing": true,
  "allowMarketplaceHome": true,
  "allowGiftDetails": true,
  "allowDiscountedGifts": true,
  "allowFilterOptions": true,
  "allowProviderPreview": true,
  "allowWishlist": true,
  "allowCart": true,
  "allowCheckout": true,
  "sessionTtlMinutes": 1.0,
  "maxRequestsPerMinute": 1.0,
  "showExactStockToGuests": true,
  "showSkuToGuests": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/guest-access-settings/audit-logs

**Summary:** List guest access settings audit logs

**Allowed role/access:** SUPER\_ADMIN or ADMIN with guestAccessSettings.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with guestAccessSettings.read. SUPER\_ADMIN or ADMIN with guestAccessSettings.read permission. SUPER\_ADMIN or ADMIN with guestAccessSettings.read.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - System Logs & Audit Trail

**GET** /api/v1/audit-logs/stats

**Summary:** Fetch audit log stats

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. System log summary cards are restricted to Super Admin. SUPER\_ADMIN only. Returns system log summary cards and security/system metrics.

**Parameters:**

- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "criticalAlerts24h": 12,
    "dailyAverageActions": 4200,
    "uptimeStatus": 99.98,
    "totalLogs": 1240,
    "successCount": 1100,
    "failedCount": 140
  },
  "message": "Audit log stats fetched successfully."
}
```

**GET** /api/v1/audit-logs/action-types

**Summary:** Fetch audit log action types

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Audit log action filter options are restricted to Super Admin. SUPER\_ADMIN only. Returns action type dropdown options for System Logs filters.

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "key": "PROVIDER_APPROVED",
      "label": "Provider Approved"
    },
    {
      "key": "FAILED_LOGIN_ATTEMPT",
      "label": "Failed Login Attempt"
    }
  ],
  "message": "Audit log action types fetched successfully."
}
```

**GET** /api/v1/audit-logs/users

**Summary:** Fetch audit log user selector options

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Audit log actor selector options are restricted to Super Admin. SUPER\_ADMIN only. Returns actor/user selector options for System Logs filters.

**Parameters:**

- search (query, optional, string)
- role (query, optional, string)
- limit (query, optional, number)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "system",
      "name": "System",
      "email": null,
      "role": "SYSTEM",
      "label": "System Automated Action"
    },
    {
      "id": "admin_id",
      "name": "Sarah Chen",
      "email": "sarah@example.com",
      "role": "ADMIN",
      "label": "Sarah Chen — Compliance Officer"
    }
  ],
  "message": "Audit log users fetched successfully."
}
```

**GET** /api/v1/audit-logs/export

**Summary:** Export audit logs CSV

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Audit log export is restricted to Super Admin. SUPER\_ADMIN only. Exports sanitized audit log records using the same filters as the list API.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- actorId (query, optional, string)
- userId (query, optional, string)
- targetId (query, optional, string)
- action (query, optional, string)
- actionType (query, optional, string)
- targetType (query, optional, string)
- module (query, optional, string)
- status (query, optional, string)
- environment (query, optional, string)
- sourceIp (query, optional, string)
- from (query, optional, string)
- to (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

#### Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/audit-logs

**Summary:** List audit logs

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Audit logs are restricted to Super Admin. SUPER\_ADMIN only. Supports filtering by action type, actor, status, date range, module, and source IP.

#### Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- actorId (query, optional, string)
- userId (query, optional, string)
- targetId (query, optional, string)
- action (query, optional, string)
- actionType (query, optional, string)
- targetType (query, optional, string)
- module (query, optional, string)
- status (query, optional, string)
- environment (query, optional, string)
- sourceIp (query, optional, string)
- from (query, optional, string)
- to (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

#### Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "audit_log_id",
      "eventId": "EV-90210",
      "logReference": "789042",
      "timestamp": "2023-10-27T14:32:01.000Z",
      "actor": {
        "id": "admin_id",
        "name": "Sarah Chen",
        "role": "Compliance Officer",
        "avatarInitials": "SC"
      },
      "action": "PROVIDER_APPROVED",
      "actionLabel": "Provider Approved",
      "module": "Provider Management",
      "sourceIp": "192.168.1.45",
      "environment": "Production-Cluster-A",
      "status": "SUCCESS",
      "target": {
        "id": "provider_id",
        "type": "PROVIDER"
      }
    },
  ],
}
```



```

      "createdAt": "2023-10-27T14:32:01.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Audit logs fetched successfully"
}

```

**GET** /api/v1/audit-logs/{id}

**Summary:** Fetch audit log detail

**Allowed role/access:** SUPER\_ADMIN

**Notes:** Access: SUPER\_ADMIN. SUPER\_ADMIN only. Audit log details are restricted to Super Admin. SUPER\_ADMIN only. Returns sanitized raw JSON payloads, system response preview, and technical metadata.

**Parameters:**

- id (path, required, string)

**Response body:**

```

{
  "success": true,
  "data": {
    "id": "audit_log_id",
    "logReference": "789042",
    "eventId": "EV-90210",
    "timestamp": "2023-10-27T14:32:01.000Z",
    "status": "SUCCESS",
    "category": "AUDIT_TRAIL",
    "actor": {
      "id": "admin_id",
      "username": "super_admin_fintech",
      "name": "Super Admin",
      "role": "SUPER_ADMIN"
    },
    "actionType": "TRANSACTION_AUTHORIZATION",
    "module": "Transactions",
    "sourceIp": "192.168.1.104",
    "environment": "Production-Cluster-A",
    "target": {
      "id": "transaction_id",
      "type": "TRANSACTION"
    },
    "requestPayload": {
      "authorization": "[REDACTED]",
      "request_id": "req_550e8400"
    },
    "systemResponse": {
      "statusCode": 200,
      "durationMs": 142,
      "message": "Transaction authorized successfully."
    },
    "createdAt": "2023-10-27T14:32:01.000Z"
  },
  "message": "Audit log details fetched successfully"
}

```

## 02 Admin - Dispute Manager

**GET** /api/v1/admin/disputes/stats

**Summary:** Fetch dispute dashboard stats

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.read. SUPER\_ADMIN or ADMIN with disputes.read permission. SUPER\_ADMIN or ADMIN with disputes.read. Supports TODAY, LAST\_7\_DAYS, LAST\_30\_DAYS, and CUSTOM ranges.

**Parameters:**

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "openCases": 12,
    "openCasesDelta": 2,
    "awaitingAction": 5,
    "escalated": 2,
    "resolvedThisWeek": 24,
    "resolvedDeltaPercent": 12,
    "currency": "PKR"
  },
  "message": "Dispute stats fetched successfully."
}
```

**GET** /api/v1/admin/disputes/export

**Summary:** Export dispute cases

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.export

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.export. SUPER\_ADMIN or ADMIN with disputes.export permission. SUPER\_ADMIN or ADMIN with disputes.export. Sensitive card/payment secrets are never exported.

**Parameters:**

- status (query, optional, string)
- priority (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- format (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/disputes

**Summary:** List dispute queue

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.read. SUPER\_ADMIN or ADMIN with disputes.read permission. SUPER\_ADMIN or ADMIN with disputes.read. Used by Dispute & Refund Cases queue with filters and sorting.

**Parameters:**

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- priority (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "dispute_id",
      "caseId": "DIS-9842",
      "customer": {
        "id": "customer_id",
        "name": "Eleanor Pena",
        "email": "eleanor.p@gmail.com"
      },
      "transactionId": "TRX-78229410",
      "orderId": "order_id",
      "orderNumber": "ORD-88421",
      "amount": 492,
      "currency": "PKR",
      "priority": "HIGH",
      "status": "ESCALATED",
      "daysOpen": 8,
      "reason": "PRODUCT_NOT_RECEIVED",
      "createdAt": "2026-04-01T10:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Disputes fetched successfully."
}
```

**GET** /api/v1/admin/disputes/{id}/timeline

**Summary:** Fetch dispute timeline

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.read. SUPER\_ADMIN or ADMIN with disputes.read permission. SUPER\_ADMIN or ADMIN with disputes.timeline.read. Returns timeline preview events in chronological order.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": [
```

```
{
  "id": "timeline_id",
  "type": "DISPUTE_CREATED",
  "title": "Dispute Created",
  "description": "Customer created dispute for product not received.",
  "actor": {
    "type": "CUSTOMER",
    "name": "Jane Doe"
  },
  "createdAt": "2026-04-05T09:15:00.000Z"
},
{
  "message": "Dispute timeline fetched successfully."
}
```

**GET** /api/v1/admin/disputes/{id}/internal-data

**Summary:** Fetch internal transaction data

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.read. SUPER\_ADMIN or ADMIN with disputes.read permission. SUPER\_ADMIN or ADMIN with disputes.read. Includes payment status, refund eligibility, auth code, and order/provider transaction history without card secrets.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/disputes/{id}/notes

**Summary:** Fetch internal dispute notes

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.read. SUPER\_ADMIN or ADMIN with disputes.read permission. SUPER\_ADMIN or ADMIN with disputes.read. Returns internal notes only.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/disputes/{id}/notes

**Summary:** Add internal dispute note

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.notes.create

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.notes.create. SUPER\_ADMIN or ADMIN with disputes.notes.create permission. SUPER\_ADMIN or ADMIN with disputes.notes.create. Notes are internal-only and create audit/timeline entries.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

internal

```
{
  "note": "Customer tracking shows pending status for over 14 days. Investigating merchant log.",
  "visibility": "INTERNAL"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/disputes/{id}

**Summary:** Fetch dispute details and evidence review summary

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.read. SUPER\_ADMIN or ADMIN with disputes.read permission. SUPER\_ADMIN or ADMIN with disputes.read. SLA remaining text is computed from slaDeadlineAt; approaching deadline is true within 24 hours.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "dispute_id",
    "caseId": "DSP-1024",
    "status": "IN_REVIEW",
    "priority": "HIGH",
    "reason": "PRODUCT_NOT_RECEIVED",
    "amount": 129.99,
    "currency": "PKR",
    "sla": {
      "deadlineAt": "2026-04-12T10:00:00.000Z",
      "remainingText": "22h 14m remaining",
      "isApproachingDeadline": true
    },
    "customer": {
      "id": "customer_id",
      "name": "Jane Doe",
      "email": "jane.doe@example.com"
    },
    "transaction": {
      "id": "transaction_id",
      "transactionId": "TXN-789012",
      "paymentStatus": "CAPTURED",
      "processorAuthCode": "AUTH-9921-X",
      "amount": 129.99,
      "currency": "PKR"
    }
  },
}
```

```

    "refund": {
      "eligible": true,
      "eligibleReason": "Within refund window",
      "maxRefundAmount": 129.99
    },
    "claimDetails": "Item never arrived. Tracking shows delivered but not at my address.",
    "createdAt": "2026-04-05T09:15:00.000Z",
    "lastUpdatedAt": "2026-04-08T11:45:00.000Z"
  },
  "message": "Dispute details fetched successfully."
}

```

## 02 Admin - Dispute Evidence

**GET** /api/v1/admin/disputes/{id}/evidence

**Summary:** Fetch dispute evidence

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.read. SUPER\_ADMIN or ADMIN with disputes.read permission. SUPER\_ADMIN or ADMIN with disputes.evidence.read. Returns only evidence rows linked to this dispute, from customer/admin uploads in dispute-evidence folder.

**Parameters:**

- id (path, required, string)

**Response body:**

```

{
  "success": true,
  "data": [
    {
      "id": "evidence_id",
      "fileName": "Order confirmation.pdf",
      "fileUrl": "https://cdn.yourdomain.com/dispute-evidence/order-confirmation.pdf",
      "contentType": "application/pdf",
      "uploadedBy": "CUSTOMER",
      "createdAt": "2026-04-05T09:30:00.000Z"
    }
  ],
  "message": "Dispute evidence fetched successfully."
}

```

## 02 Admin - Dispute Linkage

**GET** /api/v1/admin/disputes/{id}/linkage

**Summary:** Fetch current dispute transaction linkage state

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.read. SUPER\_ADMIN or ADMIN with disputes.read permission. SUPER\_ADMIN or ADMIN with disputes.read. Shows dispute summary, linked transaction, and current refund selection without card secrets.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "dispute": {
      "id": "dispute_id",
      "caseId": "DSP-1024",
      "customer": {
        "id": "customer_id",
        "name": "Jane Doe"
      },
      "disputeAmount": 129.99,
      "currency": "PKR",
      "claimDetails": "Item never arrived. Tracking shows delivered but not at my address.",
      "status": "IN_REVIEW"
    },
    "linkedTransaction": {
      "id": "transaction_id",
      "transactionId": "TXN-789012",
      "orderId": "order_id",
      "orderDate": "2026-04-01T00:00:00.000Z",
      "paymentMethod": "VISA **** 1234",
      "amount": 129.99,
      "currency": "PKR",
      "status": "SETTLED",
      "refundEligible": true,
      "eligibilityText": "Eligible within 30-day window"
    },
    "refundSelection": {
      "type": "FULL",
      "amount": 129.99,
      "recommended": true
    }
  },
  "message": "Dispute linkage fetched successfully."
}
```

**GET** /api/v1/admin/disputes/{id}/transaction-search

**Summary:** Search original transaction for a dispute

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.read. SUPER\_ADMIN or ADMIN with disputes.read permission. SUPER\_ADMIN or ADMIN with disputes.read. Search is scoped to the dispute customer where possible and never exposes card secrets.

**Parameters:**

- id (path, required, string)
- query (query, optional, string)
- recentOnly (query, optional, boolean)
- limit (query, optional, number)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/disputes/{id}/link-transaction

**Summary:** Confirm dispute transaction linkage

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.linkTransaction

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.linkTransaction. SUPER\_ADMIN or ADMIN with disputes.linkTransaction permission. SUPER\_ADMIN or ADMIN with disputes.linkTransaction. Stores linked transaction/payment/order and refund selection, creates timeline/audit records, and does not process refunds.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

full

```
{
  "transactionId": "transaction_id",
  "refundType": "FULL",
  "refundAmount": 129.99,
  "confirmCorrectTransaction": true
}
```

none

```
{
  "transactionId": "transaction_id",
  "refundType": "NONE",
  "confirmCorrectTransaction": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/disputes/{id}/refund-preview

**Summary:** Preview dispute refund selection

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.refund.evaluate

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.refund.evaluate. SUPER\_ADMIN or ADMIN with disputes.refund.evaluate permission. SUPER\_ADMIN or ADMIN with disputes.refund.evaluate. Validates requested refunds against paid amount, prior refunds, and refund window without processing a refund.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

full

```
{
  "transactionId": "transaction_id",
  "refundType": "FULL",
  "refundAmount": 129.99
}
```

partial

```
{
  "transactionId": "transaction_id",
```



```
"refundType": "PARTIAL",
"refundAmount": 50
}
```

none

```
{
  "transactionId": "transaction_id",
  "refundType": "NONE"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Dispute Decisions

**GET** /api/v1/admin/disputes/{id}/decision-summary

**Summary:** Fetch dispute decision summary

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.decide

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.decide. SUPER\_ADMIN or ADMIN with disputes.decide permission. SUPER\_ADMIN or ADMIN with disputes.decide. Summarizes customer, transaction, refund eligibility, and case history before final decision.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/disputes/{id}/decision

**Summary:** Submit final dispute decision

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.decide plus action-specific permission (approve/reject/escalate)

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.decide plus action-specific permission (approve/reject/escalate). SUPER\_ADMIN or ADMIN with disputes.decide and the action-specific permission as applicable. SUPER\_ADMIN or ADMIN with dispute decision permissions. APPROVE validates linked transaction/refund selection and creates a refund record; REJECT never creates a refund; ESCALATE assigns supervisor and resets SLA. Stripe refunds are represented by refund tracking records and no card/Stripe secrets are exposed.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

approve

```
{
  "decision": "APPROVE",
  "comment": "Customer evidence validates missing delivery.",
  "notifyCustomer": true
}
```

reject

```
{
  "decision": "REJECT",
  "reason": "INSUFFICIENT_EVIDENCE",
  "comment": "Tracking evidence confirms delivery.",
  "notifyCustomer": true
}
```

escalate

```
{
  "decision": "ESCALATE",
  "assignedToId": "admin_supervisor_id",
  "escalationReason": "Policy ambiguity requires supervisor intervention.",
  "notifyCustomer": false
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/disputes/{id}/confirmation

**Summary:** Fetch decision confirmation

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.decide

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.decide. SUPER\_ADMIN or ADMIN with disputes.decide permission. SUPER\_ADMIN or ADMIN with disputes.decide. Returns refund, processor, protocol, and customer notification confirmation.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Dispute Tracking

**GET** /api/v1/admin/disputes/{id}/tracking-log/export

**Summary:** Export full dispute tracking log

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.tracking.export

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.tracking.export. SUPER\_ADMIN or ADMIN with disputes.tracking.export permission. SUPER\_ADMIN or ADMIN with disputes.tracking.export. Includes timeline, decision, refund, notifications, and internal notes without card or Stripe secrets.

**Parameters:**

- id (path, required, string)
- format (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/disputes/{id}/tracking-log

**Summary:** Fetch full dispute tracking log

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.tracking.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.tracking.read. SUPER\_ADMIN or ADMIN with disputes.tracking.read permission. SUPER\_ADMIN or ADMIN with disputes.tracking.read. Returns secure audit timeline, customer notifications, and internal notes.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "caseId": "DSP-1024",
    "customer": {
      "name": "Jane Doe"
    },
    "finalStatus": "APPROVED",
    "lastUpdatedAt": "2026-04-08T11:45:00.000Z",
    "secureAuditActive": true,
    "timeline": [
      {
        "id": "timeline_id",
        "type": "REFUND_PROCESSED",
        "title": "System Automated Action",
        "description": "Refund processed successfully.",
        "amount": 129.99,
        "refundId": "RF-45678",
        "createdAt": "2026-04-08T11:45:00.000Z"
      }
    ],
    "customerNotifications": [
      {
        "type": "REFUND_CONFIRMATION_EMAIL",
        "status": "DELIVERED",
        "deliveredAt": "2026-04-08T11:46:00.000Z"
      }
    ],
    "internalNotes": [
      {
        "id": "note_id",
        "author": "Alex Morgan",
        "note": "Customer tracking shows pending status for over 14 days.",
        "createdAt": "2026-04-08T10:00:00.000Z"
      }
    ]
  }
}
```

```
}
]
},
"message": "Case tracking log fetched successfully."
}
```

**POST** /api/v1/admin/disputes/{id}/follow-up-notes

**Summary:** Add dispute follow-up note

**Allowed role/access:** SUPER\_ADMIN or ADMIN with disputes.notes.create

**Notes:** Access: SUPER\_ADMIN or ADMIN with disputes.notes.create. SUPER\_ADMIN or ADMIN with disputes.notes.create permission. SUPER\_ADMIN or ADMIN with disputes.notes.create. Adds internal note, tracking timeline entry, and notifies assigned admin when present.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

internal

```
{
  "note": "Followed up with provider for missing dispatch log.",
  "visibility": "INTERNAL"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Provider Dispute Manager

**GET** /api/v1/admin/provider-disputes/stats

**Summary:** Fetch provider dispute dashboard stats

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.read. SUPER\_ADMIN or ADMIN with providerDisputes.read permission. SUPER\_ADMIN or ADMIN with providerDisputes.read. Reuses Provider Orders, Payments, Notifications, Audit Logs, and dispute patterns.

**Parameters:**

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "criticalOpenCases": 8,
    "evidencePhase": 3,
    "underReview": 4,
    "escalations": 1,
    "resolvedThisWeek": 14,
    "averageClosureTimeDays": 4.2,
  }
}
```

```

    "topConflictSource": {
      "providerName": "Acme Corp",
      "category": "Quality Disputes",
      "percentOfTotal": 65
    },
    "systemHealth": {
      "status": "STABLE",
      "message": "All nodes stable",
      "apiLatencyMs": 42
    }
  },
  "message": "Provider dispute stats fetched successfully."
}

```

**GET** /api/v1/admin/provider-disputes/export

**Summary:** Export provider dispute queue

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.export

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.export. SUPER\_ADMIN or ADMIN with providerDisputes.export permission. SUPER\_ADMIN or ADMIN with providerDisputes.export. Does not expose card secrets or unrelated uploads.

**Parameters:**

- status (query, optional, string)
- severity (query, optional, string)
- category (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- format (query, optional, string)

**Response body:**

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

**GET** /api/v1/admin/provider-disputes

**Summary:** List provider dispute queue

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.read. SUPER\_ADMIN or ADMIN with providerDisputes.read permission. SUPER\_ADMIN or ADMIN with providerDisputes.read. Used by Provider Dispute Case Queue with filters and sorting.

**Parameters:**

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- providerId (query, optional, string)
- category (query, optional, string)
- severity (query, optional, string)
- status (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

#### Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "provider_dispute_id",
      "caseId": "PRV-101",
      "provider": {
        "id": "provider_id",
        "businessName": "Acme Corp",
        "contactName": "John Smith",
        "tier": "Gold Partner"
      },
      "customer": {
        "id": "customer_id",
        "name": "Michael Chen"
      },
      "transaction": {
        "id": "transaction_id",
        "transactionId": "TXN-998",
        "status": "VERIFIED"
      },
      "category": "NON_DELIVERY",
      "amount": 650,
      "currency": "PKR",
      "status": "RULING_PENDING",
      "priority": "HIGH",
      "riskAssessment": "HIGH",
      "daysOpen": 5,
      "createdAt": "2026-04-05T10:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Provider disputes fetched successfully."
}
```

**GET** /api/v1/admin/provider-disputes/{id}/timeline

**Summary:** Fetch provider dispute timeline

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.read. SUPER\_ADMIN or ADMIN with providerDisputes.read permission. SUPER\_ADMIN or ADMIN with providerDisputes.read. Includes provider dispute creation, evidence submission, requests, and review actions.

#### Parameters:

- id (path, required, string)

#### Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/provider-disputes/{id}/notes

**Summary:** Fetch provider dispute internal notes

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.read. SUPER\_ADMIN or ADMIN with providerDisputes.read permission. SUPER\_ADMIN or ADMIN with providerDisputes.read. Returns internal reviewer notes only.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/provider-disputes/{id}/notes

**Summary:** Add provider dispute internal note

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.notes.create

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.notes.create. SUPER\_ADMIN or ADMIN with providerDisputes.notes.create permission. SUPER\_ADMIN or ADMIN with providerDisputes.notes.create. Creates internal note, timeline entry, and audit log.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

internal

```
{
  "note": "Provider failed to submit required photographic proof.",
  "visibility": "INTERNAL"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/provider-disputes/{id}

**Summary:** Fetch provider dispute details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.read. SUPER\_ADMIN or ADMIN with providerDisputes.read permission. SUPER\_ADMIN or ADMIN with providerDisputes.read. Reuses Provider Orders, Customer Orders, Payments, Notifications, Storage, and Audit Logs. No card/payment secrets are exposed.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": {
```

```

    "id": "provider_dispute_id",
    "caseId": "PD-2047",
    "status": "EVIDENCE_PHASE",
    "priority": "MEDIUM",
    "category": "NON_DELIVERY",
    "reason": "Missing delivery evidence",
    "claimType": "Non-Delivery",
    "amount": 89.99,
    "currency": "PKR",
    "provider": {
      "id": "provider_id",
      "businessName": "FreshGrocer Supplies",
      "providerCode": "PRV-8923",
      "tier": "Gold Partner",
      "currentPayoutBalance": -127.5,
      "disputeCount": 4,
      "winRate": 50
    },
    "customer": {
      "id": "customer_id",
      "name": "Michael Chen",
      "email": "michael@example.com"
    },
    "order": {
      "id": "order_id",
      "orderNumber": "ORD-45678"
    },
    "transaction": {
      "id": "transaction_id",
      "transactionId": "TXN-789012",
      "grossTransaction": 89.99,
      "providerShare": 67.49,
      "platformFee": 22.5,
      "refundEligible": true,
      "eligibilityText": "Within the standard 14-day resolution window."
    },
    "customerStatement": "I stayed home all day waiting for the delivery. I got a notification saying it was delivered, but nothing was at my door.",
    "riskAlert": {
      "enabled": true,
      "message": "FreshGrocer Supplies has a 60% dispute rate over the last 30 days."
    },
    "createdAt": "2026-04-05T10:00:00.000Z"
  },
  "message": "Provider dispute details fetched successfully."
}

```

## 02 Admin - Provider Dispute Evidence

**GET** /api/v1/admin/provider-disputes/{id}/evidence

**Summary:** Fetch provider dispute evidence exchange

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.read. SUPER\_ADMIN or ADMIN with providerDisputes.read permission. SUPER\_ADMIN or ADMIN with providerDisputes.read. Returns customer/provider evidence linked to providerDisputeId only, reusing Storage and media policy.

**Parameters:**

- id (path, required, string)

**Response body:**



```
{
  "success": true,
  "data": {
    "caseId": "PD-2047",
    "reviewStatus": {
      "startedBy": "A. Marcus",
      "startedAt": "2026-04-08T09:00:00.000Z",
      "isComplete": false
    },
    "customerEvidence": {
      "submittedAt": "2026-04-05T10:00:00.000Z",
      "status": "RECEIVED",
      "narrative": "The package was never delivered to my doorstep despite tracking saying otherwise.",
      "files": [
        {
          "id": "evidence_file_id",
          "fileName": "Order confirmation screenshot.pdf",
          "fileUrl": "https://cdn.yourdomain.com/provider-dispute-evidence/order-confirmation.pdf",
          "contentType": "application/pdf",
          "sizeText": "1.2 MB",
          "category": "PDF Document"
        }
      ]
    },
    "providerEvidence": {
      "submittedAt": "2026-04-07T10:00:00.000Z",
      "status": "RECEIVED_LATE",
      "lateText": "+2 days past deadline",
      "narrative": "Delivery was completed at 2:14 PM. GPS coordinates and driver logs confirm arrival.",
      "files": [
        {
          "id": "evidence_file_id_4",
          "fileName": "GPS coordinates at delivery.json",
          "fileUrl": "https://cdn.yourdomain.com/provider-dispute-evidence/gps.json",
          "contentType": "application/json",
          "sizeText": "4 KB",
          "category": "Metadata File"
        }
      ]
    },
    "internalReviewerNotes": "Document your findings here. These notes are only visible to internal staff."
  },
  "message": "Provider dispute evidence fetched successfully."
}
```

**POST** /api/v1/admin/provider-disputes/{id}/evidence/request

**Summary:** Request additional provider dispute evidence

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.evidence.request

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.evidence.request. SUPER\_ADMIN or ADMIN with providerDisputes.evidence.request permission. SUPER\_ADMIN or ADMIN with providerDisputes.evidence.request. Creates timeline and optional notifications without changing final ruling.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

provider

```
{
  "target": "PROVIDER",
  "message": "Please upload photographic proof of delivery and driver log.",
  "dueAt": "2026-04-09T18:00:00.000Z",
  "notifyTarget": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/provider-disputes/{id}/evidence/mark-reviewed

**Summary:** Mark provider dispute evidence review complete

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.update. SUPER\_ADMIN or ADMIN with providerDisputes.update permission. SUPER\_ADMIN or ADMIN with providerDisputes.update. Marks evidence review complete, moves case to RULING\_PENDING, creates timeline and audit log.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

review

```
{
  "reviewerNotes": "Provider evidence is incomplete. GPS data was submitted late and lacks photo confirmation.",
  "nextStep": "RULING"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Provider Dispute Rulings

**GET** /api/v1/admin/provider-disputes/{id}/ruling-summary

**Summary:** Fetch provider dispute ruling summary

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.ruling.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.ruling.read. SUPER\_ADMIN or ADMIN with providerDisputes.ruling.read permission. SUPER\_ADMIN or ADMIN with providerDisputes.ruling.read. Shows ruling options, evidence summary, and financial starting point.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/provider-disputes/{id}/ruling

**Summary:** Save provider dispute ruling

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.ruling.create

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.ruling.create. SUPER\_ADMIN or ADMIN with providerDisputes.ruling.create permission. SUPER\_ADMIN or ADMIN with providerDisputes.ruling.create. Stores ruling and reason, but final financial execution remains gated behind final status update/attestation.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

full

```
{
  "ruling": "CUSTOMER_WINS_FULL_REFUND",
  "rulingReason": "Provider failed to provide required proof of delivery.",
  "refundAmount": 89.99,
  "applyPenalty": true,
  "penaltyAmount": 25,
  "penaltyReason": "Repeat offense",
  "saveAsDraft": false
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Provider Financial Adjustments

**GET** /api/v1/admin/provider-disputes/{id}/financial-impact

**Summary:** Fetch provider dispute financial impact

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.financial.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.financial.read. SUPER\_ADMIN or ADMIN with providerDisputes.financial.read permission. SUPER\_ADMIN or ADMIN with providerDisputes.financial.read. Server calculates provider share, fee reversal, refund, and penalty impact.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "caseId": "PD-2047",
    "ruling": "CUSTOMER_WINS_FULL_REFUND",
  }
}
```

```

"providerAccountPreview": {
  "currentBalance": 340.5,
  "pendingPayout": 210.0,
  "newBalance": 225.51,
  "currency": "PKR"
},
"breakdown": [
  {
    "lineItem": "Order Total",
    "adjustment": 89.99,
    "runningTotal": 89.99
  },
  {
    "lineItem": "Customer Refund",
    "adjustment": -89.99,
    "runningTotal": 0
  },
  {
    "lineItem": "Provider Lost Earnings",
    "adjustment": -67.49,
    "runningTotal": -67.49
  },
  {
    "lineItem": "Platform Fee Reversal",
    "adjustment": -22.5,
    "runningTotal": -89.99
  },
  {
    "lineItem": "Penalty Fee",
    "adjustment": -25.0,
    "runningTotal": -114.99
  }
],
"totalProviderDeduction": 114.99
},
"message": "Financial impact fetched successfully."
}

```

**POST** /api/v1/admin/provider-disputes/{id}/payout-penalty-linkage

**Summary:** Link payout and penalty adjustments

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.financial.link

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.financial.link. SUPER\_ADMIN or ADMIN with providerDisputes.financial.link permission. SUPER\_ADMIN or ADMIN with providerDisputes.financial.link. Creates provider financial adjustment ledgers; final financial execution is still deferred.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

deduct

```

{
  "adjustmentType": "DEDUCT_FROM_NEXT_PAYOUT",
  "confirmFinancialAccuracy": true,
  "sendProviderSummary": true
}

```

**Response body:**

```

{
  "success": true,

```

```
"data": "<response returned by endpoint>",
"message": "Request completed successfully."
}
```

**POST** /api/v1/admin/provider-disputes/{id}/final-attestation

**Summary:** Complete final financial attestation

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.ruling.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.ruling.update. SUPER\_ADMIN or ADMIN with providerDisputes.ruling.update permission. SUPER\_ADMIN or ADMIN with providerDisputes.ruling.update. Confirms line items and marks case ready for final status update.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

confirm

```
{
  "confirmFinancialLineItems": true,
  "sendAutomatedFinancialSummary": true,
  "comment": "All financial line items confirmed as accurate."
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Provider Dispute Resolution

**POST** /api/v1/admin/provider-disputes/{id}/finalize

**Summary:** Finalize provider dispute

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.resolve

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.resolve. SUPER\_ADMIN or ADMIN with providerDisputes.resolve permission. SUPER\_ADMIN or ADMIN with providerDisputes.resolve. Executes final refund/deduction application, updates immutable resolution state, creates financial and communication logs, and opens provider appeal window.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

finalize

```
{
  "notifyCustomer": true,
  "notifyProvider": true,
  "executeFinancialAdjustments": true,
  "comment": "Final ruling confirmed and financial adjustments approved."
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/provider-disputes/{id}/resolution

**Summary:** Fetch provider dispute resolution summary

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.resolve

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.resolve. SUPER\_ADMIN or ADMIN with providerDisputes.resolve permission. SUPER\_ADMIN or ADMIN with providerDisputes.resolve. Returns final ruling, financial execution, notification status, refund timing, and appeal window.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/admin/provider-disputes/{id}/notify-again

**Summary:** Resend provider dispute notifications

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.notify

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.notify. SUPER\_ADMIN or ADMIN with providerDisputes.notify permission. SUPER\_ADMIN or ADMIN with providerDisputes.notify. Resends email/in-app notifications, creates communication log entries, and writes a timeline event.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

provider

```
{
  "target": "PROVIDER",
  "channels": [
    "EMAIL",
    "IN_APP"
  ],
  "message": "Reminder: Your dispute resolution is available in the provider portal."
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 02 Admin - Provider Dispute Logs

**GET** /api/v1/admin/provider-disputes/{id}/resolution-log/export

**Summary:** Export provider dispute resolution log

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.logs.export

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.logs.export. SUPER\_ADMIN or ADMIN with providerDisputes.logs.export permission. SUPER\_ADMIN or ADMIN with providerDisputes.logs.export. Includes lifecycle timeline, financial audit log, communication log, ruling, and final status without Stripe/card secrets.

**Parameters:**

- id (path, required, string)
- format (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/admin/provider-disputes/{id}/resolution-log

**Summary:** Fetch provider dispute resolution log

**Allowed role/access:** SUPER\_ADMIN or ADMIN with providerDisputes.logs.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with providerDisputes.logs.read. SUPER\_ADMIN or ADMIN with providerDisputes.logs.read permission. SUPER\_ADMIN or ADMIN with providerDisputes.logs.read. Returns lifecycle timeline, financial audit log, communication log, and performance impact snapshot.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "caseId": "PD-2047",
    "finalRuling": "CUSTOMER_WINS",
    "closedAt": "2026-10-24T00:00:00.000Z",
    "description": "Complete audit trail of provider dispute, financial adjustments, and communications.",
    "lifecycleTimeline": [
      {
        "type": "PENALTY_APPLIED",
        "title": "Penalty Applied",
        "description": "System-generated penalty of 500.00 applied to provider.",
        "createdAt": "2026-10-24T14:22:00.000Z"
      }
    ],
    "financialAuditLog": [
      {
        "transactionId": "TXN_29048-REV",
        "action": "Reversal Execution",
        "amount": -1240.0,
        "currency": "PKR",
        "status": "SUCCESS"
      }
    ],
    "communicationLog": [
      {

```

```

        "type": "EMAIL",
        "title": "Resolution Decision Sent",
        "to": "claims@provider.com",
        "bodyPreview": "The evidence provided failed to meet...",
        "createdAt": "2026-10-24T10:00:00.000Z"
    }
],
"providerPerformanceImpact": {
    "winRateBefore": 50,
    "winRateAfter": 40,
    "penaltyPoints": 15,
    "tierStatus": "Silver At Risk"
}
},
"message": "Provider dispute resolution log fetched successfully."
}

```

## 03 Provider - Dashboard

**GET** /api/v1/provider/dashboard

**Summary:** Fetch mobile provider dashboard

**Allowed role/access:** Authenticated

**Notes:** Access: Authenticated. Authenticated JWT required. PROVIDER only. providerId is derived from JWT. Pending, rejected, inactive, or suspended providers cannot access the dashboard.

**Response body:**

```

{
  "success": true,
  "data": {
    "provider": {
      "id": "provider_id",
      "businessName": "Global Logistics Solutions",
      "avatarUrl": "https://cdn.yourdomain.com/provider-avatars/provider.png",
      "approvalStatus": "APPROVED",
      "status": "ACTIVE"
    },
    "operationalSummary": {
      "todayOrders": 24,
      "pendingOrders": 12,
      "activeOffers": 5,
      "totalItems": 128
    },
    "performance": {
      "range": "WEEKLY",
      "labels": [
        "Mon",
        "Tue",
        "Wed",
        "Thu",
        "Fri",
        "Sat",
        "Sun"
      ],
      "values": [
        120,
        180,
        150,
        110,
        190,

```



```

        260,
        220
    ],
    "currency": "PKR"
},
"recentOrders": [
    {
        "id": "provider_order_id",
        "orderNumber": "ORD-8821",
        "itemName": "Nike Air Max 270",
        "imageUrl": "https://cdn.yourdomain.com/gifts/shoe.png",
        "amount": 120,
        "currency": "PKR",
        "status": "PAID",
        "createdAgoText": "2m ago"
    }
]
},
"message": "Provider dashboard fetched successfully."
}

```

### 03 Provider - Earnings

**GET** /api/v1/provider/earnings/summary

**Summary:** Fetch own provider earnings summary

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. providerId is derived from JWT.

**Parameters:**

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

**GET** /api/v1/provider/earnings/chart

**Summary:** Fetch own provider earnings chart

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Uses provider earnings ledger.

**Parameters:**

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```

{
  "success": true,

```

```
"data": "<response returned by endpoint>",
"message": "Request completed successfully."
}
```

**GET** /api/v1/provider/earnings/ledger

**Summary:** List own provider earnings ledger

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Does not accept providerId query/body.

**Parameters:**

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)
- type (query, optional, string)
- status (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 03 Provider - Business Info

**GET** /api/v1/provider/business-info

**Summary:** Fetch own provider business information

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. providerId is derived from JWT.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/provider/business-info

**Summary:** Update own provider business information

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Cannot set approvalStatus/isActive; material business changes require verification review.

**Request payload(s):**

payload

```
{
  "businessName": "Global Logistics Solutions",
}
```

```
"legalName": "Global Logistics Solutions LLC",
"taxId": "XX-XXXXXXX",
"businessCategoryId": "category_id",
"email": "ops@globallogistics.com",
"phone": "+1 (555) 012-3456",
"businessAddress": "123 Main Street",
"serviceArea": "New York, USA",
"headquarters": "New York, USA",
"website": "https://www.sylviabond.com",
"storeAddress": {
  "line1": "842 Industrial Way, Suite 102",
  "city": "San Francisco",
  "state": "CA",
  "country": "USA",
  "postalCode": "94107",
  "latitude": 37.7749,
  "longitude": -122.4194
},
"businessHours": [
  {
    "day": "MONDAY",
    "isOpen": true,
    "openTime": "09:00",
    "closeTime": "18:00"
  }
],
"fulfillmentMethods": [
  "PICKUP"
],
"autoAcceptOrders": false
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 03 Provider - Reviews

**GET** /api/v1/provider/reviews/summary

**Summary:** Fetch provider rating summary

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. Provider can access only own reviews. PROVIDER only. Uses shared Review records visible to provider/customer/admin modules.

**Response body:**

```
{
  "success": true,
  "data": {
    "averageRating": 4.8,
    "reviewCount": 128,
    "distribution": {
      "1": 1,
      "2": 2,
      "3": 5,
      "4": 12,
```

```
      "5": 80
    }
  },
  "message": "Review summary fetched successfully."
}
```

**GET** /api/v1/provider/reviews/filter-options

**Summary:** Fetch provider review filter options

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. PROVIDER only. Declared before /provider/reviews/:id.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/reviews

**Summary:** List provider reviews

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. Provider can access only own reviews. PROVIDER only. Shows only reviews for own provider account/orders and excludes hidden/removed reviews.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- rating (query, optional, number)
- hasResponse (query, optional, boolean)
- search (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "review_id",
      "orderId": "order_id",
      "orderNumber": "ORD-45678",
      "customer": {
        "id": "customer_id",
        "name": "Michael Chen",
        "avatarUrl": null
      },
      "rating": 5,
      "comment": "Great packaging and timely delivery.",
      "createdAt": "2026-04-08T10:00:00.000Z",
      "isNew": true,
      "likesCount": 3,
      "response": {
        "id": "response_id",
        "body": "Thank you for your feedback!",
        "createdAt": "2026-04-08T11:00:00.000Z"
      }
    }
  ]
}
```

```
],
"meta": {
  "page": 1,
  "limit": 20,
  "total": 1,
  "totalPages": 1
},
"message": "Reviews fetched successfully."
}
```

**GET** /api/v1/provider/reviews/{id}

**Summary:** Fetch Provider Reviews details

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. Provider can access only own reviews.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "review_id",
    "rating": 5,
    "comment": "Great packaging and timely delivery.",
    "customer": {
      "id": "customer_id",
      "name": "Michael Chen",
      "avatarUrl": null
    },
    "order": {
      "id": "order_id",
      "orderNumber": "ORD-45678",
      "createdAt": "2026-04-08T09:00:00.000Z"
    },
    "response": {
      "id": "response_id",
      "body": "Thank you for your feedback!",
      "createdAt": "2026-04-08T11:00:00.000Z"
    }
  },
  "message": "Review fetched successfully."
}
```

**POST** /api/v1/provider/reviews/{id}/response

**Summary:** Post public review response

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. Provider can respond only to own reviews. PROVIDER only. Provider can respond only to own review. Only one active public response per review.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "body": "Thank you for your kind words, Sarah. We are happy you loved the packaging."
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/provider/reviews/{id}/response

**Summary:** Update public review response

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. Provider can update only own review responses. PROVIDER only. Updates only provider's own active response; customer review content is never modified.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "body": "Thank you for your kind words, Sarah. We are happy you loved the packaging."
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/provider/reviews/{id}/response

**Summary:** Delete public review response

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. Provider can delete only own review responses. PROVIDER only. Deletes only the provider's own response and does not delete the original customer review.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```

```
"message": "Request completed successfully."  
}
```

## 03 Provider - Inventory

**GET** /api/v1/provider/inventory

**Summary:** List provider inventory items

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Pending providers cannot access inventory. Provider inventory items do not require separate admin approval; visibility depends on approved/active provider plus item active, available, in stock, and not deleted.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- categoryId (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "gift_id",
      "name": "Luxury Perfume",
      "price": 99.99,
      "currency": "PKR",
      "stockQuantity": 50,
      "status": "ACTIVE",
      "moderationStatus": "NOT_REQUIRED",
      "isAvailable": true,
      "category": {
        "id": "category_id",
        "name": "Perfumes"
      },
      "variants": [
        {
          "id": "variant_id",
          "name": "50ml",
          "price": 129.99,
          "stockQuantity": 20,
          "isDefault": true
        }
      ]
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Provider inventory fetched successfully"
}
```

**POST** /api/v1/provider/inventory

**Summary:** Create provider inventory item with optional nested variants

**Allowed role/access:** PROVIDER



**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Pending providers cannot access this module. Provider inventory items do not require separate admin approval; approved active providers can create active, available inventory directly.

**Request payload(s):**

withVariants

```
{
  "name": "Luxury Perfume",
  "description": "Long-lasting premium fragrance.",
  "shortDescription": "Premium fragrance gift.",
  "categoryId": "gift_category_id",
  "price": 99.99,
  "currency": "PKR",
  "stockQuantity": 50,
  "sku": "PERFUME-001",
  "imageUrls": [
    "https://cdn.yourdomain.com/gift-images/perfume.png"
  ],
  "isAvailable": true,
  "variants": [
    {
      "name": "30ml",
      "price": 89.99,
      "originalPrice": 119.99,
      "stockQuantity": 10,
      "sku": "PERFUME-30ML",
      "isPopular": false,
      "isDefault": false,
      "sortOrder": 1,
      "isActive": true
    },
    {
      "name": "50ml",
      "price": 129.99,
      "originalPrice": 159.99,
      "stockQuantity": 20,
      "sku": "PERFUME-50ML",
      "isPopular": true,
      "isDefault": true,
      "sortOrder": 2,
      "isActive": true
    }
  ]
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume",
    "price": 99.99,
    "currency": "PKR",
    "stockQuantity": 50,
    "status": "ACTIVE",
    "moderationStatus": "NOT_REQUIRED",
    "variants": [
      {
        "id": "variant_id",
        "name": "50ml",
        "price": 129.99,
        "originalPrice": 159.99,
```

```
        "stockQuantity": 20,
        "sku": "PERFUME-50ML",
        "isDefault": true,
        "isActive": true
      }
    ]
  },
  "message": "Inventory item created successfully"
}
```

**GET** /api/v1/provider/inventory/stats

**Summary:** Fetch provider inventory stats

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/inventory/lookup

**Summary:** Lookup active provider inventory items

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Gift moderation approval is not required for provider inventory lookup.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/inventory/{id}

**Summary:** Fetch own provider inventory item details

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume",
    "description": "Long-lasting premium fragrance.",
    "price": 99.99,
    "currency": "PKR",
    "stockQuantity": 50,
  }
}
```

```

    "status": "ACTIVE",
    "moderationStatus": "NOT_REQUIRED",
    "imageUrls": [
      "https://cdn.yourdomain.com/gift-images/perfume.png"
    ],
    "variants": [
      {
        "id": "variant_id",
        "name": "50ml",
        "price": 129.99,
        "originalPrice": 159.99,
        "stockQuantity": 20,
        "sku": "PERFUME-50ML",
        "isDefault": true,
        "isActive": true
      }
    ]
  },
  "message": "Inventory item fetched successfully"
}

```

**PATCH** /api/v1/provider/inventory/{id}

**Summary:** Update own provider inventory item and upsert variants

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Variant id must belong to the provider-owned gift. Price, name, media, and variant changes do not reset provider inventory to pending moderation.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

upsertVariants

```

{
  "replaceVariants": false,
  "variants": [
    {
      "id": "variant_id",
      "name": "50ml",
      "price": 129.99,
      "originalPrice": 159.99,
      "stockQuantity": 20,
      "sku": "PERFUME-50ML",
      "isPopular": true,
      "isDefault": true,
      "sortOrder": 2,
      "isActive": true
    },
    {
      "name": "150ml",
      "price": 249.99,
      "originalPrice": 299.99,
      "stockQuantity": 5,
      "sku": "PERFUME-150ML",
      "isPopular": false,
      "isDefault": false,
      "sortOrder": 4,
      "isActive": true
    }
  ]
}

```

```
]
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume",
    "variants": [
      {
        "id": "variant_id",
        "name": "50ml",
        "price": 129.99,
        "stockQuantity": 20,
        "isDefault": true,
        "isActive": true
      }
    ]
  },
  "message": "Inventory item updated successfully"
}
```

**DELETE** /api/v1/provider/inventory/{id}

**Summary:** Delete own inventory item

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Permanently deletes the provider inventory item.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/provider/inventory/{id}/availability

**Summary:** Update own inventory availability

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "isAvailable": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 03 Provider - Promotional Offers

**GET** /api/v1/provider/offers

**Summary:** List Provider Offers

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- itemId (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/provider/offers

**Summary:** Create Provider Offers

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

**Request payload(s):**

payload

```
{
  "itemId": "<string>",
  "title": "<string>",
  "description": "<string>",
  "discountType": "PERCENTAGE",
  "discountValue": 1.0,
  "startDate": "<string>",
  "endDate": "<string>",
  "eligibilityRules": "<string>",
}
```

```
"isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/offers/{id}

**Summary:** Fetch Provider Offers details

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/provider/offers/{id}

**Summary:** Update Provider Offers

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "title": "<string>",
  "description": "<string>",
  "discountType": "PERCENTAGE",
  "discountValue": 1.0,
  "startDate": "<string>",
  "endDate": "<string>",
  "eligibilityRules": "<string>",
  "isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```

```
"message": "Request completed successfully."
}
```

**DELETE** /api/v1/provider/offers/{id}

**Summary:** Delete Provider Offers

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/provider/offers/{id}/status

**Summary:** Update Provider Offers Status

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "isActive": true,
  "reason": "<string>"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 03 Provider - Orders

**GET** /api/v1/provider/orders

**Summary:** List own assigned provider orders

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Returns only orders assigned to the authenticated providerId. Default status filter is PENDING.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)
- search (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "provider_order_id",
      "orderId": "order_id",
      "orderNumber": "ORD-10293",
      "status": "PENDING",
      "paymentStatus": "SUCCEEDED",
      "customer": {
        "name": "Sarah Jenkins",
        "phone": "+15551234567"
      },
      "itemPreview": [
        {
          "name": "Premium Sneakers",
          "imageUrl": "https://cdn.yourdomain.com/gifts/sneaker.png"
        }
      ],
      "itemCount": 3,
      "totalPayout": 142,
      "currency": "PKR",
      "createdAt": "2026-10-24T10:45:00.000Z",
      "receivedAgoText": "5m ago"
    }
  ],
  "message": "Provider orders fetched successfully."
}
```

**GET** /api/v1/provider/orders/history

**Summary:** List own provider order history

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Uses ProviderOrder records scoped to the authenticated provider. Status tabs map to provider order statuses.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)
- search (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)



- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/orders/summary

**Summary:** Fetch own provider order summary

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Route intentionally declared before :id. PROVIDER only.

**Parameters:**

- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/orders/reject-reasons

**Summary:** List provider order reject reasons

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Route intentionally declared before :id.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/provider/orders/{id}/status

**Summary:** Update own provider order fulfillment status

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Enforces ownership, valid transitions, paid-order fulfillment checks, timeline entries, and customer notifications.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "status": "SHIPPED",
  "note": "Package handed over to courier.",
  "trackingNumber": "FDX-123456",
  "carrier": "FedEx",
  "estimatedDeliveryAt": "2026-10-26T10:00:00.000Z"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/provider/orders/{id}/fulfill

**Summary:** Fulfill own provider order with dispatch details

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Dedicated Figma fulfill action. Stores dispatch date/time, estimated delivery, carrier, tracking number, moves provider order to SHIPPED, syncs parent order, creates timeline entry, and optionally notifies customer.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "dispatchAt": "2026-04-23T14:45:00.000Z",
  "estimatedDeliveryAt": "2026-04-28T10:00:00.000Z",
  "carrier": "Express Delivery Co.",
  "trackingNumber": "TRK-8842-4567-9023",
  "notifyCustomer": true,
  "note": "Order dispatched successfully."
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/orders/{id}/timeline

**Summary:** Fetch own provider order timeline

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Timeline is scoped to the authenticated provider order.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/orders/{id}/checklist

**Summary:** Fetch own provider order checklist

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Checklist is operational and does not change status automatically.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/provider/orders/{id}/checklist

**Summary:** Update own provider order checklist

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Checklist updates do not directly change order status.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "itemsPacked": true,
  "giftMessageAttached": true,
  "addressVerified": true,
  "customerContactChecked": true,
  "readyForCourier": false,
  "customItems": [
    {
      "id": "checklist_item_id",
      "label": "Include gift wrap",
      "isCompleted": true
    }
  ]
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/provider/orders/{id}/message-buyer

**Summary:** Message buyer for own provider order

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Creates an order message and customer notification; SMS is placeholder only.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "message": "Your order is being prepared and will be shipped soon.",
  "channel": "IN_APP"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/orders/{id}

**Summary:** Fetch own provider order details

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Does not expose customer card/payment secrets or admin-only order fields.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/provider/orders/{id}/accept

**Summary:** Accept own pending provider order

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Allowed transition: PENDING -> ACCEPTED. Creates timeline entry and customer notification.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "note": "Order accepted and will be processed shortly."
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/provider/orders/{id}/reject

**Summary:** Reject own pending provider order

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Allowed transition: PENDING -> REJECTED. Does not refund automatically; flags order for review/cancellation based on provider split count.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "reason": "OUT_OF_STOCK",
  "comment": "The selected size is currently unavailable."
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 03 Provider - Payout Methods

**GET** /api/v1/provider/payout-methods

**Summary:** List own provider payout methods

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. providerId is derived from JWT. Returns masked payout metadata only.

**Response body:**

```
{
  "success": true,
  "data": {
    "primary": {
      "id": "payout_method_id",
      "type": "BANK_ACCOUNT",
      "bankName": "Chase Bank",
      "maskedAccount": "Checking Account **** 5678",
    }
  }
}
```

```

    "accountHolderName": "Sylvia Bond",
    "payerId": "SB-4491-001",
    "verificationStatus": "VERIFIED",
    "isDefault": true,
    "isActive": true
  },
  "methods": [
    {
      "id": "payout_method_id",
      "type": "BANK_ACCOUNT",
      "bankName": "Chase Bank",
      "maskedAccount": "Checking Account **** 6789",
      "accountHolderName": "Sylvia Bond",
      "verificationStatus": "VERIFIED",
      "isDefault": true,
      "isActive": true
    }
  ]
},
"message": "Provider payout methods fetched successfully."
}

```

**POST** /api/v1/provider/payout-methods/bank-accounts

**Summary:** Add provider bank payout method

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Stores masked metadata only; raw routing/account/IBAN values are never returned or persisted.

**Request payload(s):**

bank

```

{
  "accountHolderName": "Sylvia Bond",
  "bankName": "Chase Bank",
  "accountType": "CHECKING",
  "country": "US",
  "currency": "USD",
  "routingNumber": "110000000",
  "accountNumber": "000123456789",
  "iban": null,
  "isDefault": true
}

```

**Response body:**

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

**GET** /api/v1/provider/payout-methods/{id}

**Summary:** Fetch own provider payout method details

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Full account number, IBAN, and routing number are never returned.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/provider/payout-methods/{id}

**Summary:** Update provider payout method display metadata

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Bank/routing/account numbers cannot be edited; add a new payout method instead.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "accountHolderName": "Sylvia Bond",
  "bankName": "Chase Bank Personal",
  "isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/provider/payout-methods/{id}

**Summary:** Delete own provider payout method

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Permanently deletes the payout method and blocks deletion when pending provider payout adjustments exist.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
```

```
"data": "<response returned by endpoint>",
"message": "Request completed successfully."
}
```

**PATCH** /api/v1/provider/payout-methods/{id}/default

**Summary:** Set default provider payout method

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Only own verified active payout methods can become default.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/provider/payout-methods/{id}/verify

**Summary:** Start provider payout method verification

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. If Plaid/Stripe Connect is not configured, MANUAL keeps verification pending for admin/system review.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "verificationMethod": "MANUAL",
  "publicToken": "plaid_public_token"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```



## 03 Provider - Payouts

**GET** /api/v1/provider/payouts

**Summary:** List own provider payout history

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. providerId is derived from JWT.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- status (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/payouts/summary

**Summary:** Fetch own provider payout summary

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Route declared before :id. PROVIDER only.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/payouts/preview

**Summary:** Preview provider payout request

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Route declared before :id. Validates available balance and verified payout method.

**Parameters:**

- amount (query, required, number)
- payoutMethodId (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/provider/payouts/request

**Summary:** Request provider payout

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Uses idempotencyKey to block duplicate payout requests.

**Request payload(s):**

payload

```
{
  "amount": 1250,
  "payoutMethodId": "payout_method_id",
  "idempotencyKey": "provider_payout_2026_001"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/payouts/{id}

**Summary:** Fetch own provider payout details

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Scoped to authenticated provider.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/provider/payouts/{id}/cancel

**Summary:** Cancel own pending provider payout

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Can cancel only PENDING payouts and returns locked balance to AVAILABLE.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "reason": "Requested by provider."
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 03 Provider - Refund Requests

**GET** /api/v1/provider/refund-requests

**Summary:** List own provider refund requests

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Returns refund requests for provider orders assigned to the authenticated provider. Search supports order number, customer name, and customer email.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)
- search (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "refund_request_id",
      "providerOrderId": "provider_order_id",
      "orderNumber": "88417",
      "customer": {
        "name": "Jane Cooper",
        "email": "jane.cooper@example.com",
        "avatarUrl": "https://cdn.yourdomain.com/customer-avatar.jpg"
      },
      "requestedAmount": 45,
    }
  ]
}
```

```
    "currency": "PKR",
    "status": "REQUESTED",
    "customerReason": "Item was damaged on arrival",
    "createdAt": "2026-10-23T18:10:00.000Z"
  }
],
"message": "Provider refund requests fetched successfully."
}
```

**GET** /api/v1/provider/refund-requests/summary

**Summary:** Fetch own refund request summary

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Route intentionally declared before :id. PROVIDER only.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/refund-requests/reject-reasons

**Summary:** List refund rejection reasons

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Route intentionally declared before :id. PROVIDER only.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/refund-requests/{id}

**Summary:** Fetch own refund request details

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Refund request must belong to the authenticated provider order and never exposes Stripe secrets or raw card data.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/provider/refund-requests/{id}/approve

**Summary:** Approve own requested refund

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Validates ownership, REQUESTED status, requested amount, refundable amount, creates refund transaction marker, timeline entry, and customer notification.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

approve

```
{
  "comment": "Refund approved after reviewing evidence.",
  "refundAmount": 45,
  "notifyCustomer": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/provider/refund-requests/{id}/reject

**Summary:** Reject own requested refund

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Validates ownership and REQUESTED status. Creates timeline entry and optional customer notification. No Stripe refund is created.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

reject

```
{
  "reason": "REFUND_WINDOW_EXPIRED",
  "comment": "The request was submitted after the allowed refund period.",
  "notifyCustomer": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 03 Provider - Order Analytics

**GET** /api/v1/provider/orders/performance

**Summary:** Fetch own provider order performance

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Completion rate uses completed / non-cancelled own provider orders.

**Parameters:**

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/orders/analytics/revenue

**Summary:** Fetch own provider revenue analytics

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Revenue uses provider totalPayout for paid active/completed provider orders.

**Parameters:**

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/orders/analytics/ratings

**Summary:** Fetch own provider ratings analytics

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Returns stable zero values until reviews module is available.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/orders/recent

**Summary:** List recent own provider orders

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Defaults to 5 latest orders.

**Parameters:**

- limit (query, optional, number)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/provider/orders/export

**Summary:** Export own provider orders as CSV

**Allowed role/access:** PROVIDER

**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Export is scoped to logged-in provider orders.

**Parameters:**

- status (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- format (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 04 Gifts - Categories

**GET** /api/v1/gift-categories/lookup

**Summary:** Lookup active gift categories

**Allowed role/access:** PUBLIC

**Notes:** Access: PUBLIC. PUBLIC. Active gift category lookup. Public lookup under Gift Categories. Returns active category identifiers and media fields for lightweight selectors.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/gift-categories

**Summary:** List gift categories

**Allowed role/access:** SUPER\_ADMIN or ADMIN with giftCategories.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with giftCategories.read. SUPER\_ADMIN or ADMIN with giftCategories.read permission. RBAC permission: giftCategories.read. Returns soft-delete-filtered categories with gift counts and category media fields.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- isActive (query, optional, boolean)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/gift-categories

**Summary:** Create gift category

**Allowed role/access:** SUPER\_ADMIN or ADMIN with giftCategories.create

**Notes:** Access: SUPER\_ADMIN or ADMIN with giftCategories.create. SUPER\_ADMIN or ADMIN with giftCategories.create permission. RBAC permission: giftCategories.create. Slug is auto-generated and unique. backgroundColor defaults to #F3E8FF; color remains a backward-compatible alias.

**Request payload(s):**

create

```
{
  "name": "Perfumes",
  "description": "Premium fragrance gifts.",
  "iconKey": "perfume",
  "backgroundColor": "#E9D5FF",
  "imageUrl": "https://<YOUR_PUBLIC_BUCKET_OR_CDN_URL>/gift-category-images/perfumes.png",
  "sortOrder": 1,
  "isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/gift-categories/stats

**Summary:** Fetch gift category stats

**Allowed role/access:** SUPER\_ADMIN or ADMIN with giftCategories.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with giftCategories.read. SUPER\_ADMIN or ADMIN with giftCategories.read permission. RBAC permission: giftCategories.read. Returns admin category inventory counters.

**Response body:**



```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/gift-categories/{id}

**Summary:** Fetch gift category details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with giftCategories.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with giftCategories.read. SUPER\_ADMIN or ADMIN with giftCategories.read permission. RBAC permission: giftCategories.read. Includes backgroundColor and imageUrl for customer app design support.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/gift-categories/{id}

**Summary:** Update gift category

**Allowed role/access:** SUPER\_ADMIN or ADMIN with giftCategories.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with giftCategories.update. SUPER\_ADMIN or ADMIN with giftCategories.update permission. RBAC permission: giftCategories.update. Slug is regenerated when name changes. Soft-deleted categories are not updated.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

update

```
{
  "backgroundColor": "#F3E8FF",
  "imageUrl": "https://<YOUR_PUBLIC_BUCKET_OR_CDN_URL>/gift-category-images/perfumes.png",
  "isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/gift-categories/{id}

**Summary:** Delete gift category

**Allowed role/access:** SUPER\_ADMIN or ADMIN with giftCategories.delete

**Notes:** Access: SUPER\_ADMIN or ADMIN with giftCategories.delete. SUPER\_ADMIN or ADMIN with giftCategories.delete permission. RBAC permission: giftCategories.delete. Permanently deletes the category. Categories with attached gifts cannot be deleted; delete writes an audit log.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 04 Gifts - Management

**GET** /api/v1/gifts

**Summary:** List admin gifts

**Allowed role/access:** SUPER\_ADMIN or ADMIN with gifts.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with gifts.read. SUPER\_ADMIN or ADMIN with gifts.read permission. SUPER\_ADMIN/ADMIN with gifts.read. Supports category/provider/status/moderation filters.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- categoryId (query, optional, string)
- providerId (query, optional, string)
- status (query, optional, string)
- moderationStatus (query, optional, string)
- isPublished (query, optional, boolean)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/gifts

**Summary:** Create admin gift with optional nested variants

**Allowed role/access:** SUPER\_ADMIN or ADMIN with gifts.create

**Notes:** Access: SUPER\_ADMIN or ADMIN with gifts.create. SUPER\_ADMIN or ADMIN with gifts.create permission. SUPER\_ADMIN/ADMIN with gifts.create. Nested variants are created in the same transaction and stored in GiftVariant.

**Request payload(s):**

withVariants

```

{
  "name": "Luxury Perfume",
  "description": "Long-lasting premium fragrance.",
  "shortDescription": "Premium fragrance gift.",
  "categoryId": "gift_category_id",
  "providerId": "provider_id",
  "price": 99.99,
  "currency": "PKR",
  "stockQuantity": 50,
  "sku": "PERFUME-001",
  "imageUrls": [
    "https://cdn.yourdomain.com/gift-images/perfume.png"
  ],
  "isPublished": true,
  "isFeatured": false,
  "tags": [
    "perfume",
    "luxury"
  ],
  "moderationStatus": "APPROVED",
  "variants": [
    {
      "name": "30ml",
      "price": 89.99,
      "originalPrice": 119.99,
      "stockQuantity": 10,
      "sku": "PERFUME-30ML",
      "isPopular": false,
      "isDefault": false,
      "sortOrder": 1,
      "isActive": true
    },
    {
      "name": "50ml",
      "price": 129.99,
      "originalPrice": 159.99,
      "stockQuantity": 20,
      "sku": "PERFUME-50ML",
      "isPopular": true,
      "isDefault": true,
      "sortOrder": 2,
      "isActive": true
    }
  ]
}

```

#### Response body:

```

{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume",
    "price": 99.99,
    "currency": "PKR",
    "stockQuantity": 50,
    "sku": "PERFUME-001",
    "variants": [
      {
        "id": "variant_id",
        "name": "50ml",
        "price": 129.99,
        "originalPrice": 159.99,

```

```
      "stockQuantity": 20,
      "sku": "PERFUME-50ML",
      "isPopular": true,
      "isDefault": true,
      "sortOrder": 2,
      "isActive": true
    }
  ]
},
"message": "Gift created successfully"
}
```

**GET** /api/v1/gifts/stats

**Summary:** Fetch gift inventory stats

**Allowed role/access:** SUPER\_ADMIN or ADMIN with gifts.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with gifts.read. SUPER\_ADMIN or ADMIN with gifts.read permission.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/gifts/export

**Summary:** Export gift inventory

**Allowed role/access:** SUPER\_ADMIN or ADMIN with gifts.export

**Notes:** Access: SUPER\_ADMIN or ADMIN with gifts.export. SUPER\_ADMIN or ADMIN with gifts.export permission.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- categoryId (query, optional, string)
- providerId (query, optional, string)
- status (query, optional, string)
- moderationStatus (query, optional, string)
- isPublished (query, optional, boolean)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)
- format (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/gifts/{id}

**Summary:** Fetch admin gift details with variants

**Allowed role/access:** SUPER\_ADMIN or ADMIN with gifts.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with gifts.read. SUPER\_ADMIN or ADMIN with gifts.read permission.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/gifts/{id}**Summary:** Update admin gift and upsert nested variants**Allowed role/access:** SUPER\_ADMIN or ADMIN with gifts.update**Notes:** Access: SUPER\_ADMIN or ADMIN with gifts.update. SUPER\_ADMIN or ADMIN with gifts.update permission. If replaceVariants=true, omitted variants are soft-deleted. Only one default variant is allowed.**Parameters:**

- id (path, required, string)

**Request payload(s):**

upsertVariants

```
{
  "name": "Luxury Perfume Updated",
  "replaceVariants": false,
  "variants": [
    {
      "id": "variant_id",
      "name": "50ml",
      "price": 129.99,
      "originalPrice": 159.99,
      "stockQuantity": 20,
      "sku": "PERFUME-50ML",
      "isPopular": true,
      "isDefault": true,
      "sortOrder": 2,
      "isActive": true
    },
    {
      "name": "150ml",
      "price": 249.99,
      "originalPrice": 299.99,
      "stockQuantity": 5,
      "sku": "PERFUME-150ML",
      "isPopular": false,
      "isDefault": false,
      "sortOrder": 4,
      "isActive": true
    }
  ]
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume Updated",
```

```
"variants": [
  {
    "id": "variant_id",
    "name": "50ml",
    "price": 129.99,
    "originalPrice": 159.99,
    "stockQuantity": 20,
    "sku": "PERFUME-50ML",
    "isDefault": true,
    "isActive": true
  }
],
"message": "Gift updated successfully"
}
```

**DELETE** /api/v1/gifts/{id}

**Summary:** Delete gift

**Allowed role/access:** SUPER\_ADMIN or ADMIN with gifts.delete

**Notes:** Access: SUPER\_ADMIN or ADMIN with gifts.delete. SUPER\_ADMIN or ADMIN with gifts.delete permission.  
Permanently deletes the gift record.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/gifts/{id}/status

**Summary:** Update gift status

**Allowed role/access:** SUPER\_ADMIN or ADMIN with gifts.status.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with gifts.status.update. SUPER\_ADMIN or ADMIN with gifts.status.update permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "status": "ACTIVE",
  "reason": "<string>"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 04 Gifts - Moderation

**GET** /api/v1/gift-moderation

**Summary:** List optional gift moderation queue

**Allowed role/access:** SUPER\_ADMIN or ADMIN with giftModeration.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with giftModeration.read. SUPER\_ADMIN or ADMIN with giftModeration.read permission. Gift moderation is optional/exception-based; default queue returns only PENDING, FLAGGED, REJECTED, or requiresManualReview=true. Provider-created inventory does not require separate Super Admin approval by default. Gift Moderation is optional/admin review workflow for flagged, reported, high-risk, or admin-forced review items. Provider-created inventory does not require separate Super Admin approval by default; provider approval is the primary marketplace trust gate. Default queue returns only PENDING, FLAGGED, REJECTED, or requiresManualReview=true. Use status=APPROVED, status=NOT\_REQUIRED, or includeResolved=true to view resolved/normal inventory.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)
- includeResolved (query, optional, boolean) When true, includes resolved/normal statuses such as APPROVED and NOT\_REQUIRED. Default queue returns only PENDING, FLAGGED, REJECTED, or requiresManualReview=true.
- search (query, optional, string)
- providerId (query, optional, string)
- view (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/gift-moderation/{id}/approve

**Summary:** Approve gift in optional moderation workflow

**Allowed role/access:** SUPER\_ADMIN or ADMIN with giftModeration.approve

**Notes:** Access: SUPER\_ADMIN or ADMIN with giftModeration.approve. SUPER\_ADMIN or ADMIN with giftModeration.approve permission. Clears manual review/hidden-by-moderation flags. This is not required for normal provider-created inventory visibility; approved active providers can publish inventory directly.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "comment": "<string>",
  "publishNow": true,
}
```

```
"notifyProvider": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/gift-moderation/{id}/reject

**Summary:** Reject gift in optional moderation workflow

**Allowed role/access:** SUPER\_ADMIN or ADMIN with giftModeration.reject

**Notes:** Access: SUPER\_ADMIN or ADMIN with giftModeration.reject. SUPER\_ADMIN or ADMIN with giftModeration.reject permission. Rejecting hides the gift from marketplace, clears manual review, sets moderationStatus=REJECTED, and writes an audit log.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "reason": "INCOMPLETE_INFORMATION",
  "comment": "<string>",
  "notifyProvider": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/gift-moderation/{id}/flag

**Summary:** Flag gift for manual review

**Allowed role/access:** SUPER\_ADMIN or ADMIN with giftModeration.flag

**Notes:** Access: SUPER\_ADMIN or ADMIN with giftModeration.flag. SUPER\_ADMIN or ADMIN with giftModeration.flag permission. Flags optional moderation case. If hideFromMarketplace=true, sets moderationStatus=FLAGGED, requiresManualReview=true, hiddenByModeration=true, and isPublished=false. If false, the gift remains visible but appears in moderation queue. Always writes an audit log.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "reason": "NEEDS_MANUAL_REVIEW",
  "comment": "<string>",
  "hideFromMarketplace": true,
}
```



```
"notifyProvider": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 05 Customer / Guest - Marketplace

**GET** /api/v1/customer/home

**Summary:** Fetch customer app home

**Allowed role/access:** REGISTERED\_USER or GUEST\_USER

**Notes:** Access: REGISTERED\_USER or GUEST\_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest response behavior includes isWishlisted=false, requiresAuthForWishlist=true, requiresAuthForCart=true, requiresAuthForCheckout=true, defaultAddress=null, upcomingReminder=null, and mode="GUEST" where applicable. REGISTERED\_USER or GUEST\_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest home responses include defaultAddress=null, upcomingReminder=null, and mode="GUEST".

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/categories

**Summary:** List customer marketplace categories

**Allowed role/access:** REGISTERED\_USER or GUEST\_USER

**Notes:** Access: REGISTERED\_USER or GUEST\_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest response behavior includes isWishlisted=false, requiresAuthForWishlist=true, requiresAuthForCart=true, requiresAuthForCheckout=true, defaultAddress=null, upcomingReminder=null, and mode="GUEST" where applicable. REGISTERED\_USER or GUEST\_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/gifts/discounted

**Summary:** List discounted customer gifts

**Allowed role/access:** REGISTERED\_USER or GUEST\_USER

**Notes:** Access: REGISTERED\_USER or GUEST\_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest response behavior includes isWishlisted=false, requiresAuthForWishlist=true, requiresAuthForCart=true, requiresAuthForCheckout=true, defaultAddress=null, upcomingReminder=null, and mode="GUEST" where applicable. REGISTERED\_USER or GUEST\_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Discounted gift cards include isWishlisted=false and auth-required flags for guests.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- categoryId (query, optional, string)
- categorySlug (query, optional, string)
- providerId (query, optional, string)
- offerOnly (query, optional, boolean)
- minPrice (query, optional, number)
- maxPrice (query, optional, number)
- minRating (query, optional, number)
- brand (query, optional, string)
- deliveryOption (query, optional, string)
- sortBy (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/gifts/filter-options

**Summary:** Fetch marketplace gift filter options

**Allowed role/access:** REGISTERED\_USER or GUEST\_USER

**Notes:** Access: REGISTERED\_USER or GUEST\_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest response behavior includes isWishlisted=false, requiresAuthForWishlist=true, requiresAuthForCart=true, requiresAuthForCheckout=true, defaultAddress=null, upcomingReminder=null, and mode="GUEST" where applicable. REGISTERED\_USER or GUEST\_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/gifts

**Summary:** List customer marketplace gifts

**Allowed role/access:** REGISTERED\_USER or GUEST\_USER

**Notes:** Access: REGISTERED\_USER or GUEST\_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest response behavior includes isWishlisted=false, requiresAuthForWishlist=true, requiresAuthForCart=true, requiresAuthForCheckout=true, defaultAddress=null, upcomingReminder=null, and mode="GUEST" where applicable. REGISTERED\_USER or GUEST\_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest gift cards include isWishlisted=false, requiresAuthForWishlist=true, requiresAuthForCart=true, and requiresAuthForCheckout=true. Provider inventory does not require separate gift moderation approval.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- categoryId (query, optional, string)
- categorySlug (query, optional, string)
- providerId (query, optional, string)
- offerOnly (query, optional, boolean)
- minPrice (query, optional, number)
- maxPrice (query, optional, number)
- minRating (query, optional, number)
- brand (query, optional, string)
- deliveryOption (query, optional, string)
- sortBy (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "gift_id",
      "name": "Luxury Perfume",
      "price": 99.99,
      "currency": "PKR",
      "imageUrl": "https://cdn.yourdomain.com/gift-images/perfume.png",
      "rating": 4.8,
      "isWishlisted": false,
      "requiresAuthForWishlist": true,
      "requiresAuthForCart": true,
      "requiresAuthForCheckout": true,
      "shortDescription": "Premium fragrance gift.",
      "reviewCount": 0,
      "stockQuantity": 50,
      "category": {
        "id": "gift_category_id",
        "name": "Perfumes",
        "slug": "perfumes"
      },
      "provider": {
        "id": "provider_id",
        "businessName": "Dcodax Gifts"
      },
      "deliveryOptions": [
        "SAME_DAY",
        "NEXT_DAY",
        "SCHEDULED"
      ],
      "activeOffer": null
    }
  ]
}
```

```

    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Customer gifts fetched successfully"
}

```

**GET** /api/v1/customer/gifts/{id}

**Summary:** Fetch customer-safe gift details

**Allowed role/access:** REGISTERED\_USER or GUEST\_USER

**Notes:** Access: REGISTERED\_USER or GUEST\_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest response behavior includes isWishlisted=false, requiresAuthForWishlist=true, requiresAuthForCart=true, requiresAuthForCheckout=true, defaultAddress=null, upcomingReminder=null, and mode="GUEST" where applicable. REGISTERED\_USER or GUEST\_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest gift details include isWishlisted=false and auth-required flags; SKU/exact stock stay hidden unless enabled in guest settings.

**Parameters:**

- id (path, required, string)

**Response body:**

```

{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume",
    "description": "Long-lasting premium fragrance.",
    "shortDescription": "Premium fragrance gift.",
    "price": 99.99,
    "originalPrice": 99.99,
    "currency": "PKR",
    "imageUrls": [
      "https://cdn.yourdomain.com/gift-images/perfume.png"
    ],
    "rating": 4.8,
    "reviewCount": 0,
    "stockQuantity": 50,
    "isWishlisted": false,
    "requiresAuthForWishlist": true,
    "requiresAuthForCart": true,
    "requiresAuthForCheckout": true,
    "badges": [
      "AUTHENTIC"
    ],
    "category": {
      "id": "gift_category_id",
      "name": "Perfumes",
      "slug": "perfumes"
    },
    "provider": {
      "id": "provider_id",
      "businessName": "Dcodax Gifts",
      "rating": 4.8,

```

```

    "reviewCount": 0,
    "fulfillmentMethods": [
      "DELIVERY"
    ]
  },
  "variants": [
    {
      "id": "variant_id",
      "name": "50ml",
      "price": 129.99,
      "originalPrice": 159.99,
      "stockQuantity": 20,
      "sku": "PERFUME-50ML",
      "isPopular": true,
      "isDefault": true
    }
  ],
  "deliveryOptions": [
    "SAME_DAY",
    "NEXT_DAY",
    "SCHEDULED"
  ],
  "activeOffer": null
},
"message": "Gift details fetched successfully"
}

```

## 05 Customer - Wishlist

**GET** /api/v1/customer/wishlist

**Summary:** List wishlist gifts

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Returns customer-visible gifts: active, available, in stock, not deleted, and owned by an approved active provider. Admin-created gifts may additionally require isPublished=true.

**Response body:**

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

**POST** /api/v1/customer/wishlist/{giftId}

**Summary:** Add gift to wishlist

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Gift must be customer-visible: active, available, in stock, not deleted, and owned by an approved active provider. Admin-created gifts may additionally require isPublished=true. Duplicate wishlist entries are ignored.

**Parameters:**

- giftId (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/customer/wishlist/{giftId}

**Summary:** Remove gift from wishlist

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Removes only the current customer wishlist row.

**Parameters:**

- giftId (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 05 Customer - Addresses

**GET** /api/v1/customer/addresses

**Summary:** List customer addresses

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Customers can only view their own non-deleted addresses.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/customer/addresses

**Summary:** Create customer address

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Maintains one default address per customer.

**Request payload(s):**

payload

```
{
  "label": "Home",
  "fullName": "Sarah Khan",
  "phone": "+923001234567",
  "line1": "House 12, Street 4, F-8/2",
  "line2": "Near Centaurus Mall",
  "city": "Islamabad",
  "state": "Islamabad Capital Territory",
  "country": "Pakistan",
  "postalCode": "44000",
  "latitude": 33.6844,
  "longitude": 73.0479,
  "deliveryInstructions": "Leave at reception.",
  "isDefault": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/addresses/{id}**Summary:** Fetch customer address**Allowed role/access:** REGISTERED\_USER**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Address must belong to the current customer.**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/customer/addresses/{id}**Summary:** Update customer address**Allowed role/access:** REGISTERED\_USER**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Maintains one default address per customer.**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "label": "Home",
```

```
"fullName": "Sarah Khan",
"phone": "+923001234567",
"line1": "House 12, Street 4, F-8/2",
"line2": "Near Centaurus Mall",
"city": "Islamabad",
"state": "Islamabad Capital Territory",
"country": "Pakistan",
"postalCode": "44000",
"latitude": 33.6844,
"longitude": 73.0479,
"deliveryInstructions": "Leave at reception.",
"isDefault": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/customer/addresses/{id}

**Summary:** Delete customer address

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Permanently deletes the address and removes default status.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/customer/addresses/{id}/default

**Summary:** Set default customer address

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Clears default flag from all other customer addresses.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```



**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 05 Customer - Contacts

**GET** /api/v1/customer/contacts

**Summary:** List customer contacts

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Lists only contacts owned by the authenticated customer.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string) Searches name, phone, email, and relationship.
- relationship (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/customer/contacts

**Summary:** Create customer contact

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Creates a personal gift contact owned by the authenticated customer. Requires at least one contact method: phone, email, or address.

**Request payload(s):**

create

```
{
  "name": "Mary Wilson",
  "relationship": "Mother",
  "phone": "+1234567890",
  "email": "mary@example.com",
  "address": "387 Merdina",
  "likes": "Glasses, makeup, dresses",
  "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/mary.png",
  "birthday": "1990-05-12",
  "notes": "Prefers elegant gifts."
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/contacts/{id}

**Summary:** Fetch customer contact

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Contact must belong to the authenticated customer.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/customer/contacts/{id}

**Summary:** Update customer contact

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Updates only contacts owned by the authenticated customer.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

update

```
{
  "name": "Mary Wilson",
  "relationship": "Mother",
  "phone": "+1234567890",
  "email": "mary@example.com",
  "address": "387 Merdina",
  "likes": "Glasses, makeup, dresses",
  "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/mary.png",
  "birthday": "1990-05-12",
  "notes": "Prefers elegant gifts."
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/customer/contacts/{id}

**Summary:** Delete customer contact

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Permanently deletes only contacts owned by the authenticated customer.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 05 Customer - Events

**GET** /api/v1/customer/events

**Summary:** List customer events

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Lists only events owned by the authenticated customer.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- eventType (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- recipientId (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/customer/events

**Summary:** Create customer event

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. recipientId must belong to the authenticated customer.

**Request payload(s):**

payload

```
{
  "eventType": "BIRTHDAY",
  "title": "Sarah's Birthday",
  "recipientId": "cmf0contactmary001",
  "eventDate": "2026-01-31T00:00:00.000Z",
  "reminderTiming": "ON_THE_DAY",
  "reminderFrequency": "ONE_TIME",
  "customAlertTime": "09:00",
  "channels": [
    "EMAIL",
    "SMS"
  ],
  "notes": "Send a birthday gift.",
  "isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/events/calendar

**Summary:** Fetch monthly calendar events

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Returns marked dates and own events.

**Parameters:**

- month (query, required, number)
- year (query, required, number)
- eventType (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/events/upcoming

**Summary:** Fetch upcoming customer events

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Defaults to 10 events within 30 days.

**Parameters:**

- limit (query, optional, number)
- daysAhead (query, optional, number)
- eventType (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/events/{id}/reminder-settings

**Summary:** Fetch event reminder settings

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Event must belong to the authenticated customer.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/customer/events/{id}/reminder-settings

**Summary:** Update event reminder settings

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Event must belong to the authenticated customer.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "reminderFrequency": "YEARLY",
  "reminderTiming": "ONE_DAY_BEFORE",
  "customAlertTime": "09:00",
  "channels": {
    "push": true,
    "email": true,
    "sms": false
  }
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/events/{id}

**Summary:** Fetch customer event details

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Event must belong to the authenticated customer.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/customer/events/{id}

**Summary:** Update customer event

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Event and recipient contact must belong to the authenticated customer.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "eventType": "ANNIVERSARY",
  "title": "Sarah's Anniversary",
  "recipientId": "cmf0contactmary001",
  "eventDate": "2026-01-31T00:00:00.000Z",
  "reminderTiming": "THREE_DAYS_BEFORE",
  "reminderFrequency": "YEARLY",
  "customAlertTime": "09:00",
  "channels": [
    "PUSH",
    "EMAIL"
  ],
  "notes": "Send flowers.",
  "isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/customer/events/{id}

**Summary:** Delete customer event

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Permanently deletes only own event and cancels pending reminder jobs.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 05 Customer - Cart

**GET** /api/v1/customer/cart

**Summary:** Fetch active cart

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Totals are backend calculated from price snapshots.

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "cart_id",
    "status": "ACTIVE",
    "items": [
      {
        "id": "cart_item_id",
        "giftId": "gift_id",
        "variantId": "variant_id",
        "name": "Luxury Perfume",
        "variantName": "50ml",
        "quantity": 1,
        "unitPrice": 129.99,
        "discountAmount": 20,
        "finalUnitPrice": 109.99,
        "lineTotal": 109.99,
        "imageUrl": "https://cdn.yourdomain.com/gift-images/perfume.png",
        "deliveryOption": "SAME_DAY",
        "recipient": {
          "contactId": "contact_id",
          "name": "Sarah Khan",
          "phone": "+923001234567",
          "addressId": "address_id"
        },
        "giftMessage": "Hope you love this special surprise!",
        "messageMediaUrls": [
          "https://cdn.yourdomain.com/gift-message-media/photo.png"
        ],
        "scheduledDeliveryAt": "2026-12-24T10:00:00.000Z"
      }
    ],
    "summary": {
```

```

        "subtotal": 129.99,
        "discountTotal": 20,
        "deliveryFee": 0,
        "tax": 0,
        "total": 109.99,
        "currency": "PKR"
    }
},
"message": "Cart fetched successfully"
}

```

**DELETE** /api/v1/customer/cart

**Summary:** Clear active cart

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Removes all items from active cart.

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

**POST** /api/v1/customer/cart/items

**Summary:** Add item to cart

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Backend calculates unit price, active offer discount, final price, subtotal, delivery fee placeholder, and total.

**Request payload(s):**

sendGift

```

{
  "giftId": "cmf0giftroses001",
  "variantId": "cmf0variant50ml001",
  "quantity": 1,
  "deliveryOption": "SAME_DAY",
  "recipientContactId": "cmf0contactmary001",
  "recipientName": "Sarah Khan",
  "recipientPhone": "+923001234567",
  "recipientAddressId": "cmf0addresshome001",
  "eventId": "cmf0eventbirthday001",
  "giftMessage": "Hope you love this special surprise!",
  "messageMediaUrls": [
    "https://cdn.yourdomain.com/gift-message-media/photo.png"
  ],
  "scheduledDeliveryAt": "2026-12-24T10:00:00.000Z"
}

```

**Response body:**



```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/customer/cart/items/{id}

**Summary:** Update cart item

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Validates ownership through the active customer cart.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

updateSelection

```
{
  "variantId": "cmf0variant100ml001",
  "quantity": 2,
  "deliveryOption": "SCHEDULED",
  "recipientContactId": "cmf0contactmary001",
  "recipientName": "Sarah Khan",
  "recipientPhone": "+923001234567",
  "recipientAddressId": "cmf0addresshome001",
  "eventId": "cmf0eventbirthday001",
  "giftMessage": "Updated gift note.",
  "messageMediaUrls": [
    "https://cdn.yourdomain.com/gift-message-media/video.mp4"
  ],
  "scheduledDeliveryAt": "2026-12-25T10:00:00.000Z"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/customer/cart/items/{id}

**Summary:** Delete cart item

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Deletes only items in the current customer active cart.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 05 Customer - Orders

**GET** /api/v1/customer/orders

**Summary:** List customer orders

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Returns orders owned by the current customer.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- type (query, optional, string)
- status (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/customer/orders

**Summary:** Create order from active cart

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Prices are backend-calculated from cart/payment snapshots. STRIPE\_CARD requires a successful owned paymentId; COD stays pending; PLACEHOLDER is for development only. Multiple providers are split into provider sub-orders.

**Request payload(s):**

stripeCard

```
{
  "cartId": "cart_id",
  "paymentId": "payment_id",
  "deliveryAddressId": "address_id",
  "paymentMethod": "STRIPE_CARD"
}
```

cod

```
{
  "cartId": "cart_id",
  "deliveryAddressId": "address_id",
  "paymentMethod": "COD"
}
```

#### Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/orders/{id}

**Summary:** Fetch customer order

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Order must belong to the current customer.

#### Parameters:

- id (path, required, string)

#### Response body:

```
{
  "success": true,
  "data": {
    "id": "order_id",
    "orderNumber": "ORD-1760000000000",
    "status": "CONFIRMED",
    "paymentStatus": "SUCCEEDED",
    "paymentMethod": "STRIPE_CARD",
    "recipient": {
      "name": "Sarah Khan",
      "email": null,
      "phone": "+923001234567",
      "avatarUrl": null
    },
    "deliveryDate": "2026-12-24T10:00:00.000Z",
    "occasion": null,
    "giftMessage": "Hope you love this special surprise!",
    "items": [
      {
        "giftId": "gift_id",
        "name": "Luxury Perfume",
        "variantName": "50ml",
        "quantity": 1,
        "imageUrl": "https://cdn.yourdomain.com/gift-images/perfume.png",
        "total": 109.99
      }
    ],
    "summary": {
      "subtotal": 129.99,
      "discountTotal": 20,
      "deliveryFee": 0,
      "tax": 0,
      "total": 109.99,
      "currency": "PKR"
    }
  },
  "message": "Order fetched successfully."
}
```

## 05 Customer - Reviews

**POST** /api/v1/customer/orders/{id}/reviews

**Summary:** Submit provider review for an order

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Uses shared Review records consumed by provider reviews and admin review management.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "providerId": "provider_id",
  "rating": 5,
  "comment": "Great service and fast delivery. The package arrived in perfect condition."
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "review_id",
    "rating": 5,
    "comment": "Great service and fast delivery.",
    "status": "PUBLISHED",
    "providerId": "provider_id",
    "orderId": "order_id",
    "createdAt": "2026-05-11T10:00:00.000Z"
  },
  "message": "Review submitted successfully."
}
```

**GET** /api/v1/customer/reviews

**Summary:** List own provider reviews

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Customer sees only their own non-deleted reviews.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- rating (query, optional, number)
- providerId (query, optional, string)
- status (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/reviews/{id}

**Summary:** Fetch Customer Reviews details

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/customer/reviews/{id}

**Summary:** Update own review

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Cannot update deleted/removed reviews; updated content is re-run through deterministic moderation.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "rating": 4,
  "comment": "Updated review text."
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/customer/reviews/{id}

**Summary:** Delete own review

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Permanently deletes the customer review record.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 05 Customer - Provider Reports

**GET** /api/v1/customer/provider-report-reasons

**Summary:** Fetch provider report reasons

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Declared before /customer/provider-reports/:id.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/customer/providers/{providerId}/reports

**Summary:** Report provider

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Customer must have an order, chat, or review relationship with provider. Duplicate active provider/order/reason reports are blocked.

**Parameters:**

- providerId (path, required, string)

**Request payload(s):**

payload

```
{
  "reason": "POOR_SERVICE_QUALITY",
  "details": "The provider did not respond and the order was delayed.",
  "orderId": "order_id",
  "evidenceUrls": []
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/provider-reports

**Summary:** List Customer Provider Reports

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/provider-reports/{id}

**Summary:** Fetch Customer Provider Reports details

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 05 Customer - Recurring Payments

**GET** /api/v1/customer/recurring-payments

**Summary:** List own recurring payments

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Returns recurring money/gift payment subscriptions owned by the logged-in customer.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- frequency (query, optional, string)
- recipientContactId (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "recurring_payment_id",
      "title": "Sarah's Birthday",
      "recipient": {
```

```

      "id": "contact_id",
      "name": "Sarah Johnson",
      "email": "sarah.j@example.com",
      "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/sarah.png"
    },
    "amount": 50,
    "currency": "PKR",
    "frequency": "MONTHLY",
    "nextBillingAt": "2026-03-15T09:00:00.000Z",
    "status": "ACTIVE",
    "message": "Monthly flowers",
    "createdAt": "2026-05-09T10:00:00.000Z"
  }
],
"meta": {
  "page": 1,
  "limit": 20,
  "total": 1,
  "totalPages": 1
},
"message": "Recurring payments fetched successfully."
}

```

**POST** /api/v1/customer/recurring-payments

**Summary:** Create recurring payment

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Recipient contact and saved Stripe payment method must both belong to the logged-in customer. Stripe card recurring payments require a saved payment method.

**Request payload(s):**

weeklyStripe

```

{
  "amount": 100,
  "currency": "PKR",
  "frequency": "WEEKLY",
  "schedule": {
    "dayOfWeek": "MONDAY",
    "dayOfMonth": null,
    "monthOfYear": null,
    "time": "09:00",
    "timezone": "Asia/Karachi"
  },
  "recipientContactId": "contact_id",
  "message": "Hope you love this special surprise!",
  "messageMediaUrls": [
    "https://cdn.yourdomain.com/gift-message-media/photo.png"
  ],
  "paymentMethod": "STRIPE_CARD",
  "stripePaymentMethodId": "pm_xxx",
  "startDate": "2026-05-10T00:00:00.000Z",
  "endDate": null,
  "autoSend": true
}

```

**Response body:**

```

{
  "success": true,
  "data": {
    "id": "recurring_payment_id",

```



```
"amount": 100,
"currency": "PKR",
"frequency": "WEEKLY",
"nextBillingAt": "2026-05-12T09:00:00.000Z",
"status": "ACTIVE"
},
"message": "Recurring payment created successfully."
}
```

**GET** /api/v1/customer/recurring-payments/summary

**Summary:** Fetch recurring payment summary counts

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. Must stay before /customer/recurring-payments/{id} route.

**Response body:**

```
{
  "success": true,
  "data": {
    "total": 5,
    "active": 3,
    "paused": 1,
    "cancelled": 1,
    "failed": 0
  },
  "message": "Recurring payment summary fetched successfully."
}
```

**GET** /api/v1/customer/recurring-payments/{id}

**Summary:** Fetch own recurring payment details

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Customer cannot access another user's recurring payment.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "recurring_payment_id",
    "title": "Monthly Flowers",
    "recipient": {
      "id": "contact_id",
      "name": "Sarah Johnson",
      "email": "sarah.j@example.com",
      "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/sarah.png"
    },
    "amount": 50,
    "currency": "PKR",
    "frequency": "MONTHLY",
    "nextBillingAt": "2026-03-15T09:00:00.000Z",
    "status": "ACTIVE",
    "message": "Fresh seasonal bouquet delivered to her doorstep every month",
    "messageMediaUrls": [],
    "paymentMethod": {
      "type": "STRIPE_CARD",

```

```

    "brand": "visa",
    "last4": "4242",
    "expiryMonth": 12,
    "expiryYear": 2026
  },
  "schedule": {
    "frequency": "MONTHLY",
    "dayOfMonth": 15,
    "time": "09:00",
    "timezone": "Asia/Karachi"
  },
  "createdAt": "2026-05-09T10:00:00.000Z"
},
"message": "Recurring payment fetched successfully."
}

```

**PATCH** /api/v1/customer/recurring-payments/{id}

**Summary:** Update own recurring payment

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. Cannot edit CANCELLED recurring payments. Changes apply from the next billing cycle and nextBillingAt is recalculated.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

monthly

```

{
  "amount": 50,
  "frequency": "MONTHLY",
  "schedule": {
    "dayOfMonth": 15,
    "time": "09:00",
    "timezone": "Asia/Karachi"
  },
  "message": "Fresh flowers every month.",
  "messageMediaUrls": [],
  "stripePaymentMethodId": "pm_xxx"
}

```

**Response body:**

```

{
  "success": true,
  "data": {
    "id": "recurring_payment_id",
    "status": "ACTIVE",
    "nextBillingAt": "2026-03-15T09:00:00.000Z"
  },
  "message": "Recurring payment updated successfully. Changes will apply from the next billing cycle."
}

```

**POST** /api/v1/customer/recurring-payments/{id}/pause

**Summary:** Pause own active recurring payment

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

pause

```
{
  "reason": "User paused recurring payment."
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/customer/recurring-payments/{id}/resume

**Summary:** Resume own paused recurring payment

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/customer/recurring-payments/{id}/cancel

**Summary:** Cancel own recurring payment

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. IMMEDIATELY cancels future processing. AFTER\_CURRENT\_BILLING\_CYCLE sets cancelAtPeriodEnd and cancelAt.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

immediately

```
{
  "cancelMode": "IMMEDIATELY",
  "reason": "No longer needed."
}
```

periodEnd

```
{
  "cancelMode": "AFTER_CURRENT_BILLING_CYCLE",
  "reason": "Finish current cycle."
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "id": "recurring_payment_id",
    "status": "CANCELLED",
    "cancelMode": "IMMEDIATELY"
  },
  "message": "Recurring payment cancelled successfully."
}
```

**GET** /api/v1/customer/recurring-payments/{id}/history

**Summary:** List own recurring payment billing history

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account.

**Parameters:**

- id (path, required, string)
- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "history_id",
      "paymentId": "payment_id",
      "amount": 50,
      "currency": "PKR",
      "status": "SUCCESS",
      "billingDate": "2026-02-15T09:00:00.000Z",
      "transactionId": "GFT-8829-XPL",
      "failureReason": null
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Recurring payment history fetched successfully."
}
```

## 05 Customer - Transactions

**GET** /api/v1/customer/transactions

**Summary:** List own customer transactions

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Normalizes backend Payment, Order, MoneyGift, and RecurringPayment occurrence records owned by the logged-in customer.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- type (query, optional, string)
- status (query, optional, string)
- paymentMethod (query, optional, string)
- minAmount (query, optional, number)
- maxAmount (query, optional, number)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "payment_id",
      "transactionId": "TXN-2026-001234",
      "title": "Monthly Flowers",
      "description": "Recurring payment",
      "recipient": {
        "id": "contact_id",
        "name": "Sarah Johnson",
        "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/sarah.png"
      },
      "amount": 50,
      "currency": "PKR",
      "type": "RECURRING_PAYMENT",
      "status": "SUCCESS",
      "paymentMethod": "STRIPE_CARD",
      "createdAt": "2026-03-01T14:34:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Transactions fetched successfully."
}
```

**GET** /api/v1/customer/transactions/summary

**Summary:** Fetch own transaction summary

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. Defaults to current month when no date range is provided. Uses backend-calculated payment records only.

**Parameters:**

- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "totalSpentThisMonth": 255,
    "currency": "PKR",
    "successfulCount": 9,
    "failedCount": 1,
    "pendingCount": 0,
    "refundedCount": 0
  },
  "message": "Transaction summary fetched successfully."
}
```

**GET** /api/v1/customer/transactions/export**Summary:** Export own transactions**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. CSV is supported and returned as a file. Export is scoped to the logged-in customer only.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- type (query, optional, string)
- status (query, optional, string)
- paymentMethod (query, optional, string)
- minAmount (query, optional, number)
- maxAmount (query, optional, number)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)
- format (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/transactions/{id}**Summary:** Fetch own transaction details**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. Includes order, money gift, recurring payment, and payment gateway references when available. Billing address returns null until available.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
```

```

"data": {
  "id": "payment_id",
  "transactionId": "TXN-2026-001234-ABC-XYZ",
  "status": "SUCCESS",
  "amount": 50,
  "currency": "PKR",
  "createdAt": "2026-03-01T14:34:00.000Z",
  "type": "RECURRING_PAYMENT",
  "giftInformation": {
    "giftName": "Monthly Flowers Subscription",
    "deliveryType": "Money",
    "recipient": {
      "id": "contact_id",
      "name": "Sarah Johnson",
      "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/sarah.png"
    },
    "orderReference": null,
    "recurringPaymentId": "recurring_payment_id"
  },
  "paymentInformation": {
    "paymentMethod": "Stripe card",
    "gatewayReference": "pi_3MmlLrLkdIwHu7ix0fhBHWqt",
    "billingAddress": null
  }
},
"message": "Transaction details fetched successfully."
}

```

**GET** /api/v1/customer/transactions/{id}/receipt

**Summary:** Download own transaction receipt

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. Receipt is generated only for the transaction owner and never exposes Stripe secret data.

**Parameters:**

- id (path, required, string)

**Response body:**

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

## 05 Customer - Referrals & Rewards

**GET** /api/v1/customer/referrals/summary

**Summary:** Fetch own referral reward summary

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Customers can view only their own referral progress and ledger-derived balances.

**Response body:**

```

{
  "success": true,
  "data": {

```

```
{
  "invitedFriends": 3,
  "successfulReferrals": 2,
  "rewardsEarned": 20,
  "availableCredit": 20,
  "currency": "USD",
  "progress": {
    "totalInvited": 3,
    "joined": 2,
    "pending": 1
  }
},
"message": "Referral summary fetched successfully."
}
```

**GET** /api/v1/customer/referrals/link

**Summary:** Fetch own referral link

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. Generates a unique customer referral code when missing. The link never exposes internal user IDs.

**Response body:**

```
{
  "success": true,
  "data": {
    "referralCode": "SARAH-M",
    "referralLink": "https://giftapp.com/share/sarah-m",
    "shareTitle": "Invite Friends, Earn Rewards",
    "shareMessage": "Join Gift App with my referral link and we both earn rewards after your first gift purchase.",
    "rewardText": "Get $10 credit after your friend's first gift purchase."
  },
  "message": "Referral link fetched successfully."
}
```

**GET** /api/v1/customer/referrals/history

**Summary:** List own referral history

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. History is scoped to referrals created by the logged-in customer.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/customer/referrals/redeem

**Summary:** Redeem own available reward credit

**Allowed role/access:** REGISTERED\_USER



**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. Creates a REDEEMED reward ledger entry. Redemption cannot exceed ledger-derived available credit.

**Request payload(s):**

payload

```
{
  "amount": 20,
  "redeemTo": "WALLET"
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "redeemedAmount": 20,
    "currency": "USD",
    "walletBalance": 20
  },
  "message": "Reward redeemed successfully."
}
```

**GET** /api/v1/customer/rewards/balance

**Summary:** Fetch own reward balance

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. Balance is calculated from RewardLedger entries, not a mutable user balance field.

**Response body:**

```
{
  "success": true,
  "data": {
    "availableCredit": 20,
    "lifetimeEarned": 20,
    "lifetimeRedeemed": 0,
    "currency": "USD"
  },
  "message": "Reward balance fetched successfully."
}
```

**GET** /api/v1/customer/rewards/ledger

**Summary:** List own reward ledger

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Returns ledger entries owned by the logged-in customer.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- type (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```

```
{
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/referrals/terms

**Summary:** Fetch referral terms

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. Returns config/env based customer referral terms for the mobile app.

**Response body:**

```
{
  "success": true,
  "data": {
    "title": "Referral Terms",
    "rewardAmount": 10,
    "currency": "USD",
    "qualificationRule": "Reward is credited after your referred friend completes their first gift purchase.",
    "terms": [
      "Referral rewards are available only for registered users.",
      "Reward is credited after the referred user's first successful purchase.",
      "Cancelled or refunded orders may revoke reward eligibility.",
      "Referral abuse may result in reward cancellation."
    ]
  },
  "message": "Referral terms fetched successfully."
}
```

## 05 Customer - Subscriptions

**GET** /api/v1/customer/subscription/plans

**Summary:** List public active subscription plans

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Uses admin-created active/public Subscription Plans. Customer cannot create/update/delete plans.

**Parameters:**

- `billingCycle` (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "plan_premium",
      "name": "Premium",
      "monthlyPrice": 4.99,
      "yearlyPrice": 39.99,
      "currency": "USD",
      "isPopular": true,
      "yearlySavingsPercent": 30,
      "features": [
        {
          "key": "ai_gift_recommendations",
          "label": "Ai Gift Recommendations",
          "enabled": true
        }
      ]
    }
  ]
}
```

```

    }
  ],
  "limits": {
    "unlimitedCredits": true
  }
}
],
"message": "Subscription plans fetched successfully."
}

```

**GET** /api/v1/customer/subscription/current

**Summary:** Fetch own current subscription

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Returns FREE state when no active premium subscription exists.

**Response body:**

```

{
  "success": true,
  "data": {
    "tier": "PREMIUM",
    "subscription": {
      "id": "sub_id",
      "planId": "plan_premium",
      "planName": "Premium",
      "billingCycle": "MONTHLY",
      "status": "ACTIVE",
      "isPremium": true,
      "cancelAtPeriodEnd": false,
      "currentPeriodStart": "2026-04-01T00:00:00.000Z",
      "currentPeriodEnd": "2026-05-01T00:00:00.000Z"
    }
  },
  "message": "Current subscription fetched successfully."
}

```

**POST** /api/v1/customer/subscription/checkout

**Summary:** Create Stripe subscription checkout

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Backend calculates price from admin-created SubscriptionPlan and optional coupon. Uses Stripe subscription flow with payment\_behavior=default\_incomplete.

**Request payload(s):**

payload

```

{
  "planId": "plan_premium",
  "billingCycle": "MONTHLY",
  "paymentMethodId": "pm_123",
  "couponCode": "SUMMER25"
}

```

**Response body:**

```

{
  "success": true,
  "data": {
    "subscriptionId": "sub_local_id",

```

```
"stripeSubscriptionId": "sub_stripe_123",
"clientSecret": "seti_client_secret",
"status": "INCOMPLETE",
"amountDue": 4.99,
"currency": "USD"
},
"message": "Subscription checkout created successfully."
}
```

**POST** /api/v1/customer/subscription/confirm

**Summary:** Confirm Stripe subscription activation

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Fetches Stripe subscription server-side and activates local entitlement when active/trialing.

**Request payload(s):**

payload

```
{
  "customerSubscriptionId": "<string>",
  "stripeSubscriptionId": "<string>"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/customer/subscription/cancel

**Summary:** Cancel own subscription

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Supports immediate cancellation or cancel\_at\_period\_end in Stripe. Does not delete local subscription record.

**Request payload(s):**

payload

```
{
  "cancelMode": "IMMEDIATELY",
  "reason": "<string>"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/customer/subscription/reactivate

**Summary:** Reactivate scheduled cancellation

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Works only when own subscription has cancelAtPeriodEnd=true.

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/subscription/invoices

**Summary:** List own subscription invoices

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Returns invoices synced from Stripe subscription webhooks.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "invoice_id",
      "stripeInvoiceId": "in_123",
      "amountDue": 4.99,
      "amountPaid": 4.99,
      "currency": "USD",
      "status": "PAID",
      "invoicePdfUrl": "https://cdn.yourdomain.com/invoices/invoice.pdf",
      "periodStart": "2026-04-01T00:00:00.000Z",
      "periodEnd": "2026-05-01T00:00:00.000Z",
      "createdAt": "2026-04-01T00:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Subscription invoices fetched successfully."
}
```

**GET** /api/v1/customer/subscription/invoices/{id}

**Summary:** Fetch own subscription invoice details

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/customer/subscription/apply-coupon

**Summary:** Preview subscription coupon

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Validates coupon against active coupon rules and plan restrictions; frontend discount amounts are ignored.

**Request payload(s):**

payload

```
{
  "planId": "<string>",
  "billingCycle": "MONTHLY",
  "couponCode": "<string>"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 05 Customer - Wallet

**GET** /api/v1/customer/wallet

**Summary:** Fetch own wallet

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Wallet is lazily created and balances are backed by wallet ledger entries.

**Response body:**

```
{
  "success": true,
  "data": {
    "totalBalance": 1240.5,
    "giftCredits": 350,
    "cashBalance": 890.5,
    "currency": "USD",
    "defaultPaymentMethod": {
      "id": "pm_xxx",
      "type": "CARD",

```

```

    "brand": "visa",
    "last4": "4242",
    "expiryMonth": 9,
    "expiryYear": 2025,
    "isDefault": true
  },
  "defaultBankAccount": {
    "id": "bank_account_id",
    "bankName": "Chase Bank",
    "last4": "8821",
    "isDefault": false
  }
},
"message": "Wallet fetched successfully."
}

```

**POST** /api/v1/customer/wallet/add-funds

**Summary:** Create wallet top-up payment

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. Uses Stripe PaymentIntent. Wallet is credited only after successful server-side confirmation/webhook.

**Request payload(s):**

payload

```

{
  "amount": 100,
  "currency": "USD",
  "paymentMethod": "STRIPE_CARD",
  "stripePaymentMethodId": "pm_xxx"
}

```

**Response body:**

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

**GET** /api/v1/customer/wallet/history

**Summary:** List own wallet history

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. Positive amounts are credits, negative amounts are debits. Results are scoped to the logged-in customer.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- type (query, optional, string)
- status (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

**Response body:**

```

{
  "success": true,
  "data": "<response returned by endpoint>",

```

```
{
  "message": "Request completed successfully."
}
```

## 05 Customer - Payment Methods

**GET** /api/v1/customer/bank-accounts

**Summary:** List own bank accounts

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account.

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "bank_account_id",
      "accountHolderName": "John Smith",
      "bankName": "Chase Bank",
      "last4": "8821",
      "maskedAccount": "**** 8821",
      "isDefault": false
    }
  ],
  "message": "Bank accounts fetched successfully."
}
```

**POST** /api/v1/customer/bank-accounts

**Summary:** Link placeholder bank account

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. Stores only masked display data. Full IBAN/account number is never returned.

**Request payload(s):**

payload

```
{
  "accountHolderName": "John Smith",
  "bankName": "Chase Bank",
  "ibanOrAccountNumber": "1234567890",
  "isDefault": false
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/customer/bank-accounts/{id}/default

**Summary:** Set own default bank account

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account.



**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/customer/bank-accounts/{id}

**Summary:** Delete own bank account

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/payment-methods

**Summary:** List supported customer payment methods

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account.

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "key": "STRIPE_CARD",
      "label": "Credit/Debit Card",
      "enabled": true
    },
    {
      "key": "BANK_TRANSFER",
      "label": "Bank Payment",
      "enabled": true
    },
  ]
}
```

```
    "key": "E_WALLET",
    "label": "E-Wallet",
    "enabled": false
  }
],
"message": "Payment methods fetched successfully."
}
```

**POST** /api/v1/customer/payment-methods/setup-intent

**Summary:** Create Stripe SetupIntent for saving card

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. Frontend confirms card with Stripe SDK. Backend never accepts raw card number or CVV.

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": {
    "setupIntentId": "seti_xxx",
    "clientSecret": "seti_xxx_secret_xxx",
    "publishableKey": "pk_test_xxx"
  },
  "message": "Setup intent created successfully."
}
```

**GET** /api/v1/customer/payment-methods/saved

**Summary:** List own saved payment methods

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. Returns masked Stripe card metadata only.

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "pm_xxx",
      "type": "CARD",
      "brand": "visa",
      "last4": "4242",
      "expiryMonth": 9,
      "expiryYear": 2025,
      "isDefault": true
    }
  ],
  "message": "Saved payment methods fetched successfully."
}
```

**PATCH** /api/v1/customer/payment-methods/{id}/default

**Summary:** Set own default payment method

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/customer/payment-methods/{id}

**Summary:** Delete own saved payment method

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. Rejects deletion when the method is used by an active recurring payment.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 06 Payments

**POST** /api/v1/customer/payments/create-intent

**Summary:** Create payment intent from active cart

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Amount is calculated from backend cart totals; frontend amount is never accepted.

**Request payload(s):**

stripe

```
{
  "cartId": "cmf0cartactive001",
  "paymentMethod": "STRIPE_CARD"
}
```

cod

```
{
  "cartId": "cmf0cartactive001",
  "paymentMethod": "COD"
}
```

**Response body:**

```
{
  "success": true,
  "data": {
    "paymentId": "payment_id",
    "stripePaymentIntentId": "pi_xxx",
    "clientSecret": "pi_xxx_secret_xxx",
    "publishableKey": "pk_live_or_test",
    "amount": 10999,
    "currency": "PKR"
  },
  "message": "Payment intent created successfully."
}
```

**POST** /api/v1/customer/payments/confirm

**Summary:** Confirm Stripe payment

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED\_USER only. Retrieves Stripe PaymentIntent server-side before updating local payment status.

**Request payload(s):**

payload

```
{
  "paymentId": "cmf0payment001",
  "stripePaymentIntentId": "pi_3Pxxxxxxxxxxxxxxxx"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/payments/{id}

**Summary:** Fetch own payment details

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": {
    "paymentId": "payment_id",

```

```
"provider": "STRIPE",
"stripePaymentIntentId": "pi_xxx",
"amount": 109.99,
"currency": "PKR",
"status": "SUCCEEDED",
"paymentMethod": "STRIPE_CARD",
"failureReason": null
},
"message": "Payment fetched successfully."
}
```

**POST** /api/v1/payments/stripe/webhook

**Summary:** Stripe webhook endpoint

**Allowed role/access:** PUBLIC

**Notes:** Access: PUBLIC. PUBLIC. Verifies Stripe-Signature using the configured webhook secret before processing events.

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/money-gifts

**Summary:** List own money gifts

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/customer/money-gifts

**Summary:** Send payment as gift

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account. Creates a customer-to-recipient money gift record and Stripe PaymentIntent for STRIPE\_CARD.

**Request payload(s):**

create

```
{
  "amount": 100,
  "currency": "PKR",
  "recipientContactId": "cmf0contactmary001",
  "message": "Hope this helps. Enjoy your day!",
  "messageMediaUrls": [],
  "deliveryDate": "2026-12-24T00:00:00.000Z",
}
```

```
"repeatAnnually": false,
"paymentMethod": "STRIPE_CARD"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/customer/money-gifts/{id}

**Summary:** Fetch own money gift details

**Allowed role/access:** REGISTERED\_USER

**Notes:** Access: REGISTERED\_USER. REGISTERED\_USER only. Endpoint is scoped to the authenticated customer account.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 06 Notifications

**GET** /api/v1/notifications

**Summary:** List notifications

**Allowed role/access:** SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER

**Notes:** Access: SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. Access is scoped to the authenticated account. JWT auth. Returns only notifications belonging to the logged-in account. Supports All, Unread, Birthdays, Deliveries, and New Contacts filters. No group gift notifications are supported.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- filter (query, optional, string)
- type (query, optional, string)
- isRead (query, optional, boolean)
- groupByDate (query, optional, boolean)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "notification_id",
      "title": "Payment successful",
      "message": "Your payment was completed successfully.",
    }
  ]
}
```

```

        "type": "PAYMENT_SUCCEEDED",
        "isRead": false,
        "metadata": {
            "paymentId": "payment_id"
        },
        "createdAt": "2026-05-09T10:00:00.000Z"
    }
],
"meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
},
"message": "Notifications fetched successfully"
}

```

**GET** /api/v1/notifications/summary

**Summary:** Fetch notification summary

**Allowed role/access:** SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER

**Notes:** Access: SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. Access is scoped to the authenticated account. JWT auth. Counts only notifications belonging to the logged-in account.

**Response body:**

```

{
  "success": true,
  "data": {
    "total": 12,
    "unread": 3,
    "byType": {
      "PAYMENT_SUCCEEDED": 2,
      "RECURRING_PAYMENT_CHARGE_FAILED": 1,
      "BROADCAST": 9
    }
  },
  "message": "Notification summary fetched successfully"
}

```

**GET** /api/v1/notifications/preferences

**Summary:** Fetch notification preferences

**Allowed role/access:** SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER

**Notes:** Access: SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. Access is scoped to the authenticated account. JWT auth. Preferences belong only to the logged-in account.

**Response body:**

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

**PATCH** /api/v1/notifications/preferences

**Summary:** Update notification preferences

**Allowed role/access:** SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER

**Notes:** Access: SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. Access is scoped to the authenticated account. JWT auth. Push toggle does not delete device tokens. No group gift preference exists.

**Request payload(s):**

payload

```
{
  "pushEnabled": true,
  "emailEnabled": true,
  "smsEnabled": false,
  "dealUpdatesEnabled": true,
  "birthdayRemindersEnabled": true,
  "deliveryUpdatesEnabled": true,
  "newContactAlertsEnabled": true,
  "providerOrderAlerts": {
    "newOrders": true,
    "orderCancellations": true,
    "orderDelays": false
  },
  "providerAccountActivity": {
    "securityAlerts": true,
    "loginFromNewDevice": true
  },
  "providerMarketingUpdates": {
    "weeklyPerformanceSummary": true,
    "newFeatureAnnouncements": false,
    "promotionalOffers": false
  }
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/notifications/read-all

**Summary:** Mark all own notifications as read

**Allowed role/access:** SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER

**Notes:** Access: SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. Access is scoped to the authenticated account. JWT auth. Marks only notifications belonging to the logged-in account.

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```



**PATCH** /api/v1/notifications/{id}/read

**Summary:** Mark notification as read

**Allowed role/access:** SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER

**Notes:** Access: SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. Access is scoped to the authenticated account. JWT auth. Notification must belong to the logged-in account.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/notifications/{id}/action

**Summary:** Process notification action

**Allowed role/access:** SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER

**Notes:** Access: SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. Access is scoped to the authenticated account. JWT auth. Supports SEND\_GIFT, REMIND\_ME\_LATER, VIEW\_ORDER, VIEW\_CONTACT. Group gift actions are not supported.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

sendGift

```
{
  "action": "SEND_GIFT"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/notifications/device-tokens

**Summary:** Save device token

**Allowed role/access:** SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER

**Notes:** Access: SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. Access is scoped to the authenticated account. JWT auth. Token belongs only to logged-in account. Duplicate deviceId updates existing record.

**Request payload(s):**

payload

```
{
  "token": "ExponentPushToken[xxxxxxxxxxxxxxxxxxxxxx]",
  "platform": "IOS",
  "deviceId": "ios-iphone-15-pro-device-id"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/notifications/device-tokens/{id}

**Summary:** Disable device token

**Allowed role/access:** SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER

**Notes:** Access: SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. Access is scoped to the authenticated account. JWT auth. Users can disable only their own device tokens.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 06 Broadcast Notifications

**GET** /api/v1/broadcasts

**Summary:** List Broadcasts

**Allowed role/access:** SUPER\_ADMIN or ADMIN with broadcasts.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with broadcasts.read. SUPER\_ADMIN or ADMIN with broadcasts.read permission.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- channel (query, optional, string)
- priority (query, optional, string)
- createdFrom (query, optional, string)
- createdTo (query, optional, string)
- scheduledFrom (query, optional, string)
- scheduledTo (query, optional, string)

- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/broadcasts

**Summary:** Create Broadcasts

**Allowed role/access:** SUPER\_ADMIN or ADMIN with broadcasts.create

**Notes:** Access: SUPER\_ADMIN or ADMIN with broadcasts.create. SUPER\_ADMIN or ADMIN with broadcasts.create permission.

**Request payload(s):**

payload

```
{
  "title": "<string>",
  "message": "<string>",
  "imageUrl": "<string>",
  "ctaLabel": "<string>",
  "ctaUrl": "<string>",
  "channels": [
    "EMAIL"
  ],
  "priority": "LOW"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/broadcasts/{id}

**Summary:** Fetch Broadcasts details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with broadcasts.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with broadcasts.read. SUPER\_ADMIN or ADMIN with broadcasts.read permission.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/broadcasts/{id}

**Summary:** Update Broadcasts

**Allowed role/access:** SUPER\_ADMIN or ADMIN with broadcasts.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with broadcasts.update. SUPER\_ADMIN or ADMIN with broadcasts.update permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "title": "<string>",
  "message": "<string>",
  "imageUrl": "<string>",
  "ctaLabel": "<string>",
  "ctaUrl": "<string>",
  "channels": [
    "EMAIL"
  ],
  "priority": "LOW"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/broadcasts/{id}/targeting

**Summary:** Update Broadcasts Targeting

**Allowed role/access:** SUPER\_ADMIN or ADMIN with broadcasts.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with broadcasts.update. SUPER\_ADMIN or ADMIN with broadcasts.update permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "mode": "ALL_USERS",
  "roles": [
    "ADMIN"
  ],
  "filters": {
    "location": "<string>",
    "onlyVerifiedEmails": true,
    "excludeUnsubscribed": true,
    "excludeSuspended": true
  }
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/broadcasts/estimate-reach

**Summary:** Create Broadcasts Estimate Reach

**Allowed role/access:** SUPER\_ADMIN or ADMIN with broadcasts.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with broadcasts.read. SUPER\_ADMIN or ADMIN with broadcasts.read permission.

**Request payload(s):**

payload

```
{
  "channels": [
    "EMAIL"
  ],
  "targeting": {
    "mode": "ALL_USERS",
    "roles": [
      "ADMIN"
    ],
    "filters": {
      "location": "<string>",
      "onlyVerifiedEmails": true,
      "excludeUnsubscribed": true,
      "excludeSuspended": true
    }
  }
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/broadcasts/{id}/schedule

**Summary:** Update Broadcasts Schedule

**Allowed role/access:** SUPER\_ADMIN or ADMIN with broadcasts.schedule

**Notes:** Access: SUPER\_ADMIN or ADMIN with broadcasts.schedule. SUPER\_ADMIN or ADMIN with broadcasts.schedule permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "sendMode": "NOW",
  "scheduledAt": "<string>",
  "timezone": "<string>",
  "isRecurring": true,
}
```

```
"recurrence": {}  
}
```

**Response body:**

```
{  
  "success": true,  
  "data": "<response returned by endpoint>",  
  "message": "Request completed successfully."  
}
```

**POST** /api/v1/broadcasts/{id}/cancel

**Summary:** Create Broadcasts Cancel

**Allowed role/access:** SUPER\_ADMIN or ADMIN with broadcasts.cancel

**Notes:** Access: SUPER\_ADMIN or ADMIN with broadcasts.cancel. SUPER\_ADMIN or ADMIN with broadcasts.cancel permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{  
  "reason": "<string>"  
}
```

**Response body:**

```
{  
  "success": true,  
  "data": "<response returned by endpoint>",  
  "message": "Request completed successfully."  
}
```

**GET** /api/v1/broadcasts/{id}/report

**Summary:** Fetch Broadcasts Report details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with broadcasts.report.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with broadcasts.report.read. SUPER\_ADMIN or ADMIN with broadcasts.report.read permission.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{  
  "success": true,  
  "data": "<response returned by endpoint>",  
  "message": "Request completed successfully."  
}
```

**GET** /api/v1/broadcasts/{id}/recipients

**Summary:** Fetch Broadcasts Recipients details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with broadcasts.report.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with broadcasts.report.read. SUPER\_ADMIN or ADMIN with broadcasts.report.read permission.

**Parameters:**

- id (path, required, string)
- page (query, optional, number)
- limit (query, optional, number)
- channel (query, optional, string)
- status (query, optional, string)
- search (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 07 Plans & Coupons

**GET** /api/v1/subscription-plans

**Summary:** List Subscription Plans

**Allowed role/access:** SUPER\_ADMIN or ADMIN with subscriptionPlans.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with subscriptionPlans.read. SUPER\_ADMIN or ADMIN with subscriptionPlans.read permission.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- visibility (query, optional, string)
- billingCycle (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/subscription-plans

**Summary:** Create Subscription Plans

**Allowed role/access:** SUPER\_ADMIN or ADMIN with subscriptionPlans.create

**Notes:** Access: SUPER\_ADMIN or ADMIN with subscriptionPlans.create. SUPER\_ADMIN or ADMIN with subscriptionPlans.create permission.

**Request payload(s):**

payload

```
{
  "name": "<string>",
  "description": "<string>",
}
```

```
"monthlyPrice": 1.0,
"yearlyPrice": 1.0,
"currency": "USD",
"visibility": "PUBLIC",
"status": "ACTIVE",
"isPopular": true,
"features": {},
"limits": {
  "maxGiftsPerMonth": 1.0,
  "maxGroupGiftingEvents": 1.0,
  "maxTeamMembers": 1.0,
  "storageGb": 1.0
}
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/subscription-plans/stats

**Summary:** List Subscription Plans Stats

**Allowed role/access:** SUPER\_ADMIN or ADMIN with subscriptionPlans.analytics.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with subscriptionPlans.analytics.read. SUPER\_ADMIN or ADMIN with subscriptionPlans.analytics.read permission.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/subscription-plans/{id}

**Summary:** Fetch Subscription Plans details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with subscriptionPlans.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with subscriptionPlans.read. SUPER\_ADMIN or ADMIN with subscriptionPlans.read permission.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/subscription-plans/{id}

**Summary:** Update Subscription Plans



**Allowed role/access:** SUPER\_ADMIN or ADMIN with subscriptionPlans.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with subscriptionPlans.update. SUPER\_ADMIN or ADMIN with subscriptionPlans.update permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "name": "<string>",
  "description": "<string>",
  "monthlyPrice": 1.0,
  "yearlyPrice": 1.0,
  "currency": "<string>",
  "visibility": "PUBLIC",
  "status": "ACTIVE",
  "isPopular": true,
  "features": {},
  "limits": {
    "maxGiftsPerMonth": 1.0,
    "maxGroupGiftingEvents": 1.0,
    "maxTeamMembers": 1.0,
    "storageGb": 1.0
  }
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/subscription-plans/{id}

**Summary:** Delete Subscription Plans

**Allowed role/access:** SUPER\_ADMIN or ADMIN with subscriptionPlans.delete

**Notes:** Access: SUPER\_ADMIN or ADMIN with subscriptionPlans.delete. SUPER\_ADMIN or ADMIN with subscriptionPlans.delete permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/subscription-plans/{id}/status

**Summary:** Update Subscription Plans Status

**Allowed role/access:** SUPER\_ADMIN or ADMIN with subscriptionPlans.status.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with subscriptionPlans.status.update. SUPER\_ADMIN or ADMIN with subscriptionPlans.status.update permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "status": "ACTIVE",
  "reason": "<string>"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/subscription-plans/{id}/visibility

**Summary:** Update Subscription Plans Visibility

**Allowed role/access:** SUPER\_ADMIN or ADMIN with subscriptionPlans.visibility.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with subscriptionPlans.visibility.update. SUPER\_ADMIN or ADMIN with subscriptionPlans.visibility.update permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "visibility": "PUBLIC"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/subscription-plans/{id}/analytics

**Summary:** Fetch Subscription Plans Analytics details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with subscriptionPlans.analytics.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with subscriptionPlans.analytics.read. SUPER\_ADMIN or ADMIN with subscriptionPlans.analytics.read permission.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/plan-features/catalog

**Summary:** List Plan Features Catalog

**Allowed role/access:** SUPER\_ADMIN or ADMIN with planFeatures.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with planFeatures.read. SUPER\_ADMIN or ADMIN with planFeatures.read permission.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/plan-features

**Summary:** List Plan Features

**Allowed role/access:** SUPER\_ADMIN or ADMIN with planFeatures.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with planFeatures.read. SUPER\_ADMIN or ADMIN with planFeatures.read permission.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- isActive (query, optional, boolean)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/plan-features

**Summary:** Create Plan Features

**Allowed role/access:** SUPER\_ADMIN or ADMIN with planFeatures.create

**Notes:** Access: SUPER\_ADMIN or ADMIN with planFeatures.create. SUPER\_ADMIN or ADMIN with planFeatures.create permission.

**Request payload(s):**

payload

```
{
  "key": "<string>",
  "label": "<string>",
  "description": "<string>",
  "type": "BOOLEAN",
  "isActive": true,
}
```

```
"sortOrder": 1.0
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/plan-features/{id}

**Summary:** Fetch Plan Features details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with planFeatures.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with planFeatures.read. SUPER\_ADMIN or ADMIN with planFeatures.read permission.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/plan-features/{id}

**Summary:** Update Plan Features

**Allowed role/access:** SUPER\_ADMIN or ADMIN with planFeatures.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with planFeatures.update. SUPER\_ADMIN or ADMIN with planFeatures.update permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "key": "<string>",
  "label": "<string>",
  "description": "<string>",
  "type": "BOOLEAN",
  "isActive": true,
  "sortOrder": 1.0
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/plan-features/{id}

**Summary:** Delete Plan Features

**Allowed role/access:** SUPER\_ADMIN or ADMIN with planFeatures.delete

**Notes:** Access: SUPER\_ADMIN or ADMIN with planFeatures.delete. SUPER\_ADMIN or ADMIN with planFeatures.delete permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/coupons

**Summary:** List Coupons

**Allowed role/access:** SUPER\_ADMIN or ADMIN with coupons.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with coupons.read. SUPER\_ADMIN or ADMIN with coupons.read permission.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- planId (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/coupons

**Summary:** Create Coupons

**Allowed role/access:** SUPER\_ADMIN or ADMIN with coupons.create

**Notes:** Access: SUPER\_ADMIN or ADMIN with coupons.create. SUPER\_ADMIN or ADMIN with coupons.create permission.

**Request payload(s):**

payload

```
{
  "code": "<string>",
  "description": "<string>",
  "discountType": "PERCENTAGE",
  "discountValue": 1.0,
  "planIds": [
    "<string>"
  ],
}
```

```
"startsWith": "<string>",
"expiresAt": "<string>",
"maxRedemptions": 1.0,
"isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/coupons/{id}

**Summary:** Fetch Coupons details

**Allowed role/access:** SUPER\_ADMIN or ADMIN with coupons.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with coupons.read. SUPER\_ADMIN or ADMIN with coupons.read permission.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/coupons/{id}

**Summary:** Update Coupons

**Allowed role/access:** SUPER\_ADMIN or ADMIN with coupons.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with coupons.update. SUPER\_ADMIN or ADMIN with coupons.update permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "code": "<string>",
  "description": "<string>",
  "discountType": "PERCENTAGE",
  "discountValue": 1.0,
  "planIds": [
    "<string>"
  ],
  "startsWith": "<string>",
  "expiresAt": "<string>",
  "maxRedemptions": 1.0,
  "isActive": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/coupons/{id}

**Summary:** Delete Coupons

**Allowed role/access:** SUPER\_ADMIN or ADMIN with coupons.delete

**Notes:** Access: SUPER\_ADMIN or ADMIN with coupons.delete. SUPER\_ADMIN or ADMIN with coupons.delete permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/coupons/{id}/status

**Summary:** Update Coupons Status

**Allowed role/access:** SUPER\_ADMIN or ADMIN with coupons.status.update

**Notes:** Access: SUPER\_ADMIN or ADMIN with coupons.status.update. SUPER\_ADMIN or ADMIN with coupons.status.update permission.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
{
  "status": "ACTIVE",
  "reason": "<string>"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 07 Storage

**POST** /api/v1/uploads/presigned-url

**Summary:** Create presigned upload URL

**Allowed role/access:** SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER

**Notes:** Access: SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. Backend derives ownerId/ownerRole from JWT. targetAccountId is forbidden for REGISTERED\_USER and PROVIDER, admin-only when authorized, and allowed for SUPER\_ADMIN. Backend derives ownerId/ownerRole from the authenticated JWT. targetAccountId is forbidden for REGISTERED\_USER and PROVIDER, allowed only for SUPER\_ADMIN/authorized ADMIN dashboard uploads. Include giftId only for gift image uploads.

**Request payload(s):**

giftUpload

```
{
  "folder": "gift-images",
  "fileName": "perfume.png",
  "contentType": "image/png",
  "sizeBytes": 1048576,
  "giftId": "gift_id"
}
```

normalUpload

```
{
  "folder": "provider-avatars",
  "fileName": "avatar.png",
  "contentType": "image/png",
  "sizeBytes": 1048576
}
```

adminOnBehalf

```
{
  "folder": "provider-logos",
  "fileName": "logo.png",
  "contentType": "image/png",
  "sizeBytes": 1048576,
  "targetAccountId": "provider_user_id"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/uploads/complete

**Summary:** Complete upload

**Allowed role/access:** SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER

**Notes:** Access: SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. Completes only uploads accessible to the authenticated account. Authenticated upload completion. REGISTERED\_USER and PROVIDER can complete only their own uploads. ADMIN defaults to own uploads. SUPER\_ADMIN can manage dashboard/admin inspection flows.

**Request payload(s):**

payload



```
{
  "uploadId": "<string>",
  "sizeBytes": 1.0
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/uploads

**Summary:** List uploads

**Allowed role/access:** SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER

**Notes:** Access: SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. REGISTERED\_USER/PROVIDER list only own uploads; ownerId is ignored. ADMIN lists own uploads by default and may use ownerId only for authorized managed access. SUPER\_ADMIN may inspect by ownerId. REGISTERED\_USER: ownerId query is ignored and only own uploads are listed. PROVIDER: ownerId query is ignored and only own uploads are listed. ADMIN: lists own uploads by default and may use ownerId only for managed dashboard access when authorized. SUPER\_ADMIN: can use ownerId for dashboard/admin inspection.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- folder (query, optional, string)
- ownerId (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": [
    {
      "id": "upload_id",
      "ownerId": "user_id",
      "ownerRole": "REGISTERED_USER",
      "targetAccountId": null,
      "folder": "user-avatars",
      "fileName": "avatar.png",
      "contentType": "image/png",
      "sizeBytes": 1048576,
      "fileUrl": "https://cdn.yourdomain.com/user-avatars/avatar.png",
      "storageKey": "user-avatars/user_id/uuid-avatar.png",
      "status": "COMPLETED",
      "giftId": null,
      "createdAt": "2026-04-08T09:00:00.000Z",
      "updatedAt": "2026-04-08T09:01:00.000Z",
      "completedAt": "2026-04-08T09:01:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
}
```

```
"message": "Uploads fetched successfully."
}
```

**GET** /api/v1/uploads/{id}

**Summary:** Fetch upload details

**Allowed role/access:** SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER

**Notes:** Access: SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. REGISTERED\_USER/PROVIDER can fetch only own uploads. ADMIN defaults to own uploads. SUPER\_ADMIN may inspect uploads. REGISTERED\_USER and PROVIDER can fetch only own uploads. ADMIN fetches own uploads by default. SUPER\_ADMIN can inspect uploads for dashboard/admin operations.

**Parameters:**

- id (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**DELETE** /api/v1/uploads/{id}

**Summary:** Delete upload

**Allowed role/access:** SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER

**Notes:** Access: SUPER\_ADMIN, ADMIN, PROVIDER, or REGISTERED\_USER. REGISTERED\_USER/PROVIDER can delete only own uploads. ADMIN defaults to own uploads. SUPER\_ADMIN may delete inspected uploads. REGISTERED\_USER and PROVIDER can delete only own uploads. ADMIN deletes own uploads by default. SUPER\_ADMIN can delete inspected dashboard uploads. Deletion is permanent in the database.

**Parameters:**

- id (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

## 08 Chat - Unified Threads

**GET** /api/v1/chats

**Summary:** List chat threads

**Allowed role/access:** REGISTERED\_USER, PROVIDER, SUPER\_ADMIN, or ADMIN with chat/support permission

**Notes:** Access: REGISTERED\_USER, PROVIDER, SUPER\_ADMIN, or ADMIN with chat/support permission. Role-aware thread listing. Customers/providers see own order/support threads; SUPER\_ADMIN sees support threads; ADMIN is scoped

by supportChats.read/read.all or moderation chat permissions. Role-aware list for customer order chats, provider buyer chats, support chats, and admin-visible support/moderation chat views.

**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- threadType (query, optional, string)
- status (query, optional, string)
- unreadOnly (query, optional, boolean)
- sourceType (query, optional, string)
- sourceId (query, optional, string)
- participantRole (query, optional, string)
- participantId (query, optional, string)
- assignedToAdminId (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/chats/quick-replies

**Summary:** Fetch role-aware chat quick replies

**Allowed role/access:** REGISTERED\_USER, PROVIDER, SUPER\_ADMIN, or ADMIN

**Notes:** Access: REGISTERED\_USER, PROVIDER, SUPER\_ADMIN, or ADMIN. Role-aware quick replies.

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/chats/threads

**Summary:** Create or get a chat thread

**Allowed role/access:** REGISTERED\_USER, PROVIDER, SUPER\_ADMIN, or ADMIN with supportChats.reply/messageModeration permission

**Notes:** Access: REGISTERED\_USER, PROVIDER, SUPER\_ADMIN, or ADMIN with supportChats.reply/messageModeration permission. Create or get an order/support/moderation chat thread based on role and sourceType.

**Request payload(s):**

payload

```
{
  "threadType": "ORDER_CHAT",
  "sourceType": "CUSTOMER_ORDER",
  "sourceId": "order_id",
  "subject": "Order support",
  "initialMessage": "Can you confirm delivery time?",
  "attachmentUrls": [],
  "createIfMissing": true,
}
```

```
"participantId": "participant_user_id",
"participantRole": "REGISTERED_USER"
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/chats/threads/{threadId}

**Summary:** Fetch chat thread details

**Allowed role/access:** REGISTERED\_USER, PROVIDER, SUPER\_ADMIN, or ADMIN with chat/support permission

**Notes:** Access: REGISTERED\_USER, PROVIDER, SUPER\_ADMIN, or ADMIN with chat/support permission. Fetch a thread only when the authenticated role can access it.

**Parameters:**

- threadId (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/chats/threads/{threadId}/messages

**Summary:** Fetch chat thread messages

**Allowed role/access:** REGISTERED\_USER, PROVIDER, SUPER\_ADMIN, or ADMIN with chat/support permission

**Notes:** Access: REGISTERED\_USER, PROVIDER, SUPER\_ADMIN, or ADMIN with chat/support permission. Fetch messages only for accessible threads.

**Parameters:**

- threadId (path, required, string)
- page (query, optional, number)
- limit (query, optional, number)
- before (query, optional, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/chats/threads/{threadId}/messages

**Summary:** Send a chat message

**Allowed role/access:** REGISTERED\_USER, PROVIDER, SUPER\_ADMIN, or ADMIN with supportChats.reply

**Notes:** Access: REGISTERED\_USER, PROVIDER, SUPER\_ADMIN, or ADMIN with supportChats.reply. Send a message in an accessible order/support thread.

**Parameters:**

- threadId (path, required, string)

**Request payload(s):**

payload

```
{
  "clientId": "mobile-generated-uuid",
  "messageType": "TEXT",
  "body": "Can you confirm delivery time?",
  "attachmentUrls": []
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/chats/threads/{threadId}/read

**Summary:** Mark a chat thread as read

**Allowed role/access:** REGISTERED\_USER, PROVIDER, SUPER\_ADMIN, or ADMIN with supportChats.read

**Notes:** Access: REGISTERED\_USER, PROVIDER, SUPER\_ADMIN, or ADMIN with supportChats.read. Mark an accessible thread as read for the authenticated participant/admin.

**Parameters:**

- threadId (path, required, string)

**Request payload(s):**

payload

```
"<standard success envelope>"
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**PATCH** /api/v1/chats/threads/{threadId}/status

**Summary:** Update chat thread status

**Allowed role/access:** SUPER\_ADMIN or ADMIN with supportChats.resolve

**Notes:** Access: SUPER\_ADMIN or ADMIN with supportChats.resolve. Update support thread status.

**Parameters:**

- threadId (path, required, string)

**Request payload(s):**

payload

```
{
  "status": "RESOLVED",
  "comment": "Issue resolved.",
}
```

```
"notifyParticipant": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/chats/threads/{threadId}/resolve

**Summary:** Resolve a support chat thread

**Allowed role/access:** SUPER\_ADMIN or ADMIN with supportChats.resolve

**Notes:** Access: SUPER\_ADMIN or ADMIN with supportChats.resolve. Resolve support chat and notify participant when requested.

**Parameters:**

- threadId (path, required, string)

**Request payload(s):**

payload

```
{
  "status": "RESOLVED",
  "comment": "Issue resolved.",
  "notifyParticipant": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**POST** /api/v1/chats/threads/{threadId}/reopen

**Summary:** Reopen a support chat thread

**Allowed role/access:** SUPER\_ADMIN or ADMIN with supportChats.resolve

**Notes:** Access: SUPER\_ADMIN or ADMIN with supportChats.resolve. Reopen support chat and notify participant when requested.

**Parameters:**

- threadId (path, required, string)

**Request payload(s):**

payload

```
{
  "status": "RESOLVED",
  "comment": "Issue resolved.",
  "notifyParticipant": true
}
```

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

**GET** /api/v1/chats/threads/{threadId}/audit-log

**Summary:** Fetch chat thread audit log

**Allowed role/access:** SUPER\_ADMIN or ADMIN with supportChats.read

**Notes:** Access: SUPER\_ADMIN or ADMIN with supportChats.read. Fetch audit trail for an accessible support/moderation thread.

**Parameters:**

- threadId (path, required, string)

**Response body:**

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```