

Gift App Backend — Full API Reference

Generated: 2026-05-18 11:23 UTC

This document is generated from the current OpenAPI for the Gift App backend. For each API, it includes allowed role/access, request payloads for write endpoints, and response bodies for read/write endpoints.

01 Auth

POST /api/v1/auth/users/register

Summary: Create Auth Users Register

Allowed role/access: PUBLIC

Notes: Access: PUBLIC. PUBLIC.

Request payload(s):

payload

```
{
  "email": "<string>",
  "password": "<string>",
  "firstName": "<string>",
  "lastName": "<string>",
  "phone": "<string>",
  "referralCode": "SARAH-M"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/auth/providers/register

Summary: Create Auth Providers Register

Allowed role/access: PUBLIC

Notes: Access: PUBLIC. PUBLIC.

Request payload(s):

payload

```
{
  "email": "<string>",
  "password": "<string>",
  "firstName": "<string>",
  "lastName": "<string>",
  "phone": "<string>",
  "referralCode": "SARAH-M",
  "businessName": "<string>",
  "businessCategoryId": "<string>",
  "taxId": "<string>",
  "businessAddress": "<string>",
  "fulfillmentMethods": [
    "PICKUP"
  ],
}
```

```
"autoAcceptOrders": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/auth/guest/session

Summary: Create Auth Guest Session

Allowed role/access: PUBLIC

Notes: Access: PUBLIC. PUBLIC.

Request payload(s):

payload

```
{
  "capabilities": [
    "<string>"
  ]
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/auth/login

Summary: Create Auth Login

Allowed role/access: PUBLIC

Notes: Access: PUBLIC. PUBLIC.

Request payload(s):

payload

```
{
  "email": "<string>",
  "password": "<string>"
}
```

Response body:

```
{
  "success": false,
  "error": {
    "code": "EMAIL_NOT_VERIFIED",
    "message": "Please verify your email before login",
    "user_verified": 0
  },
  "meta": {
    "statusCode": 403,
    "timestamp": "2026-05-18T11:04:05.524Z"
  }
}
```

```
}  
}
```

POST /api/v1/auth/refresh

Summary: Create Auth Refresh

Allowed role/access: PUBLIC

Notes: Access: PUBLIC. PUBLIC.

Request payload(s):

payload

```
{  
  "refreshToken": "<string>"  
}
```

Response body:

```
{  
  "success": true,  
  "data": "<response returned by endpoint>",  
  "message": "Request completed successfully."  
}
```

POST /api/v1/auth/logout

Summary: Create Auth Logout

Allowed role/access: Authenticated

Notes: Access: Authenticated. Authenticated JWT required.

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{  
  "success": true,  
  "data": "<response returned by endpoint>",  
  "message": "Request completed successfully."  
}
```

POST /api/v1/auth/verify-email

Summary: Create Auth Verify Email

Allowed role/access: Authenticated

Notes: Access: Authenticated. Authenticated JWT required.

Request payload(s):

payload

```
{  
  "otp": "<string>"  
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/auth/resend-otp

Summary: Create Auth Resend Otp

Allowed role/access: Authenticated

Notes: Access: Authenticated. Authenticated JWT required.

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/auth/resend-verification-email

Summary: Resend verification email for unverified login

Allowed role/access: PUBLIC

Notes: Access: PUBLIC. PUBLIC. Public endpoint. Always returns the same success message to avoid user enumeration. Sends verification OTP only when the email exists and is not verified.

Request payload(s):

payload

```
{
  "email": "user@example.com"
}
```

Response body:

```
{
  "success": true,
  "data": null,
  "message": "If the email is registered and unverified, a verification email has been sent."
}
```

POST /api/v1/auth/forgot-password

Summary: Create Auth Forgot Password

Allowed role/access: PUBLIC

Notes: Access: PUBLIC. PUBLIC.

Request payload(s):

payload

```
{
  "email": "user@example.com"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/auth/verify-reset-otp

Summary: Create Auth Verify Reset Otp

Allowed role/access: PUBLIC

Notes: Access: PUBLIC. PUBLIC.

Request payload(s):

payload

```
{
  "email": "user@example.com",
  "otp": "334018"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/auth/reset-password

Summary: Create Auth Reset Password

Allowed role/access: PUBLIC

Notes: Access: PUBLIC. PUBLIC.

Request payload(s):

payload

```
{
  "email": "user@example.com",
  "otp": "334018",
  "newPassword": "NewPassword@123"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/auth/change-password

Summary: Update Auth Change Password

Allowed role/access: Authenticated

Notes: Access: Authenticated. Authenticated JWT required.

Request payload(s):

payload

```
{
  "currentPassword": "<string>",
  "newPassword": "<string>"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/auth/me

Summary: List Auth Me

Allowed role/access: Authenticated

Notes: Access: Authenticated. Authenticated JWT required.

Response body:

```
{
  "success": true,
  "data": {
    "uid": "user_id",
    "role": "REGISTERED_USER",
    "email": "jane@example.com",
    "firstName": "Jane",
    "lastName": "Doe",
    "phone": "+923001234567",
    "avatarUrl": "https://cdn.yourdomain.com/user-avatars/jane.png",
    "permissions": null
  },
  "message": "Profile fetched successfully."
}
```

PATCH /api/v1/auth/me

Summary: Update Auth Me

Allowed role/access: Authenticated

Notes: Access: Authenticated. Authenticated JWT required.

Request payload(s):

payload

```
{
  "firstName": "Julian",
  "lastName": "Rivers",
  "phone": "+15551234567",
  "avatarUrl": "https://cdn.yourdomain.com/provider-avatars/julian.png"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/auth/sessions

Summary: List Auth Sessions

Allowed role/access: Authenticated

Notes: Access: Authenticated. Authenticated JWT required.

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "session_id",
      "deviceName": "Chrome on Mac",
      "location": "Lahore, PK",
      "ipAddress": "203.0.113.10",
      "isCurrent": true,
      "lastActiveAt": "2026-04-08T11:45:00.000Z"
    }
  ],
  "message": "Active sessions fetched successfully."
}
```

POST /api/v1/auth/sessions/logout-all

Summary: Create Auth Sessions Logout All

Allowed role/access: Authenticated

Notes: Access: Authenticated. Authenticated JWT required.

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/auth/sessions/{id}

Summary: Delete Auth Sessions

Allowed role/access: Authenticated

Notes: Access: Authenticated. Authenticated JWT required.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/auth/account

Summary: Delete Auth Account

Allowed role/access: Authenticated

Notes: Access: Authenticated. Authenticated JWT required.

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/auth/cancel-deletion

Summary: Create Auth Cancel Deletion

Allowed role/access: Authenticated

Notes: Access: Authenticated. Authenticated JWT required.

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

01 Auth - Login Attempts

GET /api/v1/login-attempts/stats

Summary: List Login Attempts Stats

Allowed role/access: SUPER_ADMIN or ADMIN with loginAttempts.read

Notes: Access: SUPER_ADMIN or ADMIN with loginAttempts.read. SUPER_ADMIN or ADMIN with loginAttempts.read permission.

Parameters:

- email (query, optional, string)
- status (query, optional, string)
- role (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)
- userId (query, optional, string)
- from (query, optional, string)
- to (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/login-attempts/export

Summary: List Login Attempts Export

Allowed role/access: SUPER_ADMIN or ADMIN with loginAttempts.export

Notes: Access: SUPER_ADMIN or ADMIN with loginAttempts.export. SUPER_ADMIN or ADMIN with loginAttempts.export permission.

Parameters:

- email (query, optional, string)
- status (query, optional, string)
- role (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)
- userId (query, optional, string)
- from (query, optional, string)
- to (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/login-attempts

Summary: List Login Attempts

Allowed role/access: SUPER_ADMIN or ADMIN with loginAttempts.read

Notes: Access: SUPER_ADMIN or ADMIN with loginAttempts.read. SUPER_ADMIN or ADMIN with loginAttempts.read permission.

Parameters:

- email (query, optional, string)
- status (query, optional, string)
- role (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)
- userId (query, optional, string)
- from (query, optional, string)
- to (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Staff Management

GET /api/v1/admins

Summary: List admin staff users

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Admin staff management is controlled by Super Admin only. SUPER_ADMIN only. Returns User.role = ADMIN staff accounts only; SUPER_ADMIN accounts are intentionally excluded.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- roleId (query, optional, string)
- role (query, optional, string)
- status (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "admin_id",
      "firstName": "Operations",
      "lastName": "Staff",
      "fullName": "Operations Staff",
      "email": "staff@example.com",
      "phone": "+15550000002",
      "role": {
        "id": "admin_role_id",
        "name": "Gift Manager",
        "slug": "gift-manager"
      },
      "isActive": true,
      "isVerified": true,
      "createdAt": "2026-05-09T10:00:00.000Z",
      "lastLoginAt": null
    }
  ],
  "meta": {
    "page": 1,
    "limit": 10,
    "total": 1,
    "totalPages": 1
  },
  "message": "Admins fetched successfully"
}
```

POST /api/v1/admins

Summary: Create admin staff user

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Creates ADMIN staff users only. Creates an ADMIN staff user under Super Admin. The roleId field is the AdminRole ID that controls this staff user's permissions. This endpoint cannot create SUPER_ADMIN, REGISTERED_USER, PROVIDER, or GUEST_USER accounts.

Request payload(s):

payload

```
{
  "email": "staff@example.com",
  "temporaryPassword": "Temp@123456",
  "generateTemporaryPassword": false,
  "mustChangePassword": true,
  "firstName": "Operations",
  "lastName": "Staff",
  "phone": "+15550000002",
  "title": "Operations Manager",
  "roleId": "admin_role_id",
  "avatarUrl": "https://cdn.yourdomain.com/admin-avatars/staff.png",
  "isActive": true,
  "sendInviteEmail": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admins/{id}

Summary: Fetch Admins details

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Fetches ADMIN staff details.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/admins/{id}

Summary: Update Admins

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Updates ADMIN staff account details.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "email": "staff.updated@example.com",
  "firstName": "<string>",
  "lastName": "<string>",
  "phone": "<string>",
  "avatarUrl": "<string>",
  "title": "<string>",
  "roleId": "<string>",
  "isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/admins/{id}

Summary: Permanently delete admin staff user

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Permanently deletes an ADMIN staff account. DANGER: This endpoint permanently deletes an ADMIN staff account from the database. This is not a soft delete. Use only from Super Admin danger zone screens. SUPER_ADMIN accounts and self-delete are blocked.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": {
    "deletedAdminId": "admin_id"
  },
  "message": "Admin staff user permanently deleted successfully."
}
```

PATCH /api/v1/admins/{id}/active-status

Summary: Update Admins Active Status

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Updates ADMIN staff active status.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/admins/{id}/password

Summary: Update Admins Password

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Changes ADMIN staff password from dashboard.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "temporaryPassword": "<string>",
  "generateTemporaryPassword": true,
  "mustChangePassword": true,
  "sendEmail": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Roles & Permissions

GET /api/v1/admin-roles

Summary: List Admin Roles

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Only SUPER_ADMIN can manage staff roles and permissions. Admin Roles / RBAC manages permission roles for ADMIN staff users only. SUPER_ADMIN has full immutable access and does not depend on AdminRole permissions.

Parameters:

- search (query, optional, string)
- isSystem (query, optional, boolean)
- isActive (query, optional, boolean)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin-roles

Summary: Create Admin Roles

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. ADMIN staff cannot create roles.

Request payload(s):

payload

```
{
  "name": "<string>",
  "description": "<string>",
  "permissions": {}
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin-roles/{id}

Summary: Fetch Admin Roles details

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. ADMIN staff cannot view role details.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/admin-roles/{id}

Summary: Update Admin Roles

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. ADMIN staff cannot update roles.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "name": "<string>",
  "description": "<string>",
  "isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/admin-roles/{id}

Summary: Delete Admin Roles

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. ADMIN staff cannot delete roles.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/admin-roles/{id}/permissions

Summary: Update Admin Roles Permissions

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. ADMIN staff cannot update role permissions.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "permissions": {}
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```

```
"message": "Request completed successfully."
}
```

GET /api/v1/permissions/catalog

Summary: List Permissions Catalog

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Read-only backend permission catalog. Read-only list of backend-supported permission keys that can be assigned to admin roles.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - User Management

GET /api/v1/users/export

Summary: List Users Export

Allowed role/access: SUPER_ADMIN or ADMIN with users.export

Notes: Access: SUPER_ADMIN or ADMIN with users.export. SUPER_ADMIN or ADMIN with users.export permission.

Parameters:

- search (query, optional, string)
- status (query, optional, string)
- registrationFrom (query, optional, string)
- registrationTo (query, optional, string)
- format (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/users

Summary: List registered users

Allowed role/access: SUPER_ADMIN or ADMIN with users.read

Notes: Access: SUPER_ADMIN or ADMIN with users.read. SUPER_ADMIN or ADMIN with users.read permission. SUPER_ADMIN/ADMIN with users.read permission.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- registrationFrom (query, optional, string)
- registrationTo (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "user_id",
      "email": "customer@example.com",
      "firstName": "Sarah",
      "lastName": "Johnson",
      "phone": "+923001234567",
      "role": "REGISTERED_USER",
      "isVerified": true,
      "isActive": true,
      "createdAt": "2026-05-09T10:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Users fetched successfully"
}
```

GET /api/v1/users/{id}

Summary: Fetch Users details

Allowed role/access: SUPER_ADMIN or ADMIN with users.read

Notes: Access: SUPER_ADMIN or ADMIN with users.read. SUPER_ADMIN or ADMIN with users.read permission.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/users/{id}

Summary: Update Users

Allowed role/access: SUPER_ADMIN or ADMIN with users.update

Notes: Access: SUPER_ADMIN or ADMIN with users.update. SUPER_ADMIN or ADMIN with users.update permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "firstName": "Alex",
  "lastName": "Johnson",
  "phone": "+15552345678",
  "avatarUrl": "https://<YOUR_PUBLIC_BUCKET_OR_CDN_URL>/user-avatars/avatar.jpg",
}
```

```
{
  "location": "New York, USA"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/users/{id}

Summary: Permanently delete registered user

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Permanent delete danger-zone endpoint. DANGER: This endpoint permanently deletes/anonymizes the registered user and removes related non-financial data from the database. This is not a soft delete. Use only from Super Admin danger zone screens.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": {
    "deletedUserId": "user_id",
    "deletedRelatedRecords": true
  },
  "message": "User permanently deleted successfully."
}
```

PATCH /api/v1/users/{id}/status

Summary: Update Users Status

Allowed role/access: SUPER_ADMIN or ADMIN with users.status.update

Notes: Access: SUPER_ADMIN or ADMIN with users.status.update. SUPER_ADMIN or ADMIN with users.status.update permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "status": "ACTIVE",
  "reason": "POLICY_VIOLATION",
  "comment": "Suspicious activity detected on this account.",
  "notifyUser": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/users/{id}/suspend

Summary: Create Users Suspend

Allowed role/access: SUPER_ADMIN or ADMIN with users.suspend

Notes: Access: SUPER_ADMIN or ADMIN with users.suspend. SUPER_ADMIN or ADMIN with users.suspend permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "reason": "POLICY_VIOLATION",
  "comment": "Suspicious account activity.",
  "notifyUser": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/users/{id}/unsuspend

Summary: Create Users Unsuspend

Allowed role/access: SUPER_ADMIN or ADMIN with users.unsuspend

Notes: Access: SUPER_ADMIN or ADMIN with users.unsuspend. SUPER_ADMIN or ADMIN with users.unsuspend permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "comment": "Account reviewed and restored.",
  "notifyUser": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/users/{id}/reset-password

Summary: Change registered user password

Allowed role/access: SUPER_ADMIN or ADMIN with users.resetPassword

Notes: Access: SUPER_ADMIN or ADMIN with users.resetPassword. SUPER_ADMIN or ADMIN with users.resetPassword permission. SUPER_ADMIN or ADMIN with users.resetPassword permission can change a REGISTERED_USER password from the dashboard. Optionally sends email and in-app notification to the user.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "newPassword": "NewUser@123456",
  "sendEmail": true,
  "sendNotification": true,
  "reason": "Password changed by support request."
}
```

Response body:

```
{
  "success": true,
  "data": {
    "userId": "user_id",
    "email": "user@example.com",
    "emailSent": true,
    "notificationSent": true
  },
  "message": "User password changed successfully."
}
```

GET /api/v1/users/{id}/activity

Summary: Fetch Users Activity details

Allowed role/access: SUPER_ADMIN or ADMIN with users.read

Notes: Access: SUPER_ADMIN or ADMIN with users.read. SUPER_ADMIN or ADMIN with users.read permission.

Parameters:

- id (path, required, string)
- page (query, optional, number)
- limit (query, optional, number)
- type (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/users/{id}/stats

Summary: Fetch Users Stats details

Allowed role/access: SUPER_ADMIN or ADMIN with users.read

Notes: Access: SUPER_ADMIN or ADMIN with users.read. SUPER_ADMIN or ADMIN with users.read permission.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Provider Management

GET /api/v1/providers/export

Summary: List Providers Export

Allowed role/access: SUPER_ADMIN or ADMIN with providers.export

Notes: Access: SUPER_ADMIN or ADMIN with providers.export. SUPER_ADMIN or ADMIN with providers.export permission.

Parameters:

- search (query, optional, string)
- status (query, optional, string)
- approvalStatus (query, optional, string)
- format (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/providers/stats

Summary: List Providers Stats

Allowed role/access: SUPER_ADMIN or ADMIN with providers.read

Notes: Access: SUPER_ADMIN or ADMIN with providers.read. SUPER_ADMIN or ADMIN with providers.read permission.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/providers

Summary: List providers

Allowed role/access: SUPER_ADMIN or ADMIN with providers.read

Notes: Access: SUPER_ADMIN or ADMIN with providers.read. SUPER_ADMIN or ADMIN with providers.read permission. SUPER_ADMIN/ADMIN with providers.read permission.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)

- search (query, optional, string)
- status (query, optional, string)
- approvalStatus (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "provider_id",
      "businessName": "Premium Gifts Co",
      "email": "provider@example.com",
      "phone": "+923001234567",
      "approvalStatus": "APPROVED",
      "isActive": true,
      "businessCategory": {
        "id": "category_id",
        "name": "Gift Supplier"
      },
      "createdAt": "2026-05-09T10:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Providers fetched successfully"
}
```

POST /api/v1/providers

Summary: Create provider from admin dashboard

Allowed role/access: SUPER_ADMIN or ADMIN with providers.create

Notes: Access: SUPER_ADMIN or ADMIN with providers.create. SUPER_ADMIN or ADMIN with providers.create permission. SUPER_ADMIN or ADMIN with providers.create permission. Creates a PROVIDER account and provider business profile. Supports same business fields as provider self-registration, plus temporary password and invite email flow.

Request payload(s):

payload

```
{
  "email": "contact@giftsandblooms.com",
  "firstName": "Ali",
  "lastName": "Raza",
  "phone": "+15551234567",
  "businessName": "Gifts & Blooms Co. Ltd",
  "businessCategoryId": "provider_business_category_id",
  "taxId": "TAX-12345",
  "businessAddress": "123 Gift Street",
  "serviceArea": "New York, USA",
  "headquarters": "New York, USA",
  "fulfillmentMethods": [
    "PICKUP",
    "DELIVERY"
  ],
  "autoAcceptOrders": false,
  "documentUrls": [
    "https://cdn.yourdomain.com/provider-documents/license.pdf"
  ]
}
```

```
],
"generateTemporaryPassword": true,
"temporaryPassword": "Provider@123456",
"mustChangePassword": true,
"sendInviteEmail": true,
"approvalStatus": "PENDING",
"isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": {
    "id": "provider_id",
    "userId": "provider_id",
    "email": "contact@giftsandblooms.com",
    "businessName": "Gifts & Blooms Co. Ltd",
    "approvalStatus": "PENDING",
    "isActive": true,
    "inviteEmailSent": true
  },
  "message": "Provider created successfully and invite email sent."
}
```

GET /api/v1/providers/lookup

Summary: List Providers Lookup

Allowed role/access: SUPER_ADMIN or ADMIN with providers.read

Notes: Access: SUPER_ADMIN or ADMIN with providers.read. SUPER_ADMIN or ADMIN with providers.read permission.

Parameters:

- search (query, optional, string)
- approvalStatus (query, optional, string)
- isActive (query, optional, boolean)
- limit (query, optional, number)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/providers/{id}

Summary: Fetch Providers details

Allowed role/access: SUPER_ADMIN or ADMIN with providers.read

Notes: Access: SUPER_ADMIN or ADMIN with providers.read. SUPER_ADMIN or ADMIN with providers.read permission.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```

```
"message": "Request completed successfully."
}
```

PATCH /api/v1/providers/{id}

Summary: Update Providers

Allowed role/access: SUPER_ADMIN or ADMIN with providers.update

Notes: Access: SUPER_ADMIN or ADMIN with providers.update. SUPER_ADMIN or ADMIN with providers.update permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "businessName": "Gifts & Blooms Co. Ltd",
  "phone": "+15551234567",
  "serviceArea": "New York, USA",
  "headquarters": "New York, USA",
  "avatarUrl": "https://<YOUR_PUBLIC_BUCKET_OR_CDN_URL>/provider-logos/logo.png",
  "documentUrls": [
    "<string>"
  ]
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/providers/{id}

Summary: Permanently delete provider

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Permanent delete danger-zone endpoint. DANGER: This endpoint permanently deletes/anonymizes the provider and related provider data from the database. This is not a soft delete. Use only from Super Admin danger zone screens. Active processing orders block deletion.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": {
    "deletedProviderId": "provider_id",
    "deletedRelatedRecords": true
  },
}
```



```
"message": "Provider permanently deleted successfully."
}
```

PATCH /api/v1/providers/{id}/status

Summary: Update provider lifecycle status

Allowed role/access: SUPER_ADMIN or ADMIN with provider lifecycle permission (APPROVE=>providers.approve, REJECT=>providers.reject, SUSPEND=>providers.suspend, UNSUSPEND=>providers.suspend, UPDATE_STATUS=>providers.updateStatus)

Notes: Access: SUPER_ADMIN or ADMIN with provider lifecycle permission (APPROVE=>providers.approve, REJECT=>providers.reject, SUSPEND=>providers.suspend, UNSUSPEND=>providers.suspend, UPDATE_STATUS=>providers.updateStatus). SUPER_ADMIN or ADMIN with lifecycle permission. APPROVE requires providers.approve; REJECT requires providers.reject; SUSPEND and UNSUSPEND require providers.suspend; UPDATE_STATUS requires providers.updateStatus. SUPER_ADMIN or ADMIN with provider lifecycle permission. APPROVE requires providers.approve, REJECT requires providers.reject, SUSPEND and UNSUSPEND require providers.suspend, UPDATE_STATUS requires providers.updateStatus. Uses action-based request body.

Parameters:

- id (path, required, string)

Request payload(s):

approveProvider

```
{
  "action": "APPROVE",
  "comment": "Documents verified successfully.",
  "notifyProvider": true
}
```

rejectProvider

```
{
  "action": "REJECT",
  "reason": "INCOMPLETE_DOCUMENTS",
  "comment": "Business license document is missing.",
  "notifyProvider": true
}
```

updateStatus

```
{
  "action": "UPDATE_STATUS",
  "status": "ACTIVE",
  "reason": "OTHER",
  "comment": "Provider account restored after review.",
  "notifyProvider": true
}
```

suspendProvider

```
{
  "action": "SUSPEND",
  "reason": "POLICY_VIOLATION",
  "comment": "Provider violated platform policy.",
  "notifyProvider": true
}
```

unsuspendProvider

```
{
  "action": "UNSUSPEND",
  "comment": "Provider account reviewed and restored.",
  "notifyProvider": true
}
```

Response body:

```
{
  "success": true,
  "data": {
    "id": "provider_id",
    "approvalStatus": "APPROVED",
    "status": "ACTIVE",
    "isActive": true
  },
  "message": "Provider approved successfully."
}
```

GET /api/v1/providers/{id}/items

Summary: Fetch Providers Items details

Allowed role/access: SUPER_ADMIN or ADMIN with providers.read

Notes: Access: SUPER_ADMIN or ADMIN with providers.read. SUPER_ADMIN or ADMIN with providers.read permission.

Parameters:

- id (path, required, string)
- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/providers/{id}/activity

Summary: Fetch Providers Activity details

Allowed role/access: SUPER_ADMIN or ADMIN with providers.read

Notes: Access: SUPER_ADMIN or ADMIN with providers.read. SUPER_ADMIN or ADMIN with providers.read permission.

Parameters:

- id (path, required, string)
- page (query, optional, number)
- limit (query, optional, number)
- type (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```

```
"message": "Request completed successfully."
}
```

POST /api/v1/providers/{id}/message

Summary: Create Providers Message

Allowed role/access: SUPER_ADMIN or ADMIN with providers.message

Notes: Access: SUPER_ADMIN or ADMIN with providers.message. SUPER_ADMIN or ADMIN with providers.message permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "subject": "Account update",
  "message": "Please update your business documents.",
  "channel": "EMAIL"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Provider Business Categories

GET /api/v1/provider-business-categories

Summary: List provider business categories

Allowed role/access: PUBLIC

Notes: Access: PUBLIC. PUBLIC. Active provider business category lookup for provider signup. Public/provider-signup dropdown. Returns active provider business categories.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- isActive (query, optional, boolean)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/provider-business-categories

Summary: Create provider business category

Allowed role/access: SUPER_ADMIN or ADMIN with providerBusinessCategories.create

Notes: Access: SUPER_ADMIN or ADMIN with providerBusinessCategories.create. SUPER_ADMIN or ADMIN with providerBusinessCategories.create permission. SUPER_ADMIN or ADMIN with providerBusinessCategories.create permission only.

Request payload(s):

payload

```
{
  "name": "<string>",
  "description": "<string>",
  "iconKey": "<string>",
  "sortOrder": 1.0,
  "isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider-business-categories/{id}

Summary: Fetch provider business category details

Allowed role/access: SUPER_ADMIN or ADMIN with providerBusinessCategories.read

Notes: Access: SUPER_ADMIN or ADMIN with providerBusinessCategories.read. SUPER_ADMIN or ADMIN with providerBusinessCategories.read permission. SUPER_ADMIN or ADMIN with providerBusinessCategories.read permission only.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/provider-business-categories/{id}

Summary: Update provider business category

Allowed role/access: SUPER_ADMIN or ADMIN with providerBusinessCategories.update

Notes: Access: SUPER_ADMIN or ADMIN with providerBusinessCategories.update. SUPER_ADMIN or ADMIN with providerBusinessCategories.update permission. SUPER_ADMIN or ADMIN with providerBusinessCategories.update permission only.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "name": "<string>",
  "description": "<string>",
  "iconKey": "<string>",
  "sortOrder": 1.0,
}
```

```
"isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/provider-business-categories/{id}

Summary: Delete provider business category

Allowed role/access: SUPER_ADMIN or ADMIN with providerBusinessCategories.delete

Notes: Access: SUPER_ADMIN or ADMIN with providerBusinessCategories.delete. SUPER_ADMIN or ADMIN with providerBusinessCategories.delete permission. SUPER_ADMIN or ADMIN with providerBusinessCategories.delete permission. Permanently deletes the category; refuses deletion when active providers are attached.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Promotional Offers Management

GET /api/v1/promotional-offers/stats

Summary: List Promotional Offers Stats

Allowed role/access: SUPER_ADMIN or ADMIN with promotionalOffers.read

Notes: Access: SUPER_ADMIN or ADMIN with promotionalOffers.read. SUPER_ADMIN or ADMIN with promotionalOffers.read permission.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/promotional-offers/export

Summary: List Promotional Offers Export

Allowed role/access: SUPER_ADMIN or ADMIN with promotionalOffers.export

Notes: Access: SUPER_ADMIN or ADMIN with promotionalOffers.export. SUPER_ADMIN or ADMIN with promotionalOffers.export permission.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- itemId (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)
- providerId (query, optional, string)
- approvalStatus (query, optional, string)
- discountType (query, optional, string)
- startFrom (query, optional, string)
- startTo (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/promotional-offers

Summary: List Promotional Offers

Allowed role/access: SUPER_ADMIN or ADMIN with promotionalOffers.read

Notes: Access: SUPER_ADMIN or ADMIN with promotionalOffers.read. SUPER_ADMIN or ADMIN with promotionalOffers.read permission.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- itemId (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)
- providerId (query, optional, string)
- approvalStatus (query, optional, string)
- discountType (query, optional, string)
- startFrom (query, optional, string)
- startTo (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/promotional-offers

Summary: Create Promotional Offers

Allowed role/access: SUPER_ADMIN or ADMIN with promotionalOffers.create

Notes: Access: SUPER_ADMIN or ADMIN with promotionalOffers.create. SUPER_ADMIN or ADMIN with promotionalOffers.create permission.

Request payload(s):

payload

```
{
  "itemId": "<string>",
  "title": "<string>",
  "description": "<string>",
  "discountType": "PERCENTAGE",
  "discountValue": 1.0,
  "startDate": "<string>",
  "endDate": "<string>",
  "eligibilityRules": "<string>",
  "isActive": true,
  "providerId": "<string>",
  "approvalStatus": "PENDING"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/promotional-offers/{id}

Summary: Fetch Promotional Offers details

Allowed role/access: SUPER_ADMIN or ADMIN with promotionalOffers.read

Notes: Access: SUPER_ADMIN or ADMIN with promotionalOffers.read. SUPER_ADMIN or ADMIN with promotionalOffers.read permission.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/promotional-offers/{id}

Summary: Update Promotional Offers

Allowed role/access: SUPER_ADMIN or ADMIN with promotionalOffers.update

Notes: Access: SUPER_ADMIN or ADMIN with promotionalOffers.update. SUPER_ADMIN or ADMIN with promotionalOffers.update permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "title": "<string>",
```

```
"description": "<string>",
"discountType": "PERCENTAGE",
"discountValue": 1.0,
"startDate": "<string>",
"endDate": "<string>",
"eligibilityRules": "<string>",
"isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/promotional-offers/{id}

Summary: Delete Promotional Offers

Allowed role/access: SUPER_ADMIN or ADMIN with promotionalOffers.delete

Notes: Access: SUPER_ADMIN or ADMIN with promotionalOffers.delete. SUPER_ADMIN or ADMIN with promotionalOffers.delete permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/promotional-offers/{id}/approve

Summary: Update Promotional Offers Approve

Allowed role/access: SUPER_ADMIN or ADMIN with promotionalOffers.approve

Notes: Access: SUPER_ADMIN or ADMIN with promotionalOffers.approve. SUPER_ADMIN or ADMIN with promotionalOffers.approve permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "comment": "<string>",
  "notifyProvider": true
}
```

Response body:


```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/promotional-offers/{id}/reject

Summary: Update Promotional Offers Reject

Allowed role/access: SUPER_ADMIN or ADMIN with promotionalOffers.reject

Notes: Access: SUPER_ADMIN or ADMIN with promotionalOffers.reject. SUPER_ADMIN or ADMIN with promotionalOffers.reject permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "reason": "INVALID_DISCOUNT",
  "comment": "<string>",
  "notifyProvider": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/promotional-offers/{id}/status

Summary: Update Promotional Offers Status

Allowed role/access: SUPER_ADMIN or ADMIN with promotionalOffers.status.update

Notes: Access: SUPER_ADMIN or ADMIN with promotionalOffers.status.update. SUPER_ADMIN or ADMIN with promotionalOffers.status.update permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "isActive": true,
  "reason": "<string>"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Dashboard Overview

GET /api/v1/admin/dashboard/overview

Summary: Fetch Super Admin dashboard overview metrics

Allowed role/access: SUPER_ADMIN or ADMIN with dashboard.read

Notes: Access: SUPER_ADMIN or ADMIN with dashboard.read. SUPER_ADMIN or ADMIN with dashboard.read permission. Read-only dashboard overview metrics. SUPER_ADMIN or ADMIN with dashboard.read. Read-only metrics are aggregated from existing users, providers, payments, and transaction records. Missing analytics sources return zeros instead of fake data.

Response body:

```
{
  "success": true,
  "data": {
    "totalUsers": 128430,
    "totalUsersDeltaPercent": 12.5,
    "totalProviders": 1240,
    "totalProvidersDeltaPercent": 5.2,
    "transactions": 45200,
    "transactionsDeltaPercent": 18.1,
    "totalRevenue": 1240000,
    "totalRevenueDeltaPercent": 10.3,
    "currency": "USD"
  },
  "message": "Dashboard overview fetched successfully."
}
```

GET /api/v1/admin/dashboard/revenue-trends

Summary: Fetch monthly revenue trends

Allowed role/access: SUPER_ADMIN or ADMIN with dashboard.read

Notes: Access: SUPER_ADMIN or ADMIN with dashboard.read. SUPER_ADMIN or ADMIN with dashboard.read permission. Read-only monthly revenue trends. SUPER_ADMIN or ADMIN with dashboard.read. Uses successful payment records for the last 12 calendar months and returns zero for months with no revenue.

Response body:

```
{
  "success": true,
  "data": {
    "range": "LAST_12_MONTHS",
    "labels": [
      "Jan",
      "Feb",
      "Mar"
    ],
    "values": [
      12000,
      28000,
      16000
    ],
    "currency": "USD"
  },
  "message": "Revenue trends fetched successfully."
}
```

GET /api/v1/admin/dashboard/gift-vs-payment

Summary: Fetch gift vs direct payment distribution

Allowed role/access: SUPER_ADMIN or ADMIN with dashboard.read

Notes: Access: SUPER_ADMIN or ADMIN with dashboard.read. SUPER_ADMIN or ADMIN with dashboard.read permission. Read-only gift versus direct payment distribution. SUPER_ADMIN or ADMIN with dashboard.read. Distribution is calculated from successful payment records; money gift payments count as gift cards and all other successful payments count as direct payments.

Response body:

```
{
  "success": true,
  "data": {
    "giftCardsPercent": 65,
    "directPaymentsPercent": 35
  },
  "message": "Gift vs payment distribution fetched successfully."
}
```

GET /api/v1/admin/dashboard/provider-performance

Summary: Fetch provider performance table

Allowed role/access: SUPER_ADMIN or ADMIN with dashboard.read

Notes: Access: SUPER_ADMIN or ADMIN with dashboard.read. SUPER_ADMIN or ADMIN with dashboard.read permission. Read-only provider performance table. SUPER_ADMIN or ADMIN with dashboard.read. Aggregates provider order success rate and fulfilled volume from existing provider order records without exposing payout or customer-sensitive data.

Response body:

```
{
  "success": true,
  "data": [
    {
      "providerId": "provider_id",
      "providerName": "Stripe Integration",
      "successRate": 99.2,
      "totalVolume": 450230,
      "currency": "USD"
    }
  ],
  "message": "Provider performance fetched successfully."
}
```

GET /api/v1/admin/dashboard/recent-disputes

Summary: Fetch recent disputes table

Allowed role/access: SUPER_ADMIN or ADMIN with dashboard.read

Notes: Access: SUPER_ADMIN or ADMIN with dashboard.read. SUPER_ADMIN or ADMIN with dashboard.read permission. Read-only recent dispute table without sensitive payment/customer data. SUPER_ADMIN or ADMIN with dashboard.read. Combines recent customer and provider dispute cases and returns non-sensitive case, customer display name, reason, and priority/status only.

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "dispute_id",
      "caseId": "DISP-9021",
      "userName": "Marcus Wright",
      "reason": "Unauthorized transaction",
      "status": "HIGH_PRIORITY"
    }
  ],
}
```

```
"message": "Recent disputes fetched successfully."
}
```

02 Admin - Commission & Payout Settings

GET /api/v1/admin/payout-settings

Summary: Fetch commission and payout settings

Allowed role/access: SUPER_ADMIN or ADMIN with payoutSettings.read

Notes: Access: SUPER_ADMIN or ADMIN with payoutSettings.read. SUPER_ADMIN or ADMIN with payoutSettings.read permission. SUPER_ADMIN or ADMIN with payoutSettings.read. Returns global platform commission, payout threshold/schedule, and active provider commission tiers. Settings affect future payout calculations only and do not rewrite historical payouts.

Response body:

```
{
  "success": true,
  "data": {
    "platformRatePercent": 5,
    "minimumPayoutThreshold": 100,
    "currency": "USD",
    "payoutSchedule": "MONTHLY_LAST_DAY",
    "payoutTimeUtc": "00:00",
    "autoPayoutEnabled": true,
    "lastUpdatedAt": "2026-05-16T10:00:00.000Z",
    "commissionTiers": [
      {
        "id": "tier_standard",
        "name": "Standard Tier",
        "commissionRatePercent": 15,
        "orderVolumeThreshold": 0,
        "sortOrder": 1,
        "isActive": true
      },
      {
        "id": "tier_silver",
        "name": "Silver Partner",
        "commissionRatePercent": 12.5,
        "orderVolumeThreshold": 5000,
        "sortOrder": 2,
        "isActive": true
      }
    ]
  },
  "message": "Payout settings fetched successfully."
}
```

PATCH /api/v1/admin/payout-settings

Summary: Update commission and payout settings

Allowed role/access: SUPER_ADMIN or ADMIN with payoutSettings.update

Notes: Access: SUPER_ADMIN or ADMIN with payoutSettings.update. SUPER_ADMIN or ADMIN with payoutSettings.update permission. Applies to future payout calculations only. SUPER_ADMIN or ADMIN with payoutSettings.update. Updates global settings for future payout calculations only; existing historical payouts are not rewritten or recalculated.

Request payload(s):

update

```
{
  "platformRatePercent": 5,
  "minimumPayoutThreshold": 100,
  "currency": "USD",
  "payoutSchedule": "MONTHLY_LAST_DAY",
  "payoutTimeUtc": "00:00",
  "autoPayoutEnabled": true
}
```

Response body:

```
{
  "success": true,
  "data": {
    "platformRatePercent": 5,
    "minimumPayoutThreshold": 100,
    "currency": "USD",
    "payoutSchedule": "MONTHLY_LAST_DAY",
    "payoutTimeUtc": "00:00",
    "autoPayoutEnabled": true,
    "lastUpdatedAt": "2026-05-16T10:00:00.000Z"
  },
  "message": "Payout settings updated successfully."
}
```

GET /api/v1/admin/payout-settings/commission-tiers

Summary: List commission tiers

Allowed role/access: SUPER_ADMIN or ADMIN with payoutSettings.read

Notes: Access: SUPER_ADMIN or ADMIN with payoutSettings.read. SUPER_ADMIN or ADMIN with payoutSettings.read permission. SUPER_ADMIN or ADMIN with payoutSettings.read. Returns active commission tiers ordered by sort order and threshold.

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "tier_standard",
      "name": "Standard Tier",
      "commissionRatePercent": 15,
      "orderVolumeThreshold": 0,
      "sortOrder": 1,
      "isActive": true
    }
  ],
  "message": "Commission tiers fetched successfully."
}
```

POST /api/v1/admin/payout-settings/commission-tiers

Summary: Create commission tier

Allowed role/access: SUPER_ADMIN or ADMIN with payoutSettings.update

Notes: Access: SUPER_ADMIN or ADMIN with payoutSettings.update. SUPER_ADMIN or ADMIN with payoutSettings.update permission. SUPER_ADMIN or ADMIN with payoutSettings.update. Creates a provider commission tier for future billing/payout cycles only. Thresholds must be unique among active tiers.

Request payload(s):

create

```
{
  "name": "Gold Elite",
  "commissionRatePercent": 10,
  "orderVolumeThreshold": 15000,
  "sortOrder": 3,
  "isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": {
    "id": "tier_gold",
    "name": "Gold Elite",
    "commissionRatePercent": 10,
    "orderVolumeThreshold": 15000,
    "sortOrder": 3,
    "isActive": true
  },
  "message": "Commission tier created successfully."
}
```

PATCH /api/v1/admin/payout-settings/commission-tiers/{id}

Summary: Update commission tier

Allowed role/access: SUPER_ADMIN or ADMIN with payoutSettings.update

Notes: Access: SUPER_ADMIN or ADMIN with payoutSettings.update. SUPER_ADMIN or ADMIN with payoutSettings.update permission. Applies next billing/payout cycle. SUPER_ADMIN or ADMIN with payoutSettings.update. Tier changes take effect at the start of the next billing/payout cycle and do not rewrite historical payouts.

Parameters:

- id (path, required, string)

Request payload(s):

update

```
{
  "name": "Gold Elite",
  "commissionRatePercent": 10,
  "orderVolumeThreshold": 15000,
  "sortOrder": 3,
  "isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": {
    "id": "tier_gold",
    "name": "Gold Elite",
    "commissionRatePercent": 10,
    "orderVolumeThreshold": 15000,
    "sortOrder": 3,
    "isActive": true
  },
  "message": "Commission tier updated successfully."
}
```

DELETE /api/v1/admin/payout-settings/commission-tiers/{id}

Summary: Delete commission tier

Allowed role/access: SUPER_ADMIN or ADMIN with payoutSettings.update

Notes: Access: SUPER_ADMIN or ADMIN with payoutSettings.update. SUPER_ADMIN or ADMIN with payoutSettings.update permission. Permanently deletes the tier record. SUPER_ADMIN or ADMIN with payoutSettings.update. Permanently deletes the tier record.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": {
    "id": "tier_gold",
    "deleted": true
  },
  "message": "Commission tier deleted successfully."
}
```

GET /api/v1/admin/payout-settings/audit-logs

Summary: List payout settings audit logs

Allowed role/access: SUPER_ADMIN or ADMIN with payoutSettings.read

Notes: Access: SUPER_ADMIN or ADMIN with payoutSettings.read. SUPER_ADMIN or ADMIN with payoutSettings.read permission. SUPER_ADMIN or ADMIN with payoutSettings.read. Returns audit logs for payout settings and commission tier changes, including sanitized before/after JSON.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "audit_log_id",
      "action": "PAYOUT_SETTINGS_UPDATED",
      "actor": {
        "id": "admin_id",
        "name": "Alex Rivera"
      },
      "targetType": "PAYOUT_SETTINGS",
      "before": {
        "platformRatePercent": 5
      },
      "after": {
        "platformRatePercent": 6
      },
      "createdAt": "2026-05-16T10:00:00.000Z"
    }
  ]
}
```

```
],
"meta": {
  "page": 1,
  "limit": 20,
  "total": 1,
  "totalPages": 1
},
"message": "Payout settings audit logs fetched successfully."
}
```

02 Admin - Provider Payouts

GET /api/v1/admin/provider-payouts/stats

Summary: Fetch provider payout dashboard stats

Allowed role/access: SUPER_ADMIN or ADMIN with providerPayouts.read

Notes: Access: SUPER_ADMIN or ADMIN with providerPayouts.read. SUPER_ADMIN or ADMIN with providerPayouts.read permission. SUPER_ADMIN or ADMIN with providerPayouts.read. Aggregates from provider payout records only; no frontend totals are trusted.

Response body:

```
{
  "success": true,
  "data": {
    "totalPayoutsThisMonth": 128430,
    "totalPayoutsDeltaPercent": 12.5,
    "pendingPayouts": 12250,
    "pendingPayoutsDeltaPercent": -2.4,
    "completedPayouts": 116180,
    "completedPayoutsDeltaPercent": 14.2,
    "platformRevenue": 19264.5,
    "platformRevenueDeltaPercent": 8.1,
    "currency": "USD"
  },
  "message": "Provider payout stats fetched successfully."
}
```

GET /api/v1/admin/provider-payouts/trends

Summary: Fetch monthly provider payout trend

Allowed role/access: SUPER_ADMIN or ADMIN with providerPayouts.read

Notes: Access: SUPER_ADMIN or ADMIN with providerPayouts.read. SUPER_ADMIN or ADMIN with providerPayouts.read permission. SUPER_ADMIN or ADMIN with providerPayouts.read. Returns last 12 months from provider payout records.

Response body:

```
{
  "success": true,
  "data": {
    "range": "LAST_12_MONTHS",
    "labels": [
      "Jan",
      "Feb",
      "Mar"
    ],
    "values": [
      12000,
      28000,
      16000
    ]
  }
}
```



```
    ],
    "currency": "USD"
  },
  "message": "Provider payout trends fetched successfully."
}
```

GET /api/v1/admin/provider-payouts/earning-distribution

Summary: Fetch earning distribution by provider tier

Allowed role/access: SUPER_ADMIN or ADMIN with providerPayouts.read

Notes: Access: SUPER_ADMIN or ADMIN with providerPayouts.read. SUPER_ADMIN or ADMIN with providerPayouts.read permission. SUPER_ADMIN or ADMIN with providerPayouts.read. Uses provider earnings ledger totals and active commission tier thresholds.

Response body:

```
{
  "success": true,
  "data": [
    {
      "tierId": "tier_silver",
      "tierName": "Silver Partner",
      "providerCount": 18,
      "totalEarnings": 450230,
      "currency": "USD"
    }
  ],
  "message": "Provider earning distribution fetched successfully."
}
```

GET /api/v1/admin/provider-payouts/export

Summary: Export provider payouts

Allowed role/access: SUPER_ADMIN or ADMIN with providerPayouts.export

Notes: Access: SUPER_ADMIN or ADMIN with providerPayouts.export. SUPER_ADMIN or ADMIN with providerPayouts.export permission. Uses list filters and excludes full bank account numbers. SUPER_ADMIN or ADMIN with providerPayouts.export. Applies the same filters as list and never exports full bank account numbers.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- providerId (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)
- format (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/provider-payouts/bulk-approve

Summary: Bulk approve provider payouts

Allowed role/access: SUPER_ADMIN or ADMIN with providerPayouts.approve

Notes: Access: SUPER_ADMIN or ADMIN with providerPayouts.approve. SUPER_ADMIN or ADMIN with providerPayouts.approve permission. Returns per-item idempotent results. SUPER_ADMIN or ADMIN with providerPayouts.approve. Idempotent per payout: already PROCESSING/COMPLETED payouts are returned as successful idempotent items and are not processed twice.

Request payload(s):

approve

```
{
  "payoutIds": [
    "payout_id_1",
    "payout_id_2"
  ],
  "comment": "Bulk approved after verification.",
  "notifyProvider": true
}
```

Response body:

```
{
  "success": true,
  "data": [
    {
      "payoutId": "payout_id_1",
      "status": "PROCESSING",
      "success": true,
      "idempotent": false
    },
    {
      "payoutId": "payout_id_2",
      "status": "PROCESSING",
      "success": true,
      "idempotent": true
    }
  ],
  "message": "Bulk payout approval processed."
}
```

GET /api/v1/admin/provider-payouts

Summary: List provider payouts

Allowed role/access: SUPER_ADMIN or ADMIN with providerPayouts.read

Notes: Access: SUPER_ADMIN or ADMIN with providerPayouts.read. SUPER_ADMIN or ADMIN with providerPayouts.read permission. SUPER_ADMIN or ADMIN with providerPayouts.read. Supports status/provider/date/search filters and sorting. Bank account data is masked only.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- providerId (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "payout_id",
      "provider": {
        "id": "provider_id",
        "businessName": "TechSolutions Inc.",
        "providerCode": "PRV-90210",
        "avatarUrl": "https://cdn.example.com/provider.png"
      },
      "pendingAmount": 3420,
      "currency": "USD",
      "lastPayoutDate": "2023-10-12T00:00:00.000Z",
      "nextPayoutDate": "2023-11-12T00:00:00.000Z",
      "status": "COMPLETED"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Provider payouts fetched successfully."
}
```

GET /api/v1/admin/provider-payouts/{id}/breakdown

Summary: Fetch pending payout transaction breakdown

Allowed role/access: SUPER_ADMIN or ADMIN with providerPayouts.read

Notes: Access: SUPER_ADMIN or ADMIN with providerPayouts.read. SUPER_ADMIN or ADMIN with providerPayouts.read permission. SUPER_ADMIN or ADMIN with providerPayouts.read. Shows gross amount, platform fee, processing fee, net payout, and recent ledger transactions without full bank details.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": {
    "payoutId": "payout_id",
    "provider": {
      "id": "provider_id",
      "businessName": "CloudTech Solutions",
      "merchantId": "MER-29401-2023"
    },
    "grossAmount": 4200,
    "platformFee": 420,
    "platformFeePercent": 10,
    "processingFee": 12.5,
    "netPayout": 3767.5,
    "currency": "USD",
    "recentTransactions": [
      {
        "orderNumber": "88392",
        "description": "Subscription - Professional Plan",
        "amount": 199
      }
    ]
  }
}
```

```
},
"message": "Payout breakdown fetched successfully."
}
```

POST /api/v1/admin/provider-payouts/{id}/approve

Summary: Approve provider payout

Allowed role/access: SUPER_ADMIN or ADMIN with providerPayouts.approve

Notes: Access: SUPER_ADMIN or ADMIN with providerPayouts.approve. SUPER_ADMIN or ADMIN with providerPayouts.approve permission. Idempotent for already approved payouts. SUPER_ADMIN or ADMIN with providerPayouts.approve. Only PENDING or ON_HOLD payouts can be approved. Approved payouts move to PROCESSING for payout processor completion.

Parameters:

- id (path, required, string)

Request payload(s):

approve

```
{
  "comment": "Approved after verification.",
  "notifyProvider": true
}
```

Response body:

```
{
  "success": true,
  "data": {
    "id": "payout_id",
    "status": "PROCESSING"
  },
  "message": "Payout approved successfully."
}
```

POST /api/v1/admin/provider-payouts/{id}/hold

Summary: Hold provider payout

Allowed role/access: SUPER_ADMIN or ADMIN with providerPayouts.hold

Notes: Access: SUPER_ADMIN or ADMIN with providerPayouts.hold. SUPER_ADMIN or ADMIN with providerPayouts.hold permission. Keeps ledger balance locked. SUPER_ADMIN or ADMIN with providerPayouts.hold. Holds a PENDING payout without releasing locked PAYOUT_PENDING ledger balance.

Parameters:

- id (path, required, string)

Request payload(s):

hold

```
{
  "reason": "BANK_VERIFICATION_PENDING",
  "comment": "Bank verification required.",
  "notifyProvider": true
}
```

Response body:

```
{
  "success": true,
  "data": {
```

```
    "id": "payout_id",
    "status": "ON_HOLD"
  },
  "message": "Payout held successfully."
}
```

POST /api/v1/admin/provider-payouts/{id}/reject

Summary: Reject provider payout

Allowed role/access: SUPER_ADMIN or ADMIN with providerPayouts.reject

Notes: Access: SUPER_ADMIN or ADMIN with providerPayouts.reject. SUPER_ADMIN or ADMIN with providerPayouts.reject permission. Releases locked ledger balance. SUPER_ADMIN or ADMIN with providerPayouts.reject. Rejects PENDING or ON_HOLD payout and releases locked PAYOUT_PENDING ledger balance back to AVAILABLE.

Parameters:

- id (path, required, string)

Request payload(s):

reject

```
{
  "reason": "INVALID_BANK_ACCOUNT",
  "comment": "Bank details are invalid.",
  "notifyProvider": true
}
```

Response body:

```
{
  "success": true,
  "data": {
    "id": "payout_id",
    "status": "REJECTED",
    "ledgerReleased": true
  },
  "message": "Payout rejected successfully."
}
```

GET /api/v1/admin/provider-payouts/{id}

Summary: Fetch provider payout details

Allowed role/access: SUPER_ADMIN or ADMIN with providerPayouts.read

Notes: Access: SUPER_ADMIN or ADMIN with providerPayouts.read. SUPER_ADMIN or ADMIN with providerPayouts.read permission. Payout destination is masked. SUPER_ADMIN or ADMIN with providerPayouts.read. Returns payout details, provider display data, and masked payout destination only.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": {
    "id": "payout_id",
    "provider": {
      "id": "provider_id",
      "businessName": "TechSolutions Inc.",
      "providerCode": "PRV-90210",
      "avatarUrl": "https://cdn.example.com/provider.png"
    },
  },
}
```

```

    "pendingAmount": 3420,
    "amount": 3420,
    "processingFee": 42,
    "totalToReceive": 3378,
    "currency": "USD",
    "status": "COMPLETED",
    "destination": {
      "id": "method_id",
      "bankName": "Chase Bank",
      "maskedAccount": "****1234",
      "last4": "1234",
      "verificationStatus": "VERIFIED"
    },
    "createdAt": "2023-10-12T00:00:00.000Z"
  },
  "message": "Provider payout details fetched successfully."
}

```

02 Admin - Transaction Monitoring

GET /api/v1/admin/transactions/stats

Summary: Fetch transaction monitoring stats

Allowed role/access: SUPER_ADMIN or ADMIN with transactions.read

Notes: Access: SUPER_ADMIN or ADMIN with transactions.read. SUPER_ADMIN or ADMIN with transactions.read permission. SUPER_ADMIN or ADMIN with transactions.read. Stats are calculated from real payment/transaction records and return zeros when no records match.

Parameters:

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- transactionType (query, optional, string)
- status (query, optional, string)

Response body:

```

{
  "success": true,
  "data": {
    "totalVolume": 124500,
    "totalVolumeDeltaPercent": 12,
    "successRate": 98.2,
    "successRateDeltaPercent": 2.1,
    "pendingReview": 14,
    "failedToday": 3,
    "failedTodayDeltaPercent": -5,
    "currency": "PKR"
  },
  "message": "Transaction stats fetched successfully."
}

```

GET /api/v1/admin/transactions/export

Summary: Export admin transactions

Allowed role/access: SUPER_ADMIN or ADMIN with transactions.export

Notes: Access: SUPER_ADMIN or ADMIN with transactions.export. SUPER_ADMIN or ADMIN with transactions.export permission. Excludes card and payment secrets. SUPER_ADMIN or ADMIN with transactions.export. Applies the same filters as the list API and excludes raw card numbers, CVV, client secrets, and Stripe secret fields.

Parameters:

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- transactionType (query, optional, string)
- status (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- gatewayProvider (query, optional, string)
- userId (query, optional, string)
- providerId (query, optional, string)
- minAmount (query, optional, number)
- maxAmount (query, optional, number)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)
- format (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/transactions**Summary:** List admin transactions**Allowed role/access:** SUPER_ADMIN or ADMIN with transactions.read

Notes: Access: SUPER_ADMIN or ADMIN with transactions.read. SUPER_ADMIN or ADMIN with transactions.read permission. SUPER_ADMIN or ADMIN with transactions.read. Admin-side financial monitoring endpoint; customer transaction history remains under /api/v1/customer/transactions. Search supports transaction ID, order number, customer name/email, gateway reference, and provider business name.

Parameters:

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- transactionType (query, optional, string)
- status (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- gatewayProvider (query, optional, string)
- userId (query, optional, string)
- providerId (query, optional, string)
- minAmount (query, optional, number)
- maxAmount (query, optional, number)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "transaction_id",
```

```

      "transactionId": "TXN-882194",
      "user": {
        "id": "user_id",
        "name": "Sarah Jenkins",
        "avatarUrl": "https://cdn.yourdomain.com/user-avatars/sarah.png"
      },
      "gatewayProvider": "STRIPE",
      "type": "PAYMENT",
      "amount": 1250,
      "currency": "PKR",
      "status": "SUCCESS",
      "createdAt": "2026-10-24T14:20:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Transactions fetched successfully."
}

```

GET /api/v1/admin/transactions/{id}/timeline

Summary: Fetch transaction timeline

Allowed role/access: SUPER_ADMIN or ADMIN with transactions.read

Notes: Access: SUPER_ADMIN or ADMIN with transactions.read. SUPER_ADMIN or ADMIN with transactions.read permission. SUPER_ADMIN or ADMIN with transactions.read. Returns ordered payment, refund, dispute, notification, and audit events without card/payment secrets.

Parameters:

- id (path, required, string)

Response body:

```

{
  "success": true,
  "data": [
    {
      "status": "INITIATED",
      "title": "Initiated",
      "description": "Checkout session started by user via mobile application.",
      "source": "User Session",
      "timestamp": "2026-11-24T14:30:02.000Z"
    },
    {
      "status": "COMPLETED",
      "title": "Completed",
      "description": "Funds successfully transferred to the merchant escrow account.",
      "source": "System Auto-Update",
      "timestamp": "2026-11-24T14:32:10.000Z"
    }
  ],
  "message": "Transaction timeline fetched successfully."
}

```

GET /api/v1/admin/transactions/{id}/receipt

Summary: Download transaction receipt

Allowed role/access: SUPER_ADMIN or ADMIN with transactions.receipt.download

Notes: Access: SUPER_ADMIN or ADMIN with transactions.receipt.download. SUPER_ADMIN or ADMIN with transactions.receipt.download permission. SUPER_ADMIN or ADMIN with transactions.receipt.download. Returns a PDF-compatible receipt file with transaction ID, order ID, customer display info, amount breakdown, gateway provider, and masked payment method only.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/transactions/{id}/refund

Summary: Refund transaction

Allowed role/access: SUPER_ADMIN or ADMIN with transactions.refund

Notes: Access: SUPER_ADMIN or ADMIN with transactions.refund. SUPER_ADMIN or ADMIN with transactions.refund permission. Refund amount is server-validated. SUPER_ADMIN or ADMIN with transactions.refund. Refund amount is server-validated against remaining refundable amount and Refund Policy Settings. No frontend amount is trusted; no card/payment secrets are exposed.

Parameters:

- id (path, required, string)

Request payload(s):

full

```
{
  "refundType": "FULL",
  "refundAmount": 1281.25,
  "reason": "CUSTOMER_REQUEST",
  "comment": "Refund approved by support.",
  "notifyUser": true
}
```

partial

```
{
  "refundType": "PARTIAL",
  "refundAmount": 250,
  "reason": "PRODUCT_NOT_RECEIVED",
  "comment": "Partial goodwill refund.",
  "notifyUser": true
}
```

Response body:

```
{
  "success": true,
  "data": {
    "transactionId": "TRX-982341",
    "refundId": "RF-45678",
    "refundAmount": 1281.25,
    "currency": "PKR",
    "status": "REFUNDED"
  },
}
```

```
"message": "Transaction refunded successfully."
}
```

POST /api/v1/admin/transactions/{id}/open-dispute

Summary: Open dispute from transaction

Allowed role/access: SUPER_ADMIN or ADMIN with transactions.openDispute

Notes: Access: SUPER_ADMIN or ADMIN with transactions.openDispute. SUPER_ADMIN or ADMIN with transactions.openDispute permission. SUPER_ADMIN or ADMIN with transactions.openDispute. Creates an Admin Dispute Manager case linked to transaction/payment/order and blocks duplicate open disputes.

Parameters:

- id (path, required, string)

Request payload(s):

open

```
{
  "reason": "PRODUCT_NOT_RECEIVED",
  "priority": "HIGH",
  "claimDetails": "Dispute opened from transaction detail screen.",
  "assignToId": "admin_id"
}
```

Response body:

```
{
  "success": true,
  "data": {
    "disputeId": "dispute_id",
    "caseId": "DSP-1024",
    "transactionId": "TRX-982341",
    "status": "OPEN"
  },
  "message": "Dispute opened successfully."
}
```

POST /api/v1/admin/transactions/{id}/notify-user

Summary: Send transaction notification to user

Allowed role/access: SUPER_ADMIN or ADMIN with transactions.notifyUser

Notes: Access: SUPER_ADMIN or ADMIN with transactions.notifyUser. SUPER_ADMIN or ADMIN with transactions.notifyUser permission. SUPER_ADMIN or ADMIN with transactions.notifyUser. Creates in-app notification and/or email handoff audit; includeReceipt links receipt metadata without exposing payment secrets.

Parameters:

- id (path, required, string)

Request payload(s):

email

```
{
  "channel": "EMAIL",
  "subject": "Transaction update",
  "message": "Your transaction has been successfully processed.",
  "includeReceipt": true
}
```

Response body:

```
{
  "success": true,
  "data": {
    "transactionId": "TRX-982341",
    "notificationSent": true,
    "channel": "EMAIL"
  },
  "message": "Notification sent successfully."
}
```

GET /api/v1/admin/transactions/{id}

Summary: Fetch transaction details

Allowed role/access: SUPER_ADMIN or ADMIN with transactions.read

Notes: Access: SUPER_ADMIN or ADMIN with transactions.read. SUPER_ADMIN or ADMIN with transactions.read permission. Card/payment secrets are masked. SUPER_ADMIN or ADMIN with transactions.read. Shows payment breakdown, gateway information, customer info, related records, and refund state. Raw card numbers, CVV, Stripe secret keys, and payment intent client secrets are never exposed.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": {
    "id": "transaction_id",
    "transactionId": "TRX-982341",
    "status": "SUCCESS",
    "type": "PAYMENT",
    "currency": "PKR",
    "paymentBreakdown": {
      "subtotal": 1250,
      "processingFee": 31.25,
      "processingFeePercent": 2.5,
      "totalAmount": 1281.25
    },
    "gatewayInformation": {
      "provider": "STRIPE",
      "gatewayReference": "REF-XP-382341",
      "paymentMethod": "Visa **** 4242",
      "settlementStatus": "CLEARED",
      "processorAuthCode": "AUTH-9921-X"
    },
    "customer": {
      "id": "user_id",
      "name": "Julianne Doe",
      "email": "julianne.doe@example.com",
      "location": "San Francisco, CA, USA",
      "kycStatus": "KYC Level 2 Verified"
    },
    "relatedRecords": {
      "orderId": "order_id",
      "orderNumber": "ORD-88421",
      "paymentId": "payment_id",
      "subscriptionId": null,
      "moneyGiftId": null,
      "walletLedgerId": null
    },
    "refund": {
      "isRefundable": true,

```

```
    "refundedAmount": 0,
    "remainingRefundableAmount": 1281.25,
    "refundWindowEndsAt": "2026-11-24T00:00:00.000Z"
  },
  "createdAt": "2026-10-24T14:20:00.000Z"
},
"message": "Transaction details fetched successfully."
}
```

02 Admin - Message Moderation

GET /api/v1/admin/message-moderation/conversations

Summary: List flagged message moderation conversations

Allowed role/access: SUPER_ADMIN or ADMIN with messageModeration.read

Notes: Access: SUPER_ADMIN or ADMIN with messageModeration.read. SUPER_ADMIN or ADMIN with messageModeration.read permission. Harmful message previews are redacted. SUPER_ADMIN or ADMIN with messageModeration.read. Returns redacted previews only.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- source (query, optional, string)
- flagType (query, optional, string)
- status (query, optional, string)
- severity (query, optional, string)
- assignedToId (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "case_1",
      "participant": {
        "id": "user_1",
        "name": "Alex Rivera",
        "avatarUrl": "https://cdn.example.com/avatar.png",
        "externalReference": "USR-99021"
      },
      "source": "WHATSAPP_BUSINESS",
      "flag": {
        "type": "PROFANITY",
        "label": "Profanity Detected",
        "severity": "HIGH",
        "confidence": 0.94
      },
      "preview": "Hey, you are a total [REDACTED] if you think I'm...",
      "status": "FLAGGED",
      "lastMessageAt": "2026-05-18T14:02:00.000Z",
      "timeAgo": "2m ago"
    }
  ],
  "meta": {
```

```
    "page": 1,  
    "limit": 20,  
    "total": 12,  
    "totalPages": 1  
  },  
  "message": "Message moderation conversations fetched successfully."  
}
```

GET /api/v1/admin/message-moderation/stats

Summary: Fetch message moderation stats

Allowed role/access: SUPER_ADMIN or ADMIN with messageModeration.read

Notes: Access: SUPER_ADMIN or ADMIN with messageModeration.read. SUPER_ADMIN or ADMIN with messageModeration.read permission. SUPER_ADMIN or ADMIN with messageModeration.read.

Response body:

```
{  
  "success": true,  
  "data": "<response returned by endpoint>",  
  "message": "Request completed successfully."  
}
```

GET /api/v1/admin/message-moderation/filter-options

Summary: Fetch message moderation filter options

Allowed role/access: SUPER_ADMIN or ADMIN with messageModeration.read

Notes: Access: SUPER_ADMIN or ADMIN with messageModeration.read. SUPER_ADMIN or ADMIN with messageModeration.read permission. Sources include chat channels and external integration placeholders.

Response body:

```
{  
  "success": true,  
  "data": "<response returned by endpoint>",  
  "message": "Request completed successfully."  
}
```

GET /api/v1/admin/message-moderation/export

Summary: Export message moderation rows

Allowed role/access: SUPER_ADMIN or ADMIN with messageModeration.export

Notes: Access: SUPER_ADMIN or ADMIN with messageModeration.export. SUPER_ADMIN or ADMIN with messageModeration.export permission. Export is redacted. SUPER_ADMIN or ADMIN with messageModeration.export. Export remains moderation-safe and redacted.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- source (query, optional, string)
- flagType (query, optional, string)
- status (query, optional, string)
- severity (query, optional, string)
- assignedToId (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/message-moderation/conversations/{id}

Summary: Fetch message moderation conversation detail

Allowed role/access: SUPER_ADMIN or ADMIN with messageModeration.read

Notes: Access: SUPER_ADMIN or ADMIN with messageModeration.read. SUPER_ADMIN or ADMIN with messageModeration.read permission. Flagged body is null by default; redactedBody is returned. Flagged harmful message body is null by default; redactedBody is always returned.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/message-moderation/conversations/{id}/history

Summary: Fetch message moderation conversation history

Allowed role/access: SUPER_ADMIN or ADMIN with messageModeration.read

Notes: Access: SUPER_ADMIN or ADMIN with messageModeration.read. SUPER_ADMIN or ADMIN with messageModeration.read permission. Returns moderation case history for the same conversation.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/message-moderation/messages/{messageId}/block

Summary: Block a flagged message

Allowed role/access: SUPER_ADMIN or ADMIN with messageModeration.block

Notes: Access: SUPER_ADMIN or ADMIN with messageModeration.block. SUPER_ADMIN or ADMIN with messageModeration.block permission. Creates moderation and audit logs. Creates moderation log and audit log; message is not physically deleted.

Parameters:

- messageId (path, required, string)

Request payload(s):

payload

```
{
  "reason": "<string>",
  "internalNote": "<string>",
  "notifyUser": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/message-moderation/messages/{messageId}/warn-user

Summary: Warn the message sender

Allowed role/access: SUPER_ADMIN or ADMIN with messageModeration.warn

Notes: Access: SUPER_ADMIN or ADMIN with messageModeration.warn. SUPER_ADMIN or ADMIN with messageModeration.warn permission. Creates warning notification and audit log. Creates warning notification, moderation log, and audit log when notifyUser=true.

Parameters:

- messageId (path, required, string)

Request payload(s):

payload

```
{
  "reason": "<string>",
  "warningMessage": "<string>",
  "internalNote": "<string>",
  "notifyUser": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/message-moderation/messages/{messageId}/suspend-account

Summary: Suspend the message sender account

Allowed role/access: SUPER_ADMIN or ADMIN with messageModeration.suspend

Notes: Access: SUPER_ADMIN or ADMIN with messageModeration.suspend. SUPER_ADMIN or ADMIN with messageModeration.suspend permission. Refuses ADMIN/SUPER_ADMIN accounts. Uses existing user suspension fields and refuses ADMIN/SUPER_ADMIN accounts.

Parameters:

- messageId (path, required, string)

Request payload(s):

payload

```
{
  "reason": "<string>",
```

```
"duration": "TEMPORARY",
"suspendUntil": "<string>",
"internalNote": "<string>",
"notifyUser": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/message-moderation/messages/{messageId}/dismiss-flag

Summary: Dismiss a moderation flag

Allowed role/access: SUPER_ADMIN or ADMIN with messageModeration.dismiss

Notes: Access: SUPER_ADMIN or ADMIN with messageModeration.dismiss. SUPER_ADMIN or ADMIN with messageModeration.dismiss permission. Marks case dismissed, keeps message visible, and writes moderation/audit logs.

Parameters:

- messageId (path, required, string)

Request payload(s):

payload

```
{
  "reason": "<string>",
  "internalNote": "<string>"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/message-moderation/messages/{messageId}/note

Summary: Add internal private moderation note

Allowed role/access: SUPER_ADMIN or ADMIN with messageModeration.notes.create

Notes: Access: SUPER_ADMIN or ADMIN with messageModeration.notes.create. SUPER_ADMIN or ADMIN with messageModeration.notes.create permission. Internal-only note. Internal-only note visible to admin moderation users; creates audit log.

Parameters:

- messageId (path, required, string)

Request payload(s):

payload

```
{
  "note": "<string>"
}
```

Response body:


```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/message-moderation/messages/{messageId}/reprocess

Summary: Reprocess a message through scanner

Allowed role/access: SUPER_ADMIN or ADMIN with messageModeration.moderate

Notes: Access: SUPER_ADMIN or ADMIN with messageModeration.moderate. SUPER_ADMIN or ADMIN with messageModeration.moderate permission. Runs deterministic scanner again and updates the moderation case.

Parameters:

- messageId (path, required, string)

Request payload(s):

payload

```
{
  "reason": "<string>"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Social Moderation

GET /api/v1/admin/social-moderation/stats

Summary: Fetch social moderation stats

Allowed role/access: SUPER_ADMIN or ADMIN with socialModeration.read

Notes: Access: SUPER_ADMIN or ADMIN with socialModeration.read. SUPER_ADMIN or ADMIN with socialModeration.read permission. SUPER_ADMIN or ADMIN with socialModeration.read.

Parameters:

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```
{
  "success": true,
  "data": {
    "totalFlaggedPosts": 245,
    "pendingReports": 38,
    "highSeverityReports": 12,
    "removedPosts": 19,
    "hiddenPosts": 44,
    "warningsSent": 28
  },
}
```

```
"message": "Social moderation stats fetched successfully."
}
```

GET /api/v1/admin/social-moderation/export

Summary: Export social moderation log

Allowed role/access: SUPER_ADMIN or ADMIN with socialModeration.export

Notes: Access: SUPER_ADMIN or ADMIN with socialModeration.export. SUPER_ADMIN or ADMIN with socialModeration.export permission. SUPER_ADMIN or ADMIN with socialModeration.export. Exports moderation-safe fields only.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- reportType (query, optional, string)
- status (query, optional, string)
- severity (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)
- format (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/social-moderation/reports

Summary: List social moderation reports

Allowed role/access: SUPER_ADMIN or ADMIN with socialModeration.read

Notes: Access: SUPER_ADMIN or ADMIN with socialModeration.read. SUPER_ADMIN or ADMIN with socialModeration.read permission. SUPER_ADMIN or ADMIN with socialModeration.read. Search supports post content, user name, username, report ID, and post ID.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- reportType (query, optional, string)
- status (query, optional, string)
- severity (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/social-moderation/reports/{id}

Summary: Fetch social report inspection details

Allowed role/access: SUPER_ADMIN or ADMIN with socialModeration.read

Notes: Access: SUPER_ADMIN or ADMIN with socialModeration.read. SUPER_ADMIN or ADMIN with socialModeration.read permission. SUPER_ADMIN or ADMIN with socialModeration.read. Returns post inspection drawer data and report history.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/social-moderation/reports/{id}/action

Summary: Run social moderation action

Allowed role/access: SUPER_ADMIN or ADMIN with socialModeration.moderate

Notes: Access: SUPER_ADMIN or ADMIN with socialModeration.moderate. SUPER_ADMIN or ADMIN with socialModeration.moderate permission. SUPER_ADMIN or ADMIN with socialModeration.moderate. HIDE/REMOVE/WARN_USER create moderation logs and audit logs; posts are not physically deleted.

Parameters:

- id (path, required, string)

Request payload(s):

hide

```
{
  "action": "HIDE",
  "reason": "SPAM",
  "comment": "Post hidden due to deceptive link reports.",
  "notifyUser": true
}
```

remove

```
{
  "action": "REMOVE",
  "reason": "DECEPTIVE_LINK",
  "comment": "Post removed after manual review.",
  "notifyUser": true
}
```

warn

```
{
  "action": "WARN_USER",
  "reason": "INAPPROPRIATE_BEHAVIOR",
  "comment": "Warning issued for repeated spam behavior.",
  "notifyUser": true
}
```

reviewed

```
{
  "action": "MARK_REVIEWED",
  "comment": "Reviewed and no additional action required.",
  "notifyUser": false
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Social Reporting Rules

GET /api/v1/admin/social-reporting-rules/stats

Summary: Fetch social reporting rule stats

Allowed role/access: SUPER_ADMIN or ADMIN with socialReportingRules.read

Notes: Access: SUPER_ADMIN or ADMIN with socialReportingRules.read. SUPER_ADMIN or ADMIN with socialReportingRules.read permission. SUPER_ADMIN or ADMIN with socialReportingRules.read.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/social-reporting-rules/export

Summary: Export social reporting rules

Allowed role/access: SUPER_ADMIN or ADMIN with socialReportingRules.export

Notes: Access: SUPER_ADMIN or ADMIN with socialReportingRules.export. SUPER_ADMIN or ADMIN with socialReportingRules.export permission. SUPER_ADMIN or ADMIN with socialReportingRules.export.

Parameters:

- format (query, optional, string)
- isActive (query, optional, boolean)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/social-reporting-rules

Summary: List social reporting rules

Allowed role/access: SUPER_ADMIN or ADMIN with socialReportingRules.read

Notes: Access: SUPER_ADMIN or ADMIN with socialReportingRules.read. SUPER_ADMIN or ADMIN with socialReportingRules.read permission. SUPER_ADMIN or ADMIN with socialReportingRules.read.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- isActive (query, optional, boolean)
- reportCategory (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/social-reporting-rules

Summary: Create social reporting rule

Allowed role/access: SUPER_ADMIN or ADMIN with socialReportingRules.create

Notes: Access: SUPER_ADMIN or ADMIN with socialReportingRules.create. SUPER_ADMIN or ADMIN with socialReportingRules.create permission. SUPER_ADMIN or ADMIN with socialReportingRules.create.

Request payload(s):

payload

```
{
  "reportCategory": "<string>",
  "label": "<string>",
  "description": "<string>",
  "iconKey": "<string>",
  "autoFlagThreshold": 1.0,
  "escalationRule": "AUTO_HIDE_CONTENT",
  "isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/social-reporting-rules/{id}

Summary: Fetch social reporting rule details

Allowed role/access: SUPER_ADMIN or ADMIN with socialReportingRules.read

Notes: Access: SUPER_ADMIN or ADMIN with socialReportingRules.read. SUPER_ADMIN or ADMIN with socialReportingRules.read permission. SUPER_ADMIN or ADMIN with socialReportingRules.read.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/admin/social-reporting-rules/{id}

Summary: Update social reporting rule

Allowed role/access: SUPER_ADMIN or ADMIN with socialReportingRules.update

Notes: Access: SUPER_ADMIN or ADMIN with socialReportingRules.update. SUPER_ADMIN or ADMIN with socialReportingRules.update permission. SUPER_ADMIN or ADMIN with socialReportingRules.update.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "label": "<string>",
  "description": "<string>",
}
```

```
"iconKey": "<string>",
"autoFlagThreshold": 1.0,
"escalationRule": "AUTO_HIDE_CONTENT",
"isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/admin/social-reporting-rules/{id}

Summary: Delete social reporting rule

Allowed role/access: SUPER_ADMIN or ADMIN with socialReportingRules.delete

Notes: Access: SUPER_ADMIN or ADMIN with socialReportingRules.delete. SUPER_ADMIN or ADMIN with socialReportingRules.delete permission. SUPER_ADMIN or ADMIN with socialReportingRules.delete. Permanently deletes the rule record.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/admin/social-reporting-rules/{id}/status

Summary: Update social reporting rule status

Allowed role/access: SUPER_ADMIN or ADMIN with socialReportingRules.update

Notes: Access: SUPER_ADMIN or ADMIN with socialReportingRules.update. SUPER_ADMIN or ADMIN with socialReportingRules.update permission. SUPER_ADMIN or ADMIN with socialReportingRules.update.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "isActive": true,
  "reason": "<string>"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Referral Settings

GET /api/v1/referral-settings

Summary: Fetch referral settings

Allowed role/access: SUPER_ADMIN or ADMIN with referralSettings.read

Notes: Access: SUPER_ADMIN or ADMIN with referralSettings.read. SUPER_ADMIN or ADMIN with referralSettings.read permission. SUPER_ADMIN or ADMIN with referralSettings.read. Customer referral APIs consume these settings. Pending referrals use the settings snapshot stored at referral creation.

Response body:

```
{
  "success": true,
  "data": {
    "isActive": true,
    "referrerRewardAmount": 25,
    "newUserRewardAmount": 10,
    "rewardCurrency": "USD",
    "minimumTransactionAmount": 50,
    "referralExpirationValue": 30,
    "referralExpirationUnit": "DAYS",
    "allowSelfReferrals": false,
    "qualificationRule": "FIRST_SUCCESSFUL_PURCHASE",
    "updatedAt": "2026-05-09T10:00:00.000Z"
  },
  "message": "Referral settings fetched successfully."
}
```

PATCH /api/v1/referral-settings

Summary: Update referral settings

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Changes apply to future referral snapshots. SUPER_ADMIN only. Changes apply to future referral snapshots and do not recalculate already-earned rewards.

Request payload(s):

payload

```
{
  "referrerRewardAmount": 25,
  "newUserRewardAmount": 10,
  "rewardCurrency": "USD",
  "minimumTransactionAmount": 50,
  "referralExpirationValue": 30,
  "referralExpirationUnit": "DAYS",
  "allowSelfReferrals": false,
  "qualificationRule": "FIRST_SUCCESSFUL_PURCHASE"
}
```

Response body:


```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/referral-settings/activate

Summary: Activate referral program

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Activates referral program. SUPER_ADMIN only. Existing earned rewards remain redeemable.

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/referral-settings/deactivate

Summary: Deactivate referral program

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Deactivates referral program. SUPER_ADMIN only. New referral rewards are blocked while inactive; earned rewards remain redeemable.

Request payload(s):

payload

```
{
  "reason": "Temporarily paused by Super Admin."
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/referral-settings/stats

Summary: Fetch referral stats

Allowed role/access: SUPER_ADMIN or ADMIN with referralSettings.read

Notes: Access: SUPER_ADMIN or ADMIN with referralSettings.read. SUPER_ADMIN or ADMIN with referralSettings.read permission. SUPER_ADMIN or ADMIN with referralSettings.read.

Response body:

```
{
  "success": true,
```

```
"data": "<response returned by endpoint>",
"message": "Request completed successfully."
}
```

GET /api/v1/referral-settings/audit-logs

Summary: List referral settings audit logs

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Referral settings audit logs. SUPER_ADMIN only.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Refund Policy Settings

GET /api/v1/admin/refund-policy-settings

Summary: Fetch refund policy settings

Allowed role/access: SUPER_ADMIN or ADMIN with refundPolicies.read

Notes: Access: SUPER_ADMIN or ADMIN with refundPolicies.read. SUPER_ADMIN or ADMIN with refundPolicies.read permission. Settings feed refund eligibility, auto-refund, dispute, and provider refund workflows. SUPER_ADMIN or ADMIN with refundPolicies.read. These global settings are used by refund eligibility, auto-refund, dispute decisions, and provider refund workflows. Only active gift categories are returned as eligible auto-refund categories; non-selected categories require manual review.

Response body:

```
{
  "success": true,
  "data": {
    "refundWindowDays": 30,
    "autoRefundThresholdAmount": 50,
    "currency": "PKR",
    "autoApproveSmallRefunds": true,
    "smallRefundAutoApproveAmount": 15,
    "eligibleCategories": [
      {
        "id": "category_electronics",
        "name": "Electronics"
      },
      {
        "id": "category_apparel",
        "name": "Apparel"
      },
      {
        "id": "category_home_decor",
        "name": "Home Decor"
      }
    ]
  },
}
```

```
"lastUpdatedAt": "2026-05-14T10:00:00.000Z",
"lastUpdatedBy": {
  "id": "admin_id",
  "name": "Alex Rivera"
},
"message": "Refund policy settings fetched successfully."
}
```

PATCH /api/v1/admin/refund-policy-settings

Summary: Update refund policy settings

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Updates global refund rules. SUPER_ADMIN only. Updates global refund policy settings used by customer refund request eligibility, small auto-refunds, provider refund handling, and admin/provider dispute workflows.

Request payload(s):

update

```
{
  "refundWindowDays": 30,
  "autoRefundThresholdAmount": 50,
  "currency": "PKR",
  "autoApproveSmallRefunds": true,
  "smallRefundAutoApproveAmount": 15,
  "eligibleCategoryIds": [
    "category_electronics",
    "category_apparel",
    "category_home_decor"
  ]
}
```

Response body:

```
{
  "success": true,
  "data": {
    "refundWindowDays": 30,
    "autoRefundThresholdAmount": 50,
    "currency": "PKR",
    "autoApproveSmallRefunds": true,
    "smallRefundAutoApproveAmount": 15,
    "eligibleCategoryIds": [
      "category_electronics",
      "category_apparel",
      "category_home_decor"
    ],
    "lastUpdatedAt": "2026-05-14T10:00:00.000Z"
  },
  "message": "Refund policy settings updated successfully."
}
```

GET /api/v1/admin/refund-policy-settings/logs

Summary: List refund policy audit logs

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Refund policy settings audit logs. SUPER_ADMIN only. Returns compliance logs for REFUND_POLICY_SETTINGS_UPDATED changes, including before/after policy JSON.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "audit_log_id",
      "action": "REFUND_POLICY_SETTINGS_UPDATED",
      "actor": {
        "id": "admin_id",
        "name": "Alex Rivera"
      },
      "before": {
        "refundWindowDays": 14,
        "autoRefundThresholdAmount": 25
      },
      "after": {
        "refundWindowDays": 30,
        "autoRefundThresholdAmount": 50
      },
      "createdAt": "2026-05-14T10:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Refund policy audit logs fetched successfully."
}
```

02 Admin - Media Upload Policy

GET /api/v1/media-upload-policy

Summary: Fetch global media upload policy

Allowed role/access: SUPER_ADMIN or ADMIN with mediaPolicy.read

Notes: Access: SUPER_ADMIN or ADMIN with mediaPolicy.read. SUPER_ADMIN or ADMIN with mediaPolicy.read permission. SUPER_ADMIN or ADMIN with mediaPolicy.read. uploads/presigned-url enforces this policy before issuing upload URLs.

Response body:

```
{
  "success": true,
  "data": {
    "allowedFileTypes": {
      "jpeg": true,
      "jpg": true,
      "png": true,
      "gif": false,
      "mp4": true,
      "mov": true,

```

```
      "mp3": true,
      "wav": false,
      "svg": false
    },
    "maxImageSizeMb": 10,
    "maxVideoSizeMb": 500,
    "maxAudioSizeMb": 50,
    "scanUploads": true,
    "blockSvgUploads": true,
    "updatedAt": "2026-05-09T10:00:00.000Z",
    "updatedBy": {
      "id": "admin_id",
      "name": "Alex Rivera"
    }
  },
  "message": "Media upload policy fetched successfully."
}
```

PATCH /api/v1/media-upload-policy

Summary: Update global media upload policy

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Updates global media upload policy. SUPER_ADMIN only. Does not expose AWS secrets or bucket credentials.

Request payload(s):

payload

```
{
  "allowedFileTypes": {
    "jpeg": true,
    "jpg": true,
    "png": true,
    "gif": false,
    "mp4": true,
    "mov": true,
    "mp3": true,
    "wav": false,
    "svg": false
  },
  "maxImageSizeMb": 10,
  "maxVideoSizeMb": 500,
  "maxAudioSizeMb": 50,
  "scanUploads": true,
  "blockSvgUploads": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/media-upload-policy/audit-logs

Summary: List media upload policy audit logs

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Media upload policy audit logs. SUPER_ADMIN only.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - System Settings

GET /api/v1/admin/system-settings

Summary: Fetch system settings

Allowed role/access: SUPER_ADMIN or ADMIN with systemSettings.read

Notes: Access: SUPER_ADMIN or ADMIN with systemSettings.read. SUPER_ADMIN or ADMIN with systemSettings.read permission. SMTP secrets are never returned. SUPER_ADMIN or ADMIN with systemSettings.read. SMTP secrets are never returned.

Response body:

```
{
  "success": true,
  "data": {
    "platformInfo": {
      "applicationName": "Gift App",
      "supportEmail": "support@giftapp.com",
      "platformLogoUrl": "https://cdn.example.com/logo.png"
    },
    "security": {
      "sessionTimeoutMinutes": 30,
      "adminMfaRequired": true,
      "passwordPolicy": {
        "minLength": 8,
        "requireUppercase": true,
        "requireLowercase": true,
        "requireNumber": true,
        "requireSymbol": true
      }
    },
    "payments": {
      "defaultCurrency": "USD",
      "transactionFeePercent": 2.5
    },
    "notifications": {
      "pushNotificationsEnabled": true,
      "emailNotificationsEnabled": true,
      "smtpConfigured": true
    }
  },
  "message": "System settings fetched successfully."
}
```

PATCH /api/v1/admin/system-settings

Summary: Update system settings

Allowed role/access: SUPER_ADMIN or ADMIN with systemSettings.update

Notes: Access: SUPER_ADMIN or ADMIN with systemSettings.update. SUPER_ADMIN or ADMIN with systemSettings.update permission. SUPER_ADMIN or ADMIN with systemSettings.update. Session timeout and payment fee changes apply to future sessions/transactions only.

Request payload(s):

payload

```
{
  "platformInfo": {
    "applicationName": "Gift App",
    "supportEmail": "support@giftapp.com",
    "platformLogoUrl": "https://cdn.example.com/logo.png"
  },
  "security": {
    "sessionTimeoutMinutes": 30,
    "adminMfaRequired": true,
    "passwordPolicy": {
      "minLength": 8,
      "requireUppercase": true,
      "requireLowercase": true,
      "requireNumber": true,
      "requireSymbol": true
    }
  },
  "payments": {
    "defaultCurrency": "USD",
    "transactionFeePercent": 2.5
  },
  "notifications": {
    "pushNotificationsEnabled": true,
    "emailNotificationsEnabled": true
  }
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/system-settings/logo

Summary: Update system logo URL/reference

Allowed role/access: SUPER_ADMIN or ADMIN with systemSettings.update

Notes: Access: SUPER_ADMIN or ADMIN with systemSettings.update. SUPER_ADMIN or ADMIN with systemSettings.update permission. Stores logo URL/reference only. SUPER_ADMIN or ADMIN with systemSettings.update. Provide a completed Storage upload reference when available; only URL/reference is stored.

Request payload(s):

payload

```
{
  "platformLogoUrl": "https://cdn.example.com/logo.png",
  "uploadId": "upload_id"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/system-settings/smtp/test

Summary: Send SMTP test email

Allowed role/access: SUPER_ADMIN or ADMIN with systemSettings.update

Notes: Access: SUPER_ADMIN or ADMIN with systemSettings.update. SUPER_ADMIN or ADMIN with systemSettings.update permission. Does not expose SMTP secrets. SUPER_ADMIN or ADMIN with systemSettings.update. Uses configured mailer and does not expose SMTP password or secrets.

Request payload(s):

payload

```
{
  "to": "admin@giftapp.com"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/system-settings/audit-logs

Summary: List system settings audit logs

Allowed role/access: SUPER_ADMIN or ADMIN with systemSettings.read

Notes: Access: SUPER_ADMIN or ADMIN with systemSettings.read. SUPER_ADMIN or ADMIN with systemSettings.read permission. SUPER_ADMIN or ADMIN with systemSettings.read.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Guest Access Settings

GET /api/v1/admin/guest-access-settings

Summary: Fetch guest access settings

Allowed role/access: SUPER_ADMIN or ADMIN with guestAccessSettings.read

Notes: Access: SUPER_ADMIN or ADMIN with guestAccessSettings.read. SUPER_ADMIN or ADMIN with guestAccessSettings.read permission. SUPER_ADMIN or ADMIN with guestAccessSettings.read.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/admin/guest-access-settings

Summary: Update guest access settings

Allowed role/access: SUPER_ADMIN or ADMIN with guestAccessSettings.update

Notes: Access: SUPER_ADMIN or ADMIN with guestAccessSettings.update. SUPER_ADMIN or ADMIN with guestAccessSettings.update permission. SUPER_ADMIN or ADMIN with guestAccessSettings.update. Creates audit logs.

Request payload(s):

payload

```
{
  "guestAccessEnabled": true,
  "allowMarketplaceBrowsing": true,
  "allowMarketplaceHome": true,
  "allowGiftDetails": true,
  "allowDiscountedGifts": true,
  "allowFilterOptions": true,
  "allowProviderPreview": true,
  "allowWishlist": true,
  "allowCart": true,
  "allowCheckout": true,
  "sessionTtlMinutes": 1.0,
  "maxRequestsPerMinute": 1.0,
  "showExactStockToGuests": true,
  "showSkuToGuests": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/guest-access-settings/audit-logs

Summary: List guest access settings audit logs

Allowed role/access: SUPER_ADMIN or ADMIN with guestAccessSettings.read

Notes: Access: SUPER_ADMIN or ADMIN with guestAccessSettings.read. SUPER_ADMIN or ADMIN with guestAccessSettings.read permission. SUPER_ADMIN or ADMIN with guestAccessSettings.read.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Support Chat

GET /api/v1/admin/support-chats

Summary: List admin support chats

Allowed role/access: SUPER_ADMIN or ADMIN with supportChats.read

Notes: Access: SUPER_ADMIN or ADMIN with supportChats.read. SUPER_ADMIN all chats; ADMIN assigned chats unless supportChats.read.all. SUPER_ADMIN sees all. ADMIN sees assigned chats unless granted supportChats.read.all.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- participantType (query, optional, string)
- status (query, optional, string)
- unreadOnly (query, optional, boolean)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "support_chat_id",
      "participant": {
        "id": "provider_id",
        "type": "PROVIDER",
        "name": "Luxe Unboxed",
        "avatarUrl": "https://cdn.example.com/avatar.png"
      },
      "subject": "Support Ticket",
      "lastMessage": "I've attached the new listing...",
      "lastMessageAt": "2026-05-16T10:00:00.000Z",
      "unreadCount": 2,
      "status": "ACTIVE"
    }
  ],
  "message": "Support chats fetched successfully."
}
```

GET /api/v1/admin/support-chats/stats

Summary: Fetch support chat stats

Allowed role/access: SUPER_ADMIN or ADMIN with supportChats.read

Notes: Access: SUPER_ADMIN or ADMIN with supportChats.read. Support chat counters.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/support-chats/{id}

Summary: Fetch support chat conversation details

Allowed role/access: SUPER_ADMIN or ADMIN with supportChats.read

Notes: Access: SUPER_ADMIN or ADMIN with supportChats.read. Conversation details scoped to support chat.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/support-chats/{id}/messages

Summary: Reply to support chat

Allowed role/access: SUPER_ADMIN or ADMIN with supportChats.reply

Notes: Access: SUPER_ADMIN or ADMIN with supportChats.reply. Reply with optional support-chat-attachments URLs. Attachments must be completed uploads in support-chat-attachments folder.

Parameters:

- id (path, required, string)

Request payload(s):

text

```
{
  "messageType": "TEXT",
  "body": "I am checking this issue now.",
  "attachmentUrls": []
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/admin/support-chats/{id}/read

Summary: Mark support chat as read

Allowed role/access: SUPER_ADMIN or ADMIN with supportChats.read

Notes: Access: SUPER_ADMIN or ADMIN with supportChats.read. Mark admin unread count read.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```

```
"message": "Request completed successfully."
}
```

POST /api/v1/admin/support-chats/{id}/resolve

Summary: Resolve support chat and notify participant

Allowed role/access: SUPER_ADMIN or ADMIN with supportChats.resolve

Notes: Access: SUPER_ADMIN or ADMIN with supportChats.resolve. Resolve support chat and notify participant.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "comment": "Issue resolved.",
  "notifyParticipant": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/support-chats/{id}/reopen

Summary: Reopen support chat and notify participant

Allowed role/access: SUPER_ADMIN or ADMIN with supportChats.resolve

Notes: Access: SUPER_ADMIN or ADMIN with supportChats.resolve. Reopen support chat and notify participant.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "comment": "Issue resolved.",
  "notifyParticipant": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - System Logs & Audit Trail

GET /api/v1/audit-logs/stats

Summary: Fetch audit log stats

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. System log summary cards are restricted to Super Admin. SUPER_ADMIN only. Returns system log summary cards and security/system metrics.

Parameters:

- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```
{
  "success": true,
  "data": {
    "criticalAlerts24h": 12,
    "dailyAverageActions": 4200,
    "uptimeStatus": 99.98,
    "totalLogs": 1240,
    "successCount": 1100,
    "failedCount": 140
  },
  "message": "Audit log stats fetched successfully."
}
```

GET /api/v1/audit-logs/action-types

Summary: Fetch audit log action types

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Audit log action filter options are restricted to Super Admin. SUPER_ADMIN only. Returns action type dropdown options for System Logs filters.

Response body:

```
{
  "success": true,
  "data": [
    {
      "key": "PROVIDER_APPROVED",
      "label": "Provider Approved"
    },
    {
      "key": "FAILED_LOGIN_ATTEMPT",
      "label": "Failed Login Attempt"
    }
  ],
  "message": "Audit log action types fetched successfully."
}
```

GET /api/v1/audit-logs/users

Summary: Fetch audit log user selector options

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Audit log actor selector options are restricted to Super Admin. SUPER_ADMIN only. Returns actor/user selector options for System Logs filters.

Parameters:

- search (query, optional, string)

- role (query, optional, string)
- limit (query, optional, number)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "system",
      "name": "System",
      "email": null,
      "role": "SYSTEM",
      "label": "System Automated Action"
    },
    {
      "id": "admin_id",
      "name": "Sarah Chen",
      "email": "sarah@example.com",
      "role": "ADMIN",
      "label": "Sarah Chen — Compliance Officer"
    }
  ],
  "message": "Audit log users fetched successfully."
}
```

GET /api/v1/audit-logs/export

Summary: Export audit logs CSV

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Audit log export is restricted to Super Admin. SUPER_ADMIN only. Exports sanitized audit log records using the same filters as the list API.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- actorId (query, optional, string)
- userId (query, optional, string)
- targetId (query, optional, string)
- action (query, optional, string)
- actionType (query, optional, string)
- targetType (query, optional, string)
- module (query, optional, string)
- status (query, optional, string)
- environment (query, optional, string)
- sourceIp (query, optional, string)
- from (query, optional, string)
- to (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/audit-logs

Summary: List audit logs

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Audit logs are restricted to Super Admin. SUPER_ADMIN only. Supports filtering by action type, actor, status, date range, module, and source IP.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- actorId (query, optional, string)
- userId (query, optional, string)
- targetId (query, optional, string)
- action (query, optional, string)
- actionType (query, optional, string)
- targetType (query, optional, string)
- module (query, optional, string)
- status (query, optional, string)
- environment (query, optional, string)
- sourceIp (query, optional, string)
- from (query, optional, string)
- to (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "audit_log_id",
      "eventId": "EV-90210",
      "logReference": "789042",
      "timestamp": "2023-10-27T14:32:01.000Z",
      "actor": {
        "id": "admin_id",
        "name": "Sarah Chen",
        "role": "Compliance Officer",
        "avatarInitials": "SC"
      },
      "action": "PROVIDER_APPROVED",
      "actionLabel": "Provider Approved",
      "module": "Provider Management",
      "sourceIp": "192.168.1.45",
      "environment": "Production-Cluster-A",
      "status": "SUCCESS",
      "target": {
        "id": "provider_id",
        "type": "PROVIDER"
      },
      "createdAt": "2023-10-27T14:32:01.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  }
},
```

```
"message": "Audit logs fetched successfully"
}
```

GET /api/v1/audit-logs/{id}

Summary: Fetch audit log detail

Allowed role/access: SUPER_ADMIN

Notes: Access: SUPER_ADMIN. SUPER_ADMIN only. Audit log details are restricted to Super Admin. SUPER_ADMIN only. Returns sanitized raw JSON payloads, system response preview, and technical metadata.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": {
    "id": "audit_log_id",
    "logReference": "789042",
    "eventId": "EV-90210",
    "timestamp": "2023-10-27T14:32:01.000Z",
    "status": "SUCCESS",
    "category": "AUDIT_TRAIL",
    "actor": {
      "id": "admin_id",
      "username": "super_admin_fintech",
      "name": "Super Admin",
      "role": "SUPER_ADMIN"
    },
    "actionType": "TRANSACTION_AUTHORIZATION",
    "module": "Transactions",
    "sourceIp": "192.168.1.104",
    "environment": "Production-Cluster-A",
    "target": {
      "id": "transaction_id",
      "type": "TRANSACTION"
    },
    "requestPayload": {
      "authorization": "[REDACTED]",
      "request_id": "req_550e8400"
    },
    "systemResponse": {
      "statusCode": 200,
      "durationMs": 142,
      "message": "Transaction authorized successfully."
    },
    "createdAt": "2023-10-27T14:32:01.000Z"
  },
  "message": "Audit log details fetched successfully"
}
```

02 Admin - Dispute Manager

GET /api/v1/admin/disputes/stats

Summary: Fetch dispute dashboard stats

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.read

Notes: Access: SUPER_ADMIN or ADMIN with disputes.read. SUPER_ADMIN or ADMIN with disputes.read permission. SUPER_ADMIN or ADMIN with disputes.read. Supports TODAY, LAST_7_DAYS, LAST_30_DAYS, and CUSTOM ranges.

Parameters:

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```
{
  "success": true,
  "data": {
    "openCases": 12,
    "openCasesDelta": 2,
    "awaitingAction": 5,
    "escalated": 2,
    "resolvedThisWeek": 24,
    "resolvedDeltaPercent": 12,
    "currency": "PKR"
  },
  "message": "Dispute stats fetched successfully."
}
```

GET /api/v1/admin/disputes/export

Summary: Export dispute cases

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.export

Notes: Access: SUPER_ADMIN or ADMIN with disputes.export. SUPER_ADMIN or ADMIN with disputes.export permission. SUPER_ADMIN or ADMIN with disputes.export. Sensitive card/payment secrets are never exported.

Parameters:

- status (query, optional, string)
- priority (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- format (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/disputes

Summary: List dispute queue

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.read

Notes: Access: SUPER_ADMIN or ADMIN with disputes.read. SUPER_ADMIN or ADMIN with disputes.read permission. SUPER_ADMIN or ADMIN with disputes.read. Used by Dispute & Refund Cases queue with filters and sorting.

Parameters:

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)

- status (query, optional, string)
- priority (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "dispute_id",
      "caseId": "DIS-9842",
      "customer": {
        "id": "customer_id",
        "name": "Eleanor Pena",
        "email": "eleanor.p@gmail.com"
      },
      "transactionId": "TRX-78229410",
      "orderId": "order_id",
      "orderNumber": "ORD-88421",
      "amount": 492,
      "currency": "PKR",
      "priority": "HIGH",
      "status": "ESCALATED",
      "daysOpen": 8,
      "reason": "PRODUCT_NOT_RECEIVED",
      "createdAt": "2026-04-01T10:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Disputes fetched successfully."
}
```

GET /api/v1/admin/disputes/{id}/timeline

Summary: Fetch dispute timeline

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.read

Notes: Access: SUPER_ADMIN or ADMIN with disputes.read. SUPER_ADMIN or ADMIN with disputes.read permission. SUPER_ADMIN or ADMIN with disputes.timeline.read. Returns timeline preview events in chronological order.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "timeline_id",
      "type": "DISPUTE_CREATED",
      "title": "Dispute Created",
      "description": "Customer created dispute for product not received.",
      "actor": {
        "type": "CUSTOMER",
        "name": "Jane Doe"
      }
    }
  ]
}
```

```
    },
    "createdAt": "2026-04-05T09:15:00.000Z"
  }
],
"message": "Dispute timeline fetched successfully."
}
```

GET /api/v1/admin/disputes/{id}/internal-data

Summary: Fetch internal transaction data

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.read

Notes: Access: SUPER_ADMIN or ADMIN with disputes.read. SUPER_ADMIN or ADMIN with disputes.read permission. SUPER_ADMIN or ADMIN with disputes.read. Includes payment status, refund eligibility, auth code, and order/provider transaction history without card secrets.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/disputes/{id}/notes

Summary: Fetch internal dispute notes

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.read

Notes: Access: SUPER_ADMIN or ADMIN with disputes.read. SUPER_ADMIN or ADMIN with disputes.read permission. SUPER_ADMIN or ADMIN with disputes.read. Returns internal notes only.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/disputes/{id}/notes

Summary: Add internal dispute note

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.notes.create

Notes: Access: SUPER_ADMIN or ADMIN with disputes.notes.create. SUPER_ADMIN or ADMIN with disputes.notes.create permission. SUPER_ADMIN or ADMIN with disputes.notes.create. Notes are internal-only and create audit/timeline entries.

Parameters:

- id (path, required, string)

Request payload(s):

internal

```
{
  "note": "Customer tracking shows pending status for over 14 days. Investigating merchant log.",
}
```

```
"visibility": "INTERNAL"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/disputes/{id}

Summary: Fetch dispute details and evidence review summary

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.read

Notes: Access: SUPER_ADMIN or ADMIN with disputes.read. SUPER_ADMIN or ADMIN with disputes.read permission. SUPER_ADMIN or ADMIN with disputes.read. SLA remaining text is computed from slaDeadlineAt; approaching deadline is true within 24 hours.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": {
    "id": "dispute_id",
    "caseId": "DSP-1024",
    "status": "IN_REVIEW",
    "priority": "HIGH",
    "reason": "PRODUCT_NOT_RECEIVED",
    "amount": 129.99,
    "currency": "PKR",
    "sla": {
      "deadlineAt": "2026-04-12T10:00:00.000Z",
      "remainingText": "22h 14m remaining",
      "isApproachingDeadline": true
    },
    "customer": {
      "id": "customer_id",
      "name": "Jane Doe",
      "email": "jane.doe@example.com"
    },
    "transaction": {
      "id": "transaction_id",
      "transactionId": "TXN-789012",
      "paymentStatus": "CAPTURED",
      "processorAuthCode": "AUTH-9921-X",
      "amount": 129.99,
      "currency": "PKR"
    },
    "refund": {
      "eligible": true,
      "eligibleReason": "Within refund window",
      "maxRefundAmount": 129.99
    },
    "claimDetails": "Item never arrived. Tracking shows delivered but not at my address.",
    "createdAt": "2026-04-05T09:15:00.000Z",
    "lastUpdatedAt": "2026-04-08T11:45:00.000Z"
  },
}
```

```
"message": "Dispute details fetched successfully."
}
```

02 Admin - Dispute Evidence

GET /api/v1/admin/disputes/{id}/evidence

Summary: Fetch dispute evidence

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.read

Notes: Access: SUPER_ADMIN or ADMIN with disputes.read. SUPER_ADMIN or ADMIN with disputes.read permission. SUPER_ADMIN or ADMIN with disputes.evidence.read. Returns only evidence rows linked to this dispute, from customer/admin uploads in dispute-evidence folder.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "evidence_id",
      "fileName": "Order confirmation.pdf",
      "fileUrl": "https://cdn.yourdomain.com/dispute-evidence/order-confirmation.pdf",
      "contentType": "application/pdf",
      "uploadedBy": "CUSTOMER",
      "createdAt": "2026-04-05T09:30:00.000Z"
    }
  ],
  "message": "Dispute evidence fetched successfully."
}
```

02 Admin - Dispute Linkage

GET /api/v1/admin/disputes/{id}/linkage

Summary: Fetch current dispute transaction linkage state

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.read

Notes: Access: SUPER_ADMIN or ADMIN with disputes.read. SUPER_ADMIN or ADMIN with disputes.read permission. SUPER_ADMIN or ADMIN with disputes.read. Shows dispute summary, linked transaction, and current refund selection without card secrets.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": {
    "dispute": {
      "id": "dispute_id",
      "caseId": "DSP-1024",
      "customer": {
        "id": "customer_id",
        "name": "Jane Doe"
      }
    },
  },
}
```

```

      "disputeAmount": 129.99,
      "currency": "PKR",
      "claimDetails": "Item never arrived. Tracking shows delivered but not at my address.",
      "status": "IN_REVIEW"
    },
    "linkedTransaction": {
      "id": "transaction_id",
      "transactionId": "TXN-789012",
      "orderId": "order_id",
      "orderDate": "2026-04-01T00:00:00.000Z",
      "paymentMethod": "VISA **** 1234",
      "amount": 129.99,
      "currency": "PKR",
      "status": "SETTLED",
      "refundEligible": true,
      "eligibilityText": "Eligible within 30-day window"
    },
    "refundSelection": {
      "type": "FULL",
      "amount": 129.99,
      "recommended": true
    }
  },
  "message": "Dispute linkage fetched successfully."
}

```

GET /api/v1/admin/disputes/{id}/transaction-search

Summary: Search original transaction for a dispute

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.read

Notes: Access: SUPER_ADMIN or ADMIN with disputes.read. SUPER_ADMIN or ADMIN with disputes.read permission. SUPER_ADMIN or ADMIN with disputes.read. Search is scoped to the dispute customer where possible and never exposes card secrets.

Parameters:

- id (path, required, string)
- query (query, optional, string)
- recentOnly (query, optional, boolean)
- limit (query, optional, number)

Response body:

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

POST /api/v1/admin/disputes/{id}/link-transaction

Summary: Confirm dispute transaction linkage

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.linkTransaction

Notes: Access: SUPER_ADMIN or ADMIN with disputes.linkTransaction. SUPER_ADMIN or ADMIN with disputes.linkTransaction permission. SUPER_ADMIN or ADMIN with disputes.linkTransaction. Stores linked transaction/ payment/order and refund selection, creates timeline/audit records, and does not process refunds.

Parameters:

- id (path, required, string)

Request payload(s):

full

```
{
  "transactionId": "transaction_id",
  "refundType": "FULL",
  "refundAmount": 129.99,
  "confirmCorrectTransaction": true
}
```

none

```
{
  "transactionId": "transaction_id",
  "refundType": "NONE",
  "confirmCorrectTransaction": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/disputes/{id}/refund-preview

Summary: Preview dispute refund selection

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.refund.evaluate

Notes: Access: SUPER_ADMIN or ADMIN with disputes.refund.evaluate. SUPER_ADMIN or ADMIN with disputes.refund.evaluate permission. SUPER_ADMIN or ADMIN with disputes.refund.evaluate. Validates requested refunds against paid amount, prior refunds, and refund window without processing a refund.

Parameters:

- id (path, required, string)

Request payload(s):

full

```
{
  "transactionId": "transaction_id",
  "refundType": "FULL",
  "refundAmount": 129.99
}
```

partial

```
{
  "transactionId": "transaction_id",
  "refundType": "PARTIAL",
  "refundAmount": 50
}
```

none

```
{
  "transactionId": "transaction_id",
  "refundType": "NONE"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Dispute Decisions

GET /api/v1/admin/disputes/{id}/decision-summary

Summary: Fetch dispute decision summary

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.decide

Notes: Access: SUPER_ADMIN or ADMIN with disputes.decide. SUPER_ADMIN or ADMIN with disputes.decide permission. SUPER_ADMIN or ADMIN with disputes.decide. Summarizes customer, transaction, refund eligibility, and case history before final decision.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/disputes/{id}/decision

Summary: Submit final dispute decision

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.decide plus action-specific permission (approve/reject/escalate)

Notes: Access: SUPER_ADMIN or ADMIN with disputes.decide plus action-specific permission (approve/reject/escalate). SUPER_ADMIN or ADMIN with disputes.decide and the action-specific permission as applicable. SUPER_ADMIN or ADMIN with dispute decision permissions. APPROVE validates linked transaction/refund selection and creates a refund record; REJECT never creates a refund; ESCALATE assigns supervisor and resets SLA. Stripe refunds are represented by refund tracking records and no card/Stripe secrets are exposed.

Parameters:

- id (path, required, string)

Request payload(s):

approve

```
{
  "decision": "APPROVE",
  "comment": "Customer evidence validates missing delivery.",
  "notifyCustomer": true
}
```

reject

```
{
  "decision": "REJECT",
  "reason": "INSUFFICIENT_EVIDENCE",
  "comment": "Tracking evidence confirms delivery.",
}
```



```
"notifyCustomer": true
}
```

escalate

```
{
  "decision": "ESCALATE",
  "assignedToId": "admin_supervisor_id",
  "escalationReason": "Policy ambiguity requires supervisor intervention.",
  "notifyCustomer": false
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/disputes/{id}/confirmation

Summary: Fetch decision confirmation

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.decide

Notes: Access: SUPER_ADMIN or ADMIN with disputes.decide. SUPER_ADMIN or ADMIN with disputes.decide permission. SUPER_ADMIN or ADMIN with disputes.decide. Returns refund, processor, protocol, and customer notification confirmation.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Dispute Tracking

GET /api/v1/admin/disputes/{id}/tracking-log/export

Summary: Export full dispute tracking log

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.tracking.export

Notes: Access: SUPER_ADMIN or ADMIN with disputes.tracking.export. SUPER_ADMIN or ADMIN with disputes.tracking.export permission. SUPER_ADMIN or ADMIN with disputes.tracking.export. Includes timeline, decision, refund, notifications, and internal notes without card or Stripe secrets.

Parameters:

- id (path, required, string)
- format (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```

```
"message": "Request completed successfully."
}
```

GET /api/v1/admin/disputes/{id}/tracking-log

Summary: Fetch full dispute tracking log

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.tracking.read

Notes: Access: SUPER_ADMIN or ADMIN with disputes.tracking.read. SUPER_ADMIN or ADMIN with disputes.tracking.read permission. SUPER_ADMIN or ADMIN with disputes.tracking.read. Returns secure audit timeline, customer notifications, and internal notes.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": {
    "caseId": "DSP-1024",
    "customer": {
      "name": "Jane Doe"
    },
    "finalStatus": "APPROVED",
    "lastUpdatedAt": "2026-04-08T11:45:00.000Z",
    "secureAuditActive": true,
    "timeline": [
      {
        "id": "timeline_id",
        "type": "REFUND_PROCESSED",
        "title": "System Automated Action",
        "description": "Refund processed successfully.",
        "amount": 129.99,
        "refundId": "RF-45678",
        "createdAt": "2026-04-08T11:45:00.000Z"
      }
    ],
    "customerNotifications": [
      {
        "type": "REFUND_CONFIRMATION_EMAIL",
        "status": "DELIVERED",
        "deliveredAt": "2026-04-08T11:46:00.000Z"
      }
    ],
    "internalNotes": [
      {
        "id": "note_id",
        "author": "Alex Morgan",
        "note": "Customer tracking shows pending status for over 14 days.",
        "createdAt": "2026-04-08T10:00:00.000Z"
      }
    ]
  },
  "message": "Case tracking log fetched successfully."
}
```

POST /api/v1/admin/disputes/{id}/follow-up-notes

Summary: Add dispute follow-up note

Allowed role/access: SUPER_ADMIN or ADMIN with disputes.notes.create

Notes: Access: SUPER_ADMIN or ADMIN with disputes.notes.create. SUPER_ADMIN or ADMIN with disputes.notes.create permission. SUPER_ADMIN or ADMIN with disputes.notes.create. Adds internal note, tracking timeline entry, and notifies assigned admin when present.

Parameters:

- id (path, required, string)

Request payload(s):

internal

```
{
  "note": "Followed up with provider for missing dispatch log.",
  "visibility": "INTERNAL"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Provider Dispute Manager

GET /api/v1/admin/provider-disputes/stats

Summary: Fetch provider dispute dashboard stats

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.read

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.read. SUPER_ADMIN or ADMIN with providerDisputes.read permission. SUPER_ADMIN or ADMIN with providerDisputes.read. Reuses Provider Orders, Payments, Notifications, Audit Logs, and dispute patterns.

Parameters:

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```
{
  "success": true,
  "data": {
    "criticalOpenCases": 8,
    "evidencePhase": 3,
    "underReview": 4,
    "escalations": 1,
    "resolvedThisWeek": 14,
    "averageClosureTimeDays": 4.2,
    "topConflictSource": {
      "providerName": "Acme Corp",
      "category": "Quality Disputes",
      "percentOfTotal": 65
    },
    "systemHealth": {
      "status": "STABLE",
      "message": "All nodes stable",
      "apiLatencyMs": 42
    }
  },
}
```

```
"message": "Provider dispute stats fetched successfully."
}
```

GET /api/v1/admin/provider-disputes/export

Summary: Export provider dispute queue

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.export

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.export. SUPER_ADMIN or ADMIN with providerDisputes.export permission. SUPER_ADMIN or ADMIN with providerDisputes.export. Does not expose card secrets or unrelated uploads.

Parameters:

- status (query, optional, string)
- severity (query, optional, string)
- category (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- format (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/provider-disputes

Summary: List provider dispute queue

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.read

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.read. SUPER_ADMIN or ADMIN with providerDisputes.read permission. SUPER_ADMIN or ADMIN with providerDisputes.read. Used by Provider Dispute Case Queue with filters and sorting.

Parameters:

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- providerId (query, optional, string)
- category (query, optional, string)
- severity (query, optional, string)
- status (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "provider_dispute_id",
      "caseId": "PRV-101",
      "provider": {
        "id": "provider_id",
        "businessName": "Acme Corp",

```

```

      "contactName": "John Smith",
      "tier": "Gold Partner"
    },
    "customer": {
      "id": "customer_id",
      "name": "Michael Chen"
    },
    "transaction": {
      "id": "transaction_id",
      "transactionId": "TXN-998",
      "status": "VERIFIED"
    },
    "category": "NON_DELIVERY",
    "amount": 650,
    "currency": "PKR",
    "status": "RULING_PENDING",
    "priority": "HIGH",
    "riskAssessment": "HIGH",
    "daysOpen": 5,
    "createdAt": "2026-04-05T10:00:00.000Z"
  }
],
"meta": {
  "page": 1,
  "limit": 20,
  "total": 1,
  "totalPages": 1
},
"message": "Provider disputes fetched successfully."
}

```

GET /api/v1/admin/provider-disputes/{id}/timeline

Summary: Fetch provider dispute timeline

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.read

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.read. SUPER_ADMIN or ADMIN with providerDisputes.read permission. SUPER_ADMIN or ADMIN with providerDisputes.read. Includes provider dispute creation, evidence submission, requests, and review actions.

Parameters:

- id (path, required, string)

Response body:

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

GET /api/v1/admin/provider-disputes/{id}/notes

Summary: Fetch provider dispute internal notes

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.read

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.read. SUPER_ADMIN or ADMIN with providerDisputes.read permission. SUPER_ADMIN or ADMIN with providerDisputes.read. Returns internal reviewer notes only.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/provider-disputes/{id}/notes

Summary: Add provider dispute internal note

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.notes.create

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.notes.create. SUPER_ADMIN or ADMIN with providerDisputes.notes.create permission. SUPER_ADMIN or ADMIN with providerDisputes.notes.create. Creates internal note, timeline entry, and audit log.

Parameters:

- id (path, required, string)

Request payload(s):

internal

```
{
  "note": "Provider failed to submit required photographic proof.",
  "visibility": "INTERNAL"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/provider-disputes/{id}

Summary: Fetch provider dispute details

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.read

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.read. SUPER_ADMIN or ADMIN with providerDisputes.read permission. SUPER_ADMIN or ADMIN with providerDisputes.read. Reuses Provider Orders, Customer Orders, Payments, Notifications, Storage, and Audit Logs. No card/payment secrets are exposed.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": {
    "id": "provider_dispute_id",
    "caseId": "PD-2047",
    "status": "EVIDENCE_PHASE",
    "priority": "MEDIUM",
    "category": "NON_DELIVERY",
    "reason": "Missing delivery evidence",
    "claimType": "Non-Delivery",
    "amount": 89.99,
    "currency": "PKR",
    "provider": {
      "id": "provider_id",
```

```

    "businessName": "FreshGrocer Supplies",
    "providerCode": "PRV-8923",
    "tier": "Gold Partner",
    "currentPayoutBalance": -127.5,
    "disputeCount": 4,
    "winRate": 50
  },
  "customer": {
    "id": "customer_id",
    "name": "Michael Chen",
    "email": "michael@example.com"
  },
  "order": {
    "id": "order_id",
    "orderNumber": "ORD-45678"
  },
  "transaction": {
    "id": "transaction_id",
    "transactionId": "TXN-789012",
    "grossTransaction": 89.99,
    "providerShare": 67.49,
    "platformFee": 22.5,
    "refundEligible": true,
    "eligibilityText": "Within the standard 14-day resolution window."
  },
  "customerStatement": "I stayed home all day waiting for the delivery. I got a notification saying it was delivered, but nothing was at my door.",
  "riskAlert": {
    "enabled": true,
    "message": "FreshGrocer Supplies has a 60% dispute rate over the last 30 days."
  },
  "createdAt": "2026-04-05T10:00:00.000Z"
},
"message": "Provider dispute details fetched successfully."
}

```

02 Admin - Provider Dispute Evidence

GET /api/v1/admin/provider-disputes/{id}/evidence

Summary: Fetch provider dispute evidence exchange

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.read

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.read. SUPER_ADMIN or ADMIN with providerDisputes.read permission. SUPER_ADMIN or ADMIN with providerDisputes.read. Returns customer/provider evidence linked to providerDisputeId only, reusing Storage and media policy.

Parameters:

- id (path, required, string)

Response body:

```

{
  "success": true,
  "data": {
    "caseId": "PD-2047",
    "reviewStatus": {
      "startedBy": "A. Marcus",
      "startedAt": "2026-04-08T09:00:00.000Z",
      "isComplete": false
    },
    "customerEvidence": {

```

```

        "submittedAt": "2026-04-05T10:00:00.000Z",
        "status": "RECEIVED",
        "narrative": "The package was never delivered to my doorstep despite tracking saying otherwise.",
        "files": [
            {
                "id": "evidence_file_id",
                "fileName": "Order confirmation screenshot.pdf",
                "fileUrl": "https://cdn.yourdomain.com/provider-dispute-evidence/order-confirmation.pdf",
                "contentType": "application/pdf",
                "sizeText": "1.2 MB",
                "category": "PDF Document"
            }
        ]
    },
    "providerEvidence": {
        "submittedAt": "2026-04-07T10:00:00.000Z",
        "status": "RECEIVED_LATE",
        "lateText": "+2 days past deadline",
        "narrative": "Delivery was completed at 2:14 PM. GPS coordinates and driver logs confirm arrival.",
        "files": [
            {
                "id": "evidence_file_id_4",
                "fileName": "GPS coordinates at delivery.json",
                "fileUrl": "https://cdn.yourdomain.com/provider-dispute-evidence/gps.json",
                "contentType": "application/json",
                "sizeText": "4 KB",
                "category": "Metadata File"
            }
        ]
    },
    "internalReviewerNotes": "Document your findings here. These notes are only visible to internal staff."
},
"message": "Provider dispute evidence fetched successfully."
}

```

POST /api/v1/admin/provider-disputes/{id}/evidence/request

Summary: Request additional provider dispute evidence

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.evidence.request

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.evidence.request. SUPER_ADMIN or ADMIN with providerDisputes.evidence.request permission. SUPER_ADMIN or ADMIN with providerDisputes.evidence.request. Creates timeline and optional notifications without changing final ruling.

Parameters:

- id (path, required, string)

Request payload(s):

provider

```

{
  "target": "PROVIDER",
  "message": "Please upload photographic proof of delivery and driver log.",
  "dueAt": "2026-04-09T18:00:00.000Z",
  "notifyTarget": true
}

```

Response body:


```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/provider-disputes/{id}/evidence/mark-reviewed

Summary: Mark provider dispute evidence review complete

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.update

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.update. SUPER_ADMIN or ADMIN with providerDisputes.update permission. SUPER_ADMIN or ADMIN with providerDisputes.update. Marks evidence review complete, moves case to RULING_PENDING, creates timeline and audit log.

Parameters:

- id (path, required, string)

Request payload(s):

review

```
{
  "reviewerNotes": "Provider evidence is incomplete. GPS data was submitted late and lacks photo confirmation.",
  "nextStep": "RULING"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Provider Dispute Rulings

GET /api/v1/admin/provider-disputes/{id}/ruling-summary

Summary: Fetch provider dispute ruling summary

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.ruling.read

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.ruling.read. SUPER_ADMIN or ADMIN with providerDisputes.ruling.read permission. SUPER_ADMIN or ADMIN with providerDisputes.ruling.read. Shows ruling options, evidence summary, and financial starting point.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/provider-disputes/{id}/ruling

Summary: Save provider dispute ruling

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.ruling.create

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.ruling.create. SUPER_ADMIN or ADMIN with providerDisputes.ruling.create permission. SUPER_ADMIN or ADMIN with providerDisputes.ruling.create. Stores ruling and reason, but final financial execution remains gated behind final status update/attestation.

Parameters:

- id (path, required, string)

Request payload(s):

full

```
{
  "ruling": "CUSTOMER_WINS_FULL_REFUND",
  "rulingReason": "Provider failed to provide required proof of delivery.",
  "refundAmount": 89.99,
  "applyPenalty": true,
  "penaltyAmount": 25,
  "penaltyReason": "Repeat offense",
  "saveAsDraft": false
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Provider Financial Adjustments

GET /api/v1/admin/provider-disputes/{id}/financial-impact

Summary: Fetch provider dispute financial impact

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.financial.read

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.financial.read. SUPER_ADMIN or ADMIN with providerDisputes.financial.read permission. SUPER_ADMIN or ADMIN with providerDisputes.financial.read. Server calculates provider share, fee reversal, refund, and penalty impact.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": {
    "caseId": "PD-2047",
    "ruling": "CUSTOMER_WINS_FULL_REFUND",
    "providerAccountPreview": {
      "currentBalance": 340.5,
      "pendingPayout": 210.0,
      "newBalance": 225.51,
      "currency": "PKR"
    },
    "breakdown": [
      {
        "lineItem": "Order Total",
```

```

      "adjustment": 89.99,
      "runningTotal": 89.99
    },
    {
      "lineItem": "Customer Refund",
      "adjustment": -89.99,
      "runningTotal": 0
    },
    {
      "lineItem": "Provider Lost Earnings",
      "adjustment": -67.49,
      "runningTotal": -67.49
    },
    {
      "lineItem": "Platform Fee Reversal",
      "adjustment": -22.5,
      "runningTotal": -89.99
    },
    {
      "lineItem": "Penalty Fee",
      "adjustment": -25.0,
      "runningTotal": -114.99
    }
  ],
  "totalProviderDeduction": 114.99
},
"message": "Financial impact fetched successfully."
}

```

POST /api/v1/admin/provider-disputes/{id}/payout-penalty-linkage

Summary: Link payout and penalty adjustments

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.financial.link

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.financial.link. SUPER_ADMIN or ADMIN with providerDisputes.financial.link permission. SUPER_ADMIN or ADMIN with providerDisputes.financial.link. Creates provider financial adjustment ledgers; final financial execution is still deferred.

Parameters:

- id (path, required, string)

Request payload(s):

deduct

```

{
  "adjustmentType": "DEDUCT_FROM_NEXT_PAYOUT",
  "confirmFinancialAccuracy": true,
  "sendProviderSummary": true
}

```

Response body:

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

POST /api/v1/admin/provider-disputes/{id}/final-attestation

Summary: Complete final financial attestation

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.ruling.update

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.ruling.update. SUPER_ADMIN or ADMIN with providerDisputes.ruling.update permission. SUPER_ADMIN or ADMIN with providerDisputes.ruling.update. Confirms line items and marks case ready for final status update.

Parameters:

- id (path, required, string)

Request payload(s):

confirm

```
{
  "confirmFinancialLineItems": true,
  "sendAutomatedFinancialSummary": true,
  "comment": "All financial line items confirmed as accurate."
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Provider Dispute Resolution

POST /api/v1/admin/provider-disputes/{id}/finalize

Summary: Finalize provider dispute

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.resolve

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.resolve. SUPER_ADMIN or ADMIN with providerDisputes.resolve permission. SUPER_ADMIN or ADMIN with providerDisputes.resolve. Executes final refund/deduction application, updates immutable resolution state, creates financial and communication logs, and opens provider appeal window.

Parameters:

- id (path, required, string)

Request payload(s):

finalize

```
{
  "notifyCustomer": true,
  "notifyProvider": true,
  "executeFinancialAdjustments": true,
  "comment": "Final ruling confirmed and financial adjustments approved."
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/provider-disputes/{id}/resolution

Summary: Fetch provider dispute resolution summary

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.resolve

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.resolve. SUPER_ADMIN or ADMIN with providerDisputes.resolve permission. SUPER_ADMIN or ADMIN with providerDisputes.resolve. Returns final ruling, financial execution, notification status, refund timing, and appeal window.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/admin/provider-disputes/{id}/notify-again

Summary: Resend provider dispute notifications

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.notify

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.notify. SUPER_ADMIN or ADMIN with providerDisputes.notify permission. SUPER_ADMIN or ADMIN with providerDisputes.notify. Resends email/in-app notifications, creates communication log entries, and writes a timeline event.

Parameters:

- id (path, required, string)

Request payload(s):

provider

```
{
  "target": "PROVIDER",
  "channels": [
    "EMAIL",
    "IN_APP"
  ],
  "message": "Reminder: Your dispute resolution is available in the provider portal."
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

02 Admin - Provider Dispute Logs

GET /api/v1/admin/provider-disputes/{id}/resolution-log/export

Summary: Export provider dispute resolution log

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.logs.export

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.logs.export. SUPER_ADMIN or ADMIN with providerDisputes.logs.export permission. SUPER_ADMIN or ADMIN with providerDisputes.logs.export. Includes lifecycle timeline, financial audit log, communication log, ruling, and final status without Stripe/card secrets.

Parameters:

- id (path, required, string)
- format (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/admin/provider-disputes/{id}/resolution-log

Summary: Fetch provider dispute resolution log

Allowed role/access: SUPER_ADMIN or ADMIN with providerDisputes.logs.read

Notes: Access: SUPER_ADMIN or ADMIN with providerDisputes.logs.read. SUPER_ADMIN or ADMIN with providerDisputes.logs.read permission. SUPER_ADMIN or ADMIN with providerDisputes.logs.read. Returns lifecycle timeline, financial audit log, communication log, and performance impact snapshot.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": {
    "caseId": "PD-2047",
    "finalRuling": "CUSTOMER_WINS",
    "closedAt": "2026-10-24T00:00:00.000Z",
    "description": "Complete audit trail of provider dispute, financial adjustments, and communications.",
    "lifecycleTimeline": [
      {
        "type": "PENALTY_APPLIED",
        "title": "Penalty Applied",
        "description": "System-generated penalty of 500.00 applied to provider.",
        "createdAt": "2026-10-24T14:22:00.000Z"
      }
    ],
    "financialAuditLog": [
      {
        "transactionId": "TXN_29048-REV",
        "action": "Reversal Execution",
        "amount": -1240.0,
        "currency": "PKR",
        "status": "SUCCESS"
      }
    ],
    "communicationLog": [
      {
        "type": "EMAIL",
        "title": "Resolution Decision Sent",
        "to": "claims@provider.com",
        "bodyPreview": "The evidence provided failed to meet...",
        "createdAt": "2026-10-24T10:00:00.000Z"
      }
    ],
    "providerPerformanceImpact": {
      "winRateBefore": 50,
      "winRateAfter": 40,

```

```
    "penaltyPoints": 15,
    "tierStatus": "Silver At Risk"
  }
},
"message": "Provider dispute resolution log fetched successfully."
}
```

03 Provider - Dashboard

GET /api/v1/provider/dashboard

Summary: Fetch mobile provider dashboard

Allowed role/access: Authenticated

Notes: Access: Authenticated. Authenticated JWT required. PROVIDER only. providerId is derived from JWT. Pending, rejected, inactive, or suspended providers cannot access the dashboard.

Response body:

```
{
  "success": true,
  "data": {
    "provider": {
      "id": "provider_id",
      "businessName": "Global Logistics Solutions",
      "avatarUrl": "https://cdn.yourdomain.com/provider-avatars/provider.png",
      "approvalStatus": "APPROVED",
      "status": "ACTIVE"
    },
    "operationalSummary": {
      "todayOrders": 24,
      "pendingOrders": 12,
      "activeOffers": 5,
      "totalItems": 128
    },
    "performance": {
      "range": "WEEKLY",
      "labels": [
        "Mon",
        "Tue",
        "Wed",
        "Thu",
        "Fri",
        "Sat",
        "Sun"
      ],
      "values": [
        120,
        180,
        150,
        110,
        190,
        260,
        220
      ],
      "currency": "PKR"
    },
    "recentOrders": [
      {
        "id": "provider_order_id",
        "orderNumber": "ORD-8821",
        "itemName": "Nike Air Max 270",

```

```

        "imageUrl": "https://cdn.yourdomain.com/gifts/shoe.png",
        "amount": 120,
        "currency": "PKR",
        "status": "PAID",
        "createdAgoText": "2m ago"
      }
    ]
  },
  "message": "Provider dashboard fetched successfully."
}

```

03 Provider - Earnings

GET /api/v1/provider/earnings/summary

Summary: Fetch own provider earnings summary

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. providerId is derived from JWT.

Parameters:

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

GET /api/v1/provider/earnings/chart

Summary: Fetch own provider earnings chart

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Uses provider earnings ledger.

Parameters:

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

GET /api/v1/provider/earnings/ledger

Summary: List own provider earnings ledger

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Does not accept providerId query/body.

Parameters:

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- page (query, optional, number)
- limit (query, optional, number)
- type (query, optional, string)
- status (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

03 Provider - Business Info

GET /api/v1/provider/business-info

Summary: Fetch own provider business information

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. providerId is derived from JWT.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/provider/business-info

Summary: Update own provider business information

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Cannot set approvalStatus/isActive; material business changes require verification review.

Request payload(s):

payload

```
{
  "businessName": "Global Logistics Solutions",
  "legalName": "Global Logistics Solutions LLC",
  "taxId": "XX-XXXXXXX",
  "businessCategoryId": "category_id",
  "email": "ops@globallogistics.com",
  "phone": "+1 (555) 012-3456",
  "businessAddress": "123 Main Street",
  "serviceArea": "New York, USA",
  "headquarters": "New York, USA",
  "website": "https://www.sylviabond.com",
  "storeAddress": {
```

```

    "line1": "842 Industrial Way, Suite 102",
    "city": "San Francisco",
    "state": "CA",
    "country": "USA",
    "postalCode": "94107",
    "latitude": 37.7749,
    "longitude": -122.4194
  },
  "businessHours": [
    {
      "day": "MONDAY",
      "isOpen": true,
      "openTime": "09:00",
      "closeTime": "18:00"
    }
  ],
  "fulfillmentMethods": [
    "PICKUP"
  ],
  "autoAcceptOrders": false
}

```

Response body:

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

03 Provider - Buyer Chat

GET /api/v1/provider/chats

Summary: List provider buyer chats

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. Provider can access only own chat threads. PROVIDER only. Uses shared ChatThread/ChatMessage records with customer provider chat. Provider sees only own provider-order threads.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- unreadOnly (query, optional, boolean)

Response body:

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

GET /api/v1/provider/chats/quick-replies

Summary: Fetch provider buyer chat quick replies

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. PROVIDER only. Declared before /provider/chats/:threadId.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/chats/{threadId}**Summary:** Fetch provider buyer chat messages**Allowed role/access:** PROVIDER**Notes:** Access: PROVIDER. PROVIDER only. Provider can access only own chat threads. PROVIDER only. Thread must belong to the authenticated provider.**Parameters:**

- threadId (path, required, string)
- page (query, optional, number)
- limit (query, optional, number)
- before (query, optional, string)

Response body:

```
{
  "success": true,
  "data": {
    "thread": {
      "id": "thread_id",
      "orderNumber": "ORD-45678",
      "customer": {
        "id": "customer_id",
        "name": "Michael Chen",
        "avatarUrl": null
      }
    },
    "messages": [
      {
        "id": "msg_1",
        "messageType": "TEXT",
        "body": "Please share delivery ETA.",
        "attachmentUrls": [],
        "createdAt": "2026-04-08T10:00:00.000Z",
        "isReadByCustomer": true,
        "isReadByProvider": true,
        "senderType": "CUSTOMER"
      }
    ]
  },
  "message": "Chat fetched successfully."
}
```

POST /api/v1/provider/chats/{threadId}/messages**Summary:** Send chat message to buyer**Allowed role/access:** PROVIDER**Notes:** Access: PROVIDER. PROVIDER only. Provider can send only in own thread. PROVIDER only. Provider can send only in own provider order thread. Creates customer notification and updates read receipts.**Parameters:**

- threadId (path, required, string)

Request payload(s):

text

```
{
  "messageType": "TEXT",
  "body": "Your order is ready for shipping.",
  "attachmentUrls": []
}
```

image

```
{
  "messageType": "IMAGE",
  "attachmentUrls": [
    "https://cdn.yourdomain.com/chat-attachments/package.png"
  ]
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/provider/chats/{threadId}/read**Summary:** Mark buyer messages read**Allowed role/access:** PROVIDER**Notes:** Access: PROVIDER. PROVIDER only. Provider can mark only own thread messages read. PROVIDER only. Marks customer messages as read for provider in an owned thread.**Parameters:**

- threadId (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/orders/{id}/chat**Summary:** Get or optionally create provider order chat**Allowed role/access:** PROVIDER**Notes:** Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Provider order must belong to logged-in provider. Reuses existing thread if present.**Parameters:**

- id (path, required, string)

- `createIfMissing` (query, optional, boolean)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST `/api/v1/provider/orders/{id}/chat`

Summary: Create provider order chat

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. `providerId` is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Creates or returns shared `ChatThread` for an owned provider order.

Parameters:

- `id` (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

03 Provider - Reviews

GET `/api/v1/provider/reviews/summary`

Summary: Fetch provider rating summary

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. Provider can access only own reviews. PROVIDER only. Uses shared Review records visible to provider/customer/admin modules.

Response body:

```
{
  "success": true,
  "data": {
    "averageRating": 4.8,
    "reviewCount": 128,
    "distribution": {
      "1": 1,
      "2": 2,
      "3": 5,
      "4": 12,
      "5": 80
    }
  },
}
```

```
{
  "message": "Review summary fetched successfully."
}
```

GET /api/v1/provider/reviews/filter-options

Summary: Fetch provider review filter options

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. PROVIDER only. Declared before /provider/reviews/:id.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/reviews

Summary: List provider reviews

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. Provider can access only own reviews. PROVIDER only. Shows only reviews for own provider account/orders and excludes hidden/removed reviews.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- rating (query, optional, number)
- hasResponse (query, optional, boolean)
- search (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "review_id",
      "orderId": "order_id",
      "orderNumber": "ORD-45678",
      "customer": {
        "id": "customer_id",
        "name": "Michael Chen",
        "avatarUrl": null
      },
      "rating": 5,
      "comment": "Great packaging and timely delivery.",
      "createdAt": "2026-04-08T10:00:00.000Z",
      "isNew": true,
      "likesCount": 3,
      "response": {
        "id": "response_id",
        "body": "Thank you for your feedback!",
        "createdAt": "2026-04-08T11:00:00.000Z"
      }
    }
  ],
  "meta": {
    "page": 1,

```

```
"limit": 20,
"total": 1,
"totalPages": 1
},
"message": "Reviews fetched successfully."
}
```

GET /api/v1/provider/reviews/{id}

Summary: Fetch Provider Reviews details

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. Provider can access only own reviews.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": {
    "id": "review_id",
    "rating": 5,
    "comment": "Great packaging and timely delivery.",
    "customer": {
      "id": "customer_id",
      "name": "Michael Chen",
      "avatarUrl": null
    },
    "order": {
      "id": "order_id",
      "orderNumber": "ORD-45678",
      "createdAt": "2026-04-08T09:00:00.000Z"
    },
    "response": {
      "id": "response_id",
      "body": "Thank you for your feedback!",
      "createdAt": "2026-04-08T11:00:00.000Z"
    }
  },
  "message": "Review fetched successfully."
}
```

POST /api/v1/provider/reviews/{id}/response

Summary: Post public review response

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. Provider can respond only to own reviews. PROVIDER only. Provider can respond only to own review. Only one active public response per review.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "body": "Thank you for your kind words, Sarah. We are happy you loved the packaging."
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/provider/reviews/{id}/response

Summary: Update public review response

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. Provider can update only own review responses. PROVIDER only. Updates only provider's own active response; customer review content is never modified.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "body": "Thank you for your kind words, Sarah. We are happy you loved the packaging."
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/provider/reviews/{id}/response

Summary: Delete public review response

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. Provider can delete only own review responses. PROVIDER only. Deletes only the provider's own response and does not delete the original customer review.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```


03 Provider - Inventory

GET /api/v1/provider/inventory

Summary: List provider inventory items

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Pending providers cannot access inventory. Provider inventory items do not require separate admin approval; visibility depends on approved/active provider plus item active, available, in stock, and not deleted.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- categoryId (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "gift_id",
      "name": "Luxury Perfume",
      "price": 99.99,
      "currency": "PKR",
      "stockQuantity": 50,
      "status": "ACTIVE",
      "moderationStatus": "NOT_REQUIRED",
      "isAvailable": true,
      "category": {
        "id": "category_id",
        "name": "Perfumes"
      },
      "variants": [
        {
          "id": "variant_id",
          "name": "50ml",
          "price": 129.99,
          "stockQuantity": 20,
          "isDefault": true
        }
      ]
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Provider inventory fetched successfully"
}
```

POST /api/v1/provider/inventory

Summary: Create provider inventory item with optional nested variants

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Pending providers cannot access this module. Provider inventory items do not require separate admin approval; approved active providers can create active, available inventory directly.

Request payload(s):

withVariants

```
{
  "name": "Luxury Perfume",
  "description": "Long-lasting premium fragrance.",
  "shortDescription": "Premium fragrance gift.",
  "categoryId": "gift_category_id",
  "price": 99.99,
  "currency": "PKR",
  "stockQuantity": 50,
  "sku": "PERFUME-001",
  "imageUrls": [
    "https://cdn.yourdomain.com/gift-images/perfume.png"
  ],
  "isAvailable": true,
  "variants": [
    {
      "name": "30ml",
      "price": 89.99,
      "originalPrice": 119.99,
      "stockQuantity": 10,
      "sku": "PERFUME-30ML",
      "isPopular": false,
      "isDefault": false,
      "sortOrder": 1,
      "isActive": true
    },
    {
      "name": "50ml",
      "price": 129.99,
      "originalPrice": 159.99,
      "stockQuantity": 20,
      "sku": "PERFUME-50ML",
      "isPopular": true,
      "isDefault": true,
      "sortOrder": 2,
      "isActive": true
    }
  ]
}
```

Response body:

```
{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume",
    "price": 99.99,
    "currency": "PKR",
    "stockQuantity": 50,
    "status": "ACTIVE",
    "moderationStatus": "NOT_REQUIRED",
    "variants": [
      {
        "id": "variant_id",
        "name": "50ml",
        "price": 129.99,
        "originalPrice": 159.99,
```

```
        "stockQuantity": 20,  
        "sku": "PERFUME-50ML",  
        "isDefault": true,  
        "isActive": true  
      }  
    ]  
  },  
  "message": "Inventory item created successfully"  
}
```

GET /api/v1/provider/inventory/stats

Summary: Fetch provider inventory stats

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

Response body:

```
{  
  "success": true,  
  "data": "<response returned by endpoint>",  
  "message": "Request completed successfully."  
}
```

GET /api/v1/provider/inventory/lookup

Summary: Lookup active provider inventory items

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Gift moderation approval is not required for provider inventory lookup.

Response body:

```
{  
  "success": true,  
  "data": "<response returned by endpoint>",  
  "message": "Request completed successfully."  
}
```

GET /api/v1/provider/inventory/{id}

Summary: Fetch own provider inventory item details

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

Parameters:

- id (path, required, string)

Response body:

```
{  
  "success": true,  
  "data": {  
    "id": "gift_id",  
    "name": "Luxury Perfume",  
    "description": "Long-lasting premium fragrance.",  
    "price": 99.99,  
    "currency": "PKR",  
    "stockQuantity": 50,  
  }  
}
```

```

    "status": "ACTIVE",
    "moderationStatus": "NOT_REQUIRED",
    "imageUrls": [
      "https://cdn.yourdomain.com/gift-images/perfume.png"
    ],
    "variants": [
      {
        "id": "variant_id",
        "name": "50ml",
        "price": 129.99,
        "originalPrice": 159.99,
        "stockQuantity": 20,
        "sku": "PERFUME-50ML",
        "isDefault": true,
        "isActive": true
      }
    ]
  },
  "message": "Inventory item fetched successfully"
}

```

PATCH /api/v1/provider/inventory/{id}

Summary: Update own provider inventory item and upsert variants

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Variant id must belong to the provider-owned gift. Price, name, media, and variant changes do not reset provider inventory to pending moderation.

Parameters:

- id (path, required, string)

Request payload(s):

upsertVariants

```

{
  "replaceVariants": false,
  "variants": [
    {
      "id": "variant_id",
      "name": "50ml",
      "price": 129.99,
      "originalPrice": 159.99,
      "stockQuantity": 20,
      "sku": "PERFUME-50ML",
      "isPopular": true,
      "isDefault": true,
      "sortOrder": 2,
      "isActive": true
    },
    {
      "name": "150ml",
      "price": 249.99,
      "originalPrice": 299.99,
      "stockQuantity": 5,
      "sku": "PERFUME-150ML",
      "isPopular": false,
      "isDefault": false,
      "sortOrder": 4,
      "isActive": true
    }
  ]
}

```

```
]
}
```

Response body:

```
{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume",
    "variants": [
      {
        "id": "variant_id",
        "name": "50ml",
        "price": 129.99,
        "stockQuantity": 20,
        "isDefault": true,
        "isActive": true
      }
    ]
  },
  "message": "Inventory item updated successfully"
}
```

DELETE /api/v1/provider/inventory/{id}

Summary: Delete own inventory item

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Permanently deletes the provider inventory item.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/provider/inventory/{id}/availability

Summary: Update own inventory availability

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "isAvailable": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

03 Provider - Promotional Offers

GET /api/v1/provider/offers

Summary: List Provider Offers

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- itemId (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/provider/offers

Summary: Create Provider Offers

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

Request payload(s):

payload

```
{
  "itemId": "<string>",
  "title": "<string>",
  "description": "<string>",
  "discountType": "PERCENTAGE",
  "discountValue": 1.0,
  "startDate": "<string>",
  "endDate": "<string>",
  "eligibilityRules": "<string>",
}
```

```
"isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/offers/{id}

Summary: Fetch Provider Offers details

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/provider/offers/{id}

Summary: Update Provider Offers

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "title": "<string>",
  "description": "<string>",
  "discountType": "PERCENTAGE",
  "discountValue": 1.0,
  "startDate": "<string>",
  "endDate": "<string>",
  "eligibilityRules": "<string>",
  "isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```

```
"message": "Request completed successfully."
}
```

DELETE /api/v1/provider/offers/{id}

Summary: Delete Provider Offers

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/provider/offers/{id}/status

Summary: Update Provider Offers Status

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "isActive": true,
  "reason": "<string>"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

03 Provider - Orders

GET /api/v1/provider/orders

Summary: List own assigned provider orders

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Returns only orders assigned to the authenticated providerId. Default status filter is PENDING.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)
- search (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "provider_order_id",
      "orderId": "order_id",
      "orderNumber": "ORD-10293",
      "status": "PENDING",
      "paymentStatus": "SUCCEEDED",
      "customer": {
        "name": "Sarah Jenkins",
        "phone": "+15551234567"
      },
      "itemPreview": [
        {
          "name": "Premium Sneakers",
          "imageUrl": "https://cdn.yourdomain.com/gifts/sneaker.png"
        }
      ],
      "itemCount": 3,
      "totalPayout": 142,
      "currency": "PKR",
      "createdAt": "2026-10-24T10:45:00.000Z",
      "receivedAgoText": "5m ago"
    }
  ],
  "message": "Provider orders fetched successfully."
}
```

GET /api/v1/provider/orders/history

Summary: List own provider order history

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Uses ProviderOrder records scoped to the authenticated provider. Status tabs map to provider order statuses.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)
- search (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/orders/summary

Summary: Fetch own provider order summary

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Route intentionally declared before :id. PROVIDER only.

Parameters:

- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/orders/reject-reasons

Summary: List provider order reject reasons

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Route intentionally declared before :id.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/provider/orders/{id}/status

Summary: Update own provider order fulfillment status

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Enforces ownership, valid transitions, paid-order fulfillment checks, timeline entries, and customer notifications.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "status": "SHIPPED",
  "note": "Package handed over to courier.",
  "trackingNumber": "FDX-123456",
  "carrier": "FedEx",
  "estimatedDeliveryAt": "2026-10-26T10:00:00.000Z"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/provider/orders/{id}/fulfill

Summary: Fulfill own provider order with dispatch details

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Dedicated Figma fulfill action. Stores dispatch date/time, estimated delivery, carrier, tracking number, moves provider order to SHIPPED, syncs parent order, creates timeline entry, and optionally notifies customer.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "dispatchAt": "2026-04-23T14:45:00.000Z",
  "estimatedDeliveryAt": "2026-04-28T10:00:00.000Z",
  "carrier": "Express Delivery Co.",
  "trackingNumber": "TRK-8842-4567-9023",
  "notifyCustomer": true,
  "note": "Order dispatched successfully."
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/orders/{id}/timeline

Summary: Fetch own provider order timeline

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Timeline is scoped to the authenticated provider order.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/orders/{id}/checklist

Summary: Fetch own provider order checklist

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Checklist is operational and does not change status automatically.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/provider/orders/{id}/checklist

Summary: Update own provider order checklist

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Checklist updates do not directly change order status.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "itemsPacked": true,
  "giftMessageAttached": true,
  "addressVerified": true,
  "customerContactChecked": true,
  "readyForCourier": false,
  "customItems": [
    {
      "id": "checklist_item_id",
      "label": "Include gift wrap",
      "isCompleted": true
    }
  ]
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/provider/orders/{id}/message-buyer

Summary: Message buyer for own provider order

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Creates an order message and customer notification; SMS is placeholder only.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "message": "Your order is being prepared and will be shipped soon.",
  "channel": "IN_APP"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/orders/{id}

Summary: Fetch own provider order details

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Does not expose customer card/payment secrets or admin-only order fields.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/provider/orders/{id}/accept

Summary: Accept own pending provider order

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Allowed transition: PENDING -> ACCEPTED. Creates timeline entry and customer notification.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "note": "Order accepted and will be processed shortly."
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/provider/orders/{id}/reject

Summary: Reject own pending provider order

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Allowed transition: PENDING -> REJECTED. Does not refund automatically; flags order for review/cancellation based on provider split count.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "reason": "OUT_OF_STOCK",
  "comment": "The selected size is currently unavailable."
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

03 Provider - Payout Methods

GET /api/v1/provider/payout-methods

Summary: List own provider payout methods

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. providerId is derived from JWT. Returns masked payout metadata only.

Response body:

```
{
  "success": true,
  "data": {
    "primary": {
      "id": "payout_method_id",
      "type": "BANK_ACCOUNT",
      "bankName": "Chase Bank",
      "maskedAccount": "Checking Account **** 5678",
    }
  }
}
```

```

    "accountHolderName": "Sylvia Bond",
    "payerId": "SB-4491-001",
    "verificationStatus": "VERIFIED",
    "isDefault": true,
    "isActive": true
  },
  "methods": [
    {
      "id": "payout_method_id",
      "type": "BANK_ACCOUNT",
      "bankName": "Chase Bank",
      "maskedAccount": "Checking Account **** 6789",
      "accountHolderName": "Sylvia Bond",
      "verificationStatus": "VERIFIED",
      "isDefault": true,
      "isActive": true
    }
  ]
},
"message": "Provider payout methods fetched successfully."
}

```

POST /api/v1/provider/payout-methods/bank-accounts

Summary: Add provider bank payout method

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Stores masked metadata only; raw routing/account/IBAN values are never returned or persisted.

Request payload(s):

bank

```

{
  "accountHolderName": "Sylvia Bond",
  "bankName": "Chase Bank",
  "accountType": "CHECKING",
  "country": "US",
  "currency": "USD",
  "routingNumber": "110000000",
  "accountNumber": "000123456789",
  "iban": null,
  "isDefault": true
}

```

Response body:

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

GET /api/v1/provider/payout-methods/{id}

Summary: Fetch own provider payout method details

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Full account number, IBAN, and routing number are never returned.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/provider/payout-methods/{id}

Summary: Update provider payout method display metadata

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Bank/routing/account numbers cannot be edited; add a new payout method instead.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "accountHolderName": "Sylvia Bond",
  "bankName": "Chase Bank Personal",
  "isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/provider/payout-methods/{id}

Summary: Delete own provider payout method

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Permanently deletes the payout method and blocks deletion when pending provider payout adjustments exist.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
```



```
"data": "<response returned by endpoint>",
"message": "Request completed successfully."
}
```

PATCH /api/v1/provider/payout-methods/{id}/default

Summary: Set default provider payout method

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Only own verified active payout methods can become default.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/provider/payout-methods/{id}/verify

Summary: Start provider payout method verification

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. If Plaid/Stripe Connect is not configured, MANUAL keeps verification pending for admin/system review.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "verificationMethod": "MANUAL",
  "publicToken": "plaid_public_token"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

03 Provider - Payouts

GET /api/v1/provider/payouts

Summary: List own provider payout history

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. providerId is derived from JWT.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- status (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/payouts/summary

Summary: Fetch own provider payout summary

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Route declared before :id. PROVIDER only.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/payouts/preview

Summary: Preview provider payout request

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Route declared before :id. Validates available balance and verified payout method.

Parameters:

- amount (query, required, number)
- payoutMethodId (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/provider/payouts/request

Summary: Request provider payout

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Uses idempotencyKey to block duplicate payout requests.

Request payload(s):

payload

```
{
  "amount": 1250,
  "payoutMethodId": "payout_method_id",
  "idempotencyKey": "provider_payout_2026_001"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/payouts/{id}

Summary: Fetch own provider payout details

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Scoped to authenticated provider.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/provider/payouts/{id}/cancel

Summary: Cancel own pending provider payout

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Can cancel only PENDING payouts and returns locked balance to AVAILABLE.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "reason": "Requested by provider."
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

03 Provider - Refund Requests

GET /api/v1/provider/refund-requests

Summary: List own provider refund requests

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Returns refund requests for provider orders assigned to the authenticated provider. Search supports order number, customer name, and customer email.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)
- search (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "refund_request_id",
      "providerOrderId": "provider_order_id",
      "orderNumber": "88417",
      "customer": {
        "name": "Jane Cooper",
        "email": "jane.cooper@example.com",
        "avatarUrl": "https://cdn.yourdomain.com/customer-avatar.jpg"
      },
      "requestedAmount": 45,
    }
  ]
}
```

```
    "currency": "PKR",
    "status": "REQUESTED",
    "customerReason": "Item was damaged on arrival",
    "createdAt": "2026-10-23T18:10:00.000Z"
  }
],
"message": "Provider refund requests fetched successfully."
}
```

GET /api/v1/provider/refund-requests/summary

Summary: Fetch own refund request summary

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Route intentionally declared before :id. PROVIDER only.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/refund-requests/reject-reasons

Summary: List refund rejection reasons

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. Route intentionally declared before :id. PROVIDER only.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/refund-requests/{id}

Summary: Fetch own refund request details

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Refund request must belong to the authenticated provider order and never exposes Stripe secrets or raw card data.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/provider/refund-requests/{id}/approve

Summary: Approve own requested refund

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Validates ownership, REQUESTED status, requested amount, refundable amount, creates refund transaction marker, timeline entry, and customer notification.

Parameters:

- id (path, required, string)

Request payload(s):

approve

```
{
  "comment": "Refund approved after reviewing evidence.",
  "refundAmount": 45,
  "notifyCustomer": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/provider/refund-requests/{id}/reject

Summary: Reject own requested refund

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Validates ownership and REQUESTED status. Creates timeline entry and optional customer notification. No Stripe refund is created.

Parameters:

- id (path, required, string)

Request payload(s):

reject

```
{
  "reason": "REFUND_WINDOW_EXPIRED",
  "comment": "The request was submitted after the allowed refund period.",
  "notifyCustomer": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

03 Provider - Order Analytics

GET /api/v1/provider/orders/performance

Summary: Fetch own provider order performance

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Completion rate uses completed / non-cancelled own provider orders.

Parameters:

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/orders/analytics/revenue

Summary: Fetch own provider revenue analytics

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Revenue uses provider totalPayout for paid active/completed provider orders.

Parameters:

- range (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/orders/analytics/ratings

Summary: Fetch own provider ratings analytics

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Returns stable zero values until reviews module is available.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/orders/recent

Summary: List recent own provider orders

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Defaults to 5 latest orders.

Parameters:

- limit (query, optional, number)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/provider/orders/export

Summary: Export own provider orders as CSV

Allowed role/access: PROVIDER

Notes: Access: PROVIDER. PROVIDER only. providerId is derived from JWT; provider can access only own inventory, offers, orders, analytics, and messages. PROVIDER only. Export is scoped to logged-in provider orders.

Parameters:

- status (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- format (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

04 Gifts - Categories

GET /api/v1/gift-categories/lookup

Summary: Lookup active gift categories

Allowed role/access: PUBLIC

Notes: Access: PUBLIC. PUBLIC. Active gift category lookup. Public lookup under Gift Categories. Returns active category identifiers and media fields for lightweight selectors.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/gift-categories

Summary: List gift categories

Allowed role/access: SUPER_ADMIN or ADMIN with giftCategories.read

Notes: Access: SUPER_ADMIN or ADMIN with giftCategories.read. SUPER_ADMIN or ADMIN with giftCategories.read permission. RBAC permission: giftCategories.read. Returns soft-delete-filtered categories with gift counts and category media fields.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- isActive (query, optional, boolean)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/gift-categories

Summary: Create gift category

Allowed role/access: SUPER_ADMIN or ADMIN with giftCategories.create

Notes: Access: SUPER_ADMIN or ADMIN with giftCategories.create. SUPER_ADMIN or ADMIN with giftCategories.create permission. RBAC permission: giftCategories.create. Slug is auto-generated and unique. backgroundColor defaults to #F3E8FF; color remains a backward-compatible alias.

Request payload(s):

create

```
{
  "name": "Perfumes",
  "description": "Premium fragrance gifts.",
  "iconKey": "perfume",
  "backgroundColor": "#E9D5FF",
  "imageUrl": "https://<YOUR_PUBLIC_BUCKET_OR_CDN_URL>/gift-category-images/perfumes.png",
  "sortOrder": 1,
  "isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/gift-categories/stats

Summary: Fetch gift category stats

Allowed role/access: SUPER_ADMIN or ADMIN with giftCategories.read

Notes: Access: SUPER_ADMIN or ADMIN with giftCategories.read. SUPER_ADMIN or ADMIN with giftCategories.read permission. RBAC permission: giftCategories.read. Returns admin category inventory counters.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/gift-categories/{id}

Summary: Fetch gift category details

Allowed role/access: SUPER_ADMIN or ADMIN with giftCategories.read

Notes: Access: SUPER_ADMIN or ADMIN with giftCategories.read. SUPER_ADMIN or ADMIN with giftCategories.read permission. RBAC permission: giftCategories.read. Includes backgroundColor and imageUrl for customer app design support.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/gift-categories/{id}

Summary: Update gift category

Allowed role/access: SUPER_ADMIN or ADMIN with giftCategories.update

Notes: Access: SUPER_ADMIN or ADMIN with giftCategories.update. SUPER_ADMIN or ADMIN with giftCategories.update permission. RBAC permission: giftCategories.update. Slug is regenerated when name changes. Soft-deleted categories are not updated.

Parameters:

- id (path, required, string)

Request payload(s):

update

```
{
  "backgroundColor": "#F3E8FF",
  "imageUrl": "https://<YOUR_PUBLIC_BUCKET_OR_CDN_URL>/gift-category-images/perfumes.png",
  "isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/gift-categories/{id}

Summary: Delete gift category

Allowed role/access: SUPER_ADMIN or ADMIN with giftCategories.delete

Notes: Access: SUPER_ADMIN or ADMIN with giftCategories.delete. SUPER_ADMIN or ADMIN with giftCategories.delete permission. RBAC permission: giftCategories.delete. Permanently deletes the category. Categories with attached gifts cannot be deleted; delete writes an audit log.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

04 Gifts - Management

GET /api/v1/gifts

Summary: List admin gifts

Allowed role/access: SUPER_ADMIN or ADMIN with gifts.read

Notes: Access: SUPER_ADMIN or ADMIN with gifts.read. SUPER_ADMIN or ADMIN with gifts.read permission. SUPER_ADMIN/ADMIN with gifts.read. Supports category/provider/status/moderation filters.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- categoryId (query, optional, string)
- providerId (query, optional, string)
- status (query, optional, string)
- moderationStatus (query, optional, string)
- isPublished (query, optional, boolean)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/gifts

Summary: Create admin gift with optional nested variants

Allowed role/access: SUPER_ADMIN or ADMIN with gifts.create

Notes: Access: SUPER_ADMIN or ADMIN with gifts.create. SUPER_ADMIN or ADMIN with gifts.create permission. SUPER_ADMIN/ADMIN with gifts.create. Nested variants are created in the same transaction and stored in GiftVariant.

Request payload(s):

withVariants

```
{
  "name": "Luxury Perfume",
  "description": "Long-lasting premium fragrance.",
  "shortDescription": "Premium fragrance gift.",
  "categoryId": "gift_category_id",
  "providerId": "provider_id",
  "price": 99.99,
  "currency": "PKR",
  "stockQuantity": 50,
  "sku": "PERFUME-001",
  "imageUrls": [
    "https://cdn.yourdomain.com/gift-images/perfume.png"
  ],
  "isPublished": true,
  "isFeatured": false,
  "tags": [
    "perfume",
    "luxury"
  ],
  "moderationStatus": "APPROVED",
  "variants": [
    {
      "name": "30ml",
      "price": 89.99,
      "originalPrice": 119.99,
      "stockQuantity": 10,
      "sku": "PERFUME-30ML",
      "isPopular": false,
      "isDefault": false,
      "sortOrder": 1,
      "isActive": true
    },
    {
      "name": "50ml",
      "price": 129.99,
      "originalPrice": 159.99,
      "stockQuantity": 20,
      "sku": "PERFUME-50ML",
      "isPopular": true,
      "isDefault": true,
      "sortOrder": 2,
      "isActive": true
    }
  ]
}
```

Response body:

```
{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume",
    "price": 99.99,
    "currency": "PKR",
    "stockQuantity": 50,
    "sku": "PERFUME-001",
    "variants": [
      {
        "id": "variant_id",
        "name": "50ml",
        "price": 129.99,
        "originalPrice": 159.99,
```

```
      "stockQuantity": 20,
      "sku": "PERFUME-50ML",
      "isPopular": true,
      "isDefault": true,
      "sortOrder": 2,
      "isActive": true
    }
  ]
},
"message": "Gift created successfully"
}
```

GET /api/v1/gifts/stats

Summary: Fetch gift inventory stats

Allowed role/access: SUPER_ADMIN or ADMIN with gifts.read

Notes: Access: SUPER_ADMIN or ADMIN with gifts.read. SUPER_ADMIN or ADMIN with gifts.read permission.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/gifts/export

Summary: Export gift inventory

Allowed role/access: SUPER_ADMIN or ADMIN with gifts.export

Notes: Access: SUPER_ADMIN or ADMIN with gifts.export. SUPER_ADMIN or ADMIN with gifts.export permission.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- categoryId (query, optional, string)
- providerId (query, optional, string)
- status (query, optional, string)
- moderationStatus (query, optional, string)
- isPublished (query, optional, boolean)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)
- format (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/gifts/{id}

Summary: Fetch admin gift details with variants

Allowed role/access: SUPER_ADMIN or ADMIN with gifts.read

Notes: Access: SUPER_ADMIN or ADMIN with gifts.read. SUPER_ADMIN or ADMIN with gifts.read permission.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/gifts/{id}**Summary:** Update admin gift and upsert nested variants**Allowed role/access:** SUPER_ADMIN or ADMIN with gifts.update**Notes:** Access: SUPER_ADMIN or ADMIN with gifts.update. SUPER_ADMIN or ADMIN with gifts.update permission. If replaceVariants=true, omitted variants are soft-deleted. Only one default variant is allowed.**Parameters:**

- id (path, required, string)

Request payload(s):

upsertVariants

```
{
  "name": "Luxury Perfume Updated",
  "replaceVariants": false,
  "variants": [
    {
      "id": "variant_id",
      "name": "50ml",
      "price": 129.99,
      "originalPrice": 159.99,
      "stockQuantity": 20,
      "sku": "PERFUME-50ML",
      "isPopular": true,
      "isDefault": true,
      "sortOrder": 2,
      "isActive": true
    },
    {
      "name": "150ml",
      "price": 249.99,
      "originalPrice": 299.99,
      "stockQuantity": 5,
      "sku": "PERFUME-150ML",
      "isPopular": false,
      "isDefault": false,
      "sortOrder": 4,
      "isActive": true
    }
  ]
}
```

Response body:

```
{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume Updated",
```

```
"variants": [
  {
    "id": "variant_id",
    "name": "50ml",
    "price": 129.99,
    "originalPrice": 159.99,
    "stockQuantity": 20,
    "sku": "PERFUME-50ML",
    "isDefault": true,
    "isActive": true
  }
],
"message": "Gift updated successfully"
}
```

DELETE /api/v1/gifts/{id}

Summary: Delete gift

Allowed role/access: SUPER_ADMIN or ADMIN with gifts.delete

Notes: Access: SUPER_ADMIN or ADMIN with gifts.delete. SUPER_ADMIN or ADMIN with gifts.delete permission.
Permanently deletes the gift record.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/gifts/{id}/status

Summary: Update gift status

Allowed role/access: SUPER_ADMIN or ADMIN with gifts.status.update

Notes: Access: SUPER_ADMIN or ADMIN with gifts.status.update. SUPER_ADMIN or ADMIN with gifts.status.update permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "status": "ACTIVE",
  "reason": "<string>"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

04 Gifts - Moderation

GET /api/v1/gift-moderation

Summary: List optional gift moderation queue

Allowed role/access: SUPER_ADMIN or ADMIN with giftModeration.read

Notes: Access: SUPER_ADMIN or ADMIN with giftModeration.read. SUPER_ADMIN or ADMIN with giftModeration.read permission. Gift moderation is optional/exception-based; default queue returns only PENDING, FLAGGED, REJECTED, or requiresManualReview=true. Provider-created inventory does not require separate Super Admin approval by default. Gift Moderation is optional/admin review workflow for flagged, reported, high-risk, or admin-forced review items. Provider-created inventory does not require separate Super Admin approval by default; provider approval is the primary marketplace trust gate. Default queue returns only PENDING, FLAGGED, REJECTED, or requiresManualReview=true. Use status=APPROVED, status=NOT_REQUIRED, or includeResolved=true to view resolved/normal inventory.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)
- includeResolved (query, optional, boolean) When true, includes resolved/normal statuses such as APPROVED and NOT_REQUIRED. Default queue returns only PENDING, FLAGGED, REJECTED, or requiresManualReview=true.
- search (query, optional, string)
- providerId (query, optional, string)
- view (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/gift-moderation/{id}/approve

Summary: Approve gift in optional moderation workflow

Allowed role/access: SUPER_ADMIN or ADMIN with giftModeration.approve

Notes: Access: SUPER_ADMIN or ADMIN with giftModeration.approve. SUPER_ADMIN or ADMIN with giftModeration.approve permission. Clears manual review/hidden-by-moderation flags. This is not required for normal provider-created inventory visibility; approved active providers can publish inventory directly.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "comment": "<string>",
  "publishNow": true,
}
```



```
"notifyProvider": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/gift-moderation/{id}/reject

Summary: Reject gift in optional moderation workflow

Allowed role/access: SUPER_ADMIN or ADMIN with giftModeration.reject

Notes: Access: SUPER_ADMIN or ADMIN with giftModeration.reject. SUPER_ADMIN or ADMIN with giftModeration.reject permission. Rejecting hides the gift from marketplace, clears manual review, sets moderationStatus=REJECTED, and writes an audit log.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "reason": "INCOMPLETE_INFORMATION",
  "comment": "<string>",
  "notifyProvider": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/gift-moderation/{id}/flag

Summary: Flag gift for manual review

Allowed role/access: SUPER_ADMIN or ADMIN with giftModeration.flag

Notes: Access: SUPER_ADMIN or ADMIN with giftModeration.flag. SUPER_ADMIN or ADMIN with giftModeration.flag permission. Flags optional moderation case. If hideFromMarketplace=true, sets moderationStatus=FLAGGED, requiresManualReview=true, hiddenByModeration=true, and isPublished=false. If false, the gift remains visible but appears in moderation queue. Always writes an audit log.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "reason": "NEEDS_MANUAL_REVIEW",
  "comment": "<string>",
  "hideFromMarketplace": true,
}
```

```
"notifyProvider": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

05 Customer / Guest - Marketplace

GET /api/v1/customer/home

Summary: Fetch customer app home

Allowed role/access: REGISTERED_USER or GUEST_USER

Notes: Access: REGISTERED_USER or GUEST_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest response behavior includes isWishlisted=false, requiresAuthForWishlist=true, requiresAuthForCart=true, requiresAuthForCheckout=true, defaultAddress=null, upcomingReminder=null, and mode="GUEST" where applicable. REGISTERED_USER or GUEST_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest home responses include defaultAddress=null, upcomingReminder=null, and mode="GUEST".

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/categories

Summary: List customer marketplace categories

Allowed role/access: REGISTERED_USER or GUEST_USER

Notes: Access: REGISTERED_USER or GUEST_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest response behavior includes isWishlisted=false, requiresAuthForWishlist=true, requiresAuthForCart=true, requiresAuthForCheckout=true, defaultAddress=null, upcomingReminder=null, and mode="GUEST" where applicable. REGISTERED_USER or GUEST_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/gifts/discounted

Summary: List discounted customer gifts

Allowed role/access: REGISTERED_USER or GUEST_USER

Notes: Access: REGISTERED_USER or GUEST_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest response behavior includes isWishlisted=false, requiresAuthForWishlist=true, requiresAuthForCart=true, requiresAuthForCheckout=true, defaultAddress=null, upcomingReminder=null, and mode="GUEST" where applicable. REGISTERED_USER or GUEST_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Discounted gift cards include isWishlisted=false and auth-required flags for guests.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- categoryId (query, optional, string)
- categorySlug (query, optional, string)
- providerId (query, optional, string)
- offerOnly (query, optional, boolean)
- minPrice (query, optional, number)
- maxPrice (query, optional, number)
- minRating (query, optional, number)
- brand (query, optional, string)
- deliveryOption (query, optional, string)
- sortBy (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/gifts/filter-options

Summary: Fetch marketplace gift filter options

Allowed role/access: REGISTERED_USER or GUEST_USER

Notes: Access: REGISTERED_USER or GUEST_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest response behavior includes isWishlisted=false, requiresAuthForWishlist=true, requiresAuthForCart=true, requiresAuthForCheckout=true, defaultAddress=null, upcomingReminder=null, and mode="GUEST" where applicable. REGISTERED_USER or GUEST_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/gifts

Summary: List customer marketplace gifts

Allowed role/access: REGISTERED_USER or GUEST_USER

Notes: Access: REGISTERED_USER or GUEST_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest response behavior includes isWishlisted=false, requiresAuthForWishlist=true, requiresAuthForCart=true, requiresAuthForCheckout=true, defaultAddress=null, upcomingReminder=null, and mode="GUEST" where applicable. REGISTERED_USER or GUEST_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest gift cards include isWishlisted=false, requiresAuthForWishlist=true, requiresAuthForCart=true, and requiresAuthForCheckout=true. Provider inventory does not require separate gift moderation approval.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- categoryId (query, optional, string)
- categorySlug (query, optional, string)
- providerId (query, optional, string)
- offerOnly (query, optional, boolean)
- minPrice (query, optional, number)
- maxPrice (query, optional, number)
- minRating (query, optional, number)
- brand (query, optional, string)
- deliveryOption (query, optional, string)
- sortBy (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "gift_id",
      "name": "Luxury Perfume",
      "price": 99.99,
      "currency": "PKR",
      "imageUrl": "https://cdn.yourdomain.com/gift-images/perfume.png",
      "rating": 4.8,
      "isWishlisted": false,
      "requiresAuthForWishlist": true,
      "requiresAuthForCart": true,
      "requiresAuthForCheckout": true,
      "shortDescription": "Premium fragrance gift.",
      "reviewCount": 0,
      "stockQuantity": 50,
      "category": {
        "id": "gift_category_id",
        "name": "Perfumes",
        "slug": "perfumes"
      },
      "provider": {
        "id": "provider_id",
        "businessName": "Dcodax Gifts"
      },
      "deliveryOptions": [
        "SAME_DAY",
        "NEXT_DAY",
        "SCHEDULED"
      ],
      "activeOffer": null
    }
  ]
}
```

```

    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Customer gifts fetched successfully"
}

```

GET /api/v1/customer/gifts/{id}

Summary: Fetch customer-safe gift details

Allowed role/access: REGISTERED_USER or GUEST_USER

Notes: Access: REGISTERED_USER or GUEST_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest response behavior includes isWishlisted=false, requiresAuthForWishlist=true, requiresAuthForCart=true, requiresAuthForCheckout=true, defaultAddress=null, upcomingReminder=null, and mode="GUEST" where applicable. REGISTERED_USER or GUEST_USER. Registered users receive personalized marketplace fields such as wishlist state, default address, and upcoming reminders where applicable. Guest users receive guest-safe marketplace data only. Guest users cannot access wishlist, cart, checkout, addresses, contacts, events, orders, payments, wallet, recurring payments, chats, reviews, or referrals. Guest gift details include isWishlisted=false and auth-required flags; SKU/exact stock stay hidden unless enabled in guest settings.

Parameters:

- id (path, required, string)

Response body:

```

{
  "success": true,
  "data": {
    "id": "gift_id",
    "name": "Luxury Perfume",
    "description": "Long-lasting premium fragrance.",
    "shortDescription": "Premium fragrance gift.",
    "price": 99.99,
    "originalPrice": 99.99,
    "currency": "PKR",
    "imageUrls": [
      "https://cdn.yourdomain.com/gift-images/perfume.png"
    ],
    "rating": 4.8,
    "reviewCount": 0,
    "stockQuantity": 50,
    "isWishlisted": false,
    "requiresAuthForWishlist": true,
    "requiresAuthForCart": true,
    "requiresAuthForCheckout": true,
    "badges": [
      "AUTHENTIC"
    ],
    "category": {
      "id": "gift_category_id",
      "name": "Perfumes",
      "slug": "perfumes"
    },
    "provider": {
      "id": "provider_id",
      "businessName": "Dcodax Gifts",
      "rating": 4.8,

```

```

    "reviewCount": 0,
    "fulfillmentMethods": [
      "DELIVERY"
    ]
  },
  "variants": [
    {
      "id": "variant_id",
      "name": "50ml",
      "price": 129.99,
      "originalPrice": 159.99,
      "stockQuantity": 20,
      "sku": "PERFUME-50ML",
      "isPopular": true,
      "isDefault": true
    }
  ],
  "deliveryOptions": [
    "SAME_DAY",
    "NEXT_DAY",
    "SCHEDULED"
  ],
  "activeOffer": null
},
"message": "Gift details fetched successfully"
}

```

05 Customer - Wishlist

GET /api/v1/customer/wishlist

Summary: List wishlist gifts

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Returns customer-visible gifts: active, available, in stock, not deleted, and owned by an approved active provider. Admin-created gifts may additionally require isPublished=true.

Response body:

```

{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}

```

POST /api/v1/customer/wishlist/{giftId}

Summary: Add gift to wishlist

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Gift must be customer-visible: active, available, in stock, not deleted, and owned by an approved active provider. Admin-created gifts may additionally require isPublished=true. Duplicate wishlist entries are ignored.

Parameters:

- giftId (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/customer/wishlist/{giftId}

Summary: Remove gift from wishlist

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Removes only the current customer wishlist row.

Parameters:

- giftId (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

05 Customer - Addresses

GET /api/v1/customer/addresses

Summary: List customer addresses

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Customers can only view their own non-deleted addresses.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/customer/addresses

Summary: Create customer address

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Maintains one default address per customer.

Request payload(s):

payload

```
{
  "label": "Home",
  "fullName": "Sarah Khan",
  "phone": "+923001234567",
  "line1": "House 12, Street 4, F-8/2",
  "line2": "Near Centaurus Mall",
  "city": "Islamabad",
  "state": "Islamabad Capital Territory",
  "country": "Pakistan",
  "postalCode": "44000",
  "latitude": 33.6844,
  "longitude": 73.0479,
  "deliveryInstructions": "Leave at reception.",
  "isDefault": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/addresses/{id}**Summary:** Fetch customer address**Allowed role/access:** REGISTERED_USER**Notes:** Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Address must belong to the current customer.**Parameters:**

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/customer/addresses/{id}**Summary:** Update customer address**Allowed role/access:** REGISTERED_USER**Notes:** Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Maintains one default address per customer.**Parameters:**

- id (path, required, string)

Request payload(s):

payload

```
{
  "label": "Home",
```



```
"fullName": "Sarah Khan",
"phone": "+923001234567",
"line1": "House 12, Street 4, F-8/2",
"line2": "Near Centaurus Mall",
"city": "Islamabad",
"state": "Islamabad Capital Territory",
"country": "Pakistan",
"postalCode": "44000",
"latitude": 33.6844,
"longitude": 73.0479,
"deliveryInstructions": "Leave at reception.",
"isDefault": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/customer/addresses/{id}

Summary: Delete customer address

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Permanently deletes the address and removes default status.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/customer/addresses/{id}/default

Summary: Set default customer address

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Clears default flag from all other customer addresses.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

05 Customer - Contacts

GET /api/v1/customer/contacts

Summary: List customer contacts

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Lists only contacts owned by the authenticated customer.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string) Searches name, phone, email, and relationship.
- relationship (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/customer/contacts

Summary: Create customer contact

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Creates a personal gift contact owned by the authenticated customer. Requires at least one contact method: phone, email, or address.

Request payload(s):

create

```
{
  "name": "Mary Wilson",
  "relationship": "Mother",
  "phone": "+1234567890",
  "email": "mary@example.com",
  "address": "387 Merdina",
  "likes": "Glasses, makeup, dresses",
  "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/mary.png",
  "birthday": "1990-05-12",
  "notes": "Prefers elegant gifts."
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/contacts/{id}

Summary: Fetch customer contact

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Contact must belong to the authenticated customer.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/customer/contacts/{id}

Summary: Update customer contact

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Updates only contacts owned by the authenticated customer.

Parameters:

- id (path, required, string)

Request payload(s):

update

```
{
  "name": "Mary Wilson",
  "relationship": "Mother",
  "phone": "+1234567890",
  "email": "mary@example.com",
  "address": "387 Merdina",
  "likes": "Glasses, makeup, dresses",
  "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/mary.png",
  "birthday": "1990-05-12",
  "notes": "Prefers elegant gifts."
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/customer/contacts/{id}

Summary: Delete customer contact

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Permanently deletes only contacts owned by the authenticated customer.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

05 Customer - Events

GET /api/v1/customer/events

Summary: List customer events

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Lists only events owned by the authenticated customer.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- eventType (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- recipientId (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/customer/events

Summary: Create customer event

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. recipientId must belong to the authenticated customer.

Request payload(s):

payload

```
{
  "eventType": "BIRTHDAY",
  "title": "Sarah's Birthday",
  "recipientId": "cmf0contactmary001",
  "eventDate": "2026-01-31T00:00:00.000Z",
  "reminderTiming": "ON_THE_DAY",
  "reminderFrequency": "ONE_TIME",
  "customAlertTime": "09:00",
  "channels": [
    "EMAIL",
    "SMS"
  ],
  "notes": "Send a birthday gift.",
  "isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/events/calendar

Summary: Fetch monthly calendar events

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Returns marked dates and own events.

Parameters:

- month (query, required, number)
- year (query, required, number)
- eventType (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/events/upcoming

Summary: Fetch upcoming customer events

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Defaults to 10 events within 30 days.

Parameters:

- limit (query, optional, number)
- daysAhead (query, optional, number)
- eventType (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/events/{id}/reminder-settings

Summary: Fetch event reminder settings

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Event must belong to the authenticated customer.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/customer/events/{id}/reminder-settings

Summary: Update event reminder settings

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Event must belong to the authenticated customer.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "reminderFrequency": "YEARLY",
  "reminderTiming": "ONE_DAY_BEFORE",
  "customAlertTime": "09:00",
  "channels": {
    "push": true,
    "email": true,
    "sms": false
  }
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/events/{id}

Summary: Fetch customer event details

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Event must belong to the authenticated customer.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/customer/events/{id}

Summary: Update customer event

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Event and recipient contact must belong to the authenticated customer.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "eventType": "ANNIVERSARY",
  "title": "Sarah's Anniversary",
  "recipientId": "cmf0contactmary001",
  "eventDate": "2026-01-31T00:00:00.000Z",
  "reminderTiming": "THREE_DAYS_BEFORE",
  "reminderFrequency": "YEARLY",
  "customAlertTime": "09:00",
  "channels": [
    "PUSH",
    "EMAIL"
  ],
  "notes": "Send flowers.",
  "isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/customer/events/{id}

Summary: Delete customer event

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Permanently deletes only own event and cancels pending reminder jobs.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

05 Customer - Cart

GET /api/v1/customer/cart

Summary: Fetch active cart

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Totals are backend calculated from price snapshots.

Response body:

```
{
  "success": true,
  "data": {
    "id": "cart_id",
    "status": "ACTIVE",
    "items": [
      {
        "id": "cart_item_id",
        "giftId": "gift_id",
        "variantId": "variant_id",
        "name": "Luxury Perfume",
        "variantName": "50ml",
        "quantity": 1,
        "unitPrice": 129.99,
        "discountAmount": 20,
        "finalUnitPrice": 109.99,
        "lineTotal": 109.99,
        "imageUrl": "https://cdn.yourdomain.com/gift-images/perfume.png",
        "deliveryOption": "SAME_DAY",
        "recipient": {
          "contactId": "contact_id",
          "name": "Sarah Khan",
          "phone": "+923001234567",
          "addressId": "address_id"
        },
        "giftMessage": "Hope you love this special surprise!",
        "messageMediaUrls": [
          "https://cdn.yourdomain.com/gift-message-media/photo.png"
        ],
        "scheduledDeliveryAt": "2026-12-24T10:00:00.000Z"
      }
    ],
    "summary": {
```



```
    "subtotal": 129.99,  
    "discountTotal": 20,  
    "deliveryFee": 0,  
    "tax": 0,  
    "total": 109.99,  
    "currency": "PKR"  
  }  
},  
"message": "Cart fetched successfully"  
}
```

DELETE /api/v1/customer/cart

Summary: Clear active cart

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Removes all items from active cart.

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{  
  "success": true,  
  "data": "<response returned by endpoint>",  
  "message": "Request completed successfully."  
}
```

POST /api/v1/customer/cart/items

Summary: Add item to cart

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Backend calculates unit price, active offer discount, final price, subtotal, delivery fee placeholder, and total.

Request payload(s):

sendGift

```
{  
  "giftId": "cmf0giftroses001",  
  "variantId": "cmf0variant50ml001",  
  "quantity": 1,  
  "deliveryOption": "SAME_DAY",  
  "recipientContactId": "cmf0contactmary001",  
  "recipientName": "Sarah Khan",  
  "recipientPhone": "+923001234567",  
  "recipientAddressId": "cmf0addresshome001",  
  "eventId": "cmf0eventbirthday001",  
  "giftMessage": "Hope you love this special surprise!",  
  "messageMediaUrls": [  
    "https://cdn.yourdomain.com/gift-message-media/photo.png"  
  ],  
  "scheduledDeliveryAt": "2026-12-24T10:00:00.000Z"  
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/customer/cart/items/{id}

Summary: Update cart item

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Validates ownership through the active customer cart.

Parameters:

- id (path, required, string)

Request payload(s):

updateSelection

```
{
  "variantId": "cmf0variant100ml001",
  "quantity": 2,
  "deliveryOption": "SCHEDULED",
  "recipientContactId": "cmf0contactmary001",
  "recipientName": "Sarah Khan",
  "recipientPhone": "+923001234567",
  "recipientAddressId": "cmf0addresshome001",
  "eventId": "cmf0eventbirthday001",
  "giftMessage": "Updated gift note.",
  "messageMediaUrls": [
    "https://cdn.yourdomain.com/gift-message-media/video.mp4"
  ],
  "scheduledDeliveryAt": "2026-12-25T10:00:00.000Z"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/customer/cart/items/{id}

Summary: Delete cart item

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Deletes only items in the current customer active cart.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

05 Customer - Orders

GET /api/v1/customer/orders

Summary: List customer orders

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Returns orders owned by the current customer.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- type (query, optional, string)
- status (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/customer/orders

Summary: Create order from active cart

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Prices are backend-calculated from cart/payment snapshots. STRIPE_CARD requires a successful owned paymentId; COD stays pending; PLACEHOLDER is for development only. Multiple providers are split into provider sub-orders.

Request payload(s):

stripeCard

```
{
  "cartId": "cart_id",
  "paymentId": "payment_id",
  "deliveryAddressId": "address_id",
  "paymentMethod": "STRIPE_CARD"
}
```

cod

```
{
  "cartId": "cart_id",
  "deliveryAddressId": "address_id",
  "paymentMethod": "COD"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/orders/{id}**Summary:** Fetch customer order**Allowed role/access:** REGISTERED_USER**Notes:** Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Order must belong to the current customer.**Parameters:**

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": {
    "id": "order_id",
    "orderNumber": "ORD-1760000000000",
    "status": "CONFIRMED",
    "paymentStatus": "SUCCEEDED",
    "paymentMethod": "STRIPE_CARD",
    "recipient": {
      "name": "Sarah Khan",
      "email": null,
      "phone": "+923001234567",
      "avatarUrl": null
    },
    "deliveryDate": "2026-12-24T10:00:00.000Z",
    "occasion": null,
    "giftMessage": "Hope you love this special surprise!",
    "items": [
      {
        "giftId": "gift_id",
        "name": "Luxury Perfume",
        "variantName": "50ml",
        "quantity": 1,
        "imageUrl": "https://cdn.yourdomain.com/gift-images/perfume.png",
        "total": 109.99
      }
    ],
    "summary": {
      "subtotal": 129.99,
      "discountTotal": 20,
      "deliveryFee": 0,
      "tax": 0,
      "total": 109.99,
      "currency": "PKR"
    }
  },
  "message": "Order fetched successfully."
}
```

05 Customer - Provider Chat

GET /api/v1/customer/chats

Summary: List customer provider chats

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Uses shared ChatThread/ChatMessage records with provider buyer chat. Customer sees only own order threads.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- unreadOnly (query, optional, boolean)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/chats/quick-replies

Summary: Fetch provider chat quick replies

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Declared before /customer/chats/:threadId.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/chats/{threadId}

Summary: Fetch customer chat messages

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Thread must belong to the current customer.

Parameters:

- threadId (path, required, string)
- page (query, optional, number)
- limit (query, optional, number)
- before (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/customer/chats/{threadId}/messages

Summary: Send message to provider

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Customer can send only in own order thread. Creates provider notification and updates read receipts.

Parameters:

- threadId (path, required, string)

Request payload(s):

text

```
{
  "messageType": "TEXT",
  "body": "Can you confirm delivery time?",
  "attachmentUrls": []
}
```

image

```
{
  "messageType": "IMAGE",
  "attachmentUrls": [
    "https://cdn.yourdomain.com/chat-attachments/package.png"
  ]
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/customer/chats/{threadId}/read

Summary: Mark provider messages read

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Marks provider messages as read for the customer in the owned thread.

Parameters:

- threadId (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/orders/{id}/chat

Summary: Get or optionally create order chat

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Order must belong to the logged-in customer and have an attached provider order.

Parameters:

- id (path, required, string)
- createIfMissing (query, optional, boolean)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/customer/orders/{id}/chat

Summary: Create order chat

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Reuses existing ChatThread if already created for the provider order.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

05 Customer - Reviews

POST /api/v1/customer/orders/{id}/reviews

Summary: Submit provider review for an order

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Uses shared Review records consumed by provider reviews and admin review management.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "providerId": "provider_id",
```

```
"rating": 5,
"comment": "Great service and fast delivery. The package arrived in perfect condition."
}
```

Response body:

```
{
  "success": true,
  "data": {
    "id": "review_id",
    "rating": 5,
    "comment": "Great service and fast delivery.",
    "status": "PUBLISHED",
    "providerId": "provider_id",
    "orderId": "order_id",
    "createdAt": "2026-05-11T10:00:00.000Z"
  },
  "message": "Review submitted successfully."
}
```

GET /api/v1/customer/reviews

Summary: List own provider reviews

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Customer sees only their own non-deleted reviews.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- rating (query, optional, number)
- providerId (query, optional, string)
- status (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/reviews/{id}

Summary: Fetch Customer Reviews details

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```


PATCH /api/v1/customer/reviews/{id}

Summary: Update own review

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Cannot update deleted/removed reviews; updated content is re-run through deterministic moderation.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "rating": 4,
  "comment": "Updated review text."
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/customer/reviews/{id}

Summary: Delete own review

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Permanently deletes the customer review record.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

05 Customer - Provider Reports

GET /api/v1/customer/provider-report-reasons

Summary: Fetch provider report reasons

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Declared before /customer/provider-reports/:id.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/customer/providers/{providerId}/reports**Summary:** Report provider**Allowed role/access:** REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Customer must have an order, chat, or review relationship with provider. Duplicate active provider/order/reason reports are blocked.

Parameters:

- providerId (path, required, string)

Request payload(s):

payload

```
{
  "reason": "POOR_SERVICE_QUALITY",
  "details": "The provider did not respond and the order was delayed.",
  "orderId": "order_id",
  "evidenceUrls": []
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/provider-reports**Summary:** List Customer Provider Reports**Allowed role/access:** REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/provider-reports/{id}

Summary: Fetch Customer Provider Reports details

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

05 Customer - Recurring Payments

GET /api/v1/customer/recurring-payments

Summary: List own recurring payments

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Returns recurring money/gift payment subscriptions owned by the logged-in customer.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- frequency (query, optional, string)
- recipientContactId (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "recurring_payment_id",
      "title": "Sarah's Birthday",
      "recipient": {
        "id": "contact_id",
        "name": "Sarah Johnson",
        "email": "sarah.j@example.com",
        "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/sarah.png"
      },
      "amount": 50,
      "currency": "PKR",
      "frequency": "MONTHLY",
      "nextBillingAt": "2026-03-15T09:00:00.000Z",
      "status": "ACTIVE",
      "message": "Monthly flowers",
      "createdAt": "2026-05-09T10:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
  }
}
```

```
    "total": 1,  
    "totalPages": 1  
  },  
  "message": "Recurring payments fetched successfully."  
}
```

POST /api/v1/customer/recurring-payments

Summary: Create recurring payment

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Recipient contact and saved Stripe payment method must both belong to the logged-in customer. Stripe card recurring payments require a saved payment method.

Request payload(s):

weeklyStripe

```
{  
  "amount": 100,  
  "currency": "PKR",  
  "frequency": "WEEKLY",  
  "schedule": {  
    "dayOfWeek": "MONDAY",  
    "dayOfMonth": null,  
    "monthOfYear": null,  
    "time": "09:00",  
    "timezone": "Asia/Karachi"  
  },  
  "recipientContactId": "contact_id",  
  "message": "Hope you love this special surprise!",  
  "messageMediaUrls": [  
    "https://cdn.yourdomain.com/gift-message-media/photo.png"  
  ],  
  "paymentMethod": "STRIPE_CARD",  
  "stripePaymentMethodId": "pm_xxx",  
  "startDate": "2026-05-10T00:00:00.000Z",  
  "endDate": null,  
  "autoSend": true  
}
```

Response body:

```
{  
  "success": true,  
  "data": {  
    "id": "recurring_payment_id",  
    "amount": 100,  
    "currency": "PKR",  
    "frequency": "WEEKLY",  
    "nextBillingAt": "2026-05-12T09:00:00.000Z",  
    "status": "ACTIVE"  
  },  
  "message": "Recurring payment created successfully."  
}
```

GET /api/v1/customer/recurring-payments/summary

Summary: Fetch recurring payment summary counts

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. Must stay before /customer/recurring-payments/:id route.

Response body:

```
{
  "success": true,
  "data": {
    "total": 5,
    "active": 3,
    "paused": 1,
    "cancelled": 1,
    "failed": 0
  },
  "message": "Recurring payment summary fetched successfully."
}
```

GET /api/v1/customer/recurring-payments/{id}

Summary: Fetch own recurring payment details

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Customer cannot access another user's recurring payment.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": {
    "id": "recurring_payment_id",
    "title": "Monthly Flowers",
    "recipient": {
      "id": "contact_id",
      "name": "Sarah Johnson",
      "email": "sarah.j@example.com",
      "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/sarah.png"
    },
    "amount": 50,
    "currency": "PKR",
    "frequency": "MONTHLY",
    "nextBillingAt": "2026-03-15T09:00:00.000Z",
    "status": "ACTIVE",
    "message": "Fresh seasonal bouquet delivered to her doorstep every month",
    "messageMediaUrls": [],
    "paymentMethod": {
      "type": "STRIPE_CARD",
      "brand": "visa",
      "last4": "4242",
      "expiryMonth": 12,
      "expiryYear": 2026
    },
    "schedule": {
      "frequency": "MONTHLY",
      "dayOfMonth": 15,
      "time": "09:00",
      "timezone": "Asia/Karachi"
    },
    "createdAt": "2026-05-09T10:00:00.000Z"
  },
  "message": "Recurring payment fetched successfully."
}
```

PATCH /api/v1/customer/recurring-payments/{id}

Summary: Update own recurring payment

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. Cannot edit CANCELLED recurring payments. Changes apply from the next billing cycle and nextBillingAt is recalculated.

Parameters:

- id (path, required, string)

Request payload(s):

monthly

```
{
  "amount": 50,
  "frequency": "MONTHLY",
  "schedule": {
    "dayOfMonth": 15,
    "time": "09:00",
    "timezone": "Asia/Karachi"
  },
  "message": "Fresh flowers every month.",
  "messageMediaUrls": [],
  "stripePaymentMethodId": "pm_xxx"
}
```

Response body:

```
{
  "success": true,
  "data": {
    "id": "recurring_payment_id",
    "status": "ACTIVE",
    "nextBillingAt": "2026-03-15T09:00:00.000Z"
  },
  "message": "Recurring payment updated successfully. Changes will apply from the next billing cycle."
}
```

POST /api/v1/customer/recurring-payments/{id}/pause

Summary: Pause own active recurring payment

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account.

Parameters:

- id (path, required, string)

Request payload(s):

pause

```
{
  "reason": "User paused recurring payment."
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```

```
"message": "Request completed successfully."
}
```

POST /api/v1/customer/recurring-payments/{id}/resume

Summary: Resume own paused recurring payment

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/customer/recurring-payments/{id}/cancel

Summary: Cancel own recurring payment

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. IMMEDIATELY cancels future processing. AFTER_CURRENT_BILLING_CYCLE sets cancelAtPeriodEnd and cancelAt.

Parameters:

- id (path, required, string)

Request payload(s):

immediately

```
{
  "cancelMode": "IMMEDIATELY",
  "reason": "No longer needed."
}
```

periodEnd

```
{
  "cancelMode": "AFTER_CURRENT_BILLING_CYCLE",
  "reason": "Finish current cycle."
}
```

Response body:

```
{
  "success": true,
  "data": {
    "id": "recurring_payment_id",
    "status": "CANCELLED",
    "cancelMode": "IMMEDIATELY"
  },
}
```

```
"message": "Recurring payment cancelled successfully."
}
```

GET /api/v1/customer/recurring-payments/{id}/history

Summary: List own recurring payment billing history

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account.

Parameters:

- id (path, required, string)
- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "history_id",
      "paymentId": "payment_id",
      "amount": 50,
      "currency": "PKR",
      "status": "SUCCESS",
      "billingDate": "2026-02-15T09:00:00.000Z",
      "transactionId": "GFT-8829-XPL",
      "failureReason": null
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Recurring payment history fetched successfully."
}
```

05 Customer - Transactions

GET /api/v1/customer/transactions

Summary: List own customer transactions

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Normalizes backend Payment, Order, MoneyGift, and RecurringPayment occurrence records owned by the logged-in customer.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- type (query, optional, string)
- status (query, optional, string)
- paymentMethod (query, optional, string)

- minAmount (query, optional, number)
- maxAmount (query, optional, number)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "payment_id",
      "transactionId": "TXN-2026-001234",
      "title": "Monthly Flowers",
      "description": "Recurring payment",
      "recipient": {
        "id": "contact_id",
        "name": "Sarah Johnson",
        "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/sarah.png"
      },
      "amount": 50,
      "currency": "PKR",
      "type": "RECURRING_PAYMENT",
      "status": "SUCCESS",
      "paymentMethod": "STRIPE_CARD",
      "createdAt": "2026-03-01T14:34:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Transactions fetched successfully."
}
```

GET /api/v1/customer/transactions/summary

Summary: Fetch own transaction summary

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. Defaults to current month when no date range is provided. Uses backend-calculated payment records only.

Parameters:

- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```
{
  "success": true,
  "data": {
    "totalSpentThisMonth": 255,
    "currency": "PKR",
    "successfulCount": 9,
    "failedCount": 1,
    "pendingCount": 0,
    "refundedCount": 0
  },
  "message": "Transaction summary fetched successfully."
}
```

GET /api/v1/customer/transactions/export

Summary: Export own transactions

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. CSV is supported and returned as a file. Export is scoped to the logged-in customer only.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)
- type (query, optional, string)
- status (query, optional, string)
- paymentMethod (query, optional, string)
- minAmount (query, optional, number)
- maxAmount (query, optional, number)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)
- format (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/transactions/{id}

Summary: Fetch own transaction details

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. Includes order, money gift, recurring payment, and payment gateway references when available. Billing address returns null until available.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": {
    "id": "payment_id",
    "transactionId": "TXN-2026-001234-ABC-XYZ",
    "status": "SUCCESS",
    "amount": 50,
    "currency": "PKR",
    "createdAt": "2026-03-01T14:34:00.000Z",
    "type": "RECURRING_PAYMENT",
    "giftInformation": {
      "giftName": "Monthly Flowers Subscription",
      "deliveryType": "Money",
      "recipient": {
        "id": "contact_id",
        "name": "Sarah Johnson",
        "avatarUrl": "https://cdn.yourdomain.com/customer-contact-avatars/sarah.png"
      },
      "orderReference": null,
      "recurringPaymentId": "recurring_payment_id"
    },
    "paymentInformation": {
      "paymentMethod": "Stripe card",
      "gatewayReference": "pi_3MmlLrLkdIwHu7ix0fhBHWqt",
      "billingAddress": null
    }
  },
  "message": "Transaction details fetched successfully."
}
```

GET /api/v1/customer/transactions/{id}/receipt

Summary: Download own transaction receipt

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. Receipt is generated only for the transaction owner and never exposes Stripe secret data.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

05 Customer - Referrals & Rewards

GET /api/v1/customer/referrals/summary

Summary: Fetch own referral reward summary

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Customers can view only their own referral progress and ledger-derived balances.

Response body:

```
{
  "success": true,
  "data": {
    "invitedFriends": 3,
    "successfulReferrals": 2,
    "rewardsEarned": 20,
    "availableCredit": 20,
    "currency": "USD",
    "progress": {
      "totalInvited": 3,
      "joined": 2,
      "pending": 1
    }
  },
  "message": "Referral summary fetched successfully."
}
```

GET /api/v1/customer/referrals/link

Summary: Fetch own referral link

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. Generates a unique customer referral code when missing. The link never exposes internal user IDs.

Response body:

```
{
  "success": true,
  "data": {
    "referralCode": "SARAH-M",
    "referralLink": "https://giftapp.com/share/sarah-m",
    "shareTitle": "Invite Friends, Earn Rewards",
    "shareMessage": "Join Gift App with my referral link and we both earn rewards after your first gift purchase.",
    "rewardText": "Get $10 credit after your friend's first gift purchase."
  },
  "message": "Referral link fetched successfully."
}
```

GET /api/v1/customer/referrals/history

Summary: List own referral history

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. History is scoped to referrals created by the logged-in customer.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/customer/referrals/redeem

Summary: Redeem own available reward credit

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. Creates a REDEEMED reward ledger entry. Redemption cannot exceed ledger-derived available credit.

Request payload(s):

payload

```
{
  "amount": 20,
  "redeemTo": "WALLET"
}
```

Response body:

```
{
  "success": true,
  "data": {
    "redeemedAmount": 20,
    "currency": "USD",
    "walletBalance": 20
  },
  "message": "Reward redeemed successfully."
}
```

GET /api/v1/customer/rewards/balance

Summary: Fetch own reward balance

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. Balance is calculated from RewardLedger entries, not a mutable user balance field.

Response body:

```
{
  "success": true,
  "data": {
    "availableCredit": 20,
    "lifetimeEarned": 20,
    "lifetimeRedeemed": 0,
    "currency": "USD"
  },
  "message": "Reward balance fetched successfully."
}
```

GET /api/v1/customer/rewards/ledger

Summary: List own reward ledger

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Returns ledger entries owned by the logged-in customer.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- type (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/referrals/terms

Summary: Fetch referral terms

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. Returns config/env based customer referral terms for the mobile app.

Response body:

```
{
  "success": true,
  "data": {
    "title": "Referral Terms",
    "rewardAmount": 10,
    "currency": "USD",
    "qualificationRule": "Reward is credited after your referred friend completes their first gift purchase.",
    "terms": [
      "Referral rewards are available only for registered users.",
      "Reward is credited after the referred user's first successful purchase.",
      "Cancelled or refunded orders may revoke reward eligibility.",
      "Referral abuse may result in reward cancellation."
    ]
  },
  "message": "Referral terms fetched successfully."
}
```

05 Customer - Subscriptions

GET /api/v1/customer/subscription/plans

Summary: List public active subscription plans

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Uses admin-created active/public Subscription Plans. Customer cannot create/update/delete plans.

Parameters:

- billingCycle (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
```

```
{
  "id": "plan_premium",
  "name": "Premium",
  "monthlyPrice": 4.99,
  "yearlyPrice": 39.99,
  "currency": "USD",
  "isPopular": true,
  "yearlySavingsPercent": 30,
  "features": [
    {
      "key": "ai_gift_recommendations",
      "label": "Ai Gift Recommendations",
      "enabled": true
    }
  ],
  "limits": {
    "unlimitedCredits": true
  }
},
{
  "message": "Subscription plans fetched successfully."
}
```

GET /api/v1/customer/subscription/current

Summary: Fetch own current subscription

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Returns FREE state when no active premium subscription exists.

Response body:

```
{
  "success": true,
  "data": {
    "tier": "PREMIUM",
    "subscription": {
      "id": "sub_id",
      "planId": "plan_premium",
      "planName": "Premium",
      "billingCycle": "MONTHLY",
      "status": "ACTIVE",
      "isPremium": true,
      "cancelAtPeriodEnd": false,
      "currentPeriodStart": "2026-04-01T00:00:00.000Z",
      "currentPeriodEnd": "2026-05-01T00:00:00.000Z"
    }
  },
  "message": "Current subscription fetched successfully."
}
```

POST /api/v1/customer/subscription/checkout

Summary: Create Stripe subscription checkout

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Backend calculates price from admin-created SubscriptionPlan and optional coupon. Uses Stripe subscription flow with payment_behavior=default_incomplete.

Request payload(s):

payload

```
{
  "planId": "plan_premium",
  "billingCycle": "MONTHLY",
  "paymentMethodId": "pm_123",
  "couponCode": "SUMMER25"
}
```

Response body:

```
{
  "success": true,
  "data": {
    "subscriptionId": "sub_local_id",
    "stripeSubscriptionId": "sub_stripe_123",
    "clientSecret": "seti_client_secret",
    "status": "INCOMPLETE",
    "amountDue": 4.99,
    "currency": "USD"
  },
  "message": "Subscription checkout created successfully."
}
```

POST /api/v1/customer/subscription/confirm

Summary: Confirm Stripe subscription activation

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Fetches Stripe subscription server-side and activates local entitlement when active/trialing.

Request payload(s):

payload

```
{
  "customerSubscriptionId": "<string>",
  "stripeSubscriptionId": "<string>"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/customer/subscription/cancel

Summary: Cancel own subscription

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Supports immediate cancellation or cancel_at_period_end in Stripe. Does not delete local subscription record.

Request payload(s):

payload

```
{
  "cancelMode": "IMMEDIATELY",
  "reason": "<string>"
}
```


Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/customer/subscription/reactivate**Summary:** Reactivate scheduled cancellation**Allowed role/access:** REGISTERED_USER**Notes:** Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Works only when own subscription has cancelAtPeriodEnd=true.**Request payload(s):**

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/subscription/invoices**Summary:** List own subscription invoices**Allowed role/access:** REGISTERED_USER**Notes:** Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Returns invoices synced from Stripe subscription webhooks.**Parameters:**

- page (query, optional, number)
- limit (query, optional, number)
- status (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "invoice_id",
      "stripeInvoiceId": "in_123",
      "amountDue": 4.99,
      "amountPaid": 4.99,
      "currency": "USD",
      "status": "PAID",
      "invoicePdfUrl": "https://cdn.yourdomain.com/invoices/invoice.pdf",
      "periodStart": "2026-04-01T00:00:00.000Z",
      "periodEnd": "2026-05-01T00:00:00.000Z",
      "createdAt": "2026-04-01T00:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
  }
}
```

```
"total": 1,  
  "totalPages": 1  
},  
"message": "Subscription invoices fetched successfully."  
}
```

GET /api/v1/customer/subscription/invoices/{id}

Summary: Fetch own subscription invoice details

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only.

Parameters:

- id (path, required, string)

Response body:

```
{  
  "success": true,  
  "data": "<response returned by endpoint>",  
  "message": "Request completed successfully."  
}
```

POST /api/v1/customer/subscription/apply-coupon

Summary: Preview subscription coupon

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Validates coupon against active coupon rules and plan restrictions; frontend discount amounts are ignored.

Request payload(s):

payload

```
{  
  "planId": "<string>",  
  "billingCycle": "MONTHLY",  
  "couponCode": "<string>"  
}
```

Response body:

```
{  
  "success": true,  
  "data": "<response returned by endpoint>",  
  "message": "Request completed successfully."  
}
```

05 Customer - Wallet

GET /api/v1/customer/wallet

Summary: Fetch own wallet

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Wallet is lazily created and balances are backed by wallet ledger entries.

Response body:

```
{
  "success": true,
  "data": {
    "totalBalance": 1240.5,
    "giftCredits": 350,
    "cashBalance": 890.5,
    "currency": "USD",
    "defaultPaymentMethod": {
      "id": "pm_xxx",
      "type": "CARD",
      "brand": "visa",
      "last4": "4242",
      "expiryMonth": 9,
      "expiryYear": 2025,
      "isDefault": true
    },
    "defaultBankAccount": {
      "id": "bank_account_id",
      "bankName": "Chase Bank",
      "last4": "8821",
      "isDefault": false
    }
  },
  "message": "Wallet fetched successfully."
}
```

POST /api/v1/customer/wallet/add-funds

Summary: Create wallet top-up payment

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. Uses Stripe PaymentIntent. Wallet is credited only after successful server-side confirmation/webhook.

Request payload(s):

payload

```
{
  "amount": 100,
  "currency": "USD",
  "paymentMethod": "STRIPE_CARD",
  "stripePaymentMethodId": "pm_xxx"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/wallet/history

Summary: List own wallet history

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. Positive amounts are credits, negative amounts are debits. Results are scoped to the logged-in customer.

Parameters:

- page (query, optional, number)

- limit (query, optional, number)
- type (query, optional, string)
- status (query, optional, string)
- fromDate (query, optional, string)
- toDate (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

05 Customer - Payment Methods

GET /api/v1/customer/bank-accounts

Summary: List own bank accounts

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account.

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "bank_account_id",
      "accountHolderName": "John Smith",
      "bankName": "Chase Bank",
      "last4": "8821",
      "maskedAccount": "**** 8821",
      "isDefault": false
    }
  ],
  "message": "Bank accounts fetched successfully."
}
```

POST /api/v1/customer/bank-accounts

Summary: Link placeholder bank account

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. Stores only masked display data. Full IBAN/account number is never returned.

Request payload(s):

payload

```
{
  "accountHolderName": "John Smith",
  "bankName": "Chase Bank",
  "ibanOrAccountNumber": "1234567890",
  "isDefault": false
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/customer/bank-accounts/{id}/default

Summary: Set own default bank account

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/customer/bank-accounts/{id}

Summary: Delete own bank account

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/payment-methods

Summary: List supported customer payment methods

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account.

Response body:

```
{
  "success": true,
  "data": [
    {
      "key": "STRIPE_CARD",
      "label": "Credit/Debit Card",
      "enabled": true
    },
    {
      "key": "BANK_TRANSFER",
      "label": "Bank Payment",
      "enabled": true
    },
    {
      "key": "E_WALLET",
      "label": "E-Wallet",
      "enabled": false
    }
  ],
  "message": "Payment methods fetched successfully."
}
```

POST /api/v1/customer/payment-methods/setup-intent

Summary: Create Stripe SetupIntent for saving card

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. Frontend confirms card with Stripe SDK. Backend never accepts raw card number or CVV.

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": {
    "setupIntentId": "seti_xxx",
    "clientSecret": "seti_xxx_secret_xxx",
    "publishableKey": "pk_test_xxx"
  },
  "message": "Setup intent created successfully."
}
```

GET /api/v1/customer/payment-methods/saved

Summary: List own saved payment methods

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. Returns masked Stripe card metadata only.

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "pm_xxx",
      "type": "CARD",
```

```
    "brand": "visa",
    "last4": "4242",
    "expiryMonth": 9,
    "expiryYear": 2025,
    "isDefault": true
  }
],
"message": "Saved payment methods fetched successfully."
}
```

PATCH /api/v1/customer/payment-methods/{id}/default

Summary: Set own default payment method

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/customer/payment-methods/{id}

Summary: Delete own saved payment method

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. Rejects deletion when the method is used by an active recurring payment.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

06 Payments

POST /api/v1/customer/payments/create-intent

Summary: Create payment intent from active cart

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Amount is calculated from backend cart totals; frontend amount is never accepted.

Request payload(s):

stripe

```
{
  "cartId": "cmf0cartactive001",
  "paymentMethod": "STRIPE_CARD"
}
```

cod

```
{
  "cartId": "cmf0cartactive001",
  "paymentMethod": "COD"
}
```

Response body:

```
{
  "success": true,
  "data": {
    "paymentId": "payment_id",
    "stripePaymentIntentId": "pi_xxx",
    "clientSecret": "pi_xxx_secret_xxx",
    "publishableKey": "pk_live_or_test",
    "amount": 10999,
    "currency": "PKR"
  },
  "message": "Payment intent created successfully."
}
```

POST /api/v1/customer/payments/confirm

Summary: Confirm Stripe payment

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. REGISTERED_USER only. Retrieves Stripe PaymentIntent server-side before updating local payment status.

Request payload(s):

payload

```
{
  "paymentId": "cmf0payment001",
  "stripePaymentIntentId": "pi_3Pxxxxxxxxxxxxxxxx"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```



```
"message": "Request completed successfully."
}
```

GET /api/v1/customer/payments/{id}

Summary: Fetch own payment details

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": {
    "paymentId": "payment_id",
    "provider": "STRIPE",
    "stripePaymentIntentId": "pi_xxx",
    "amount": 109.99,
    "currency": "PKR",
    "status": "SUCCEEDED",
    "paymentMethod": "STRIPE_CARD",
    "failureReason": null
  },
  "message": "Payment fetched successfully."
}
```

POST /api/v1/payments/stripe/webhook

Summary: Stripe webhook endpoint

Allowed role/access: PUBLIC

Notes: Access: PUBLIC. PUBLIC. Verifies Stripe-Signature using the configured webhook secret before processing events.

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/money-gifts

Summary: List own money gifts

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```

```
"message": "Request completed successfully."
}
```

POST /api/v1/customer/money-gifts

Summary: Send payment as gift

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account. Creates a customer-to-recipient money gift record and Stripe PaymentIntent for STRIPE_CARD.

Request payload(s):

create

```
{
  "amount": 100,
  "currency": "PKR",
  "recipientContactId": "cmf0contactmary001",
  "message": "Hope this helps. Enjoy your day!",
  "messageMediaUrls": [],
  "deliveryDate": "2026-12-24T00:00:00.000Z",
  "repeatAnnually": false,
  "paymentMethod": "STRIPE_CARD"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/customer/money-gifts/{id}

Summary: Fetch own money gift details

Allowed role/access: REGISTERED_USER

Notes: Access: REGISTERED_USER. REGISTERED_USER only. Endpoint is scoped to the authenticated customer account.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

06 Notifications

GET /api/v1/notifications

Summary: List notifications

Allowed role/access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER

Notes: Access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. Access is scoped to the authenticated account. JWT auth. Returns only notifications belonging to the

logged-in account. Supports All, Unread, Birthdays, Deliveries, and New Contacts filters. No group gift notifications are supported.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- filter (query, optional, string)
- type (query, optional, string)
- isRead (query, optional, boolean)
- groupByDate (query, optional, boolean)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "notification_id",
      "title": "Payment successful",
      "message": "Your payment was completed successfully.",
      "type": "PAYMENT_SUCCEEDED",
      "isRead": false,
      "metadata": {
        "paymentId": "payment_id"
      },
      "createdAt": "2026-05-09T10:00:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Notifications fetched successfully"
}
```

GET /api/v1/notifications/summary

Summary: Fetch notification summary

Allowed role/access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER

Notes: Access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. Access is scoped to the authenticated account. JWT auth. Counts only notifications belonging to the logged-in account.

Response body:

```
{
  "success": true,
  "data": {
    "total": 12,
    "unread": 3,
    "byType": {
      "PAYMENT_SUCCEEDED": 2,
      "RECURRING_PAYMENT_CHARGE_FAILED": 1,
      "BROADCAST": 9
    }
  },
  "message": "Notification summary fetched successfully"
}
```

GET /api/v1/notifications/preferences

Summary: Fetch notification preferences

Allowed role/access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER

Notes: Access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. Access is scoped to the authenticated account. JWT auth. Preferences belong only to the logged-in account.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/notifications/preferences

Summary: Update notification preferences

Allowed role/access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER

Notes: Access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. Access is scoped to the authenticated account. JWT auth. Push toggle does not delete device tokens. No group gift preference exists.

Request payload(s):

payload

```
{
  "pushEnabled": true,
  "emailEnabled": true,
  "smsEnabled": false,
  "dealUpdatesEnabled": true,
  "birthdayRemindersEnabled": true,
  "deliveryUpdatesEnabled": true,
  "newContactAlertsEnabled": true,
  "providerOrderAlerts": {
    "newOrders": true,
    "orderCancellations": true,
    "orderDelays": false
  },
  "providerAccountActivity": {
    "securityAlerts": true,
    "loginFromNewDevice": true
  },
  "providerMarketingUpdates": {
    "weeklyPerformanceSummary": true,
    "newFeatureAnnouncements": false,
    "promotionalOffers": false
  }
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/notifications/read-all

Summary: Mark all own notifications as read

Allowed role/access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER

Notes: Access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. Access is scoped to the authenticated account. JWT auth. Marks only notifications belonging to the logged-in account.

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/notifications/{id}/read

Summary: Mark notification as read

Allowed role/access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER

Notes: Access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. Access is scoped to the authenticated account. JWT auth. Notification must belong to the logged-in account.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/notifications/{id}/action

Summary: Process notification action

Allowed role/access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER

Notes: Access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. Access is scoped to the authenticated account. JWT auth. Supports SEND_GIFT, REMIND_ME_LATER, VIEW_ORDER, VIEW_CONTACT. Group gift actions are not supported.

Parameters:

- id (path, required, string)

Request payload(s):

sendGift

```
{
  "action": "SEND_GIFT"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/notifications/device-tokens**Summary:** Save device token**Allowed role/access:** SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER**Notes:** Access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. Access is scoped to the authenticated account. JWT auth. Token belongs only to logged-in account. Duplicate deviceId updates existing record.**Request payload(s):**

payload

```
{
  "token": "ExponentPushToken[xxxxxxxxxxxxxxxxxxxxxxxx]",
  "platform": "IOS",
  "deviceId": "ios-iphone-15-pro-device-id"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/notifications/device-tokens/{id}**Summary:** Disable device token**Allowed role/access:** SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER**Notes:** Access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. Access is scoped to the authenticated account. JWT auth. Users can disable only their own device tokens.**Parameters:**

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

06 Broadcast Notifications

GET /api/v1/broadcasts

Summary: List Broadcasts

Allowed role/access: SUPER_ADMIN or ADMIN with broadcasts.read

Notes: Access: SUPER_ADMIN or ADMIN with broadcasts.read. SUPER_ADMIN or ADMIN with broadcasts.read permission.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- channel (query, optional, string)
- priority (query, optional, string)
- createdFrom (query, optional, string)
- createdTo (query, optional, string)
- scheduledFrom (query, optional, string)
- scheduledTo (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/broadcasts

Summary: Create Broadcasts

Allowed role/access: SUPER_ADMIN or ADMIN with broadcasts.create

Notes: Access: SUPER_ADMIN or ADMIN with broadcasts.create. SUPER_ADMIN or ADMIN with broadcasts.create permission.

Request payload(s):

payload

```
{
  "title": "<string>",
  "message": "<string>",
  "imageUrl": "<string>",
  "ctaLabel": "<string>",
  "ctaUrl": "<string>",
  "channels": [
    "EMAIL"
  ],
  "priority": "LOW"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/broadcasts/{id}

Summary: Fetch Broadcasts details

Allowed role/access: SUPER_ADMIN or ADMIN with broadcasts.read

Notes: Access: SUPER_ADMIN or ADMIN with broadcasts.read. SUPER_ADMIN or ADMIN with broadcasts.read permission.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/broadcasts/{id}

Summary: Update Broadcasts

Allowed role/access: SUPER_ADMIN or ADMIN with broadcasts.update

Notes: Access: SUPER_ADMIN or ADMIN with broadcasts.update. SUPER_ADMIN or ADMIN with broadcasts.update permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "title": "<string>",
  "message": "<string>",
  "imageUrl": "<string>",
  "ctaLabel": "<string>",
  "ctaUrl": "<string>",
  "channels": [
    "EMAIL"
  ],
  "priority": "LOW"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/broadcasts/{id}/targeting

Summary: Update Broadcasts Targeting

Allowed role/access: SUPER_ADMIN or ADMIN with broadcasts.update

Notes: Access: SUPER_ADMIN or ADMIN with broadcasts.update. SUPER_ADMIN or ADMIN with broadcasts.update permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "mode": "ALL_USERS",
  "roles": [
    "ADMIN"
  ],
  "filters": {
    "location": "<string>",
    "onlyVerifiedEmails": true,
    "excludeUnsubscribed": true,
    "excludeSuspended": true
  }
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/broadcasts/estimate-reach

Summary: Create Broadcasts Estimate Reach

Allowed role/access: SUPER_ADMIN or ADMIN with broadcasts.read

Notes: Access: SUPER_ADMIN or ADMIN with broadcasts.read. SUPER_ADMIN or ADMIN with broadcasts.read permission.

Request payload(s):

payload

```
{
  "channels": [
    "EMAIL"
  ],
  "targeting": {
    "mode": "ALL_USERS",
    "roles": [
      "ADMIN"
    ],
    "filters": {
      "location": "<string>",
      "onlyVerifiedEmails": true,
      "excludeUnsubscribed": true,
      "excludeSuspended": true
    }
  }
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/broadcasts/{id}/schedule

Summary: Update Broadcasts Schedule

Allowed role/access: SUPER_ADMIN or ADMIN with broadcasts.schedule

Notes: Access: SUPER_ADMIN or ADMIN with broadcasts.schedule. SUPER_ADMIN or ADMIN with broadcasts.schedule permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "sendMode": "NOW",
  "scheduledAt": "<string>",
  "timezone": "<string>",
  "isRecurring": true,
  "recurrence": {}
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/broadcasts/{id}/cancel

Summary: Create Broadcasts Cancel

Allowed role/access: SUPER_ADMIN or ADMIN with broadcasts.cancel

Notes: Access: SUPER_ADMIN or ADMIN with broadcasts.cancel. SUPER_ADMIN or ADMIN with broadcasts.cancel permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "reason": "<string>"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/broadcasts/{id}/report

Summary: Fetch Broadcasts Report details

Allowed role/access: SUPER_ADMIN or ADMIN with broadcasts.report.read

Notes: Access: SUPER_ADMIN or ADMIN with broadcasts.report.read. SUPER_ADMIN or ADMIN with broadcasts.report.read permission.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/broadcasts/{id}/recipients

Summary: Fetch Broadcasts Recipients details

Allowed role/access: SUPER_ADMIN or ADMIN with broadcasts.report.read

Notes: Access: SUPER_ADMIN or ADMIN with broadcasts.report.read. SUPER_ADMIN or ADMIN with broadcasts.report.read permission.

Parameters:

- id (path, required, string)
- page (query, optional, number)
- limit (query, optional, number)
- channel (query, optional, string)
- status (query, optional, string)
- search (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

07 Plans & Coupons

GET /api/v1/subscription-plans

Summary: List Subscription Plans

Allowed role/access: SUPER_ADMIN or ADMIN with subscriptionPlans.read

Notes: Access: SUPER_ADMIN or ADMIN with subscriptionPlans.read. SUPER_ADMIN or ADMIN with subscriptionPlans.read permission.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- visibility (query, optional, string)
- billingCycle (query, optional, string)
- sortBy (query, optional, string)
- sortOrder (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```

```
"message": "Request completed successfully."
}
```

POST /api/v1/subscription-plans

Summary: Create Subscription Plans

Allowed role/access: SUPER_ADMIN or ADMIN with subscriptionPlans.create

Notes: Access: SUPER_ADMIN or ADMIN with subscriptionPlans.create. SUPER_ADMIN or ADMIN with subscriptionPlans.create permission.

Request payload(s):

payload

```
{
  "name": "<string>",
  "description": "<string>",
  "monthlyPrice": 1.0,
  "yearlyPrice": 1.0,
  "currency": "USD",
  "visibility": "PUBLIC",
  "status": "ACTIVE",
  "isPopular": true,
  "features": {},
  "limits": {
    "maxGiftsPerMonth": 1.0,
    "maxGroupGiftingEvents": 1.0,
    "maxTeamMembers": 1.0,
    "storageGb": 1.0
  }
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/subscription-plans/stats

Summary: List Subscription Plans Stats

Allowed role/access: SUPER_ADMIN or ADMIN with subscriptionPlans.analytics.read

Notes: Access: SUPER_ADMIN or ADMIN with subscriptionPlans.analytics.read. SUPER_ADMIN or ADMIN with subscriptionPlans.analytics.read permission.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/subscription-plans/{id}

Summary: Fetch Subscription Plans details

Allowed role/access: SUPER_ADMIN or ADMIN with subscriptionPlans.read

Notes: Access: SUPER_ADMIN or ADMIN with subscriptionPlans.read. SUPER_ADMIN or ADMIN with subscriptionPlans.read permission.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/subscription-plans/{id}**Summary:** Update Subscription Plans**Allowed role/access:** SUPER_ADMIN or ADMIN with subscriptionPlans.update**Notes:** Access: SUPER_ADMIN or ADMIN with subscriptionPlans.update. SUPER_ADMIN or ADMIN with subscriptionPlans.update permission.**Parameters:**

- id (path, required, string)

Request payload(s):

payload

```
{
  "name": "<string>",
  "description": "<string>",
  "monthlyPrice": 1.0,
  "yearlyPrice": 1.0,
  "currency": "<string>",
  "visibility": "PUBLIC",
  "status": "ACTIVE",
  "isPopular": true,
  "features": {},
  "limits": {
    "maxGiftsPerMonth": 1.0,
    "maxGroupGiftingEvents": 1.0,
    "maxTeamMembers": 1.0,
    "storageGb": 1.0
  }
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/subscription-plans/{id}**Summary:** Delete Subscription Plans**Allowed role/access:** SUPER_ADMIN or ADMIN with subscriptionPlans.delete**Notes:** Access: SUPER_ADMIN or ADMIN with subscriptionPlans.delete. SUPER_ADMIN or ADMIN with subscriptionPlans.delete permission.**Parameters:**

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/subscription-plans/{id}/status

Summary: Update Subscription Plans Status

Allowed role/access: SUPER_ADMIN or ADMIN with subscriptionPlans.status.update

Notes: Access: SUPER_ADMIN or ADMIN with subscriptionPlans.status.update. SUPER_ADMIN or ADMIN with subscriptionPlans.status.update permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "status": "ACTIVE",
  "reason": "<string>"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/subscription-plans/{id}/visibility

Summary: Update Subscription Plans Visibility

Allowed role/access: SUPER_ADMIN or ADMIN with subscriptionPlans.visibility.update

Notes: Access: SUPER_ADMIN or ADMIN with subscriptionPlans.visibility.update. SUPER_ADMIN or ADMIN with subscriptionPlans.visibility.update permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "visibility": "PUBLIC"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/subscription-plans/{id}/analytics

Summary: Fetch Subscription Plans Analytics details

Allowed role/access: SUPER_ADMIN or ADMIN with subscriptionPlans.analytics.read

Notes: Access: SUPER_ADMIN or ADMIN with subscriptionPlans.analytics.read. SUPER_ADMIN or ADMIN with subscriptionPlans.analytics.read permission.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/plan-features/catalog

Summary: List Plan Features Catalog

Allowed role/access: SUPER_ADMIN or ADMIN with planFeatures.read

Notes: Access: SUPER_ADMIN or ADMIN with planFeatures.read. SUPER_ADMIN or ADMIN with planFeatures.read permission.

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/plan-features

Summary: List Plan Features

Allowed role/access: SUPER_ADMIN or ADMIN with planFeatures.read

Notes: Access: SUPER_ADMIN or ADMIN with planFeatures.read. SUPER_ADMIN or ADMIN with planFeatures.read permission.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- isActive (query, optional, boolean)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/plan-features

Summary: Create Plan Features

Allowed role/access: SUPER_ADMIN or ADMIN with planFeatures.create

Notes: Access: SUPER_ADMIN or ADMIN with planFeatures.create. SUPER_ADMIN or ADMIN with planFeatures.create permission.

Request payload(s):

payload

```
{
  "key": "<string>",
  "label": "<string>",
  "description": "<string>",
  "type": "BOOLEAN",
  "isActive": true,
  "sortOrder": 1.0
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/plan-features/{id}

Summary: Fetch Plan Features details

Allowed role/access: SUPER_ADMIN or ADMIN with planFeatures.read

Notes: Access: SUPER_ADMIN or ADMIN with planFeatures.read. SUPER_ADMIN or ADMIN with planFeatures.read permission.

Parameters:

- id (path, required, string)

Response body:


```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/plan-features/{id}

Summary: Update Plan Features

Allowed role/access: SUPER_ADMIN or ADMIN with planFeatures.update

Notes: Access: SUPER_ADMIN or ADMIN with planFeatures.update. SUPER_ADMIN or ADMIN with planFeatures.update permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "key": "<string>",
  "label": "<string>",
  "description": "<string>",
  "type": "BOOLEAN",
  "isActive": true,
  "sortOrder": 1.0
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/plan-features/{id}

Summary: Delete Plan Features

Allowed role/access: SUPER_ADMIN or ADMIN with planFeatures.delete

Notes: Access: SUPER_ADMIN or ADMIN with planFeatures.delete. SUPER_ADMIN or ADMIN with planFeatures.delete permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/coupons

Summary: List Coupons

Allowed role/access: SUPER_ADMIN or ADMIN with coupons.read

Notes: Access: SUPER_ADMIN or ADMIN with coupons.read. SUPER_ADMIN or ADMIN with coupons.read permission.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- search (query, optional, string)
- status (query, optional, string)
- planId (query, optional, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/coupons

Summary: Create Coupons

Allowed role/access: SUPER_ADMIN or ADMIN with coupons.create

Notes: Access: SUPER_ADMIN or ADMIN with coupons.create. SUPER_ADMIN or ADMIN with coupons.create permission.

Request payload(s):

payload

```
{
  "code": "<string>",
  "description": "<string>",
  "discountType": "PERCENTAGE",
  "discountValue": 1.0,
  "planIds": [
    "<string>"
  ],
  "startsAt": "<string>",
  "expiresAt": "<string>",
  "maxRedemptions": 1.0,
  "isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/coupons/{id}

Summary: Fetch Coupons details

Allowed role/access: SUPER_ADMIN or ADMIN with coupons.read

Notes: Access: SUPER_ADMIN or ADMIN with coupons.read. SUPER_ADMIN or ADMIN with coupons.read permission.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

PATCH /api/v1/coupons/{id}

Summary: Update Coupons

Allowed role/access: SUPER_ADMIN or ADMIN with coupons.update

Notes: Access: SUPER_ADMIN or ADMIN with coupons.update. SUPER_ADMIN or ADMIN with coupons.update permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "code": "<string>",
  "description": "<string>",
  "discountType": "PERCENTAGE",
  "discountValue": 1.0,
  "planIds": [
    "<string>"
  ],
  "startsAt": "<string>",
  "expiresAt": "<string>",
  "maxRedemptions": 1.0,
  "isActive": true
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/coupons/{id}

Summary: Delete Coupons

Allowed role/access: SUPER_ADMIN or ADMIN with coupons.delete

Notes: Access: SUPER_ADMIN or ADMIN with coupons.delete. SUPER_ADMIN or ADMIN with coupons.delete permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
}
```

```
"message": "Request completed successfully."
}
```

PATCH /api/v1/coupons/{id}/status

Summary: Update Coupons Status

Allowed role/access: SUPER_ADMIN or ADMIN with coupons.status.update

Notes: Access: SUPER_ADMIN or ADMIN with coupons.status.update. SUPER_ADMIN or ADMIN with coupons.status.update permission.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
{
  "status": "ACTIVE",
  "reason": "<string>"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

07 Storage

POST /api/v1/uploads/presigned-url

Summary: Create presigned upload URL

Allowed role/access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER

Notes: Access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. Backend derives ownerId/ownerRole from JWT. targetAccountId is forbidden for REGISTERED_USER and PROVIDER, admin-only when authorized, and allowed for SUPER_ADMIN. Backend derives ownerId/ownerRole from the authenticated JWT. targetAccountId is forbidden for REGISTERED_USER and PROVIDER, allowed only for SUPER_ADMIN/authorized ADMIN dashboard uploads. Include giftId only for gift image uploads.

Request payload(s):

giftUpload

```
{
  "folder": "gift-images",
  "fileName": "perfume.png",
  "contentType": "image/png",
  "sizeBytes": 1048576,
  "giftId": "gift_id"
}
```

normalUpload

```
{
  "folder": "provider-avatars",
  "fileName": "avatar.png",
  "contentType": "image/png",
}
```

```
"sizeBytes": 1048576
}
```

adminOnBehalf

```
{
  "folder": "provider-logos",
  "fileName": "logo.png",
  "contentType": "image/png",
  "sizeBytes": 1048576,
  "targetAccountId": "provider_user_id"
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

POST /api/v1/uploads/complete

Summary: Complete upload

Allowed role/access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER

Notes: Access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. Completes only uploads accessible to the authenticated account. Authenticated upload completion. REGISTERED_USER and PROVIDER can complete only their own uploads. ADMIN defaults to own uploads. SUPER_ADMIN can manage dashboard/admin inspection flows.

Request payload(s):

payload

```
{
  "uploadId": "<string>",
  "sizeBytes": 1.0
}
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

GET /api/v1/uploads

Summary: List uploads

Allowed role/access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER

Notes: Access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. REGISTERED_USER/PROVIDER list only own uploads; ownerId is ignored. ADMIN lists own uploads by default and may use ownerId only for authorized managed access. SUPER_ADMIN may inspect by ownerId. REGISTERED_USER: ownerId query is ignored and only own uploads are listed. PROVIDER: ownerId query is ignored and only own uploads are listed. ADMIN: lists own uploads by default and may use ownerId only for managed dashboard access when authorized. SUPER_ADMIN: can use ownerId for dashboard/admin inspection.

Parameters:

- page (query, optional, number)
- limit (query, optional, number)
- folder (query, optional, string)

- ownerId (query, optional, string)

Response body:

```
{
  "success": true,
  "data": [
    {
      "id": "upload_id",
      "ownerId": "user_id",
      "ownerRole": "REGISTERED_USER",
      "targetAccountId": null,
      "folder": "user-avatars",
      "fileName": "avatar.png",
      "contentType": "image/png",
      "sizeBytes": 1048576,
      "fileUrl": "https://cdn.yourdomain.com/user-avatars/avatar.png",
      "storageKey": "user-avatars/user_id/uuid-avatar.png",
      "status": "COMPLETED",
      "giftId": null,
      "createdAt": "2026-04-08T09:00:00.000Z",
      "updatedAt": "2026-04-08T09:01:00.000Z",
      "completedAt": "2026-04-08T09:01:00.000Z"
    }
  ],
  "meta": {
    "page": 1,
    "limit": 20,
    "total": 1,
    "totalPages": 1
  },
  "message": "Uploads fetched successfully."
}
```

GET /api/v1/uploads/{id}

Summary: Fetch upload details

Allowed role/access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER

Notes: Access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. REGISTERED_USER/PROVIDER can fetch only own uploads. ADMIN defaults to own uploads. SUPER_ADMIN may inspect uploads. REGISTERED_USER and PROVIDER can fetch only own uploads. ADMIN fetches own uploads by default. SUPER_ADMIN can inspect uploads for dashboard/admin operations.

Parameters:

- id (path, required, string)

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```

DELETE /api/v1/uploads/{id}

Summary: Delete upload

Allowed role/access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER

Notes: Access: SUPER_ADMIN, ADMIN, PROVIDER, or REGISTERED_USER. REGISTERED_USER/PROVIDER can delete only own uploads. ADMIN defaults to own uploads. SUPER_ADMIN may delete inspected uploads. REGISTERED_USER and

PROVIDER can delete only own uploads. ADMIN deletes own uploads by default. SUPER_ADMIN can delete inspected dashboard uploads. Deletion is permanent in the database.

Parameters:

- id (path, required, string)

Request payload(s):

payload

```
"<standard success envelope>"
```

Response body:

```
{
  "success": true,
  "data": "<response returned by endpoint>",
  "message": "Request completed successfully."
}
```