# FEITENG **LYRA**

## COPPER COMPOSITE PANEL

FEITENG

### Performance index

| | | **PREMIUM** (Copper Thickness: 0.3mm) | |
|---|---|---|---|
| **Panel thickness tolerance** | **Units** | **3mm** | **4mm** |
| Copper thickness tolerance | mm | ±0.02 | |
| Copper grade | | T2 | |
| **Composite Panel Size** | | | |
| Panel weight | kg/m² | ≥8.09 | ≥9.24 |
| Panel length tolerance | mm | ±3 | |
| Panel width tolerance | mm | ±2 | |
| Panel thickness tolerance | mm | ±0.2 | |
| **Mechanical Property** | | | |
| Bending strength | MPa | ≥100 | |
| Penetration resistance | KN | ≥8 | |
| Shear strength | MPa | ≥28 | |
| Tensile strength of Copper | MPa | ≥50 | |
| Thermal expansion coefficient | °C⁻¹ | ≤0.0004 | |
| Heat distortion temperature | °C | 95 | |
| 180° peel strength | N/mm | ≥3 | |
| Heat resistance water | / | No change | |
| **Composite Panel Core** | | | |
| Core density | g/cm³ | 1.15~1.20 | |
| **Fire Rating Classification** | | EN13501-1/Class C-s1,d0 | |
| **Coating** | | Polyester | |
| Coating thickness | μm | / | |
| Glossiness | % | ≥25 | |
| Coating hardness | / | ≥HB | |

ZHANGJIAGANG FEITENG NEW COMPOSITE MATERIALS CO., LTD.

Specialize in Producing Metal Coating Panel and Composite Panel for 30 Years

www.feitengacp.com