CUI INC®

SERIES: PDQE20-D | DESCRIPTION: DC-DC CONVERTER

FEATURES

- 20 W isolated output
- ultra-wide input voltage range
- single/dual regulated outputs
- 1500 Vdc isolation
- extended temperature range (-40~105°C)
- input under-voltage protection
- output short circuit, over-current, over-voltage protection
- DIP package

RoHS c UL us CE

MODEL	input voltage		output voltage	output current		output power	ripple & noise[1]	efficiency[2]
	typ (Vdc)	range (Vdc)	(Vdc)	min (mA)	max (mA)	max (W)	max (mVp-p)	typ (%)
PDQE20-Q24-S3-D	24	9~36	3.3	0	5000	16.5	100	88
PDQE20-Q24-S5-D	24	9~36	5	0	4000	20	100	90
PDQE20-Q24-S12-D	24	9~36	12	0	1667	20	100	90
PDQE20-Q24-S15-D	24	9~36	15	0	1333	20	100	91
PDQE20-Q24-S24-D	24	9~36	24	0	833	20	100	91
PDQE20-Q24-D5-D[3]	24	9~36	±5	0	±2000	20	200	87
PDQE20-Q24-D12-D[3]	24	9~36	±12	0	±833	20	200	90
PDQE20-Q24-D15-D[3]	24	9~36	±15	0	±667	20	200	90
PDQE20-Q24-D24-D[3]	24	9~36	±24	0	±417	20	200	89
PDQE20-Q48-S3-D	48	18~75	3.3	0	5000	16.5	100	88
PDQE20-Q48-S5-D	48	18~75	5	0	4000	20	100	90
PDQE20-Q48-S12-D	48	18~75	12	0	1667	20	100	91
PDQE20-Q48-S15-D	48	18~75	15	0	1333	20	100	91
PDQE20-Q48-S24-D	48	18~75	24	0	833	20	100	91
PDQE20-Q48-D5-D[3]	48	18~75	±5	0	±2000	20	200	86
PDQE20-Q48-D12-D[3]	48	18~75	±12	0	±833	20	200	90
PDQE20-Q48-D15-D[3]	48	18~75	±15	0	±667	20	200	90
PDQE20-Q48-D24-D[3]	48	18~75	±24	0	±417	20	200	90

Notes:
1. From 5~100% load, nominal input, 20 MHz bandwidth oscilloscope, with 10 µF tantalum and 1 µF ceramic capacitors on the output. From 0~5% load, ripple and noise is <5% Vo.
2. Measured at nominal input voltage, full load.
3. Dual output models are only CE certified.
4. All specifications are measured at Ta=25°C, humidity < 75%, nominal input voltage, and rated output load unless otherwise specified.

PART NUMBER KEY



INPUT

parameter	conditions/description		min	typ	max	units
operating input voltage	24 Vdc input models		9	24	36	Vdc
	48 Vdc input models		18	48	75	Vdc
start-up voltage	24 Vdc input models				9	Vdc
	48 Vdc input models				18	Vdc
surge voltage	for maximum of 1 second					
	24 Vdc input models		-0.7		50	Vdc
	48 Vdc input models		-0.7		100	Vdc
under voltage shutdown	24 Vdc input models		5.5	6.5		Vdc
	48 Vdc input models		12	15.5		Vdc
current	24 Vdc input models	3.3 Vdc output models			800	mA
		5, 12 Vdc output models			947	mA
		15, 24 Vdc output models			937	mA
		all dual output models		958		mA
	48 Vdc input models	3.3 Vdc output models			400	mA
		5 Vdc output models			474	mA
		12, 15, 24 Vdc output models			469	mA
		all dual output models		969		mA
remote on/off (CTRL)[5]	turn on (CTRL pin open or pulled high (3.5~12 Vdc))					
	turn off (CTRL pin pulled low to GND (0~1.2 Vdc))					
	input current when switched off			2	7	mA
filter	Pi filter					

Notes: 5. The voltage of the CTRL pin is referenced to input GND pin.

OUTPUT

parameter	conditions/description	min	typ	max	units
maximum capacitive load[6]	3.3, 5 Vdc output models			10,000	µF
	12 Vdc output models			1,600	µF
	15 Vdc output models			1,000	µF
	24 Vdc output models			500	µF
	±5 Vdc output models			2,000	µF
	±12 Vdc output models			800	µF
	±15 Vdc output models			600	µF
	±24 Vdc output models			300	µF
voltage accuracy[7]	single output models: 0% to full load		±1	±3	%
	dual output models: 5% to full load		±1	±3	%
line regulation	from low line to high line, full load				
	positive outputs		±0.2	±0.5	%
	negative outputs		±0.4	±1	%
load regulation[8]	from 5% to full load		±0.5	±1	%

Note: 6. Tested at input voltage range and full load.
7. At 0~5% load, the max output voltage accuracy for the dual output models is ±4%.
8. At 0~100% load, the max load regulation for the dual output models is ±5%.

OUTPUT (CONTINUED)

parameter	conditions/description	min	typ	max	units
cross regulation	dual output models: main output 50% load secondary output from 10~100% load			±5	%
start-up time	nominal input, constant resistive load		10		ms
adjustability[9]	see application notes		±10		%
switching frequency[10]	PWM mode 3.3, 5 Vdc output models all other models		 300 270		 kHz kHz
transient recovery time	25% load step change, nominal input voltage		300	500	µs
transient response deviation	25% load step change, nominal input voltage 3.3, 5 Vdc output models ±5 Vdc output models all other models		 ±5 ±3 ±3	 ±8 ±8 ±5	 % % %
temperature coefficient	at full load			±0.03	%/°C

Note: 9. For single output models only.
10. Value is based on full load. At loads <50%, the switching frequency decreases with decreasing load

PROTECTIONS

parameter	conditions/description	min	typ	max	units
over voltage protection		110		160	%
over current protection	single output models dual output models	110 110	150 150	190 200	% %
short circuit protection	hiccup, continuous, self recovery				

SAFETY AND COMPLIANCE

parameter	conditions/description	min	typ	max	units
isolation voltage	input to output for 1 minute at 1 mA input/output to case for 1 minute at 1 mA	1,500 1,000			Vdc Vdc
isolation resistance	input to output at 500 Vdc	1,000			MΩ
isolation capacitance	input to output, 100 kHz / 0.1 V		2,000		pF
safety approvals[11]	UL 62368-1, EN 62368-1, IEC 62368-1				
conducted emissions	CISPR32/EN55032, class B (external circuit required, see Figure 3-b, 4-b)				
radiated emissions	CISPR32/EN55032, class B (external circuit required, see Figure 3-b, 4-b)				
ESD	IEC/EN61000-4-2, contact ±6 kV; air ±8 kV, class B (single output models) IEC/EN61000-4-2, contact ±4 kV, class B (dual output models)				
radiated immunity	IEC/EN61000-4-3, 10 V/m, class A				
EFT/burst	IEC/EN61000-4-4, ±2 kV, class B (external circuit required, see Figure 3-a, 4-a)				
surge	IEC/EN61000-4-5, line-line ±2 kV, class B (external circuit required, see Figure 3-a, 4-a)				
conducted immunity	IEC/EN61000-4-6, 3 Vr.m.s, class A				
MTBF	as per MIL-HDBK-217F, 25°C	1,000,000			hours
RoHS	yes				

Note: 11. UL approval only on single output models.

ENVIRONMENTAL

parameter	conditions/description	min	typ	max	units
operating temperature	see derating curves 3.3, 5 Vdc output models all other models	 -40 -40		 95 105	 °C °C
storage temperature		-55		125	°C
storage humidity	non-condensing	5		95	%
vibration	10~150 Hz, 0.75 mm for 90 minutes on each axis		5		G

DERATING CURVES







SOLDERABILITY

parameter	conditions/description	min	typ	max	units
hand soldering	1.5 mm from case for 10 seconds			300	°C
wave soldering	see wave soldering profile			260	°C



MECHANICAL

parameter	conditions/description	min	typ	max	units
dimensions	25.40 x 25.40 x 11.70 [1.000 x 1.000 x 0.461 inch]				mm
case material	aluminum alloy				
weight			15		g

MECHANICAL DRAWING

units: mm [inch]
tolerance: ±0.50[±0.020]
pin diameter tolerance: ±0.10[±0.004]

PIN CONNECTIONS		
PIN	Function	
	Single	Dual
1	CTRL	CTRL
2	GND	GND
3	Vin	Vin
4	+Vo	+Vo
5	trim	0V
6	0V	-Vo





Note:Grid 2.54*2.54mm
Recommended PCB Layout
Top View

APPLICATION CIRCUIT

This series has been tested according to the following recommended circuits (Figures 1 & 2) before leaving the factory. If you want to further reduce the input and output ripple, you can increase the input and output capacitors or select capacitors of low equivalent series resistance provided that the capacitance is less than the maximum capacitive load of the model.

Figure 1
Single Output Models

Table 1

Vout (Vdc)	Cin (µF)	Cout (µF)
3.3/5/12/15	100	100
24	100	47

Figure 2
Dual Output Models



Table 2

Vin (Vdc)	Cin (µF)	Cout (µF)
24	100	10
48	10~47	10

EMC RECOMMENDED CIRCUIT

Figure 3
Single Output Models



Table 3

Recommended External Circuit Components		
Vin (Vdc)	24	48
FUSE	choose according to actual input current	
C0, C4	330 µF / 50 V	330 µF / 100 V
C1, C2	4.7 µF / 50 V	4.7 µF / 100 V
C3	Refer to the Cout in Table 1	
LDM1	2.2 µH / 4 A	2.2 µH / 2 A
CY1, CY2	1 nF / 2 kV	

Figure 4
Dual Output Models



Table 4

Recommended External Circuit Components		
Vin (Vdc)	24	48
FUSE	choose according to actual input current	
C0, C4	330 µF / 50 V	330 µF / 100 V
C1, C2	4.7 µF / 50 V	4.7 µF / 100 V
C3	Refer to the Cout in Table 2	
LDM1	4.7 µH	
CY1, CY2	1 nF / 2 kV	

APPLICATION NOTES

Output voltage trimming
Leave open if not used.

Figure 5

Application Circuit for Trim pin
(part in broken line is the interior of models)



Formula for Trim Resistor

$$\text{up:}\quad R_T = \frac{aR_2}{R_2 - a} - R_3 \qquad a = \frac{Vref}{Vo' - Vref} \cdot R_1$$

$$\text{down:}\quad R_T = \frac{aR_1}{R_1 - a} - R_3 \qquad a = \frac{Vo' - Vref}{Vref} \cdot R_2$$

Note: Value for R1, R2, R3, and Vref refer to Table 5
R_T: Trim Resistor
a: User-defined parameter, no actual meanings
Vo': The trim up/down voltage

Table 5

Vout (Vdc)	R1 (kΩ)	R2 (kΩ)	R3 (kΩ)	Vref (V)
3.3	4.829	2.87	15	1.24
5	2.894	2.87	10	2.5
12	11.000	2.87	17.4	2.5
15	14.494	2.87	17.4	2.5
24	24.872	2.87	20	2.5

PACKAGING

units: mm

Tube Size: 28.6 x 19.8 mm
Inner Carton Size: 575 x 135 x 100 mm
Outer Carton Size: 600 x 285 x 225 mm
Outer Carton QTY: 912 pcs









REVISION HISTORY

rev.	description	date
1.0	initial release	05/16/2019

The revision history provided is for informational purposes only and is believed to be accurate.

CUI INC®

Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

CUI Inc.:

PDQE20-Q48-S12-D PDQE20-Q48-D24-D PDQE20-Q48-D5-D PDQE20-Q24-D12-D PDQE20-Q24-D15-D PDQE20-Q24-S5-D PDQE20-Q48-S24-D PDQE20-Q48-D15-D PDQE20-Q24-D24-D PDQE20-Q24-D5-D PDQE20-Q24-S12-D PDQE20-Q24-S15-D PDQE20-Q24-S3-D PDQE20-Q48-D12-D PDQE20-Q48-S15-D PDQE20-Q48-S3-D PDQE20-Q24-S24-D PDQE20-Q48-S5-D