

Compiling the Debussy Suite on UNIX systems with Anaconda Anaconda Python3

Preliminary requirements

- 1) You MUST have **Anaconda Python** installed. If not, then download the latest version of Anaconda3 from:

<https://www.anaconda.com/products/individual>

After launching the installer, please pay attention at the following options:

Destination Select: Select HD=> click on Choose Folder button and select `/Users/your_username` as installation folder (check the message related to the chosen folder)

Installation type=> click on “ad hoc” button => disable modify PATH (under package name: Anaconda3)=> click Install

VERY IMPORTANT: if Anaconda3 is added to the environmental variables (i.e. to the `.bash_profile/.bash` file) every new terminal will be opened under the Anaconda3 base environment. You may experience issues with other applications (e.g., command line tools in MacOSX), and the Debussy compilation from source will likely fail. In such a case, please comment out the Anaconda3 commands in the `.bash_profile/.bash`, compile the software, and then go back to the original bash if needed.

- Wxpython is missing from the Anaconda package (and it is needed for running the Debussy GUI). Please install it, by typing on a terminal:

`pip3 install wxpython`

(NB. Don't use `conda install ***!`)

- **For Linux system only:** if the installation of wxpython gives errors, please try first installing **python3- wxgtk4.0** (or newer versions, depending on the OS) from the OS repositories:

`sudo apt-get install python3- wxgtk4.0`

- If you have another Python3 version already installed on your PC (or do you prefer to save disk space, by installing Python3 from scratch: <https://www.python.org/downloads/>), please install the required libraries (matplotlib, numpy, wxpython), by typing on a terminal:

`(Python3 path)pip3 install library`

- 2) You MUST have **gfortran** and **gcc** compilers installed. You can download them from *homebrew* repositories (<https://brew.sh> both for Linux and MacOSX systems).

The compilers must be properly linked and called by the system directly as **gcc** and **gfortran**, as required by the makefile of the suite

(e.g. `ln -s /usr/bin/gcc-13 /usr/bin/gcc`)

`ln -s /usr/bin/gfortran-13 /usr/bin/gfortran )`

3) **For MacOSX systems only:** you must install XQuartz. It can be downloaded the dmg from the following website: www.xquartz.org and installed.

IMPORTANT: Restart your computer after installing XQuartz!

4) **For Linux systems only:** be sure to have xterm installed (e.g. by `sudo apt-get install xterm`)

3) You MUST have **Java** installed for running **Jmol-13.0.08** package, which is used as the visualization tool of atomistic models in Debussy. **Jmol-13.0.08** is provided with the Suite. However, **Java** is required. Download and install it from www.java.com (it is suggested to download the last version available on the website: Java version older than April 2019 may give some issues, due to modification in the Oracle Java license).

4) We suggest having the package **Mercury** (available for free from the Cambridge Crystallographic Data Center – CCDC) as an integrative visualization tool, downloadable from. www.ccdc.cam.ac.uk/Solutions/FreeSoftware/pages/FreeMercury.aspx

Debussy Suite installation

1) Download from https://github.com/DeByeUSerSYstem/DEBUSSY_v2.2-UNIX the Suite by clicking on the green button **Code** → **Download ZIP** and unzip DEBUSSY_v2.2-UNIX -main.zip.

2) Unzip the file and move the DEBUSSY_v2.2 subfolder from the subfolder UNIX to `/Users/your_username` (or `/home/your_username` depending on your system)

Some executables must need permissions to be executed under your *User* account.

To do so, please type on a Terminal:

`chmod -R 777 /Users/your_username/DEBUSSY_v2.2`

3) In order to compile the Debussy- Suite, using a terminal, move into the folder DEBUSSY_v2.2, by typing:

`cd /Users/your_username/DEBUSSY_v2.2`

You are ready to install the Debussy Suite. You need root credentials for this operation. Type on the command line:

`./install_debussy_v2.2`

You will be asked three important questions:

a) insert the installation folder. Use the full path:

`/Users/your_username/DEBUSSY_v2.2`

b) compiling the external lib (LAPACK, LCREP, NLOPT), type YES (**Y**)

c) installing the Graphical User Interface (GUI), type YES (**Y**)

d) [if you are working on a linux-gnu platform (Ubuntu or Debian)] downloading lapack and blas from system repositories, type YES (**Y**)

The installation can take some min. At the end of the procedure, you will have a message "DONE!!" and "BYE BYE" on your terminal window.

Check that 16 binaries have been created in the **DEBUSSY_v2.2/bin** subfolder.

Possible error: aclocal-1.15 missing → go to extlib/automake-1.15 and follow the instructions reported in README_FB

4) Inside the **DEBUSSY_v2.2** folder you can find a **RUN_TEST_UNIX** folder, containing some files to test the Debussy workflow. Type on the Terminal:

```
cd RUN_TEST_UNIX
```

```
sh drun
```

The output of the program should appear on the Terminal ending with "***** Debussy simulation DONE! *****".

The installation of the Debussy Suite is successfully completed.

5) Check the GUI installation, by typing on the command line (in the **DEBUSSY_v2.2/bin** folder):

```
./debussy-suite_gui
```

If you see on your screen the GUI as in the image below, the GUI installation procedure ended successfully.

NB. If the expected xterm windows don't appear when running the GUI (with a shell error similar to "Can't open display: ..."), the **xterm** command in the GUI's py files must be replaced with other terminals (e.g. **xinit**). If you need help, please contact us.