

DEVELOPING INNOVATIVE FRAMEWORKS FOR EFFICIENT CODE-BASED SIGNATURES

Edoardo Persichetti

9 June 2022



- Introduction
- Traditional Approach
- Zero-Knowledge Protocols
- New Frameworks
- Conclusions

Part I

INTRODUCTION

POST-QUANTUM CRYPTOGRAPHY

In a few years time large-scale quantum computers might be reality.

POST-QUANTUM CRYPTOGRAPHY

In a few years time large-scale quantum computers might be reality.
But then (Shor, '95):

POST-QUANTUM CRYPTOGRAPHY

In a few years time large-scale quantum computers might be reality.
But then (Shor, '95):

- RSA
- DSA
- ECC
- Diffie-Hellman key exchange
- and many others ... **not secure** !

POST-QUANTUM CRYPTOGRAPHY

In a few years time large-scale quantum computers might be reality.
But then (Shor, '95):

- RSA
- DSA
- ECC
- Diffie-Hellman key exchange
- and many others ... **not secure** !

→ NIST's Post-Quantum Cryptography Standardization Call

POST-QUANTUM CRYPTOGRAPHY

In a few years time large-scale quantum computers might be reality.
But then (Shor, '95):

- RSA
- DSA
- ECC
- Diffie-Hellman key exchange
- and many others ... **not secure** !

→ NIST's Post-Quantum Cryptography Standardization Call

Main areas of research:

- Lattice-based cryptography.
- Hash-based cryptography.
- **Code-based cryptography** (McEliece, Niederreiter).
- Multivariate cryptography.
- Isogeny-based cryptography.

Code-based cryptography has been doing really well for encryption/key establishment.

Code-based cryptography has been doing really well for encryption/key establishment.

3 finalists in NIST's process:

- Classic McEliece (binary Goppa)
- BIKE (QC-MDPC)
- HQC (QC Random Codes)

Code-based cryptography has been doing really well for encryption/key establishment.

3 finalists in NIST's process:

- Classic McEliece (binary Goppa)
- BIKE (QC-MDPC)
- HQC (QC Random Codes)

The same cannot be said for code-based signatures.

Code-based cryptography has been doing really well for encryption/key establishment.

3 finalists in NIST's process:

- Classic McEliece (binary Goppa)
- BIKE (QC-MDPC)
- HQC (QC Random Codes)

The same cannot be said for code-based signatures.

Only 4 NIST submissions, all either **broken or withdrawn**.

Code-based cryptography has been doing really well for encryption/key establishment.

3 finalists in NIST's process:

- Classic McEliece (binary Goppa)
- BIKE (QC-MDPC)
- HQC (QC Random Codes)

The same cannot be said for code-based signatures.

Only 4 NIST submissions, all either broken or withdrawn.

Yet, signature schemes are a crucial component in cryptography.

Code-based cryptography has been doing really well for encryption/key establishment.

3 finalists in NIST's process:

- Classic McEliece (binary Goppa)
- BIKE (QC-MDPC)
- HQC (QC Random Codes)

The same cannot be said for code-based signatures.

Only 4 NIST submissions, all either broken or withdrawn.

Yet, signature schemes are a crucial component in cryptography.

Can we fix this?

ERROR-CORRECTING CODES

$[n, k]$ LINEAR CODE OVER \mathbb{F}_q

A subspace of **dimension** k of \mathbb{F}_q^n . Value n is called **length**.

ERROR-CORRECTING CODES

$[n, k]$ LINEAR CODE OVER \mathbb{F}_q

A subspace of dimension k of \mathbb{F}_q^n . Value n is called length.

HAMMING METRIC

$wt(x) = |\{i : x_i \neq 0, 1 \leq i \leq n\}|$, $d(x, y) = wt(x - y)$.

Minimum distance (of \mathcal{C}): $\min\{d(x, y) : x, y \in \mathcal{C}\}$.

ERROR-CORRECTING CODES

$[n, k]$ LINEAR CODE OVER \mathbb{F}_q

A subspace of dimension k of \mathbb{F}_q^n . Value n is called length.

HAMMING METRIC

$$wt(x) = |\{i : x_i \neq 0, 1 \leq i \leq n\}|, d(x, y) = wt(x - y).$$

Minimum distance (of \mathcal{C}): $\min\{d(x, y) : x, y \in \mathcal{C}\}.$

GENERATOR MATRIX

$G \in \mathbb{F}_q^{k \times n}$ defines the code as : $x \in \mathcal{C} \iff x = uG$ for $u \in \mathbb{F}_q^k$.

Not unique: $SG, S \in GL(k, q)$; **Systematic form:** $(I_k | M)$.

ERROR-CORRECTING CODES

$[n, k]$ LINEAR CODE OVER \mathbb{F}_q

A subspace of dimension k of \mathbb{F}_q^n . Value n is called length.

HAMMING METRIC

$wt(x) = |\{i : x_i \neq 0, 1 \leq i \leq n\}|$, $d(x, y) = wt(x - y)$.

Minimum distance (of \mathcal{C}): $\min\{d(x, y) : x, y \in \mathcal{C}\}$.

GENERATOR MATRIX

$G \in \mathbb{F}_q^{k \times n}$ defines the code as : $x \in \mathcal{C} \iff x = uG$ for $u \in \mathbb{F}_q^k$.

Not unique: SG , $S \in GL(k, q)$; Systematic form: $(I_k | M)$.

PARITY-CHECK MATRIX

$H \in \mathbb{F}_q^{(n-k) \times n}$ defines the code as: $x \in \mathcal{C} \iff Hx^T = 0$ (syndrome).

Not unique: SH , $S \in GL(n-k, q)$; **Systematic form:** $(M^T | I_{n-k})$.

ERROR-CORRECTING CODES

$[n, k]$ LINEAR CODE OVER \mathbb{F}_q

A subspace of dimension k of \mathbb{F}_q^n . Value n is called length.

HAMMING METRIC

$wt(x) = |\{i : x_i \neq 0, 1 \leq i \leq n\}|$, $d(x, y) = wt(x - y)$.

Minimum distance (of \mathcal{C}): $\min\{d(x, y) : x, y \in \mathcal{C}\}$.

GENERATOR MATRIX

$G \in \mathbb{F}_q^{k \times n}$ defines the code as : $x \in \mathcal{C} \iff x = uG$ for $u \in \mathbb{F}_q^k$.

Not unique: SG , $S \in GL(k, q)$; Systematic form: $(I_k | M)$.

PARITY-CHECK MATRIX

$H \in \mathbb{F}_q^{(n-k) \times n}$ defines the code as: $x \in \mathcal{C} \iff Hx^T = 0$ (syndrome).

Not unique: SH , $S \in GL(n-k, q)$; Systematic form: $(M^T | I_{n-k})$.

w-error correcting: \exists algorithm that corrects up to w errors.

DECODING PROBLEMS

In general, it is hard to decode **random codes**.

DECODING PROBLEMS

In general, it is hard to decode random codes.

PROBLEM (GENERAL DECODING)

Given: $G \in \mathbb{F}_q^{k \times n}$, $y \in \mathbb{F}_q^n$ and $w \in \mathbb{N}$.

Goal: find a word $e \in \mathbb{F}_q^n$ with $\text{wt}(e) \leq w$ such that $y - e = x \in \mathcal{C}_G$.

DECODING PROBLEMS

In general, it is hard to decode random codes.

PROBLEM (GENERAL DECODING)

Given: $G \in \mathbb{F}_q^{k \times n}$, $y \in \mathbb{F}_q^n$ and $w \in \mathbb{N}$.

Goal: find a word $e \in \mathbb{F}_q^n$ with $\text{wt}(e) \leq w$ such that $y - e = x \in \mathcal{C}_G$.

Easy to see this is equivalent to the following.

DECODING PROBLEMS

In general, it is hard to decode random codes.

PROBLEM (GENERAL DECODING)

Given: $G \in \mathbb{F}_q^{k \times n}$, $y \in \mathbb{F}_q^n$ and $w \in \mathbb{N}$.

Goal: find a word $e \in \mathbb{F}_q^n$ with $\text{wt}(e) \leq w$ such that $y - e = x \in \mathcal{C}_G$.

Easy to see this is equivalent to the following.

PROBLEM (SYNDROME DECODING)

Given: $H \in \mathbb{F}_q^{(n-k) \times n}$, $y \in \mathbb{F}_q^{(n-k)}$ and $w \in \mathbb{N}$.

Goal: find a word $e \in \mathbb{F}_q^n$ with $\text{wt}(e) \leq w$ such that $He^T = y$.

DECODING PROBLEMS

In general, it is hard to decode random codes.

PROBLEM (GENERAL DECODING)

Given: $G \in \mathbb{F}_q^{k \times n}$, $y \in \mathbb{F}_q^n$ and $w \in \mathbb{N}$.

Goal: find a word $e \in \mathbb{F}_q^n$ with $\text{wt}(e) \leq w$ such that $y - e = x \in \mathcal{C}_G$.

Easy to see this is equivalent to the following.

PROBLEM (SYNDROME DECODING)

Given: $H \in \mathbb{F}_q^{(n-k) \times n}$, $y \in \mathbb{F}_q^{(n-k)}$ and $w \in \mathbb{N}$.

Goal: find a word $e \in \mathbb{F}_q^n$ with $\text{wt}(e) \leq w$ such that $He^T = y$.

NP-Complete (Berlekamp, McEliece and Van Tilborg, 1978; Barg, 1994).

DECODING PROBLEMS

In general, it is hard to decode random codes.

PROBLEM (GENERAL DECODING)

Given: $G \in \mathbb{F}_q^{k \times n}$, $y \in \mathbb{F}_q^n$ and $w \in \mathbb{N}$.

Goal: find a word $e \in \mathbb{F}_q^n$ with $\text{wt}(e) \leq w$ such that $y - e = x \in \mathcal{C}_G$.

Easy to see this is equivalent to the following.

PROBLEM (SYNDROME DECODING)

Given: $H \in \mathbb{F}_q^{(n-k) \times n}$, $y \in \mathbb{F}_q^{(n-k)}$ and $w \in \mathbb{N}$.

Goal: find a word $e \in \mathbb{F}_q^n$ with $\text{wt}(e) \leq w$ such that $He^T = y$.

NP-Complete (Berlekamp, McEliece and Van Tilborg, 1978; Barg, 1994).

Unique solution when w is below a certain threshold.

DECODING PROBLEMS

In general, it is hard to decode random codes.

PROBLEM (GENERAL DECODING)

Given: $G \in \mathbb{F}_q^{k \times n}$, $y \in \mathbb{F}_q^n$ and $w \in \mathbb{N}$.

Goal: find a word $e \in \mathbb{F}_q^n$ with $\text{wt}(e) \leq w$ such that $y - e = x \in \mathcal{C}_G$.

Easy to see this is equivalent to the following.

PROBLEM (SYNDROME DECODING)

Given: $H \in \mathbb{F}_q^{(n-k) \times n}$, $y \in \mathbb{F}_q^{(n-k)}$ and $w \in \mathbb{N}$.

Goal: find a word $e \in \mathbb{F}_q^n$ with $\text{wt}(e) \leq w$ such that $He^T = y$.

NP-Complete (Berlekamp, McEliece and Van Tilborg, 1978; Barg, 1994).

Unique solution when w is below a certain threshold.

Very well-studied, solid security understanding (ISD).

HOW TO DO CODE-BASED CRYPTOGRAPHY?

Use hard problems from coding theory.

HOW TO DO CODE-BASED CRYPTOGRAPHY?

Use hard problems from coding theory.

To get trapdoor, need one more ingredient.

HOW TO DO CODE-BASED CRYPTOGRAPHY?

Use hard problems from coding theory.

To get trapdoor, need one more ingredient.

ASSUMPTION (CODE INDISTINGUISHABILITY)

Let M be a matrix defining a code. Then M is indistinguishable from a randomly generated matrix of the same size.

HOW TO DO CODE-BASED CRYPTOGRAPHY?

Use hard problems from coding theory.

To get trapdoor, need one more ingredient.

ASSUMPTION (CODE INDISTINGUISHABILITY)

Let M be a matrix defining a code. Then M is indistinguishable from a randomly generated matrix of the same size.

Hardness of assumption depends on chosen code family.

HOW TO DO CODE-BASED CRYPTOGRAPHY?

Use hard problems from coding theory.

To get trapdoor, need one more ingredient.

ASSUMPTION (CODE INDISTINGUISHABILITY)

Let M be a matrix defining a code. Then M is indistinguishable from a randomly generated matrix of the same size.

Hardness of assumption depends on chosen code family.

Choose a code family with efficient decoding algorithm associated to description Δ and **hide** the structure.

Part II

TRADITIONAL APPROACH

Use the traditional SDP-based trapdoor.

Use the traditional SDP-based trapdoor.

Use **hash-and-sign** framework as in e.g. Full Domain Hash (RSA).

Use the traditional SDP-based trapdoor.

Use hash-and-sign framework as in e.g. Full Domain Hash (RSA).

Given message msg , trapdoor OW function f and hash function H .

Use the traditional SDP-based trapdoor.

Use hash-and-sign framework as in e.g. Full Domain Hash (RSA).

Given message msg , trapdoor OW function f and hash function \mathbf{H} .

Create signature $\sigma = f^{-1}(\mathbf{H}(msg))$.

Use the traditional SDP-based trapdoor.

Use hash-and-sign framework as in e.g. Full Domain Hash (RSA).

Given message msg , trapdoor OW function f and hash function \mathbf{H} .

Create signature $\sigma = f^{-1}(\mathbf{H}(msg))$.

Verify signature if $f(\sigma) = \mathbf{H}(msg)$.

Use the traditional SDP-based trapdoor.

Use hash-and-sign framework as in e.g. Full Domain Hash (RSA).

Given message msg , trapdoor OW function f and hash function \mathbf{H} .

Create signature $\sigma = f^{-1}(\mathbf{H}(msg))$.

Verify signature if $f(\sigma) = \mathbf{H}(msg)$.

For code-based, trapdoor is decoding: CFS scheme.

(Courtois, Finiasz, Sendrier, 2001)

THE CFS SCHEME

Select hash function $\mathbf{H} : \{0, 1\}^* \rightarrow \mathbb{F}_q^{(n-k)}$.

THE CFS SCHEME

Select hash function $\mathbf{H} : \{0, 1\}^* \rightarrow \mathbb{F}_q^{(n-k)}$.

KEY GENERATION

- Choose a code \mathcal{C} (e.g. Goppa).
- SK: code description Δ for \mathcal{C} .
- PK: parity-check matrix H in systematic form for \mathcal{C} .

THE CFS SCHEME

Select hash function $\mathbf{H} : \{0, 1\}^* \rightarrow \mathbb{F}_q^{(n-k)}$.

KEY GENERATION

- Choose a code \mathcal{C} (e.g. Goppa).
- SK: code description Δ for \mathcal{C} .
- PK: parity-check matrix H in systematic form for \mathcal{C} .

SIGN

- Compute $y = \mathbf{H}(msg)$.
- Set $e = \text{Decode}_\Delta(y)$, with $e \in \mathbb{F}_q^n$ of weight w .
- Signature is $\sigma = e$.

THE CFS SCHEME

Select hash function $\mathbf{H} : \{0, 1\}^* \rightarrow \mathbb{F}_q^{(n-k)}$.

KEY GENERATION

- Choose a code \mathcal{C} (e.g. Goppa).
- SK: code description Δ for \mathcal{C} .
- PK: parity-check matrix H in systematic form for \mathcal{C} .


SIGN

- Compute $y = \mathbf{H}(msg)$.
- Set $e = Decode_{\Delta}(y)$, with $e \in \mathbb{F}_q^n$ of weight w .
- Signature is $\sigma = e$.

VERIFY

- Compute $y' = H\sigma^T$.
- Accept if $y' = \mathbf{H}(msg)$, otherwise reject.

Decoding a random word is not always possible!



Decoding a random word is not always possible!

Solution: try again.

Decoding a random word is not always possible!

Solution: try again.

Add **counter** c to the input of \mathbf{H} and try to decode $y = \mathbf{H}(msg, c)$.
Send c along with signature.

Decoding a random word is not always possible!

Solution: try again.

Add counter c to the input of \mathbf{H} and try to decode $y = \mathbf{H}(msg, c)$.

Send c along with signature.

With McEliece parameters $(1024, 524, 50)$ average of 2^{216} decoding attempts.

Decoding a random word is not always possible!

Solution: try again.

Add counter c to the input of \mathbf{H} and try to decode $y = \mathbf{H}(msg, c)$.

Send c along with signature.

With McEliece parameters (1024, 524, 50) average of 2^{216} decoding attempts.

Optimize parameters, e.g. $(2^{16}, 2^{16} - 144, 9)$ code: 9! decoding attempts.

Decoding a random word is not always possible!

Solution: try again.

Add counter c to the input of \mathbf{H} and try to decode $y = \mathbf{H}(msg, c)$.

Send c along with signature.

With McEliece parameters (1024, 524, 50) average of 2^{216} decoding attempts.

Optimize parameters, e.g. $(2^{16}, 2^{16} - 144, 9)$ code: 9! decoding attempts.

CFS parameters:

q	m	n	w	PK (kB)	Sig (bits)	Security
2	16	65536	9	1152	144	80

Decoding a random word is not always possible!

Solution: try again.

Add counter c to the input of \mathbf{H} and try to decode $y = \mathbf{H}(msg, c)$.

Send c along with signature.

With McEliece parameters (1024, 524, 50) average of 2^{216} decoding attempts.

Optimize parameters, e.g. (2^{16} , $2^{16} - 144$, 9) code: 9! decoding attempts.

CFS parameters:

q	m	n	w	PK (kB)	Sig (bits)	Security
2	16	65536	9	1152	144	80

Also, signing is **very slow**: in the order of seconds.

Additional security concerns: **very high rate** leads to **distinguishers**.

(Faugère Gauthier-Umana, Otmani, Perret, Tillich, 2013)

Additional security concerns: very high rate leads to distinguishers.

(Faugère Gauthier-Umana, Otmani, Perret, Tillich, 2013)

Generalized Birthday Attack by Bleichenbacher (2009) invalidates previous parameters: minimum $(m, w) = (15, 12)$ for 80 sec bits.

Additional security concerns: very high rate leads to distinguishers.

(Faugère Gauthier-Umana, Otmani, Perret, Tillich, 2013)

Generalized Birthday Attack by Bleichenbacher (2009) invalidates previous parameters: minimum $(m, w) = (15, 12)$ for 80 sec bits.

Completely impractical performance: implementations show GB of public key, and several seconds to sign.

(Landais, Sendrier, 2012; Bernstein, Chou, Schwabe, 2013)

Additional security concerns: very high rate leads to distinguishers.

(Faugère Gauthier-Umana, Otmani, Perret, Tillich, 2013)

Generalized Birthday Attack by Bleichenbacher (2009) invalidates previous parameters: minimum $(m, w) = (15, 12)$ for 80 sec bits.

Completely impractical performance: implementations show GB of public key, and several seconds to sign.

(Landais, Sendrier, 2012; Bernstein, Chou, Schwabe, 2013)

Recent approach using **high-weight** decoding presents an improvement (Debris-Alazard, Sendrier, Tillich, 2018).

Additional security concerns: very high rate leads to distinguishers.

(Faugère Gauthier-Umana, Otmani, Perret, Tillich, 2013)

Generalized Birthday Attack by Bleichenbacher (2009) invalidates previous parameters: minimum $(m, w) = (15, 12)$ for 80 sec bits.

Completely impractical performance: implementations show GB of public key, and several seconds to sign.

(Landais, Sendrier, 2012; Bernstein, Chou, Schwabe, 2013)

Recent approach using high-weight decoding presents an improvement (Debris-Alazard, Sendrier, Tillich, 2018).

Still shows many similar features.

Additional security concerns: very high rate leads to distinguishers.

(Faugère Gauthier-Umana, Otmani, Perret, Tillich, 2013)

Generalized Birthday Attack by Bleichenbacher (2009) invalidates previous parameters: minimum $(m, w) = (15, 12)$ for 80 sec bits.

Completely impractical performance: implementations show GB of public key, and several seconds to sign.

(Landais, Sendrier, 2012; Bernstein, Chou, Schwabe, 2013)

Recent approach using high-weight decoding presents an improvement (Debris-Alazard, Sendrier, Tillich, 2018).

Still shows many similar features.

Wave parameters:

q	n	k_u	k_v	w	PK (MB)	Sig (kB)	Security
3	8492	3558	2047	7980	3.2	1.6	128

Part III

ZERO-KNOWLEDGE PROTOCOLS

ZERO-KNOWLEDGE IDENTIFICATION SCHEMES


An interactive protocol to prove knowledge of a secret...

ZERO-KNOWLEDGE IDENTIFICATION SCHEMES

An interactive protocol to prove knowledge of a secret...
...without revealing anything about it.


ZERO-KNOWLEDGE IDENTIFICATION SCHEMES

An interactive protocol to prove knowledge of a secret...
...without revealing anything about it.



ZERO-KNOWLEDGE IDENTIFICATION SCHEMES


An interactive protocol to prove knowledge of a secret...
...without revealing anything about it.



- **Correctness**: honest prover always gets accepted.

ZERO-KNOWLEDGE IDENTIFICATION SCHEMES


An interactive protocol to prove knowledge of a secret...
...without revealing anything about it.



- Correctness: honest prover always gets accepted.
- **Soundness**: dishonest prover (impersonator) has a bounded probability of succeeding.

ZERO-KNOWLEDGE IDENTIFICATION SCHEMES

An interactive protocol to prove knowledge of a secret...
...without revealing anything about it.



- Correctness: honest prover always gets accepted.
- Soundness: dishonest prover (impersonator) has a bounded probability of succeeding.
- **Zero-Knowledge**: no information about the secret is leaked.

ZKIDs can be turned into signature schemes using **Fiat-Shamir** transformation.

ZKIDs can be turned into signature schemes using Fiat-Shamir transformation.

- Replace verifier's challenge with $\mathbf{H}(com, msg)$.

ZKIDs can be turned into signature schemes using Fiat-Shamir transformation.

- Replace verifier's challenge with $\mathbf{H}(com, msg)$.
- Form signature as $\sigma = (com, rsp)$.

ZKIDs can be turned into signature schemes using Fiat-Shamir transformation.

- Replace verifier's challenge with $\mathbf{H}(com, msg)$.
- Form signature as $\sigma = (com, rsp)$.
- Verify as in identification protocol.

ZKIDs can be turned into signature schemes using Fiat-Shamir transformation.

- Replace verifier's challenge with $\mathbf{H}(com, msg)$.
 - Form signature as $\sigma = (com, rsp)$.
 - Verify as in identification protocol.
-

This method for building signatures is very promising and leads to efficient schemes.

ZKIDs can be turned into signature schemes using Fiat-Shamir transformation.

- Replace verifier's challenge with $\mathbf{H}(com, msg)$.
 - Form signature as $\sigma = (com, rsp)$.
 - Verify as in identification protocol.
-

This method for building signatures is very promising and leads to efficient schemes.

Strong security guarantees. No trapdoor is required!

ZKIDs can be turned into signature schemes using Fiat-Shamir transformation.

- Replace verifier's challenge with $H(com, msg)$.
 - Form signature as $\sigma = (com, rsp)$.
 - Verify as in identification protocol.
-

This method for building signatures is very promising and leads to efficient schemes.

Strong security guarantees. No trapdoor is required!

For code-based, can avoid decoding: rely **directly** on SDP.

ZKIDs can be turned into signature schemes using Fiat-Shamir transformation.

- Replace verifier's challenge with $H(com, msg)$.
 - Form signature as $\sigma = (com, rsp)$.
 - Verify as in identification protocol.
-

This method for building signatures is very promising and leads to efficient schemes.

Strong security guarantees. No trapdoor is required!

For code-based, can avoid decoding: rely directly on SDP.

Use **random codes** and exploit hardness of **finding low-weight words**.

(Stern, 1993)

STERN'S ZKID PROTOCOL

Select hash function **H**.

STERN'S ZKID PROTOCOL

Select hash function H .

KEY GENERATION

- Choose **random** binary code \mathcal{C} , given by parity-check matrix H .
- SK: $e \in \mathbb{F}_2^n$ of weight w .
- PK: the syndrome $s = He^T$.

STERN'S ZKID PROTOCOL

Select hash function \mathbf{H} .

KEY GENERATION


- Choose random binary code \mathcal{C} , given by parity-check matrix H .
- SK: $\mathbf{e} \in \mathbb{F}_2^n$ of weight w .
- PK: the syndrome $\mathbf{s} = H\mathbf{e}^T$.

PROVER

Choose $\mathbf{y} \in \mathbb{F}_2^n$ and permutation π .

Set $\mathbf{c}_1 = \mathbf{H}(\pi, H\mathbf{y}^T)$, $\mathbf{c}_2 = \mathbf{H}(\pi(\mathbf{y}))$

$\mathbf{c}_3 = \mathbf{H}(\pi(\mathbf{y} + \mathbf{e}))$



If $b = 0$ set $\mathbf{rsp} = (\mathbf{y}, \pi)$

If $b = 1$ set $\mathbf{rsp} = (\mathbf{y} + \mathbf{e}, \pi) \xrightarrow{\mathbf{rsp}}$

If $b = 2$ set $\mathbf{rsp} = (\pi(\mathbf{y}), \pi(\mathbf{e}))$

VERIFIER

Select random $b \in \{0, 1, 2\}$.

Verify $\mathbf{c}_1, \mathbf{c}_2$.

Verify $\mathbf{c}_1, \mathbf{c}_3$.

Verify $\mathbf{c}_2, \mathbf{c}_3$
and $\text{wt}(\pi(\mathbf{e})) = w$.

ABOUT STERN'S ZKID

High **soundness error** implies that adversary has non-trivial **cheating probability**.

ABOUT STERN'S ZKID

High soundness error implies that adversary has non-trivial cheating probability.

For Stern's scheme, soundness error is $2/3$.

ABOUT STERN'S ZKID

High soundness error implies that adversary has non-trivial cheating probability.

For Stern's scheme, soundness error is $2/3$.

For instance: choose random y and π , then $x \in \mathbb{F}_2^n$ with $Hx^T = Hy^T + s$. Build c_1 and c_2 normally and $c_3 = \mathbf{H}(\pi(x))$. Then $rsp = (y, \pi)$ and $rsp = (x, \pi)$ pass verification for $b = 0$ and $b = 1$ (strategy fails for $b = 2$). Similarly for other combinations.

ABOUT STERN'S ZKID

High soundness error implies that adversary has non-trivial cheating probability.

For Stern's scheme, soundness error is $2/3$.

For instance: choose random y and π , then $x \in \mathbb{F}_2^n$ with $Hx^T = Hy^T + s$. Build c_1 and c_2 normally and $c_3 = \mathbf{H}(\pi(x))$. Then $rsp = (y, \pi)$ and $rsp = (x, \pi)$ pass verification for $b = 0$ and $b = 1$ (strategy fails for $b = 2$). Similarly for other combinations.

This means several **repetitions** are necessary to amplify error and reach target authentication level.

ABOUT STERN'S ZKID

High soundness error implies that adversary has non-trivial cheating probability.

For Stern's scheme, soundness error is $2/3$.

For instance: choose random y and π , then $x \in \mathbb{F}_2^n$ with $Hx^T = Hy^T + s$. Build c_1 and c_2 normally and $c_3 = \mathbf{H}(\pi(x))$. Then $rsp = (y, \pi)$ and $rsp = (x, \pi)$ pass verification for $b = 0$ and $b = 1$ (strategy fails for $b = 2$). Similarly for other combinations.

This means several repetitions are necessary to amplify error and reach target authentication level.

Transmitting the entire transcript produces a **very long** signature.

ABOUT STERN'S ZKID

High soundness error implies that adversary has non-trivial cheating probability.

For Stern's scheme, soundness error is $2/3$.

For instance: choose random y and π , then $x \in \mathbb{F}_2^n$ with $Hx^T = Hy^T + s$. Build c_1 and c_2 normally and $c_3 = \mathbf{H}(\pi(x))$. Then $rsp = (y, \pi)$ and $rsp = (x, \pi)$ pass verification for $b = 0$ and $b = 1$ (strategy fails for $b = 2$). Similarly for other combinations.

This means several repetitions are necessary to amplify error and reach target authentication level.

Transmitting the entire transcript produces a very long signature.

Stern's ZKID parameters:

q	n	w	τ	PK (bits)	Sig (kB)	Security	Auth.
2	512	56	35	256	5	60	20
2	620	68	137	310	93.3	80	80
2	1024	112	219	512	245	128	128

Several variants proposed over the years:

Several variants proposed over the years:

- Stern, 1993.
- Véron, 1996.
- Gaborit, Girault, 2007.
- Cayrel, Véron, El Yousfi, 2010.
- Aguilar, Gaborit, Schrek, 2011.
- ...

Several variants proposed over the years:

- Stern, 1993.
- Véron, 1996.
- Gaborit, Girault, 2007.
- Cayrel, Véron, El Yousfi, 2010.
- Aguilar, Gaborit, Schrek, 2011.
- ...

Goal: decreasing soundness error.

Several variants proposed over the years:

- Stern, 1993.
- Véron, 1996.
- Gaborit, Girault, 2007.
- Cayrel, Véron, El Yousfi, 2010.
- Aguilar, Gaborit, Schrek, 2011.
- ...

Goal: decreasing soundness error.

For example, CVE scheme achieves $\frac{q}{2(q-1)} \approx 1/2$.

Several variants proposed over the years:

- Stern, 1993.
- Véron, 1996.
- Gaborit, Girault, 2007.
- Cayrel, Véron, El Yousfi, 2010.
- Aguilar, Gaborit, Schrek, 2011.
- ...

Goal: decreasing soundness error.

For example, CVE scheme achieves $\frac{q}{2(q-1)} \approx 1/2$.

Efficient for large finite fields.

Select hash function **H**.

CVE'S PROTOCOL

Select hash function **H**.

KEY GENERATION

- Choose random **q -ary** code \mathcal{C} , given by parity-check matrix H .
- SK: $\mathbf{e} \in \mathbb{F}_q^n$ of weight w .
- PK: the syndrome $\mathbf{s} = H\mathbf{e}^T$.

CVE'S PROTOCOL

Select hash function \mathbf{H} .

KEY GENERATION

- Choose random q -ary code \mathcal{C} , given by parity-check matrix H .
- SK: $\mathbf{e} \in \mathbb{F}_q^n$ of weight w .
- PK: the syndrome $s = H\mathbf{e}^T$.

PROVER

Choose $y \in \mathbb{F}_q^n$ and **monomial** μ .


Set $c_1 = \mathbf{H}(\mu, Hy^T)$,

$c_2 = \mathbf{H}(\mu(y), \mu(\mathbf{e}))$

$z = \mu(y + c\mathbf{e})$

If $b = 0$ set $rsp = \mu$

If $b = 1$ set $rsp = \mu(\mathbf{e})$



VERIFIER

Select random $c \in \mathbb{F}_q^*$.

Select random $b \in \{0, 1\}$.

Verify $c_1 = \mathbf{H}(\mu, H\mu^{-1}(z))^T - cs$.

Verify $c_2 = \mathbf{H}(z - c\mu(\mathbf{e}), \mu(\mathbf{e}))$
and $wt(\mu(\mathbf{e})) = w$.

Part IV

NEW FRAMEWORKS

DECREASING THE SOUNDNESS ERROR

Signature sizes still too large (> 30 kB).

DECREASING THE SOUNDNESS ERROR

Signature sizes still too large (> 30 kB).

The idea is still valid - need to use a different **protocol**.

DECREASING THE SOUNDNESS ERROR

Signature sizes still too large (> 30 kB).

The idea is still valid - need to use a different protocol.

“MPC-in-the-head” approach used e.g. in Picnic.

(Ishai, Kushilevitz, Ostrovsky, Sahai, 2007; Katz, Kolesnikov, Wang, 2018)

Signature sizes still too large (> 30 kB).

The idea is still valid - need to use a different protocol.

“MPC-in-the-head” approach used e.g. in Picnic.

(Ishai, Kushilevitz, Ostrovsky, Sahai, 2007; Katz, Kolesnikov, Wang, 2018)

Some of the verifier's checks are independent from the secret.

DECREASING THE SOUNDNESS ERROR

Signature sizes still too large (> 30 kB).

The idea is still valid - need to use a different protocol.

“MPC-in-the-head” approach used e.g. in Picnic.

(Ishai, Kushilevitz, Ostrovsky, Sahai, 2007; Katz, Kolesnikov, Wang, 2018)

Some of the verifier's checks are independent from the secret.

These can be offloaded to a **trusted setup** (“helper”).

DECREASING THE SOUNDNESS ERROR

Signature sizes still too large (> 30 kB).

The idea is still valid - need to use a different protocol.

“MPC-in-the-head” approach used e.g. in Picnic.

(Ishai, Kushilevitz, Ostrovsky, Sahai, 2007; Katz, Kolesnikov, Wang, 2018)

Some of the verifier's checks are independent from the secret.

These can be offloaded to a trusted setup (“helper”).

Preprocessing phase prepares auxiliary collection of samples (shares).

DECREASING THE SOUNDNESS ERROR

Signature sizes still too large (> 30 kB).

The idea is still valid - need to use a different protocol.

“MPC-in-the-head” approach used e.g. in Picnic.

(Ishai, Kushilevitz, Ostrovsky, Sahai, 2007; Katz, Kolesnikov, Wang, 2018)

Some of the verifier's checks are independent from the secret.

These can be offloaded to a trusted setup (“helper”).

Preprocessing phase prepares auxiliary collection of samples (shares).

“Opening” of a subset does not compromise security...

DECREASING THE SOUNDNESS ERROR

Signature sizes still too large (> 30 kB).

The idea is still valid - need to use a different protocol.

“MPC-in-the-head” approach used e.g. in Picnic.

(Ishai, Kushilevitz, Ostrovsky, Sahai, 2007; Katz, Kolesnikov, Wang, 2018)

Some of the verifier's checks are independent from the secret.

These can be offloaded to a trusted setup (“helper”).

Preprocessing phase prepares auxiliary collection of samples (shares).

“Opening” of a subset does not compromise security...

...but allows for much larger challenge space.

KeyGen: as in CVE, using a **commitment scheme** **Com.**

KeyGen: as in CVE, using a commitment scheme **Com**.

HELPER

- Generate random $y, \tilde{e} \in \mathbb{F}_q^n$, with \tilde{e} of weight w , from **seed**.
- Compute $aux = \{\mathbf{Com}(y + c\tilde{e})\}_{c \in \mathbb{F}_q}$.
- Send seed to prover and aux to verifier.

GPS PROTOCOL

KeyGen: as in CVE, using a commitment scheme **Com**.

HELPER

- Generate random $y, \tilde{e} \in \mathbb{F}_q^n$, with \tilde{e} of weight w , from seed.
- Compute $aux = \{\mathbf{Com}(y + c\tilde{e})\}_{c \in \mathbb{F}_q}$.
- Send seed to prover and aux to verifier.

PROVER

Regenerate y, \tilde{e} from seed.

Determine μ s.t. $e = \mu(\tilde{e})$

$$\alpha = \mathbf{Com}(\mu, H(\mu(y))^T)$$

$$z = y + c\tilde{e}$$

$$\xrightarrow{\alpha}$$

$$\xleftarrow{c}$$

$$\xrightarrow{z}$$

VERIFIER

Select random $c \in \mathbb{F}_q$.

Verify $\alpha = \mathbf{Com}(\mu, H(\mu(z))^T - cs)$.

Verify **Com**(z) with corresponding value from aux .

GPS PROTOCOL

KeyGen: as in CVE, using a commitment scheme **Com**.

HELPER

- Generate random $y, \tilde{e} \in \mathbb{F}_q^n$, with \tilde{e} of weight w , from seed.
- Compute $aux = \{\mathbf{Com}(y + c\tilde{e})\}_{c \in \mathbb{F}_q}$.
- Send seed to prover and aux to verifier.

PROVER

Regenerate y, \tilde{e} from seed.

Determine μ s.t. $e = \mu(\tilde{e})$

$$\alpha = \mathbf{Com}(\mu, H(\mu(y))^T)$$

$$z = y + c\tilde{e}$$

$$\xrightarrow{\alpha}$$

$$\xleftarrow{c}$$

$$\xrightarrow{z}$$

VERIFIER

Select random $c \in \mathbb{F}_q$.

Verify $\alpha = \mathbf{Com}(\mu, H(\mu(z))^T - cs)$.

Verify **Com**(z) with corresponding value from aux .

Here the soundness error is $1/q$.

PRODUCING A SIGNATURE SCHEME

Use “cut-and-choose” technique to remove preprocessing.

PRODUCING A SIGNATURE SCHEME

Use “cut-and-choose” technique to remove preprocessing.

Executing 1 out of M setups produces soundness error $\max\left(\frac{1}{M}, \frac{1}{q}\right)$.

PRODUCING A SIGNATURE SCHEME

Use “cut-and-choose” technique to remove preprocessing.

Executing 1 out of M setups produces soundness error $\max\left(\frac{1}{M}, \frac{1}{q}\right)$.

Iterate as needed, then apply Fiat-Shamir.

PRODUCING A SIGNATURE SCHEME

Use “cut-and-choose” technique to remove preprocessing.

Executing 1 out of M setups produces soundness error $\max\left(\frac{1}{M}, \frac{1}{q}\right)$.

Iterate as needed, then apply Fiat-Shamir.

Several optimizations are possible (e.g. **Merkle trees**, **seed trees**).

PRODUCING A SIGNATURE SCHEME

Use “cut-and-choose” technique to remove preprocessing.

Executing 1 out of M setups produces soundness error $\max\left(\frac{1}{M}, \frac{1}{q}\right)$.

Iterate as needed, then apply Fiat-Shamir.

Several optimizations are possible (e.g. Merkle trees, seed trees).

Can potentially yield smaller signatures, at the cost of increased computation (signing/verification time).

PRODUCING A SIGNATURE SCHEME

Use “cut-and-choose” technique to remove preprocessing.

Executing 1 out of M setups produces soundness error $\max\left(\frac{1}{M}, \frac{1}{q}\right)$.

Iterate as needed, then apply Fiat-Shamir.

Several optimizations are possible (e.g. Merkle trees, seed trees).

Can potentially yield smaller signatures, at the cost of increased computation (signing/verification time).

GPS scheme parameters ($\lambda = 128$, sizes in kB):

M	τ	q	n	k	w	PK	Sig
512	23	128	220	101	90	0.10	27.06
1024	19	256	207	93	90	0.11	23.98
2048	16	512	196	92	84	0.11	21.22
4096	14	1024	187	90	80	0.12	19.76

The GPS machinery is very expensive.

SHARED PERMUTATIONS

The GPS machinery is very expensive.

Idea: use MPC-in-the-head on **permutations**.

(Feneuil, Joux, Rivain, 2021)

SHARED PERMUTATIONS

The GPS machinery is very expensive.

Idea: use MPC-in-the-head on permutations.

(Feneuil, Joux, Rivain, 2021)

As in Stern, reveal $v := \pi(e)$ and $\tilde{e} := e + y$, for **codeword** y .
Verifier then checks $s = H\tilde{e}^T$ and $wt(v)$.

SHARED PERMUTATIONS

The GPS machinery is very expensive.

Idea: use MPC-in-the-head on permutations.

(Feneuil, Joux, Rivain, 2021)

As in Stern, reveal $v := \pi(e)$ and $\tilde{e} := e + y$, for codeword y .
Verifier then checks $s = H\tilde{e}^T$ and $wt(v)$.

This is equivalent to showing existence of (π, y) such that $Hy^T = 0$
and $\pi(\tilde{e}) = v + \pi(y)$.

SHARED PERMUTATIONS

The GPS machinery is very expensive.

Idea: use MPC-in-the-head on permutations.

(Feneuil, Joux, Rivain, 2021)

As in Stern, reveal $v := \pi(e)$ and $\tilde{e} := e + y$, for codeword y .
Verifier then checks $s = H\tilde{e}^T$ and $wt(v)$.

This is equivalent to showing existence of (π, y) such that $Hy^T = 0$ and $\pi(\tilde{e}) = v + \pi(y)$.

Can prove the former using cut-and-choose, and the latter via an **affine transformation** $A(\cdot) = \pi(\cdot) + r$, for random r , so that

$$A(\tilde{e}) = \pi(e) + \pi(y) + r = v + q$$

where q is a “trusted” vector.

SHARED PERMUTATIONS

The GPS machinery is very expensive.

Idea: use MPC-in-the-head on permutations.

(Feneuil, Joux, Rivain, 2021)

As in Stern, reveal $v := \pi(e)$ and $\tilde{e} := e + y$, for codeword y .
Verifier then checks $s = H\tilde{e}^T$ and $wt(v)$.

This is equivalent to showing existence of (π, y) such that $Hy^T = 0$ and $\pi(\tilde{e}) = v + \pi(y)$.

Can prove the former using cut-and-choose, and the latter via an affine transformation $A(\cdot) = \pi(\cdot) + r$, for random r , so that

$$A(\tilde{e}) = \pi(e) + \pi(y) + r = v + q$$

where q is a “trusted” vector.

A is decomposed into $A_N \circ \dots \circ A_1$ to apply MPC.

SHARED PERMUTATIONS

The GPS machinery is very expensive.

Idea: use MPC-in-the-head on permutations.

(Feneuil, Joux, Rivain, 2021)

As in Stern, reveal $v := \pi(e)$ and $\tilde{e} := e + y$, for codeword y .
Verifier then checks $s = H\tilde{e}^T$ and $wt(v)$.

This is equivalent to showing existence of (π, y) such that $Hy^T = 0$ and $\pi(\tilde{e}) = v + \pi(y)$.

Can prove the former using cut-and-choose, and the latter via an affine transformation $A(\cdot) = \pi(\cdot) + r$, for random r , so that

$$A(\tilde{e}) = \pi(e) + \pi(y) + r = v + q$$

where q is a “trusted” vector.

A is decomposed into $A_N \circ \dots \circ A_1$ to apply MPC.

FJR scheme parameters ($\lambda = 128$, sizes in kB):

M	τ	q	n	k	w	PK	Sig
389	28	2	1280	640	132	0.96	16.34

PROVING HAMMING WEIGHT VIA POLYNOMIALS

Observation: if $H = (H' | I_{n-k})$ write $e = (e_A, e_B)$, so $s = H(e_A, e_B)^T$.
Then e_A uniquely determines e given s and H .

PROVING HAMMING WEIGHT VIA POLYNOMIALS

Observation: if $H = (H' | I_{n-k})$ write $e = (e_A, e_B)$, so $s = H(e_A, e_B)^T$. Then e_A uniquely determines e given s and H .

Let $\mathbb{F}_q \subset \mathbb{F}_{\text{poly}}$ such that $n \leq |\mathbb{F}_{\text{poly}}|$ and let $\{\gamma_1, \dots, \gamma_n\}$ be distinct elements of \mathbb{F}_{poly} .

PROVING HAMMING WEIGHT VIA POLYNOMIALS

Observation: if $H = (H' | I_{n-k})$ write $e = (e_A, e_B)$, so $s = H(e_A, e_B)^T$. Then e_A uniquely determines e given s and H .

Let $\mathbb{F}_q \subset \mathbb{F}_{\text{poly}}$ such that $n \leq |\mathbb{F}_{\text{poly}}|$ and let $\{\gamma_1, \dots, \gamma_n\}$ be distinct elements of \mathbb{F}_{poly} .

Build $S(X) \in \mathbb{F}_{\text{poly}}[X]$ via polynomial interpolation of the points (γ_i, e_i) .

PROVING HAMMING WEIGHT VIA POLYNOMIALS

Observation: if $H = (H' | I_{n-k})$ write $e = (e_A, e_B)$, so $s = H(e_A, e_B)^T$. Then e_A uniquely determines e given s and H .

Let $\mathbb{F}_q \subset \mathbb{F}_{\text{poly}}$ such that $n \leq |\mathbb{F}_{\text{poly}}|$ and let $\{\gamma_1, \dots, \gamma_n\}$ be distinct elements of \mathbb{F}_{poly} .

Build $S(X) \in \mathbb{F}_{\text{poly}}[X]$ via polynomial interpolation of the points (γ_i, e_i) .

Build $Q(X) = \prod_{i \in E} (X - \gamma_i)$ where $E = \{\text{nonzero pos. of } e\}$.

PROVING HAMMING WEIGHT VIA POLYNOMIALS

Observation: if $H = (H' | I_{n-k})$ write $e = (e_A, e_B)$, so $s = H(e_A, e_B)^T$. Then e_A uniquely determines e given s and H .

Let $\mathbb{F}_q \subset \mathbb{F}_{\text{poly}}$ such that $n \leq |\mathbb{F}_{\text{poly}}|$ and let $\{\gamma_1, \dots, \gamma_n\}$ be distinct elements of \mathbb{F}_{poly} .

Build $S(X) \in \mathbb{F}_{\text{poly}}[X]$ via polynomial interpolation of the points (γ_i, e_i) .

Build $Q(X) = \prod_{i \in E} (X - \gamma_i)$ where $E = \{\text{nonzero pos. of } e\}$.

Then $\deg(Q) = w$ and $wt(e) \leq w$ is equivalent to

$$Q \cdot S - P \cdot F = 0$$

where $F = \prod_{i=1}^n (X - \gamma_i)$ and $\deg(P) \leq w - 1$.

PROVING HAMMING WEIGHT VIA POLYNOMIALS

Observation: if $H = (H' | I_{n-k})$ write $e = (e_A, e_B)$, so $s = H(e_A, e_B)^T$. Then e_A uniquely determines e given s and H .

Let $\mathbb{F}_q \subset \mathbb{F}_{\text{poly}}$ such that $n \leq |\mathbb{F}_{\text{poly}}|$ and let $\{\gamma_1, \dots, \gamma_n\}$ be distinct elements of \mathbb{F}_{poly} .

Build $S(X) \in \mathbb{F}_{\text{poly}}[X]$ via polynomial interpolation of the points (γ_i, e_i) .

Build $Q(X) = \prod_{i \in E} (X - \gamma_i)$ where $E = \{\text{nonzero pos. of } e\}$.

Then $\deg(Q) = w$ and $wt(e) \leq w$ is equivalent to

$$Q \cdot S - P \cdot F = 0$$

where $F = \prod_{i=1}^n (X - \gamma_i)$ and $\deg(P) \leq w - 1$.

This transforms SDP into a **polynomial problem** and completely avoids the need for an isometry.

(Feneuil, Joux, Rivain, 2022)

PROOF OF KNOWLEDGE (IN A NUTSHELL)

Create some **shares** $e_A = \sum_{j=1}^M e_A^{(j)}$ and hence $e = \sum_{j=1}^M e^{(j)}$.

PROOF OF KNOWLEDGE (IN A NUTSHELL)

Create some shares $e_A = \sum_{j=1}^M e_A^{(j)}$ and hence $e = \sum_{j=1}^M e^{(j)}$.

Find $S^{(j)}(X)$ using points $(\gamma_i, e_i^{(j)})$, where $e^{(j)} = (e_1^{(j)}, \dots, e_n^{(j)})$.

PROOF OF KNOWLEDGE (IN A NUTSHELL)

Create some shares $e_A = \sum_{j=1}^M e_A^{(j)}$ and hence $e = \sum_{j=1}^M e^{(j)}$.

Find $S^{(j)}(X)$ using points $(\gamma_i, e_i^{(j)})$, where $e^{(j)} = (e_1^{(j)}, \dots, e_n^{(j)})$.

By the **linearity** of the Lagrange interpolation, $S(X) = \sum_{j=1}^M S^{(j)}(X)$.

PROOF OF KNOWLEDGE (IN A NUTSHELL)

Create some shares $e_A = \sum_{j=1}^M e_A^{(j)}$ and hence $e = \sum_{j=1}^M e^{(j)}$.

Find $S^{(j)}(X)$ using points $(\gamma_i, e_i^{(j)})$, where $e^{(j)} = (e_1^{(j)}, \dots, e_n^{(j)})$.

By the linearity of the Lagrange interpolation, $S(X) = \sum_{j=1}^M S^{(j)}(X)$.

Write $Q(X) = \sum_{j=1}^M Q^{(j)}(X)$ and then $(P \cdot F)(X) = \sum_{j=1}^M (P \cdot F)^{(j)}(X)$.

PROOF OF KNOWLEDGE (IN A NUTSHELL)

Create some shares $e_A = \sum_{j=1}^M e_A^{(j)}$ and hence $e = \sum_{j=1}^M e^{(j)}$.

Find $S^{(j)}(X)$ using points $(\gamma_i, e_i^{(j)})$, where $e^{(j)} = (e_1^{(j)}, \dots, e_n^{(j)})$.

By the linearity of the Lagrange interpolation, $S(X) = \sum_{j=1}^M S^{(j)}(X)$.

Write $Q(X) = \sum_{j=1}^M Q^{(j)}(X)$ and then $(P \cdot F)(X) = \sum_{j=1}^M (P \cdot F)^{(j)}(X)$.

To verify that $Q(X)S(X) = (P \cdot F)(X)$, check $Q(r_l)S(r_l) = (P \cdot F)(r_l)$ for $1 \leq l \leq t$ and r_l elements of an extension field $\mathbb{F}_{\text{points}}$ of \mathbb{F}_{poly} (**Schwartz-Zippel lemma**).

PROOF OF KNOWLEDGE (IN A NUTSHELL)

Create some shares $e_A = \sum_{j=1}^M e_A^{(j)}$ and hence $e = \sum_{j=1}^M e^{(j)}$.

Find $S^{(j)}(X)$ using points $(\gamma_i, e_i^{(j)})$, where $e^{(j)} = (e_1^{(j)}, \dots, e_n^{(j)})$.

By the linearity of the Lagrange interpolation, $S(X) = \sum_{j=1}^M S^{(j)}(X)$.

Write $Q(X) = \sum_{j=1}^M Q^{(j)}(X)$ and then $(P \cdot F)(X) = \sum_{j=1}^M (P \cdot F)^{(j)}(X)$.

To verify that $Q(X)S(X) = (P \cdot F)(X)$, check $Q(r_l)S(r_l) = (P \cdot F)(r_l)$ for $1 \leq l \leq t$ and r_l elements of an extension field $\mathbb{F}_{\text{points}}$ of \mathbb{F}_{poly} (Schwartz-Zippel lemma).

This is done directly on shares $Q^{(j)}(r_l)$, $S^{(j)}(r_l)$ and $(P \cdot F)^{(j)}(r_l)$, via standard MPC techniques to verify **multiplication triple**.

Signature scheme obtained via usual means (cut-and-choose, repetition, Fiat-Shamir).

CONSIDERATIONS AND FUTURE WORK

Signature scheme obtained via usual means (cut-and-choose, repetition, Fiat-Shamir).

Performance is extremely competitive!

CONSIDERATIONS AND FUTURE WORK

Signature scheme obtained via usual means (cut-and-choose, repetition, Fiat-Shamir).

Performance is extremely competitive!

Scheme parameters ($\lambda = 128$, sizes in kB):

M	τ	q	n	k	w	\mathbb{F}_{poly}	$\mathbb{F}_{\text{points}}$	PK	Sig
256	17	2	1280	640	132	2^{11}	2^{22}	0.96	11.2
256	17	2^8	256	128	80	2^8	2^{24}	0.15	8.5

CONSIDERATIONS AND FUTURE WORK

Signature scheme obtained via usual means (cut-and-choose, repetition, Fiat-Shamir).

Performance is extremely competitive!

Scheme parameters ($\lambda = 128$, sizes in kB):

M	τ	q	n	k	w	\mathbb{F}_{poly}	$\mathbb{F}_{\text{points}}$	PK	Sig
256	17	2	1280	640	132	2^{11}	2^{22}	0.96	11.2
256	17	2^8	256	128	80	2^8	2^{24}	0.15	8.5

Possible improvement using **linear complexity** to avoid interpolation.

(P., Randrianarisoa, 2022)

CONSIDERATIONS AND FUTURE WORK

Signature scheme obtained via usual means (cut-and-choose, repetition, Fiat-Shamir).

Performance is extremely competitive!

Scheme parameters ($\lambda = 128$, sizes in kB):

M	τ	q	n	k	w	\mathbb{F}_{poly}	$\mathbb{F}_{\text{points}}$	PK	Sig
256	17	2	1280	640	132	2^{11}	2^{22}	0.96	11.2
256	17	2^8	256	128	80	2^8	2^{24}	0.15	8.5

Possible improvement using linear complexity to avoid interpolation.

(P., Randrianarisoa, 2022)

q -ary parameters can be refined, leading to improved performance (e.g. Sig ≈ 7 kB).

CONSIDERATIONS AND FUTURE WORK

Signature scheme obtained via usual means (cut-and-choose, repetition, Fiat-Shamir).

Performance is extremely competitive!

Scheme parameters ($\lambda = 128$, sizes in kB):

M	τ	q	n	k	w	\mathbb{F}_{poly}	$\mathbb{F}_{\text{points}}$	PK	Sig
256	17	2	1280	640	132	2^{11}	2^{22}	0.96	11.2
256	17	2^8	256	128	80	2^8	2^{24}	0.15	8.5

Possible improvement using linear complexity to avoid interpolation.

(P., Randrianarisoa, 2022)

q -ary parameters can be refined, leading to improved performance (e.g. Sig ≈ 7 kB).

Optimized implementation underway, NIST submission on the horizon.

Part V

CONCLUSIONS

Finally, viable solutions for code-based signatures begin to appear.

Finally, viable solutions for code-based signatures begin to appear.

MPC-in-the-head approach allows to achieve **high soundness**, bypassing traditional Achilles' heel of ZK-based schemes.

Finally, viable solutions for code-based signatures begin to appear.

MPC-in-the-head approach allows to achieve high soundness, bypassing traditional Achilles' heel of ZK-based schemes.

Another line of research uses **isometries** to build efficient schemes in a completely different way: for code-based, LESS (code equivalence).

(Biasse, Micheli, P. Santini, 2020; Barengi, Biasse, P., Santini, 2021)

Finally, viable solutions for code-based signatures begin to appear.

MPC-in-the-head approach allows to achieve high soundness, bypassing traditional Achilles' heel of ZK-based schemes.

Another line of research uses isometries to build efficient schemes in a completely different way: for code-based, LESS (code equivalence).

(Biasse, Micheli, P. Santini, 2020; Barengi, Biasse, P., Santini, 2021)

A lot of work to do for designing, optimizing and cryptanalyzing such schemes.

Finally, viable solutions for code-based signatures begin to appear.

MPC-in-the-head approach allows to achieve high soundness, bypassing traditional Achilles' heel of ZK-based schemes.

Another line of research uses isometries to build efficient schemes in a completely different way: for code-based, LESS (code equivalence).

(Biasse, Micheli, P. Santini, 2020; Barengi, Biasse, P., Santini, 2021)

A lot of work to do for designing, optimizing and cryptanalyzing such schemes.

Investigate applicability to several **advanced frameworks** (e.g. ring sigs, identity-based sigs, threshold sigs, multi-sigs...)

Grazie per l'attenzione!