

# Generating True Random Numbers From Vacuum Fluctuations in a Quantum System

Love Arreborn, Nadim Lakrouz

## ABSTRACT

TODO

## 1 INTRODUCTION

In cryptography, there are many applications for randomly generated numbers. However, the process of producing these random numbers tends to be pseudo-random, e.g. utilizing the current states of various modules. These numbers do not generate true randomness, and in order to heighten security other methods of generating these are required. Current random number generators (*RNG*) are usually implemented in code, using certain states of the host machine as a starting point before running a predetermined algorithm. This pseudo-random number generation (*PRNG*) comes with the drawback that the result is always deterministic, provided that the initial state is known.

True random numbers, then, cannot be produced solely through code. These systems require some input that is neither replicable nor reproducible. One proposed solution for this is quantum random number generation (*QRNG*) [1]. By reading quantum fluctuations from any given source, for instance an optical signal, the inherent unpredictability of said source can be harnessed in order to produce a random number from a state that is nigh impossible to reproduce accurately.

In this project, we will be writing firmware for one such solution, which reads quantum variations from an optical signal. Further details about how this signal is produced will be introduced in section 2 and builds on the work of M. Clason [2]. This optical signal will be converted to a stream of random, raw bits via an Analog to Digital Converter (*ADC*). In turn, these random bits will be processed via Toeplitz-hashing [3] in order to process these bits into random numbers. Some processing has to be done on the microcontrollers themselves in order to ensure that the data is workable, and Topelitz-hashing is a tried and tested method to accomplish this. These random numbers will then be output from the microcontroller to the host computer via USB. This thesis will aim to answer one key research question: How can sampled vacuum fluctuations be processed efficiently in order to output QRNG?

In producing this firmware, several key considerations have to be made in order for this system to be usable in a production environment. The vision for the end product is a simple USB-stick that can be connected to a host, and produce true random numbers from ambient quantum fluctuations. While this system could very well be implemented on physically larger hardware, thus avoiding the constraints that limited hardware introduces, Clason proposes a simpler and cheaper way to achieve QRNG [2]. In keeping with this, utilizing microcontrollers for processing the raw bits extracted further helps to keep the costs low and the solution reasonably complex. However, due to this portability constraint, our implementation needs to work quickly and efficiently on resource constrained hardware. As such, our main question is broken down into two concrete research areas:

**Research area 1 (*RA1*):** How can Toeplitz-hashing be implemented as effectively as possible on resource constrained hardware in order to process raw bits into a workable random number?

Toeplitz-hashing been optimized quite well, and previous research can be utilized for this. However, there are still considerations when implementing the firmware for the microcontroller in order to optimize the code. Our goal is to attempt several implementations in order to find the most optimal implementation with the least amount of CPU-cycles.

**Research area 2 (*RA2*):** How can we ensure that the output of random numbers is not limited by our firmware, but rather only limited by the USB transfer speed of the microcontroller or the ADC?

There will unequivocally be a bottleneck for the processing speed. For instance, the speed at which the ADC can process the optical signal into raw bits as well as the speed that the USB output can transfer processed random number to the host computer will be limiting factors. The slowest of these bottlenecks will inevitably be the limiting factor for any implementation. Our research aims to ensure that our implementation does not become the limiting factor, but rather processing data fast enough to match or exceed the speed of the hardware.

## 2 BACKGROUND

This work is a practical continuation of the work of Clason [2]. In this work, the author aimed to study quantum shot noise originating from photodiodes, and in so doing built a device which read from an optical source, outputting analog voltage from the data “seen” by the

diodes. A prototype was constructed, in which an LED is read by a photodiode soldered millimeters apart.

The idea of an optical QRNG (*OQRNG*) is not a novel one. The basis of the theory is that intrinsically random properties of a quantum process. Stefanov et. al. proposes using the random choice of a photon between two output signals to generate a random stream of bits, however the theory behind it can be applied to other quantum processes as well [4]. This particular theorem has been implemented by Wayne et. al. to create a quantum number generator [5].

However, our work revolves around the measurement of shot noise of vacuum states. Essentially, this is another quantum process with the same inherently random properties as described by Stefanov et. al., but instead using **insert reference for shot noise here**.

Implementations of this theory exist, however with significant drawbacks. Shen et. al. presents an implementation using a fairly complex setup, in which a continuous-wave fiber laser is the optical source [6]. They conclude that sampling the shot noise is, indeed, suitable for OQRNG. However, the implementation requires expensive and complex hardware.

- [1] M. Herrero-Collantes and J. C. Garcia-Escartin, "Quantum random number generators," *Rev. Mod. Phys.*, vol. 89, p. 015004, Feb. 2017, doi: 10.1103/RevModPhys.89.015004.
- [2] M. Clason, "Development of a QRNG front-end for shot noise measurement: Analysis of quantum shot noise originating from photodiodes," Independent thesis Advanced level (degree of Master (Two Years)), Linköping University, Department of Electrical Engineering, Information Coding, Linköping, Sweden, 2023.
- [3] X. Zhang, Y.-Q. Nie, H. Liang, and J. Zhang, "FPGA implementation of toeplitz hashing extractor for real time post-processing of raw random numbers," in *2016 IEEE-NPSS real time conference (RT)*, 2016, pp. 1–5. doi: 10.1109/RTC.2016.7543094.
- [4] O. G. André Stefanov Nicolas Gisin and H. Zbinden, "Optical quantum random number generator," *Journal of Modern Optics*, vol. 47, no. 4, pp. 595–598, 2000, doi: 10.1080/09500340008233380.
- [5] G. M. A. Michael A. Wayne Evan R. Jeffrey and P. G. Kwiat, "Photon arrival time quantum random number generation," *Journal of Modern Optics*, vol. 56, no. 4, pp. 516–522, 2009, doi: 10.1080/09500340802553244.
- [6] Y. Shen, L. Tian, and H. Zou, "Practical quantum random number generator based on measuring the shot noise of vacuum states," *Phys. Rev. A*, vol. 81, p. 063814, Jun. 2010, doi: 10.1103/PhysRevA.81.063814.