


Size A2



Comment	Description	Designator	Footprint	LibRef	Quantity
		C1, C2, C3, C4, C5, C6,			
100nF	SMD Capacitor	C7, C8, C9, C10, C11, C12	CAPC0603(1608)_M	Capacitor	12
	·		CAPC1210(3225)_M_Pol		
10uF	SMD Capacitor_Polar	C13, C15	ar	Capacitor_Polar	2
330nF	SMD Capacitor	C14	CAPC0603(1608)_M	Capacitor	1
470uF	SMD Capacitor_Polar	C16	CAPC1210(3225)_M_Pol ar	Capacitor_Polar	1
330uF	SMD Capacitor_Polar	C17, C18	CAPC Gcase	Capacitor_Polar	2
	LED with various				
LED	footprints	LED1, LED2, LED3	LEDC0603(1608)	LED	3
Mounting Hole	Mounting hole in different footprints	MH1, MH2, MH3, MH4, MH5	Hole_Mounting	Hole_Mounting	5
HDR1x8	Header, 8-Pin	P1, P3	HDR1X8_SMD	HDR1x8	2
HDR1x6	Header, 6-Pin	P2	HDR1X6_SMD	HDR1x6	1
HDR1x10	Header, 10-Pin	P4	HDR1X10_SMD	HDR1x10	1
	Header, 14-Pin, Dual	5-	HDR2X14_Female_Right	11000 11	
HDR2x14	row	P7	Angle	HDR2x14	1
4.7k	SMD Resistor	R1, R2	RESC0603(1608)_M	Resistor	2
220	SMD Resistor	R7, R8, R14	RESC0603(1608)_M	Resistor	3
10k	SMD Resistor	R9, R10, R12, R13	RESC0603(1608)_M	Resistor	4
33k	SMD Resistor	R11	RESC0603(1608)_M	Resistor	1
2k9	SMD Resistor	R15 R16, R17, R18, R19,	RESC0603(1608)_M	Resistor	1
		R20, R21, R22, R23,			
3k9	SMD Resistor	R24, R25	RESC0603(1608)_M	Resistor	10
		SW1, SW2, SW3, SW4, SW5, SW6, SW7, SW8, SW9, SW10, SW11,			
	Switch Tactile in	SW12, SW13, SW14,	Switch_tactile_SMD_12x		
Switch_Tactile	different footprints Switch Rocker in	SW15, SW16	12 Switch_Rocker_NKK_G	Switch_Tactile	16
Switch_Rocker	different footprints	SW17	W12_series	Switch_Rocker	1
	Switch DIP in different				
Switch_DIP_2	footprints,2 leads 30V P-CHANNEL	SW18	Switch_Dip_2 SOT23-	Switch_DIP_2	1
	ENHANCEMENT MODE		3ld_M_0.95PITCH_3x1.4		
ZXM61P03F	MOSFET	T1, T2, T3, T4, T5, T6, T7	BODY	ZXM61P03F	7
	5x7 DOT matrix,	U1, U2, U3, U4, U5, U6, U7, U8, U9, U10, U11, U12, U13, U14, U15,			
DOTmatrix_5x7_CC	Column Cathode	U16	DOTmatrix_5x7_0.7"	DOTmatrix_5x7_CC	16
	8-Bit Serial-Input Shift		T0000		
	Register with Latched 3-State Outputs and	U17, U18, U19, U20, U21, U22, U23, U24,	TSSOP- 16ld_M_0.65Pitch_5X4.4		
STP08DP05	current reference	U25, U26, U27	body	STP08DP05	11
Joystick	Joystick, 2 axis, select	U28	Joystick_ALPS_RKJXK122 400Y	JoyStick_2axis_select	1
AD5694RARUZ	Ouad 12-Bit nanoDAC+ with I2C Interface and 2 ppm/degC On-Chip Reference, -40 to +105 degC, RU-16, Pb-Free, Tube	U29	RU-16_N	CMP-0318-01679-2	1
Buzzer	Buzzer in different foot		Buzzer, IMO 41.T70P015		1
DUZZOI	Dazzer in different 100t	000	D42201, 1100 41.1701 0131	DULLUI	'
	1		I.		