

EEGpal: **GEDAI** module

Version 2.16, 05.09.2026

Video tutorial: *Coming soon*

The GEDAI toolbox (Generalized Eigenvalue De-Artifacting Instrument) offers a new approach to correcting EEG artefacts caused by muscles, eyes, electronic noise, etc with a fully automated strategy that does not require any human supervision or clean data samples.

Based on prior knowledge of the brain's 'signal' subspace (i.e. its spatial covariance), the authors computed a matrix that corresponds to the theoretical EEG signal if all cortical sources were active simultaneously. This matrix is computed based solely on the spatial distribution of the electrodes (synthetic signal), and is therefore completely free from artefacts. The GEDAI toolbox then uses generalized eigenvalue decomposition (GEVD) to compare your real data with this theoretical perfect signal. This allows you to effectively separate source components belonging to the artefact subspace from those belonging to the brain subspace. The result is a new version of your EEG signal containing only the most probable brain signal (without artefact). This provides better results and faster processing than ICA or ASR strategies (which should not be applied in addition to GEDAI correction).

A complete theoretical description and demonstration of its capacity can be found at the following website: <https://cibm.ch/noise-cancelling-headphones-for-the-brain-how-a-new-algorithm-eliminates-noise-in-eeeg-data/>

The original paper which described the algorithm can be found at the following location:
Ros, T., Férat, V., Huang, Y., et al. (2025). Return of the GEDAI: Unsupervised EEG Denoising based on Leadfield Filtering. bioRxiv. <https://doi.org/10.1101/2025.10.04.680449>

EEGpal_GEDAI

Generalized Eigenvalue De-Artifacting Instrument (GEDAI) ?

A

Denoising strength: auto 1

Leadfield matrix: interpolated 2

Epochs size (wave cycles): 12 3

Low-cut frequency (Hz): 0.5 4

B

Optional parameters

Sliding threshold adaptation (only for long recording): ☒ 5

Window duration (in seconds): 1200

Reject bad epochs: ☒ 6

Epoch ENOVA Threshold (0-1): 0.9

Reject bad channels: ☒ 7

Channel ENOVA Threshold (0-1): 0.9

Parallel processing: ☒ 8

Artifact visualization: ☐ 9

OUTPUT OPTIONS

Extension of output files: .sef 10

Select uppermost folder where to save the files: Select folder C

Saving folder: 11

Suffix string: GEDAIcorrected 12

APPLY 13

Run Save in memory Cancel

CIBM
Center for Biomedical Imaging

Pannel A: Main option

1. Determining deartifacting strength.
Stronger threshold type:
 - a. **auto** : Default option:
 - b. **auto+** might remove more noise at the expense of signal, while milder threshold
 - c. **auto-** might retain more signal at the expense of noise.
2. The leadfield matrix corresponds to the matrix of the theoretical clean EEG signal used as a reference. This matrix has been pre-computed based on a configuration of 343 electrodes (10-5 layout). The toolbox needs to interpolate it to match the electrode configuration of your data using a spherical algorithm. By default, leave the option **interpolated**. Use the option **precomputed** only if the electrode names load in *Electrode Setting* (main EEGpal window) respect the international convention (e.g. Fp1, Cz, ...) with a standard electrode configuration.
3. Epoch size in number of wave cycles for each wavelet band. Default is 12 which is a good compromise (see FAQ for more explanation of this parameter)
4. Low-cut frequency in Hz. Wavelet bands below this frequency will be excluded. Default is 0.5 Hz to use if no filter has been applied to your data. If you have already applied a high-pass filter to your signal using the Filtering+ module, this is unnecessary. In this case, it is recommended that you use the same cut-off frequency as in the Filtering+ module. For example, if you applied a high-pass filter at 1 Hz, you should set the low-cut frequency threshold in GEDAI to 1 Hz.

Pannel B: Optional parameters

5. In the case of a very long recording (for example, a sleep recording), you can expect the noise pattern to change over time due to factors such as gel drying or changes in the participant's sweat pattern. This is what we call the non-stationarity of the noise pattern. This option allows you to cut your recording into several sections and recompute the noise threshold for each section. This allows for the most accurate noise correction possible.
GEDAI uses a sliding window with 50% overlap. This means that if you enter a window duration of 1,200 seconds (20 minutes), GEDAI will compute the noise threshold of the signal over windows of 0–20 minutes, 10–30 minutes, 20–40 minutes and 30–50 minutes. See the FAQ for a discussion on the windows size.
6. This option allows you to remove part of the signal rather than denoise it. Epochs are rejected based on Explained Noise Variance (ENOVA). Setting the threshold to 0.9 will result in the rejection of all epochs in which more than 90% of the signal is identified as noise. A smaller value will lead to more conservative processing. The toolbox automatically adjusts the position of EEG events recorded in MRK files.
This option is NOT RECOMMENDED for an ERP study! Indeed, the epochs used by GEDAI (typically 1 s) are independent of the events (triggers/markers) in the file. This means that epochs centred on events (triggers/markers) used for averaging could be truncated. This is why using this option for an ERP study is strongly not recommended, and the artefact rejection options in the *Epoching module* should be used instead. Keep this option for resting state recording.
7. This option permits us to automatically detect bad channels and interpolate them. This is an alternative to the automatic bad channel detection of *CleanRawData* available in the **Filtering+ module**. To detect bad channels, it used the Explained Noise Variance (ENOVA).

Setting the threshold to 0.9 will result in the rejection of all channels in which more than 90% of the signal is identified as noise. GEDAI drops the bad channels, cleans the data on the remaining good ones, and then interpolates the missing channels back from the clean neighbors using the default EEGLAB spherical spline interpolation.

8. This option allows you to speed up processing by using multiple threads. This option is only available if you have the **Parallel Computing Toolbox** from MathWorks installed in your Matlab.
9. Open an additional window overlaying the original and corrected signals for visualization.

Pannel C: Output option

10. Select the format for the output files.
11. Select the destination folder where the results files will be saved. Note that this reproduces the input structure. For example, if the input files were in subfolders, there would be a folder per participant.
12. The suffix added to the input filename to obtain the output filename.
13. There are three validation buttons:
 - a. The **Run** button will carry out the processing.
 - b. The **Save in memory** button will store all the parameters in memory and close the GEDAI module without performing the processing. This is a useful option if you want to integrate GEDAI processing into a batch job.
 - c. The button **Cancel** closes the module without processing and without keeping the entered parameters in memory. The same effect will be achieved by closing the GEDAI module window.

FAQ

What is the impact of the parameter “Epochs size (wave cycles)”

In GEDAI, EEG data are not analyzed as one long continuous signal. Instead, the data are segmented into short epochs, and these epochs are used to compute frequency-specific covariance matrices that feed the GED (Generalized EigenDecomposition).

The parameter *Epochs size (wave cycles)* defines the length of each epoch in terms of the number of oscillatory cycles, not in seconds.

Key idea

The actual duration (in seconds) of an epoch depends on the frequency being analyzed:

$$\text{Epoch duration (s)} \approx \frac{\text{Number of cycles}}{\text{Frequency (Hz)}}$$

With the default value:

- Epochs size (wave cycles) = 12

Examples:

- At 10 Hz → epoch ≈ 1.2 s
- At 5 Hz → epoch ≈ 2.4 s
- At 30 Hz → epoch ≈ 0.4 s

GEDAI relies on:

- Band-limited covariance matrices
- Wavelet-based spectral filtering
- Generalized eigenvalue decomposition to separate neural signal from noise/artifacts

The epoch length directly affects:

1. Covariance estimation quality
 - Too short → ill-conditioned, noisy covariance matrices
 - Too long → smearing of nonstationary brain dynamics
2. Time–frequency trade-off
 - More cycles = better frequency precision, worse temporal precision
 - Fewer cycles = better temporal precision, worse frequency precision
3. Artifact detection sensitivity
 - Short epochs → better detection of brief EMG or movement artifacts
 - Long epochs → more robust detection of sustained noise sources

The default value (12 cycles) is a well-balanced compromise between statistical stability and temporal sensitivity across common EEG frequency bands.

Written by ChatGPT.

Is the GEDAI correction suitable for any types of EEG experiment, such ERP studies (visual, auditory, somatosensory) or resting state?

Yes. The GEDAI correction is independent of the task and relies on the biophysical spatial constraints of the cerebral EEG. This artefact rejection depends of :

- the geometry of the electrodes (this is why it is mandatory to load a file in the *Electrode Setting*)
- the conductive volume
- the fact that the sources are intracerebral and bipolar

It does not depend on:

- timing (ERP vs. ongoing)
- frequency
- phase locking
- inter-trial repeatability

Written with the help of ChatGPT

Are there any limitations to this artefact rejection method?

As the correction is based on the spatial distribution of the electrodes, it should be reasonable (medium head size, symmetric layout, more or less standard disposition). Efficiency depends on the number of electrodes, so this method is not suitable for single channels.

In terms of anatomy, the sources of deep brain structures such as the thalamus and the brainstem are not well estimated, and the signals from these regions are not well corrected.

Finally, the reference matrix has been computed for the entire brain. The GEDAI artefact correction will be less accurate for atypical brain anatomy, such as in patients with cerebral lesions. In addition, the presence of an active neurostimulator cannot be managed and will impair denoising.

Is it better to work with filtered or raw EEG signal when using GEDAI toolbox?

Very low-frequency noise, such as signal drift, would cause problems with GEDAI corrections. Therefore, it is recommended that you apply a high-pass filter to your signal and correct the line noise using either a 50 Hz notch filter or the CleanLine toolbox. If you are working with a raw signal, you will need to use the 'Low-cut frequency (Hz)' parameter from the GEDAI toolbox to apply a high-pass filter before artefact correction.

Applying a low-pass filter to the data (e.g. at 40 Hz) will not impair the GEDAI work.

In summary, it is advisable to apply filters using the *Filtering+* module before proceeding to the GEDAI module.

Is GEDAI changing the references used in the data?

Yes, the output files generated by the GEDAI toolbox will be automatically re-referenced to the average. However, it is still necessary to re-reference the signal to the average using the *Re-reference module* after interpolation, in order to remove the impact of bad channels.

What is the recommended processing pipeline for an ERP study using the GEDAI toolbox?

I would recommend using a similar processing pipeline as usual but without ASR or ICA:

- 1) Bridge Detection
- 2) Filtering +: Apply a high-pass filter with a threshold of at least 0.5 Hz and deactivate the *ASR bad burst correction* and *Additional removal of bad data periods* options for CLEAN RAWDATA
- 3) GEDAI: use the GEDAI toolbox with the same *Low-cut frequency value* as the high-pass threshold used in step 2. Do not activate the option *Reject bad epochs*.
- 4) Interpolation: Make a visual inspection of your signal to check for bad electrodes. Interpolate them with the bridged channels detect in step 1
- 5) Re-reference: Re-reference to *average reference* to correct the impact of bad channels on the signal
- 6) Epoching: Use the Epoching module as usual to create your Evoked Related Potential (ERP) files.

For the sliding threshold adaptation, which size of windows should I use ?

It depends on how much you expected the EEG signal artefact to change. As explained above, this option was created for long recordings (sleep, long rest periods, etc.). I would not use this option if you have several 10-minute runs with separate files.

In the original EEGLAB interface of GEDAI, there is a third option of the leadfiled matrix called “waped”. What is this option and why it is not available in the GEDAI interface?

A new leadfiled option called “warped” as been added in GEDAI 1.7. It takes the 3D coordinates from your dataset, aligns them to the Fieldtrip Colin27 head model, and computes an individual BEM leadfield on the fly via EEGLAB DIPFIT. It's frankly just an additional anatomical model if the other two don't work well. "Interpolated" is much faster since it just takes our precomputed OpenMEEG 343-channel leadfield and splines it directly to your sensor layout without needing DIPFIT.

This option is not available in the **GEDAI module** interface because the EEGLAB version included in the EEGpal installation does not contain the required tools for this option: Fieldtrip Lite and the DIPFIT plug-in. The authors chose not to include them because they take up space, and the 'warped' option is only supplementary and not required if the 'interpolated' option works. If you wish to use this option, please install the necessary modules and use the GEDAI interface in EEGLAB.