

Replit Fix Brief: Prompt Whisperer — Typewriter Animation (V3)

Replit, we need to implement the definitive version of the "Prompt Whisperer" feature.

The previous versions either looked too much like the main prompt builder or suffered from text truncation on mobile. This V3 design solves both problems by using a **slim, single-line input bar with a typewriter cycling animation** for the placeholder text.

This ensures the Whisperer looks like a dynamic, interactive "search bar" (completely distinct from the static main builder) and prevents long questions from getting cut off on small screens.

The Layout (Top to Bottom)

Plain Text

```
[ ✨ Prompt Whisperer – slim glowing search bar with typewriter text + Spark bu  
[ – or build from scratch below – ]  
[ Main Prompt Builder – the existing dark workspace box ]
```

1. HTML Structure

Inject this HTML directly above the main `pmgv3-goal-input` container.

HTML

```
<!-- Prompt Whisperer: Slim Search Bar -->  
<div class="pmgv3-whisperer-bar" id="pmgv3-whisperer-bar">  
  <div class="whisperer-label">  
    <span class="whisperer-icon">✨</span>  
    <span class="whisperer-title">Prompt Whisperer</span>  
  </div>  
  <div class="whisperer-input-row">  
    <!-- We use a wrapper to handle the typewriter effect cleanly -->  
    <div class="whisperer-input-wrapper">  
      <input  
        type="text"  
        class="whisperer-input"  
        id="whisperer-input"  
        placeholder=""  
        autocomplete="off"  
      />  
    </div>  
  </div>  
</div>
```

```

    <!-- The animated placeholder text sits behind the transparent input -->
    <div class="whisperer-typewriter" id="whisperer-typewriter"></div>
  </div>
  <button class="whisperer-spark-btn" id="btn-whisperer-spark">Spark →</button>
</div>

<!-- Divider between Whisperer and Main Builder -->
<div class="pmgv3-whisperer-divider">
  <span>— or build from scratch below —</span>
</div>

```

2. CSS Styling

Add these styles to `pmg-chassis-v3.css`. The key design goals are: slim height, animated glowing border, and the typewriter text overlay.

CSS

```

/* Whisperer Bar Container */
.pmgv3-whisperer-bar {
  margin-bottom: 12px;
  padding: 14px 18px;
  background: linear-gradient(135deg, rgba(0, 200, 150, 0.06) 0%, rgba(0, 0, 0, 0.06) 100%);
  border: 1px solid rgba(0, 200, 150, 0.5);
  border-radius: 14px;
  box-shadow: 0 0 18px rgba(0, 200, 150, 0.12);
  animation: whisperPulse 3s ease-in-out infinite;
}

@keyframes whisperPulse {
  0%, 100% { box-shadow: 0 0 12px rgba(0, 200, 150, 0.1); }
  50% { box-shadow: 0 0 24px rgba(0, 200, 150, 0.25); }
}

/* Label row */
.whisperer-label {
  display: flex;
  align-items: center;
  gap: 6px;
  margin-bottom: 10px;
}

.whisperer-icon {
  font-size: 14px;
}

```

```
.whisperer-title {
  color: #00c896;
  font-size: 11px;
  font-weight: 700;
  text-transform: uppercase;
  letter-spacing: 1.2px;
}

/* Input row */
.whisperer-input-row {
  display: flex;
  gap: 10px;
  align-items: center;
}

.whisperer-input-wrapper {
  flex: 1;
  position: relative;
  display: flex;
  align-items: center;
}

/* The actual input field (transparent background) */
.whisperer-input {
  width: 100%;
  background: transparent;
  border: none;
  border-bottom: 1px solid rgba(0, 200, 150, 0.3);
  color: #fff;
  font-size: 15px;
  padding: 6px 4px;
  outline: none;
  font-family: inherit;
  transition: border-color 0.2s;
  z-index: 2; /* Sits above the typewriter text */
}

.whisperer-input:focus {
  border-bottom-color: #00c896;
}

/* The animated typewriter text (sits behind the input) */
.whisperer-typewriter {
  position: absolute;
  left: 4px;
  top: 50%;
  transform: translateY(-50%);
```

```

color: rgba(255, 255, 255, 0.45);
font-style: italic;
font-size: 15px;
pointer-events: none; /* Let clicks pass through to the input */
z-index: 1;
white-space: nowrap;
overflow: hidden;
border-right: 2px solid rgba(0, 200, 150, 0.7); /* The blinking cursor */
animation: blinkCursor 0.75s step-end infinite;
}

@keyframes blinkCursor {
  from, to { border-color: transparent; }
  50% { border-color: rgba(0, 200, 150, 0.7); }
}

/* Hide typewriter text when user starts typing */
.whisperer-input:not(:placeholder-shown) + .whisperer-typewriter,
.whisperer-input:focus + .whisperer-typewriter {
  display: none;
}

/* Spark button */
.whisperer-spark-btn {
  background: #00c896;
  color: #000;
  border: none;
  padding: 8px 18px;
  border-radius: 20px;
  font-weight: 700;
  font-size: 13px;
  cursor: pointer;
  white-space: nowrap;
  transition: background 0.2s, transform 0.1s;
}

.whisperer-spark-btn:hover {
  background: #00e6ac;
  transform: scale(1.03);
}

.whisperer-spark-btn:active {
  transform: scale(0.98);
}

/* Divider */
.pmgv3-whisperer-divider {
  text-align: center;
}

```

```

margin: 16px 0;
position: relative;
}

.pmgv3-whisperer-divider::before {
  content: '';
  position: absolute;
  top: 50%;
  left: 0;
  right: 0;
  height: 1px;
  background: rgba(255, 255, 255, 0.08);
}

.pmgv3-whisperer-divider span {
  position: relative;
  background: #0d1f1a; /* Match the page background color */
  padding: 0 12px;
  color: rgba(255, 255, 255, 0.35);
  font-size: 12px;
  letter-spacing: 0.5px;
}

```

3. JavaScript Logic (The Typewriter Effect)

Add this logic to `pmg-chassis-v3.js` to handle the typewriter animation and the Spark button click.

JavaScript

```

const sparkQuestions = [
  "What's a problem you've been putting off solving?",
  "If you had a world-class expert on call right now, what would you ask them?",
  "What's something you wish you could explain better to someone?",
  "What's a business idea you've never had time to explore?",
  "What would you create if you knew it couldn't fail?",
  "What do you need written that you've been dreading?",
  "What's a complex topic you want to understand in 5 minutes?",
  "What's a skill you want to learn but don't know where to start?",
  "What's a message you've been struggling to write?",
  "What would you build if you had a team of experts helping you?"
];

function initWhisperer() {
  const whispererInput = document.getElementById('whisperer-input');
  const typewriterEl = document.getElementById('whisperer-typewriter');

```

```

const sparkBtn = document.getElementById('btn-whisperer-spark');

if (!whispererInput || !typewriterEl) return;

// --- Typewriter Animation Logic ---
let questionIndex = 0;
let charIndex = 0;
let isDeleting = false;
let typingDelay = 50; // Speed of typing

function type() {
  const currentQuestion = sparkQuestions[questionIndex];

  if (isDeleting) {
    // Remove a character
    typewriterEl.innerText = currentQuestion.substring(0, charIndex - 1);
    charIndex--;
    typingDelay = 30; // Delete faster
  } else {
    // Add a character
    typewriterEl.innerText = currentQuestion.substring(0, charIndex + 1);
    charIndex++;
    typingDelay = 50; // Type normal speed
  }

  // If finished typing the whole question
  if (!isDeleting && charIndex === currentQuestion.length) {
    typingDelay = 2500; // Pause at the end to let them read it
    isDeleting = true;
  }

  // If finished deleting the whole question
  else if (isDeleting && charIndex === 0) {
    isDeleting = false;
    questionIndex = (questionIndex + 1) % sparkQuestions.length; // Move to next question
    typingDelay = 500; // Pause before typing next question
  }

  // Only continue animation if the input is empty and not focused
  if (whispererInput.value === '' && document.activeElement !== whispererInput)
    setTimeout(type, typingDelay);
}

// Start the animation
setTimeout(type, 1000);

// Restart animation if input is cleared and blurred
whispererInput.addEventListener('blur', () => {

```

```

    if (whispererInput.value === '') {
      setTimeout(type, 500);
    }
  });

  // --- Spark Button Logic ---
  sparkBtn.addEventListener('click', () => {
    const answer = whispererInput.value.trim();
    if (!answer) {
      // If empty, just focus the input to prompt the user to type
      whispererInput.focus();
      whispererInput.style.borderBottomColor = '#ff4444';
      setTimeout(() => { whispererInput.style.borderBottomColor = 'rgba(0, 200, 200, 0.5)'; }, 500);
      return;
    }

    // Transfer the answer to the main goal box
    const mainGoalInput = document.querySelector('.pmgv3-goal-input');
    if (mainGoalInput) {
      mainGoalInput.value = answer;
    }

    // Trigger the Analyze My Idea flow automatically
    const analyzeBtn = document.querySelector('.pmgv3-analyze-btn');
    if (analyzeBtn) {
      analyzeBtn.click();
    }
  });

  // Allow pressing Enter in the whisperer input to trigger Spark
  whispererInput.addEventListener('keydown', (e) => {
    if (e.key === 'Enter') {
      e.preventDefault();
      sparkBtn.click();
    }
  });
}

document.addEventListener('DOMContentLoaded', initWhisperer);

```