

PromptMeGood Comprehensive Repair Brief

CORE OBJECTIVE

The live site is suffering from severe layout regressions, script conflicts, and broken features. This brief provides the exact fixes needed to restore stability, fix the Auto-Boost placement, and clean up the script architecture.

NON-NEGOTIABLE RULES

- Do NOT rebuild the chassis or change the core layout structure.
- Do NOT remove the Auto-Boost feature.
- Apply these specific fixes to resolve the conflicts.

BUG 1: AUTO-BOOST BUTTON FLOATING OUTSIDE RESULT PANEL

The Problem:

The "✨ Auto-Boost Prompt" button is floating at the top of the right column, completely disconnected from the result panel. This is caused by a conflict between `pmg-auto-boost.js` (which mounts the button as a sibling of the strength slot) and `pmg-auto-boost.css` (which tries to force it visible even when the parent `.output-box` is collapsed).

The Fix:

1. In `pmg-auto-boost.js` : Change the `mountTarget` for the text suite so the button mounts *inside* the result panel, right next to the "Run With AI" and "Copy" buttons.
 - Locate `SUITES.text.mountTarget` in `pmg-auto-boost.js` .
 - Change it to return the actions row or the copy button: `return document.getElementById('copy-btn');`
2. In `pmg-auto-boost.css` : Remove the hacky CSS that forces the button to be visible when its parent is collapsed. The button should only be visible when the result panel is visible.
 - Remove these lines:

CSS

```
html.pmg-chassis-v3 #pmg-ab-btn-text {  
  display: inline-flex !important;
```

```
visibility: visible !important;
}
html.pmg-chassis-v3 .output-box.is-collapsed #pmg-ab-btn-text {
  display: inline-flex !important;
  margin: 8px 0 4px;
}
```



BUG 2: NATIVE ALERT() DIALOGS BLOCKING UX

The Problem:

There are 4 instances of native browser `alert()` calls in `index.html` (lines 9318, 9322, 9468, 9527) for things like "Your prompt is too long" or "Generate a prompt first". These block the UI and feel unpolished.

The Fix:

Replace all `alert()` calls with the existing `toast()` notification system or inline error messages.



BUG 3: CHASSIS POLLING LOOPS AND FORCE-HIDES

The Problem:

`pmg-chassis-v3.js` uses 8 `setInterval` polling loops and force-hides legacy elements using `!important`. This creates race conditions and performance issues.

The Fix:

Refactor the chassis initialization to rely on `DOMContentLoaded` and `MutationObservers` instead of aggressive polling. Remove the `!important` force-hides if the elements can be properly managed by state classes (like `pmg-has-result`).



IMPLEMENTATION STEPS

1. Apply the JS mount target fix to `pmg-auto-boost.js`.
2. Apply the CSS cleanup to `pmg-auto-boost.css`.
3. Replace `alert()` calls in `index.html`.
4. Optimize `pmg-chassis-v3.js` polling.