

PMG Deferred Items Spec — Save Button, Overwrite Confirm, Contact Modal

Project: PromptMeGood (PMG)

Target: July 1, 2026 Launch

Files touched: `app.html` , `pmg-save-result.js` , `pmg-contact-modal.js`

⚠ Pre-Execution Audit Checklist

Before writing any code, Replit MUST verify the following. **Do not break any existing functionality.**

- ☐ Confirm `pmg-save-result.js` exists and handles the `pmg-save-prompt-btn` injection.
- ☐ Confirm `pmg-save-result.js` has the `showAiSaveConfirm` function for the "Replace / Save as New / Cancel" flow.
- ☐ Confirm `pmg-contact-modal.js` exists and intercepts clicks via `isContactHref` .
- ☐ Confirm `app.html` has the `.pmg-result-actions-row` around line 5228.
- ☐ Confirm `app.html` has `support@promptmegood.com` links in the footer (e.g., lines 5593, 5669, 5671, 5695).

1. Explicit "Save Prompt" Button in Built-Prompt Area

Context: The `pmg-save-result.js` script already injects a  Save Prompt button into the `.pmg-result-actions-row` dynamically. However, to ensure it's always present and doesn't suffer from layout shift or script-loading delays, we want to hardcode it into `app.html` alongside the other action buttons.

Implementation:

Find the `.pmg-result-actions-row` in `app.html` (around line 5228). Add the hardcoded `<button>` right after the "Copy Prompt" button:

HTML

```
<div class="actions-row pmg-result-actions-row" data-pmg-empty="1">
  <button class="btn btn-primary" type="button" id="copy-btn" disab
  <!-- NEW: Hardcoded Save Prompt button -->
  <button class="btn btn-secondary" type="button" id="pmg-save-prom
  <button class="btn btn-secondary" type="button" id="download-prom
```

```

<button class="btn btn-secondary" type="button" id="share-btn" hi
<button class="btn btn-secondary" type="button" id="print-btn" di
<button class="btn btn-secondary btn-clear btn-destructive" type=
<span class="pmg-vault-saved-indicator" id="pmg-vault-saved-indic
</div>

```

Update `pmg-save-result.js` :

Modify `injectSavePromptButton()` to attach the click listener to the hardcoded button instead of creating a new one:

JavaScript

```

function injectSavePromptButton() {
  var btn = document.getElementById('pmg-save-prompt-btn');
  if (!btn) return false;

  // Prevent attaching multiple listeners if called repeatedly
  if (btn.dataset.listenerAttached) return true;

  btn.addEventListener('click', function () { handleSavePromptClick(btn); });
  btn.dataset.listenerAttached = 'true';

  // Mirror the disabled-until-result behavior of #copy-btn.
  function syncDisabled() {
    var hasPrompt = !!getCurrentPrompt();
    btn.disabled = !hasPrompt;
    btn.setAttribute('aria-disabled', hasPrompt ? 'false' : 'true');
  }
  syncDisabled();
  var box = document.getElementById('resultBox');
  if (box) {
    var mo = new MutationObserver(syncDisabled);
    mo.observe(box, { childList: true, characterData: true, subtree: true });
  }
  return true;
}

```

2. Overwrite Confirmation for AI Results

Context: When a user clicks "Save to Vault" on an AI result, and that prompt already has a saved AI result, `pmg-save-result.js` currently shows an inline confirm popover ("Replace / Save as New / Cancel"). We need to ensure the wording explicitly asks "Replace previous AI result?".

Implementation:

In `pmg-save-result.js`, find the `showAiSaveConfirm` function. Update the `msg.textContent` to explicitly ask the required question:

JavaScript

```
function showAiSaveConfirm(anchorBtn, prompt, aiResponse, existingCount) {
  var pop = document.createElement('div');
  pop.className = 'pmg-save-confirm';
  var msg = document.createElement('div');
  msg.className = 'pmg-save-confirm__msg';
  // NEW: Explicitly ask to replace previous AI result
  msg.textContent = 'This prompt already has ' + existingCount + ' saved AI r
  pop.appendChild(msg);

  var row = document.createElement('div');
  row.className = 'pmg-save-confirm__row';

  // Update button text for clarity
  var bReplace = makeBtn('Replace Previous', 'primary');
  var bNew = makeBtn('Save as New', 'secondary');
  var bCancel = makeBtn('Cancel', 'cancel');

  // ... rest of the function remains the same
```

3. Contact Modal Trigger for `support@promptmegood.com`

Context: The contact modal currently intercepts clicks on links ending in `contact.html`. We need it to also intercept clicks on `mailto:support@promptmegood.com` or any link containing that email address.

Implementation:

In `pmg-contact-modal.js`, update the `isContactHref` function to also match the support email:

JavaScript

```
function isContactHref(href) {
  if (!href) return false;
  var s = href.trim();
  if (!s || s.charAt(0) === '#') return false;

  // Match: /contact.html, ./contact.html, contact.html, https://.../contact..
  var isContactPage = /^(^|\/)contact\.html(?:[?#].*)?$/i.test(s);

  // NEW: Match mailto:support@promptmegood.com or just the email address
  var isSupportEmail = s.toLowerCase().indexOf('support@promptmegood.com') !== -1;
```

```
return isContactPage || isSupportEmail;  
}
```

Update `app.html` Footer Links:

Ensure all `support@promptmegood.com` text in the footer is wrapped in an `<a>` tag with `href="mailto:support@promptmegood.com"` (or `/contact.html` as it currently is). The updated `isContactHref` will catch both.

Example (around line 5593):

HTML

```
<p class="site-footer-contact"><a class="site-footer-link" href="mailto:support
```

(Update any other instances in the footer to use the `mailto:` link for semantic correctness, knowing the JS will intercept it and open the modal instead).

✓ Post-Execution Verification Checklist

- ☐ `app.html` has the hardcoded  Save Prompt button next to "Copy Prompt".
- ☐ Clicking  Save Prompt successfully saves the prompt to the Vault.
- ☐ Saving an AI result for a prompt that already has one shows the "Replace previous AI result?" confirmation.
- ☐ Clicking any `support@promptmegood.com` link in the footer opens the Contact Modal instead of the default mail client.
- ☐ No existing functionality is broken.