

PromptMeGood — DEFINITIVE REDESIGN COMMAND

For Replit AI — Read Every Word. Do Not Improvise.

PRIME DIRECTIVE

You are restructuring the PromptMeGood workstation for **maximum user flow efficiency and minimum cognitive load**. You are NOT mimicking the current layout. You are IMPROVING it. This means you will move elements, delete elements, and reorganize the DOM significantly. Do NOT preserve the current layout "as-is." The goal is a clean, guided, step-by-step experience where the next action is always obvious.

Do NOT touch any JavaScript generation logic, API calls, localStorage, or prompt-building functions. Only touch HTML structure and CSS layout/positioning.

STEP 0 — DELETE THESE ELEMENTS ENTIRELY

Remove the following from the DOM completely. No hiding with `display:none`. Delete the HTML, delete the associated JavaScript event listeners, delete the associated CSS classes.

1. **"Help Me Get Started" button** — any button with text containing "Help Me", "Get Started", "Help Me Start", or similar onboarding wizard triggers.
 2. **The guided question modal/flow** — any modal, drawer, or overlay that asks the user a series of questions to help them get started. The entire multi-step onboarding wizard is gone.
 3. **Any duplicate "Your Fixed Prompt Will Appear Here" placeholder boxes** — keep only ONE output box (see Step 3 for its exact location and markup).
 4. **Any "Shortcuts" info box** — the box showing keyboard shortcut hints (G to fix, C to copy, / to search). Remove it from the visible UI. Keyboard shortcuts can remain functional but the hint box is deleted.
 5. **Any "Free tier with daily limits" or pricing copy inside the workstation** — this belongs on the landing/pricing page, not inside the tool.
 6. **The "Help Me Start" pill or any pill that triggers the onboarding wizard.**
-

STEP 1 — THE WORKSTATION SHELL (The Chassis)

Overall Page Structure

The workstation page (`/app` route) must use this exact CSS grid layout:

CSS

```
body.app-page {
  display: flex;
  flex-direction: column;
  height: 100vh;
  overflow: hidden;
  background: #0d2b1e;
}

.topbar {
  height: 52px;
  flex-shrink: 0;
  display: flex;
  align-items: center;
  justify-content: space-between;
  padding: 0 20px;
  background: #0a2218;
  border-bottom: 1px solid rgba(0,200,150,0.15);
  z-index: 50;
}

.module-tabs {
  height: 44px;
  flex-shrink: 0;
  display: flex;
  align-items: center;
  gap: 4px;
  padding: 0 20px;
  background: #0a2218;
  border-bottom: 1px solid rgba(0,200,150,0.1);
}

.workstation-body {
  flex: 1;
  display: grid;
  grid-template-columns: 1fr 1fr;
  gap: 16px;
  padding: 16px;
  overflow: hidden;
}

.left-column {
```

```

display: flex;
flex-direction: column;
gap: 12px;
overflow-y: auto;
padding-right: 8px;
}

.right-column {
display: flex;
flex-direction: column;
gap: 12px;
overflow-y: auto;
}

.bottom-bar {
height: 64px;
flex-shrink: 0;
display: flex;
align-items: center;
padding: 0 16px;
background: #0a2218;
border-top: 1px solid rgba(0,200,150,0.15);
}

.mobile-tab-bar {
display: none; /* shown only on mobile – see mobile section */
}

```

STEP 2 — THE TOP BAR

The topbar contains exactly these elements, left to right:

Plain Text

[PromptMeGood Logo + wordmark] [Vault icon] [Settings icon] [Upgrade button]

- Logo on the far left.
- Vault icon () , Settings icon () , and Upgrade button on the far right.
- **Remove** any pricing copy, beta banners, or shortcut hints from the topbar.
- The beta badge (if it exists) can remain as a small pill on the logo only.

STEP 3 — THE MODULE TABS (Below the Topbar)

Three tabs, full-width row, directly below the topbar:

HTML

```
<div class="module-tabs">
  <button class="module-tab active" data-module="text">🗒️ Text Prompts</button>
  <button class="module-tab" data-module="photography">📷 Photography</button>
  <button class="module-tab" data-module="video">🎬 Video</button>
</div>
```

CSS for tabs:

CSS

```
.module-tab {
  padding: 8px 20px;
  border-radius: 20px;
  border: 1px solid transparent;
  background: transparent;
  color: rgba(255, 255, 255, 0.5);
  font-size: 14px;
  cursor: pointer;
  transition: all 0.2s;
}

.module-tab.active {
  background: rgba(0, 200, 150, 0.15);
  border-color: #00c896;
  color: #00c896;
  font-weight: 600;
}
```

Switching tabs shows/hides the relevant left-column content. The right column (output area) resets when switching tabs.

STEP 4 — THE LEFT COLUMN (The Input + Tuning Engine)

The left column is a **top-to-bottom guided flow**. The user reads from top to bottom. Each section flows naturally into the next. Here is the exact order of elements from TOP to BOTTOM:

4A. IDEA INPUT (TOP of left column — first thing user sees)

HTML

```

<div class="idea-section">
  <label class="section-label">Your Idea</label>
  <p class="section-hint">Describe what you want to create. Be as brief or deta
  <textarea id="goal" class="idea-textarea"
    placeholder="e.g. I want to write a LinkedIn post about my new product laun
  </textarea>
  <button id="analyze-btn" class="btn-analyze">→ Analyze My Idea</button>
</div>

```

CSS:

CSS

```

.idea-textarea {
  width: 100%;
  min-height: 100px;
  max-height: 160px;
  resize: vertical;
  background: rgba(255,255,255,0.05);
  border: 1px solid rgba(0,200,150,0.3);
  border-radius: 10px;
  padding: 12px;
  color: #fff;
  font-size: 15px;
  line-height: 1.5;
}

.btn-analyze {
  width: 100%;
  padding: 12px;
  background: #00c896;
  color: #0d2b1e;
  font-weight: 700;
  border-radius: 10px;
  border: none;
  font-size: 15px;
  cursor: pointer;
  margin-top: 8px;
}

```

IMPORTANT: When the user clicks "→ Analyze My Idea", the system reads the textarea content and **auto-selects the most relevant pills** in the tuning section below. This is the existing "Fix My Prompt" logic — just triggered from this button instead. The textarea ID remains `#goal` to preserve all existing JavaScript.

4B. PROMPT TUNING (Middle of left column — appears after Analyze)

This section is **hidden by default** and slides into view after the user clicks "→ Analyze My Idea."

HTML

```
<div class="tuning-section" id="tuning-panel" style="display:none;">

  <div class="tuning-header">
    <span class="tuning-title">🔧 Tune Your Prompt</span>
    <span class="tuning-hint">We've pre-selected settings based on your idea. A
  </div>

  <!-- CATEGORY PILLS — move existing category pills here -->
  <div class="pill-group">
    <label class="pill-label">Category</label>
    <div class="pill-row" id="category-pills">
      <!-- All existing category pills go here, unchanged -->
    </div>
  </div>

  <!-- TONE PILLS — move existing tone pills here -->
  <div class="pill-group">
    <label class="pill-label">Tone</label>
    <div class="pill-row" id="tone-pills">
      <!-- All existing tone pills go here, unchanged -->
    </div>
  </div>

  <!-- FORMAT PILLS — move existing format pills here -->
  <div class="pill-group">
    <label class="pill-label">Format</label>
    <div class="pill-row" id="format-pills">
      <!-- All existing format pills go here, unchanged -->
    </div>
  </div>

  <!-- LENGTH PILLS — move existing length pills here -->
  <div class="pill-group">
    <label class="pill-label">Length</label>
    <div class="pill-row" id="length-pills">
      <!-- All existing length pills go here, unchanged -->
    </div>
  </div>

  <!-- PERSONALITY PILLS — move existing personality pills here if they exist -
  <div class="pill-group">
```

```

    <label class="pill-label">Personality</label>
    <div class="pill-row" id="personality-pills">
      <!-- All existing personality pills go here, unchanged -->
    </div>
  </div>

  <!-- LANGUAGE PILLS – move existing language pills here if they exist -->
  <div class="pill-group">
    <label class="pill-label">Language</label>
    <div class="pill-row" id="language-pills">
      <!-- All existing language pills go here, unchanged -->
    </div>
  </div>

</div>

```

CSS for pill groups:

CSS

```

.pill-group {
  margin-bottom: 12px;
}

.pill-label {
  display: block;
  font-size: 11px;
  font-weight: 600;
  text-transform: uppercase;
  letter-spacing: 0.08em;
  color: rgba(0,200,150,0.7);
  margin-bottom: 6px;
}

.pill-row {
  display: flex;
  flex-wrap: wrap;
  gap: 6px;
}

/* Existing pill styles remain unchanged – just ensure they use these base clas

```

4C. GENERATE PROMPT BUTTON (Bottom of left column — always the last item)

This is the **final action in the left column**. It must be the last element, visually anchored at the bottom of the tuning section.

HTML

```
<div class="generate-section" id="generate-section" style="display:none;">
  <div class="generate-divider"></div>
  <button id="fix-prompt-btn" class="btn-generate">
    ✨ Done Tuning – Generate My Prompt
  </button>
</div>
```

CSS:

CSS

```
.btn-generate {
  width: 100%;
  padding: 14px;
  background: linear-gradient(135deg, #00c896, #00a878);
  color: #0d2b1e;
  font-weight: 800;
  font-size: 16px;
  border-radius: 12px;
  border: none;
  cursor: pointer;
  box-shadow: 0 4px 20px rgba(0,200,150,0.3);
  transition: all 0.2s;
}

.btn-generate:hover {
  transform: translateY(-1px);
  box-shadow: 0 6px 24px rgba(0,200,150,0.4);
}
```

IMPORTANT: This button calls the **exact same function** that the existing "Fix My Prompt" button calls. Do NOT rewrite the generation logic. Just wire this button to the same handler. The existing `#fix-prompt-btn` ID can be reused if that is what the existing JS listens for.

STEP 5 — THE RIGHT COLUMN (The Output Area)

The right column contains two boxes stacked vertically. Both start empty/hidden and appear progressively as the user completes each step.

5A. BOX 1 — THE GENERATED PROMPT (Top of right column)

This box is **hidden by default** and appears after the user clicks "Generate My Prompt."

HTML

```
<div class="output-box" id="prompt-output-box" style="display:none;">

  <!-- PROMPT STRENGTH SCORE — at the very top of Box 1 -->
  <div class="strength-bar-container">
    <div class="strength-header">
      <span class="strength-label">Prompt Strength</span>
      <span class="strength-score" id="strength-score-badge">--</span>
    </div>
    <div class="strength-track">
      <div class="strength-fill" id="strength-fill" style="width:0%"></div>
    </div>
    <div class="strength-status" id="strength-status">Analyzing...</div>
  </div>

  <!-- THE GENERATED PROMPT TEXT — editable -->
  <label class="section-label" style="margin-top:12px;">Your Engineered Prompt<
  <textarea id="output" class="prompt-output-textarea"
    placeholder="Your generated prompt will appear here...">
  </textarea>

  <!-- PROMPT ACTION BUTTONS -->
  <div class="prompt-actions">
    <button class="btn-secondary" id="edit-prompt-btn"><img alt="pencil icon" data-bbox="675 565 695 585"/> Edit</button>
    <button class="btn-secondary" id="rewrite-btn"><img alt="refresh icon" data-bbox="630 585 650 605"/> Rewrite</button>
    <button class="btn-secondary" id="save-draft-btn"><img alt="save icon" data-bbox="660 605 680 625"/> Save Draft</button>
  </div>

  <!-- NEXT STEP PROMPT -->
  <div class="next-step-divider">
    <span>Happy with your prompt?</span>
  </div>

  <!-- PRIMARY: RUN WITH AI -->
  <button class="btn-run-primary" id="run-with-ai-btn">
    ▶ Run with AI to see your result
  </button>

  <!-- SECONDARY: SEND TO PLATFORM BUTTONS -->
  <div class="send-to-row">
    <button class="btn-send-to" data-platform="chatgpt">
       Send to ChatGPT
    </button>
```

```
<button class="btn-send-to" data-platform="claude">
   Send to Claude
</button>
<button class="btn-send-to" data-platform="gemini">
   Send to Gemini
</button>
</div>

</div>
```

CSS for Box 1:

CSS

```
.output-box {
  background: rgba(255,255,255,0.04);
  border: 1px solid rgba(0,200,150,0.2);
  border-radius: 14px;
  padding: 16px;
}

.strength-track {
  height: 8px;
  background: rgba(255,255,255,0.1);
  border-radius: 4px;
  overflow: hidden;
  margin: 6px 0;
}

.strength-fill {
  height: 100%;
  background: linear-gradient(90deg, #f0c040, #00c896);
  border-radius: 4px;
  transition: width 0.8s ease;
}

.strength-score {
  font-size: 22px;
  font-weight: 800;
  color: #00c896;
}

.strength-status {
  font-size: 12px;
  color: #00c896;
  font-weight: 600;
}
```

```
.prompt-output-textarea {
  width: 100%;
  min-height: 140px;
  background: rgba(0,0,0,0.2);
  border: 1px solid rgba(0,200,150,0.2);
  border-radius: 10px;
  padding: 12px;
  color: #fff;
  font-size: 14px;
  line-height: 1.6;
  resize: vertical;
}
```

```
.prompt-actions {
  display: flex;
  gap: 8px;
  margin-top: 10px;
}
```

```
.btn-secondary {
  flex: 1;
  padding: 8px;
  background: transparent;
  border: 1px solid rgba(0,200,150,0.4);
  border-radius: 8px;
  color: #00c896;
  font-size: 13px;
  cursor: pointer;
}
```

```
.next-step-divider {
  text-align: center;
  color: rgba(255,255,255,0.4);
  font-size: 13px;
  margin: 14px 0 10px;
  position: relative;
}
```

```
.next-step-divider::before,
.next-step-divider::after {
  content: '';
  position: absolute;
  top: 50%;
  width: 30%;
  height: 1px;
  background: rgba(255,255,255,0.1);
}
```

```

.next-step-divider::before { left: 0; }
.next-step-divider::after { right: 0; }

.btn-run-primary {
  width: 100%;
  padding: 14px;
  background: #00c896;
  color: #0d2b1e;
  font-weight: 800;
  font-size: 15px;
  border-radius: 12px;
  border: none;
  cursor: pointer;
}

.send-to-row {
  display: flex;
  gap: 8px;
  margin-top: 10px;
}

.btn-send-to {
  flex: 1;
  padding: 8px 6px;
  background: transparent;
  border: 1px solid rgba(255,255,255,0.15);
  border-radius: 8px;
  color: rgba(255,255,255,0.7);
  font-size: 12px;
  cursor: pointer;
  display: flex;
  align-items: center;
  justify-content: center;
  gap: 4px;
}

```

Send To Button Logic:

JavaScript

```

document.querySelectorAll('.btn-send-to').forEach(btn => {
  btn.addEventListener('click', () => {
    const prompt = document.getElementById('output').value;
    const platform = btn.dataset.platform;
    const encoded = encodeURIComponent(prompt);

    const urls = {
      chatgpt: `https://chatgpt.com/?q=${encoded}`,
    }
  })
})

```

```

    claude: `https://claude.ai/new?q=${encoded}`,
    gemini: `https://gemini.google.com/app?q=${encoded}`
  };

  // Copy to clipboard as fallback
  navigator.clipboard.writeText(prompt );

  // Open platform in new tab
  window.open(urls[platform], '_blank');
});
});

```

5B. BOX 2 — THE AI RESPONSE (Below Box 1 in right column)

This box is **hidden by default** and appears ONLY after the user clicks "► Run with AI to see your result."

HTML

```

<div class="output-box ai-response-box" id="ai-response-box" style="display:none">

  <div class="ai-response-header">
    <span class="ai-response-title">✨ AI Result</span>
    <span class="ai-response-model">GPT-4o</span>
  </div>

  <!-- AI RESPONSE TEXT – streaming output goes here -->
  <div class="ai-response-content" id="ai-response-content">
    <!-- Streaming text appears here -->
  </div>

  <!-- FINAL ACTION BUTTONS – appear after streaming completes -->
  <div class="ai-response-actions" id="ai-response-actions" style="display:none">
    <button class="btn-download" id="download-btn">⬇️ Download</button>
    <button class="btn-save-vault" id="save-vault-btn">🗄️ Save to Vault</button>
    <button class="btn-share" id="share-btn">➦ Share</button>
    <button class="btn-copy-result" id="copy-result-btn">📋 Copy</button>
  </div>

</div>

```

Show/Hide Logic for Box 2:

JavaScript

```
document.getElementById('run-with-ai-btn').addEventListener('click', () => {
  const box = document.getElementById('ai-response-box');
  box.style.display = 'block';
  box.scrollIntoView({ behavior: 'smooth', block: 'start' });
  // Existing AI generation logic fires here – do NOT rewrite it
  // Just ensure the result streams into #ai-response-content
  // And show #ai-response-actions when streaming is complete
});
```

STEP 6 — PHOTOGRAPHY MODULE (Tab 2)

When the user clicks the "📷 Photography" tab, the left column shows this content instead of the Text tuning:

Left Column — Photography (same top-to-bottom flow):

Plain Text

```
[Your Image Idea textarea] (#photo-goal)
[→ Analyze My Idea button]
  ↓ (after analyze)
[Tuning: Style pills]
[Tuning: Camera & Lens pills]
[Tuning: Lighting pills]
[Tuning: Aperture pills – f/1.4, f/1.8, f/2.8, f/4, f/8, f/11]
[Tuning: Shutter Speed pills – 1/1000s, 1/500s, 1/250s, 1s, 5s, 30s]
[Tuning: ISO pills – 100, 400, 800, 1600, 3200]
[Tuning: Film Stock pills – Kodak Portra 400, Fuji Velvia, Kodak Tri-X, Digital]
[Tuning: Composition pills – Rule of Thirds, Centered, Leading Lines, Symmetry]
[✨ Done Tuning – Generate My Image Prompt button]
```

Right Column — Photography:

- Box 1: Generated image prompt (editable textarea) + Prompt Strength Score
- Send To buttons: [Send to Midjourney] [Send to DALL-E] [Send to Firefly]
- Run with AI button: Generates image in-house via DALL-E 3 API
- Box 2: Generated image (img tag, appears after Run with AI)
- Final actions: [ Download Image] [ Save to Vault] [ Share]

STEP 7 — VIDEO MODULE (Tab 3)

When the user clicks the "🎬 Video" tab, the left column shows:

Left Column — Video (same top-to-bottom flow):

Plain Text

```
[Your Video Concept textarea] (#video-goal)
[→ Analyze My Idea button]
  ↓ (after analyze)
[Tuning: Scene Type pills – Cinematic, Documentary, Animation, Product Demo, Ta
[Tuning: Motion pills – Static, Slow Pan, Tracking Shot, Handheld, Drone]
[Tuning: Duration pills – 5s, 10s, 15s, 30s, 60s]
[Tuning: Mood pills – Epic, Calm, Dramatic, Playful, Mysterious]
[Tuning: Aspect Ratio pills – 16:9, 9:16, 1:1, 4:3]
[Tuning: Platform pills – Sora, Runway ML, Pika, Kling]
[✨ Done Tuning – Generate My Video Prompt button]
```

Right Column — Video:

- Box 1: Generated video prompt (editable textarea) + Prompt Strength Score
- Send To buttons (platform-specific based on pill selection):
 - [Open in Sora] [Open in Runway] [Open in Pika]
- **NO "Run with AI" in-house button for Video** — video generation is not in-house
- Box 2: Replaced with a styled info card: "Your prompt is ready. Click your platform above to generate your video."
- Final actions: [ Copy Prompt] [ Save to Vault] [ Download .txt]

STEP 8 — THE BOTTOM BAR

The bottom bar is a **persistent quick-entry** bar fixed to the bottom of the screen. It is always visible regardless of scroll position.

HTML

```
<div class="bottom-bar">
  <div class="quick-entry-pill">
    <span class="quick-entry-icon">✏️</span>
    <input type="text" id="quick-entry" placeholder="What do you want to build?"
    <button id="quick-entry-submit" class="quick-entry-btn">▲</button>
  </div>
</div>
```

Quick Entry Logic: When the user types in the quick entry bar and presses Enter or clicks ▲, the text is copied into the #goal textarea of the active module tab, and the "→ Analyze My Idea" button is automatically triggered. This is a shortcut to Step 4A — it does not bypass tuning.

STEP 9 — MOBILE LAYOUT

On screens 768px and below, the two-column layout collapses to single column with a bottom tab bar.

CSS

```
@media (max-width: 768px) {  
  .workstation-body {  
    grid-template-columns: 1fr;  
    overflow-y: auto;  
    padding-bottom: 120px; /* space for bottom bar + tab bar */  
  }  
  
  .right-column {  
    /* Right column stacks below left column on mobile */  
  }  
  
  .mobile-tab-bar {  
    display: flex;  
    position: fixed;  
    bottom: 64px; /* above the bottom bar */  
    left: 0;  
    right: 0;  
    height: 52px;  
    background: #0a2218;  
    border-top: 1px solid rgba(0,200,150,0.15);  
    justify-content: space-around;  
    align-items: center;  
    z-index: 100;  
  }  
  
  .mobile-tab-btn {  
    flex: 1;  
    display: flex;  
    flex-direction: column;  
    align-items: center;  
    font-size: 10px;  
    color: rgba(255,255,255,0.5);  
    gap: 2px;  
    cursor: pointer;  
  }  
}
```



```
padding: 6px 0;
}

.mobile-tab-btn.active {
  color: #00c896;
}
}
```

Mobile tab bar buttons: [ Vault] [ Workstation] [ Visual]

STEP 10 — THE VAULT (Accessible via Vault tab or icon)

The Vault is a **separate view**, not a column. When the user clicks the Vault icon or tab, the workstation body is replaced with the Vault view. The Vault shows:

- A search/filter bar at the top
- Filter pills: [All] [Text] [Photography] [Video]
- A grid of saved prompt cards, each showing:
 - The prompt title (first 60 chars)
 - Module tag (Text / Photography / Video)
 - Tuning summary (e.g., "Professional • Social Media • Short")
 - Date saved
 - [Copy] [Run Again] [Delete] buttons

STEP 11 — JAVASCRIPT SHOW/HIDE FLOW CONTROLLER

Add this JavaScript to control the progressive reveal of sections. This is NEW JavaScript — it does not replace any existing generation logic.

JavaScript

```
// Progressive reveal controller
const analyzeBtn = document.getElementById('analyze-btn');
const tuningPanel = document.getElementById('tuning-panel');
const generateSection = document.getElementById('generate-section');
const promptOutputBox = document.getElementById('prompt-output-box');
const aiResponseBox = document.getElementById('ai-response-box');
const aiResponseActions = document.getElementById('ai-response-actions');

// Step 1 → Step 2: Show tuning after Analyze
analyzeBtn.addEventListener('click', () => {
```

```

// Auto-prefill pills based on textarea content (existing logic)
// Then show tuning panel
tuningPanel.style.display = 'block';
generateSection.style.display = 'block';
tuningPanel.scrollToView({ behavior: 'smooth', block: 'start' });
});

// Step 2 → Step 3: Show Box 1 after Generate
// Wire to existing fix-prompt-btn handler
const originalFixHandler = document.getElementById('fix-prompt-btn').onclick;
document.getElementById('fix-prompt-btn').addEventListener('click', () => {
  // Existing generation logic fires
  // Then reveal Box 1
  setTimeout(() => {
    promptOutputBox.style.display = 'block';
    promptOutputBox.scrollToView({ behavior: 'smooth', block: 'start' });
  }, 300);
});

// Step 3 → Step 4: Show Box 2 after Run with AI
document.getElementById('run-with-ai-btn').addEventListener('click', () => {
  aiResponseBox.style.display = 'block';
  aiResponseBox.scrollToView({ behavior: 'smooth', block: 'start' });
  // Existing AI run logic fires here
  // When streaming completes, show action buttons:
  // aiResponseActions.style.display = 'flex';
});

```

STEP 12 — WHAT NOT TO TOUCH

The following must remain completely unchanged:

1. All prompt generation API calls and logic
2. All localStorage read/write operations for the Vault
3. All existing prompt strength scoring logic — just wire its output to `#strength-fill` width and `#strength-score-badge` text
4. All existing "Rewrite" and "Refine" button logic
5. All existing Download and Share functionality
6. The `#goal` textarea ID — this is the anchor for all existing JS
7. The `#output` textarea ID — this is where the generated prompt is written
8. All existing CSS color variables (`--pmg-*`)

ACCEPTANCE CRITERIA

Before marking this complete, verify:

- ☐ "Help Me Get Started" and all onboarding wizard elements are deleted from DOM
- ☐ The workstation loads with ONLY the Idea textarea visible — no tuning pills visible on load
- ☐ Clicking "→ Analyze My Idea" reveals the tuning panel with pre-selected pills
- ☐ The "Generate My Prompt" button is the LAST element in the left column
- ☐ Box 1 (Generated Prompt) is hidden on load and appears after Generate is clicked
- ☐ Box 2 (AI Response) is hidden on load and appears ONLY after "Run with AI" is clicked
- ☐ "Send to ChatGPT/Claude/Gemini" buttons open the correct URLs with the prompt pre-filled
- ☐ Prompt Strength Score bar animates to the correct width when Box 1 appears
- ☐ Photography tab shows photography-specific tuning pills (Aperture, ISO, Film Stock, etc.)
- ☐ Video tab shows video-specific tuning pills and NO in-house Run button
- ☐ Mobile layout is single column with bottom tab bar
- ☐ The bottom quick-entry bar is fixed and always visible
- ☐ No duplicate output boxes exist anywhere in the DOM
- ☐ No pricing copy or shortcut hint boxes exist inside the workstation

End of PromptMeGood Definitive Redesign Command

Version: FINAL — Do not modify without owner approval