

Replit Fix Brief: Photography Suite UX Restructure

Replit, we need to fix a critical UX issue in the Photography Suite. Currently, the "Upload & Edit" and "Reverse Engineer" features are taking center stage, which creates friction for the 80% of users who just want to create an image from scratch using a text prompt.

We need to restructure the Photography Suite to use a **sub-tab system**.

CRITICAL REQUIREMENT: Do not delete any existing functionality. We are simply reorganizing the layout so that "Create" is the default view, and the other tools are moved to secondary tabs.

1. The New Sub-Tab UI (HTML)

Inject this HTML at the very top of the Photography Suite container (`#pmg-photo-suite`), right below the main suite header.

HTML

```
<div class="pmgv3-photo-subtabs">
  <button class="photo-subtab active" data-mode="create">🌟 Create New</button>
  <button class="photo-subtab" data-mode="edit">📷 Edit Photo</button>
  <button class="photo-subtab" data-mode="reverse">🔍 Reverse Engineer</button>
</div>
```

2. Reorganizing the Content Containers

You need to wrap the existing sections of the Photography Suite into three distinct containers that correspond to the sub-tabs.

HTML

```
<!-- 1. The Create Container (Default Active) -->
<div class="photo-mode-container active" id="photo-mode-create">
  <!-- MOVE ALL EXISTING PROMPT BUILDER ELEMENTS HERE -->
  <!-- This includes the goal input, pill accordions, lighting studio, and Gene
</div>

<!-- 2. The Edit Container (Hidden by Default) -->
<div class="photo-mode-container" id="photo-mode-edit" style="display: none;">
  <!-- MOVE ALL EXISTING UPLOAD & EDIT ELEMENTS HERE -->
  <!-- This includes the file upload zone, edit instructions, and related butto
</div>
```

```

<!-- 3. The Reverse Engineer Container (Hidden by Default) -->
<div class="photo-mode-container" id="photo-mode-reverse" style="display: none;
  <!-- MOVE ALL EXISTING REVERSE ENGINEER ELEMENTS HERE -->
  <!-- This includes the image upload for analysis and the extraction output ar
</div>

```

3. The Tab Switching Logic (JavaScript)

Add this logic to `pmg-visual-studio.js` to handle switching between the three modes.

JavaScript

```

function initPhotoSubTabs() {
  const subTabs = document.querySelectorAll('.photo-subtab');
  const containers = document.querySelectorAll('.photo-mode-container');

  subTabs.forEach(tab => {
    tab.addEventListener('click', () => {
      // Remove active class from all tabs and containers
      subTabs.forEach(t => t.classList.remove('active'));
      containers.forEach(c => {
        c.classList.remove('active');
        c.style.display = 'none';
      });

      // Add active class to clicked tab
      tab.classList.add('active');

      // Show the corresponding container
      const targetMode = tab.getAttribute('data-mode');
      const targetContainer = document.getElementById(`photo-mode-${targetMode}`);
      if (targetContainer) {
        targetContainer.classList.add('active');
        targetContainer.style.display = 'block';
      }
    });
  });

  // Initialize when DOM is ready
  document.addEventListener('DOMContentLoaded', initPhotoSubTabs);
}

```

4. CSS Styling

Add these styles to `pmg-visual-studio.css` to make the sub-tabs look clean and integrated.

CSS

```
.pmgv3-photo-subtabs {
  display: flex;
  gap: 8px;
  margin-bottom: 24px;
  background: rgba(0, 0, 0, 0.2);
  padding: 6px;
  border-radius: 12px;
  border: 1px solid rgba(255, 255, 255, 0.05);
}

.photo-subtab {
  flex: 1;
  background: transparent;
  border: none;
  color: rgba(255, 255, 255, 0.6);
  padding: 10px 16px;
  border-radius: 8px;
  font-size: 14px;
  font-weight: 600;
  cursor: pointer;
  transition: all 0.2s ease;
}

.photo-subtab:hover {
  color: #fff;
  background: rgba(255, 255, 255, 0.05);
}

.photo-subtab.active {
  background: rgba(0, 200, 150, 0.15);
  color: #00c896;
  border: 1px solid rgba(0, 200, 150, 0.3);
}

.photo-mode-container {
  animation: fadeIn 0.3s ease-in-out;
}

@keyframes fadeIn {
  from { opacity: 0; transform: translateY(5px); }
  to { opacity: 1; transform: translateY(0); }
}
```