

Replit Implementation Brief: The "Prompt Whisperer" Spark Panel

Replit, we are adding a new "on-ramp" feature called the **Prompt Whisperer (Spark Panel)**.

This feature solves the "blank page syndrome" by presenting users with a rotating curiosity question when they first open the app. If they answer it, the app automatically builds their prompt, selects tone pills, and runs the analysis step. If they skip it, they see the standard UI.

CRITICAL REQUIREMENT: This feature must be a pure addition. Do not delete, alter, or rewrite any existing functionality in the prompt builder, tuning section, or generation flow. The Spark Panel sits *above* the existing goal box and acts as an optional entry point.

1. The Spark Panel UI (HTML)

Inject this HTML directly above the main `pmgv3-goal-input` container in the Text Suite (and optionally Photo/Video suites if applicable).

HTML

```
<!-- The Spark Panel Container -->
<div class="pmgv3-spark-panel" id="pmgv3-spark-panel">
  <div class="spark-header">
    <span class="spark-icon">🌟</span>
    <span class="spark-label">Prompt Whisperer</span>
    <button class="spark-close-btn" id="btn-close-spark" title="Skip this">x</button>
  </div>

  <div class="spark-content" id="spark-question-container">
    <h3 class="spark-question" id="spark-question-text">Loading spark...</h3>
    <p class="spark-subtext">Answer simply. We'll build the perfect prompt for you</p>

    <textarea class="spark-input" id="spark-answer-input" placeholder="Type your answer here"></textarea>

    <div class="spark-actions">
      <button class="spark-btn-primary" id="btn-spark-submit">Build My Prompt</button>
      <button class="spark-btn-secondary" id="btn-spark-skip">Skip — I know what I want</button>
    </div>
  </div>
</div>
```

2. The Logic (JavaScript)

Add this logic to `pmg-chassis-v3.js` (or a new dedicated file `pmg-spark-panel.js` that is loaded alongside it).

JavaScript

```
const sparkQuestions = [
  "What's a problem you've been putting off solving?",
  "If you had a world-class expert on call right now, what would you ask them?",
  "What's something you wish you could explain better to someone?",
  "What's a business idea you've never had time to explore?",
  "What would you create if you knew it couldn't fail?",
  "What do you need written that you've been dreading?",
  "What's a complex topic you want to understand in 5 minutes?"
];

function initSparkPanel() {
  const sparkPanel = document.getElementById('pmgv3-spark-panel');
  const questionText = document.getElementById('spark-question-text');
  const answerInput = document.getElementById('spark-answer-input');
  const btnSubmit = document.getElementById('btn-spark-submit');
  const btnSkip = document.getElementById('btn-spark-skip');
  const btnClose = document.getElementById('btn-close-spark');

  // Check if user previously dismissed the panel
  if (localStorage.getItem('pmg_spark_dismissed') === 'true') {
    sparkPanel.style.display = 'none';
    return;
  }

  // Select a random question
  const randomQuestion = sparkQuestions[Math.floor(Math.random() * sparkQuestions.length)];
  questionText.innerText = randomQuestion;

  // Handle Skip / Close
  const dismissPanel = () => {
    sparkPanel.style.display = 'none';
    localStorage.setItem('pmg_spark_dismissed', 'true'); // Remember preference
    // Focus the main goal input so they can start typing immediately
    const mainGoalInput = document.querySelector('.pmgv3-goal-input');
    if (mainGoalInput) mainGoalInput.focus();
  };

  btnSkip.addEventListener('click', dismissPanel);
  btnClose.addEventListener('click', dismissPanel);

  // Handle Submit
  btnSubmit.addEventListener('click', async () => {
    const answer = answerInput.value.trim();
  });
}
```

```

if (!answer) {
  answerInput.classList.add('error-shake');
  setTimeout(() => answerInput.classList.remove('error-shake'), 500);
  return;
}

// 1. Show loading state on button
const originalText = btnSubmit.innerText;
btnSubmit.innerText = "Building...";
btnSubmit.disabled = true;

try {
  // 2. Transfer the answer to the main goal box
  const mainGoalInput = document.querySelector('.pmgv3-goal-input');
  if (mainGoalInput) {
    mainGoalInput.value = `I am answering this prompt: "${randomQuestion}"`;
  }

  // 3. Hide the Spark Panel
  sparkPanel.style.display = 'none';

  // 4. Programmatically trigger the "Analyze My Idea" flow
  // Find the analyze button and click it to trigger the existing auto-tune
  const analyzeBtn = document.querySelector('.pmgv3-analyze-btn');
  if (analyzeBtn) {
    analyzeBtn.click();
  } else {
    console.warn("Analyze button not found. User must click manually.");
  }

} catch (error) {
  console.error("Error in Spark Panel submission:", error);
  btnSubmit.innerText = originalText;
  btnSubmit.disabled = false;
}
});
}

document.addEventListener('DOMContentLoaded', initSparkPanel);

```

3. CSS Styling

Add these styles to `pmg-chassis-v3.css`. The design uses a soft gradient and border to make it feel distinct from the standard input boxes, emphasizing that it's a "helper" tool.

CSS

```
.pmgv3-spark-panel {
  background: linear-gradient(145deg, rgba(0, 200, 150, 0.08) 0%, rgba(0, 0, 0,
  border: 1px solid rgba(0, 200, 150, 0.4);
  border-radius: 12px;
  padding: 20px;
  margin-bottom: 24px;
  position: relative;
  box-shadow: 0 4px 20px rgba(0, 200, 150, 0.1);
  transition: all 0.3s ease;
}

.spark-header {
  display: flex;
  align-items: center;
  margin-bottom: 16px;
}

.spark-icon {
  font-size: 18px;
  margin-right: 8px;
}

.spark-label {
  color: #00c896;
  font-size: 12px;
  font-weight: 700;
  text-transform: uppercase;
  letter-spacing: 1px;
}

.spark-close-btn {
  position: absolute;
  top: 16px;
  right: 16px;
  background: transparent;
  border: none;
  color: rgba(255, 255, 255, 0.5);
  font-size: 24px;
  line-height: 1;
  cursor: pointer;
  transition: color 0.2s;
}

.spark-close-btn:hover {
  color: #fff;
}
```

```
.spark-question {
  color: #fff;
  font-size: 22px;
  font-weight: 600;
  margin: 0 0 8px 0;
  line-height: 1.3;
}

.spark-subtext {
  color: rgba(255, 255, 255, 0.6);
  font-size: 14px;
  margin: 0 0 16px 0;
}

.spark-input {
  width: 100%;
  min-height: 80px;
  background: rgba(0, 0, 0, 0.3);
  border: 1px solid rgba(255, 255, 255, 0.15);
  border-radius: 8px;
  padding: 12px;
  color: #fff;
  font-size: 15px;
  resize: vertical;
  margin-bottom: 16px;
  font-family: inherit;
}

.spark-input:focus {
  outline: none;
  border-color: #00c896;
  background: rgba(0, 0, 0, 0.5);
}

.spark-actions {
  display: flex;
  gap: 12px;
  align-items: center;
}

.spark-btn-primary {
  background: #00c896;
  color: #000;
  border: none;
  padding: 10px 20px;
  border-radius: 8px;
  font-weight: 600;
  font-size: 14px;
}
```

```
    cursor: pointer;
    transition: background 0.2s;
}

.spark-btn-primary:hover {
    background: #00e6ac;
}

.spark-btn-secondary {
    background: transparent;
    border: 1px solid rgba(255, 255, 255, 0.2);
    color: rgba(255, 255, 255, 0.7);
    padding: 10px 20px;
    border-radius: 8px;
    font-weight: 500;
    font-size: 14px;
    cursor: pointer;
    transition: all 0.2s;
}

.spark-btn-secondary:hover {
    background: rgba(255, 255, 255, 0.05);
    color: #fff;
    border-color: rgba(255, 255, 255, 0.4);
}

/* Simple shake animation for empty submission */
@keyframes shake {
    0%, 100% { transform: translateX(0); }
    25% { transform: translateX(-5px); }
    75% { transform: translateX(5px); }
}

.error-shake {
    animation: shake 0.3s ease-in-out;
    border-color: #ff4444 !important;
}
```