

**Make a
forward pass
before the
backward pass**

Backpropagation: Understanding the implications of the chain rule

Jonathon Hare


Vision, Learning and Control
University of Southampton

A lot of the ideas in this lecture come from Andrej Karpathy's blog post on backprop (<https://medium.com/@karpathy/yes-you-should-understand-backprop-e2f06eab496b>) and his CS231n Lecture Notes (<http://cs231n.github.io/optimization-2/>)



- A quick look at an MLP again
- The chain rule (again)
- Unintuitive gradient effects
- A closer look at basic stochastic gradient descent algorithms

The unbiased Multilayer Perceptron (again)...



Without loss of generality, we can write the above as:

$$\hat{\mathbf{y}} = g(f(\mathbf{x}; \mathbf{W}^{(1)}); \mathbf{W}^{(2)}) = g(\mathbf{W}^{(2)} f(\mathbf{W}^{(1)} \mathbf{x}))$$

where f and g are activation functions.

Gradients of our simple unbiased MLP

- Let's assume MSE Loss

$$\ell_{MSE}(\hat{\mathbf{y}}, \mathbf{y}) = \|\hat{\mathbf{y}} - \mathbf{y}\|_2^2$$

Gradients of our simple unbiased MLP

- Let's assume MSE Loss

$$\ell_{MSE}(\hat{\mathbf{y}}, \mathbf{y}) = \|\hat{\mathbf{y}} - \mathbf{y}\|_2^2$$

- What are the gradients?

$$\nabla_{\mathbf{W}^*} \ell_{MSE}(\mathcal{G}(\mathbf{W}^{(2)} f(\mathbf{W}^{(1)} \mathbf{x})), \mathbf{y})$$

Gradients of our simple unbiased MLP

- Let's assume MSE Loss

$$\ell_{MSE}(\hat{\mathbf{y}}, \mathbf{y}) = \|\hat{\mathbf{y}} - \mathbf{y}\|_2^2$$

- What are the gradients?

$$\nabla_{\mathbf{W}^*} \ell_{MSE}(g(\mathbf{W}^{(2)} f(\mathbf{W}^{(1)} \mathbf{x})), \mathbf{y})$$

- Clearly we need to apply the chain rule (vector form) multiple times

Gradients of our simple unbiased MLP

- Let's assume MSE Loss

$$\ell_{MSE}(\hat{\mathbf{y}}, \mathbf{y}) = \|\hat{\mathbf{y}} - \mathbf{y}\|_2^2$$

- What are the gradients?

$$\nabla_{\mathbf{W}^*} \ell_{MSE}(g(\mathbf{W}^{(2)} f(\mathbf{W}^{(1)} \mathbf{x})), \mathbf{y})$$

- Clearly we need to apply the chain rule (vector form) multiple times
- We could do this by hand

Gradients of our simple unbiased MLP

- Let's assume MSE Loss

$$\ell_{MSE}(\hat{\mathbf{y}}, \mathbf{y}) = \|\hat{\mathbf{y}} - \mathbf{y}\|_2^2$$

- What are the gradients?

$$\nabla_{\mathbf{W}^*} \ell_{MSE}(g(\mathbf{W}^{(2)} f(\mathbf{W}^{(1)} \mathbf{x})), \mathbf{y})$$

- Clearly we need to apply the chain rule (vector form) multiple times
- We could do this by hand
- (But we're not that crazy!)

Let's go back to a simpler expression

$$\begin{aligned} f(x, y, z) &= (x + y)z \\ &\equiv qz \text{ where } q = (x + y) \end{aligned}$$

Let's go back to a simpler expression

$$\begin{aligned}f(x, y, z) &= (x + y)z \\ &\equiv qz \text{ where } q = (x + y)\end{aligned}$$

Clearly the partial derivatives of the subexpressions are trivial:

$$\begin{aligned}\partial f / \partial z &= q & \partial f / \partial q &= z \\ \partial q / \partial x &= 1 & \partial q / \partial y &= 1\end{aligned}$$

Let's go back to a simpler expression

$$\begin{aligned}f(x, y, z) &= (x + y)z \\ &\equiv qz \text{ where } q = (x + y)\end{aligned}$$

Clearly the partial derivatives of the subexpressions are trivial:

$$\begin{aligned}\partial f / \partial z &= q & \partial f / \partial q &= z \\ \partial q / \partial x &= 1 & \partial q / \partial y &= 1\end{aligned}$$

and the chain rule tells us how to combine these:

$$\begin{aligned}\partial f / \partial x &= \partial f / \partial q \cdot \partial q / \partial x = z \\ \partial f / \partial y &= \partial f / \partial q \cdot \partial q / \partial y = z\end{aligned}$$

Let's go back to a simpler expression

$$\begin{aligned}f(x, y, z) &= (x + y)z \\ &\equiv qz \text{ where } q = (x + y)\end{aligned}$$

Clearly the partial derivatives of the subexpressions are trivial:

$$\begin{aligned}\partial f / \partial z &= q & \partial f / \partial q &= z \\ \partial q / \partial x &= 1 & \partial q / \partial y &= 1\end{aligned}$$

and the chain rule tells us how to combine these:

$$\begin{aligned}\partial f / \partial x &= \partial f / \partial q \cdot \partial q / \partial x = z \\ \partial f / \partial y &= \partial f / \partial q \cdot \partial q / \partial y = z\end{aligned}$$

$$\text{so } \nabla_{[x, y, z]} f = [z, z, q]$$

A computational graph perspective

$$f(x, y, z) = (x + y)z$$

An intuition of the chain rule

- Notice how every operation in the computational graph given its inputs can immediately compute two things:
 - ① its output value
 - ② the *local* gradient of its inputs with respect to its output value
- The chain rule tells us literally that each operation should take its local gradients and multiply them by the gradient that *flows* backwards into it

This is backpropagation

- The backprop algorithm is just the idea that you can perform the forward pass (computing and caching the local gradients as you go),
- and then perform a backward pass to compute the total gradient by applying the chain rule and re-utilising the cached local gradients

This is backpropagation

- The backprop algorithm is just the idea that you can perform the forward pass (computing and caching the local gradients as you go),
- and then perform a backward pass to compute the total gradient by applying the chain rule and re-utilising the cached local gradients
- Backprop is just another name for 'Reverse Mode Automatic Differentiation'...

Unintuitive effects I: Multiplication

- Consider the multiplication operation $f(a, b) = a * b$.

Unintuitive effects I: Multiplication

- Consider the multiplication operation $f(a, b) = a * b$.
- The gradients are clearly $\partial f / \partial b = a$ and $\partial f / \partial a = b$.

Unintuitive effects I: Multiplication

- Consider the multiplication operation $f(a, b) = a * b$.
- The gradients are clearly $\partial f / \partial b = a$ and $\partial f / \partial a = b$.
 - (in a computational graph these would be the local gradients w.r.t the inputs)

Unintuitive effects I: Multiplication

- Consider the multiplication operation $f(a, b) = a * b$.
- The gradients are clearly $\partial f / \partial b = a$ and $\partial f / \partial a = b$.
 - (in a computational graph these would be the local gradients w.r.t the inputs)
- If a is large and b is tiny the gradient assigned to b will be large, and the gradient to a small.

Unintuitive effects I: Multiplication

- Consider the multiplication operation $f(a, b) = a * b$.
- The gradients are clearly $\partial f / \partial b = a$ and $\partial f / \partial a = b$.
 - (in a computational graph these would be the local gradients w.r.t the inputs)
- If a is large and b is tiny the gradient assigned to b will be large, and the gradient to a small.
- This has implications for e.g. linear classifiers ($\mathbf{w}^\top \mathbf{x}_i$) where you perform many multiplications

Unintuitive effects I: Multiplication

- Consider the multiplication operation $f(a, b) = a * b$.
- The gradients are clearly $\partial f / \partial b = a$ and $\partial f / \partial a = b$.
 - (in a computational graph these would be the local gradients w.r.t the inputs)
- If a is large and b is tiny the gradient assigned to b will be large, and the gradient to a small.
- This has implications for e.g. linear classifiers ($\mathbf{w}^\top \mathbf{x}_i$) where you perform many multiplications
 - the magnitude of the gradient is directly proportional to the magnitude of the data

Unintuitive effects I: Multiplication

- Consider the multiplication operation $f(a, b) = a * b$.
- The gradients are clearly $\partial f / \partial b = a$ and $\partial f / \partial a = b$.
 - (in a computational graph these would be the local gradients w.r.t the inputs)
- If a is large and b is tiny the gradient assigned to b will be large, and the gradient to a small.
- This has implications for e.g. linear classifiers ($\mathbf{w}^\top \mathbf{x}_i$) where you perform many multiplications
 - the magnitude of the gradient is directly proportional to the magnitude of the data
 - multiple \mathbf{x}_i by 1000, and the gradients also increase by 1000

Unintuitive effects I: Multiplication

- Consider the multiplication operation $f(a, b) = a * b$.
- The gradients are clearly $\partial f / \partial b = a$ and $\partial f / \partial a = b$.
 - (in a computational graph these would be the local gradients w.r.t the inputs)
- If a is large and b is tiny the gradient assigned to b will be large, and the gradient to a small.
- This has implications for e.g. linear classifiers ($\mathbf{w}^\top \mathbf{x}_i$) where you perform many multiplications
 - the magnitude of the gradient is directly proportional to the magnitude of the data
 - multiple \mathbf{x}_i by 1000, and the gradients also increase by 1000
 - if you don't lower the learning rate to compensate your model might not learn

Unintuitive effects I: Multiplication

- Consider the multiplication operation $f(a, b) = a * b$.
- The gradients are clearly $\partial f / \partial b = a$ and $\partial f / \partial a = b$.
 - (in a computational graph these would be the local gradients w.r.t the inputs)
- If a is large and b is tiny the gradient assigned to b will be large, and the gradient to a small.
- This has implications for e.g. linear classifiers ($\mathbf{w}^\top \mathbf{x}_i$) where you perform many multiplications
 - the magnitude of the gradient is directly proportional to the magnitude of the data
 - multiple \mathbf{x}_i by 1000, and the gradients also increase by 1000
 - if you don't lower the learning rate to compensate your model might not learn
 - **Hence you need to always pay attention to data normalisation!**

Unintuitive effects II: vanishing gradients of the sigmoid

Unintuitive effects III: dying ReLUs

Unintuitive effects III: Exploding gradients in recurrent networks