AiSensy APIs

Search Project API...

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in

Project Webhook

Webhooks provide the ability to receive real-time data updates about activities in your AiSensy project.

Choose to receive data by subscribing to topics and have all applicable data sent to a URL of your choice. You can then use your own custom script to read, save, and do whatever you want with that data. This is a powerful option that allows you to keep all of your data in sync and opens up the possible integration options like never before.

The main concepts for webhooks are **subscriptions**, **topics**, and **notifications**.

Subscriptions

A subscription is where you provide an endpoint & select a topic/topics you want to be notified about.

Topics

A subscription will contain one or more topics. Topics are types of events that you want to be informed about.

Notifications

The request was sent to the webhook-endpoint/application about the subscribed topic. It contains updates & necessary data to enable automations.

Webhook Topics

The following topics are available and you can be notified when an action relating to that topic occurs.

Project Webhook

AiSensy APIs

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in

TOPIC NAME	RESOURCE NAME	DESCRIPTION
contact.created	Contact	Triggered when a new contact gets created
DEPRECATED contact.attribute.updated	Contact	Triggered when attributes gets updated in the contact. **Note**: This topic is deprecated. Please use **contact.attribute.revised** instead
message.created	Message	Triggered when a new message is sent by assistant or agent or user or through broadcasts
message.status.updated	Message	Triggered when message status gets updated
message.sender.user	Message	Triggered when a user sends message to the business
DEPRECATED contact.tag.added	Contact	Triggered when a new tag gets added to a contact. **Note**: This topic is deprecated. Please use **contact.tag.updated** instead
DEPRECATED contact.tag.removed	Contact	Triggered when a existing tag gets removed from a contact. **Note**: This topic is deprecated. Please use **contact.tag.updated** instead
DEPRECATED contact.first_message.added	Contact	Triggered when first message tag is added to a contact. **Note**: This topic is deprecated. Please use **contact.first_message.updated** instead
DEPRECATED contact.first_message.removed	Contact	Triggered when first message tag is removed. **Note**: This topic is deprecated. Please use **contact.first_message.updated** instead
contact.chat.intervened	Contact	Triggered when agent intervenes a chat
contact.chat.closed	Contact	Triggered when agent closes a intervened chat
contact.chat.requesting	Contact, Message	Triggered every time when chatbot returns Fallback response to user queries
contact.campaign.sent	Contact, Message	Triggered when campaign is sent to a contact
contact.campaign.delivered	Contact, Message	Triggered when campaign is delivered to a contact
contact.campaign.read	Contact, Message	Triggered when campaign is read by the contact
order.placed	Order, Placed	Triggered when a user places an order

Subscriptions

Topics

Notifications

Webhook Topics

Webhook Request

Notification Object

Notification Data

Resource Objects

Handling Webhook Reque...

Verifying Request Authent...

AiSensy APIs

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in

TOPIC NAME	RESOURCE NAME	DESCRIPTION
payment.captured	Payment, Captured	Triggered when a user completes payment
payment.refunded	Payment, Refunded	Triggered when a refund request for an order is processed
contact.first_message.updated	Contact	Triggered when the first message tag is either added or removed from the contact
contact.tag.updated	Contact	Triggered when a tag is either added or removed from a contact
contact.attribute.revised	Contact	Triggered when attributes gets updated in the contact

Notes -

For bulk import contacts, contact.created notification are not sent. This is to avoid throttling on your webhook endpoint.

Current implementation of webhooks is in beta phase. Specifications or models may change in official release. We'll try our best to make it backwards compatible.

Webhook Request

Request sent to the webhook endpoint

HTTP Method. POST

Headers

NAME	DESCRIPTION
Content-type	application/json
X-AiSensy-Signature	Signed payload to verify the authenticity of request.
X-AiSensy-API-Version	Webhook API version. Use this to avoid payload structure mismatches with new releases.
X-AiSensy-Project-Id	Project Id with which the notification is associated with.

AiSensy APIs

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in

Request Body Notification object

Expected Response

Endpoint is expected to return 2xx status

Notification Object

Request body which is sent with every webhook request.

```
{
  "id": "",
  "created_at": "",
  "topic": "",
  "delivery_attempt": 2,
  "app_id": "",
  "webhook_id": "",
  "project_id": "",
  "data": {}
}
```

FIELD NAME	DESCRIPTION
id	Unique notification id
created_at	The timestamp the notification was created. (milliseconds)
topic	Type of the notification
delivery_attempt	Number of time notification has been tried to delivered
app_id	Id of the app with which the webhook is associated.
webhook_id	Unique id of webhook
project_id	Project Id with which the notification is associated with.
data	The data associated with the notification.

Notification Data

Data sent with different topics. You'll be receiving resource object with "type" field inside them to identify the data structures in them.

AiSensy APIs

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in

See details about {CONTACT_OBJECT} & {MESSAGE_OBJECT} below.

Value of data field for different topics -

• contact.created

```
{
  "contact": "CONTACT_OBJ"
}
```

• contact.first_message.updated

```
{
  "contact": "{CONTACT_OBJECT}",
  "first_message": {
    "type": "first_message",
    "id": "",
    "added_at": ""
  }
}
```

• contact.tag.updated

```
{
  "contact": "{CONTACT_OBJECT}",
  "tag": {
    "type": "tag",
    "id": "",
    "added_by": "",
    "added_at": ""
  }
}
```

• contact.attribute.revised

```
{
  "contact": "{CONTACT_OBJECT}",
  // Updated attributes in this object
  "attribute": {
    "type": "attribute",
    // Key value pairs of your attributes' name
    "fields": {}
  }
}
```

• `DEPRECATED` contact.attribute.updated

AiSensy APIs

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in

```
{
  "contact": "{CONTACT_OBJECT}",
  // Updated attributes in this object
  "attribute": {
    "type": "attribute",
    // Key value pairs of your attributes' name
    "fields": {}
  }
}
```

- `DEPRECATED` contact.tag.added

```
{
  "contact": "{CONTACT_OBJECT}",
  "tag": {
    "type": "tag",
    "id": "",
    "added_by": "",
    "added_at": ""
  }
}
```

- `DEPRECATED` contact.tag.removed

```
{
  "contact": "{CONTACT_OBJECT}",
  "tag": {
    "type": "tag",
    "id": "",
    "removed_by": "",
    "removed_at": ""
  }
}
```

- `DEPRECATED` contact.first_message.added

```
{
  "contact": "{CONTACT_OBJECT}",
  "first_message": {
    "type": "first_message",
    "id": "",
    "added_at": ""
  }
}
```

- `DEPRECATED` contact.first_message.removed

AiSensy APIs

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in

```
{
  "contact": "{CONTACT_OBJECT}",
  "first_message": {
    "type": "first_message",
    "id": "",
    "removed_at": ""
  }
}
```

• contact.chat.[intervened / closed]

```
{
  "contact": "{CONTACT_OBJECT}"
}
```

• contact.chat.requesting

```
{
  "contact": "{CONTACT_OBJECT}",
  "message": "{MESSAGE_OBJECT}"
}
```

• contact.campaign.[sent/ read]

```
{
  "contact": "{CONTACT_OBJECT}",
  "message": "{MESSAGE_OBJECT}"
}
```

• message.created

```
{
  "message": "{MESSAGE_OBJECT}"
}
```

• message.status.updated

```
{
  "message": "{MESSAGE_OBJECT}"
}
```

• message.sender.user

AiSensy APIs

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in

```
{
  "message": "{MESSAGE_OBJECT}"
}
```

• order.placed

```
{
  "order": "{ORDER_OBJECT}"
}
```

• payment.captured

```
{
  "payment": "{PAYMENT_OBJECT}"
}
```

• payment.refunded

```
{
  "payment": "{PAYMENT_OBJECT}"
}
```

Resource Objects

Contact Object

```
{
  "type": "contact",
  "id": "",
  "project_id": "",
  "name": "",
  "phone_number": "",
  "is_closed": false,
  "is_requesting": false,
  "is_intervened": false,
  "created_at": "Date",
  "tags": [ { "id": "", "added_at": "", "added_by": "" }],
  "attributes": {},
  "last_active": "Date",
  "last_message": "Date",
  "source": "",
  "country_code": "",
  "first_messaage": { "id": "", "added_at": "" }
```

AiSensy APIs

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in

```
}
```

FIELD NAME	DESCRIPTION
id	*String* Contact Id
project_id	*String* Project id
name	*String* Name of the contact on WhatsApp
phone_number	*String* WhatsApp Number of contact
is_closed	*Boolean* Closed status
is_requesting	*Boolean* Requesting status
is_intervened	*Boolean* Intervened status
created_at	*Number* Indicates the timestamp(in milli seconds) when the contact was created.
tags	*Array* Tags assigned to the contact.
tags.id	*String* Id of tag assigned to the contact. View specific tag in AiSensy App to find its id.
tags.added_at	*Number* Indicates the timestamp(in milli seconds) when the tag was assigned.
tags.added_by	*String* Id of agent
attributes	*Object* Contains key-value pairs of all the attributes assigned to the contact.
last_active	*Number* Indicates the timestamp(in milli seconds) when the contact has sent last message to the business.

AiSensy APIs

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in

FIELD NAME	DESCRIPTION
last_message	*Number* Indicates the timestamp(in milli seconds) when the last message has been sent (either by business or contact).
source	*String* Source of contact through which the contact was created.
country_code	*String* Country code of the contact's WhatsApp number.
first_message.id	*String* Id of the tag assigned to the contact based on the first message.
first_message.added_at	*Number* Indicates the timestamp(in milli seconds) when the first message tag was assigned to the contact.

Message Object

```
{
  "type": "message",
  "id": "",
  "project_id": "",
  "phone_number": "",
  "contact_id": "",
  "campaign": { "name": "", "sent_at": ""},
  "sender": "",
  "message_content": {}, // message payload
  "message_type": "TEXT",
  "status": "",
  "is_HSM": false,
  "chatbot_response": {
    "queryText": "",
    "intent": "",
  },
  "delivered_at": "Date",
  "read_at": "Date",
  "sent_at": "Date",
  "failed_at": "Date"
  "agent_id": "",
  "failureResponse": {"code": "", "reason": ""},
  "messageId": ""
```

AiSensy APIs

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in

FIELD NAME	DESCRIPTION
id	*String* Unique Identifier of the event
project_id	*String* Project id
phone_number	*String* WhatsApp Number of contact
contact_id	*String* Contact Id
campaign	*Object* If the message is part of any campaign, it will have details related to it.
campaign.name	*String* Name of the campaign sent
campaign.sent_at	*Number* Indicates the timestamp(in milli seconds) when the campaign was sent.
sender	*String* It represents who sent that message. It can have following values -
message_content	*Object* Details related to the content of the message.
message_type	*String* Type of message sent. It can have following values -
status	*String* Message status. It can have following values -

AiSensy APIs

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in

FIELD NAME	DESCRIPTION
is_HSM	*Boolean* Represents whether the message was template message or session message. For true value, it is template message.
chatbot_response.queryText	*String* Query sent by the contact for which this message has been sent to the contact.
chatbot_response.intent	*String* Intent detected by Dialogflow
delivered_at	*Number* Indicates the timestamp(in milli seconds) when the message status was set to Delivered.
read_at	*Number* Indicates the timestamp(in milli seconds) when the message status was set to Read.
sent_at	*Number* Indicates the timestamp(in milli seconds) when the message status was set to Sent.
failed_at	*Number* Indicates the timestamp(in milli seconds) when the message status was set to Failed.
agent_id	*String* Agent id of the agent who sent this message. Applicable for sender set to AGENT.
failureResponse.code	*Number* Message failure code
failureResponse.reason	*Number* Message failure reason
messageId	*String* Unique identifier of the message

Order Object

```
{
   "phone_number":"",
```

AiSensy APIs

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in

```
    "catalog_id":"",
    "text":"",
    "product_items":[
       {
          "product_retailer_id":"",
          "quantity":1,
          "item_price":1,
          "currency":"INR"
       }
    ]
 }
```

FIELD NAME	DESCRIPTION
phone_number	*String* WhatsApp Number of the contact
messageId	*String* Unique identifier of the message
catalog_id	*String* Unique identifier of the message
product_items.product_retailer_id	*String* Unique identifier of the product
product_items.quantity	*Number* Product Quantity selected
product_items.item_price	*Number* Product Quantity selected
product_items.currency	*String* Currency

Payment Object

```
{
   "phone_number":"",
   "reference_id":"",
   "amount":{
      "value":1000,
      "offset":100
   },
   "currency":"INR",
   "transaction":{
      "id":"",
```

AiSensy APIs

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in


```
"type":"",
"status":"captured",
"created_timestamp":1703063690,
"updated_timestamp":1703063690,
"refunds":[
   {
      "id":"",
      "amount":{
         "value":1000,
         "offset":100
      },
      "speed_processed":"normal",
```


FIELD NAME	DESCRIPTION
phone_number	*String* WhatsApp Number of the contact
messageId	*String* Unique identifier of the message
reference_id	*String* Unique identifier of the message
currency	*String* Currency of the transaction
amount.value	*Number* Positive integer representing the amount value multiplied by offset. For example, ₹12.34 has value 1234.
amount.offset	*Number* The given offset for the transaction
transaction.id	*String* Unique identifier of the transaction
transaction.type	*String* Type of the transaction
transaction.status	*String* Product Quantity selected
transaction.created_timestamp	*Number* Time when transaction was created in epoch seconds.
transaction.updated_timestamp	*Number* Time when transaction was last updated in epoch seconds.

AiSensy APIs

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in

FIELD NAME	DESCRIPTION
transaction.refunds	*Array[Optional]* The list of refunds for this order.Each refund object contains the following fields id *String* The alpha-numeric ID of the refund. amount *Object* The total amount of the refund. speed_processed *String* Speed by which refund was processed. Can be one of instant or normal. status *String* The status of the refund. Can be one of pending, success or failed. created_timestamp *Number* Time when refund was created in epoch seconds. updated_timestamp *Number* Time when refund was last updated in epoch seconds.
transaction.notes	*String[Optional]* Supported for only Razorpay PG, this contains the key-value pairs sent as part of Order Details message.
notes.referenceId	*String* Reference Id of the transaction
notes.source	*String* Source of the note

Handling Webhook Requests

AiSensy APIs

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in

When you setup a subscription you will receive notifications on your chosen topics. How you handle those notifications, i.e. the HTTP status code returned, will determine the subsequent state of that subscription.

> Webhook should process inbound notifications asynchronous but acknowledge its reception synchronously & immediately. Best acknowledge time should be less than 100 millisecond, it is understood that there can be a network delay. Hence, recommended is within 500-1000 millisecond. The greater your response time, the more delayed inbound notifications the webhook will receive each time.
>
> It is expected to receive 2xx response from Webhook endpoint within 5s, otherwise It will be marked failed.
>
> Notification will be delivered at-least one time. For some reason(e.g.- Network issue or API timeout) if notification delivery is marked failed, It will be retried again after 5mins.
>
> As same notification can be delivered multiple times, design your application/endpoint to handle such scenarios. You can use notification id & delivery attempts fields sent in the notifications to handle in these scenarios.
>
> Ideally, you should receive webhook in the order in which the notifications occur. However, you may not always receive the webhooks in the order.

RESPONSE CODE	DESCRIPTION	ACTION
2xx	Success	The webhook was successfully delivered.
410	Gone	When a 410 is received, we assume the resource is no longer available. We will disable the subscription and no more notifications will be sent.
4xx (excl. 429)5xx	Client or service errors	Webhook will be retried once after 5mins. If the webhook is repeatedly failing to respond, It will be disabled. Having more than 100 failed delivery attempts in 20 minutes period will cause temporary disabling of the webhook. You can re-enable it from the dashboard after fixing the issues.

Verifying Request Authenticity

Each webhook notification is signed by AiSensy via an `X-AiSensy-Signature` header. We do this so that you can verify the notification came from AiSensy by decoding the signature.

The hash signature is calculated using HMAC with SHA-2 algorithm with your webhook's shared-secret set as the key and the webhook request body as the message.

The signature is the hexadecimal representation of a SHA-2 signature computed using the HMAC algorithm.

AiSensy APIs

Home

Project API

DOCS

Getting Started

Project Webhook

Getting Started

Project Webhook

Resources and Relations

APIS

Project API Reference

Business

Project

Messages

Project Webhook

WA Template Message

Contact

Campaign

Catalogue

Media

SCHEMAS

Schemas

Business

Project

Campaign

Contact

Agent

Sign in

Note: Do Not Parse or Cast the Webhook Request Body**.** While generating the signature at your end, ensure that the webhook body passed as an argument is the raw webhook request body.

Node.js example for webhook authentication

```
const express = require('express');
const bodyParser = require('body-parser');
const { createHmac } = require("crypto");

app.use(bodyParser.json());

const createHash = async (text, secret) => {
  const hash = createHmac("sha256", secret).update(text).digest("hex");
  return hash;
};

app.post('/test-webhook-signature', async(req, res) => {
        try {
                const notification = req.body;
                const receivedSignature = req.headers["x-aisensy-signature"];
                const sharedSecret = "WEBHOOK_SHARED_SECRET";
        // Provide the notificaiton data as it is
                const generatedSignature = await createHash(`${JSON.stringify(notification)}`, shar

                if (receivedSignature === generatedSignature) {
        res.status(200).send("Signature Matched");
} else {
```