



#### BYD COMPANY LIMITED

Address: No.3009, BYD Road, Pingshan, Shenzhen, 518118, P.R.China

#### **Global Contact**

Email: eubattery@byd.com Web: www.byd.com/energy

Tel: +86-89888888-61801/61579 /61581









## Safe Battery Chemistry

B-Box is designed with LiFePO<sub>4</sub> chemistry battery which has been widely recognized as one of the safest battery technologies. LiFePO<sub>4</sub> chemistry features stable structures and its thermal runaway temperature is over 480°C. That's 100% higher than NCM and NCA chemistry. It is designed for residential and commercial applications with absolute safety.

### Railway and Automotive Standard Battery

As the world's largest Electric Vehicle manufacturer, BYD brings railway and automotive battery standards to residential and commercial solutions: B-Box. 6+ years' track records of large scale applications in Electric Vehicles ensure its safety and reliability. All products have been certified according to international standards including TUV, UL and CE.

## **High Power Output**

B-Box has the highest output power in industry, which brings the highest performance to customers. The system is able to reach C rate at max 1C and 2C at peak to support critical loads such as A/C and pumps, etc.

#### Easy Installation and Uninterruptible Maintenance

All B-Box systems have modular design featuring uninterruptible maintenance, and easy installation.

#### Flexible Extension Life Time

B-Box is equipped with modular design and smart BMS (Battery Management System), allowing extension throughout its lifetime.

# **Natural Cooling**

B-Box is designed with natural cooling providing optimum efficiency.

#### 10 Years Warranty

10 Years Warranty provides the best guarantee of operation.

# BYD B-Box BATTERY STORAGE



**B-Box Compact** 

Model	B-Box Compact 2.5
Battery Type	LiFePO <sub>4</sub>
Battery Module	B-Plus 2.5 (2.56 kWh)
	1 module
Usable Energy [1] [kWh]	2.56
Max Output Power [kW]	2.56
Peak Output Power [kW]	5.12, 30s
Round-Trip Efficiency	≥95.3% (Under test condition [1])
Nominal Voltage [V]	51.2
Operating Voltage Range [V]	43.2~56.4
Communication	CAN / RS485
Dimension [W×H×D,mm]	483×130×478
Net Weight of B-Plus [kg]	34
Net Weight [kg]	38
Enclosure Protection Rating	IP20
Warranty	10 years
Ambient Temperature Range [2] [°C]	-10 ~ +50
Certification & Safety Standard	TUV / CE / RCM / UN38.3
Scalability	Max. 2 B-Plus 2.5 in parallel
Compatible Inverters	SMA / GOODWE / SOLAX / Victron, more brands to be announced

<sup>[1]</sup> Test conditions: 100% DOD, 0.5C charge & discharge @+25  $^{\circ}\!\text{C}$ 

<sup>[2]</sup>  $-10^{\circ}$ C  $\sim$ 10  $^{\circ}$ C will be derating

<sup>[3]</sup> Max. 32 B-Plus 2.5 in parallel with cabinet design

<sup>\*</sup>System Usable Energy may be variant with differnet inverter brands