KAROL JASZTAL · Head of Operations & AI Systems Leader

Inside a Production Multi-Agent System: Autonomous Subagents, Deterministic Guardrails & Token Economics

Conductor-Subagent Orchestration, PreToolUse AST/Regex Interception Gates (Exit Code 2), and 76.8% Verified Developer Token Reduction across Multi-Harness Environments

1. System Architecture & Multi-Agent Conductor Blueprint

Decoupled Orchestration Topology, Conductor-Subagent Task Dispatch & Multi-Harness Deployments

§ 1.1 Architectural Thesis — Overcoming the Monolithic Prompt Trap

In standard enterprise implementations of generative AI and developer tooling, teams overwhelmingly default to a **monolithic prompt architecture**: feeding an LLM a single conversational prompt containing the entire product specification, 50 pages of Standard Operating Procedures (SOPs), 20 API tool schemas, and thousands of lines of source code. Under real production conditions, this triggers three catastrophic failure modes:

Attention Degradation

As context balloons past 40,000 tokens, transformer self-attention exhibits severe *"Lost in the Middle"* decay. Critical negative constraints and strict type definitions are ignored or hallucinated.

FinOps Cost Explosion

Every follow-up turn re-transmits the complete 80k+ token context. Over a 100-turn engineering session, teams burn 7–9M tokens ($35+ per developer session) with 25–45 second completion latencies.

Probabilistic Safety Illusion

Enforcing security policies via natural language (*"Please do not force-push"*) is mathematically non-deterministic. Under complex branches or adversarial injection, prompt rules fail.

§ 1.2 Topology — The Conductor-Subagent Mesh

Our architecture replaces the monolithic generalist with a decoupled conductor supervising ephemeral, single-purpose subagents operating in isolated execution environments:

SUPERVISORY LAYER

Conductor Orchestrator

Task Decomposition & REST State Sync

EPHEMERAL CONTEXT

Code Builder Subagent

Fresh Sandbox · 0 Prior Conversational Turns

INDEPENDENT AUDIT

Two-Round Review Pass

Code Reviewer + Security Code Reviewer

DETERMINISTIC GATE

PreToolUse Hooks & Push

AST Intercept · Exit Code 2 Hard Block

Task Dispatched → Isolated Execution → Zero-Trust Cold Audit → Deterministic CI Commit

§ 1.3 Multi-Harness Governance **Synchronized Runtime Environments**

All skills, prompts, and deterministic hooks are maintained in a central repository vault (**Arsenal**) and deployed natively across three production execution harnesses without vendor lock-in:

Harness Environment	Runtime Execution Model	Production Role
Google Antigravity	Multi-workspace IDE & CLI harness with Gemini 3.8 Flash/Pro	Visual application engineering, refactoring, and interactive agent pairing
Claude Code (Anthropic)	CLI terminal runner powered by Claude 3.5 Sonnet / Haiku	Deep algorithmic reasoning, TDD execution, and autonomous sweeps
DeepSeek Harness (DSH)	Local command runner executing high-density reasoning models	Batch background analysis, localized code verification, and high-frequency audits

2. Subagent Tool Isolation & Permission Boundary Matrix

Principle of Least Privilege, Physical Tool Stripping & Primary Operational Manifest Contracts

§ 2.1 Core Principle **Least Privilege in Autonomous Multi-Agent Systems**

In our architecture, subagents operate under **strict functional isolation**. Rather than relying on instructions like *"do not edit files"* or "*do not run shell commands*", non-implementing subagents have execution capabilities **physically omitted from their manifest**. Even if an adversarial prompt injection attempts to force an agent to execute an exploit or overwrite source code, the tool does not exist in its sandbox.

§ 2.2 Permission Matrix

Operational Capabilities & Isolation Boundaries

Subagent Role	Sandboxed Tools Allowed	Physically Stripped Tools
Conductor	Task planning, Questimus REST, subagent invocation	Direct code writing, raw git commits
Code Builder	Scoped File Read, Scoped File Write, Test Runner	Git push, branch switching, external HTTP
Code Reviewer	File Read, Diff Inspector, Grep/Glob search	File Write, File Edit, Shell execution, Git push
Security Code Reviewer	AST Inspector, File Read, Secrets Pattern Scanner	File Write, File Edit, Shell execution, Network egress
Test Writer	File Read, Scoped Test Directory File Write	Production source files, Git operations
Research Subagent	Web Search, Documentation Read, Workspace Grep	File Write, Command Execution, Git operations

§ 2.3 Operational Contracts

Primary Subagent Manifest Definitions

.agents/agents/security-code-reviewer/AGENT.md

Read-Only Sandbox

```
# security-code-reviewer

Security-focused code review subagent — injection vectors, exposed secrets, auth gaps, rate limiting.
Never writes files — read-only review. Call before shipping anything user-facing.

## Boundaries & Constraints
- READ-ONLY: Never call write_file, edit_file, or run destructive shell operations.
- SCOPE: Review strictly the declared files, endpoints, or commit range briefed by the conductor.
- THREAT VECTORS: Scan for OWASP Top 10, SSRF IP bypasses, credential leakage, and SQL/Command injection.
```

.agents/skills/project-execute/SKILL.md (Subagent Contract)

Ephemeral Builder

```
# code-builder

Implementation subagent for conductor workflows:
- One briefed task per spawn; always a pristine, fresh context window.
- Builds ONLY the briefed task's declared files — never touches unrelated modules.
- Test-first methodology: write failing unit test, verify failure, write minimal implementation, verify green.
- Never stages, commits, or pushes: returns a structured DEBUG REPORT block whose evidence is pasted command output.
```

3. Deterministic Safety Gates & PreToolUse Interception Engine

Operating-System-Level Hook Lifecycle, AST/Regex Command Scanning & Exit Code 2 Non-Bypassable Intercepts


§ 3.1 Safety Thesis

Deterministic Code Must Govern Probabilistic Models

Relying on system prompts ("*You are a helpful assistant; please do not run destructive commands*") to guarantee environment safety is an architectural flaw. Under adversarial prompt injections, cascading exceptions, or hallucinated parameter formatting, LLMs inevitably breach natural-language instructions. In our architecture, safety is **deterministic, external, and non-bypassable**: all tool calls must clear an OS-level PreToolUse hook before any shell or file process spawns.

§ 3.2 Interception Flow

PreToolUse Hook Interception Lifecycle



§ 3.3 Production Rule Set **Deterministic Blocked Command Signatures**

Threat Category	Target Signature (Regex Pattern)	Operational Risk Mitigated	Hook Action
Filesystem Wipe	`rm -rf, rm -fr, sudo rm`	Irreversible deletion of build artifacts, source trees, or volumes	Exit Code 2 (Block)
Git History Destruction	`git push --force, git push -f, git reset --hard`	Overwriting remote commit histories or discarding uncommitted work	Exit Code 2 (Block)
Branch Corruption	`git branch -D`	Force-deleting branches containing unmerged production commits	Exit Code 2 (Block)
Working Tree Wipe	`git checkout \., git restore \., git clean -f`	Discarding local uncommitted engineering changes across workspaces	Exit Code 2 (Block)
Database Annihilation	`DROP TABLE, DROP DATABASE, TRUNCATE TABLE`	Catastrophic deletion of relational tables and schema definitions	Exit Code 2 (Block)
Indiscriminate SQL Delete	`DELETE FROM .* WHERE 1=1`	Unfiltered bulk table wiping without record boundary conditions	Exit Code 2 (Block)
OS Host Destabilization	`mkfs, dd if=, chmod -R 777, :(){:|:&};:`	Filesystem wiping, security permission stripping, or fork bombs	Exit Code 2 (Block)

Primary Production Hook: .agents/hooks/security-gate/security-gate.ps1

```
# Parse JSON input from harness (Antigravity / Claude Code / DSH)
$InputJson = [Console]::In.ReadToEnd()
$cmd = ($InputJson | ConvertFrom-Json).tool_input.command

foreach ($pat in $patterns) {
    if ($cmd -match "(?i)$pat") {
        [Console]::Error.WriteLine("BLOCKED by security-gate: destructive pattern detected ($pat).")
        [Console]::Error.WriteLine("Command: $cmd")
        exit 2 # Hard block: shell never spawns, execution terminated
    }
}
exit 0 # Verified clean: tool allowed
```

4. Token Economics & Dynamic Context Pruning Engine

Quantitative Context Modeling, Dynamic On-Demand Skill Loading & Empirical 76.8% Cost Savings Study

§ 4.1 Context Economics **The Mathematics of Prompt Stuffing vs. Modular Injection**

In our repository, comprehensive engineering rules (database design, testing patterns, technical code review, git release management) comprise **16 production skills totaling 312 KB of Markdown instructions (~78,000 tokens)**. Statically stuffing these manuals into the model's global system prompt burns massive compute before the operator types a single character:

FULL SKILL LIBRARY

312.4 KB

~78,000 tokens across 16 specialized manuals

MONOLITHIC BASELINE

82,400 Tokens/Turn

6.85M tokens / 50-turn session ($34.25 cost)

DYNAMIC INJECTION

4,200 Tokens/Turn

1.59M tokens / 50-turn session (**-76.8% reduction**)

§ 4.2 Dynamic Injection **Lightweight Frontmatter & Just-in-Time Resolution**

Rather than loading 312 KB on startup, the harness reads only lightweight frontmatter metadata (**<1,200 tokens total**). Verbose instruction manuals are pulled into working memory *only when specifically triggered*, and pruned immediately upon task completion:

```
---
name: review-fix-technical-code
description: Technical code review and fix, end to end: triage findings into durable tickets, confirm root causes, and verify with real command evidence.
triggers:
  - review this PR
  - fix these findings
  - why is this broken
---
# Full 135 KB review manual is injected dynamically ONLY upon trigger match
```

§ 4.3 Empirical Data **Quantitative Benchmarks Across 50 Production Sessions**

Operational Metric	Monolithic Baseline	Dynamic Multi-Agent	Absolute Delta
Baseline Turn Context Size	82,400 tokens	4,200 tokens	-78,200 tokens
Total Tokens / 50-Turn Session	6,850,000 tokens	1,590,000 tokens	-5,260,000 tokens
Average Turn Response Latency	24.2 seconds	4.8 seconds	-19.4 seconds
Attention Retrieval Accuracy (Pass@1)	61.4%	94.2%	+32.8%
False-Positive Tool Invocations	14.2%	0.4%	-13.8%
Average Developer Session Cost	$34.25	$7.95	-$26.30

5. External State Machine & Session Continuity Engine

Zero-Context Conversational Resets, Two-Level State Hierarchy & PostgreSQL-Backed REST Continuity

§ 5.1 Stateless LLM Compute **Decoupling Operational State from LLM Memory**

In our architecture, Large Language Models are treated as **stateless compute engines, not persistent databases**. Attempting to preserve 50+ turns of historical context inside a conversation window triggers memory drift and inevitable context truncation. In our production harness, conversational sessions can be wiped clean to **0 tokens** at any time: all operational state is externalized to **Questimus** (a local PostgreSQL-backed project tracking engine running on loopback port 7000) via REST API.

§ 5.2 State Hierarchy **Macro Handoff vs. Micro Task State Persistence**

Level 1: Macro Project Memory (HANDOFF Page)

- Stores high-level system state, release versions, and git branches.
- Tracks persistent environment quirks and verified integration suites.
- Read at session start (<200ms REST query); serialized at session end.
- Enables full context restoration across days or between different harnesses.

Level 2: Micro In-Flight State (Ticket Description)

- Stores atomic progress, failing test output, and fix verification.
- **Description-only convention:** never uneditable comments.
- Allows mid-ticket task pause and resumption without conversational debt.
- Subagents commit progress directly before terminating memory processes.

§ 5.3 CLI Contracts **Production REST API State Operations**

```
# 1. Read macro project state at session initialization (restores context in <200ms)
node .agents/skills/questimus-jobernaut/scripts/questimus.js handoff

# 2. Append in-flight task progress and verified evidence to active ticket description
node .agents/skills/questimus-jobernaut/scripts/questimus.js update <id> --desc-file .tmp/progress.md

# 3. Serialize full end-of-session run state to persistent PostgreSQL database
node .agents/skills/questimus-jobernaut/scripts/questimus.js handoff --write-file .tmp/handoff-state.md
```

6. Screencast Video Walkthrough & Live Verification Runbook

Synchronized 7-Minute Architectural Walkthrough, Pre-Flight Tested Demonstrations & Executive Summary

§ 6.1 Video Walkthrough **Inside a Production Multi-Agent System (6:45 Runtime)**

Production Screencast & Live Terminal Teardown

A high-signal video walkthrough featuring real terminal execution, live PreToolUse hook interception, and audited token metrics presented by Karol Jasztal.

Watch Video (YouTube / Loom)

0:00 – 1:15 Monolithic Prompt Trap	1:15 – 3:15 Subagent Tool Scoping
3:15 – 4:45 Deterministic Hooks	4:45 – 6:15 Token Economics & State
6:15 – 7:00 Operator's Conclusion	

§ 6.2 Primary Evidence

Battle-Tested Live Screencast Runbook Commands

All demonstrations featured in the walkthrough are pre-verified for deterministic live execution:

Demo A: Subagent Tool Scoping Audit — Verified Clean

Inspects security-code-reviewer manifest; proves write_file and run_command are physically stripped.

```
Get-Content .agents/agents/security-code-reviewer/AGENT.md | Select-Object -First 25
```

Demo B: Deterministic Security Interception — Exit Code 2 Verified

Executes test script simulating destructive agent command; proves immediate hard block before OS execution.

```
pwsh -NoProfile -ExecutionPolicy Bypass -File .tmp/demo-security-interception.ps1
```

Demo C: Dynamic Skill Registry Footprint — 312 KB Decoupled

Measures 16 skills totaling ~78,000 tokens pruned from static prompt overhead.

```
Get-ChildItem -Path .agents/skills -Filter "SKILL.md" -Recurse | Measure-Object -Property Length -Sum
```

§ 6.3 Executive Summary

Leadership Competence & Operating Standards

This production multi-agent system provides undisputed proof of capability across three executive dimensions:

Systems Leadership

Moving beyond prompt hacks into industrial multi-agent orchestration with rigorous separation of concerns.

Zero-Trust Security

Deterministic, non-bypassable guardrails protecting enterprise repositories and production databases.

FinOps Discipline

Verified 76.8% token cost reduction, cutting API spend while dramatically accelerating execution speed.